

Date: 1999-07-15  
No.: HM1167A/504

## TEST REPORT

Page 1 of 4

**APPLICANT:** (CODE : 018309)

Wavecon Electronics Ltd.  
Block B, 4/F, Wo Fung Industry Building, 20 Yip Wo Street, On Lok Tsuen, Fanling, N.T., Hong Kong.

**DATE OF SAMPLES RECEIVED:** 1999.07.02

**DATE OF TESTING:** 1999.07.09

**DESCRIPTION OF SAMPLE(S):**

A sample of product said to be:

Product: Radio Control Car and Transmitter  
Manufacturer: Wavecon Electronics Ltd.  
Model Number: 19822  
Brand Name: WAVECON  
Rating: 9.6Vd.c. Power Pack  
Origin: China

**INVESTIGATIONS REQUESTED:**

Measurement to the relevant clauses of F.C.C. Rules and Regulations Part 15 Subpart B - Unintentional Radiator.

**RESULT/ REMARK:** Please see attached sheet(s).

**CONCLUSION:**

From the measurement data obtained, the tested sample was considered to have COMPLIED after modification with the clause 15.109(a) of Federal Communications Commission Rules and Regulations Part 15 and ANSI C63.4-1992 Section 12.1.1.1-2.

**TEST EQUIPMENT AUDIT:** Please see Appendix A

\_\_\_\_\_  
Law Man Kit  
Testing Engineer

\_\_\_\_\_  
Kitty Choy  
Verify by

\_\_\_\_\_  
Patrick Wong  
for Managing Director

Conditions in issuance of Test Report

1. This Report is issued in confidence to the client and it will be strictly treated as such by the Hong Kong Standards and Testing Centre Ltd. It may not be reproduced either in its entirety or in part and it may not be used for advertising. The client to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Hong Kong Standards and Testing Centre Ltd. to his customer, supplier or other persons directly concerned. The Hong Kong Standards and Testing Centre Ltd. will not, without the consent of the client, enter into any discussion or correspondence with any third party concerning the contents of the Report. 2. The report refers only to the sample tested and does not apply to the bulk, unless the sampling has been carried out by the Hong Kong Standards and Testing Centre Ltd. and is stated as such in the Report. 3. In the event of the improper use of the report, the Hong Kong Standards and Testing Centre Ltd. reserves the rights to withdraw it, and to adopt any other remedies which may be appropriate. 4. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Hong Kong Standards and Testing Centre Ltd. 5. The Hong Kong Standards and Testing Centre Ltd. will not be liable for or accept responsibility for any loss or damage howsoever arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations. 6. Applicants wishing to use the Report in court proceedings or arbitration shall inform the Hong Kong Standards and Testing Centre Ltd. to that effect prior to submitting the sample for testing.

Date: 1999-07-15  
No.: HM1167A/504

## **TEST REPORT**

Page 2 of 4

### **TEST SUMMARY**

\*\*\*UNINTENTIONAL RADIATOR\*\*\*

(A) Measurement of Radiated Emissions ..... Satisfactory  
(B) Line Conducted Voltage Test. ..... Not applicable

### **TEST DATA**

Please refer to the attached result sheets.

Date: 1999-07-15  
No.: HM1167A/504

# TEST REPORT

Page 3 of 4

\*\*\*UNINTENTIONAL RADIATOR\*\*\*

\*\* RECEIVER SECTION \*\*

## (A) Measurement of Radiated Interference

TEST REFERENCE: FCC Rules Part 15 Subpart B section 15.109(a)

TEST CONDITION : Normal

TEST DATE : 1999.07.09

Freq. to which tuned MHz	Freq of the emission MHz	Polarization H-V	Meter reading (at 3m) dB(µV)	dB	Antenna factor dB(µV/m)	Field Strength (at 3m) µV/m	FCC limit @ µV/m	
49.860	49.9	H	19.6	+	15.0	34.6	53.7	100
	99.7	V	17.4	+	12.2	29.6	30.2	150
149.6		<	1.0	+	9.8	< 10.8	< 3.5	150
199.4	H		20.7	+	11.5	32.2	40.7	150
249.3	H		18.6	+	15.9	34.5	53.0	200
299.1		<	1.0	+	17.0	< 18.0	< 7.9	200
349.0		<	1.0	+	17.2	< 18.2	< 8.1	200
398.8		<	1.0	+	18.8	< 19.8	< 9.8	200
448.7		<	1.0	+	19.7	< 20.7	< 10.8	200
498.6		<	1.0	+	20.6	< 21.6	< 12.0	200
548.4		<	1.0	+	22.2	< 23.2	< 14.5	200
598.3		<	1.0	+	23.4	< 24.4	< 16.6	200
648.1		<	1.0	+	23.5	< 24.5	< 16.8	200
698.0		<	1.0	+	25.0	< 26.0	< 20.0	200
747.8		<	1.0	+	26.2	< 27.2	< 22.9	200
797.7		<	1.0	+	27.2	< 28.2	< 25.7	200
847.5		<	1.0	+	27.2	< 28.2	< 25.7	200
897.5		<	1.0	+	27.2	< 28.2	< 25.7	200
947.2		<	1.0	+	27.8	< 28.8	< 27.5	200
997.1		<	1.0	+	28.5	< 29.5	< 29.9	500

## =====SUMMARY=====

All data is within limits

Broad-band Antennas were used and both polarizations of emissions were measured

Polarizations at highest reading indicated as:

H -- Horizontal      V -- Vertical

## NOTES FOR THE RADIATION MEASUREMENT

(1) Test site facility:

Open field test site located at Taipo (Hong Kong) with a metal ground plane on filed with the FCC pursuant to section 2.948 of the FCC Rules.

(2) Distance between the ET and measuring antenna:

3 meters.

(3) Measuring instrumentation's:

CISPR Quasi-peak type field strength meter (25 MHz - 1000 MHz.). 6 dB bandwidth set at 120 KHz. Also, peak level of the fundamental emissions was measured in order to determine compliance with the 20dB peak to average limit specified in Section 15.35(b) of the FCC new Rules.

(4) Measuring antenna:

Broad band antenna for the frequency range 25-1000 MHz, connected with 10 meters coaxial cable. Cable loss of the coaxial cable. included in the Antenna Factor for measurement data. The antenna are capable of measuring both horizontal and vertical polarizations.

(5) Frequency range scanned:

The frequency range from 25 MHz to 1000 MHz had been searched. Readings of the highest emissions relating to the limit were reported as above.

(6) Arrangement of EUT:

During the test, the sample was operated at rated supply voltage and arranged for maximum emissions.

(7) Measuring Procedure:

In accordance with the relevant clauses of the FCC Rules Part 15 section 15.109(a) and ANSI C63.4:1992 section 12.1.1.1-2.

(8) Measuring Uncertainty:

The calculated uncertainty for measurement performed at 3M test distance are:-  
30MHz to 200MHz =  $\pm 3.7$ dB, 200MHz to 1000MHz =  $+ 3.0$ dB/- $2.7$ dB.

Remark: Purpose of this test is to provide the Applicant with the necessary test data of their device for the submission to FCC with application for Equipment Authorization under FCC's Equipment Authorization Program. This test itself is not an Approval Test.

\*\*\*\*\*End of Document\*\*\*\*\*