

FCC RF Exposure Requirements

General information:

FCCID: H7C-M10

Device category: Mobile per Part 2.1091

Environment: Controlled Exposure

Mobile devices that operate under Part 90 of this chapter are subject to routine environmental evaluation for RF exposure prior to equipment authorization or use if they operate at frequencies of 1.5 GHz or below and their effective radiated power (ERP) is 1.5 watts or more. However, compliance with the power density limits of 1.1310 is not required.

Antenna:

The manufacturer does not specify any antenna to be used with this device.

This device has provisions for operation in a vehicle, or a fixed location.

Configuration	Antenna p/n	Type	Max. Gain (dBi)
Vehicle	Any	omni	3

Operating configuration and exposure conditions:

The conducted output power is 30 watt. Typical use qualifies for a maximum duty cycle factor of 50%. The manufacturer also markets this device only for occupation use.

- Part 2.1091 states that devices are excluded from routine evaluation if the EIRP is less than 2.46Watt (or 1.5WERP).
- Vehicle Operation: The maximum antenna gain that can be used is 5dBi. A coaxial cable of the type RG 58 has a loss of 1dB for a length of 15 feet.

MPE Calculation:

The minimum separation distance is calculated as follows:

$$E(V/m) = \frac{\sqrt{30 \times P \times G}}{d}$$

$$\text{Power density: } P_d(mW/cm^2) = \frac{E^2}{3770}$$

The limit for occupation/controlled exposure environment below 300 MHz and above 30 MHz is 1.0 mW/cm².

Channel Frequency: 138-174 MHz
The conducted power output is 30 watt.
The coax loss was taken as 1 dB.
Antenna gain was taken as 5 dBi
50% talk time in 6 minutes

Exposure time in minutes $U := 6$ (use 6 for controlled and 30 for uncontrolled)

$$E := 3$$

$$W_{\text{exp}} := W \cdot D \cdot \left(\frac{E}{U} \right)$$

$$PC := \frac{E}{U} \quad \text{percent on time}$$

$$PC = 0.5$$

Time compensated power output

Wexp = 15 Watts

$$W1exp := Wexp \cdot 1000 \quad \text{mWatts}$$

$$W_{1\text{exp}} = 1.5 \times 10^4$$

Antenna gain	Coax Loss	For all VHF frequencies
$\text{dBd} := 3.85$	$\text{CL} := 1 \text{ dB}$	
$G := \text{dBd} + 2.15 - \text{CL}$	Net gain in dBi	$S := 1 \frac{\text{mW}}{\text{cm}^2}$ from
$G = 5$		OET 6

Gain Numeric

$$Gn \equiv 10^{\frac{G}{10}}$$

$$Gn = 3.162$$

$$R := \sqrt{\frac{(W1 \exp \cdot G_n)}{(4 \cdot \pi \cdot S)}}$$

R = 61.439 distance in centimeters
 required for compliance

$$\text{Rinches} := \frac{\text{R}}{2.54}$$

Rinches = 24.188

Conclusion:

The device complies with the MPE requirements by providing a safe separation distance of 61.5 cm between the antenna, including any radiating structure, and any persons when normally operated .

Proposed RF exposure safety information to include in User's Manual:

“FCC RF Exposure Requirements:


CAUTION:

The antenna(s) used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. This device is approved with emissions having a source-based time-averaging duty factor not exceeding 50%.

Vehicle – Antenna Installation:

- Antennas used for this transmitter must not exceed an antenna gain of 5 dBi with a minimum cable loss of 1dB.
- For rear deck trunk and roof top installations, the antenna must be located at least 61.5 cm away from rear-seat passengers and bystanders in order to comply with the FCC RF exposure requirements.

The following label will be mounted in conspicuous view on the radio.



Failure to observe these restrictions will result in exceeding the FCC RF exposure limits.