



Askey Computer Corporation
10F, No. 119, Jiankang Rd., Zhonghe Dist.,
New Taipei City, 23585, Taiwan

Date: 2025-07-04

FCC ID: H8NPCTE020

MIF for HAC RF Interference Evaluation

To Whom It May Concern,

We, [Askey Computer Corp](#) hereby declare that this device will be certified under ANSI C63.19-2019 version per Part 20.19 for Hearing Aid Compatibility Requirement.

The interference to comply with C63.19-2019 Clause 4 Evaluation of WDRF interference potential. The MIF values below for the worst-case operation mode for all air interfaces are pre-determined values provided by SPEAG.

UID	Reversion	Communication System Name	MIF (dB)
10061	CAB	IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)	-2.02
10077	CAB	IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps)	0.12
10591	AAD	IEEE 802.11n (HT Mixed, 20MHz, MCS0, 90pc duty cycle)	-5.59
10599	AAD	IEEE 802.11n (HT Mixed, 40MHz, MCS0, 90pc duty cycle)	-5.59
10607	AAD	IEEE 802.11ac WiFi (20MHz, MCS0, 90pc duty cycle)	-5.6
10616	AAB	IEEE 802.11ac WiFi (40MHz, MCS0, 90pc duty cycle)	-5.57
10626	AAD	IEEE 802.11ac WiFi (80MHz, MCS0, 90pc duty cycle)	-5.64
10636	AAE	IEEE 802.11ac WiFi (160MHz, MCS0, 90pc duty cycle)	-5.56
10671	AAC	IEEE 802.11ax (20MHz, MCS0, 90pc duty cycle)	-5.58
10695	AAC	IEEE 802.11ax (40MHz, MCS0, 90pc duty cycle)	-6.01
10719	AAC	IEEE 802.11ax (80MHz, MCS0, 90pc duty cycle)	-6.04
10743	AAC	IEEE 802.11ax (160MHz, MCS0, 90pc duty cycle)	-5.6
10069	CAE	IEEE 802.11ah WiFi 5 GHz (OFDM, 54 Mbps)	-3.15
11026	AAB	IEEE 802.11be (320MHz, MCS0, 99pc duty cycle)	-28.73
10021	DAC	GSM-FDD (TDMA, GMSK)	3.63
10023	DAC	GPRS-FDD (TDMA, GMSK, TN 0)	3.8
10025	DAC	EDGE-FDD (TDMA, 8PSK, TN 0)	3.75
10460	AAB	UMTS-FDD (WCDMA, AMR)	-25.43
10225	CAC	UMTS-FDD (HSPA+)	-20.39
10081	CAB	CDMA2000 (1xEV-RTT, RC3)	-19.71
10295	AAB	CDMA2000, RC1, SO3, 1/8th Rate 25 #	3.26
10403	AAB	CDMA2000 (1xEV-DO, Rev 0)	-17.67
10170	CAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	-9.76
10169	CAF	LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	-15.63
10647	AAG	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK, UL Subframe=2,7)	1.5
10172	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)	-1.62
10173	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)	-1.44
10174	CAH	LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)	-1.54
10930	AAA	5G NR (DFT-s-OFDM, 1 RB, 15 MHz, QPSK, 15 kHz) FDD	-15.06
10769	AAC	5G NR (CP-OFDM, 1 RB, 15 MHz, QPSK, 15 kHz) TDD	-12.08

We confirm that the SPEAG simulation provided represents all the air interface modes applicable for this handset.

Sincerely yours,

Jack Po, Director
Askey Computer Corp
Tel: 886 2 2228-7588 #18734
Fax: 886 2 3234-9340
E-mail: jackpo@askey.com