

FCC TEST REPORT

REPORT NO.: RF940503L15

MODEL NO.: WLC3110

(refer to page 6 for other Models)

RECEIVED: May 03, 2005

TESTED: May 06 ~ May 17, 2005

ISSUED: May 19, 2005

APPLICANT: ASKEY COMPUTER CORP.

ADDRESS: 10F, No.119, Chien Kang Rd., Chung-Ho, Taipei,
Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Tsuen, Lin Kou
Hsiang 244, Taipei Hsien, Taiwan, R.O.C.

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan,
R.O.C.

This test report consists of 88 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CNLA, A2LA or any government agencies. The test results in the report only apply to the tested sample.



0528
ILAC MRA



No. 2177-01

Table of Contents

1.	CERTIFICATION.....	4
2.	SUMMARY OF TEST RESULTS	5
2.1	MEASUREMENT UNCERTAINTY	5
3.	GENERAL INFORMATION.....	6
3.1	GENERAL DESCRIPTION OF EUT.....	6
3.2	DESCRIPTION OF TEST MODES.....	7
3.2.1	CONFIGURATION OF SYSTEM UNDER TEST	7
3.2.2	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:.....	8
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	10
3.4	DESCRIPTION OF SUPPORT UNITS	10
4.	TEST TYPES AND RESULTS	11
4.1	CONDUCTED EMISSION MEASUREMENT	11
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT.....	11
4.1.2	TEST INSTRUMENTS.....	11
4.1.3	TEST PROCEDURES	12
4.1.4	DEVIATION FROM TEST STANDARD	12
4.1.5	TEST SETUP	13
4.1.6	EUT OPERATING CONDITIONS	13
4.1.7	TEST RESULTS	14
4.2	RADIATED EMISSION MEASUREMENT	26
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT.....	26
4.2.2	TEST INSTRUMENTS.....	27
4.2.3	TEST PROCEDURES	28
4.2.4	DEVIATION FROM TEST STANDARD	28
4.2.5	TEST SETUP	29
4.2.6	EUT OPERATING CONDITIONS	29
4.2.7	TEST RESULTS	30
4.3	6dB BANDWIDTH MEASUREMENT	45
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	45
4.3.2	TEST INSTRUMENTS.....	45
4.3.3	TEST PROCEDURE.....	46
4.3.4	DEVIATION FROM TEST STANDARD	46
4.3.5	TEST SETUP	46



4.3.6	EUT OPERATING CONDITIONS	46
4.3.7	TEST RESULTS	47
4.4	MAXIMUM PEAK OUTPUT POWER	55
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	55
4.4.2	INSTRUMENTS.....	55
4.4.3	TEST PROCEDURES	56
4.4.4	DEVIATION FROM TEST STANDARD	56
4.4.5	TEST SETUP	56
4.4.6	EUT OPERATING CONDITIONS	56
4.4.7	TEST RESULTS	57
4.5	POWER SPECTRAL DENSITY MEASUREMENT.....	59
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	59
4.5.2	TEST INSTRUMENTS.....	59
4.5.3	TEST PROCEDURE.....	60
4.5.4	DEVIATION FROM TEST STANDARD	60
4.5.5	TEST SETUP	60
4.5.6	EUT OPERATING CONDITION	60
4.5.7	TEST RESULTS	61
4.6	BAND EDGES MEASUREMENT	69
4.6.1	LIMITS OF BAND EDGES MEASUREMENT	69
4.6.2	TEST INSTRUMENTS.....	69
4.6.3	TEST PROCEDURE.....	69
4.6.4	DEVIATION FROM TEST STANDARD	69
4.6.5	EUT OPERATING CONDITION	69
4.6.6	TEST RESULTS	70
4.6.7	TEST RESULTS	70
4.7	ANTENNA REQUIREMENT	83
4.7.1	STANDARD APPLICABLE	83
4.7.2	ANTENNA CONNECTED CONSTRUCTION	83
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	84
6.	INFORMATION ON THE TESTING LABORATORIES	88

1. CERTIFICATION

PRODUCT: Laptop Adapter
BRAND NAME: Askey
MODEL NO.: WLC3110
(Refer to page 6 for other model)
TEST SAMPLE: ENGINEERING SAMPLE
TESTED: May 06 ~ May 17, 2005
APPLICANT: Askey COMPUTER CORP.
STANDARDS: FCC Part 15, Subpart C (Section 15.247),
ANSI C63.4-2003

The above equipment (Model: WLC3110, WLC3111) have been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Wendy Liao , **DATE:** May 19, 2005
(Wendy Liao)

TECHNICAL
ACCEPTANCE : Gary Chang , **DATE:** May 19, 2005
Responsible for RF (Gary Chang)

APPROVED BY : Cody Chang , **DATE:** May 19, 2005
(Cody Chang, Deputy Manager)

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
Standard Section	Test Type and Limit	Result	Remark
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -14.68dB at 0.166MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -2.25dB at 4924.00MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

Measurement	Frequency	Uncertainty
Conducted emissions	9kHz~30MHz	2.44 dB
Radiated emissions	30MHz ~ 200MHz	3.73 dB
	200MHz ~ 1000MHz	3.74 dB
	1GHz ~ 18GHz	2.20 dB
	18GHz ~ 40GHz	1.88 dB

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Laptop Adapter
MODEL NO.	WLC3110
POWER SUPPLY	3.3Vdc from host equipment
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
RADIO TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps (Turbo mode: up to 125Mbps *see Note 3)
FREQUENCY RANGE	2412MHz ~ 2462MHz
NUMBER OF CHANNEL	Normal:11; Turbo :1
OUTPUT POWER	25.293mW
ANTENNA TYPE	Printed antenna with 2dBi gain
DATA CABLE	NA
I/O PORTS	NA
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT complies with IEEE 802.11g standards and backwards compatible with IEEE 802.11b products.
2. The EUT operates in the 2.4GHz frequency spectrum with throughput of up to 54Mbps.
3. This EUT is capable of providing data rates of up to 125Mbps in Turbo Mode depending upon reception quality.
4. The models as below are identical to each other except for their model designation, brand name and the chip version due to marketing requirement. This EUT used two kind of version chip. The chip model: BCM4318KF13G included the 11g turbo function and the chip model: 13CM4318KF13G didn't include the 11g turbo function. The difference is the software version which controlled the turbo function to be on or off.

Model Name	Brand	Description
WLC3110	Askey	With turbo mode
WLC3111	Askey	Without Turbo mode
F5D7010	Belkin	Same as WLC3110
F5D7011	Belkin	Same as WLC3111


5. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST



3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
A	x	x	x	Note 1	Tested by model no :WLC3110 (with turbo mode)
B	x	x	x	Note 1	Tested by model no :WLC3111 (without turbo mode)

Where PLC: Power Line Conducted Emission

RE<1G RE: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

APCM: Antenna Port Conducted Measurement

Note 1: Conducted RF Measurement is independent of the chip software.

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
B	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

Radiated Emission Test (Below 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11g	1 to 11	11	OFDM	BPSK	6
B	802.11g	1 to 11	11	OFDM	BPSK	6

Radiated Emission Test (Above 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
A	802.11g Turbo	6	6	OFDM	BPSK	12
B	802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
B	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6

Bandedge Measurement:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11b	1 to 11	1, 11	DSSS	CCK	11
A	802.11g	1 to 11	1, 11	OFDM	BPSK	6
A	802.11g Turbo	6	6	OFDM	BPSK	12

Antenna Port Conducted Measurement:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT configure mode	Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	CCK	11
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6
A	802.11g Turbo	6	6	OFDM	BPSK	12

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a Laptop Adapter. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4- 2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Notebook	DELL	D600	F8HBC1S	E2K24CLNS
2	Printer	EPSON	LQ-300+	DCGY054105	FCC DoC Approved
3	Modem	ACEEX	1414V/3	0401008270	IFAXDM1414
4	Wireless AP	BUFFALO	WBR2-G54	34059544811648	FDI-04600142-0

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.2 m shielded cable without core
3	1.2 m shielded cable without core
4	NA

NOTE: 1. All power cords of the above support units are non shielded (1.8m).
2. Item 4 act as a communication partner to transfer data.

4. TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESCS30	100288	Nov. 06, 2005
RF signal cable Woken	5D-FB	Cable-HyC02-01	Jan. 09, 2006
LISN ROHDE & SCHWARZ	ESH2-Z5	100100	Jan. 20, 2006
LISN ROHDE & SCHWARZ	ESH3-Z5	100311	Jan. 20, 2006
Software ADT	ADT_Cond_V3	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Shielded Room 3.
 3. The VCCI Site Registration No. is C-2047.




4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

- a. Connected the EUT to a notebook system placed on a testing table.
- b. The notebook system ran a test program (provided by manufacturer) to enable EUT under transmission/receiving condition continuously at specific channel frequency.
- c. The notebook system sent "H" messages to its screen.
- d. The notebook system sent "H" messages to modem.
- e. The notebook system sent "H" messages to printer, and the printer printed them on paper.
- f. Steps c ~ e were repeated.


4.1.7 TEST RESULTS

Conducted Worst-Case Data

EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3110	PHASE	Line 1
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	23deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Gary Chang	TEST MODE	Mode A

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.150	0.10	44.43	-	44.53	-	66.00	56.00	-21.47	-
2	0.173	0.10	48.16	27.54	48.26	27.64	64.79	54.79	-16.53	-27.15
3	0.271	0.10	35.23	-	35.33	-	61.08	51.08	-25.75	-
4	1.898	0.20	29.64	-	29.84	-	56.00	46.00	-26.16	-
5	10.313	0.31	34.00	-	34.31	-	60.00	50.00	-25.69	-
6	18.508	0.68	26.37	-	27.05	-	60.00	50.00	-32.95	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3110	PHASE	Line 2
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	23deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Gary Chang	TEST MODE	Mode A

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.177	0.10	47.49	28.73	47.59	28.83	64.61	54.61	-17.02	-25.78
2	0.306	0.10	35.62	-	35.72	-	60.07	50.07	-24.35	-
3	0.611	0.14	33.55	-	33.69	-	56.00	46.00	-22.31	-
4	2.020	0.20	30.31	-	30.51	-	56.00	46.00	-25.49	-
5	10.492	0.41	33.65	-	34.06	-	60.00	50.00	-25.94	-
6	18.184	0.69	25.33	-	26.02	-	60.00	50.00	-33.98	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3110	PHASE	Line 1
CHANNEL	Channel 6	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	23deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Gary Chang	TEST MODE	Mode A

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	43.27	-	43.37	-	64.98	54.98	-21.61	-
2	0.275	0.10	34.69	-	34.79	-	60.97	50.97	-26.18	-
3	0.634	0.14	32.24	-	32.38	-	56.00	46.00	-23.62	-
4	2.184	0.20	30.59	-	30.79	-	56.00	46.00	-25.21	-
5	3.781	0.20	26.98	-	27.18	-	56.00	46.00	-28.82	-
6	10.273	0.31	33.66	-	33.97	-	60.00	50.00	-26.03	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3110	PHASE	Line 2
CHANNEL	Channel 6	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	23deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Gary Chang	TEST MODE	Mode A

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.173	0.10	44.94	21.77	45.04	21.87	64.79	54.79	-19.75	-32.92
2	0.201	0.10	45.93	33.37	46.03	33.47	63.58	53.58	-17.55	-20.11
3	0.240	0.10	31.17	-	31.27	-	62.10	52.10	-30.83	-
4	0.630	0.14	23.77	-	23.91	-	56.00	46.00	-32.09	-
5	2.105	0.20	30.80	-	31.00	-	56.00	46.00	-25.00	-
6	9.840	0.39	33.42	-	33.81	-	60.00	50.00	-26.19	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3110	PHASE	Line 1
CHANNEL	Channel 11	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	23deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Gary Chang	TEST MODE	Mode A

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.166	0.10	43.10	-	43.20	-	65.18	55.18	-21.98	-
2	0.189	0.10	44.36	24.55	44.46	24.65	64.08	54.08	-19.62	-29.43
3	0.259	0.10	31.65	-	31.75	-	61.45	51.45	-29.70	-
4	2.051	0.20	29.76	-	29.96	-	56.00	46.00	-26.04	-
5	10.465	0.31	33.37	-	33.68	-	60.00	50.00	-26.32	-
6	16.566	0.53	26.07	-	26.60	-	60.00	50.00	-33.40	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3110	PHASE	Line 2
CHANNEL	Channel 11	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	23deg. C, 65%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Gary Chang	TEST MODE	Mode A

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.166	0.10	44.33	-	44.43	-	65.18	55.18	-20.75	-
2	0.181	0.10	46.86	27.68	46.96	27.78	64.43	54.43	-17.47	-26.65
3	0.259	0.10	31.29	-	31.39	-	61.45	51.45	-30.06	-
4	0.634	0.14	33.07	-	33.21	-	56.00	46.00	-22.79	-
5	2.070	0.20	29.19	-	29.39	-	56.00	46.00	-26.61	-
6	9.992	0.40	33.69	-	34.09	-	60.00	50.00	-25.91	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC311	PHASE	Line 1
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	22deg. C, 63%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Brad Wu	TEST MODE	Mode B

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.154	0.10	48.91	32.38	49.01	32.48	65.79	55.79	-16.78	-23.31
2	0.224	0.10	31.97	-	32.07	-	62.66	52.66	-30.59	-
3	1.945	0.20	27.62	-	27.82	-	56.00	46.00	-28.18	-
4	4.168	0.20	23.67	-	23.87	-	56.00	46.00	-32.13	-
5	9.102	0.29	32.63	-	32.92	-	60.00	50.00	-27.08	-
6	10.195	0.30	35.01	-	35.31	-	60.00	50.00	-24.69	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC311	PHASE	Line 2
CHANNEL	Channel 1	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	22deg. C, 63%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Brad Wu	TEST MODE	Mode B

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.158	0.10	44.31	-	44.41	-	65.58	55.58	-21.17	-
2	0.185	0.10	39.18	-	39.28	-	64.25	54.25	-24.97	-
3	0.752	0.16	21.52	-	21.68	-	56.00	46.00	-34.32	-
4	2.184	0.20	27.63	-	27.83	-	56.00	46.00	-28.17	-
5	9.070	0.37	32.95	-	33.32	-	60.00	50.00	-26.68	-
6	10.539	0.41	34.82	-	35.23	-	60.00	50.00	-24.77	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC311	PHASE	Line 1
CHANNEL	Channel 6	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	22deg. C, 63%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Brad Wu	TEST MODE	Mode B

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.170	0.10	40.28	-	40.38	-	64.98	54.98	-24.60	-
2	0.197	0.10	39.36	-	39.46	-	63.74	53.74	-24.28	-
3	0.353	0.10	33.23	-	33.33	-	58.89	48.89	-25.56	-
4	2.133	0.20	29.27	-	29.47	-	56.00	46.00	-26.53	-
5	4.320	0.21	23.17	-	23.38	-	56.00	46.00	-32.62	-
6	10.797	0.32	34.95	-	35.27	-	60.00	50.00	-24.73	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC311	PHASE	Line 2
CHANNEL	Channel 6	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	22deg. C, 63%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Brad Wu	TEST MODE	Mode B

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.166	0.10	50.40	28.26	50.50	28.36	65.18	55.18	-14.68	-26.82
2	0.177	0.10	39.80	-	39.90	-	64.61	54.61	-24.71	-
3	0.709	0.15	26.82	-	26.97	-	56.00	46.00	-29.03	-
4	2.297	0.20	27.36	-	27.56	-	56.00	46.00	-28.44	-
5	4.086	0.20	22.80	-	23.00	-	56.00	46.00	-33.00	-
6	10.422	0.41	35.04	-	35.45	-	60.00	50.00	-24.55	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3111	PHASE	Line 1
CHANNEL	Channel 11	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	22deg. C, 63%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Brad Wu	TEST MODE	Mode B

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.185	0.10	38.03	-	38.13	-	64.25	54.25	-26.12	-
2	0.228	0.10	34.14	-	34.24	-	62.52	52.52	-28.28	-
3	0.705	0.15	26.34	-	26.49	-	56.00	46.00	-29.51	-
4	1.996	0.20	28.59	-	28.79	-	56.00	46.00	-27.21	-
5	4.078	0.20	23.57	-	23.77	-	56.00	46.00	-32.23	-
6	10.359	0.31	33.31	-	33.62	-	60.00	50.00	-26.38	-


- REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3111	PHASE	Line 2
CHANNEL	Channel 11	6dB BANDWIDTH	9 kHz
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	22deg. C, 63%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Brad Wu	TEST MODE	Mode B

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.154	0.10	48.49	26.25	48.59	26.35	65.79	55.79	-17.20	-29.44
2	0.185	0.10	37.55	-	37.65	-	64.25	54.25	-26.60	-
3	0.701	0.15	27.40	-	27.55	-	56.00	46.00	-28.45	-
4	2.258	0.20	29.84	-	30.04	-	56.00	46.00	-25.96	-
5	3.848	0.20	23.52	-	23.72	-	56.00	46.00	-32.28	-
6	9.773	0.39	34.49	-	34.88	-	60.00	50.00	-25.12	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver ROHDE & SCHWARZ	ESI7	100033	Jun. 08, 2005
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100040	Jun. 03, 2005
BILOG Antenna SCHWARZBECK	VULB9168	9168-160	Jun. 01, 2005
HORN Antenna SCHWARZBECK	9120D	9120D-408	Jan. 17, 2006
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170243	Jan. 23, 2006
Preamplifier Agilent	8447D	2944A10633	Nov. 09, 2005
Preamplifier Agilent	8449B	3008A01964	Nov. 06, 2005
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	218183/4	Jan. 26, 2006
RF signal cable HUBER+SUHNNER	SUCOFLEX 104	218195/4	Jan. 26, 2006
Software ADT.	ADT_Radiated_V5.14	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA
Antenna Tower Controller inn-co GmbH	CO2000	017303	NA
Turn Table ADT.	TT100.	TT93021703	NA
Turn Table Controller ADT.	SC100.	SC93021703	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 2.

3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.

4. The VCCI Site Registration No. is R-237.

5. The IC Site Registration No. is IC4924-3.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 1KHz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

Below 1GHz Worst-Case Data

EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3110	FREQUENCY RANGE	Below 1000MHz
CHANNEL	Channel 11	DETECTOR FUNCTION	Quasi-Peak
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	23deg. C, 69%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen	TEST MODE	Mode A

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	117.47	30.38 QP	43.50	-13.12	1.50 H	223	17.27	13.11
2	168.02	33.91 QP	43.50	-9.59	1.50 H	244	19.43	14.48
3	199.12	27.62 QP	43.50	-15.88	2.00 H	256	15.69	11.93
4	333.25	31.21 QP	46.00	-14.79	1.00 H	301	15.43	15.78
5	465.43	29.95 QP	46.00	-16.05	2.50 H	181	11.11	18.84
6	601.50	28.26 QP	46.00	-17.74	2.00 H	97	6.55	21.71

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	43.61	31.82 QP	40.00	-8.18	1.00 V	73	16.25	15.57
2	121.36	30.98 QP	43.50	-12.52	1.00 V	331	17.52	13.46
3	160.24	32.08 QP	43.50	-11.42	1.00 V	190	16.86	15.21
4	333.25	32.53 QP	46.00	-13.47	2.00 V	172	16.75	15.78
5	465.43	29.06 QP	46.00	-16.94	1.00 V	184	10.22	18.84
6	607.33	31.48 QP	46.00	-14.52	1.50 V	133	9.70	21.78

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3111	FREQUENCY RANGE	Below 1000MHz
CHANNEL	Channel 11	DETECTOR FUNCTION	Quasi-Peak
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	22deg. C, 70%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen	TEST MODE	Mode B

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	133.03	35.59 QP	43.50	-7.91	1.50 H	19	21.32	14.27
2	166.07	33.81 QP	43.50	-9.69	1.50 H	31	19.14	14.67
3	199.12	37.59 QP	43.50	-5.91	1.50 H	37	25.66	11.93
4	232.16	37.64 QP	46.00	-8.36	1.50 H	49	24.60	13.03
5	465.43	37.35 QP	46.00	-8.65	1.50 H	262	18.51	18.84
6	599.56	37.94 QP	46.00	-8.06	1.00 H	22	16.26	21.68

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	63.05	26.23 QP	40.00	-13.77	1.00 V	154	12.55	13.68
2	111.64	35.50 QP	43.50	-8.00	1.00 V	217	22.99	12.50
3	173.85	35.57 QP	43.50	-7.93	1.00 V	313	21.63	13.94
4	210.78	30.57 QP	43.50	-12.93	2.00 V	202	18.47	12.09
5	331.30	34.88 QP	46.00	-11.12	1.50 V	316	19.14	15.74
6	465.43	35.99 QP	46.00	-10.01	1.00 V	283	17.15	18.84

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.

802.11b DSSS modulation

EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3110	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 1	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	CCK	ENVIRONMENTAL CONDITIONS	23deg. C, 69%RH, 991hPa
TRANSFER RATE	11Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen	TEST MODE	Mode A

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	43.58 PK	74.00	-30.42	1.11 H	25	14.83	28.75
2	2390.00	51.57 PK	74.00	-22.43	1.00 H	67	20.25	31.32
2	2390.00	44.29 AV	54.00	-9.71	1.00 H	67	12.97	31.32
3	*2412.00	108.77 PK			1.00 H	67	77.36	31.41
3	*2412.00	101.49 AV			1.00 H	67	70.08	31.41
4	3216.00	53.25 PK	74.00	-20.75	1.00 H	20	20.13	33.12
4	3216.00	48.12 AV	54.00	-5.88	1.00 H	20	15.00	33.12
5	4824.00	53.71 PK	74.00	-20.29	1.05 H	0	16.90	36.81
5	4824.00	49.71 AV	54.00	-4.29	1.05 H	0	12.90	36.81

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	41.15 PK	74.00	-32.85	1.57 V	32	12.40	28.75
2	2390.00	40.46 PK	74.00	-33.54	1.70 V	10	9.14	31.32
2	2390.00	33.50 AV	54.00	-20.50	1.70 V	10	2.18	31.32
3	*2412.00	98.66 PK			1.70 V	10	67.25	31.41
3	*2412.00	91.55 AV			1.70 V	10	60.14	31.41
4	3216.00	51.25 PK	74.00	-22.75	1.75 V	324	18.13	33.12
4	3216.00	46.88 AV	54.00	-7.12	1.75 V	324	13.76	33.12
5	4824.00	53.12 PK	74.00	-20.88	1.15 V	254	16.31	36.81
5	4824.00	49.41 AV	54.00	-4.59	1.15 V	254	12.60	36.81

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “ : Fundamental frequency

EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3110	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 6	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	CCK	ENVIRONMENTAL CONDITIONS	23deg. C, 69%RH, 991hPa
TRANSFER RATE	11Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen	TEST MODE	Mode A

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	43.98 PK	74.00	-30.02	1.10 H	20	15.18	28.80
2	*2437.00	108.47 PK			1.00 H	71	76.95	31.52
2	*2437.00	100.87 AV			1.00 H	71	69.35	31.52
3	3248.00	53.11 PK	74.00	-20.89	1.00 H	25	19.96	33.15
3	3248.00	48.88 AV	54.00	-5.12	1.00 H	25	15.73	33.15
4	4874.00	53.14 PK	74.00	-20.86	1.04 H	32	16.19	36.95
4	4874.00	49.04 AV	54.00	-4.96	1.04 H	32	12.09	36.95

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	41.25 PK	74.00	-32.75	1.59 V	35	12.45	28.80
2	*2437.00	98.87 PK			1.75 V	20	67.35	31.52
2	*2437.00	91.68 AV			1.75 V	20	60.16	31.52
3	3248.00	52.25 PK	74.00	-21.75	1.70 V	256	19.10	33.15
3	3248.00	48.41 AV	54.00	-5.59	1.70 V	256	15.26	33.15
4	4874.00	52.47 PK	74.00	-21.53	1.19 V	300	15.52	36.95
4	4874.00	48.75 AV	54.00	-5.25	1.19 V	300	11.80	36.95

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * “ : Fundamental frequency

EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3110	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 11	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	CCK	ENVIRONMENTAL CONDITIONS	23deg. C, 69%RH, 991hPa
TRANSFER RATE	11Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen	TEST MODE	Mode A

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	43.51 PK	74.00	-30.49	1.14 H	20	14.67	28.84
2	*2462.00	108.74 PK			1.29 H	95	77.11	31.63
2	*2462.00	101.23 AV			1.29 H	95	69.60	31.63
3	2483.50	51.54 PK	74.00	-22.46	1.29 H	95	19.82	31.72
3	2483.50	44.03 AV	54.00	-9.97	1.29 H	95	12.31	31.72
4	3282.00	54.15 PK	74.00	-19.85	1.01 H	35	20.97	33.18
4	3282.00	49.15 AV	54.00	-4.85	1.01 H	35	15.97	33.18
5	4924.00	53.78 PK	74.00	-20.22	1.00 H	17	16.68	37.10
5	4924.00	51.75 AV	54.00	-2.25	1.00 H	17	14.65	37.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	41.06 PK	74.00	-32.94	1.52 V	6	12.22	28.84
2	*2462.00	99.10 PK			1.22 V	286	67.47	31.63
2	*2462.00	92.21 AV			1.22 V	286	60.58	31.63
3	2483.50	40.90 PK	74.00	-33.10	1.22 V	286	9.18	31.72
3	2483.50	34.01 AV	54.00	-19.99	1.22 V	286	2.29	31.72
4	3282.00	51.25 PK	74.00	-22.75	1.65 V	278	18.07	33.18
4	3282.00	46.98 AV	54.00	-7.02	1.65 V	278	13.80	33.18
5	4924.00	54.76 PK	74.00	-19.24	1.13 V	215	17.65	37.10
5	4924.00	51.25 AV	54.00	-2.75	1.13 V	215	14.15	37.10

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3111	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 1	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	CCK	ENVIRONMENTAL CONDITIONS	22deg. C, 70%RH, 991hPa
TRANSFER RATE	11Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen	TEST MODE	Mode B

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	43.83 PK	74.00	-30.17	1.00 H	155	15.08	28.75
2	2390.00	47.97 PK	74.00	-26.03	1.32 H	75	16.65	31.32
2	2390.00	40.74 AV	54.00	-13.26	1.32 H	75	9.42	31.32
3	*2412.00	107.74 PK			1.32 H	75	76.33	31.41
3	*2412.00	100.51 AV			1.32 H	75	69.10	31.41
4	3216.00	45.82 PK	74.00	-28.18	1.31 H	340	12.70	33.12
5	4824.00	54.06 PK	74.00	-19.94	1.00 H	50	17.25	36.81
5	4824.00	47.60 AV	54.00	-6.40	1.00 H	50	10.79	36.81

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	40.31 PK	74.00	-33.69	1.35 V	50	11.56	28.75
2	2390.00	39.87 PK	74.00	-34.13	1.29 V	45	8.55	31.32
3	*2412.00	99.68 PK			1.44 V	187	68.27	31.41
3	*2412.00	92.78 AV			1.44 V	187	61.37	31.41
4	3216.00	45.58 PK	74.00	-28.42	1.29 V	45	12.46	33.12
5	4824.00	52.09 PK	74.00	-21.91	1.18 V	32	15.28	36.81
5	4824.00	44.97 AV	54.00	-9.03	1.18 V	32	8.16	36.81

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3111	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 6	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	CCK	ENVIRONMENTAL CONDITIONS	22deg. C, 70%RH, 991hPa
TRANSFER RATE	11Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen	TEST MODE	Mode B

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	43.88 PK	74.00	-30.12	1.01 H	77	15.08	28.80
2	*2437.00	107.50 PK			1.00 H	29	75.98	31.52
2	*2437.00	100.17 AV			1.00 H	29	68.65	31.52
3	3248.00	47.20 PK	74.00	-26.80	1.10 H	23	14.05	33.15
4	4874.00	53.19 PK	74.00	-20.81	1.00 H	39	16.23	36.95
4	4874.00	46.69 AV	54.00	-7.31	1.00 H	39	9.73	36.95

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	40.78 PK	74.00	-33.22	1.41 V	48	11.98	28.80
2	*2437.00	99.90 PK			1.02 V	185	68.38	31.52
2	*2437.00	92.67 AV			1.02 V	185	61.15	31.52
3	3248.00	47.15 PK	74.00	-26.85	1.31 V	38	14.00	33.15
4	4874.00	53.07 PK	74.00	-20.93	1.05 V	40	16.11	36.95
4	4874.00	45.26 AV	54.00	-8.74	1.05 V	40	8.30	36.95

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3111	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 11	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	CCK	ENVIRONMENTAL CONDITIONS	22deg. C, 70%RH, 991hPa
TRANSFER RATE	11Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen	TEST MODE	Mode B

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	43.78 PK	74.00	-30.22	1.16 H	26	14.94	28.84
2	*2462.00	107.03 PK			1.00 H	81	75.40	31.63
2	*2462.00	100.03 AV			1.00 H	81	68.40	31.63
3	2483.50	49.03 PK	74.00	-24.97	1.00 H	81	17.31	31.72
3	2483.50	42.03 AV	54.00	-11.97	1.00 H	81	10.31	31.72
4	3282.00	47.88 PK	74.00	-26.12	1.02 H	41	14.70	33.18
5	4924.00	54.78 PK	74.00	-19.22	1.07 H	323	17.68	37.10
5	4924.00	51.49 AV	54.00	-2.51	1.07 H	323	14.39	37.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	40.54 PK	74.00	-33.46	1.37 V	44	11.70	28.84
2	*2462.00	99.12 PK			1.03 V	178	67.49	31.63
2	*2462.00	92.32 AV			1.03 V	178	60.69	31.63
3	2483.50	41.12 PK	74.00	-32.88	1.03 V	178	9.40	31.72
4	3282.00	47.70 PK	74.00	-26.30	1.35 V	32	14.52	33.18
5	4924.00	54.67 PK	74.00	-19.33	1.07 V	6	17.56	37.10
5	4924.00	51.38 AV	54.00	-2.62	1.07 V	6	14.27	37.10

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

802.11g OFDM modulation

EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3110	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 1	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	23deg. C, 69%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen	TEST MODE	Mode A

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	42.52 PK	74.00	-31.48	1.06 H	12	13.77	28.75
2	2390.00	59.74 PK	74.00	-14.26	1.00 H	65	28.42	31.32
2	2390.00	50.01 AV	54.00	-3.99	1.00 H	65	18.69	31.32
3	*2412.00	107.10 PK			1.00 H	61	75.69	31.41
3	*2412.00	97.37 AV			1.00 H	61	65.96	31.41
4	3216.00	51.46 PK	74.00	-22.54	1.00 H	65	18.34	33.12
4	3216.00	47.35 AV	54.00	-6.65	1.00 H	65	14.23	33.12
5	4824.00	52.12 PK	74.00	-21.88	1.02 H	25	15.31	36.81
5	4824.00	48.05 AV	54.00	-5.95	1.02 H	25	11.24	36.81

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	41.25 PK	74.00	-32.75	1.57 V	65	12.50	28.75
2	2390.00	49.64 PK	74.00	-24.36	1.25 V	325	18.32	31.32
2	2390.00	42.79 AV	54.00	-11.21	1.25 V	325	11.47	31.32
3	*2412.00	97.00 PK			1.25 V	325	65.59	31.41
3	*2412.00	90.15 AV			1.25 V	325	58.74	31.41
4	3216.00	50.88 PK	74.00	-23.12	1.48 V	32	17.76	33.12
4	3216.00	46.25 AV	54.00	-7.75	1.48 V	32	13.13	33.12
5	4824.00	51.05 PK	74.00	-22.95	1.65 V	35	14.24	36.81
5	4824.00	47.12 AV	54.00	-6.88	1.65 V	35	10.31	36.81

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3110	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 6	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	23deg. C, 69%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen	TEST MODE	Mode A

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	42.87 PK	74.00	-31.13	1.07 H	35	14.07	28.80
2	*2437.00	107.24 PK			1.00 H	25	75.72	31.52
2	*2437.00	97.55 AV			1.00 H	25	66.03	31.52
3	3248.00	51.24 PK	74.00	-22.76	1.02 H	58	18.09	33.15
3	3248.00	41.11 AV	54.00	-12.89	1.02 H	58	7.96	33.15
4	4874.00	52.54 PK	74.00	-21.46	1.05 H	24	15.59	36.95
4	4874.00	48.78 AV	54.00	-5.22	1.05 H	24	11.83	36.95

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	41.57 PK	74.00	-32.43	1.67 V	258	12.77	28.80
2	*2437.00	97.40 PK			1.54 V	325	65.88	31.52
2	*2437.00	90.25 AV			1.54 V	325	58.73	31.52
3	3248.00	50.15 PK	74.00	-23.85	1.68 V	324	17.00	33.15
3	3248.00	40.25 AV	54.00	-13.75	1.68 V	324	7.10	33.15
4	4874.00	51.22 PK	74.00	-22.78	1.74 V	65	14.27	36.95
4	4874.00	47.25 AV	54.00	-6.75	1.74 V	65	10.30	36.95

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3110	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 11	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	23deg. C, 69%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen	TEST MODE	Mode A

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	42.10 PK	74.00	-31.90	1.05 H	25	13.26	28.84
2	*2462.00	106.78 PK			1.00 H	47	75.15	31.63
2	*2462.00	97.66 AV			1.00 H	47	66.03	31.63
3	2483.50	59.37 PK	74.00	-14.63	1.00 H	47	27.65	31.72
3	2483.50	50.25 AV	54.00	-3.75	1.00 H	47	18.53	31.72
4	3282.00	50.05 PK	74.00	-23.95	1.01 H	10	16.87	33.18
4	3282.00	46.15 AV	54.00	-7.85	1.01 H	10	12.97	33.18
5	4924.00	51.87 PK	74.00	-22.13	1.05 H	33	14.77	37.10
5	4924.00	47.02 AV	54.00	-6.98	1.05 H	33	9.92	37.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	41.05 PK	74.00	-32.95	1.68 V	25	12.21	28.84
2	*2462.00	97.25 PK			1.55 V	35	65.62	31.63
2	*2462.00	90.11 AV			1.55 V	35	58.48	31.63
3	2483.50	50.25 PK	74.00	-23.75	1.55 V	35	18.53	31.72
3	2483.50	41.25 AV	54.00	-12.75	1.55 V	35	9.53	31.72
4	3282.00	49.15 PK	74.00	-24.85	1.58 V	25	15.97	33.18
5	4924.00	50.87 PK	74.00	-23.13	1.69 V	36	13.77	37.10
5	4924.00	46.11 AV	54.00	-7.89	1.69 V	36	9.01	37.10

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3111	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 1	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	22deg. C, 70%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen	TEST MODE	Mode B

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	43.25 PK	74.00	-30.75	1.05 H	13	14.50	28.75
2	2390.00	57.18 PK	74.00	-16.82	1.00 H	20	25.86	31.32
2	2390.00	47.50 AV	54.00	-6.50	1.00 H	20	16.18	31.32
3	*2412.00	105.55 PK			1.00 H	20	74.14	31.41
3	*2412.00	95.87 AV			1.00 H	20	64.46	31.41
4	3216.00	44.87 PK	74.00	-29.13	1.11 H	342	11.75	33.12
5	4824.00	50.59 PK	74.00	-23.41	1.07 H	20	13.78	36.81
5	4824.00	44.01 AV	54.00	-9.99	1.07 H	20	7.20	36.81

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1608.00	40.15 PK	74.00	-33.85	1.25 V	36	11.40	28.75
2	2390.00	51.82 PK	74.00	-22.18	1.40 V	159	20.50	31.32
2	2390.00	40.17 AV	54.00	-13.83	1.40 V	159	8.85	31.32
3	*2412.00	100.12 PK			1.40 V	159	68.71	31.41
3	*2412.00	88.47 AV			1.40 V	159	57.06	31.41
4	3216.00	44.35 PK	74.00	-29.65	1.30 V	48	11.23	33.12
5	4824.00	50.55 PK	74.00	-23.45	1.12 V	30	13.74	36.81
5	4824.00	43.99 AV	54.00	-10.01	1.12 V	30	7.18	36.81

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3111	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 6	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	22deg. C, 70%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen	TEST MODE	Mode B

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	42.87 PK	74.00	-31.13	1.08 H	27	14.07	28.80
2	*2437.00	106.27 PK			1.00 H	21	74.75	31.52
2	*2437.00	96.82 AV			1.00 H	21	65.30	31.52
3	3248.00	46.12 PK	74.00	-27.88	1.01 H	35	12.97	33.15
4	4874.00	51.63 PK	74.00	-22.37	1.00 H	39	14.67	36.95
4	4874.00	37.82 AV	54.00	-16.18	1.00 H	39	0.86	36.95

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	40.75 PK	74.00	-33.25	1.23 V	32	11.95	28.80
2	*2437.00	99.75 PK			1.48 V	343	68.23	31.52
2	*2437.00	90.15 AV			1.48 V	343	58.63	31.52
3	3248.00	45.58 PK	74.00	-28.42	1.35 V	55	12.43	33.15
4	4874.00	51.58 PK	74.00	-22.42	1.13 V	34	14.63	36.95
4	4874.00	37.76 AV	54.00	-16.24	1.13 V	34	0.81	36.95

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3111	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 11	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	22deg. C, 70%RH, 991hPa
TRANSFER RATE	6Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen	TEST MODE	Mode B

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	42.09 PK	74.00	-31.91	1.07 H	12	13.25	28.84
2	*2462.00	106.95 PK			1.00 H	9	75.32	31.63
2	*2462.00	96.11 AV			1.00 H	9	64.48	31.63
3	2483.50	58.83 PK	74.00	-15.17	1.00 H	9	27.11	31.72
3	2483.50	47.99 AV	54.00	-6.01	1.00 H	9	16.27	31.72
4	3282.00	47.39 PK	74.00	-26.61	1.11 H	32	14.21	33.18
5	4924.00	53.56 PK	74.00	-20.44	1.07 H	12	16.45	37.10
5	4924.00	38.37 AV	54.00	-15.63	1.07 H	12	1.26	37.10

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1641.00	40.15 PK	74.00	-33.85	1.28 V	41	11.31	28.84
2	*2462.00	97.53 PK			1.48 V	36	65.90	31.63
2	*2462.00	90.36 AV			1.48 V	36	58.73	31.63
3	2483.50	49.41 PK	74.00	-24.59	1.28 V	41	17.69	31.72
4	3282.00	46.87 PK	74.00	-27.13	1.35 V	30	13.69	33.18
5	4924.00	53.44 PK	74.00	-20.56	1.25 V	38	16.34	37.10
5	4924.00	38.21 AV	54.00	-15.79	1.25 V	38	1.11	37.10

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

802.11g Turbo OFDM modulation

EUT	Laptop Adapter	MEASUREMENT DETAIL	
MODEL	WLC3110	FREQUENCY RANGE	1 ~ 25GHz
CHANNEL	Channel 6	DETECTOR FUNCTION	Peak(PK) Average (AV)
MODULATION TYPE	BPSK	ENVIRONMENTAL CONDITIONS	23deg. C, 69%RH, 991hPa
TRANSFER RATE	12Mbps	INPUT POWER (SYSTEM)	120Vac, 60 Hz
TESTED BY	Morgan Chen	TEST MODE	Mode A

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	43.15 PK	74.00	-30.85	1.02 H	25	14.35	28.80
2	*2437.00	106.12 PK			1.01 H	35	74.60	31.52
2	*2437.00	96.42 AV			1.01 H	35	64.90	31.52
3	3248.00	51.36 PK	74.00	-22.64	1.02 H	39	18.21	33.15
4	4874.00	52.87 PK	74.00	-21.13	1.08 H	98	15.92	36.95
4	4874.00	48.95 AV	54.00	-5.05	1.08 H	98	12.00	36.95

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1624.00	42.11 PK	74.00	-31.89	1.65 V	265	13.31	28.80
2	*2437.00	97.47 PK			1.59 V	321	65.95	31.52
2	*2437.00	90.35 AV			1.59 V	321	58.83	31.52
3	3248.00	50.28 PK	74.00	-23.72	1.64 V	320	17.13	33.15
3	3248.00	41.05 AV	54.00	-12.95	1.64 V	320	7.90	33.15
4	4874.00	51.25 PK	74.00	-22.75	1.70 V	25	14.30	36.95
4	4874.00	47.34 AV	54.00	-6.66	1.70 V	25	10.39	36.95

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. “ * ” : Fundamental frequency

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
SPECTRUM ANALYZER	FSEK 30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.3.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100kHz RBW and 100kHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


4.3.7 TEST RESULTS

802.11b DSSS modulation


EUT	Laptop Adapter	MODEL	WLC3110
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH, 991hPa
TESTED BY	Brad Wu	TEST MODE	Mode A

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	10.60	0.5	PASS
6	2437	10.80	0.5	PASS
11	2462	10.68	0.5	PASS

CH1




CH6





CH11




802.11g OFDM modulation


EUT	Laptop Adapter	MODEL	WLC3110
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH, 991hPa
TESTED BY	Brad Wu	TEST MODE	Mode A

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
1	2412	16.40	0.5	PASS
6	2437	16.36	0.5	PASS
11	2462	16.40	0.5	PASS


CH1



CH6



CH11




802.11g Turbo OFDM modulation

EUT	Laptop Adapter	MODEL	WLC3110
MODULATION TYPE	BPSK	TRANSFER RATE	12Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH, 991hPa
TESTED BY	Brad Wu	TEST MODE	Mode A

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS/FAIL
6	2437	16.44	0.5	PASS

CH6



4.4 MAXIMUM PEAK OUTPUT POWER

4.4.1 LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT

The Maximum Peak Output Power Measurement is 30dBm.

4.4.2 INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005
AGILENT SIGNAL GENERATOR	E8257C	MY43320668	Dec. 06, 2005
DIGITAL RT OSCILLOSCOPE	TDS1012	C037299	Dec. 07, 2005
NARDA DETECTOR	4503A	FSCM99899	NA

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA..

4.4.3 TEST PROCEDURES

1. A detector was used on the output port of the EUT. An oscilloscope was used to read the response of the detector.
2. Replaced the EUT by the signal generator. The center frequency of the S.G was adjusted to the center frequency of the measured channel.
3. Adjusted the power to have the same reading on oscilloscope. Record the power level.

4.4.4 DEVIATION FROM TEST STANDARD

No deviation

4.4.5 TEST SETUP



4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6

4.4.7 TEST RESULTS

802.11b DSSS modulation

EUT	Laptop Adapter	MODEL	WLC3110
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH, 991hPa
TESTED BY	Brad Wu	TEST MODE	Mode A

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	25.235	14.02	30	PASS
6	2437	25.293	14.03	30	PASS
11	2462	25.235	14.02	30	PASS

802.11g OFDM modulation

EUT	Laptop Adapter	MODEL	WLC3110
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH, 991hPa
TESTED BY	Brad Wu	TEST MODE	Mode A

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
1	2412	22.387	13.50	30	PASS
6	2437	22.491	13.52	30	PASS
11	2462	22.439	13.51	30	PASS

802.11g Turbo OFDM modulation

EUT	Laptop Adapter	MODEL	WLC3110
MODULATION TYPE	BPSK	TRANSFER RATE	12Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH, 991hPa
TESTED BY	Brad Wu	TEST MODE	Mode A

CHANNEL	CHANNEL FREQUENCY (MHz)	PEAK POWER OUTPUT (mW)	PEAK POWER OUTPUT (dBm)	PEAK POWER LIMIT (dBm)	PASS/FAIL
6	2437	22.491	13.52	30	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


4.5.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3kHz RBW and 30kHz VBW, set sweep time = span/3kHz. The power spectral density was measured and recorded. The sweep time is allowed to be longer than span/3kHz for a full response of the mixer in the spectrum analyzer.

4.5.4 DEVIATION FROM TEST STANDARD

No deviation

4.5.5 TEST SETUP



4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6


4.5.7 TEST RESULTS

802.11b DSSS modulation


EUT	Laptop Adapter	MODEL	WLC3110
MODULATION TYPE	CCK	TRANSFER RATE	11Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH, 991hPa
TESTED BY	Brad Wu	TEST MODE	Mode A

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-11.55	8	PASS
6	2437	-11.27	8	PASS
11	2462	-11.32	8	PASS


CH1



CH6



CH11




802.11g OFDM modulation


EUT	Laptop Adapter	MODEL	WLC3110
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH, 991hPa
TESTED BY	Brad Wu	TEST MODE	Mode A

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
1	2412	-13.89	8	PASS
6	2437	-14.06	8	PASS
11	2462	-13.90	8	PASS

CH1



CH6



Ref 20.5 dBm *Att 30 dB *RBW 3 kHz Marker 1 [T1] -13.90 dBm
 *VBW 30 kHz *SWT 500 s 2.462912000 GHz

20 Offset 0.5 dB

1 PK
 VIEW

LVL


Center 2.462963 GHz 150 kHz/ Span 1.5 MHz

802.11g Turbo OFDM modulation

EUT	Laptop Adapter	MODEL	WLC3110
MODULATION TYPE	BPSK	TRANSFER RATE	12Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	ENVIRONMENTAL CONDITIONS	25deg. C, 68%RH, 991hPa
TESTED BY	Brad Wu	TEST MODE	Mode B

CHANNEL	CHANNEL FREQUENCY (MHz)	RF POWER LEVEL IN 3kHz BW (dBm)	MAXIMUM LIMIT (dBm)	PASS/FAIL
6	2437	-13.82	8	PASS

CH6



4.6 BAND EDGES MEASUREMENT

4.6.1 LIMITS OF BAND EDGES MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Calibrated Until
R&S SPECTRUM ANALYZER	FSEK30	100049	Aug. 12, 2005

NOTE: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 100 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

The spectrum plots (Peak RBW=VBW=100kHz ; Average RBW=1MHz, VBW=1KHz) are attached on the following pages.

4.6.4 DEVIATION FROM TEST STANDARD

No deviation

4.6.5 EUT OPERATING CONDITION

Same as Item 4.3.6



4.6.6 TEST RESULTS

The spectrum plots are attached on the following 18 images. D2 line indicates the highest level, and D1 line indicates the 20dB offset below D2. It shows compliance with the requirement in part 15.247(d).

4.6.7 TEST RESULTS

802.11b DSSS modulation (Mode A)

NOTE 1: The band edge emission plot on page 74 show 50.31dBc delta between carrier maximum power and local maximum emission in restrict band (2.3688GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 108.77dBuV/m (Peak), so the maximum field strength in restrict band is $108.77 - 50.31 = 58.46$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on page 74 show 61.18dBc delta between carrier maximum power and local maximum emission in restrict band (2.3894GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 101.49dBuV/m (Average), so the maximum field strength in restrict band is $101.49 - 61.18 = 40.31$ dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot on the page 75 show 51.14dBc delta between carrier maximum power and local maximum emission in restrict band (2.4850GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 108.74dBuV/m (Peak), so the maximum field strength in restrict band is $108.74 - 51.14 = 57.60$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on the page 76 show 59.31dBc delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 101.23dBuV/m (Average), so the maximum field strength in restrict band is $101.23 - 59.31 = 41.92$ dBuV/m which is under 54dBuV/m limit.

**802.11b DSSS modulation (Mode B)**

NOTE 1: The band edge emission plot on page 74 show 50.31dBc delta between carrier maximum power and local maximum emission in restrict band (2.3688GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 107.74dBuV/m (Peak), so the maximum field strength in restrict band is $107.74 - 50.31 = 57.43$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on page 74 show 61.18dBc delta between carrier maximum power and local maximum emission in restrict band (2.3894GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 100.51dBuV/m (Average), so the maximum field strength in restrict band is $100.51 - 61.18 = 39.33$ dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot on the page 75 show 51.14dBc delta between carrier maximum power and local maximum emission in restrict band (2.4850GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 107.03dBuV/m (Peak), so the maximum field strength in restrict band is $107.03 - 51.14 = 55.89$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on the page 76 show 59.31dBc delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 100.03dBuV/m (Average), so the maximum field strength in restrict band is $100.03 - 59.31 = 40.72$ dBuV/m which is under 54dBuV/m limit.

802.11g OFDM modulation (Mode A)

NOTE 1: The band edge emission plot on page 77 show 46.25dBc delta between carrier maximum power and local maximum emission in restrict band (2.3892GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 107.10dBuV/m (Peak), so the maximum field strength in restrict band is $107.10 - 46.25 = 60.85$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on page 77 show 53.58dBc delta between carrier maximum power and local maximum emission in restrict band (2.3898GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 97.37dBuV/m (Average), so the maximum field strength in restrict band is $97.37 - 53.58 = 43.79$ dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot on page 78 show 47.08dBc delta between carrier maximum power and local maximum emission in restrict band (2.4855GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 106.78dBuV/m (Peak), so the maximum field strength in restrict band is $106.78 - 47.08 = 59.70$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on page 79 show 53.00dBc delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 97.66dBuV/m (Average), so the maximum field strength in restrict band is $97.66 - 53.00 = 44.66$ dBuV/m which is under 54dBuV/m limit.

802.11g OFDM modulation (Mode B)

NOTE 1: The band edge emission plot on page 77 show 46.25dBc delta between carrier maximum power and local maximum emission in restrict band (2.3892GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 105.55dBuV/m (Peak), so the maximum field strength in restrict band is $105.55 - 46.25 = 59.30$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on page 77 show 53.58dBc delta between carrier maximum power and local maximum emission in restrict band (2.3898GHz). The emission of carrier strength list in the test result of channel 1 at the item 4.2.7 is 95.87dBuV/m (Average), so the maximum field strength in restrict band is $95.87 - 53.58 = 42.29$ dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot on page 78 show 47.08dBc delta between carrier maximum power and local maximum emission in restrict band (2.4855GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 106.95 (Peak), so the maximum field strength in restrict band is $106.95 - 47.08 = 59.87$ dBuV/m which is under 74dBuV/m limit.

The band edge emission plot on page 79 show 53.00dBc delta between carrier maximum power and local maximum emission in restrict band (2.4835GHz). The emission of carrier strength list in the test result of channel 11 at the item 4.2.7 is 96.11dBuV/m (Average), so the maximum field strength in restrict band is $96.11 - 53.00 = 43.11$ dBuV/m which is under 54dBuV/m limit.



**802.11g Turbo OFDM modulation (Mode A)**



NOTE 1: The band edge emission plot on page 80 shows 45.78dBc between carrier maximum power and local maximum emission in restrict band (2.3820GHz). The emission of carrier strength list in the test result of channel 6 at the item 4.2.7 is 106.12dBuV/m (Peak), so the maximum field strength in restrict band is $106.12 - 45.78 = 60.34$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot on page 80 shows 57.08dBc between carrier maximum power and local maximum emission in restrict band (2.3900GHz). The emission of carrier strength list in the test result of channel 6 at the item 4.2.7 is 96.42dBuV/m (Average), so the maximum field strength in restrict band is $96.42 - 57.08 = 39.34$ dBuV/m which is under 54dBuV/m limit.

NOTE 2: The band edge emission plot on page 81 shows 45.72dBc between carrier maximum power and local maximum emission in restrict band (2.4899GHz). The emission of carrier strength list in the test result of channel 6 at the item 4.2.7 is 106.12dBuV/m (Peak), so the maximum field strength in restrict band is $106.12 - 45.72 = 60.40$ dBuV/m which is under 74dBuV/m limit.



The band edge emission plot on page 82 shows 56.93dBc between carrier maximum power and local maximum emission in restrict band (2.4839GHz). The emission of carrier strength list in the test result of channel 6 at the item 4.2.7 is 96.42dBuV/m (Average), so the maximum field strength in restrict band is $96.42 - 56.93 = 39.49$ dBuV/m which is under 54dBuV/m limit.



802.11b DSSS modulation











802.11g OFDM modulation









802.11g Turbo OFDM modulation





4.7 ANTENNA REQUIREMENT

4.7.1 STANDARD APPLICABLE

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

4.7.2 ANTENNA CONNECTED CONSTRUCTION

The antenna used in this product is Printed antenna without antenna connector. The maximum Gain of the antenna is 2dBi.

5. PHOTOGRAPHS OF THE TEST CONFIGURATION

CONDUCTED EMISSION TEST
(Mode A)



(Mode B)



RADIATED EMISSION TEST (Mode A)



(Mode B)



6. INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025.

USA	FCC, NVLAP, UL, A2LA
Germany	TUV Rheinland
Japan	VCCI
Norway	NEMKO
Canada	INDUSTRY CANADA , CSA
R.O.C.	CNLA, BSMI, DGT
Netherlands	Telefication
Singapore	PSB , GOST-ASIA(MOU)
Russia	CERTIS(MOU)

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site:

www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab:

Tel: 886-2-26052180

Fax: 886-2-26052943

Hsin Chu EMC/RF Lab:

Tel: 886-3-5935343

Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Telecom Lab:

Tel: 886-3-3183232

Fax: 886-3-3185050

Linko RF Lab.

Tel: 886-3-3270910

Fax: 886-3-3270892

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also