

FCC ID: H8NWLL3050



RF EXPOSURE REPORT

REPORT NO.: RF920624R01A

MODEL NO.: WLL3050

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Askey Computer Corp.

ADDRESS: 10F, No.119, ChienKang Rd., Chung-Ho,
Taipei, Taiwan, R.O.C.

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: No. 19, Hwa Ya 2nd Rd., Kueishan, Taoyuan,
Taiwan, R.O.C.



RF Exposure Measurement (Mobile Device)

1. Introduction

2.4GHz frequency band is regarded specially as a dangerous band for its heating harmfulness to the human body. That's why microwave oven is operating in this frequency band. The manufacturer whose product is working in this frequency band is obligatory to prove the harmfulness of his product.

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC), and the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

2. Classification

The antenna of the product, under normal use condition, is at least 20cm away from the body of the user. Warning statement for keeping 20cm separation distance and the prohibition of operating next to a person has been printed on the user's manual. So, this product is classified as the **Mobile Device**.

3. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b).



LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A) Limits For Occupational / Control Exposures				
30-300	61.4	0.163	1.0	6
300-1500	F/300	6
1500-100,000	5	6
(B) Limits For General Population / Uncontrolled Exposure				
30-300	27.5	0.073	0.2	30
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

4. Friis Formula

Friis transmission formula : $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm^2 . If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

Ref. : David K. Cheng, *Field and Wave Electromagnetics*, Second Edition,
Page 640, Eq. (11-133).

5. EUT Operating condition

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.



6. Test Results

6.1 Antenna Gain

The maximum Gain measured in Fully Anechoic Chamber is 2.85dBi or 1.928 (numeric).

6.2 Output Power Into Antenna & RF Exposure value at distance 20cm:

Inverted F antenna with 0.19dBi gain

For CCK technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	49.888	0.010	1.0
6	2437	49.545	0.010	1.0
11	2462	49.774	0.010	1.0

For OFDM technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	48.865	0.010	1.0
6	2437	49.204	0.010	1.0
11	2462	48.978	0.010	1.0

The minimum allowable distance is very close to the enclosure of the antenna and is very far away from the human being under normal use condition.

Inverted F antenna with -1.19dBi gain

For CCK technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	49.888	0.008	1.0
6	2437	49.545	0.007	1.0
11	2462	49.774	0.008	1.0

For OFDM technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	48.865	0.007	1.0
6	2437	49.204	0.007	1.0
11	2462	48.978	0.007	1.0

The minimum allowable distance is very close to the enclosure of the antenna and is very far away from the human being under normal use condition.



Inverted F antenna with 0.39dBi gain

For CCK technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	49.888	0.011	1.0
6	2437	49.545	0.011	1.0
11	2462	49.774	0.011	1.0

For OFDM technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	48.865	0.011	1.0
6	2437	49.204	0.011	1.0
11	2462	48.978	0.011	1.0

The minimum allowable distance is very close to the enclosure of the antenna and is very far away from the human being under normal use condition.

Inverted F antenna with -0.97dBi gain

For CCK technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	49.888	0.008	1.0
6	2437	49.545	0.008	1.0
11	2462	49.774	0.008	1.0

For OFDM technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	48.865	0.008	1.0
6	2437	49.204	0.008	1.0
11	2462	48.978	0.008	1.0

The minimum allowable distance is very close to the enclosure of the antenna and is very far away from the human being under normal use condition.



Inverted F antenna with 1.05dBi gain

For CCK technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	49.888	0.013	1.0
6	2437	49.545	0.013	1.0
11	2462	49.774	0.013	1.0

For OFDM technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	48.865	0.012	1.0
6	2437	49.204	0.012	1.0
11	2462	48.978	0.012	1.0

The minimum allowable distance is very close to the enclosure of the antenna and is very far away from the human being under normal use condition.

Inverted F antenna with 1.06dBi gain

For CCK technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	49.888	0.013	1.0
6	2437	49.545	0.013	1.0
11	2462	49.774	0.013	1.0

For OFDM technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	48.865	0.012	1.0
6	2437	49.204	0.012	1.0
11	2462	48.978	0.012	1.0

The minimum allowable distance is very close to the enclosure of the antenna and is very far away from the human being under normal use condition.



Inverted F antenna with 0.14dBi gain

For CCK technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	49.888	0.010	1.0
6	2437	49.545	0.010	1.0
11	2462	49.774	0.010	1.0

For OFDM technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	48.865	0.010	1.0
6	2437	49.204	0.010	1.0
11	2462	48.978	0.010	1.0

The minimum allowable distance is very close to the enclosure of the antenna and is very far away from the human being under normal use condition.

Inverted F antenna with 2.57dBi gain

For CCK technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	49.888	0.018	1.0
6	2437	49.545	0.018	1.0
11	2462	49.774	0.018	1.0

For OFDM technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	48.865	0.018	1.0
6	2437	49.204	0.018	1.0
11	2462	48.978	0.018	1.0

The minimum allowable distance is very close to the enclosure of the antenna and is very far away from the human being under normal use condition.



Inverted F antenna with -0.80dBi gain

For CCK technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	49.888	0.008	1.0
6	2437	49.545	0.008	1.0
11	2462	49.774	0.008	1.0

For OFDM technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	48.865	0.008	1.0
6	2437	49.204	0.008	1.0
11	2462	48.978	0.008	1.0

The minimum allowable distance is very close to the enclosure of the antenna and is very far away from the human being under normal use condition.

Inverted F antenna with 2.48dBi gain

For CCK technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	49.888	0.018	1.0
6	2437	49.545	0.017	1.0
11	2462	49.774	0.018	1.0

For OFDM technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	48.865	0.017	1.0
6	2437	49.204	0.017	1.0
11	2462	48.978	0.017	1.0

The minimum allowable distance is very close to the enclosure of the antenna and is very far away from the human being under normal use condition.



Inverted F antenna with 2.85dBi gain

For CCK technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	49.888	0.019	1.0
6	2437	49.545	0.019	1.0
11	2462	49.774	0.019	1.0

For OFDM technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	48.865	0.019	1.0
6	2437	49.204	0.019	1.0
11	2462	48.978	0.019	1.0

The minimum allowable distance is very close to the enclosure of the antenna and is very far away from the human being under normal use condition.

Inverted F antenna with 0.69dBi gain

For CCK technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	49.888	0.012	1.0
6	2437	49.545	0.012	1.0
11	2462	49.774	0.012	1.0

For OFDM technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	48.865	0.011	1.0
6	2437	49.204	0.011	1.0
11	2462	48.978	0.011	1.0

The minimum allowable distance is very close to the enclosure of the antenna and is very far away from the human being under normal use condition.



Inverted F antenna with 1.03dBi gain

For CCK technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	49.888	0.013	1.0
6	2437	49.545	0.012	1.0
11	2462	49.774	0.013	1.0

For OFDM technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	48.865	0.012	1.0
6	2437	49.204	0.012	1.0
11	2462	48.978	0.012	1.0

The minimum allowable distance is very close to the enclosure of the antenna and is very far away from the human being under normal use condition.

Inverted F antenna with 1.49dBi gain

For CCK technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	49.888	0.014	1.0
6	2437	49.545	0.014	1.0
11	2462	49.774	0.014	1.0

For OFDM technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	48.865	0.014	1.0
6	2437	49.204	0.014	1.0
11	2462	48.978	0.014	1.0

The minimum allowable distance is very close to the enclosure of the antenna and is very far away from the human being under normal use condition.



Inverted F antenna with 2.31dBi gain

For CCK technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	49.888	0.017	1.0
6	2437	49.545	0.017	1.0
11	2462	49.774	0.017	1.0

For OFDM technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	48.865	0.017	1.0
6	2437	49.204	0.017	1.0
11	2462	48.978	0.017	1.0

The minimum allowable distance is very close to the enclosure of the antenna and is very far away from the human being under normal use condition.

Inverted F antenna with -0.14ddBi gain

For CCK technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	49.888	0.010	1.0
6	2437	49.545	0.010	1.0
11	2462	49.774	0.010	1.0

For OFDM technique

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	48.865	0.009	1.0
6	2437	49.204	0.009	1.0
11	2462	48.978	0.009	1.0

The minimum allowable distance is very close to the enclosure of the antenna and is very far away from the human being under normal use condition.