

FCC TEST REPORT (15.247)

REPORT NO.: RF960622H02

MODEL NO.: LA-5137C2

RECEIVED: June 22, 2007

TESTED: July 04 to 10, 2007

ISSUED: July 12, 2007

APPLICANT: Symbol Technologies Inc.

ADDRESS: One Symbol Plaza, Holtsville, NY 11742-1300 U.S.A.

ISSUED BY: Advance Data Technology Corporation

TEST LOCATION: No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien, Taiwan, R.O.C.

This test report consists of 130 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by TAF, A2LA or any government agencies. The test results in the report only apply to the tested sample.



No. 2177-01

Table of Contents

1.	CERTIFICATION	5
2.	SUMMARY OF TEST RESULTS	6
2.1	MEASUREMENT UNCERTAINTY	8
3.	GENERAL INFORMATION	9
3.1	GENERAL DESCRIPTION OF EUT	9
3.2	DESCRIPTION OF TEST MODES	11
3.2.1	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:	12
3.3	GENERAL DESCRIPTION OF APPLIED STANDARDS	14
3.4	DESCRIPTION OF SUPPORT UNITS	15
3.5	CONFIGURATION OF SYSTEM UNDER TEST	15
4.	TEST TYPES AND RESULTS (802.11b & g, 2400 ~ 2483.5MHz Band).....	16
4.1	CONDUCTED EMISSION MEASUREMENT	16
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	16
4.1.2	TEST INSTRUMENTS	16
4.1.3	TEST PROCEDURES.....	17
4.1.4	DEVIATION FROM TEST STANDARD	17
4.1.5	TEST SETUP	18
4.1.6	EUT OPERATING CONDITIONS	18
4.1.7	TEST RESULTS	19
4.2	RADIATED EMISSION MEASUREMENT	21
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	21
4.2.2	TEST INSTRUMENTS	22
4.2.3	TEST PROCEDURES.....	23
4.2.4	DEVIATION FROM TEST STANDARD	23
4.2.5	TEST SETUP	24
4.2.6	EUT OPERATING CONDITIONS	24
4.2.7	TEST RESULTS	25
4.3	6dB BANDWIDTH MEASUREMENT	70
4.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT	70
4.3.2	TEST INSTRUMENTS	70
4.3.3	TEST PROCEDURE	71
4.3.4	DEVIATION FROM TEST STANDARD	71
4.3.5	TEST SETUP	71
4.3.6	EUT OPERATING CONDITIONS	71
4.3.7	TEST RESULTS	72
4.4	MAXIMUM PEAK OUTPUT POWER.....	78
4.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	78
4.4.2	INSTRUMENTS	78

4.4.3	TEST PROCEDURES.....	79
4.4.4	DEVIATION FROM TEST STANDARD	79
4.4.5	TEST SETUP	79
4.4.6	EUT OPERATING CONDITIONS	79
4.4.7	TEST RESULTS	80
4.5	POWER SPECTRAL DENSITY MEASUREMENT	82
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	82
4.5.2	TEST INSTRUMENTS	82
4.5.3	TEST PROCEDURE	83
4.5.4	DEVIATION FROM TEST STANDARD	83
4.5.5	TEST SETUP	83
4.5.6	EUT OPERATING CONDITION.....	83
4.5.7	TEST RESULTS	84
4.6	BAND EDGES MEASUREMENT	90
4.6.1	LIMITS OF BAND EDGES MEASUREMENT	90
4.6.2	TEST INSTRUMENTS	90
4.6.3	TEST PROCEDURE	90
4.6.4	EUT OPERATING CONDITION.....	90
4.6.5	TEST RESULTS.....	91
4.7	ANTENNA REQUIREMENT.....	96
4.7.1	STANDARD APPLICABLE.....	96
4.7.2	ANTENNA CONNECTED CONSTRUCTION.....	96
5.	TEST TYPES AND RESULTS (802.11a, 5725~5850MHz Band)	97
5.1	CONDUCTED EMISSION MEASUREMENT	97
5.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	97
5.1.2	TEST INSTRUMENTS	97
5.1.3	TEST PROCEDURES.....	98
5.1.4	DEVIATION FROM TEST STANDARD	98
5.1.5	TEST SETUP	99
5.1.6	EUT OPERATING CONDITIONS	99
5.1.7	TEST RESULTS.....	100
5.2	RADIATED EMISSION MEASUREMENT	102
5.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	102
5.2.2	TEST INSTRUMENTS	103
5.2.3	TEST PROCEDURES.....	104
5.2.4	DEVIATION FROM TEST STANDARD	104
5.2.5	TEST SETUP	105
5.2.6	EUT OPERATING CONDITIONS	105
5.2.7	TEST RESULTS.....	106
5.3	6dB BANDWIDTH MEASUREMENT.....	110
5.3.1	LIMITS OF 6dB BANDWIDTH MEASUREMENT.....	110

5.3.2	TEST INSTRUMENTS	110
5.3.3	TEST PROCEDURE	111
5.3.4	DEVIATION FROM TEST STANDARD	111
5.3.5	TEST SETUP	111
5.3.6	EUT OPERATING CONDITIONS	111
5.3.7	TEST RESULTS	112
5.4	MAXIMUM PEAK OUTPUT POWER.....	115
5.4.1	LIMITS OF MAXIMUM PEAK OUTPUT POWER MEASUREMENT	115
5.4.2	INSTRUMENTS	115
5.4.3	TEST PROCEDURES.....	116
5.4.4	DEVIATION FROM TEST STANDARD	116
5.4.5	TEST SETUP	116
5.4.6	EUT OPERATING CONDITIONS	116
5.4.7	TEST RESULTS	117
5.5	POWER SPECTRAL DENSITY MEASUREMENT	118
5.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	118
5.5.2	TEST INSTRUMENTS	118
5.5.3	TEST PROCEDURE	119
5.5.4	DEVIATION FROM TEST STANDARD	119
5.5.5	TEST SETUP	119
5.5.6	EUT OPERATING CONDITION.....	119
5.5.7	TEST RESULTS	120
5.6	BAND EDGES MEASUREMENT	123
5.6.1	LIMITS OF BAND EDGES MEASUREMENT	123
5.6.2	TEST INSTRUMENTS	123
5.6.3	TEST PROCEDURE	124
5.6.4	DEVIATION FROM TEST STANDARD	124
5.6.5	EUT OPERATING CONDITION.....	124
5.6.6	TEST RESULTS	125
5.7	ANTENNA REQUIREMENT.....	128
5.7.1	STANDARD APPLICABLE.....	128
5.7.2	ANTENNA CONNECTED CONSTRUCTION.....	128
6.	INFORMATION ON THE TESTING LABORATORIES.....	129
7.	APPENDIX-A MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	130

1. CERTIFICATION

PRODUCT: 802.11a/b/g Compact Flash Radio Card
BRAND NAME: Symbol Technologies Inc.
MODEL NO.: LA-5137C2
TEST SAMPLE: ENGINEERING SAMPLE
TESTED: July 04 to 10, 2007
APPLICANT: Symbol Technologies Inc.
STANDARDS: FCC Part 15, Subpart C (Section 15.247),
ANSI C63.4-2003

The above equipment (Model: LA-5137C2) has been tested by **Advance Data Technology Corporation**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY :  , **DATE:** July 12, 2007
(Midoli Peng, Specialist)

TECHNICAL ACCEPTANCE :  , **DATE:** July 12, 2007
Responsible for RF (Hank Chung, Deputy Manager)

APPROVED BY :  , **DATE:** July 12, 2007
(May Chen, Deputy Manager)

2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

For 802.11b & g, 2412~2462MHz Band

APPLIED STANDARD: FCC Part 15, Subpart C (Section 15.247)			
Standard Section	Test Type and Limit	Result	Remark
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -16.29dB at 0.158MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -1.00dB at 2483.5MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.

For 802.11a, 5725~5850MHz Band

APPLIED STANDARD: FCC Part 15, Subpart C (Section 15.247)			
Standard Section	Test Type and Limit	Result	Remark
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit. Minimum passing margin is -25.23dB at 0.209MHz
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit: min. 500kHz	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power Limit: max. 30dBm	PASS	Meet the requirement of limit.
15.247(d)	Radiated Emissions Limit: Table 15.209	PASS	Meet the requirement of limit. Minimum passing margin is -2.0dB at 11570.00MHz & 11650.00MHz
15.247(e)	Power Spectral Density Limit: max. 8dBm	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement Limit: 20dB less than the peak value of fundamental frequency	PASS	Meet the requirement of limit.

NOTE:

1. The EUT was operating in 2.412 ~ 2.462GHz, 5.15~5.35GHz, 5.47~5.725GHz and 5.725~5.850GHz frequencies band. This report was recorded the RF parameters including 2.412 ~ 2.462GHz and 5.725 ~ 5.850GHz. For the 5.15~5.35GHz and 5.47~5.725GHz RF parameters was recorded in another test report.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Conducted emissions	2.41 dB
Radiated emissions (30MHz-1GHz)	3.89 dB
Radiated emissions (1GHz -18GHz)	2.21 dB
Radiated emissions (18GHz -40GHz)	1.88 dB

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	802.11a/b/g Compact Flash Radio Card
MODEL NO.	LA-5137C2
FCC ID	H9PLA5137C2
POWER SUPPLY	DC 3.3 V +/-5% from host equipment
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
TRANSFER RATE	802.11b: 11/5.5/2/1Mbps 802.11g: 54/48/36/24/18/12/9/6Mbps 802.11a: 54/48/36/24/18/12/9/6Mbps
FREQUENCY RANGE	For 15.407 802.11a: 5.18 ~ 5.32GHz and 5.50 ~ 5.70GHz
	For 15.247 802.11b & 802.11g: 2412 ~ 2462MHz 802.11a: 5.745 ~ 5.825GHz
NUMBER OF CHANNEL	For 15.407 802.11a (5.15 ~ 5.35GHz): 8 802.11a (5.47 ~ 5.725GHz): 11
	For 15.247 802.11b & 802.11g: 11 802.11a (5.725 ~ 5.850GHz): 5
CHANNEL SPACING	802.11b & 802.11g: 5MHz 802.11a: 20MHz
OUTPUT POWER	For 802.11b: 91.201mW For 802.11g: 100.000mW For 802.11a (FCC15.247): 63.096mW For 802.11a (FCC15.407): 36.392mW
DATA CABLE	NA
ANTENNA TYPE	Please see note 2 (on next page)
ASSOCIATED DEVICES	NA

NOTE:

1. The EUT operates in both the 5GHz and 2.4GHz Bands and compatibility with 802.11a and 802.11b, 802.11g technology.
2. There is one antenna provided to this EUT, please refer to the following table:

Model No.	Frequency	Gain (dBi)	Antenna Type	Antenna Connector	Cable loss	Net gain (dBi)
ML-2452-APA2-01	2.4GHz	3	Dipole	R-SMA	0.9dB	2.1
	5GHz	4			1.5dB	2.5

Above antennas the indicated in bold type was chosen for final test.

3. The above EUT information was declared by the manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Operated in 2400 ~ 2483.5MHz band:

For 802.11b/g: Eleven channels are provided to this EUT.

Channel	Frequency	Channel	Frequency
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

Operated in 5725 ~ 5850MHz band:

For 802.11a (5725 ~ 5850MHz band): Five channels are provided to this EUT.

Channel	Frequency
1	5745 MHz
2	5765 MHz
3	5785 MHz
4	5805 MHz
5	5825 MHz

3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL:

EUT configure mode	Applicable to				Description
	PLC	RE<1G	RE≥1G	APCM	
-	√	√	√	√	NA

Where PLC: Power Line Conducted Emission

RE≥1G: Radiated Emission above 1GHz

RE<1G RE: Radiated Emission below 1GHz

APCM: Antenna Port Conducted Measurement

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1	DSSS	CCK	1
802.11a	1 to 5	5	OFDM	BPSK	6

Radiated Emission Test (Below 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1	DSSS	CCK	1
802.11a	1 to 5	5	OFDM	BPSK	6

Radiated Emission Test (Above 1 GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 2, 3, 6, 9, 10, 11	DSSS	CCK	1
802.11g	1 to 11	1, 2, 3, 4, 6, 8, 9, 10, 11	OFDM	BPSK	6
802.11a	1 to 5	1, 3, 5	OFDM	BPSK	6

Channel 2~4 and 8~10 are required by manufacture.

Bandedge Measurement:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1 11	DSSS	CCK	1
802.11g	1 to 11	1, 11	OFDM	BPSK	6
802.11a	1 to 5	1, 5	OFDM	BPSK	6

Antenna Port Conducted Measurement:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Data Rate (Mbps)
802.11b	1 to 11	1, 2, 3, 6, 9, 10, 11	DSSS	CCK	1
802.11g	1 to 11	1, 2, 3, 4, 6, 8, 9, 10, 11	OFDM	BPSK	6
802.11a	1 to 5	1, 3, 5	OFDM	BPSK	6

Channel 2~4 and 8~10 are required by manufacture.

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is an 802.11a/b/g Compact Flash Radio Card. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. (15.247)

ANSI C63.4-2003

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

3.4 DESCRIPTION OF SUPPORT UNITS


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

No.	Product	Brand	Model No.	Serial No.	FCC ID
1	NOTEBOOK COMPUTER	IBM	2372	9949APL	FCC DoC
2	PCMCIA Ext Card	USI	NA	NA	NA
3	CF to PCMCIA Card	USI	NA	NA	NA

No.	Signal cable description
1	NA
2	NA
3	NA

Note: 1. All power cords of the above support units are unshielded (1.8m).

3.5 CONFIGURATION OF SYSTEM UNDER TEST



4. TEST TYPES AND RESULTS (802.11b & g, 2400 ~ 2483.5MHz Band)

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
Test Receiver	ESCS 30	847124/029	Mar. 01, 2008
Line-Impedance Stabilization Network(for EUT)	ENV-216	100071	Nov. 26, 2007
Line-Impedance Stabilization Network(for Peripheral)	ESH3-Z5	848773/004	Oct. 26, 2007
RF Cable (JETBAO)	RG233/U	Cable_CB_01	Dec. 09, 2007
Terminator	50	2	Oct. 30, 2007
Software	ADT_Cond_V7.3.2	NA	NA

- NOTE:**
1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in ADT Shielded Room No. B.
 3. The VCCI Con B Registration No. is C-2193.


4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation

4.1.5 TEST SETUP



Note: 1. Support units were connected to second LISN.

2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.1.6 EUT OPERATING CONDITIONS

- a. Connect the EUT with the support unit 1 (Notebook computer) and placed it on the testing table.
- b. The support unit 1 (Notebook computer) ran a test program “cTxRx 3.0.1.1” to enable EUT under transmission condition continuously.


4.1.7 TEST RESULTS

Conducted Worst-Case Data

MODULATION TYPE	CCK	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TRANSFER RATE	1Mbps
ENVIRONMENTAL CONDITIONS	26deg. C, 58%RH, 960hPa	PHASE	Line (L)
TESTED BY	Wen Yu		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.158	0.40	48.30	-	48.70	-	65.58	55.58	-16.88	-
2	0.259	0.40	27.40	-	27.80	-	61.45	51.45	-33.65	-
3	0.564	0.40	28.38	-	28.78	-	56.00	46.00	-27.22	-
4	1.380	0.44	26.28	-	26.72	-	56.00	46.00	-29.28	-
5	1.935	0.49	25.37	-	25.86	-	56.00	46.00	-30.14	-
6	2.513	0.53	24.80	-	25.33	-	56.00	46.00	-30.67	-


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



MODULATION TYPE	CCK	6dB BANDWIDTH	9 kHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TRANSFER RATE	1Mbps
ENVIRONMENTAL CONDITIONS	26deg. C, 58%RH, 960hPa	PHASE	Neutral (N)
TESTED BY	Wen Yu		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value		Emission Level		Limit		Margin	
			[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.158	0.20	49.09	-	49.29	-	65.58	55.58	-16.29	-
2	0.259	0.20	31.35	-	31.55	-	61.45	51.45	-29.90	-
3	0.576	0.23	28.60	-	28.83	-	56.00	46.00	-27.17	-
4	0.771	0.26	25.88	-	26.14	-	56.00	46.00	-29.86	-
5	0.896	0.28	22.53	-	22.81	-	56.00	46.00	-33.19	-
6	1.119	0.31	21.54	-	21.85	-	56.00	46.00	-34.15	-

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209 as following:

Frequencies (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED UNTIL
ADVANTEST Spectrum Analyzer	R3271A	85060311	July 03, 2008
HP Pre_Amplifier	8449B	3008A01922	Sep. 18, 2007
ROHDE & SCHWARZ Test Receiver	ESCS30	100375	Sep. 20, 2007
CHASE Broadband Antenna	VULB9168	138	Dec. 10, 2007
Schwarzbeck Horn_Antenna	BBHA9120	D124	Jan. 01, 2008
Schwarzbeck Horn_Antenna	BBHA 9170	BBHA9170153	Jan. 04, 2008
SCHWARZBECK Biconical Antenna	VHBA9123	459	Jun. 08, 2009
SCHWARZBECK Periodic Antenna	UPA6108	1148	Jun. 08, 2009
RF Switches (ARNITSU)	CS-201	1565157	NA
RF CABLE (Chaintek)	SF102	22054-2	Nov. 14, 2007
RF Cable(RICHTEC)	9913-30M N-N Cable	STCCAB-30M-1 GHz	July 15, 2007
Software	ADT_Radiated_V 7.6.15.7	NA	NA
CHANCE MOST Antenna Tower	AT-100	0203	NA
CHANCE MOST Turn Table	TT-100	0203	NA

- Note: 1. The calibration interval of the above test instruments is 12 months (36 months for Biconical and Periodic Antenna) and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, HP preamplifier (model: 8449B) and Spectrum Analyzer (model: R3271A) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in ADT Open Site No. C.
4. The FCC Site Registration No. is 656396.
5. The VCCI Site Registration No. is R-1626.
6. The CANADA Site Registration No. is IC 4824A-3.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi- anechoic. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using the quasi-peak method or average method as specified and then reported in Data sheet peak mode and QP mode.


NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation

4.2.5 TEST SETUP



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS

Same as 4.1.6

4.2.7 TEST RESULTS

Below 1GHz Worst-Case Data

MODULATION TYPE	CCK	FREQUENCY RANGE	Below 1000MHz
INPUT POWER (SYSTEM)	120Vac, 60 Hz	TRANSFER RATE	1Mbps
ENVIRONMENTAL CONDITIONS	21deg. C, 66%RH, 960hPa	DETECTOR FUNCTION	Quasi-Peak
TESTED BY	Phoenix Huang		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	80.59	29.48 QP	40.00	-10.52	1.08 H	223	19.44	10.04
2	153.73	32.09 QP	43.50	-11.41	1.08 H	63	18.17	13.92
3	199.39	33.77 QP	43.50	-9.73	1.08 H	247	22.13	11.64
4	288.00	37.31 QP	46.00	-8.69	1.05 H	201	21.06	16.25
5	300.00	32.73 QP	46.00	-13.27	1.01 H	232	15.90	16.83
6	367.50	35.15 QP	46.00	-10.85	1.38 H	3	17.20	17.95
7	500.50	32.35 QP	46.00	-13.65	1.30 H	1	10.58	21.77
8	640.00	32.42 QP	46.00	-13.58	1.27 H	177	7.50	24.92
9	800.30	35.46 QP	46.00	-10.54	1.18 H	137	7.89	27.57
10	880.00	39.15 QP	46.00	-6.85	1.00 H	153	10.48	28.67
11	959.99	35.91 QP	46.00	-10.09	1.00 H	302	6.02	29.89

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	79.71	34.32 QP	40.00	-5.68	1.00 V	220	24.11	10.21
2	200.38	29.82 QP	43.50	-13.68	1.00 V	21	18.20	11.62
3	400.00	31.04 QP	46.00	-14.96	1.00 V	1	12.02	19.02
4	500.50	32.08 QP	46.00	-13.92	1.00 V	1	10.31	21.77
5	600.00	32.27 QP	46.00	-13.73	1.57 V	283	7.79	24.48
6	666.00	29.90 QP	46.00	-16.10	1.45 V	185	4.62	25.28
7	766.70	34.43 QP	46.00	-11.57	1.35 V	1	7.01	27.42
8	959.99	32.46 QP	46.00	-13.54	1.39 V	326	2.57	29.89

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value

802.11b DSSS modulation

CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	1Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 69%RH, 960hPa	TESTED BY	Sky Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2386.00	57.18 PK	74.00	-16.82	1.60 H	277	26.80	30.38
2	2386.00	45.68 AV	54.00	-8.32	1.60 H	277	15.30	30.38
3	*2412.00	97.80 PK			1.05 H	245	67.31	30.49
4	*2412.00	92.10 AV			1.05 H	245	61.61	30.49
5	4824.00	47.60 PK	74.00	-26.40	1.36 H	58	11.91	35.69
6	4824.00	36.40 AV	54.00	-17.60	1.36 H	58	0.71	35.69
7	7236.00	52.60 PK	74.00	-21.40	1.30 H	15	10.36	42.24
8	7236.00	39.30 AV	54.00	-14.70	1.30 H	15	-2.94	42.24

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2386.00	62.78 PK	74.00	-11.22	1.94 V	290	32.40	30.38
2	2386.00	52.98 AV	54.00	-1.02	1.94 V	290	22.60	30.38
3	*2412.00	109.10 PK			1.88 V	270	78.61	30.49
4	*2412.00	104.10 AV			1.88 V	270	73.61	30.49
5	4824.00	49.10 PK	74.00	-24.90	1.55 V	95	13.41	35.69
6	4824.00	41.70 AV	54.00	-12.30	1.55 V	95	6.01	35.69
7	7236.00	53.00 PK	74.00	-21.00	1.50 V	60	10.76	42.24
8	7236.00	39.20 AV	54.00	-14.80	1.50 V	60	-3.04	42.24

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * ” : Fundamental frequency

CHANNEL	Channel 2	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	1Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 69%RH, 960hPa	TESTED BY	Sky Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.64 PK	74.00	-16.36	1.37 H	280	27.24	30.40
2	2390.00	45.89 AV	54.00	-8.11	1.37 H	280	15.49	30.40
3	*2417.00	99.50 PK			1.05 H	246	68.98	30.52
4	*2417.00	93.80 AV			1.05 H	246	63.28	30.52

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	64.40 PK	74.00	-9.60	1.94 V	281	34.01	30.40
2	2390.00	52.82 AV	54.00	-1.18	1.94 V	281	22.42	30.40
3	*2417.00	109.80 PK			1.88 V	280	79.28	30.52
4	*2417.00	105.00 AV			1.88 V	280	74.48	30.52

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. The limit value is defined as per 15.247
6. “ * ” : Fundamental frequency

CHANNEL	Channel 3	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	1Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 69%RH, 960hPa	TESTED BY	Sky Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2385.00	58.11 PK	74.00	-15.89	1.37 H	280	27.74	30.37
2	2385.00	45.43 AV	54.00	-8.57	1.37 H	280	15.06	30.37
3	*2422.00	101.60 PK			1.05 H	248	71.06	30.54
4	*2422.00	96.20 AV			1.05 H	248	65.66	30.54

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2385.00	62.63 PK	74.00	-11.37	1.93 V	282	32.26	30.37
2	2385.00	51.76 AV	54.00	-2.24	1.93 V	282	21.39	30.37
3	*2422.00	111.50 PK			1.88 V	258	80.96	30.54
4	*2422.00	106.60 AV			1.88 V	258	76.06	30.54

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * ” : Fundamental frequency

CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	1Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 69%RH, 960hPa	TESTED BY	Sky Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	101.30 PK			1.06 H	246	70.69	30.61
2	*2437.00	96.00 AV			1.06 H	246	65.39	30.61
3	4874.00	50.50 PK	74.00	-23.50	1.35 H	16	14.70	35.80
4	4874.00	43.70 AV	54.00	-10.30	1.35 H	16	7.90	35.80
5	7311.00	55.00 PK	74.00	-19.00	1.25 H	70	12.48	42.52
6	7311.00	42.40 AV	54.00	-11.60	1.25 H	70	-0.12	42.52

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	111.20 PK			1.87 V	280	80.59	30.61
2	*2437.00	106.50 AV			1.87 V	280	75.89	30.61
3	4874.00	51.90 PK	74.00	-22.10	1.44 V	190	16.10	35.80
4	4874.00	46.30 AV	54.00	-7.70	1.44 V	190	10.50	35.80
5	7311.00	55.40 PK	74.00	-18.60	1.80 V	108	12.88	42.52
6	7311.00	43.10 AV	54.00	-10.90	1.80 V	108	0.58	42.52

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * ” : Fundamental frequency

CHANNEL	Channel 9	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	1Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 69%RH, 960hPa	TESTED BY	Sky Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	101.60 PK			1.26 H	246	70.93	30.67
2	*2452.00	96.10 AV			1.26 H	246	65.43	30.67
3	2488.00	57.40 PK	74.00	-16.60	1.51 H	286	26.56	30.84
4	2488.00	45.85 AV	54.00	-8.15	1.51 H	286	15.01	30.84

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	110.32 PK			1.87 V	260	79.65	30.67
2	*2452.00	105.60 AV			1.87 V	260	74.93	30.67
3	2488.00	61.76 PK	74.00	-12.24	1.57 V	268	30.92	30.84
4	2488.00	52.41 AV	54.00	-1.59	1.57 V	268	21.57	30.84

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency

CHANNEL	Channel 10	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	1Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 69%RH, 960hPa	TESTED BY	Sky Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2457.00	100.10 PK			1.27 H	246	69.40	30.70
2	*2457.00	94.30 AV			1.27 H	246	63.60	30.70
3	2483.50	57.89 PK	74.00	-16.11	1.50 H	284	27.07	30.82
4	2483.50	45.85 AV	54.00	-8.15	1.50 H	284	15.03	30.82

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2457.00	108.10 PK			1.89 V	288	77.40	30.70
2	*2457.00	103.30 AV			1.89 V	288	72.60	30.70
3	2483.50	62.43 PK	74.00	-11.57	1.57 V	267	31.61	30.82
4	2483.50	52.26 AV	54.00	-1.74	1.57 V	267	21.44	30.82

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency

CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	CCK	TRANSFER RATE	1Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 69%RH, 960hPa	TESTED BY	Sky Liao



ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	99.30 PK			1.26 H	245	68.58	30.72
2	*2462.00	93.80 AV			1.26 H	245	63.08	30.72
3	2487.00	57.69 PK	74.00	-16.31	1.51 H	286	26.86	30.83
4	2487.00	46.05 AV	54.00	-7.95	1.51 H	286	15.22	30.83
5	4924.00	47.80 PK	74.00	-26.20	1.30 H	52	11.90	35.90
6	4924.00	36.80 AV	54.00	-17.20	1.30 H	52	0.90	35.90
7	7386.00	53.00 PK	74.00	-21.00	1.22 H	4	10.20	42.80
8	7386.00	39.60 AV	54.00	-14.40	1.22 H	4	-3.20	42.80



ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M



No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	109.40 PK			1.72 V	289	78.68	30.72
2	*2462.00	104.60 AV			1.72 V	289	73.88	30.72
3	2487.00	62.20 PK	74.00	-11.80	1.59 V	268	31.37	30.83
4	2487.00	52.21 AV	54.00	-1.79	1.59 V	268	21.38	30.83
5	4924.00	49.40 PK	74.00	-24.60	1.52 V	86	13.50	35.90
6	4924.00	42.00 AV	54.00	-12.00	1.52 V	86	6.10	35.90
7	7386.00	53.30 PK	74.00	-20.70	1.44 V	72	10.50	42.80
8	7386.00	39.60 AV	54.00	-14.40	1.44 V	72	-3.20	42.80

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * ” : Fundamental frequency





RESTRICTED BANDEDGE (802.11b MODE,CH1, VERTICAL)









RESTRICTED BANDEDGE (802.11b MODE, CH2, HORIZONTAL)





RESTRICTED BANDEDGE (802.11b MODE,CH2, VERTICAL)



RESTRICTED BANDEDGE (802.11b MODE,CH10, VERTICAL)



RESTRICTED BANDEDGE (802.11b MODE,CH3, VERTICAL)



802.11g OFDM modulation

CHANNEL	Channel 1	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 69%RH, 960hPa	TESTED BY	Sky Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	60.62 PK	74.00	-13.38	1.60 H	283	30.22	30.40
2	2390.00	45.97 AV	54.00	-8.03	1.60 H	283	15.57	30.40
3	*2412.00	97.00 PK			1.04 H	246	66.51	30.49
4	*2412.00	86.70 AV			1.04 H	246	56.21	30.49
5	4824.00	45.60 PK	74.00	-28.40	1.23 H	36	9.91	35.69
6	4824.00	32.80 AV	54.00	-21.20	1.23 H	36	-2.89	35.69
7	7236.00	52.80 PK	74.00	-21.20	1.22 H	20	10.56	42.24
8	7236.00	39.20 AV	54.00	-14.80	1.22 H	20	-3.04	42.24

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	72.19 PK	74.00	-1.81	1.47 V	274	41.79	30.40
2	2390.00	52.87 AV	54.00	-1.13	1.47 V	274	22.47	30.40
3	*2412.00	109.30 PK			1.87 V	288	78.81	30.49
4	*2412.00	98.80 AV			1.87 V	288	68.31	30.49
5	4824.00	46.20 PK	74.00	-27.80	1.25 V	6	10.51	35.69
6	4824.00	33.20 AV	54.00	-20.80	1.25 V	6	-2.49	35.69
7	7236.00	52.60 PK	74.00	-21.40	1.15 V	24	10.36	42.24
8	7236.00	39.30 AV	54.00	-14.70	1.15 V	24	-2.94	42.24

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency

CHANNEL	Channel 2	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 69%RH, 960hPa	TESTED BY	Sky Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	59.45 PK	74.00	-14.55	1.60 H	282	29.05	30.40
2	2390.00	45.93 AV	54.00	-8.07	1.60 H	282	15.53	30.40
3	*2417.00	99.40 PK			1.05 H	247	68.88	30.52
4	*2417.00	88.30 AV			1.05 H	247	57.78	30.52

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	68.85 PK	74.00	-5.15	1.47 V	290	38.45	30.40
2	2390.00	52.84 AV	54.00	-1.16	1.47 V	290	22.45	30.40
3	*2417.00	110.30 PK			1.88 V	288	79.78	30.52
4	*2417.00	99.60 AV			1.88 V	288	69.08	30.52

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * ” : Fundamental frequency

CHANNEL	Channel 3	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 69%RH, 960hPa	TESTED BY	Sky Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	60.15 PK	74.00	-13.85	1.61 H	282	29.75	30.40
2	2390.00	46.02 AV	54.00	-7.98	1.61 H	282	15.62	30.40
3	*2422.00	100.50 PK			1.05 H	246	69.96	30.54
4	*2422.00	90.10 AV			1.05 H	246	59.56	30.54

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	69.64 PK	74.00	-4.36	1.47 V	274	39.24	30.40
2	2390.00	52.75 AV	54.00	-1.25	1.47 V	274	22.35	30.40
3	*2422.00	111.00 PK			1.89 V	289	80.46	30.54
4	*2422.00	101.00 AV			1.89 V	289	70.46	30.54

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency

CHANNEL	Channel 4	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 69%RH, 960hPa	TESTED BY	Sky Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	60.71 PK	74.00	-13.29	1.61 H	283	30.31	30.40
2	2390.00	46.10 AV	54.00	-7.90	1.61 H	283	15.70	30.40
3	*2427.00	101.10 PK			1.27 H	245	70.54	30.56
4	*2427.00	90.90 AV			1.27 H	245	60.34	30.56

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	70.96 PK	74.00	-3.04	1.48 V	274	40.56	30.40
2	2390.00	52.99 AV	54.00	-1.01	1.48 V	274	22.59	30.40
3	*2427.00	112.50 PK			1.86 V	289	81.94	30.56
4	*2427.00	102.20 AV			1.86 V	289	71.64	30.56

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * ” : Fundamental frequency

CHANNEL	Channel 6	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 69%RH, 960hPa	TESTED BY	Sky Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	102.30 PK			1.28 H	244	71.69	30.61
2	*2437.00	91.60 AV			1.28 H	244	60.99	30.61
3	4874.00	46.40 PK	74.00	-27.60	1.20 H	28	10.60	35.80
4	4874.00	33.50 AV	54.00	-20.50	1.20 H	28	-2.30	35.80
5	7311.00	53.40 PK	74.00	-20.60	1.15 H	6	10.88	42.52
6	7311.00	40.40 AV	54.00	-13.60	1.15 H	6	-2.12	42.52

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2437.00	113.00 PK			1.86 V	290	82.39	30.61
2	*2437.00	102.70 AV			1.86 V	290	72.09	30.61
3	4874.00	47.60 PK	74.00	-26.40	1.43 V	353	11.80	35.80
4	4874.00	34.60 AV	54.00	-19.40	1.43 V	353	-1.20	35.80
5	7311.00	53.50 PK	74.00	-20.50	1.22 V	66	10.98	42.52
6	7311.00	40.20 AV	54.00	-13.80	1.22 V	66	-2.32	42.52

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * ” : Fundamental frequency

CHANNEL	Channel 8	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 69%RH, 960hPa	TESTED BY	Sky Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2447.00	102.00 PK			1.28 H	282	71.35	30.65
2	*2447.00	91.40 AV			1.28 H	282	60.75	30.65
3	2483.50	61.71 PK	74.00	-12.29	1.03 H	14	30.89	30.82
4	2483.50	46.29 AV	54.00	-7.71	1.03 H	14	15.47	30.82

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2447.00	111.90 PK			1.87 V	287	81.25	30.65
2	*2447.00	101.60 AV			1.87 V	287	70.95	30.65
3	2483.50	71.26 PK	74.00	-2.74	1.38 V	248	40.44	30.82
4	2483.50	52.97 AV	54.00	-1.03	1.38 V	248	22.15	30.82

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * ” : Fundamental frequency

CHANNEL	Channel 9	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 69%RH, 960hPa	TESTED BY	Sky Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	101.10 PK			1.27 H	248	70.43	30.67
2	*2452.00	90.90 AV			1.27 H	248	60.23	30.67
3	2483.50	62.22 PK	74.00	-11.78	1.04 H	12	31.40	30.82
4	2483.50	46.07 AV	54.00	-7.93	1.04 H	12	15.25	30.82

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2452.00	110.50 PK			1.90 V	288	79.83	30.67
2	*2452.00	100.00 AV			1.90 V	288	69.33	30.67
3	2483.50	71.66 PK	74.00	-2.34	1.54 V	264	40.84	30.82
4	2483.50	52.71 AV	54.00	-1.29	1.54 V	264	21.89	30.82

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency

CHANNEL	Channel 10	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 69%RH, 960hPa	TESTED BY	Sky Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2457.00	99.80 PK			1.28 H	248	69.10	30.70
2	*2457.00	89.20 AV			1.28 H	248	58.50	30.70
3	2483.50	61.16 PK	74.00	-12.84	1.03 H	14	30.34	30.82
4	2483.50	45.96 AV	54.00	-8.04	1.03 H	14	15.14	30.82

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2457.00	109.40 PK			1.75 V	288	78.70	30.70
2	*2457.00	99.00 AV			1.75 V	288	68.30	30.70
3	2483.50	71.49 PK	74.00	-2.51	1.63 V	85	40.67	30.82
4	2483.50	52.54 AV	54.00	-1.46	1.63 V	85	21.72	30.82

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * “ : Fundamental frequency

CHANNEL	Channel 11	FREQUENCY RANGE	1 ~ 25GHz
MODULATION TYPE	BPSK	TRANSFER RATE	6Mbps
INPUT POWER (SYSTEM)	120Vac, 60 Hz	DETECTOR FUNCTION	Peak(PK) Average (AV)
ENVIRONMENTAL CONDITIONS	26deg. C, 69%RH, 960hPa	TESTED BY	Sky Liao

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M



No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	98.40 PK			1.26 H	247	67.68	30.72
2	*2462.00	87.40 AV			1.26 H	247	56.68	30.72
3	2483.50	59.81 PK	74.00	-14.19	1.02 H	14	28.99	30.82
4	2483.50	45.74 AV	54.00	-8.26	1.02 H	14	14.92	30.82
5	4924.00	45.90 PK	74.00	-28.10	1.22 H	45	10.00	35.90
6	4924.00	33.40 AV	54.00	-20.60	1.22 H	45	-2.50	35.90
7	7386.00	53.40 PK	74.00	-20.60	1.05 H	32	10.60	42.80
8	7386.00	39.80 AV	54.00	-14.20	1.05 H	32	-3.00	42.80

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M



No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2462.00	108.60 PK			1.75 V	288	77.88	30.72
2	*2462.00	98.10 AV			1.75 V	288	67.38	30.72
3	2483.50	70.91 PK	74.00	-3.09	1.64 V	85	40.09	30.82
4	2483.50	53.00 AV	54.00	-1.00	1.64 V	85	22.18	30.82
5	4924.00	46.50 PK	74.00	-27.50	1.18 V	16	10.60	35.90
6	4924.00	33.30 AV	54.00	-20.70	1.18 V	16	-2.60	35.90
7	7386.00	52.80 PK	74.00	-21.20	1.02 V	25	10.00	42.80
8	7386.00	39.50 AV	54.00	-14.50	1.02 V	25	-3.30	42.80

- REMARKS:**
1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.
 5. The limit value is defined as per 15.247
 6. “ * ” : Fundamental frequency

RESTRICTED BANDEDGE (802.11g MODE,CH1, VERTICAL)



RESTRICTED BANDEDGE (802.11g MODE, CH11, VERTICAL)



RESTRICTED BANDEDGE (802.11g MODE,CH2, VERTICAL)

