



RF EXPOSURE REPORT

REPORT NO.: SA960622H02

MODEL NO.: LA-5137C2

FCC ID: H9PLA5137C2

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: Symbol Technologies Inc.

ADDRESS: One Symbol Plaza, Holtsville, NY 11742- 1300
U.S.A.

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung
Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien,
Taiwan, R.O.C.



RF Exposure Measurement

1. Introduction

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC) calibrated for antenna measurement in ADT, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
300-1500	F/300	6
1500-100,000	5	6
(B)Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	6
1500-100,000	1.0	30

F = Frequency in MHz



3. Friis Formula

Friis transmission formula : $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$

where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm^2 . If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the MPE value at distance 20cm.

Ref. : David K. Cheng, *Field and Wave Electromagnetics*, Second Edition,
Page 640, Eq. (11-133).

4 EUT Operating condition

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

5. Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in users manual. So, this device is classified as **Mobile Device**



6 Test Results

6.1 Antenna Gain

There is one antenna provided to this EUT, please refer to the following table:

Model No.	Frequency	Gain (dBi)	Antenna Type	Antenna Connector	Cable loss	Net gain (dBi)
ML-2452-APA2-01	2.4GHz	3	Dipole	R-SMA	0.9dB	2.1
	5GHz	4			1.5dB	2.5



6.2 Output Power Into Antenna & RF Exposure value:

For 2.4GHz

802.11b:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	60.256	0.019	1.0
2	2417	64.565	0.021	1.0
3	2422	87.096	0.028	1.0
6	2437	79.433	0.026	1.0
9	2452	91.201	0.029	1.0
10	2457	66.069	0.021	1.0
11	2462	63.096	0.020	1.0

802.11g:

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	45.709	0.015	1.0
2	2417	58.884	0.019	1.0
3	2422	77.625	0.025	1.0
4	2427	91.201	0.029	1.0
6	2437	100.000	0.032	1.0
8	2447	93.325	0.030	1.0
9	2452	74.131	0.024	1.0
10	2457	56.234	0.018	1.0
11	2462	42.658	0.014	1.0

Note: Channel 2~4 and 8~10 are required by manufacture.

For 5GHz

Operated in 5150MHz ~ 5350MHz: (15.407)

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	5180	26.363	0.009	1.0
4	5240	23.121	0.008	1.0
5	5260	25.704	0.009	1.0
8	5320	22.080	0.008	1.0



Operated in 5470MHz ~ 5725MHz: (15.407)

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
9	5500	36.396	0.0129	1.0
14	5600	35.892	0.0127	1.0
19	5700	34.914	0.0124	1.0

Operated in 5725 ~ 5850MHz band: (15.247)

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	5745	63.096	0.022	1.0
3	5785	60.256	0.021	1.0
5	5825	60.256	0.021	1.0