

APPROVAL SHEET

FPC Antenna

2.4~2.5 GHz Working Frequency

Halogens Free Product

P/N: RFFPA301914IMAB301

Customer : Primax Electronics Ltd.

Customer 's Part No. :

Production : 禾邦电子（苏州）有限公司
INPAQ TECHNOLOGY(SUZHOU) CO., LTD

Address : 中國江苏省无锡市锡山区安泰一路81号
No.81, Antai 1st Road, Xishan District, Wuxi, Jiangsu, China

[illegible]

品名：RFFPA301914IMAB301

1. Explanation of part number：

RF	FPA	3019	14	I	M	A	B	3	01
Type Code	Product Code	FPCB Dimension (Unit: mm)	Cable Length (unit: cm)	Connector Brand	Type of Connector	Application	Project status	Wire Diameter	Project
RF Device	FPC Antenna	Per 2 digits of length, width e.g.: 3019 Length 30.0mm, Width 19.7mm	2 digits for cable length e.g.: 14 Length 14.7cm	A: N C:MCX D:IPEX III E: IPEX IV F: IPEX A13 H: Hirose I: IPEX M: MMCX S: SMA T: TNC U:MURATA N: None	A: Reverse Female B: Reverse Male F: Female M: Male N: None	0: 0GHz 3: 3GHz 5: 5GHz 6: 6GHz A: 2.4GHz ISM band B: GSM 900/1800 dual band G: GPS band L: 2.4/5.2/5.8 GHz tri-band N: NFC T: LTE band W: WCDMA band	B: MP T:During Test X: Pile Run	0:None 1:Ø 0.81 2:Ø 1.32 3:Ø 1.13 4:Low Loss Ø 1.13 5:Ø 0.5 6:RG316 7: Ø 1.37 8:RG178 9:Low Loss Ø 1.37	01~99 series number

2. Electrical Specification：

Item	Specification
Working Frequency Range	2.4~2.5 GHz (note-1)
Return Loss	-10.0 dB(Max)
VSWR	2.0 (Max)
Polarization	Linear
Radiation Pattern	Omni-directional
Impedance	50Ω

UNLESS OTHER SPECIFIED TOLERANCES ON：
X=N/A X.X=N/A X.XX=N/A
ANGLES=N/A HOLEDIA=N/A



INPAQ TECHNOLOGY CO., LTD.

SCALE：N/A

UNIT：mm

DRAWN BY：劉采璇

CHECKED BY：詹惠雯

DESIGNED BY：林育帆

APPROVED BY：陳振榮


THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE：RFFPA301914IMAB301

DOCUMENT NO.

SPEC REV.
P0

3. Antenna Drawing :



UNLESS OTHER SPECIFIED TOLERANCES ON :
X = N/A X.X = N/A X.XX = N/A
ANGLES = N/A HOLEDIA = N/A



INPAQ TECHNOLOGY CO., LTD.

SCALE : N/A

UNIT : mm

DRAWN BY : 劉采璇

CHECKED BY : 詹惠愛

DESIGNED BY : 林育帆

APPROVED BY : 陳振榮

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF INPAQ TECHNOLOGY CO.,LTD.AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

TITLE : RFFPA301914IMAB301

DOCUMENT
NO.SPEC REV.
P0


Bubblicious

Antenna measurement report



- 1. Brand: Primax
- 2. Model Name : 12-D0101CG01
- 3. Manufacture information: Primax
- 4. Test engineer name :Kyle Wang
- 5. Test date:2024.03.13
- 6. Test Equipment : SATIMO Testing System (SG-24L)
- 7. test set up photo/equipment/ measure method



Antenna	WiFi	BLE
Type	Metal	FPC
model	RFMTA250900NNAB001	RFFPA301914IMAB301
connector info	X	IPEX



Measurement Information

Test Setup:

1. Test in anechoic chamber(Satimo Antenna Testing System)
2. Use instrument such as VNA(vector network analyzer),active switching unit , amplification unit, radio communication unit
3. Scan WIFI band test frequency
4. Test Return Loss by using Network analyzer
5. The DUT with housing and internal antenna




Wi-Fi ANT




BLE ANT

Bubblicious Performance


WIFI



BLE



Isolation



Frequency(MHz)	WiFi		BLE	
	Efficiency(%)	Peak Gain(dBi)	Efficiency(%)	Peak Gain(dBi)
2412	51%	0.87	45%	1.81
2442	55%	1.18	47%	1.65
2484	56%	1.37	47%	1.96




Wi-Fi ANT




BLE ANT

2D Radiation Patterns _ Wi-Fi


XZ-Plane



YZ-Plane




XY-Plane




2D Radiation Patterns _ BLE


XZ-Plane









YZ-Plane



XY-Plane



3D Radiation Patterns



3D Radiation Patterns_BLE

3D Radiation Patterns

