



588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Telephone: +86 (0) 21 6191 5666

Fax: +86 (0) 21 6191 5678

ee.shanghai@sgs.com

Report No.: SHEM180200141603

Page: 1 of 153

## **TEST REPORT**

**Application No.:** SHEM1802001416CR  
**Applicant:** THE CHAMBERLAIN GROUP, INC.  
**Address of Applicant:** 300 Windsor Drive Oakbrook, Illinois, USA 60523  
**Manufacturer:** THE CHAMBERLAIN GROUP, INC.  
**Address of Manufacturer:** 300 Windsor Drive Oakbrook, Illinois, USA 60523  
**Factory:**  
1. Hangzhou Hikvision Technology Co., Ltd.  
2. Hangzhou Hikvision Electronics Co., Ltd.  
**Address of Factory:**  
1. No.700, Dongliu Road, Binjiang District, Hangzhou City, Zhejiang, 310052, China  
2. No.299, Qiushi Road, Tonglu Economic Development Zone, Tonglu County, Hangzhou, Zhejiang, 310052, China.

**Equipment Under Test (EUT):**

**EUT Name:** Wi-Fi Security Camera  
**FCC ID** HBW-VIDSA1INT  
**IC** 2666A- VIDSA1INT  
**Model No.:** MYQ-VIDSA1INT  
**Standard(s) :** 47 CFR Part 15, Subpart E 15.407  
RSS-247 Issue 2, February 2017  
RSS-Gen Issue 5, April 2018

**Date of Receipt:** 2018-02-28  
**Date of Test:** 2018-03-24 to 2018-05-08  
**Date of Issue:** 2018-05-09

<b>Test Result:</b>	<b>Pass*</b>
---------------------	--------------

\* In the configuration tested, the EUT complied with the standards specified above.




Parlam Zhan  
E&E Section Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Revision Record			
Version	Description	Date	Remark
00	Original	2018-05-09	/

Authorized for issue by:			
			
		<b>Vincent Zhu / Project Engineer</b>	
			
		<b>Parlam Zhan / Reviewer</b>	

## 2 Test Summary

Radio Spectrum Technical Requirement				
Item	Standard	Method	Requirement	Result
Antenna Requirement	47 CFR Part 15, Subpart E 15.407	N/A	47 CFR Part 15, Subpart C 15.203	Pass
Transmission in the Absence of Data	47 CFR Part 15, Subpart E 15.407	N/A	47 CFR Part 15, Subpart C 15.407 (c)	Pass

N/A: Not applicable

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart E 15.407	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207 & 15.407 b(6)	Pass
Duty Cycle	47 CFR Part 15, Subpart E 15.407	KDB 789033 II B 1	KDB 789033 D02 II B 1	Pass
99% Bandwidth	47 CFR Part 15, Subpart E 15.407	KDB 789033 II D	N/A	Pass
26dB Emission bandwidth	47 CFR Part 15, Subpart E 15.407	KDB 789033 D02 II C 1	47 CFR Part 15, Subpart C 15.407 (a)	Pass
Minimum 6 dB bandwidth (5.725-5.85 GHz band )	47 CFR Part 15, Subpart E 15.407	KDB 789033 D02 II C 2	47 CFR Part 15, Subpart C 15.407 (e)	Pass
Maximum Conducted output power	47 CFR Part 15, Subpart E 15.407	KDB 789033 D02 II E	47 CFR Part 15, Subpart C 15.407 (a)	Pass
Peak Power spectrum density	47 CFR Part 15, Subpart E 15.407	KDB 789033 D02 II F	47 CFR Part 15, Subpart C 15.407 (a)	Pass
Radiated Emissions	47 CFR Part 15, Subpart E 15.407	KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & 15.407(b)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart E 15.407	KDB 789033 D02 II G	47 CFR Part 15, Subpart C 15.209 & 15.407(b)	Pass
Frequency Stability	47 CFR Part 15, Subpart E 15.407	ANSI C63.10 (2013) Section 6.8	47 CFR Part 15, Subpart C 15.407 (g)	Pass

N/A: Not applicable

### 3 Contents

	Page
1 COVER PAGE .....	1
2 TEST SUMMARY .....	3
3 CONTENTS.....	4
4 GENERAL INFORMATION .....	6
4.1 DETAILS OF E.U.T. .....	6
4.2 DESCRIPTION OF SUPPORT UNITS.....	7
4.3 MEASUREMENT UNCERTAINTY.....	8
4.4 TEST LOCATION .....	9
4.5 TEST FACILITY .....	9
4.6 DEVIATION FROM STANDARDS .....	9
4.7 ABNORMALITIES FROM STANDARD CONDITIONS.....	9
5 EQUIPMENT LIST .....	10
6 RADIO SPECTRUM TECHNICAL REQUIREMENT .....	11
6.1 ANTENNA REQUIREMENT .....	11
6.1.1 Test Requirement:.....	11
6.1.2 Conclusion.....	11
6.2 TRANSMISSION IN THE ABSENCE OF DATA .....	12
6.2.1 Test Requirement:.....	12
6.2.2 Conclusion.....	12
7 RADIO SPECTRUM MATTER TEST RESULTS .....	13
7.1 CONDUCTED EMISSIONS AT AC POWER LINE (150KHz-30MHz) .....	13
7.1.1 E.U.T. Operation .....	13
7.1.2 Test Setup Diagram .....	14
7.1.3 Measurement Procedure and Data .....	14
7.2 DUTY CYCLE.....	17
7.2.1 E.U.T. Operation .....	17
7.2.2 Test Setup Diagram .....	17
7.2.3 Measurement Procedure and Data .....	17
7.3 99% BANDWIDTH.....	18
7.3.1 E.U.T. Operation .....	18
7.3.2 Test Setup Diagram .....	19
7.3.3 Measurement Procedure and Data .....	19
7.4 26dB EMISSION BANDWIDTH.....	20
7.4.1 E.U.T. Operation .....	20
7.4.2 Test Setup Diagram .....	21
7.4.3 Measurement Procedure and Data .....	21
7.5 MINIMUM 6 DB BANDWIDTH (5.725-5.85 GHZ BAND) .....	22
7.5.1 E.U.T. Operation .....	22
7.5.2 Test Setup Diagram .....	22
7.5.3 Measurement Procedure and Data .....	22
7.6 MAXIMUM CONDUCTED OUTPUT POWER .....	23
7.6.1 E.U.T. Operation .....	23
7.6.2 Test Setup Diagram .....	24
7.6.3 Measurement Procedure and Data .....	24
7.7 PEAK POWER SPECTRUM DENSITY .....	25

7.7.1	<i>E.U.T. Operation</i> .....	25
7.7.2	<i>Test Setup Diagram</i> .....	26
7.7.3	<i>Measurement Procedure and Data</i> .....	26
7.8	RADIATED EMISSIONS .....	27
7.8.1	<i>E.U.T. Operation</i> .....	27
7.8.2	<i>Test Setup Diagram</i> .....	28
7.8.3	<i>Measurement Procedure and Data</i> .....	29
7.9	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....	59
7.9.1	<i>E.U.T. Operation</i> .....	59
7.9.2	<i>Test Setup Diagram</i> .....	60
7.9.3	<i>Measurement Procedure and Data</i> .....	61
7.10	FREQUENCY STABILITY.....	151
7.10.1	<i>E.U.T. Operation</i> .....	151
7.10.2	<i>Test Setup Diagram</i> .....	152
7.10.3	<i>Measurement Procedure and Data</i> .....	152
<b>8</b>	<b>TEST SETUP PHOTOGRAPHS.....</b>	<b>153</b>
<b>9</b>	<b>EUT CONSTRUCTIONAL DETAILS.....</b>	<b>153</b>

## 4 General Information

### 4.1 Details of E.U.T.

Power supply: DC 5V 1A, 4.5W MAX By Adapter  
Adapter:  
Model:ED1-050100UA  
INPUT:100-240V~,50/60Hz,0.2A  
OUTPUT:5V 1A

Test voltage: AC 120V  
Cable: DC Cable 300mm for Adapter  
Antenna Gain -4 dBi  
Antenna Type PCB Antenna  
DFS Function Slave without Radar detection  
TPC Function Not Support

Operation Frequency:	Band	Mode	Frequency Range(MHz)	Number of channels
UNII Band I	802.11a/n(HT20)/ac(HT20)	5180-5240	4	
	802.11n(HT40)/ac(HT40)	5190-5230	2	
	802.11ac(HT80)	5210	1	
UNII Band II-A	802.11a/n(HT20)/ac(HT20)	5260-5320	4	
	802.11n(HT40)/ac(HT40)	5270-5310	2	
	802.11ac(HT80)	5290	1	
UNII Band II-C	802.11a/n(HT20)/ac(HT20)	5500-5700	11	
	802.11n(HT40)/ac(HT40)	5510-5670	5	
	802.11ac(HT80)	5530~5610	2	
UNII Band III	802.11a/n(HT20)/ac(HT20)	5745-5825	5	
	802.11n(HT40)/ac(HT40)	5755-5795	2	
	802.11ac(HT80)	5775	1	
Modulation Type:	802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)			
Channel Spacing:	802.11a/n(HT20)/ac(HT20): 20MHz 802.11n(HT40)/ac(HT40): 40MHz 802.11ac(HT80): 80MHz			
Data Rate:	802.11a: 6/9/12/18/24/36/48/54Mbps 802.11n: MCS0-15 802.11ac: MCS0-9			

**Selected Test Channel for 802.11a/n(HT20)/ac(HT20)**

Band	Channel	Frequency
U-NII Band I	The lowest channel (CH36)	5180MHz
	The middle channel (CH40)	5200MHz
	The highest channel (CH48)	5240MHz
U-NII Band II-A	The lowest channel (CH52)	5260MHz
	The middle channel (CH60)	5300MHz
	The highest channel (CH64)	5320MHz
U-NII Band II-C	The lowest channel (CH100)	5500MHz
	The middle channel (CH120)	5600MHz
	The highest channel (CH140)	5700MHz
U-NII Band III	The lowest channel (CH149)	5745MHz
	The middle channel (CH157)	5785MHz
	The highest channel (CH165)	5825MHz

**Selected Test Channel for 802.11n(HT40)/ac(HT40)**

Band	Channel	Frequency
U-NII Band I	The lowest channel (CH38)	5190MHz
	The highest channel (CH46)	5230MHz
U-NII Band II-A	The lowest channel (CH54)	5270MHz
	The highest channel (CH62)	5310MHz
U-NII Band II-C	The lowest channel (CH102)	5510MHz
	The middle channel (CH118)	5590MHz
	The highest channel (CH134)	5670MHz
U-NII Band III	The lowest channel (CH151)	5755MHz
	The highest channel (CH159)	5795MHz

**Selected Test Channel for 802.11ac(HT80)**

Band	Channel	Frequency
U-NII Band I	One channel (CH42)	5210MHz
U-NII Band II-A	One channel (CH58)	5290MHz
U-NII Band II-C	The lowest channel (CH106)	5530MHz
	The middle channel (CH122)	5610MHz
U-NII Band III	One channel (CH155)	5775MHz

## 4.2 Description of Support Units

Description	Manufacturer	Model No.	Serial No.
Laptop	Lenovo	ThinkPad X100e	/
SecureCRT	VanDyke	V 6.2.0	/
Serial port adapter plate	/	Test Plate 3	/

#### 4.3 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Radio Frequency	7.25 x 10-8
2	Timeout	2s
3	Duty cycle	0.37%
4	Occupied Bandwidth	3%
5	RF conducted power	0.75dB
6	RF power density	2.84dB
7	Conducted Spurious emissions	0.75dB
8	RF Radiated power	4.5dB (Below 1GHz) 4.8dB (Above 1GHz)
9	Radiated Spurious emission test	4.2dB (Below 30MHz) 4.4dB (30MHz-1GHz) 4.6dB (1GHz-18GHz) 5.2dB (Above 18GHz)
10	Temperature test	1°C
11	Humidity test	3%
12	Supply voltages	1.5%
13	Time	3%

Note: The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

#### **4.4 Test Location**

All tests were performed at:

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. E&E Lab

588 West Jindu Road, Xinqiao, Songjiang, 201612 Shanghai, China

Tel: +86 21 6191 5666      Fax: +86 21 6191 5678

No tests were sub-contracted.

#### **4.5 Test Facility**

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L0599)**

CNAS has accredited SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **NVLAP (Certificate No. 201034-0)**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. is accredited by the National Voluntary Laboratory Accreditation Program(NVLAP). Certificate No. 201034-0.

- **FCC –Designation Number: CN5033**

SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been recognized as an accredited testing laboratory.

Designation Number: CN5033. Test Firm Registration Number: 479755.

- **Industry Canada (IC) – IC Assigned Code: 8617A**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 8617A-1.

- **VCCI (Member No.: 3061)**

The 3m Semi-anechoic chamber and Shielded Room of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-3868,C-4336,T-12221,G-10830 respectively.

#### **4.6 Deviation from Standards**

None

#### **4.7 Abnormalities from Standard Conditions**

None

## 5 Equipment List

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
<b>Conducted Emission at AC Power Line</b>					
EMI test receiver	R&S	ESR7	SHEM162-1	2017-12-20	2018-12-19
LISN	Schwarzbeck	NSLK8127	SHEM061-1	2017-12-20	2018-12-19
LISN	EMCO	3816/2	SHEM019-1	2017-12-20	2018-12-19
Pulse limiter	R&S	ESH3-Z2	SHEM029-1	2017-12-20	2018-12-19
CE test Cable	/	CE01	/	2017-12-26	2018-12-25
<b>Conducted Test</b>					
Spectrum Analyzer	R&S	FSP-30	SHEM002-1	2017-12-20	2018-12-19
Spectrum Analyzer	Agilent	N9020A	SHEM181-1	2017-09-26	2018-09-25
Power meter	R&S	NRP	SHEM057-1	2017-12-26	2018-12-25
Power Sensor	R&S	NRP-Z22	SHEM136-1	2017-07-22	2018-07-21
Power Sensor	R&S	NRP-Z91	SHEM057-2	2017-12-26	2018-12-25
Signal Generator	R&S	SMR40	SHEM058-1	2017-07-03	2018-07-02
Signal Generator	Agilent	N5182A	SHEM182-1	2017-09-26	2018-09-25
Communication Tester	R&S	CMW270	SHEM183-1	2017-10-22	2018-10-21
Switcher	Tonscend	JS0806	SHEM184-1	2017-09-26	2018-09-25
Splitter	Anritsu	MA1612A	SHEM185-1	/	/
Coupler	e-meca	803-S-1	SHEM186-1	/	/
High-low Temp Cabinet	Suzhou Zhihe	TL-40	SHEM087-1	2017-09-26	2018-09-25
AC Power Stabilizer	WOCEN	6100	SHEM045-1	2017-12-26	2018-12-25
DC Power Supply	QJE	QJ30003SII	SHEM046-1	2017-12-26	2018-12-25
Conducted test Cable	/	RF01, RF 02	/	2017-12-26	2018-12-25
<b>Radiated Test</b>					
EMI test receiver	R&S	ESU40	SHEM051-1	2017-12-20	2018-12-19
Spectrum Analyzer	R&S	FSP-30	SHEM002-1	2017-12-20	2018-12-19
Loop Antenna (9kHz-30MHz)	Schwarzbeck	FMZB1519	SHEM135-1	2017-04-10	2020-04-09
Antenna (25MHz-2GHz)	Schwarzbeck	VULB9168	SHEM048-1	2017-02-28	2020-02-27
Antenna (25MHz-3GHz)	Schwarzbeck	HL562	SHEM010-1	2017-02-28	2020-02-27
Horn Antenna (1-8GHz)	Schwarzbeck	HF906	SHEM009-1	2017-10-24	2020-10-23
Horn Antenna (1-18GHz)	Schwarzbeck	BBHA9120D	SHEM050-1	2017-01-14	2020-01-13
Horn Antenna (14-40GHz)	Schwarzbeck	BBHA 9170	SHEM049-1	2017-12-03	2020-12-02
Pre-amplifier (9KHz-2GHz)	CLAVIIO	LNA-0001-412010	SHEM164-1	2017-08-22	2018-08-21
Pre-amplifier (1-18GHz)	CLAVIIO	BDLNA-0118-352810	SHEM050-2	2017-08-22	2018-08-21
High-amplifier (14-40GHz)	Schwarzbeck	10001	SHEM049-2	2017-12-20	2018-12-19
Band filter	LORCH	9BRX-875/X150-SR	SHEM156-1	/	/
Band filter	LORCH	13BRX-1950/X500-SR	SHEM083-2	/	/
Band filter	LORCH	5BRX-2400/X200-SR	SHEM155-1	/	/
Band filter	LORCH	5BRX-5500/X1000-SR	SHEM157-2	/	/
High pass Filter	Wainwright	WHK3.0/18G-100SS	SHEM157-1	/	/
High pass Filter	Wainwright	WHKS1700-3SS	SHEM157-3	/	/
Semi/Fully Anechoic	ST	11*6*6M	SHEM078-2	2017-07-22	2020-07-21
RE test Cable	/	RE01, RE02, RE06	/	2017-12-26	2018-12-25

## 6 Radio Spectrum Technical Requirement

### 6.1 Antenna Requirement

#### 6.1.1 Test Requirement:

47 CFR Part 15, Subpart C 15.203

#### 6.1.2 Conclusion

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is PCB antenna and no consideration of replacement. The best case gain of the antenna is -4dBi.



## 6.2 Transmission in the Absence of Data

### 6.2.1 Test Requirement:

47 CFR Part 15, Subpart C 15.407 (c)

### 6.2.2 Conclusion

Standard Requirement:

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signalling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Applicants shall include in their application for equipment authorization a description of how this requirement is met.

EUT Details:

WIFI chip (AW-CM256SM) support automatically discontinue transmission in case of either absence of information to transmit or operational failure, if the chip detect absence of information to transmit or operational failure, it will be automatically shut off.

## 7 Radio Spectrum Matter Test Results

### 7.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207 &amp; 15.407 b(6)

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

#### 7.1.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1002 mbar

Pretest these mode to find the worst case:  
c:TX mode (Band 1)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

d:TX mode (Band 2A)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.


e:TX mode (Band 2C)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

f:TX mode (Band 3)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

The worst case for final test:  
c:TX mode (Band 1)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and

found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

### 7.1.2 Test Setup Diagram




### 7.1.3 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50 $\mu$ H + 50hm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor

Mode:c; Line:Live Line




**LISN : LINE**  
**EUT/Project No : 1414CR**  
**Test Mode : c**

Freq (MHz)	Read level (dBuV)	LISN Factor (dB)	Cable Loss (dB)	Emission Level (dBuV)	Emission Limit (dBuV)	Over Limit (dB)	Remark
1 0.15	11.89	0.11	9.81	21.81	55.87	-34.06	Average
2 0.15	29.61	0.11	9.81	39.53	65.87	-26.34	QP
3 0.17	11.77	0.11	9.81	21.69	55.16	-33.47	Average
4 0.17	28.95	0.11	9.81	38.87	65.16	-26.29	QP
5 0.53	20.81	0.11	9.82	30.74	46.00	-15.26	Average
6 0.53	27.87	0.11	9.82	37.80	56.00	-18.20	QP
7 0.92	10.31	0.11	9.83	20.25	46.00	-25.75	Average
8 0.92	17.68	0.11	9.83	27.62	56.00	-28.38	QP
9 1.46	8.37	0.11	9.84	18.32	46.00	-27.68	Average
10 1.46	17.84	0.11	9.84	27.79	56.00	-28.21	QP
11 1.76	8.68	0.12	9.85	18.65	46.00	-27.35	Average
12 1.76	17.49	0.12	9.85	27.46	56.00	-28.54	QP

Notes: Emission Level = Read Level +LISN Factor + Cable loss

Mode:c; Line:Neutral Line



**LISN : NEUTRAL**  
**EUT/Project No : 1414CR**  
**Test Mode : c**

Freq (MHz)	Read level (dBuV)	LISN Factor (dB)	Cable Loss (dB)	Emission		Over Limit (dB)	Remark
				Level (dBuV)	Limit (dBuV)		
1 0.16	14.42	0.12	9.81	24.35	55.52	-31.17	Average
2 0.16	29.60	0.12	9.81	39.53	65.52	-25.99	QP
3 0.23	10.47	0.11	9.81	20.39	52.44	-32.05	Average
4 0.23	23.57	0.11	9.81	33.49	62.44	-28.95	QP
5 0.53	21.78	0.11	9.82	31.71	46.00	-14.29	Average
6 0.53	31.45	0.11	9.82	41.38	56.00	-14.62	QP
7 0.95	16.35	0.11	9.84	26.30	46.00	-19.70	Average
8 0.95	26.61	0.11	9.84	36.56	56.00	-19.44	QP
9 1.24	16.70	0.11	9.84	26.65	46.00	-19.35	Average
10 1.24	25.82	0.11	9.84	35.77	56.00	-20.23	QP
11 1.51	15.11	0.12	9.84	25.07	46.00	-20.93	Average
12 1.51	26.58	0.12	9.84	36.54	56.00	-19.46	QP

Notes: Emission Level = Read Level +LISN Factor + Cable loss

## 7.2 Duty Cycle

Test Requirement KDB 789033 D02 II B 1

Test Method: KDB 789033 II B 1


### 7.2.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

Test mode e:TX mode (Band 2C)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

### 7.2.2 Test Setup Diagram



### 7.2.3 Measurement Procedure and Data

The detailed test data see: Appendix C for SHEM180200141603

### 7.3 99% Bandwidth

Test Requirement N/A  
Test Method: KDB 789033 II D

#### 7.3.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C      Humidity: 50 % RH      Atmospheric Pressure: 1001 mbar


Pretest these mode to find the worst case:  
c:TX mode (Band 1)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

d:TX mode (Band 2A)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

e:TX mode (Band 2C)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

f:TX mode (Band 3)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

The worst case for final test:  
c:TX mode (Band 1)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

**7.3.2 Test Setup Diagram****7.3.3 Measurement Procedure and Data**

The detailed test data see: Appendix C for SHEMA180200141603

## 7.4 26dB Emission bandwidth

Test Requirement 47 CFR Part 15, Subpart C 15.407 (a)

Test Method: KDB 789033 D02 II C 1

### 7.4.1 E.U.T. Operation

Operating Environment:


Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

Pretest these mode to find the worst case: d:TX mode (Band 2A)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

e:TX mode (Band 2C)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

f:TX mode (Band 3)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

The worst case for final test: d:TX mode (Band 2A)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

**7.4.2 Test Setup Diagram****7.4.3 Measurement Procedure and Data**

The detailed test data see: Appendix C for SHEMA180200141603

## 7.5 Minimum 6 dB bandwidth (5.725-5.85 GHz band )

Test Requirement 47 CFR Part 15, Subpart C 15.407 (e)

Test Method: KDB 789033 D02 II C 2

Limit:  $\geq 500$  kHz


### 7.5.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

Test mode f:TX mode (Band 3)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

### 7.5.2 Test Setup Diagram



### 7.5.3 Measurement Procedure and Data

The detailed test data see: Appendix C for SHEMA180200141603

## 7.6 Maximum Conducted output power

Test Requirement 47 CFR Part 15, Subpart C 15.407 (a)

Test Method: KDB 789033 D02 II E

Limit:

Frequency band(MHz)	Limit
5150-5250	≤1W(30dBm) for master device
	≤250mW(24dBm) for client device
5250-5350	≤250mW(24dBm) for client device or 11dBm+10logB*
5470-5725	≤250mW(24dBm) for client device or 11dBm+10logB*
5725-5850	≤1W(30dBm)

Remark: \*Where B is the 26dB emission bandwidth in MHz.  
The maximum conducted output power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage.  
For IC 5150MHz to 5250MHz limit is EIRP≤200mW(23dBm)

### 7.6.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

Pretest these mode to find the worst case: c:TX mode (Band 1)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

d:TX mode (Band 2A)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.


e:TX mode (Band 2C)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

f:TX mode (Band 3)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

The worst case for final test:

c:TX mode (Band 1)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

#### 7.6.2 Test Setup Diagram



#### 7.6.3 Measurement Procedure and Data

The detailed test data see: Appendix C for SHEMA180200141603

## 7.7 Peak Power spectrum density

Test Requirement 47 CFR Part 15, Subpart C 15.407 (a)

Test Method: KDB 789033 D02 II F

Limit:

Frequency band(MHz)	Limit
5150-5250	≤17dBm in 1MHz for master device
	≤11dBm in 1MHz for client device
5250-5350	≤11dBm in 1MHz for client device
5470-5725	≤11dBm in 1MHz for client device
5725-5850	≤30dBm in 500 kHz

Remark: The maximum power spectral density is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test.

For IC 5150MHz to 5250MHz limit is EIRP PSD≤10dBm

### 7.7.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

Pretest these mode to find the worst case:  
c:TX mode (Band 1)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

d:TX mode (Band 2A)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

e:TX mode (Band 2C)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.


f:TX mode (Band 3)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

The worst case

c:TX mode (Band 1)\_Keep the EUT in continuously transmitting mode with all

for final test: modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

### 7.7.2 Test Setup Diagram



### 7.7.3 Measurement Procedure and Data

The detailed test data see: Appendix C for SHEMA180200141603

## 7.8 Radiated Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.407(b)

Test Method: KDB 789033 D02 II G

### 7.8.1 E.U.T. Operation

Operating Environment:


Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

Test mode: c:TX mode (Band 1)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

d:TX mode (Band 2A)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

e:TX mode (Band 2C)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

f:TX mode (Band 3)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

**7.8.2 Test Setup Diagram**

### 7.8.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark 1: Level= Read Level- factory

Factory= Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: Peak limit for Band 1 is -27dBm/MHz, according  $EIRP[dBm] = E[dB\mu V/m] - 95.2$ , So the converted "E" value is 68.2dB $\mu$ V/m

Below 1GHz:


Polarization:Horizontal

**Antenna Polarity :HORIZONTAL****EUT/Project :1414CR****Test mode :a**

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
	MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1	167.82	57.62	11.93	0.65	42.58	27.62	43.50	-15.88	QP
2	216.02	70.97	10.12	0.72	42.50	39.31	46.00	-6.69	QP
3	270.37	60.41	12.22	0.80	42.43	31.00	46.00	-15.00	QP
4	432.55	61.00	15.83	1.06	42.11	35.78	46.00	-10.22	QP
5	552.88	56.45	18.43	1.28	42.17	33.99	46.00	-12.01	QP
6	564.64	54.39	18.68	1.30	42.17	32.20	46.00	-13.80	QP

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Polarization:Vertical

**Antenna Polarity :VERTICAL****EUT/Project :1414CR****Test mode :a**

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
	MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1	43.35	54.97	14.25	0.23	42.63	26.82	40.00	-13.18	QP
2	62.00	49.53	12.35	0.30	42.66	19.52	40.00	-20.48	QP
3	167.82	55.66	11.93	0.65	42.58	25.66	43.50	-17.84	QP
4	216.02	64.33	10.12	0.72	42.50	32.67	46.00	-13.33	QP
5	432.55	59.76	15.83	1.06	42.11	34.54	46.00	-11.46	QP
6	649.66	55.49	19.82	1.51	42.23	34.59	46.00	-11.41	QP

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Mode:c; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10360	34.54	14.28	48.82	68.2	-19.38	peak
15540	30.12	21.58	51.70	54	-2.30	peak
20720	26.51	23.16	49.67	54	-4.33	peak

Mode:c; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10360	29.86	14.28	44.14	68.2	-24.06	peak
15540	27.48	21.58	49.06	54	-4.94	peak
20720	29.64	23.16	52.80	54	-1.20	peak

Mode:c; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10440	31.06	14.14	45.20	68.2	-23.00	peak
15660	30.66	21.22	51.88	54	-2.12	peak
20880	26.00	23.24	49.24	54	-4.76	peak

Mode:c; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10440	33.66	14.14	47.80	68.2	-20.40	peak
15660	29.09	21.22	50.31	54	-3.69	peak
20880	29.62	23.24	52.86	54	-1.14	peak

Mode:c; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10480	33.62	14.08	47.70	68.2	-20.50	peak
15720	28.39	21.10	49.49	54	-4.51	peak
20960	28.28	23.64	51.92	54	-2.08	peak

Mode:c; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10480	36.37	14.08	50.45	68.2	-17.75	peak
15720	29.58	21.10	50.68	54	-3.32	peak
20960	25.52	23.64	49.16	54	-4.84	peak

Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10360	29.20	14.28	43.48	68.2	-24.72	peak
15540	27.78	21.58	49.36	54	-4.64	peak
20720	27.44	23.16	50.60	54	-3.40	peak

Mode:c; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10360	34.02	14.28	48.30	68.2	-19.90	peak
15540	26.87	21.58	48.45	54	-5.55	peak
20720	26.41	23.16	49.57	54	-4.43	peak

Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10440	30.20	14.14	44.34	68.2	-23.86	peak
15660	29.41	21.22	50.63	54	-3.37	peak
20880	25.68	23.24	48.92	54	-5.08	peak

Mode:c; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10440	30.77	14.14	44.91	68.2	-23.29	peak
15660	27.78	21.22	49.00	54	-5.00	peak
20880	27.54	23.24	50.78	54	-3.22	peak

Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10480	31.38	14.08	45.46	68.2	-22.74	peak
15720	27.03	21.10	48.13	54	-5.87	peak
20960	27.02	23.64	50.66	54	-3.34	peak

Mode:c; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10480	33.39	14.08	47.47	68.2	-20.73	peak
15720	27.98	21.10	49.08	54	-4.92	peak
20960	26.55	23.64	50.19	54	-3.81	peak

Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10380	30.81	14.25	45.06	68.2	-23.14	peak
15570	29.18	21.49	50.67	54	-3.33	peak
20760	29.87	23.16	53.03	54	-0.97	peak

Mode:c; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10380	30.87	14.25	45.12	68.2	-23.08	peak
15570	26.80	21.49	48.29	54	-5.71	peak
20760	26.84	23.16	50.00	54	-4.00	peak

Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10460	33.51	14.11	47.62	68.2	-20.58	peak
15690	25.58	21.14	46.72	54	-7.28	peak
20920	28.96	23.31	52.27	54	-1.73	peak

Mode:c; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10460	34.25	14.11	48.36	68.2	-19.84	peak
15690	26.85	21.14	47.99	54	-6.01	peak
20920	28.13	23.31	51.44	54	-2.56	peak

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10360	32.79	14.28	47.07	68.2	-21.13	peak
15540	31.22	21.58	52.80	54	-1.20	peak
20720	27.74	23.16	50.90	54	-3.10	peak

Mode:c; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10360	31.60	14.28	45.88	68.2	-22.32	peak
15540	29.15	21.58	50.73	54	-3.27	peak
20720	30.04	23.16	53.20	54	-0.80	peak

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10440	33.71	14.14	47.85	68.2	-20.35	peak
15660	26.73	21.22	47.95	54	-6.05	peak
20880	29.34	23.24	52.58	54	-1.42	peak

Mode:c; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10440	31.40	14.14	45.54	68.2	-22.66	peak
15660	27.08	21.22	48.30	54	-5.70	peak
20880	26.71	23.24	49.95	54	-4.05	peak

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10480	34.83	14.08	48.91	68.2	-19.29	peak
15720	29.58	21.10	50.68	54	-3.32	peak
20960	26.83	23.64	50.47	54	-3.53	peak

Mode:c; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10480	32.12	14.08	46.20	68.2	-22.00	peak
15720	27.35	21.10	48.45	54	-5.55	peak
20960	30.12	23.64	53.76	54	-0.24	peak

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10380	33.66	14.25	47.91	68.2	-20.29	peak
15570	27.92	21.49	49.41	54	-4.59	peak
20760	29.32	23.16	52.48	54	-1.52	peak

Mode:c; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10380	32.51	14.25	46.76	68.2	-21.44	peak
15570	27.00	21.49	48.49	54	-5.51	peak
20760	28.43	23.16	51.59	54	-2.41	peak

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10460	33.25	14.11	47.36	68.2	-20.84	peak
15690	27.86	21.14	49.00	54	-5.00	peak
20920	29.44	23.31	52.75	54	-1.25	peak

Mode:c; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10460	34.57	14.11	48.68	68.2	-19.52	peak
15690	30.55	21.14	51.69	54	-2.31	peak
20920	26.33	23.31	49.64	54	-4.36	peak

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:80MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10420	30.85	14.17	45.02	68.2	-23.18	peak
15630	27.07	21.32	48.39	54	-5.61	peak
20840	28.09	23.54	51.63	54	-2.37	peak

Mode:c; Polarization:Vertical; Modulation:c; bandwidth:80MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
10420	34.90	14.17	49.07	68.2	-19.13	peak
15630	27.73	21.32	49.05	54	-4.95	peak
20840	26.76	23.54	50.30	54	-3.70	peak

Mode:d; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10520	31.08	14.04	45.12	68.2	-23.08	peak
15780	31.22	21.10	52.32	54	-1.68	peak
21040	30.78	23.08	53.86	54	-0.14	peak

Mode:d; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10520	32.21	14.04	46.25	68.2	-21.95	peak
15780	31.15	21.10	52.25	54	-1.75	peak
21040	28.78	23.08	51.86	54	-2.14	peak

Mode:d; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10560	33.33	14.05	47.38	68.2	-20.82	peak
15840	31.52	21.10	52.62	54	-1.38	peak
21120	27.96	23.14	51.10	54	-2.90	peak

Mode:d; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10560	32.58	14.05	46.63	68.2	-21.57	peak
15840	29.16	21.10	50.26	54	-3.74	peak
21120	28.21	23.14	51.35	54	-2.65	peak

Mode:d; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10640	28.56	14.13	42.69	54	-11.31	peak
15960	28.23	21.10	49.33	54	-4.67	peak
21280	28.21	23.27	51.48	54	-2.52	peak

Mode:d; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10640	33.72	14.13	47.85	54	-6.15	peak
15960	30.61	21.10	51.71	54	-2.29	peak
21280	28.84	23.27	52.11	54	-1.89	peak

Mode:d; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10520	33.11	14.04	47.15	68.2	-21.05	peak
15780	32.47	21.10	53.57	54	-0.43	peak
21040	30.67	23.08	53.75	54	-0.25	peak

Mode:d; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10520	33.01	14.04	47.05	68.2	-21.15	peak
15780	28.72	21.10	49.82	54	-4.18	peak
21040	28.97	23.08	52.05	54	-1.95	peak

Mode:d; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10560	33.70	14.05	47.75	68.2	-20.45	peak
15840	30.45	21.10	51.55	54	-2.45	peak
21120	28.94	23.14	52.08	54	-1.92	peak

Mode:d; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10560	34.63	14.05	48.68	68.2	-19.52	peak
15840	29.60	21.10	50.70	54	-3.30	peak
21120	28.09	23.14	51.23	54	-2.77	peak

Mode:d; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10640	32.48	14.13	46.61	54	-7.39	peak
15960	30.51	21.10	51.61	54	-2.39	peak
21280	28.10	23.27	51.37	54	-2.63	peak

Mode:d; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10640	34.51	14.13	48.64	54	-5.36	peak
15960	31.04	21.10	52.14	54	-1.86	peak
21280	28.93	23.27	52.20	54	-1.80	peak

Mode:d; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10540	33.46	14.05	47.51	68.2	-20.69	peak
15810	32.74	21.10	53.84	54	-0.16	peak
21080	29.06	23.11	52.17	54	-1.83	peak

Mode:d; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10540	32.48	14.05	46.53	68.2	-21.67	peak
15810	32.63	21.10	53.73	54	-0.27	peak
21080	29.90	23.11	53.01	54	-0.99	peak

Mode:d; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10620	33.56	14.08	47.64	54	-6.36	peak
15930	29.57	21.10	50.67	54	-3.33	peak
21240	29.35	23.24	52.59	54	-1.41	peak

Mode:d; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10620	31.21	14.08	45.29	54	-8.71	peak
15930	31.39	21.10	52.49	54	-1.51	peak
21240	28.51	23.24	51.75	54	-2.25	peak

Mode:d; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10520	32.17	14.04	46.21	68.2	-21.99	peak
15780	31.67	21.10	52.77	54	-1.23	peak
21040	27.18	23.08	50.26	54	-3.74	peak

Mode:d; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10520	33.47	14.04	47.51	68.2	-20.69	peak
15780	30.17	21.10	51.27	54	-2.73	peak
21040	27.35	23.08	50.43	54	-3.57	peak

Mode:d; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10560	32.17	14.05	46.22	68.2	-21.98	peak
15840	32.03	21.10	53.13	54	-0.87	peak
21120	29.39	23.14	52.53	54	-1.47	peak

Mode:d; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10560	34.60	14.05	48.65	68.2	-19.55	peak
15840	29.78	21.10	50.88	54	-3.12	peak
21120	30.27	23.14	53.41	54	-0.59	peak

Mode:d; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10640	30.10	14.13	44.23	54	-9.77	peak
15960	28.97	21.10	50.07	54	-3.93	peak
21280	30.58	23.27	53.85	54	-0.15	peak

Mode:d; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10640	30.03	14.13	44.16	54	-9.84	peak
15960	31.68	21.10	52.78	54	-1.22	peak
21280	29.73	23.27	53.00	54	-1.00	peak

Mode:d; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10540	31.33	14.05	45.38	68.2	-22.82	peak
15810	29.84	21.10	50.94	54	-3.06	peak
21080	30.50	23.11	53.61	54	-0.39	peak

Mode:d; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10540	33.71	14.05	47.76	68.2	-20.44	peak
15810	31.59	21.10	52.69	54	-1.31	peak
21080	29.05	23.11	52.16	54	-1.84	peak

Mode:d; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10620	32.60	14.08	46.68	54	-7.32	peak
15930	29.07	21.10	50.17	54	-3.83	peak
21240	29.37	23.24	52.61	54	-1.39	peak

Mode:d; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10620	33.19	14.08	47.27	54	-6.73	peak
15930	31.24	21.10	52.34	54	-1.66	peak
21240	30.02	23.24	53.26	54	-0.74	peak

Mode:d; Polarization:Horizontal; Modulation:c; bandwidth:80MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10580	30.65	14.05	44.70	68.2	-23.50	peak
15870	31.83	21.09	52.92	54	-1.08	peak
21160	29.00	23.17	52.17	54	-1.83	peak

Mode:d; Polarization:Vertical; Modulation:c; bandwidth:80MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
10580	34.95	14.05	49.00	68.2	-19.20	peak
15870	28.63	21.09	49.72	54	-4.28	peak
21160	29.82	23.17	52.99	54	-1.01	peak

Mode:e; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11000	32.37	14.54	46.91	54	-7.09	peak
16500	29.13	22.64	51.77	68.2	-16.43	peak
22000	29.69	23.83	53.52	68.2	-14.68	peak

Mode:e; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11000	33.12	14.54	47.66	54	-6.34	peak
16500	29.47	22.64	52.11	68.2	-16.09	peak
22000	29.33	23.83	53.16	68.2	-15.04	peak

Mode:e; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11200	35.99	14.25	50.24	54	-3.76	peak
16800	30.11	22.92	53.03	68.2	-15.17	peak
22400	28.27	24.06	52.33	54	-1.67	peak

Mode:e; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11200	36.10	14.25	50.35	54	-3.65	peak
16800	28.10	22.92	51.02	68.2	-17.18	peak
22400	28.13	24.06	52.19	54	-1.81	peak

Mode:e; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11400	30.97	14.37	45.34	54	-8.66	peak
17100	29.73	22.87	52.60	68.2	-15.60	peak
22800	26.35	24.47	50.82	54	-3.18	peak

Mode:e; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11400	33.76	14.37	48.13	54	-5.87	peak
17100	29.15	22.87	52.02	68.2	-16.18	peak
22800	28.74	24.47	53.21	54	-0.79	peak

Mode:e; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11000	33.17	14.54	47.71	54	-6.29	peak
16500	31.15	22.64	53.79	68.2	-14.41	peak
22000	27.06	23.83	50.89	68.2	-17.31	peak

Mode:e; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11000	36.61	14.54	51.15	54	-2.85	peak
16500	28.82	22.64	51.46	68.2	-16.74	peak
22000	28.78	23.83	52.61	68.2	-15.59	peak

Mode:e; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11200	32.58	14.25	46.83	54	-7.17	peak
16800	27.17	22.92	50.09	68.2	-18.11	peak
22400	29.28	24.06	53.34	54	-0.66	peak

Mode:e; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11200	33.22	14.25	47.47	54	-6.53	peak
16800	30.62	22.92	53.54	68.2	-14.66	peak
22400	29.20	24.06	53.26	54	-0.74	peak

Mode:e; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11400	31.50	14.38	45.88	54	-8.12	peak
17100	26.92	22.82	49.74	68.2	-18.46	peak
22800	28.67	24.56	53.23	54	-0.77	peak

Mode:e; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11400	33.26	14.38	47.64	54	-6.36	peak
17100	31.35	22.82	54.17	68.2	-14.03	peak
22800	27.00	24.56	51.56	54	-2.44	peak

Mode:e; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11020	35.76	14.52	50.28	54	-3.72	peak
16530	30.20	22.70	52.90	68.2	-15.30	peak
22040	28.10	23.86	51.96	54	-2.04	peak

Mode:e; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11020	33.61	14.52	48.13	54	-5.87	peak
16530	27.99	22.70	50.69	68.2	-17.51	peak
22040	28.03	23.86	51.89	54	-2.11	peak

Mode:e; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11180	35.27	14.29	49.56	54	-4.44	peak
16770	30.99	22.91	53.90	68.2	-14.30	peak
22360	27.29	24.03	51.32	54	-2.68	peak

Mode:e; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11180	34.30	14.29	48.59	54	-5.41	peak
16770	31.54	22.91	54.45	68.2	-13.75	peak
22360	29.82	24.03	53.85	54	-0.15	peak

Mode:e; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11340	29.38	14.38	43.76	54	-10.24	peak
17010	29.16	22.85	52.01	68.2	-16.19	peak
22680	29.68	24.53	54.21	54	0.21	peak

Mode:e; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11340	30.02	14.38	44.40	54	-9.60	peak
17010	27.62	22.85	50.47	68.2	-17.73	peak
22680	28.83	24.53	53.36	54	-0.64	peak

Mode:e; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11000	37.42	14.54	51.96	54	-2.04	peak
16500	29.45	22.64	52.09	68.2	-16.11	peak
22000	28.09	23.83	51.92	68.2	-16.28	peak

Mode:e; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11200	32.62	14.25	46.87	54	-7.13	peak
16800	32.39	22.92	55.31	68.2	-12.89	peak
22400	28.80	24.06	52.86	68.2	-15.34	peak

Mode:e; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11200	32.96	14.25	47.21	54	-6.79	peak
16800	31.22	22.92	54.14	68.2	-14.06	peak
22400	26.18	24.06	50.24	54	-3.76	peak

Mode:e; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11200	33.64	14.25	47.89	54	-6.11	peak
16800	31.70	22.92	54.62	68.2	-13.58	peak
22400	27.62	24.06	51.68	54	-2.32	peak

Mode:e; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11400	33.17	14.38	47.55	54	-6.45	peak
17100	27.81	22.82	50.63	68.2	-17.57	peak
22800	30.02	24.56	54.58	54	0.58	peak

Mode:e; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11400	36.06	14.38	50.44	54	-3.56	peak
17100	30.66	22.82	53.48	68.2	-14.72	peak
22800	28.73	24.56	53.29	54	-0.71	peak

Mode:e; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11020	35.63	14.52	50.15	54	-3.85	peak
16530	28.34	22.70	51.04	68.2	-17.16	peak
22040	29.36	23.86	53.22	54	-0.78	peak

Mode:e; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11020	33.18	14.52	47.70	54	-6.30	peak
16530	29.05	22.70	51.75	68.2	-16.45	peak
22040	26.83	23.86	50.69	54	-3.31	peak

Mode:e; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11180	33.82	14.29	48.11	54	-5.89	peak
16770	30.27	22.91	53.18	68.2	-15.02	peak
22360	26.43	24.03	50.46	54	-3.54	peak

Mode:e; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11180	31.85	14.29	46.14	54	-7.86	peak
16770	27.71	22.91	50.62	68.2	-17.58	peak
22360	28.78	24.03	52.81	54	-1.19	peak

Mode:e; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11340	31.12	14.38	45.50	54	-8.50	peak
17010	30.65	22.85	53.50	68.2	-14.70	peak
22680	26.86	24.53	51.39	54	-2.61	peak

Mode:e; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11340	33.24	14.38	47.62	54	-6.38	peak
17010	28.42	22.85	51.27	68.2	-16.93	peak
22680	28.37	24.53	52.90	54	-1.10	peak

Mode:e; Polarization:Horizontal; Modulation:c; bandwidth:80MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11060	33.01	14.46	47.47	54	-6.53	peak
16590	28.58	22.82	51.40	68.2	-16.80	peak
22120	26.24	23.90	50.14	54	-3.86	peak

Mode:e; Polarization:Vertical; Modulation:c; bandwidth:80MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11060	32.64	14.46	47.10	54	-6.90	peak
16590	30.60	22.82	53.42	68.2	-14.78	peak
22120	28.46	23.90	52.36	54	-1.64	peak

Mode:e; Polarization:Horizontal; Modulation:c; bandwidth:80MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11220	31.73	14.35	46.08	54	-7.92	peak
16830	29.96	22.90	52.86	68.2	-15.34	peak
22440	29.01	24.43	53.44	54	-0.56	peak

Mode:e; Polarization:Vertical; Modulation:c; bandwidth:80MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV	dBuV	dB	
11220	35.03	14.35	49.38	54	-4.62	peak
16830	28.79	22.90	51.69	68.2	-16.51	peak
22440	27.21	24.43	51.64	54	-2.36	peak

Mode:f; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11490	34.65	14.41	49.06	54	-4.94	peak
17235	29.49	22.57	52.06	68.2	-16.14	peak
22980	24.97	24.45	49.42	54	-4.58	peak

Mode:f; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11490	33.48	14.41	47.89	54	-6.11	peak
17235	29.96	22.57	52.53	68.2	-15.67	peak
22980	27.35	24.45	51.80	54	-2.20	peak

Mode:f; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11570	33.57	14.25	47.82	54	-6.18	peak
17355	27.99	21.86	49.85	68.2	-18.35	peak
23140	27.51	24.68	52.19	68.2	-16.01	peak

Mode:f; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11570	36.49	14.25	50.74	54	-3.26	peak
17355	26.72	21.86	48.58	68.2	-19.62	peak
23140	28.82	24.68	53.50	68.2	-14.70	peak

Mode:f; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11650	33.69	14.06	47.75	54	-6.25	peak
17475	28.26	21.15	49.41	68.2	-18.79	peak
23300	26.57	25.11	51.68	68.2	-16.52	peak

Mode:f; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11650	34.91	14.06	48.97	54	-5.03	peak
17475	27.14	21.15	48.29	68.2	-19.91	peak
23300	25.04	25.11	50.15	68.2	-18.05	peak

Mode:f; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11490	34.96	14.41	49.37	54	-4.63	peak
17235	29.02	22.57	51.59	68.2	-16.61	peak
22980	27.12	24.45	51.57	54	-2.43	peak

Mode:f; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11490	33.55	14.41	47.96	54	-6.04	peak
17235	26.93	22.57	49.50	68.2	-18.70	peak
22980	27.22	24.45	51.67	54	-2.33	peak

Mode:f; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11570	33.25	14.25	47.50	54	-6.50	peak
17355	27.42	21.86	49.28	68.2	-18.92	peak
23140	27.23	24.68	51.91	68.2	-16.29	peak

Mode:f; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11570	35.40	14.25	49.65	54	-4.35	peak
17355	27.63	21.86	49.49	68.2	-18.71	peak
23140	26.36	24.68	51.04	68.2	-17.16	peak

Mode:f; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11650	31.96	14.06	46.02	54	-7.98	peak
17475	30.35	21.15	51.50	68.2	-16.70	peak
23300	29.78	25.11	54.89	68.2	-13.31	peak

Mode:f; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11650	35.99	14.06	50.05	54	-3.95	peak
17475	27.30	21.15	48.45	68.2	-19.75	peak
23300	26.30	25.11	51.41	68.2	-16.79	peak

Mode:f; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11510	30.56	14.40	44.96	54	-9.04	peak
17265	29.75	22.40	52.15	68.2	-16.05	peak
23020	23.88	24.68	48.56	54	-5.44	peak

Mode:f; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11510	32.60	14.40	47.00	54	-7.00	peak
17265	30.32	22.40	52.72	68.2	-15.48	peak
23020	27.13	24.68	51.81	54	-2.19	peak

Mode:f; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11590	35.10	14.20	49.30	54	-4.70	peak
17385	28.18	21.68	49.86	68.2	-18.34	peak
23180	26.22	24.72	50.94	68.2	-17.26	peak

Mode:f; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11590	32.34	14.20	46.54	54	-7.46	peak
17385	26.31	21.68	47.99	68.2	-20.21	peak
23180	27.79	24.72	52.51	68.2	-15.69	peak

Mode:f; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11490	34.07	14.41	48.48	54	-5.52	peak
17235	29.81	22.57	52.38	68.2	-15.82	peak
22980	27.35	24.45	51.80	54	-2.20	peak

Mode:f; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11490	34.01	14.41	48.42	54	-5.58	peak
17235	29.19	22.57	51.76	68.2	-16.44	peak
22980	28.55	24.45	53.00	54	-1.00	peak

Mode:f; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11570	36.63	14.25	50.88	54	-3.12	peak
17355	28.36	21.86	50.22	68.2	-17.98	peak
23140	25.86	24.68	50.54	68.2	-17.66	peak

Mode:f; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:middle

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11570	32.43	14.25	46.68	54	-7.32	peak
17355	28.78	21.86	50.64	68.2	-17.56	peak
23140	31.78	24.68	56.46	68.2	-11.74	peak

Mode:f; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11650	31.60	14.06	45.66	54	-8.34	peak
17475	26.89	21.15	48.04	68.2	-20.16	peak
23300	27.03	25.11	52.14	68.2	-16.06	peak

Mode:f; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11650	32.33	14.06	46.39	54	-7.61	peak
17475	27.16	21.15	48.31	68.2	-19.89	peak
23300	25.84	25.11	50.95	68.2	-17.25	peak

Mode:f; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11510	32.58	14.40	46.98	54	-7.02	peak
17265	26.57	22.40	48.97	68.2	-19.23	peak
23020	28.26	24.68	52.94	54	-1.06	peak

Mode:f; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11510	33.43	14.40	47.83	54	-6.17	peak
17265	28.16	22.40	50.56	68.2	-17.64	peak
23020	26.52	24.68	51.20	54	-2.80	peak

Mode:f; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11590	32.25	14.20	46.45	54	-7.55	peak
17385	27.00	21.68	48.68	68.2	-19.52	peak
23180	24.15	24.72	48.87	68.2	-19.33	peak

Mode:f; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:High

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11590	35.37	14.20	49.57	54	-4.43	peak
17385	26.38	21.68	48.06	68.2	-20.14	peak
23180	28.33	24.72	53.05	68.2	-15.15	peak

Mode:f; Polarization:Horizontal; Modulation:c; bandwidth:80MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11550	32.24	14.30	46.54	54	-7.46	peak
17325	30.38	22.04	52.42	68.2	-15.78	peak
23100	27.92	24.60	52.52	54	-1.48	peak

Mode:f; Polarization:Vertical; Modulation:c; bandwidth:80MHz; Channel:Low

Frequency	RX_R	Factor	Emission	Limit	Margin	Detector
MHz	dBuV	dB	dBuV/m	dBuV/m	dB	
11550	36.20	14.30	50.50	54	-3.50	peak
17325	27.46	22.04	49.50	68.2	-18.70	peak
23100	26.34	24.60	50.94	54	-3.06	peak

## 7.9 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 &amp; 15.407(b)

Test Method: KDB 789033 D02 II G

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

### 7.9.1 E.U.T. Operation

Operating Environment:

Temperature: 22 °C Humidity: 50 % RH Atmospheric Pressure: 1001 mbar

Test mode: c:TX mode (Band 1)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.


d:TX mode (Band 2A)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

e:TX mode (Band 2C)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.

f:TX mode (Band 3)\_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE

802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE  
802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE  
802.11ac(VHT80). Only the data of worst case is recorded in the report.

### 7.9.2 Test Setup Diagram




### 7.9.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor


Mode:c; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5144.02	49.82	31.61	9.06	38.81	51.68	74.00	-22.32	Peak
2 5150.00	51.41	31.61	9.06	38.81	53.27	74.00	-20.73	Peak
3 5181.84	93.27	31.65	8.86	38.80	94.98	74.00	20.98	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:c; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5140.25	57.29	31.59	9.06	38.82	59.12	74.00	-14.88	Peak
2 5150.00	59.93	31.61	9.06	38.81	61.79	74.00	-12.21	Peak
3 5179.56	102.69	31.65	8.86	38.80	104.40	74.00	30.40	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:c; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5076.64	33.99	31.51	9.44	38.85	36.09	54.00	-17.91	Average
2 5150.00	44.31	31.61	9.06	38.81	46.17	54.00	-7.83	Average
3 5179.56	92.51	31.65	8.86	38.80	94.22	54.00	40.22	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5076.64	45.45	31.51	9.44	38.85	47.55	74.00	-26.45	Peak
2 5150.00	48.36	31.61	9.06	38.81	50.22	74.00	-23.78	Peak
3 5181.84	92.85	31.65	8.86	38.80	94.56	74.00	20.56	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:c; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5146.28	60.39	31.61	9.06	38.81	62.25	74.00	-11.75	Peak
2 5150.00	59.52	31.61	9.06	38.81	61.38	74.00	-12.62	Peak
3 5178.80	102.67	31.65	8.86	38.80	104.38	74.00	30.38	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:c; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 4996.21	32.08	31.40	9.81	38.89	34.40	54.00	-19.60	Average
2 5150.00	40.74	31.61	9.06	38.81	42.60	54.00	-11.40	Average
3 5178.80	88.51	31.65	8.86	38.80	90.22	54.00	36.22	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5139.59	56.62	31.59	9.06	38.82	58.45	74.00	-15.55	Peak
2 5150.00	53.08	31.61	9.06	38.81	54.94	74.00	-19.06	Peak
3 5192.40	91.45	31.68	8.86	38.79	93.20	74.00	19.20	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:c; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5131.87	33.85	31.59	9.06	38.82	35.68	54.00	-18.32	Average
2 5150.00	34.09	31.61	9.06	38.81	35.95	54.00	-18.05	Average
3 5193.18	77.91	31.68	8.86	38.79	79.66	54.00	25.66	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:c; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5144.22	65.53	31.61	9.06	38.81	67.39	74.00	-6.61	Peak
2 5150.00	65.36	31.61	9.06	38.81	67.22	74.00	-6.78	Peak
3 5196.30	99.22	31.68	8.86	38.79	100.97	74.00	26.97	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:c; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low



Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5076.62	34.11	31.51	9.44	38.85	36.21	54.00	-17.79	Average
2 5150.00	45.79	31.61	9.06	38.81	47.65	54.00	-6.35	Average
3 5193.18	83.80	31.68	8.86	38.79	85.55	54.00	31.55	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5142.51	47.56	31.61	9.06	38.81	49.42	74.00	-24.58	Peak
2 5150.00	48.63	31.61	9.06	38.81	50.49	74.00	-23.51	Peak
3 5177.28	92.10	31.65	8.86	38.80	93.81	74.00	19.81	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:c; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5149.29	61.01	31.61	9.06	38.81	62.87	74.00	-11.13	Peak
2 5150.00	56.57	31.61	9.06	38.81	58.43	74.00	-15.57	Peak
3 5179.56	101.72	31.65	8.86	38.80	103.43	74.00	29.43	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor


Mode:c; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5076.64	33.53	31.51	9.44	38.85	35.63	54.00	-18.37	Average
2 5150.00	38.48	31.61	9.06	38.81	40.34	54.00	-13.66	Average
3 5181.84	87.52	31.65	8.86	38.80	89.23	54.00	35.23	Average

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5132.64	56.81	31.59	9.06	38.82	58.64	74.00	-15.36	Peak
2 5150.00	51.76	31.61	9.06	38.81	53.62	74.00	-20.38	Peak
3 5192.40	91.72	31.68	8.86	38.79	93.47	74.00	19.47	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5111.08	35.99	31.55	9.26	38.84	37.96	54.00	-16.04	Average
2 5150.00	36.38	31.61	9.06	38.81	38.24	54.00	-15.76	Average
3 5192.40	77.97	31.68	8.86	38.79	79.72	54.00	25.72	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:c; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5142.68	62.08	31.61	9.06	38.81	63.94	74.00	-10.06	Peak
2 5150.00	63.34	31.61	9.06	38.81	65.20	74.00	-8.80	Peak
3 5192.40	99.05	31.68	8.86	38.79	100.80	74.00	26.80	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:c; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5146.54	41.74	31.61	9.06	38.81	43.60	54.00	-10.40	Average
2 5150.00	42.51	31.61	9.06	38.81	44.37	54.00	-9.63	Average
3 5192.40	82.66	31.68	8.86	38.79	84.41	54.00	30.41	Average

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor


Mode:c; Polarization:Horizontal; Modulation:c; bandwidth:80MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5060.35	45.81	31.48	9.63	38.86	48.06	74.00	-25.94	Peak
2 5150.00	46.12	31.61	9.06	38.81	47.98	74.00	-26.02	Peak
3 5215.35	87.73	31.70	8.66	38.78	89.31	74.00	15.31	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:c; Polarization:Vertical; Modulation:c; bandwidth:80MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5137.67	61.70	31.59	9.06	38.82	63.53	74.00	-10.47	Peak
2 5150.00	59.16	31.61	9.06	38.81	61.02	74.00	-12.98	Peak
3 5207.94	95.18	31.70	8.66	38.78	96.76	74.00	22.76	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:c; Polarization:Vertical; Modulation:c; bandwidth:80MHz; Channel:Low




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5135.24	40.84	31.59	9.06	38.82	42.67	54.00	-11.33	Average
2 5150.00	41.42	31.61	9.06	38.81	43.28	54.00	-10.72	Average
3 5207.94	78.27	31.70	8.66	38.78	79.85	54.00	25.85	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:d; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5319.27	95.91	31.85	8.95	38.72	97.99	74.00	23.99	Peak
2 5350.00	52.90	31.89	9.20	38.70	55.29	74.00	-18.71	Peak
3 5352.28	56.23	31.89	9.20	38.70	58.62	74.00	-15.38	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:d; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:High

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5318.95	86.37	31.85	8.95	38.72	88.45	54.00	34.45	Average
2 5350.00	38.79	31.89	9.20	38.70	41.18	54.00	-12.82	Average
3 5354.35	38.52	31.91	9.20	38.69	40.94	54.00	-13.06	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:d; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:High



Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5318.95	101.82	31.85	8.95	38.72	103.90	74.00	29.90	Peak
2 5350.00	54.19	31.89	9.20	38.70	56.58	74.00	-17.42	Peak
3 5352.12	57.69	31.89	9.20	38.70	60.08	74.00	-13.92	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:d; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:High

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5319.11	92.60	31.85	8.95	38.72	94.68	54.00	40.68	Average
2 5350.00	41.37	31.89	9.20	38.70	43.76	54.00	-10.24	Average
3 5353.87	40.48	31.89	9.20	38.70	42.87	54.00	-11.13	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:d; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5321.17	95.53	31.85	8.95	38.72	97.61	74.00	23.61	Peak
2 5350.05	48.44	31.89	9.20	38.70	50.83	74.00	-23.17	Peak
3 5351.64	50.24	31.89	9.20	38.70	52.63	74.00	-21.37	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:d; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5318.95	102.29	31.85	8.95	38.72	104.37	74.00	30.37	Peak
2 5350.00	54.88	31.89	9.20	38.70	57.27	74.00	-16.73	Peak
3 5352.59	57.21	31.89	9.20	38.70	59.60	74.00	-14.40	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:d; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5318.63	88.75	31.85	8.95	38.72	90.83	54.00	36.83	Average
2 5350.00	38.76	31.89	9.20	38.70	41.15	54.00	-12.85	Average
3 5351.16	38.65	31.89	9.20	38.70	41.04	54.00	-12.96	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:d; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5313.74	91.65	31.85	8.95	38.72	93.73	74.00	19.73	Peak
2 5350.00	55.60	31.89	9.20	38.70	57.99	74.00	-16.01	Peak
3 5351.82	57.21	31.89	9.20	38.70	59.60	74.00	-14.40	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:d; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5313.56	75.91	31.85	8.95	38.72	77.99	54.00	23.99	Average
2 5350.00	36.81	31.89	9.20	38.70	39.20	54.00	-14.80	Average
3 5352.35	36.58	31.89	9.20	38.70	38.97	54.00	-15.03	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:d; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5314.27	97.71	31.85	8.95	38.72	99.79	74.00	25.79	Peak
2 5350.00	61.20	31.89	9.20	38.70	63.59	74.00	-10.41	Peak
3 5351.46	64.68	31.89	9.20	38.70	67.07	74.00	-6.93	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:d; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5313.56	82.11	31.85	8.95	38.72	84.19	54.00	30.19	Average
2 5350.00	43.48	31.89	9.20	38.70	45.87	54.00	-8.13	Average
3 5353.79	41.61	31.89	9.20	38.70	44.00	54.00	-10.00	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:d; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5318.48	95.05	31.85	8.95	38.72	97.13	74.00	23.13	Peak
2 5350.00	47.95	31.89	9.20	38.70	50.34	74.00	-23.66	Peak
3 5354.35	50.56	31.91	9.20	38.69	52.98	74.00	-21.02	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:d; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:High

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5321.64	101.76	31.85	8.95	38.72	103.84	74.00	29.84	Peak
2 5350.00	52.40	31.89	9.20	38.70	54.79	74.00	-19.21	Peak
3 5352.12	55.37	31.89	9.20	38.70	57.76	74.00	-16.24	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:d; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:High

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5321.17	87.62	31.85	8.95	38.72	89.70	54.00	35.70	Average
2 5350.00	37.11	31.89	9.20	38.70	39.50	54.00	-14.50	Average
3 5351.80	36.94	31.89	9.20	38.70	39.33	54.00	-14.67	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:d; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:High




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5314.98	91.84	31.85	8.95	38.72	93.92	74.00	19.92	Peak
2 5350.00	53.05	31.89	9.20	38.70	55.44	74.00	-18.56	Peak
3 5352.89	57.61	31.89	9.20	38.70	60.00	74.00	-14.00	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:d; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:High

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5314.81	75.46	31.85	8.95	38.72	77.54	54.00	23.54	Average
2 5350.00	36.45	31.89	9.20	38.70	38.84	54.00	-15.16	Average
3 5352.53	36.60	31.89	9.20	38.70	38.99	54.00	-15.01	Average

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor


Mode:d; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:High

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5308.22	97.22	31.85	8.95	38.72	99.30	74.00	25.30	Peak
2 5350.00	64.58	31.89	9.20	38.70	66.97	74.00	-7.03	Peak
3 5351.28	63.46	31.89	9.20	38.70	65.85	74.00	-8.15	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:d; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:High




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5314.81	81.60	31.85	8.95	38.72	83.68	54.00	29.68	Average
2 5350.00	43.02	31.89	9.20	38.70	45.41	54.00	-8.59	Average
3 5352.35	42.35	31.89	9.20	38.70	44.74	54.00	-9.26	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:d; Polarization:Horizontal; Modulation:c; bandwidth:80MHz; Channel:High




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5292.85	87.76	31.82	8.71	38.73	89.56	74.00	15.56	Peak
2 5350.00	51.77	31.89	9.20	38.70	54.16	74.00	-19.84	Peak
3 5353.71	55.03	31.89	9.20	38.70	57.42	74.00	-16.58	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:d; Polarization:Horizontal; Modulation:c; bandwidth:80MHz; Channel:High




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5292.63	70.96	31.82	8.71	38.73	72.76	54.00	18.76	Average
2 5350.00	36.05	31.89	9.20	38.70	38.44	54.00	-15.56	Average
3 5353.71	37.05	31.89	9.20	38.70	39.44	54.00	-14.56	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:d; Polarization:Vertical; Modulation:c; bandwidth:80MHz; Channel:High

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5282.85	95.35	31.80	8.71	38.74	97.12	74.00	23.12	Peak
2 5350.00	60.89	31.89	9.20	38.70	63.28	74.00	-10.72	Peak
3 5386.40	58.08	31.95	9.44	38.68	60.79	74.00	-13.21	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Mode:d; Polarization:Vertical; Modulation:c; bandwidth:80MHz; Channel:High




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5287.19	77.55	31.80	8.71	38.74	79.32	54.00	25.32	Average
2 5350.00	42.37	31.89	9.20	38.70	44.76	54.00	-9.24	Average
3 5353.71	43.63	31.89	9.20	38.70	46.02	54.00	-7.98	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:e; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5453.07	48.28	32.04	9.23	38.64	50.91	74.00	-23.09	Peak
2 5460.00	47.02	32.04	9.23	38.64	49.65	74.00	-24.35	Peak
3 5498.46	96.91	32.10	9.13	38.61	99.53	74.00	25.53	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:e; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5455.97	51.39	32.04	9.23	38.64	54.02	74.00	-19.98	Peak
2 5460.00	53.28	32.04	9.23	38.64	55.91	74.00	-18.09	Peak
3 5499.32	99.96	32.10	9.13	38.61	102.58	74.00	28.58	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:e; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:Low



Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5456.99	37.99	32.04	9.23	38.64	40.62	54.00	-13.38	Average
2 5460.00	38.35	32.04	9.23	38.64	40.98	54.00	-13.02	Average
3 5499.15	90.19	32.10	9.13	38.61	92.81	54.00	38.81	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:e; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5383.58	45.79	31.93	9.44	38.68	48.48	74.00	-25.52	Peak
2 5460.00	43.32	32.04	9.23	38.64	45.95	74.00	-28.05	Peak
3 5497.25	94.07	32.10	9.13	38.61	96.69	74.00	22.69	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:e; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5452.21	49.73	32.04	9.23	38.64	52.36	74.00	-21.64	Peak
2 5460.00	48.50	32.04	9.23	38.64	51.13	74.00	-22.87	Peak
3 5498.46	100.16	32.10	9.13	38.61	102.78	74.00	28.78	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:e; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5459.39	48.81	32.04	9.23	38.64	51.44	74.00	-22.56	Peak
2 5460.00	47.08	32.04	9.23	38.64	49.71	74.00	-24.29	Peak
3 5513.77	92.46	32.10	9.13	38.60	95.09	74.00	21.09	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:e; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5425.77	47.48	31.99	9.34	38.66	50.15	74.00	-23.85	Peak
2 5460.00	49.16	32.04	9.23	38.64	51.79	74.00	-22.21	Peak
3 5507.62	95.12	32.10	9.13	38.61	97.74	74.00	23.74	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:e; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:Low



Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5409.91	44.75	31.97	9.44	38.67	47.49	74.00	-26.51	Peak
2 5460.00	42.56	32.04	9.23	38.64	45.19	74.00	-28.81	Peak
3 5498.80	93.63	32.10	9.13	38.61	96.25	74.00	22.25	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:e; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5455.46	48.11	32.04	9.23	38.64	50.74	74.00	-23.26	Peak
2 5460.00	47.06	32.04	9.23	38.64	49.69	74.00	-24.31	Peak
3 5499.49	99.30	32.10	9.13	38.61	101.92	74.00	27.92	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:e; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5432.22	46.22	32.02	9.34	38.65	48.93	74.00	-25.07	Peak
2 5460.00	46.32	32.04	9.23	38.64	48.95	74.00	-25.05	Peak
3 5514.73	92.62	32.10	9.13	38.60	95.25	74.00	21.25	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:e; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5432.97	50.08	32.02	9.34	38.65	52.79	74.00	-21.21	Peak
2 5460.00	49.97	32.04	9.23	38.64	52.60	74.00	-21.40	Peak
3 5507.81	95.02	32.10	9.13	38.61	97.64	74.00	23.64	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:e; Polarization:Horizontal; Modulation:c; bandwidth:80MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq MHz	Read Level dBuv	Antenna Factor dB/m	Cable Loss dB	Preamp Factor dB	Emission Level dBuv/m	Limit Line dBuv/m	Over Limit dB	Remark
	-----	-----	-----	-----	-----	-----	-----	-----
1 5454.14	49.94	32.04	9.23	38.64	52.57	74.00	-21.43	Peak
2 5460.00	47.03	32.04	9.23	38.64	49.66	74.00	-24.34	Peak
3 5535.09	89.13	32.11	9.07	38.61	91.70	74.00	17.70	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:e; Polarization:Vertical; Modulation:c; bandwidth:80MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5434.43	48.40	32.02	9.34	38.65	51.11	74.00	-22.89	Peak
2 5460.00	46.18	32.04	9.23	38.64	48.81	74.00	-25.19	Peak
3 5531.59	90.57	32.11	9.07	38.61	93.14	74.00	19.14	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:f; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5723.54	65.54	32.15	9.00	38.75	67.94	74.00	-6.06	Peak
2 5725.00	64.63	32.15	9.00	38.75	67.03	74.00	-6.97	Peak
3 5744.44	98.83	32.15	9.00	38.76	101.22	74.00	27.22	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:f; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5722.40	42.17	32.15	9.00	38.75	44.57	54.00	-9.43	Average
2 5725.00	44.82	32.15	9.00	38.75	47.22	54.00	-6.78	Average
3 5744.06	88.78	32.15	9.00	38.76	91.17	54.00	37.17	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:f; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5722.78	63.36	32.15	9.00	38.75	65.76	74.00	-8.24	Peak
2 5725.00	59.73	32.15	9.00	38.75	62.13	74.00	-11.87	Peak
3 5746.72	95.99	32.15	9.00	38.76	98.38	74.00	24.38	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:f; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5555.36	33.05	32.11	9.07	38.62	35.61	54.00	-18.39	Average
2 5725.00	37.51	32.15	9.00	38.75	39.91	54.00	-14.09	Average
3 5746.34	85.55	32.15	9.00	38.76	87.94	54.00	33.94	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:f; Polarization:Horizontal; Modulation:a; bandwidth:20MHz; Channel:High

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5824.24	95.61	32.17	8.87	38.77	97.88	74.00	23.88	Peak
2 5850.00	49.37	32.17	8.90	38.75	51.69	74.00	-22.31	Peak
3 5860.88	48.08	32.17	8.90	38.74	50.41	74.00	-23.59	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:f; Polarization:Vertical; Modulation:a; bandwidth:20MHz; Channel:High

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5823.25	91.54	32.17	8.87	38.77	93.81	74.00	19.81	Peak
2 5850.00	49.28	32.17	8.90	38.75	51.60	74.00	-22.40	Peak
3 5857.70	47.95	32.17	8.90	38.74	50.28	74.00	-23.72	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:f; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5723.92	65.17	32.15	9.00	38.75	67.57	74.00	-6.43	Peak
2 5725.00	61.47	32.15	9.00	38.75	63.87	74.00	-10.13	Peak
3 5744.44	98.04	32.15	9.00	38.76	100.43	74.00	26.43	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:f; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5702.33	34.21	32.14	9.06	38.73	36.68	54.00	-17.32	Average
2 5725.00	46.04	32.15	9.00	38.75	48.44	54.00	-5.56	Average
3 5744.06	88.27	32.15	9.00	38.76	90.66	54.00	36.66	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:f; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low



Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5722.02	60.32	32.14	9.00	38.74	62.72	74.00	-11.28	Peak
2 5725.00	58.27	32.15	9.00	38.75	60.67	74.00	-13.33	Peak
3 5744.06	94.93	32.15	9.00	38.76	97.32	74.00	23.32	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:f; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:Low




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5555.73	33.10	32.11	9.07	38.62	35.66	54.00	-18.34	Average
2 5725.00	42.41	32.15	9.00	38.75	44.81	54.00	-9.19	Average
3 5744.06	85.28	32.15	9.00	38.76	87.67	54.00	33.67	Average

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor


Mode:f; Polarization:Horizontal; Modulation:n; bandwidth:20MHz; Channel:High

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5822.26	94.86	32.17	8.87	38.77	97.13	74.00	23.13	Peak
2 5850.00	49.99	32.17	8.90	38.75	52.31	74.00	-21.69	Peak
3 5866.05	45.56	32.17	8.90	38.74	47.89	74.00	-26.11	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:f; Polarization:Vertical; Modulation:n; bandwidth:20MHz; Channel:High

**Antenna Polarity :VERTICAL**

Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz								
1	5823.05	91.23	32.17	8.87	38.77	93.50	74.00	19.50 Peak
2	5850.00	46.67	32.17	8.90	38.75	48.99	74.00	-25.01 Peak
3	5858.69	46.62	32.17	8.90	38.74	48.95	74.00	-25.05 Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:f; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5722.57	64.39	32.15	9.00	38.75	66.79	74.00	-7.21	Peak
2 5725.00	62.30	32.15	9.00	38.75	64.70	74.00	-9.30	Peak
3 5753.38	93.26	32.15	8.93	38.76	95.58	74.00	21.58	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:f; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

Freq	Read	Antenna	Cable	Preamp	Emission	Limit	Over	Remark
	Level	Factor	Loss	Factor	Level	Line	Limit	
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5722.96	46.47	32.15	9.00	38.75	48.87	54.00	-5.13	Average
2 5725.00	46.68	32.15	9.00	38.75	49.08	54.00	-4.92	Average
3 5757.39	82.42	32.15	8.93	38.78	84.72	54.00	30.72	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:f; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5721.77	55.31	32.14	9.00	38.74	57.71	74.00	-16.29	Peak
2 5725.00	52.49	32.15	9.00	38.75	54.89	74.00	-19.11	Peak
3 5758.19	89.88	32.15	8.93	38.78	92.18	74.00	18.18	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:f; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:Low



Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5718.58	37.89	32.14	9.00	38.74	40.29	54.00	-13.71	Average
2 5725.00	39.99	32.15	9.00	38.75	42.39	54.00	-11.61	Average
3 5757.79	79.06	32.15	8.93	38.78	81.36	54.00	27.36	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:f; Polarization:Horizontal; Modulation:n; bandwidth:40MHz; Channel:High

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5798.22	89.49	32.16	8.87	38.80	91.72	74.00	17.72	Peak
2 5850.00	45.33	32.17	8.90	38.75	47.65	74.00	-26.35	Peak
3 5881.18	45.24	32.18	8.93	38.72	47.63	74.00	-26.37	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:f; Polarization:Vertical; Modulation:n; bandwidth:40MHz; Channel:High




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5793.25	87.34	32.16	8.87	38.80	89.57	74.00	15.57	Peak
2 5850.00	44.28	32.17	8.90	38.75	46.60	74.00	-27.40	Peak
3 5860.09	45.97	32.17	8.90	38.74	48.30	74.00	-25.70	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:f; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5714.82	51.63	32.14	9.00	38.74	54.03	74.00	-19.97	Peak
2 5725.00	58.01	32.15	9.00	38.75	60.41	74.00	-13.59	Peak
3 5743.68	97.24	32.15	9.00	38.76	99.63	74.00	25.63	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:f; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5702.71	33.28	32.14	9.06	38.73	35.75	54.00	-18.25	Average
2 5725.00	39.01	32.15	9.00	38.75	41.41	54.00	-12.59	Average
3 5743.68	83.47	32.15	9.00	38.76	85.86	54.00	31.86	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:f; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5722.02	54.30	32.14	9.00	38.74	56.70	74.00	-17.30	Peak
2 5725.00	54.12	32.15	9.00	38.75	56.52	74.00	-17.48	Peak
3 5744.44	94.22	32.15	9.00	38.76	96.61	74.00	22.61	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:f; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5555.36	32.81	32.11	9.07	38.62	35.37	54.00	-18.63	Average
2 5725.00	35.18	32.15	9.00	38.75	37.58	54.00	-16.42	Average
3 5744.06	79.87	32.15	9.00	38.76	82.26	54.00	28.26	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:f; Polarization:Horizontal; Modulation:c; bandwidth:20MHz; Channel:High




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5823.64	94.98	32.17	8.87	38.77	97.25	74.00	23.25	Peak
2 5850.00	49.08	32.17	8.90	38.75	51.40	74.00	-22.60	Peak
3 5852.14	49.99	32.17	8.90	38.75	52.31	74.00	-21.69	Peak

Note: Emission Level = Read Level + Antenna Factor + Cable loss - Preamp Factor

Mode:f; Polarization:Vertical; Modulation:c; bandwidth:20MHz; Channel:High




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5821.47	89.87	32.16	8.87	38.78	92.12	74.00	18.12	Peak
2 5850.00	45.05	32.17	8.90	38.75	47.37	74.00	-26.63	Peak
3 5856.11	46.71	32.17	8.90	38.74	49.04	74.00	-24.96	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:f; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:Low



Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
1 5717.78	65.54	32.14	9.00	38.74	67.94	74.00	-6.06	Peak
2 5725.00	62.07	32.15	9.00	38.75	64.47	74.00	-9.53	Peak
3 5760.60	93.48	32.15	8.93	38.78	95.78	74.00	21.78	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:f; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5717.38	41.79	32.14	9.00	38.74	44.19	54.00	-9.81	Average
2 5725.00	41.23	32.15	9.00	38.75	43.63	54.00	-10.37	Average
3 5757.79	77.32	32.15	8.93	38.78	79.62	54.00	25.62	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:f; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5718.18	61.27	32.14	9.00	38.74	63.67	74.00	-10.33	Peak
2 5725.00	55.93	32.15	9.00	38.75	58.33	74.00	-15.67	Peak
3 5758.59	89.94	32.15	8.93	38.78	92.24	74.00	18.24	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:f; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:Low




Antenna Polarity :VERTICAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5717.38	36.25	32.14	9.00	38.74	38.65	54.00	-15.35	Average
2 5725.00	36.20	32.15	9.00	38.75	38.60	54.00	-15.40	Average
3 5757.79	73.93	32.15	8.93	38.78	76.23	54.00	22.23	Average

Note: Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor


Mode:f; Polarization:Horizontal; Modulation:c; bandwidth:40MHz; Channel:High

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5800.35	90.40	32.16	8.87	38.80	92.63	74.00	18.63	Peak
2 5850.05	43.39	32.17	8.90	38.75	45.71	74.00	-28.29	Peak
3 5857.70	46.59	32.17	8.90	38.74	48.92	74.00	-25.08	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:f; Polarization:Vertical; Modulation:c; bandwidth:40MHz; Channel:High

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5800.35	88.44	32.16	8.87	38.80	90.67	74.00	16.67	Peak
2 5850.00	42.92	32.17	8.90	38.75	45.24	74.00	-28.76	Peak
3 5886.94	44.89	32.18	8.93	38.72	47.28	74.00	-26.72	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:f; Polarization:Horizontal; Modulation:c; bandwidth:80MHz; Channel:Low

**Antenna Polarity :HORIZONTAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5720.27	58.07	32.14	9.00	38.74	60.47	74.00	-13.53	Peak
2 5725.00	54.22	32.15	9.00	38.75	56.62	74.00	-17.38	Peak
3 5763.85	88.54	32.15	8.93	38.78	90.84	74.00	16.84	Peak
4 5850.00	47.68	32.17	8.90	38.75	50.00	74.00	-24.00	Peak
5 5857.25	46.62	32.17	8.90	38.74	48.95	74.00	-25.05	Peak

Note: Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor

Mode:f; Polarization:Horizontal; Modulation:c; bandwidth:80MHz; Channel:Low




Antenna Polarity :HORIZONTAL

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5721.06	40.79	32.14	9.00	38.74	43.19	54.00	-10.81	Average
2 5725.00	38.58	32.15	9.00	38.75	40.98	54.00	-13.02	Average
3 5762.26	71.04	32.15	8.93	38.78	73.34	54.00	19.34	Average
4 5850.00	33.47	32.17	8.90	38.75	35.79	54.00	-18.21	Average
5 5858.87	33.08	32.17	8.90	38.74	35.41	54.00	-18.59	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


Mode:f; Polarization:Vertical; Modulation:c; bandwidth:80MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5720.27	54.62	32.14	9.00	38.74	57.02	74.00	-16.98	Peak
2 5725.00	49.34	32.15	9.00	38.75	51.74	74.00	-22.26	Peak
3 5763.06	85.21	32.15	8.93	38.78	87.51	74.00	13.51	Peak
4 5850.00	45.00	32.17	8.90	38.75	47.32	74.00	-26.68	Peak
5 5909.62	45.32	32.18	8.96	38.69	47.77	74.00	-26.23	Peak

Note:Emission Level=Read Level+Antenna Factor+Cable loss+Preamp Factor

Mode:f; Polarization:Vertical; Modulation:c; bandwidth:80MHz; Channel:Low

**Antenna Polarity :VERTICAL**

Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Emission Level	Limit Line	Over Limit	Remark
MHz	dBuv	dB/m	dB	dB	dBuv/m	dBuv/m	dB	
1 5717.51	37.87	32.14	9.00	38.74	40.27	54.00	-13.73	Average
2 5725.00	35.93	32.15	9.00	38.75	38.33	54.00	-15.67	Average
3 5766.24	68.44	32.15	8.93	38.78	70.74	54.00	16.74	Average
4 5850.00	32.89	32.17	8.90	38.75	35.21	54.00	-18.79	Average
5 5887.64	32.92	32.18	8.93	38.72	35.31	54.00	-18.69	Average

Note:Emission Level=Read Level+Antenna Factor+Cable loss-Preamp Factor


## 7.10 Frequency Stability

Test Requirement	47 CFR Part 15, Subpart C 15.407 (g)
Test Method:	ANSI C63.10 (2013) Section 6.8
Limit:	The frequency tolerance shall be maintained within the band of operation frequency over a temperature variation of -20 degrees to 55 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

### 7.10.1 E.U.T. Operation

#### Operating Environment:

Temperature:	22 °C	Humidity:	50 % RH	Atmospheric Pressure:	1001 mbar
Pretest these mode to find the worst case:	c:TX mode (Band 1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.				
	d:TX mode (Band 2A)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.				
	e:TX mode (Band 2C)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.				
	f:TX mode (Band 3)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80). Only the data of worst case is recorded in the report.				

**7.10.2 Test Setup Diagram****7.10.3 Measurement Procedure and Data**

The detailed test data see: Appendix C for SHEMA180200141603

## 8 Test Setup Photographs

Refer to the < Test Setup photos-FCC>.

## 9 EUT Constructional Details

Refer to the < External Photos > & < Internal Photos >.

**- End of the Report -**