




Engineering Test Report No. 2402627-03	
Report Date	April 30, 2025
Manufacturer Name	Chamberlain Group LLC
Manufacturer Address	300 Windsor Dr Oak Brook, IL 60523
Product Name Brand/Model No.	Universal Remote
Date Received	March 17, 2025
Assessment Date	April 1, 2025
Specifications	FCC 47 CFR Part 2.1093 KDB, 447498 D01 OET Bulletin 65:1997 RSS-102 Issue 6
Test Facility	Elite Electronic Engineering, Inc. 1516 Centre Circle, Downers Grove, IL 60515
Signature	
Tested by	Edwin Casas
Signature	
Approved by	Raymond J. Klouda, Registered Professional Engineer of Illinois – 44894
PO Number	4900099236
This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. This report shall not be reproduced, except in full, without the written approval of Elite Electronic Engineering Inc.	

Table of Contents

1.	Report Revision History	3
2.	Introduction	4
3.	Subject of Investigation	4
4.	Standards and Requirements	4
5.	Sample Calculations	4
6.	Photographs of EUT	6
7.	Limits and Requirements	7
7.1.	Requirements mandated by the FCC	7
7.2.	Requirements mandated by Innovation, Science and Economic Development Canada	9
8.	Assessment Results	10
8.1.	RF Exposure Evaluation Pertinent to the Requirements of the FCC for Standalone Source(s)	10
8.2.	RF Exposure Evaluation Relevant to the Requirements of the ISED for Standalone Sources	11
9.	Statement of Compliance	13
10.	Certification	13

**This report shall not be reproduced, except in full,
without the written approval of Elite Electronic Engineering Inc.**

1. Report Revision History

Revision	Date	Description
–	5 MAY 2025	Initial Release of Engineering Test Report No. 2402627-03

2. Introduction

The FCC & Innovation, Science and Economic Development Canada publish standards regarding the evaluation of the RF Exposure hazard of radio communications devices. An evaluation has been performed on the Chamberlain Group LLC Universal Remote, Model No. 900-16329-1/014D16329 Rev C pursuant to the relevant requirements.

3. Subject of Investigation

This document presents the demonstration of RF Exposure compliance on a Universal Remote, (hereinafter referred to as the Equipment under Test (EUT)). The EUT was identified as follows:

EUT Identification	
Description	Universal Remote
Model/Part No.	900-16329-1/014D16329 Rev C
S/N	Sample U1 & Sample U3
Radio Access Technology	BLE, OOK
Bands of Operation	2400-2483.5MHz BLE 315MHz D Code 390MHz D Code 315MHz E Code 390MHz E Code 315MHz Genie Code 390MHz Genie Code 390MHz Billion A Code 318MHz Linear Mega Code 310MHz Stanley Code 372.5MhzWayne-Dalton Code 303MHz Guardian Code 310MHz Sommer Code 372.5MHz Ryobi Code

4. Standards and Requirements

The tests were performed to selected portions of, and in accordance with the following specifications.

- 47 CFR Parts 1.1310, 2.1091 and 2.1093 Code of Federal Regulations, Title 47, Telecommunications
- KDB 447498 D01 – “RF Exposure Procedures and Equipment Authorization Policies for Mobile and Portable Devices, General RF Exposure Guidance v06”
- OET Bulletin 65 Edition 97-01:1997 – “Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields”
- ANSI/IEEE C95.1:1992 – "Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz,"
- RSS-102, Issue 6 Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)

5. Sample Calculations

The far field power density can be calculated using the following formula:

$$S = \frac{PG}{4\pi R^2} \quad (1)$$

where P is the transmit output power (mW), G is the maximum antenna gain relative to an isotropic antenna (linear) and R is the evaluation distance (cm).

In cases where multiple antennas are utilized for a single signal, the following formula is applied to calculate the maximum antenna gain:

$$Gain (dBi) = G + 10 \log N \quad (2)$$

where N is the number of antennas, G is the gain of a single antenna.

A minimum separation distance can be calculated using the following formulas

$$Minimum Separation Distance = \sqrt{\frac{PG}{4\pi(Power Density Limit)}} \quad (3)$$

where P is the transmitted output power (mW) and G is the maximum antenna gain relative to an isotropic antenna (linear).

For sources with frequencies <30MHz

$$Seperation Distance = R \left(10^{\frac{(FS_{Limit}-FS_R)}{40}} \right)^{-1} \quad (4)$$

For sources with frequencies >30MHz

$$Seperation Distance = R \left(10^{\frac{(FS_{Limit}-FS_R)}{20}} \right)^{-1} \quad (5)$$

where R is the measurement distance, FS_{Limit} is the field strength limit and FS_R is the measured field strength at distance R.

6. Photographs of EUT



7. Limits and Requirements

7.1. Requirements mandated by the FCC

Equipment pursuing compliance with the requirements with respect to the limits of human exposure to RF provided in FCC 1.1310, need follow the criteria in FCC 1.1307(b)(1).

Equipment exemption qualification must be demonstrated pursuant to FCC 1.1307(b)(3).

For single RF sources (i.e., any single portable device, mobile device or fixed RF source), the EUT is exempt if:

- FCC 1.1307(b)(3)(i)(A) - The available maximum time-averaged power is no more than 1 mW, regardless of separation distance.
- FCC 1.1307(b)(3)(i)(B) - The available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW). This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive).
- FCC 1.1307(b)(3)(i)(C) – The available maximum ERP (watts) shall not exceed the calculated ERP_{th} (watts) in this section. For the exemption to apply, the separation distance, R (meters), must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

For multiple RF sources (i.e., any single portable device, mobile device or fixed RF source), the EUT is exempt if:

- FCC 1.1307(b)(3)(ii)(A) The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required).
- FCC 1.1307(b)(3)(ii)(B) in the case of fixed RF sources operating at the same time-averaging period, or of multiple mobile or portable RF sources within a device operating at the same time averaging period if the sum of the fractional contributions to the applicable thresholds is less than or equal to 1.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

If it is determined that the equipment under investigation is not exempt from routine evaluation an assessment must be performed to determine compliance in regard to the RF exposure limits by means of measurement or calculation of the electric field, magnetic field, power density or SAR.

It may be the case that a minimum separation distance will need to be calculated or measured and maintained from the source of RF to meet radiofrequency radiation exposure restrictions.

Per 1.1310(e)(1), the power density shall not exceed the levels below:

Specific Absorption Rate (SAR) - SAR Limits for Occupational/Controlled Exposure			
Frequency Range (MHz)	Whole Body SAR Limit (W/kg)	Peak Spatial AVG SAR Limit (W/kg)	Peak Spatial Extremities SAR Limit 10g (W/kg)
0.1 - 6000	0.4	8	20
Specific Absorption Rate (SAR) - SAR Limits for General/Uncontrolled Exposure			
Frequency Range (MHz)	Whole Body SAR Limit (W/kg)	Peak Spatial AVG SAR Limit 1g (W/kg)	Peak Spatial Extremities SAR Limit 10g (W/kg)
0.1 - 6000	0.08	1.6	4

Limits for Maximum Permissible Exposure (MPE) - Limits for Occupational/Controlled Exposure			
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)
0.3 - 3.0	614	1.63	*100
3.0 - 30	1842 / f	4.89 / f	*900 / f ²
30 - 300	61.4	0.163	1.0
300 - 1,500	—	—	f / 300
1,500 - 100,000	—	—	5
Limits for Maximum Permissible Exposure (MPE) - Limits for General/Uncontrolled Exposure			
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)
0.3 - 1.34	614	1.63	*100
1.34 - 30	842 / f	2.19 / f	*180 / f ²
30 - 300	27.5	0.073	0.2
300 - 1,500	—	—	f / 1500
1,500 - 100,000	—	—	1.0
f – Frequency in MHz			
* – Plane wave Equivalent Power Density			

7.2. Requirements mandated by Innovation, Science and Economic Development Canada

Equipment exemption qualification must be demonstrated pursuant to RSS-102 Issue 6 section 6. If it is determined that the equipment under investigation is not exempt, it must be demonstrated that the equipment does not exceed the exposure limits in section 5 of RSS-102 Issue 6 or a minimum separation distance must be calculated to ensure that the exposure limits are met.

Per RSS 102 Section 5, the equipment shall not exceed the levels below:

Specific Absorption Rate (SAR) - SAR Limits for Occupational/Controlled Exposure			
Frequency Range (MHz)	Whole Body SAR Limit (W/kg)	Peak Spatial AVG SAR Limit (W/kg)	Peak Spatial Extremities SAR Limit 10g (W/kg)
0.1 - 6000	0.4	8	20
Specific Absorption Rate (SAR) - SAR Limits for General/Uncontrolled Exposure			
Frequency Range (MHz)	Whole Body SAR Limit (W/kg)	Peak Spatial AVG SAR Limit 1g (W/kg)	Peak Spatial Extremities SAR Limit 10g (W/kg)
0.1 - 6000	0.08	1.6	4

Limits for Occupational/Controlled Exposure			
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (W/m ²)
0.003 – 10*	170	180	—
0.1 – 10*	—	1.6 / f	—
1.29 – 10*	193 / f ^{0.5}	—	—
10 – 20	61.4	0.163	10
20 – 48	129.8 / f ^{0.25}	0.3444 / f ^{0.25}	44.72 / f ^{0.5}
48 – 100	49.33	0.1309	6.455
100 – 6000	15.60 f ^{0.25}	0.04138 f ^{0.25}	0.6455 f ^{0.5}
6000 – 15000	137	0.364	50
15000 – 150000	137	0.364	50
150000 – 300000	0.354 f ^{0.5}	9.40x10 ⁻⁴ f ^{0.5}	3.33x10 ⁻⁴ f
Limits for General/Uncontrolled Exposure			
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (W/m ²)
0.003 – 10*	83	90	—
0.1 – 10*	—	0.73 / f	—
1.1 – 10*	87 / f ^{0.5}	—	—
10 – 20	27.46	0.0728	2
20 – 48	58.07 / f ^{0.25}	0.1540 / f ^{0.25}	8.944 / f ^{0.5}
48 – 300	22.06	0.05852	1.291
300 – 6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}
6000 – 15000	61.4	0.163	10
15000 – 150000	61.4	0.163	10
150000 – 300000	0.158 f ^{0.5}	4.21x10 ⁻⁴ f ^{0.5}	6.67x10 ⁻⁵ f
f – Frequency in MHz			
*Limits only apply to Specific Absorption Rate and Nerve Stimulation requirements.			

8. Assessment Results

The following evaluations were performed at a separation distance of 0.6cm. The separation distance was measured based on the minimum use case separation between the radiating element of the RF source and the end user.

8.1. RF Exposure Evaluation Pertinent to the Requirements of the FCC for Standalone Source(s)

The table below contains the highest measured, calculated or reported field strengths and output power for each RF source.

Radio Access Technology	f Transmit Frequency (MHz)	Electric Field Strength (V/m)	ERP (mW)	EIRP (mW)	Duty Cycle
BLE	2402	---	1.77827941	2.91742701	0.34
OOK D Code	390	0.60113222	0.00026431	0.00043363	0.225
OOK D Code	315	1.40919147	0.00145252	0.00238298	0.22
OOK E Code	315	0.98621137	0.00071141	0.00116714	0.155
OOK E Code	390	0.86890041	0.00055223	0.00090599	0.155
Genie	315	1.00918318	0.00074494	0.00122214	0.234
Genie	390	0.59425111	0.0002583	0.00042376	0.222
Billion A	390	0.56100923	0.00023021	0.00037768	0.21
Linear Mega	318	1.08135926	0.00085531	0.00140321	0.17
Sommer	310	0.74811783	0.00040937	0.00067162	0.118
Stanley	310	1.49269131	0.00162975	0.00267375	0.234
Wayne-Dalton	372.5	0.608093	0.00027047	0.00044373	0.236
Guardian	303	0.88913971	0.00057826	0.00094868	0.455
Ryobi	372.5	0.63675154	0.00029657	0.00048654	0.234

The output power levels listed above were used to complete an exemption assessment. The results are as follows:

Radio Access Technology	f Transmit Frequency (MHz)	ERP (mW)	ERP (W)	Pth (mW)	Exemption Rule	Exemption Results
BLE	2402	1.77827941	0.00177828	3.9401779	FCC 1.1307(b)(3)(i)(B)	Exempt
OOK D Code	390	0.00026431	2.6431E-07	31.8109479	FCC 1.1307(b)(3)(i)(B)	Exempt
OOK D Code	315	0.00145252	1.4525E-06	41.8506609	FCC 1.1307(b)(3)(i)(B)	Exempt
OOK E Code	315	0.00071141	7.1141E-07	41.8506609	FCC 1.1307(b)(3)(i)(B)	Exempt
OOK E Code	390	0.00055223	5.5223E-07	31.8109479	FCC 1.1307(b)(3)(i)(B)	Exempt
Genie	315	0.00074494	7.4494E-07	41.8506609	FCC 1.1307(b)(3)(i)(B)	Exempt
Genie	390	0.0002583	2.583E-07	31.8109479	FCC 1.1307(b)(3)(i)(B)	Exempt
Billion A	390	0.00023021	2.3021E-07	31.8109479	FCC 1.1307(b)(3)(i)(B)	Exempt
Linear Mega	318	0.00085531	8.5531E-07	41.3442712	FCC 1.1307(b)(3)(i)(B)	Exempt
Sommer	310	0.00040937	4.0937E-07	42.7195695	FCC 1.1307(b)(3)(i)(B)	Exempt
Stanley	310	0.00162975	1.6298E-06	42.7195695	FCC 1.1307(b)(3)(i)(B)	Exempt
Wayne-Dalton	372.5	0.00027047	2.7047E-07	33.7430059	FCC 1.1307(b)(3)(i)(B)	Exempt
Guardian	303	0.00057826	5.7826E-07	43.9912298	FCC 1.1307(b)(3)(i)(B)	Exempt
Ryobi	372.5	0.00029657	2.9657E-07	33.7430059	FCC 1.1307(b)(3)(i)(B)	Exempt

It was determined that the EUT is exempt from routine evaluation per FCC 1.1307(b)(3)(i)(B).

8.2. RF Exposure Evaluation Relevant to the Requirements of the ISED for Standalone Sources

The following evaluation(s) was performed at a separation distance of 0.6cm. The separation distance was measured based on the minimum use case separation between the radiating element of the RF source and the end user.

The table below contains the highest measured, calculated or reported field strengths and output power for each RF source.

Radio Access Technology	f Transmit Frequency (MHz)	Electric Field Strength (V/m)	EIRP (W)	Duty Cycle
BLE	2402	---	0.00291743	0.34
OOK D Code	390	0.60113222	4.3363E-07	0.225
OOK D Code	315	1.40919147	2.383E-06	0.22
OOK E Code	315	0.98621137	1.1671E-06	0.155
OOK E Code	390	0.86890041	9.0599E-07	0.155
Genie	315	1.00918318	1.2221E-06	0.234
Genie	390	0.59425111	4.2376E-07	0.222
Billion A	390	0.56100923	3.7768E-07	0.21
Linear Mega	318	1.08135926	1.4032E-06	0.17
Sommer	310	0.74811783	6.7162E-07	0.118
Stanley	310	1.49269131	2.6738E-06	0.234
Wayne-Dalton	372.5	0.608093	4.4373E-07	0.236
Guardian	303	0.88913971	9.4868E-07	0.455
Ryobi	372.5	0.63675154	4.8654E-07	0.234

The output power levels listed above were used to complete an exemption assessment. The results are as follows:

Radio Access Technology	f Transmit Frequency (MHz)	Nerve Stimulation ¹	SAR ²	Localized APD ³	Localized IPD ⁴	FRL ⁵
BLE	2402	NA	Exempt	NA	NA	NA
OOK D Code	390	NA	Exempt	NA	NA	NA
OOK D Code	315	NA	Exempt	NA	NA	NA
OOK E Code	315	NA	Exempt	NA	NA	NA
OOK E Code	390	NA	Exempt	NA	NA	NA
Genie	315	NA	Exempt	NA	NA	NA
Genie	390	NA	Exempt	NA	NA	NA
Billion A	390	NA	Exempt	NA	NA	NA
Linear Mega	318	NA	Exempt	NA	NA	NA
Sommer	310	NA	Exempt	NA	NA	NA
Stanley	310	NA	Exempt	NA	NA	NA
Wayne-Dalton	372.5	NA	Exempt	NA	NA	NA
Guardian	303	NA	Exempt	NA	NA	NA
Ryobi	372.5	NA	Exempt	NA	NA	NA

¹Only applicable to inductive systems operating in the 3kHz to 10MHz range with loop outer dimensions less than or equal to 100mm and separation distances greater than and equal to 0.15mm and separation distance less than or equal to 50mm.

²Only applicable to sources operating in the 100kHz to 6GHz range if the separation between the user or bystander is less than and equal to 20cm.

³Only applicable to sources operating in the 7GHz to 30GHz range if the separation between the user or bystander is less than and equal to 20cm.

⁴Only applicable to sources operating in the 6GHz to 30GHz range.

⁵Only applicable to sources operating at or below 6GHz if the separation between the user or bystander is greater than 20cm.

9. Statement of Compliance

The Chamberlain Group LLC Universal Remote, Model 900-16329-1/014D16329 Rev C is in compliance with the FCC and Innovation, Science and Economic Development Canada requirements for RF Exposure at a minimum separation distance of 0.6cm.

10. Certification

Elite Electronic Engineering Incorporated certifies that the information contained in this report was obtained under conditions which meet or exceed those specified in the FCC and Innovation, Science and Economic Development Canada requirements for RF Exposure test specifications. The data presented in this test report pertains to the EUT as provided by the customer on the test date specified. Any electrical or mechanical modifications made to the EUT subsequent to the specified test date will serve to invalidate the data and void this certification.