



**Solutions**

## **RF EXPOSURE REPORT**

**Report Number. : R15165141-E2**

**Applicant :** The Chamberlain Group, Inc.  
300 Windsor Dr  
Oak Brook, IL, 60523

**Model :** E943LA

**FCC ID :** HBW9835-4

**EUT Description :** Remote-Control Transmitter

**Test Standard(s) :** FCC 47 CFR PART 1 Subpart I  
FCC 47 CFR PART 2 Subpart J

**Date Of Issue:**  
2024-08-23

**Prepared by:**  
UL LLC  
12 Laboratory Dr.  
Research Triangle Park, NC 27709 U.S.A.  
TEL: (919) 549-1400



Revision History

Rev.	Issue Date	Revisions	Revised By
V1	2024-06-03	Initial Issue	Noah Bennett
V2	2024-06-25	Updated Exclusion calculation.	Noah Bennett
V3	2024-08-23	Updated Max E-Field	Noah Bennett

## TABLE OF CONTENTS

<b>1. ATTESTATION OF TEST RESULTS.....</b>	<b>4</b>
<b>2. TEST METHODOLOGY .....</b>	<b>5</b>
<b>3. REFERENCES.....</b>	<b>5</b>
<b>4. FACILITIES AND ACCREDITATION.....</b>	<b>5</b>
<b>5. DECISION RULES AND MEASUREMENT UNCERTAINTY .....</b>	<b>5</b>
5.1. <i>METROLOGICAL TRACEABILITY.....</i>	<i>5</i>
5.2. <i>DECISION RULES.....</i>	<i>5</i>
<b>6. MAXIMUM PERMISSIBLE EXPOSURE (LIMITS AND EQUATIONS).....</b>	<b>6</b>
6.1. <i>FCC RULES.....</i>	<i>6</i>
6.2. <i>EQUATIONS.....</i>	<i>7</i>
<b>7. FCC PORTABLE DEVICE TEST EXCLUSION CONSIDERATIONS .....</b>	<b>9</b>
7.1. <i>Stand-alone test exclusion KDB 447498 D01 v6. ....</i>	<i>9</i>

## 1. ATTESTATION OF TEST RESULTS

**COMPANY NAME:** The Chamberlain Group, Inc.  
300 Windsor Dr  
Oak Brook, IL, 60523

**EUT DESCRIPTION:** Remote-Control Transmitter

**MODEL:** E943LA

**SERIAL NUMBER:** 132C2708-15

**SAMPLE RECEIPT DATE:** 2024-03-21; 2024-05-20

**DATE TESTED:** 2024-05-13 Thru 2024-05-21

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	Complies

UL LLC tested the above equipment in accordance with the requirements set forth in the above standards. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. All samples tested were in good operating condition throughout the entire test program. Measurement Uncertainties are published for informational purposes only and were not taken into account unless noted otherwise.

This document may not be altered or revised in any way unless done so by UL LLC and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL LLC will constitute fraud and shall nullify the document.

Approved & Released  
For UL LLC By:



Mike Antola  
Staff Engineer  
Consumer Technology Division  
UL LLC

Prepared By:



Noah Bennett  
Engineering Project Associate  
Consumer Technology Division  
UL LLC

## 2. TEST METHODOLOGY

All calculations were made in accordance with FCC Parts 1.1310, 2.1091, 2.1093, KDB 447498 D01 v06, KDB 447498 D03 V01, IEEE Std C95.1-2005, and IEEE Std C95.3-2002.

## 3. REFERENCES

Output power is excerpted from client declarations.

100% Duty Cycle and 0dB Antenna Gain was used as worst case.

## 4. FACILITIES AND ACCREDITATION

UL LLC is accredited by A2LA, certification # 0751.06, for all testing performed within the scope of this report. Testing was performed at the locations noted below.

	Address	ISED CABID	ISED Company Number	FCC Registration
<input type="checkbox"/>	Building: 12 Laboratory Dr RTP, NC 27709, U.S.A	US0067	2180C	825374
<input checked="" type="checkbox"/>	Building: 2800 Perimeter Park Dr. Suite B Morrisville, NC 27560, U.S.A		27265	

## 5. DECISION RULES AND MEASUREMENT UNCERTAINTY

### 5.1. METROLOGICAL TRACEABILITY

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

### 5.2. DECISION RULES

For all tests where the applicable  $U_{LAB} \leq U_{MAX}$  the Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2, where  $U_{MAX} = 30\% (0.3)$  for RF Exposure evaluations. (Measurement uncertainty is not taken into account when stating conformity with a specified requirement.)

For all tests where the applicable  $U_{LAB} > U_{MAX}$  the Decision Rule is based on Guarded Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.3.2, with a guard band equal to  $(U_{LAB} - U_{MAX})$ , where  $U_{MAX} = 30\% (0.3)$  for RF Exposure evaluations. (Test results are adjusted by the value of the guard band to determine conformity with a specified requirement.)

## 6. MAXIMUM PERMISSIBLE EXPOSURE (LIMITS AND EQUATIONS)

### 6.1. FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

#### Notes:

- (1) Occupational/controlled exposure limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when a person is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.
- (2) General population/uncontrolled exposure limits apply in situations in which the general public may be exposed, or in which persons who are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure

## 6.2. EQUATIONS

### POWER DENSITY

Power density is given by:

$$S = \text{EIRP} / (4 * \pi * D^2)$$

Where

S = Power density in mW/cm<sup>2</sup>

EIRP = Equivalent Isotropic Radiated Power in mW

D = Separation distance in cm

Power density in units of mW/cm<sup>2</sup> is converted to units of W/m<sup>2</sup> by multiplying by 10.

### DISTANCE

Distance is given by:

$$D = \sqrt{(\text{EIRP} / (4 * \pi * S))}$$

Where

D = Separation distance in cm

EIRP = Equivalent Isotropic Radiated Power in mW

S = Power density in mW/cm<sup>2</sup>

### SOURCE-BASED DUTY CYCLE

Where applicable (for example, multi-slot cell phone applications) a duty cycle factor may be applied.

$$\text{Source-based time-averaged EIRP} = (\text{DC} / 100) * \text{EIRP}$$

Where

DC = Duty Cycle in %, as applicable

EIRP = Equivalent Isotropic Radiated Power in mW

### DISTANCE CORRECTION

Distance correction factor to scale E-field reading from x meters to y meters is as follows:

$$\text{Correction Factor} = 20 \log(x/y)$$

Where x is the initial measurement distance and y is the desired distance.

### **MAXIMUM E-FIELD STRENGTH (dBuV/m to V/m)**

To convert from dBuV/m to V/m, the following equation was used:

$$V/m = 10^{[(dBuV/m - 120) / 20]}$$

### **MIMO AND COLOCATED TRANSMITTERS (IDENTICAL LIMIT FOR ALL TRANSMITTERS)**

For multiple chain devices, and colocated transmitters operating simultaneously in frequency bands where the limit is identical, the total power density is calculated using the total EIRP obtained by summing the EIRP (in linear units) of each transmitter.

$$\text{Total EIRP} = (\text{EIRP}_1) + (\text{EIRP}_2) + \dots + (\text{EIRP}_n)$$

where

$\text{EIRP}_x$  = Source-based time-averaged EIRP of chain x or transmitter x

The total EIRP is then used to calculate the Power Density or the Distance as applicable.

### **MIMO AND COLOCATED TRANSMITTERS (NON-IDENTICAL LIMIT FOR ALL TRANSMITTERS)**

For multiple colocated transmitters operating simultaneously in frequency bands where different limits apply:

The Power Density at the specified separation distance is calculated for each transmitter chain or transmitter.

The fraction of the exposure limit is calculated for each chain or transmitter as  $(\text{Power Density of chain or transmitter}) / (\text{Limit applicable to that chain or transmitter})$ .

The fractions are summed.

Compliance is established if the sum of the fractions is less than or equal to one.

## 7. FCC PORTABLE DEVICE TEST EXCLUSION CONSIDERATIONS

### 7.1. Stand-alone test exclusion KDB 447498 D01 v6.

a) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [f(\text{GHz})] \leq 3.0$ , for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

SAR Exclusion Calculations Table for Portable Devices (separation distance  $\leq 50$  mm)

Antenna	Frequency (MHz)	Maximum E-Field Strength at 3m		Maximum Output Power		Separation Distances (mm)	Calculated Threshold Value
		dBuV/m	V/m	dBm	mW		
Standard LA Visor	433	72.77	0.0044	-22.49	0.00564	5	0.0

Conclusion:

The computed value is  $\leq 3$ ; therefore, EUT qualifies for Standalone 1-gm body SAR test exclusion.

Note: Conversion of  $X \text{ dBm} = Y \text{ dBuV/m} + 20\log(D) - 104.8$  where  $X$  is the transmitter power in dBm,  $Y$  is the Max E-Field strength at 3m in dBuV/m, and  $D$  is the measurement distance in meters.

$$X \text{ dBm} = 72.77 \text{ dBuV} + 20\log(3) - 104.8$$

$$X \text{ dBm} = -22.49$$