

FCC SAR Test Report

APPLICANT : Honeywell International Inc
EQUIPMENT : mobile computer
BRAND NAME : Honeywell
MODEL NAME : CT37X0N
FCC ID : HD5-CT37X0N
STANDARD : FCC 47 CFR Part 2 (2.1093)

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures given in 47 CFR Part 2.1093 and FCC KDB and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.



Approved by: Si Zhang



Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



Table of Contents

1. Statement of Compliance	4
2. Administration Data	5
3. Guidance Applied	5
4. Equipment Under Test (EUT) Information	6
4.1 General Information	6
5. RF Exposure Limits	7
5.1 Uncontrolled Environment	7
5.2 Controlled Environment	7
6. Specific Absorption Rate (SAR)	8
6.1 Introduction	8
6.2 SAR Definition	8
7. System Description and Setup	9
7.1 E-Field Probe	10
7.2 Data Acquisition Electronics (DAE)	10
7.3 Phantom	11
7.4 Device Holder	12
8. Measurement Procedures	13
8.1 Spatial Peak SAR Evaluation	13
8.2 Power Reference Measurement	14
8.3 Area Scan	14
8.4 Zoom Scan	15
8.5 Volume Scan Procedures	15
8.6 Power Drift Monitoring	15
9. Test Equipment List	16
10. System Verification	17
10.1 Tissue Simulating Liquids	17
10.2 Tissue Verification	17
10.3 System Performance Check Results	18
11. RF Exposure Positions	19
11.1 Ear and handset reference point	19
11.2 Definition of the cheek position	20
11.3 Definition of the tilt position	21
11.4 Body Worn Accessory	22
11.5 Product Specific 10g SAR Exposure	23
11.6 Wireless Router	23
12. Conducted RF Output Power (Unit: dBm)	24
13. Antenna Location	26
14. SAR Test Results	27
14.1 Head SAR	29
14.2 Hotspot SAR	30
14.3 Body Worn Accessory SAR	31
14.4 Product Specific SAR	32
14.5 Repeated SAR Measurement	33
15. Simultaneous Transmission Analysis	34
15.1 Head Exposure Conditions	35
15.2 Hotspot Exposure Conditions	35
15.3 Body-Worn Accessory Exposure Conditions	36
15.4 Product Specific Exposure Conditions	36
16. Uncertainty Assessment	37
17. References	38
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	
Appendix E. Conducted RF Output Power Table	
Appendix F. Power reduction mechanism verification	

Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA461913	Rev. 01	Initial issue of report.	Jul. 26, 2024

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Honeywell International Inc, mobile computer, CT37X0N**, are as follows.

Highest 1g SAR Summary						
Equipment Class	Frequency Band		Head (Separation 0mm)	Hotspot (Separation 10mm)	Body-worn (Separation 10mm)	Highest Simultaneous Transmission 1g SAR (W/kg)
			1g SAR (W/kg)			
DTS	WLAN	2.4GHz WLAN	1.33	1.12	1.13	1.54
NII		5GHz WLAN	1.14	1.08	1.08	1.54
DSS	Bluetooth	2.4GHz Bluetooth	0.11	<0.10	<0.10	1.32
Highest 10g SAR Summary						
Equipment Class	Frequency Band		Product Specific 10g SAR (W/kg) (Separation 0mm)			Highest Simultaneous Transmission 10g SAR (W/kg)
NII	WLAN	5GHz WLAN	1.46			1.46
Date of Testing:			2024/7/15 ~ 2024/7/26			

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR, 4.0 W/kg for Product Specific 10g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

2. Administration Data

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Testing Laboratory			
Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR05-KS, SAR06-KS	CN1257	314309

Applicant	
Company Name	Honeywell International Inc
Address	9680 Old Bailes Rd, Fort Mill, SC 29707

Manufacturer	
Company Name	Honeywell International Inc
Address	9680 Old Bailes Rd, Fort Mill, SC 29707

3. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01
- FCC KDB 616217 D04 SAR for laptop and tablets v01r02

4. Equipment Under Test (EUT) Information

4.1 General Information

Product Feature & Specification	
Equipment Name	mobile computer
Brand Name	Honeywell
Model Name	CT37X0N
FCC ID	HD5-CT37X0N
SN Code	Sample 1: 2417300138 Sample 2: 241730003C Sample 3: 24173002B2 Sample 5: 241730023A
Wireless Technology and Frequency Range	WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5720 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz WLAN 6GHz U-NII-5: 5925 MHz ~ 6425 MHz WLAN 6GHz U-NII-6: 6425 MHz ~ 6525 MHz WLAN 6GHz U-NII-7: 6525 MHz ~ 6875 MHz WLAN 6GHz U-NII-8: 6875 MHz ~ 7125 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC: 13.56 MHz
Mode	WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 2.4GHz 802.11ax HE20/HE40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac/ax VHT20/VHT40/VHT80/VHT160/HE20/HE40/HE80/HE160 WLAN 6GHz 802.11a WLAN 6GHz 802.11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE NFC: ASK
HW Version	V1.0
SW Version	514.03.00.0273-N-DEBUG-FIMG
EUT Stage	Identical Prototype
Remark: 1. This device 2.4GHz WLAN support hotspot operation and Bluetooth support tethering applications. 2. This device 5.2GHz WLAN/5.8GHz WLAN support hotspot operation, and 5.2GHz WLAN/5.8GHz WLAN supports WiFi Direct (GC/GO), and 5.3GHz / 5.5GHz supports WiFi Direct (GC only). WLAN 6GHz has no hotspot function. 3. The 2.4GHz/5GHz/6GHz WLAN can transmit in MIMO/SISO antenna mode. 4. The device implements receiver detection/hotspot mode for SAR compliance at different exposure conditions (head, hotspot, body-worn, and extremity). This device uses the receiver to indicate whether the user is making a call in head scenario or not. The selection between head and body power levels is based on the receiver detection mechanism. It can determine proximity to head or body and set the relevant power level for WLAN/BT antennas accordingly. 5. The device support DBS (Dual Band Simultaneous) function, when the device 2.4GHz and 5GHz or 6GHz transmit at the same time and it will limit different output power for simultaneous transmission compliance. 6. Bluetooth LE has two States for normal state (Module 1) and switch OFF state (Module 2). Bluetooth LE (Module 2) is to ensure it sends beacons and beep when the device is switch OFF and cannot be transmitted simultaneously with other wireless modes. And Bluetooth LE (Module 2) has no voice function. 7. SAR and Power density test report for WLAN 6GHz U-NII-5/6/7/8 will be separately submitted. About co-located SAR with WWAN/Bluetooth always chose higher SAR of WLAN5GHz U-NII-1/2A/2C/3 and WLAN 6GHz U-NII-5/6/7/8. 8. This device has NFC function and the NFC SAR report will be separately submitted. 9. There are five samples. The difference between them could be referred to the CT37X0N_Operational Description of Product Equality Declaration which is exhibited separately. According to the difference, sample 1 was chosen to perform full SAR testing and sample 2/3/5 verified the worst case of sample 1. For sample 4, the differences do not affect the test, so sample 4 are not tested.	

5. RF Exposure Limits

5.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

5.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

6. Specific Absorption Rate (SAR)

6.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

6.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$\text{SAR} = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$\text{SAR} = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

7. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running Win7 or Win10 and the DASy5 or DASy6 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

7.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	4 MHz – 10 GHz Linearity: ± 0.2 dB (30 MHz – 10 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

7.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Photo of DAE

7.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices or for evaluating transmitters operating at low frequencies. ELI is fully compatible with standard and all known tissue simulating liquids.

7.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

8. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

8.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

8.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

8.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: $\Delta x_{\text{Area}}, \Delta y_{\text{Area}}$	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

8.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm *	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

8.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

8.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

9. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	2450MHz System Validation Kit	D2450V2	1095	2024/2/8	2025/2/7
SPEAG	5000MHz System Validation Kit	D5GHzV2	1113	2022/9/23	2025/9/22
SPEAG	Data Acquisition Electronics	DAE4	1303	2023/11/20	2024/11/19
SPEAG	Dosimetric E-Field Probe	EX3DV4	7764	2023/10/5	2024/10/4
SPEAG	SAM Twin Phantom	SAM Twin	TP-2022	NCR	NCR
Testo	Thermo-Hygrometer	HTC-1	55009	2024/1/4	2025/1/3
SPEAG	Phone Positioner	N/A	N/A	NCR	NCR
Rohde & Schwarz	Signal Generator	SMB100A	100455	2024/1/2	2025/1/1
Keysight	Preamplifier	83017A	MY57280106	2024/4/18	2025/4/17
Anritsu	Radio Communication Analyzer	MT8821C	6262306175	2024/7/4	2025/7/3
Agilent	ENA Series Network Analyzer	E5071C	MY46112129	2024/7/4	2025/7/3
SPEAG	Dielectric Probe Kit	DAK-3.5	1144	2023/8/17	2024/8/16
Anritsu	Vector Signal Generator	MG3710A	6201682672	2024/1/2	2025/1/1
Rohde & Schwarz	Power Meter	NRVD	102081	2024/7/4	2025/7/3
Rohde & Schwarz	Power Sensor	NRV-Z5	100538	2024/7/4	2025/7/3
Rohde & Schwarz	Power Sensor	NRV-Z5	100539	2024/7/4	2025/7/3
Rohde & Schwarz	Power Sensor	NRP50S	101385	2023/10/11	2024/10/10
R&S	BLUETOOTH TESTER	CBT	100641	2024/1/2	2025/1/1
Rohde & Schwarz	Spectrum Analyzer	FSV7	101631	2023/10/11	2024/10/10
TES	DIGITAC THERMOMETER	TYPE-K	220305411	2024/1/4	2025/1/3
ARRA	Power Divider	A3200-2	N/A	NA	NA
MCL	Attenuation1	BW-S10W5+	N/A	NA	NA
MCL	Attenuation2	BW-S10W5+	N/A	NA	NA
MCL	Attenuation3	BW-S10W5+	N/A	NA	NA
BONN	POWER AMPLIFIER	BLMA 0830-3	087193A	Note 1	
BONN	POWER AMPLIFIER	BLMA 2060-2	087193B	Note 1	
Agilent	Dual Directional Coupler	778D	20500	Note 1	
Agilent	Dual Directional Coupler	11691D	MY48151020	Note 1	

Note:

1. Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check.
2. Referring to KDB 865664 D01v01r04, the dipole calibration interval can be extended to 3 years with justification. The dipoles are also not physically damaged, or repaired during the interval.
3. The justification data of dipole can be found in appendix C. The return loss is < -20dB, within 20% of prior calibration, the impedance is within 5 ohm of prior calibration.

10. System Verification

10.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 11.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 11.2.




Fig 11.1 Photo of Liquid Height for Head SAR



Fig 11.2 Photo of Liquid Height for Body SAR

10.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
2450	55.0	0	0	0	0	45.0	1.80	39.2

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
2450	Head	22.6	1.770	39.300	1.80	39.20	-1.67	0.26	±5	2024/7/15
5250	Head	22.8	4.740	35.900	4.71	35.90	0.64	0.00	±5	2024/7/16
5600	Head	22.8	5.160	35.300	5.07	35.50	1.78	-0.56	±5	2024/7/16
5750	Head	22.7	5.340	35.000	5.22	35.40	2.30	-1.13	±5	2024/7/17
5600	Head	22.7	4.930	34.900	5.07	35.50	-2.76	-1.69	±5	2024/7/26

10.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

<1g SAR>

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2024/7/15	2450	Head	50	1095	7764	1303	2.840	52.60	56.8	7.98
2024/7/16	5250	Head	50	1113	7764	1303	4.370	81.50	87.4	7.24
2024/7/16	5600	Head	50	1113	7764	1303	4.440	82.60	88.8	7.51
2024/7/17	5750	Head	50	1113	7764	1303	4.260	80.80	85.2	5.45
2024/7/26	5600	Head	50	1113	7764	1303	4.210	82.60	84.2	1.94

<10g SAR>

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)
2024/7/15	2450	Head	50	1095	7764	1303	1.310	24.70	26.2	6.07
2024/7/16	5250	Head	50	1113	7764	1303	1.240	23.30	24.8	6.44
2024/7/16	5600	Head	50	1113	7764	1303	1.260	23.70	25.2	6.33
2024/7/17	5750	Head	50	1113	7764	1303	1.210	23.00	24.2	5.22
2024/7/26	5600	Head	50	1113	7764	1303	1.210	23.70	24.2	2.11



Fig 11.3.1 System Performance Check Setup

Fig 11.3.2 Setup Photo

11. RF Exposure Positions

11.1 Ear and handset reference point

Figure 12.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled “M,” the left ear reference point (ERP) is marked “LE,” and the right ERP is marked “RE.” Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 12.1.2 The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 12.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 12.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 12.1.1 Front, back, and side views of SAM twin phantom




Fig 12.1.2 Close-up side view of phantom showing the ear region.




Fig 12.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

11.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 12.2.1 and Figure 12.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 12.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the handset. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 12.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 12.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 12.2.3. The actual rotation angles should be documented in the test report.




Fig 12.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 12.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 12.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

11.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 12.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 12.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

11.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 12.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 12.4 Body Worn Position

11.5 Product Specific 10g SAR Exposure

For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm, that can provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets and support voice calls next to the ear, According to KDB648474 D04v01r03, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.⁶ The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

11.6 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets ($L \times W \geq 9$ cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

12. Conducted RF Output Power (Unit: dBm)

The detailed conducted power table can refer to Appendix E.

<WLAN Conducted Power>

General Note:


1. The maximum output power specified for production units are determined for all applicable 802.11 transmission modes in each standalone and aggregated frequency band. Maximum output power is measured for the highest maximum output power configuration(s) in each frequency band according to the default power measurement procedures. For "Not required", SAR Test reduction was applied from KDB 248227 guidance, Sec. 2.1, b), 1) when the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration. Additional output power measurements were not necessary.
2. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
3. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
4. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
5. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.18 The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
6. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
7. 802.11 ax supports both full tone size mode and partial tone size mode, after verification on partial tone size mode that partial size tone mode power will not be higher than full tone size mode, therefore, full tone mode power was chosen to be measured in this report.
8. SISO and MIMO all supported by WLAN2.4GHz/WLAN5GHz, for SISO mode power is less than per chain power of MIMO mode. For WLAN SISO & MIMO mode, the whole testing has assessed only MIMO mode by referring to their higher conducted power, so only chose MIMO mode to perform SAR testing.

9. For the conducted power measurement is MIMO chains transmitting simultaneously and measured the separately conducted power for both chains and then based on the conducted power of SISO antenna respectively to calculate sum of the power for MIMO mode.

<2.4GHz Bluetooth>

General Note:

1. For 2.4GHz Bluetooth SAR testing was selected 1Mbps, due to its highest average power.
2. The Bluetooth duty cycle is 76.82% as following figure, for Bluetooth SAR scaling need further consideration and the theoretical duty cycle is 83.3%, therefore the actual duty cycle will be scaled up to 100% for Bluetooth reported SAR calculation.



2nd BLE Exclusions Applied:

Mode Band	Max Average power(dBm)
	LE
2.4GHz Bluetooth	4.0

Note:

- Per KDB 447498 D01v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$$

for 1-g SAR and ≤ 7.5 for 10-g extremity SAR

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

LE Max Power (dBm)	Separation Distance (mm)	Frequency (GHz)	exclusion thresholds
4.0	10	2.48	0.40

Note:

Per KDB 447498 D01v06, when the minimum test separation distance is 10mm and applied to determine SAR test exclusion. The test exclusion threshold is 0.40 which is ≤ 3 , SAR testing is not required.

13. Antenna Location

The detailed antenna location information can refer to SAR Test Setup Photos.

14. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)".
 - c. For SAR testing of Bluetooth signal with 83.3% theoretical duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle) *83.3%".
 - d. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required when the measured SAR is ≥ 0.8 W/kg. Per KDB 865664 D01v01r04, if the extremity repeated SAR is necessary, the same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.
4. Per KDB648474 D04v01r03, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm, when hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg, however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold.
 - a. WLAN 5.3/5.5GHz tested the product specific 10g SAR since it has no hotspot mode.
 - b. When 10-g product specific 10g SAR is considered, SAR thresholds is specified in the procedures for SAR test reduction and exclusion should be multiplied by 2.5.
5. For determination of the scaling factor for report SAR of MIMO mode, if the hot spots are separated the scaling factors are individually determined from each transmit chain. Further simplification chose the worse SAR value and the worst scaling factor from each transmit chain perform reported SAR calculation conservatively. If the hot spots are not spatially separated, the scaling factor is determined from the worst number of each transmit chain.

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. Per KDB 248227 D01v02r02, U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band.
3. Per KDB 248227 D01v02r02, when SAR measurement is required for at least one of the two U-NII bands and the highest reported SAR adjusted by the ratio of specified maximum output power of aggregated to standalone band is < 1.2 W/kg, SAR is not required for the 160 MHz channel.
4. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
5. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
6. During SAR testing the WLAN transmission was verified using a spectrum analyzer.
7. SISO and MIMO all supported by WLAN2.4GHz/WLAN5GHz, for SISO mode power is less than per chain power of MIMO mode. For WLAN SISO & MIMO mode, the whole testing has assessed only MIMO mode by referring to their higher conducted power, so only chose MIMO mode to perform SAR testing.
8. For the conducted power measurement is MIMO chains transmitting simultaneously and measured the separately conducted power for both chains and then based on the conducted power of two antennas respectively to calculate sum of the power for MIMO mode.



14.1 Head SAR

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
01	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	Ant 6+7(6)	Receiver on	11	2462	1	15.24	17.00	1.500	98.99	1.010	0.08	0.528	0.800
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	Ant 6+7(6)	Receiver on	1	2412	1	15.12	17.00	1.542	98.99	1.010	-0.12	0.856	1.333
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	Ant 6+7(6)	Receiver on	6	2437	1	15.07	17.00	1.560	98.99	1.010	-0.08	0.790	1.244
	WLAN2.4GHz	802.11n-HT40 MCS0	Right Cheek	0mm	Ant 6+7(6)	Receiver on	6	2437	1	15.31	17.00	1.476	100	1.000	-0.12	0.755	1.114
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	Ant 6+7(6)	Receiver on	11	2462	1	15.24	17.00	1.500	98.99	1.010	0.01	0.356	0.539
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Ant 6+7(6)	Receiver on	11	2462	1	15.24	17.00	1.500	98.99	1.010	0.03	0.364	0.551
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	0mm	Ant 6+7(6)	Receiver on	11	2462	1	15.24	17.00	1.500	98.99	1.010	-0.08	0.342	0.518
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	Ant 6+7(6)	Receiver on	1	2412	2	15.12	17.00	1.542	98.99	1.010	0.1	0.761	1.185
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	Ant 6+7(6)	Receiver on	1	2412	3	15.12	17.00	1.542	98.99	1.010	0.06	0.790	1.230
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	Ant 6+7(6)	Receiver on	1	2412	5	15.12	17.00	1.542	98.99	1.010	0.03	0.733	1.141
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	Ant 6+7(6)	For DBS	1	2412	1	12.62	14.50	1.542	98.99	1.010	0.04	0.493	0.768
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	Ant 6+7(6)	For DBS	1	2412	1	12.62	14.50	1.542	98.99	1.010	-0.17	0.332	0.517
02	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	Ant 6+7(6)	For DBS	1	2412	1	12.62	14.50	1.542	98.99	1.010	-0.03	0.340	0.529
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	0mm	Ant 6+7(6)	For DBS	1	2412	1	12.62	14.50	1.542	98.99	1.010	0.14	0.319	0.497
	Bluetooth	1Mbps	Right Cheek	0mm	Ant 6	Full Power	39	2441	1	7.89	8.50	1.152	76.82	1.084	0.18	0.000	0.000
	Bluetooth	1Mbps	Right Tilted	0mm	Ant 6	Full Power	39	2441	1	7.89	8.50	1.152	76.82	1.084	0.14	0.000	0.000
	Bluetooth	1Mbps	Left Cheek	0mm	Ant 6	Full Power	39	2441	1	7.89	8.50	1.152	76.82	1.084	-0.08	0.088	0.110
	Bluetooth	1Mbps	Left Cheek	0mm	Ant 6	Full Power	0	2402	1	7.58	8.50	1.237	76.82	1.084	0.17	0.080	0.107
03	Bluetooth	1Mbps	Left Cheek	0mm	Ant 6	Full Power	78	2480	1	6.79	8.50	1.484	76.82	1.084	-0.05	0.066	0.106
	Bluetooth	1Mbps	Left Tilted	0mm	Ant 6	Full Power	39	2441	1	7.89	8.50	1.152	76.82	1.084	-0.17	0.045	0.056
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Cheek	0mm	Ant 6+7(6)	Receiver on	54	5270	1	15.12	16.50	1.374	100	1.000	0.08	0.785	1.079
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Cheek	0mm	Ant 6+7(7)	Receiver on	62	5310	1	13.18	15.00	1.521	100	1.000	0.08	0.551	0.838
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Tilted	0mm	Ant 6+7(6)	Receiver on	54	5270	1	15.12	16.50	1.374	100	1.000	0.1	0.575	0.790
	WLAN5.3GHz	802.11n-HT40 MCS0	Left Cheek	0mm	Ant 6+7(6)	Receiver on	54	5270	1	15.12	16.50	1.374	100	1.000	-0.18	0.709	0.974
	WLAN5.3GHz	802.11n-HT40 MCS0	Left Cheek	0mm	Ant 6+7(6)	Receiver on	62	5310	1	13.18	15.00	1.521	100	1.000	0.08	0.482	0.733
	WLAN5.3GHz	802.11n-HT40 MCS0	Left Tilted	0mm	Ant 6+7(6)	Receiver on	54	5270	1	15.12	16.50	1.374	100	1.000	0.1	0.634	0.871
	WLAN5.3GHz	802.11n-HT40 MCS0	Left Tilted	0mm	Ant 6+7(6)	Receiver on	62	5310	1	13.18	15.00	1.521	100	1.000	0.01	0.422	0.642
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Cheek	0mm	Ant 6+7(6)	Receiver on	54	5270	2	15.12	16.50	1.374	100	1.000	0.18	0.731	1.004
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Cheek	0mm	Ant 6+7(6)	Receiver on	54	5270	3	15.12	16.50	1.374	100	1.000	0.17	0.704	0.967
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Cheek	0mm	Ant 6+7(6)	Receiver on	54	5270	5	15.12	16.50	1.374	100	1.000	0.08	0.755	1.037
04	WLAN5.3GHz	802.11n-HT40 MCS0	Right Cheek	0mm	Ant 6+7(6)	For DBS	54	5270	1	13.51	15.00	1.409	100	1.000	0.06	0.531	0.748
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Tilted	0mm	Ant 6+7(6)	For DBS	54	5270	1	13.51	15.00	1.409	100	1.000	0.11	0.389	0.548
	WLAN5.3GHz	802.11n-HT40 MCS0	Left Cheek	0mm	Ant 6+7(6)	For DBS	54	5270	1	13.51	15.00	1.409	100	1.000	-0.05	0.480	0.676
	WLAN5.3GHz	802.11n-HT40 MCS0	Left Tilted	0mm	Ant 6+7(6)	For DBS	54	5270	1	13.51	15.00	1.409	100	1.000	0.18	0.429	0.605
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Ant 6+7(6)	Receiver on	106	5530	1	11.40	13.00	1.445	100	1.000	0.12	0.581	0.840
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Ant 6+7(6)	Receiver on	138	5690	1	11.31	13.00	1.476	100	1.000	0.03	0.601	0.887
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Ant 6+7(6)	Receiver on	122	5610	1	11.35	13.00	1.462	100	1.000	-0.08	0.653	0.955
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	Ant 6+7(6)	Receiver on	106	5530	1	11.40	13.00	1.445	100	1.000	0.08	0.492	0.711
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Ant 6+7(6)	Receiver on	106	5530	1	11.40	13.00	1.445	100	1.000	-0.17	0.622	0.899
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Ant 6+7(6)	Receiver on	138	5690	1	11.31	13.00	1.476	100	1.000	-0.17	0.660	0.974
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Ant 6+7(6)	Receiver on	122	5610	1	11.35	13.00	1.462	100	1.000	-0.05	0.739	1.081
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Ant 6+7(6)	Receiver on	106	5530	1	11.40	13.00	1.445	100	1.000	-0.03	0.604	0.873
05	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Ant 6+7(6)	Receiver on	138	5690	1	11.31	13.00	1.476	100	1.000	-0.08	0.634	0.936
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Ant 6+7(6)	Receiver on	122	5610	1	11.35	13.00	1.462	100	1.000	0.1	0.701	1.025
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Ant 6+7(6)	Receiver on	122	5610	2	11.35	13.00	1.462	100	1.000	0.1	0.653	0.955
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Ant 6+7(6)	Receiver on	122	5610	3	11.35	13.00	1.462	100	1.000	0.18	0.691	1.010
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Ant 6+7(6)	Receiver on	122	5610	5	11.35	13.00	1.462	100	1.000	0.06	0.701	1.025
	WLAN5.5GHz	802.11ac-VHT160 MCS0	Left Cheek	0mm	Ant 6+7(6)	Receiver on	114	5570	1	11.34	13.00	1.466	100	1.000	0.04	0.608	0.891
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Ant 6+7(7)	For DBS	122	5610	1	9.31	11.00	1.476	100	1.000	0.14	0.461	0.680
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	Ant 6+7(7)	For DBS	122	5610	1	9.31	11.00	1.476	100	1.000	-0.17	0.390	0.576
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Ant 6+7(7)	For DBS	122	5610	1	9.31	11.00	1.476	100	1.000	0.09	0.493	0.728
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Ant 6+7(7)	For DBS	122	5610	1	9.31	11.00	1.476	100	1.000	0.09	0.493	0.728



FCC SAR Test Report

Report No. : FA461913

	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Ant 6+7(7)	For DBS	122	5610	1	9.31	11.00	1.476	100	1.000	0.17	0.479	0.707
	WLAN5.8GHz	802.11ac-VHT160 MCS0	Left Cheek	0mm	Ant 6+7(6)	For DBS	114	5570	1	9.28	11.00	1.486	100	1.000	0.06	0.413	0.614
05	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Ant 6+7(6)	Receiver on	155	5775	1	11.33	13.00	1.469	100	1.000	0.02	0.776	1.140
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	Ant 6+7(6)	Receiver on	155	5775	1	11.33	13.00	1.469	100	1.000	0.08	0.604	0.887
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Ant 6+7(6)	Receiver on	155	5775	1	11.33	13.00	1.469	100	1.000	0.01	0.709	1.041
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Ant 6+7(6)	Receiver on	155	5775	1	11.33	13.00	1.469	100	1.000	0.03	0.687	1.009
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Ant 6+7(6)	Receiver on	155	5775	2	11.33	13.00	1.469	100	1.000	0.1	0.755	1.109
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Ant 6+7(6)	Receiver on	155	5775	3	11.33	13.00	1.469	100	1.000	0.14	0.713	1.047
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Ant 6+7(6)	Receiver on	155	5775	5	11.33	13.00	1.469	100	1.000	0.17	0.729	1.071
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	Ant 6+7(6)	For DBS	155	5775	1	9.20	11.00	1.514	100	1.000	-0.06	0.511	0.773
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	Ant 6+7(6)	For DBS	155	5775	1	9.20	11.00	1.514	100	1.000	-0.05	0.398	0.602
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	Ant 6+7(6)	For DBS	155	5775	1	9.20	11.00	1.514	100	1.000	0.01	0.467	0.707
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	Ant 6+7(6)	For DBS	155	5775	1	9.20	11.00	1.514	100	1.000	0.1	0.452	0.684

14.2 Hotspot SAR

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	Ant 6+7(6)	Full Power	11	2462	1	19.15	21.00	1.531	98.99	1.010	0.08	0.379	0.586
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Ant 6+7(6)	Full Power	11	2462	1	19.15	21.00	1.531	98.99	1.010	0.01	0.417	0.645
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant 6+7(6)	Full Power	11	2462	1	19.15	21.00	1.531	98.99	1.010	0.1	0.381	0.589
	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	Ant 6+7(6)	Full Power	11	2462	1	19.15	21.00	1.531	98.99	1.010	0.12	0.275	0.425
	WLAN2.4GHz	802.11b 1Mbps	Top Side	10mm	Ant 6+7(6)	Full Power	11	2462	1	19.15	21.00	1.531	98.99	1.010	0.08	0.617	0.954
06	WLAN2.4GHz	802.11b 1Mbps	Top Side	10mm	Ant 6+7(6)	Full Power	1	2412	1	19.11	21.00	1.545	98.99	1.010	-0.11	0.717	1.119
	WLAN2.4GHz	802.11b 1Mbps	Top Side	10mm	Ant 6+7(6)	Full Power	6	2437	1	19.13	21.00	1.538	98.99	1.010	-0.17	0.705	1.095
	WLAN2.4GHz	802.11b 1Mbps	Top Side	10mm	Ant 6+7(6)	Full Power	1	2412	2	19.11	21.00	1.545	98.99	1.010	0.08	0.688	1.074
	WLAN2.4GHz	802.11b 1Mbps	Top Side	10mm	Ant 6+7(6)	Full Power	1	2412	3	19.11	21.00	1.545	98.99	1.010	0.01	0.653	1.019
	WLAN2.4GHz	802.11b 1Mbps	Top Side	10mm	Ant 6+7(6)	Full Power	1	2412	5	19.11	21.00	1.545	98.99	1.010	0.03	0.633	0.988
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	Ant 6+7(6)	For DBS	1	2412	1	17.02	19.00	1.578	98.99	1.010	0.1	0.302	0.481
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Ant 6+7(6)	For DBS	1	2412	1	17.02	19.00	1.578	98.99	1.010	-0.18	0.333	0.531
	WLAN2.4GHz	802.11b 1Mbps	Left Side	10mm	Ant 6+7(6)	For DBS	1	2412	1	17.02	19.00	1.578	98.99	1.010	0.1	0.304	0.484
	WLAN2.4GHz	802.11b 1Mbps	Right Side	10mm	Ant 6+7(6)	For DBS	1	2412	1	17.02	19.00	1.578	98.99	1.010	0.12	0.219	0.349
	WLAN2.4GHz	802.11b 1Mbps	Top Side	10mm	Ant 6+7(6)	For DBS	1	2412	1	17.02	19.00	1.578	98.99	1.010	0.08	0.492	0.784
07	Bluetooth	1Mbps	Front	10mm	Ant 6	Full Power	39	2441	1	7.89	8.50	1.152	76.82	1.084	-0.09	0.018	0.022
	Bluetooth	1Mbps	Back	10mm	Ant 6	Full Power	39	2441	1	7.89	8.50	1.152	76.82	1.084	0.18	0.000	0.000
	Bluetooth	1Mbps	Left Side	10mm	Ant 6	Full Power	39	2441	1	7.89	8.50	1.152	76.82	1.084	0.18	0.000	0.000
	Bluetooth	1Mbps	Right Side	10mm	Ant 6	Full Power	39	2441	1	7.89	8.50	1.152	76.82	1.084	-0.1	0.000	0.000
	Bluetooth	1Mbps	Top Side	10mm	Ant 6	Full Power	39	2441	1	7.89	8.50	1.152	76.82	1.084	0.01	0.016	0.020
	Bluetooth	1Mbps	Front	10mm	Ant 6	Full Power	0	2402	1	7.58	8.50	1.237	76.82	1.084	0.16	0.013	0.017
	Bluetooth	1Mbps	Front	10mm	Ant 6	Full Power	78	2480	1	6.79	8.50	1.484	76.82	1.084	-0.1	0.011	0.018
	WLAN5.2GHz	802.11n-HT40 MCS0	Front	10mm	Ant 6+7(6)	Full Power	46	5230	1	15.41	17.00	1.442	100	1.000	0.01	0.200	0.288
	WLAN5.2GHz	802.11n-HT40 MCS0	Back	10mm	Ant 6+7(6)	Full Power	46	5230	1	15.41	17.00	1.442	100	1.000	0.03	0.180	0.260
	WLAN5.2GHz	802.11n-HT40 MCS0	Left Side	10mm	Ant 6+7(6)	Full Power	46	5230	1	15.41	17.00	1.442	100	1.000	-0.08	0.159	0.229
08	WLAN5.2GHz	802.11n-HT40 MCS0	Right Side	10mm	Ant 6+7(6)	Full Power	46	5230	1	15.41	17.00	1.442	100	1.000	-0.12	0.204	0.294
	WLAN5.2GHz	802.11n-HT40 MCS0	Top Side	10mm	Ant 6+7(6)	Full Power	46	5230	1	15.41	17.00	1.442	100	1.000	-0.08	0.156	0.225
	WLAN5.2GHz	802.11n-HT40 MCS0	Right Side	10mm	Ant 6+7(7)	Full Power	38	5190	1	14.40	16.00	1.445	100	1.000	-0.12	0.159	0.230
	WLAN5.2GHz	802.11n-HT40 MCS0	Right Side	10mm	Ant 6+7(6)	Full Power	46	5230	2	15.41	17.00	1.442	100	1.000	-0.08	0.188	0.271
	WLAN5.2GHz	802.11n-HT40 MCS0	Right Side	10mm	Ant 6+7(6)	Full Power	46	5230	3	15.41	17.00	1.442	100	1.000	-0.08	0.173	0.249
	WLAN5.2GHz	802.11n-HT40 MCS0	Right Side	10mm	Ant 6+7(6)	Full Power	46	5230	5	15.41	17.00	1.442	100	1.000	0.1	0.176	0.254
09	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	Full Power	155	5775	1	16.30	17.50	1.318	100	1.000	0.06	0.822	1.084
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Back	10mm	Ant 6+7(6)	Full Power	155	5775	1	16.30	17.50	1.318	100	1.000	0.08	0.755	0.995
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Side	10mm	Ant 6+7(6)	Full Power	155	5775	1	16.30	17.50	1.318	100	1.000	0.01	0.500	0.659
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Side	10mm	Ant 6+7(6)	Full Power	155	5775	1	16.30	17.50	1.318	100	1.000	0.03	0.522	0.688
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Top Side	10mm	Ant 6+7(6)	Full Power	155	5775	1	16.30	17.50	1.318	100	1.000	-0.08	0.632	0.833
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	Full Power	155	5775	2	16.30	17.50	1.318	100	1.000	0.02	0.791	1.043

Sporton International Inc. (Kunshan)

TEL : +86-512-57900158

FCC ID : HD5-CT37X0N

Page 30 of 38

Issued Date : Jul. 26, 2024

Form version. : 200414



FCC SAR Test Report

Report No. : FA461913

WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	Full Power	155	5775	3	16.30	17.50	1.318	100	1.000	0.03	0.762	1.005
WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	Full Power	155	5775	5	16.30	17.50	1.318	100	1.000	-0.18	0.777	1.024
WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	For DBS	155	5775	1	14.82	16.00	1.312	100	1.000	-0.08	0.551	0.723
WLAN5.8GHz	802.11ac-VHT80 MCS0	Back	10mm	Ant 6+7(6)	For DBS	155	5775	1	14.82	16.00	1.312	100	1.000	-0.08	0.506	0.664
WLAN5.8GHz	802.11ac-VHT80 MCS0	Left Side	10mm	Ant 6+7(6)	For DBS	155	5775	1	14.82	16.00	1.312	100	1.000	0.14	0.323	0.424
WLAN5.8GHz	802.11ac-VHT80 MCS0	Right Side	10mm	Ant 6+7(6)	For DBS	155	5775	1	14.82	16.00	1.312	100	1.000	-0.17	0.337	0.442
WLAN5.8GHz	802.11ac-VHT80 MCS0	Top Side	10mm	Ant 6+7(6)	For DBS	155	5775	1	14.82	16.00	1.312	100	1.000	0.17	0.408	0.535

14.3 Body Worn Accessory SAR

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	Ant 6+7(6)	Full Power	11	2462	1	19.15	21.00	1.531	98.99	1.010	0.08	0.379	0.586
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Ant 6+7(6)	Full Power	11	2462	1	19.15	21.00	1.531	98.99	1.010	0.01	0.417	0.645
10	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Ant 6+7(6)	Full Power	1	2412	1	19.11	21.00	1.545	98.99	1.010	-0.18	0.723	1.128
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Ant 6+7(6)	Full Power	6	2437	1	19.13	21.00	1.538	98.99	1.010	0.03	0.671	1.042
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Ant 6+7(6)	Full Power	1	2412	2	19.11	21.00	1.545	98.99	1.010	-0.08	0.701	1.094
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Ant 6+7(6)	Full Power	1	2412	3	19.11	21.00	1.545	98.99	1.010	0.01	0.688	1.074
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Ant 6+7(6)	Full Power	1	2412	5	19.11	21.00	1.545	98.99	1.010	-0.08	0.691	1.078
	WLAN2.4GHz	802.11b 1Mbps	Front	10mm	Ant 6+7(6)	For DBS	1	2412	1	17.02	19.00	1.578	98.99	1.010	0.11	0.334	0.532
	WLAN2.4GHz	802.11b 1Mbps	Back	10mm	Ant 6+7(6)	For DBS	1	2412	1	17.02	19.00	1.578	98.99	1.010	0.06	0.477	0.760
11	Bluetooth	1Mbps	Front	10mm	Ant 6	Full Power	39	2441	1	7.89	8.50	1.152	76.82	1.084	-0.09	0.018	0.022
	Bluetooth	1Mbps	Back	10mm	Ant 6	Full Power	39	2441	1	7.89	8.50	1.152	76.82	1.084	0.18	0.000	0.000
	Bluetooth	1Mbps	Front	10mm	Ant 6	Full Power	0	2402	1	7.58	8.50	1.237	76.82	1.084	0.16	0.013	0.017
	Bluetooth	1Mbps	Front	10mm	Ant 6	Full Power	78	2480	1	6.79	8.50	1.484	76.82	1.084	-0.1	0.011	0.018
12	WLAN5.3GHz	802.11n-HT40 MCS0	Front	10mm	Ant 6+7(6)	Full Power	54	5270	1	17.53	19.00	1.403	100	1.000	-0.17	0.476	0.668
	WLAN5.3GHz	802.11n-HT40 MCS0	Back	10mm	Ant 6+7(6)	Full Power	54	5270	1	17.53	19.00	1.403	100	1.000	0.06	0.463	0.650
	WLAN5.3GHz	802.11n-HT40 MCS0	Back	10mm	Ant 6+7(7)	Full Power	62	5310	1	13.18	15.00	1.521	100	1.000	0.02	0.302	0.459
	WLAN5.3GHz	802.11n-HT40 MCS0	Front	10mm	Ant 6+7(6)	Full Power	54	5270	2	17.53	19.00	1.403	100	1.000	0.01	0.455	0.638
	WLAN5.3GHz	802.11n-HT40 MCS0	Front	10mm	Ant 6+7(6)	Full Power	54	5270	3	17.53	19.00	1.403	100	1.000	0.1	0.419	0.588
	WLAN5.3GHz	802.11n-HT40 MCS0	Front	10mm	Ant 6+7(6)	Full Power	54	5270	5	17.53	19.00	1.403	100	1.000	-0.17	0.404	0.567
13	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	Full Power	138	5690	1	15.32	17.00	1.472	100	1.000	0.03	0.678	0.998
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	10mm	Ant 6+7(6)	Full Power	138	5690	1	15.32	17.00	1.472	100	1.000	-0.08	0.462	0.680
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	Full Power	122	5610	1	15.25	17.00	1.496	100	1.000	0.1	0.601	0.899
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	Full Power	106	5530	1	13.38	15.00	1.452	100	1.000	-0.18	0.401	0.582
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	Full Power	138	5690	2	15.32	17.00	1.472	100	1.000	0.04	0.611	0.900
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	Full Power	138	5690	3	15.32	17.00	1.472	100	1.000	-0.01	0.589	0.867
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	Full Power	138	5690	5	15.32	17.00	1.472	100	1.000	-0.08	0.638	0.939
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	For DBS	138	5690	1	14.38	16.00	1.452	100	1.000	0.01	0.511	0.742
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	10mm	Ant 6+7(6)	For DBS	138	5690	1	14.38	16.00	1.452	100	1.000	0.03	0.348	0.505
14	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	Full Power	155	5775	1	16.30	17.50	1.318	100	1.000	0.06	0.822	1.084
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Back	10mm	Ant 6+7(6)	Full Power	155	5775	1	16.30	17.50	1.318	100	1.000	0.08	0.755	0.995
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	Full Power	155	5775	2	16.30	17.50	1.318	100	1.000	0.02	0.791	1.043
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	Full Power	155	5775	3	16.30	17.50	1.318	100	1.000	0.03	0.762	1.005
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	Full Power	155	5775	5	16.30	17.50	1.318	100	1.000	-0.18	0.777	1.024
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	For DBS	155	5775	1	14.82	16.00	1.312	100	1.000	-0.08	0.551	0.723
	WLAN5.8GHz	802.11ac-VHT80 MCS0	Back	10mm	Ant 6+7(6)	For DBS	155	5775	1	14.82	16.00	1.312	100	1.000	-0.08	0.506	0.664



14.4 Product Specific SAR

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Sample	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WLAN5.3GHz	802.11n-HT40 MCS0	Front	0mm	Ant 6+7(6)	Full Power	54	5270	1	17.53	19.00	1.403	100	1.000	0.1	0.788	1.105
	WLAN5.3GHz	802.11n-HT40 MCS0	Back	0mm	Ant 6+7(6)	Full Power	54	5270	1	17.53	19.00	1.403	100	1.000	-0.18	0.931	1.306
	WLAN5.3GHz	802.11n-HT40 MCS0	Left Side	0mm	Ant 6+7(6)	Full Power	54	5270	1	17.53	19.00	1.403	100	1.000	0.1	0.649	0.910
15	WLAN5.3GHz	802.11n-HT40 MCS0	Right Side	0mm	Ant 6+7(6)	Full Power	54	5270	1	17.53	19.00	1.403	100	1.000	-0.09	1.040	1.459
	WLAN5.3GHz	802.11n-HT40 MCS0	Top Side	0mm	Ant 6+7(6)	Full Power	54	5270	1	17.53	19.00	1.403	100	1.000	0.12	0.440	0.617
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Side	0mm	Ant 6+7(7)	Full Power	62	5310	1	13.18	14.50	1.355	100	1.000	0.03	0.497	0.674
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Side	0mm	Ant 6+7(6)	Full Power	54	5270	2	17.53	19.00	1.403	100	1.000	-0.18	0.931	1.306
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Side	0mm	Ant 6+7(6)	Full Power	54	5270	3	17.53	19.00	1.403	100	1.000	0.1	0.863	1.211
	WLAN5.3GHz	802.11n-HT40 MCS0	Right Side	0mm	Ant 6+7(6)	Full Power	54	5270	5	17.53	19.00	1.403	100	1.000	0.12	0.897	1.258
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	0mm	Ant 6+7(6)	Full Power	138	5690	1	15.32	17.00	1.472	100	1.000	0.08	0.579	0.852
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	0mm	Ant 6+7(6)	Full Power	138	5690	1	15.32	17.00	1.472	100	1.000	0.01	0.698	1.028
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Side	0mm	Ant 6+7(6)	Full Power	138	5690	1	15.32	17.00	1.472	100	1.000	0.03	0.606	0.892
16	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Side	0mm	Ant 6+7(6)	Full Power	138	5690	1	15.32	17.00	1.472	100	1.000	0.04	0.774	1.140
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Top Side	0mm	Ant 6+7(6)	Full Power	138	5690	1	15.32	17.00	1.472	100	1.000	-0.08	0.595	0.876
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Side	0mm	Ant 6+7(6)	Full Power	122	5610	1	15.25	17.00	1.496	100	1.000	-0.08	0.758	1.134
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Side	0mm	Ant 6+7(6)	Full Power	106	5530	1	13.38	15.00	1.452	100	1.000	0.1	0.411	0.597
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Side	0mm	Ant 6+7(6)	Full Power	138	5690	2	15.32	17.00	1.472	100	1.000	0.08	0.711	1.047
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Side	0mm	Ant 6+7(6)	Full Power	138	5690	3	15.32	17.00	1.472	100	1.000	-0.17	0.683	1.006
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Side	0mm	Ant 6+7(6)	Full Power	138	5690	5	15.32	17.00	1.472	100	1.000	-0.03	0.739	1.088
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Front	0mm	Ant 6+7(6)	For DBS	138	5690	1	14.38	16.00	1.452	100	1.000	-0.17	0.444	0.645
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Back	0mm	Ant 6+7(6)	For DBS	138	5690	1	14.38	16.00	1.452	100	1.000	-0.03	0.535	0.777
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Left Side	0mm	Ant 6+7(6)	For DBS	138	5690	1	14.38	16.00	1.452	100	1.000	0.14	0.464	0.674
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Right Side	0mm	Ant 6+7(6)	For DBS	138	5690	1	14.38	16.00	1.452	100	1.000	0.03	0.593	0.861
	WLAN5.5GHz	802.11ac-VHT80 MCS0	Top Side	0mm	Ant 6+7(6)	For DBS	138	5690	1	14.38	16.00	1.452	100	1.000	0.11	0.456	0.662

14.5 Repeated SAR Measurement

Plot No.	Band	Mode	Test Position	Gap (mm)	Antenna	Power Reduction	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	Ant 6+7(6)	Receiver on	1	2412	15.12	17.00	1.542	98.99	1.010	-0.12	0.856	1	1.333
2nd	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	Ant 6+7(6)	Receiver on	1	2412	15.12	17.00	1.542	98.99	1.010	0.06	0.831	1.030	1.294
1st	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	Full Power	155	5775	16.30	17.50	1.318	100	1.000	0.06	0.822	1	1.084
2nd	WLAN5.8GHz	802.11ac-VHT80 MCS0	Front	10mm	Ant 6+7(6)	Full Power	155	5775	16.30	17.50	1.318	100	1.000	0.05	0.815	1.009	1.074

General Note:

1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is $\geq 0.8\text{W/kg}$.
2. Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR $< 1.45\text{W/kg}$, only one repeated measurement is required.
3. The ratio is the difference in percentage between original and repeated *measured SAR*.
4. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

15. Simultaneous Transmission Analysis

No.	Simultaneous Transmission Configurations	mobile computer			
		Head	Body-worn	Hotspot	Product specific 10g SAR
1.	WLAN2.4GHz + WLAN5GHz	Yes	Yes	Yes	Yes
2.	WLAN2.4GHz + WLAN6GHz	Yes	Yes		Yes
3.	WLAN5GHz + Bluetooth	Yes	Yes	Yes	Yes
4.	WLAN6GHz + Bluetooth	Yes	Yes		Yes
5.	WLAN2.4GHz + WLAN5GHz + NFC				Yes
6.	WLAN2.4GHz + WLAN6GHz + NFC				Yes
7.	WLAN5GHz + Bluetooth + NFC				Yes
8.	WLAN6GHz + Bluetooth + NFC				Yes

General Note:

- This device 2.4GHz WLAN support hotspot operation and Bluetooth support tethering applications.
- This device 5.2GHz WLAN/5.8GHz WLAN support hotspot operation, and 5.2GHz WLAN/5.8GHz WLAN supports WLAN Direct (GC/GO), and 5.3GHz / 5.5GHz supports WLAN Direct (GC only). WLAN 6GHz has no hotspot function.
- The worst case 5 GHz WLAN SAR for each configuration was used for SAR summation.
- The 2.4GHz/5GHz/6GHz WLAN can transmit in SISO/MIMO antenna mode and MIMO SAR can represent SISO SAR.
- WLAN 2.4GHz Ant6 and Bluetooth share the same antenna so can't transmit simultaneously.
- According to the EUT characteristic, WLAN 5GHz/6GHz and Bluetooth can transmit simultaneously.
- According to the EUT characteristic, WLAN 5GHz/6GHz and WLAN 2.4GHz can transmit simultaneously.
- According to the EUT characteristic, Bluetooth LE (Module 2) cannot be transmitted simultaneously with other wireless modes.
- NFC can transmit simultaneously with other Radios in extremity exposure condition.
- The maximum SAR summation is calculated based on the same configuration and test position.
- Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - 1g Scalar SAR summation < 1.6W/kg and 10g Scalar SAR summation < 4.0W/kg.
 - $SPLSR = (SAR1 + SAR2)^{1.5} / (\min. \text{ separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - If $SPLSR \leq 0.04$ for 1g SAR and $SPLSR \leq 0.10$ for 10g SAR, simultaneously transmission SAR measurement is not necessary.
 - Simultaneously transmission SAR measurement, and the reported multi-band 1g SAR < 1.6W/kg and 10g SAR < 4.0W/kg.

15.1 Head Exposure Conditions

<For Non DBS>

Exposure Position	1	2	3	1+3	2+3
	WLAN5GHz Ant 6+7	WLAN6GHz Ant 6+7	Bluetooth Ant 6	Summed	Summed
	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)
Right Cheek	1.140	1.207		1.14	1.21
Right Tilted	0.887	1.207		0.89	1.21
Left Cheek	1.081	1.207	0.110	1.19	1.32
Left Tilted	1.025	1.207	0.056	1.08	1.26

<For DBS>

Exposure Position	1	2	3	1+2	1+3
	WLAN2.4GHz Ant 6+7	WLAN5GHz Ant 6+7	WLAN6GHz Ant 6+7	Summed	Summed
	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)
Right Cheek	0.768	0.773	0.728	1.54	1.50
Right Tilted	0.517	0.602	0.728	1.12	1.25
Left Cheek	0.529	0.728	0.728	1.26	1.26
Left Tilted	0.497	0.707	0.728	1.20	1.23

15.2 Hotspot Exposure Conditions

<For Non DBS>

Exposure Position	1	2	1+2
	WLAN5GHz Ant 6+7	Bluetooth Ant 6	Summed
	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)
Front	1.084	0.022	1.11
Back	0.995		1.00
Left side	0.659		0.66
Right side	0.688		0.69
Top side	0.833	0.020	0.85
Bottom side			0.00

<For DBS>

Exposure Position	1	2	1+2
	WLAN2.4GHz Ant 6+7	WLAN5GHz Ant 6+7	Summed
	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)
Front	0.481	0.697	1.18
Back	0.531	0.640	1.17
Left side	0.484	0.424	0.91
Right side	0.349	0.442	0.79
Top side	0.784	0.535	1.32
Bottom side			0.00

15.3 Body-Worn Accessory Exposure Conditions

<For Non DBS>

Exposure Position	1	2	3	1+3	2+3
	WLAN5GHz Ant 6+7	WLAN6GHz Ant 6+7	Bluetooth Ant 6	Summed	Summed
	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)
Front	1.084	0.624	0.022	1.11	0.65
Back	0.995	0.624		1.00	0.62

<For DBS>

Exposure Position	1	2	3	1+2	1+3
	WLAN2.4GHz Ant 6+7	WLAN5GHz Ant 6+7	WLAN6GHz Ant 6+7	Summed	Summed
	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)
Front	0.532	0.742	0.624	1.27	1.16
Back	0.760	0.664	0.624	1.42	1.38

15.4 Product Specific Exposure Conditions

Note: 1. For WLAN2.4GHz/Bluetooth Product specific 10g stand-alone SAR is not required for a transmitter or antenna, due to 1g hotspot SAR is <1.2W/kg.

Exposure Position	1	2	3	1+3	2+3
	WLAN5GHz Ant 6+7	WLAN6GHz Ant 6+7	NFC	Summed	Summed
	10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)	10g SAR (W/kg)
Front	1.105	0.395	0.003	1.11	0.40
Back	1.306	0.395	0.066	1.37	0.46
Left side	0.910	0.395	0.001	0.91	0.40
Right side	1.459	0.395	0.001	1.46	0.40
Top side	0.876	0.395	0.005	0.88	0.40
Bottom side			0.001	0.00	0.00

Test Engineer : Martin Li, Varus Wang, Light Wang, Ricky Gu

16. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

17. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [6] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.
- [7] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [8] FCC KDB 648474 D04 v01r03, "SAR Evaluation Considerations for Wireless Handsets", Oct 2015.
- [9] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [10] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.

-----THE END-----