



FCC RF Test Report

APPLICANT : Honeywell International Inc.
Honeywell Safety and Productivity Solutions

EQUIPMENT : Mobile Computer

BRAND NAME : Honeywell

MODEL NAME : CT40P-L1N

FCC ID : HD5-CT40PL1N

STANDARD : FCC Part 15 Subpart C §15.247

CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Jul. 24, 2020 and testing was completed on Aug. 24, 2020. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

James Huang

Approved by: James Huang / Manager



Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	6
1.5 Modification of EUT	6
1.6 Testing Location	7
1.7 Test Software.....	7
1.8 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
2.1 Carrier Frequency Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	11
2.5 EUT Operation Test Setup	11
2.6 Measurement Results Explanation Example.....	11
3 TEST RESULT	12
3.1 6dB and 99% Bandwidth Measurement	12
3.2 Output Power Measurement.....	25
3.3 Power Spectral Density Measurement	26
3.4 Conducted Band Edges and Spurious Emission Measurement	39
3.5 Radiated Band Edges and Spurious Emission Measurement	56
3.6 AC Conducted Emission Measurement.....	60
3.7 Antenna Requirements.....	62
4 LIST OF MEASURING EQUIPMENT.....	63
5 UNCERTAINTY OF EVALUATION.....	64
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. DUTY CYCLE PLOTS	
APPENDIX E. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR072404B	Rev. 01	Initial issue of report	Sep. 02, 2020

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)(3)	Peak Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 20\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.98 dB at 2483.500 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 13.03 dB at 0.507 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Honeywell International Inc.
Honeywell Safety and Productivity Solutions
9680 Old Bailes Rd. Fort Mill, SC 29707 United States

1.2 Manufacturer

Honeywell International Inc.
Honeywell Safety and Productivity Solutions
9680 Old Bailes Rd. Fort Mill, SC 29707 United States

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Computer
Brand Name	Honeywell
Model Name	CT40P-L1N
FCC ID	HD5-CT40PL1N
EUT supports Radios application	CDMA/GSM/WCDMA/LTE/NFC/GNSS WLAN 2.4GHz 802.11b/g/n (HT20/HT40) WLAN 5GHz 802.11a/n/ac (HT20/HT40/VHT20/VHT40/VHT80) Bluetooth BR / EDR / LE
IMEI Code	Conducted:N/A Conduction: 990016300002019 Radiation: 990016300003215 for BLE module 1 990016300003546 for BLE module 2
HW Version	V2.0
SW Version	OS.03.003-HON.02.001
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two samples, the differences between two samples are sample 1 has Type C charging port and sample 2 has none. According to the difference, sample 1 perform full test.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	Module 1 : Bluetooth v4.2 LE: 1.48 dBm (0.0014 W) Bluetooth v5.0 LE: 1.65 dBm (0.0015 W) Module 2 : Bluetooth v4.2 LE: 4.85 dBm (0.0031 W) Bluetooth v5.1 LE: 5.12 dBm (0.0033 W)
99% Occupied Bandwidth	Module 1: Bluetooth v4.2 LE: 1.025MHz Bluetooth v5.0 LE: 2.033MHz Module 2: Bluetooth v4.2 LE: 1.041MHz Bluetooth v5.1 LE: 2.038MHz
Antenna Type / Gain	IFA Antenna with gain 1.60 dBi
Type of Modulation	Bluetooth LE : GFSK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH05-KS TH01-KS	CN1257	314309

1.7 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH05-KS	AUDIX	E3	6.2009-8-24al
2.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013
- FCC RSS-247 Issue 2
- FCC RSS-Gen Issue 5

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y,Z plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz Mode 2: Bluetooth Tx CH19_2440 MHz Mode 3: Bluetooth Tx CH39_2480 MHz
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz Mode 2: Bluetooth Tx CH19_2440 MHz Mode 3: Bluetooth Tx CH39_2480 MHz
AC Conducted Emission	Mode 1: GSM 850 Idle + Bluetooth module 1 Link + WLAN Link(2.4G) + USB Cable (Charging from Adapter) (type C)
Remark: For Radiated Test Cases, The tests were performance with Adapter	

2.3 Connection Diagram of Test System

For Radiation



For Conducted Emission



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
3.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	AC I/P: Unshielded, 1.8m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
5.	SD Card	Kingston	8GB	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For BLE function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Offset(dB) = RF cable loss(dB).

= 6.5 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.
6. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

Module 1:


Bluetooth v4.2 LE

6 dB Bandwidth Plot on Channel 00



Date: 20.AUG.2020 05:18:31


6 dB Bandwidth Plot on Channel 19



Date: 20.AUG.2020 05:21:36




6 dB Bandwidth Plot on Channel 39



Date: 20.AUG.2020 05:23:23

Bluetooth v5.0 LE


6 dB Bandwidth Plot on Channel 00



Date: 20.AUG.2020 05:31:05




6 dB Bandwidth Plot on Channel 19



Date: 20.AUG.2020 05:28:42

6 dB Bandwidth Plot on Channel 39




Date: 20.AUG.2020 05:26:12



Module 2:


Bluetooth v4.2 LE

6 dB Bandwidth Plot on Channel 00



Date: 18.AUG.2020 21:57:14


6 dB Bandwidth Plot on Channel 19



Date: 18.AUG.2020 21:48:14




6 dB Bandwidth Plot on Channel 39



Date: 18.AUG.2020 22:04:53

Bluetooth v5.1 LE


6 dB Bandwidth Plot on Channel 00



Date: 18.AUG.2020 22:31:21




6 dB Bandwidth Plot on Channel 19



Date: 18.AUG.2020 22:40:29

6 dB Bandwidth Plot on Channel 39



Date: 18.AUG.2020 22:35:16




3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

Module 1:


Bluetooth v4.2 LE

99% Bandwidth Plot on Channel 00



Date: 20.AUG.2020 05:20:22


99% Occupied Bandwidth Plot on Channel 19



Date: 20.AUG.2020 05:22:43




99% Occupied Bandwidth Plot on Channel 39



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.


Bluetooth v5.0 LE

99% Bandwidth Plot on Channel 00






99% Occupied Bandwidth Plot on Channel 19



Date: 20.AUG.2020 05:30:01

99% Occupied Bandwidth Plot on Channel 39



Date: 20.AUG.2020 05:27:34


Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



Module 2:


Bluetooth v4.2 LE

99% Bandwidth Plot on Channel 00



Date: 18.AUG.2020 22:01:22


99% Occupied Bandwidth Plot on Channel 19



Date: 18.AUG.2020 21:50:49



99% Occupied Bandwidth Plot on Channel 39




Date: 18.AUG.2020 22:07:07

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

Bluetooth v5.1 LE


99% Bandwidth Plot on Channel 00




Date: 18.AUG.2020 22:33:25



99% Occupied Bandwidth Plot on Channel 19



99% Occupied Bandwidth Plot on Channel 39



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.2 Method AVGPM-G method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.




3.3.6 Test Result of Power Spectral Density Plots (100kHz)

Module 1:


Bluetooth v4.2 LE

PSD 100kHz Plot on Channel 00



Date: 20.AUG.2020 05:18:58


PSD 100kHz Plot on Channel 19



Date: 20.AUG.2020 05:22:17




PSD 100kHz Plot on Channel 39



Date: 20.AUG.2020 05:23:48

Bluetooth v5.0 LE


PSD 100kHz Plot on Channel 00



Date: 20.AUG.2020 05:31:38




PSD 100kHz Plot on Channel 19



Date: 20.AUG.2020 05:29:28

PSD 100kHz Plot on Channel 39




Date: 20.AUG.2020 05:26:51



Module 2:


Bluetooth v4.2 LE

PSD 100kHz Plot on Channel 00



Date: 18.AUG.2020 21:59:23


PSD 100kHz Plot on Channel 19



Date: 18.AUG.2020 21:49:28




PSD 100kHz Plot on Channel 39



Date: 18.AUG.2020 22:05:30

Bluetooth v5.1 LE


PSD 100kHz Plot on Channel 00



Date: 18.AUG.2020 22:32:08




PSD 100kHz Plot on Channel 19



Date: 18.AUG.2020 22:24:23

PSD 100kHz Plot on Channel 39




Date: 18.AUG.2020 22:35:56

3.3.7 Test Result of Power Spectral Density Plots (3kHz)

Module 1:


Bluetooth v4.2 LE

PSD 3kHz Plot on Channel 00



Date: 20.AUG.2020 05:18:49


PSD 3kHz Plot on Channel 19



Date: 20.AUG.2020 05:22:04




PSD 3kHz Plot on Channel 39



Date: 20.AUG.2020 05:23:37


Bluetooth v5.0 LE

PSD 3kHz Plot on Channel 00




Date: 20.AUG.2020 05:31:27

PSD 3kHz Plot on Channel 19



Date: 20.AUG.2020 05:29:10

PSD 3kHz Plot on Channel 39




Date: 20.AUG.2020 05:26:40

Module 2:


Bluetooth v4.2 LE

PSD 3kHz Plot on Channel 00




Date: 18.AUG.2020 21:58:44

PSD 3kHz Plot on Channel 19



Date: 18.AUG.2020 21:49:03


PSD 3kHz Plot on Channel 39



Date: 18.AUG.2020 22:05:10

Bluetooth v5.1 LE


PSD 3kHz Plot on Channel 00



Date: 18.AUG.2020 22:31:39




PSD 3kHz Plot on Channel 19



Date: 18.AUG.2020 22:23:30

PSD 3kHz Plot on Channel 39



Date: 18.AUG.2020 22:35:30

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges Plots

Module 1:


Bluetooth v4.2 LE

Low Band Edge Plot on Channel 00



Date: 20.AUG.2020 05:19:14

High Band Edge Plot on Channel 39




Date: 20.AUG.2020 05:23:56




Bluetooth v5.0 LE

Low Band Edge Plot on Channel 00



Date: 20.AUG.2020 05:33:18

High Band Edge Plot on Channel 39




Date: 20.AUG.2020 05:27:01



Module 2:


Bluetooth v4.2 LE

Low Band Edge Plot on Channel 00



Date: 18.AUG.2020 22:00:27

High Band Edge Plot on Channel 39




Date: 18.AUG.2020 22:05:48




Bluetooth v5.1 LE

Low Band Edge Plot on Channel 00



Date: 18.AUG.2020 22:32:31

High Band Edge Plot on Channel 39



Date: 18.AUG.2020 22:36:04




3.4.6 Test Result of Conducted Spurious Emission Plots

Module 1:

Bluetooth v4.2 LE

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps


GFSK Channel 00



Date: 20.AUG.2020 05:20:05


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 00




Date: 20.AUG.2020 05:20:13

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 20.AUG.2020 05:22:27

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 20.AUG.2020 05:22:35

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 20.AUG.2020 05:24:07


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 20.AUG.2020 05:24:15


Bluetooth v5.0 LE

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 20.AUG.2020 05:33:32

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 20.AUG.2020 05:33:40

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 20.AUG.2020 05:29:39

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 20.AUG.2020 05:29:47

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 20.AUG.2020 05:27:12

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39




Date: 20.AUG.2020 05:27:20




Module 2:

Bluetooth v4.2 LE

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 00


Date: 18.AUG.2020 22:11:37

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 00

Date: 18.AUG.2020 22:12:01




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 19



Date: 18.AUG.2020 22:13:51


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 19



Date: 18.AUG.2020 22:14:16




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 39



Date: 18.AUG.2020 22:06:13

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 39




Date: 18.AUG.2020 22:06:36




Bluetooth v5.1 LE

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 00



Date: 18.AUG.2020 22:32:43


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 00



Date: 18.AUG.2020 22:32:58




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 19



Date: 18.AUG.2020 22:24:38


Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 19



Date: 18.AUG.2020 22:24:54




Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 39



Date: 18.AUG.2020 22:36:18

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps
GFSK Channel 39



Date: 18.AUG.2020 22:36:34

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Nov. 02, 2019	Aug. 18, 2020~ Aug. 20, 2020	Nov. 01, 2020	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 15, 2020	Aug. 18, 2020~ Aug. 20, 2020	Jan. 14, 2021	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 08, 2020	Aug. 18, 2020~ Aug. 20, 2020	Jan. 07, 2021	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz; Max 30dBm	Oct. 18, 2019	Aug. 24, 2020	Oct. 17, 2020	Radiation (03CH05-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz, MAX 30dB	Apr. 15, 2020	Aug. 24, 2020	Apr. 14, 2021	Radiation (03CH05-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 10, 2019	Aug. 24, 2020	Nov. 09, 2020	Radiation (03CH05-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz~1GHz	May 30, 2020	Aug. 24, 2020	May 29, 2021	Radiation (03CH05-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218652	1GHz~18GHz	Apr. 26, 2020	Aug. 24, 2020	Apr. 25, 2021	Radiation (03CH05-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 10, 2019	Aug. 24, 2020	Nov. 09, 2020	Radiation (03CH05-KS)
Amplifier	SONOMA	310N	187289	9kHz~1GHz	Apr. 14, 2020	Aug. 24, 2020	Apr. 13, 2021	Radiation (03CH05-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 08, 2020	Aug. 24, 2020	Jan. 07, 2021	Radiation (03CH05-KS)
high gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	2012228	1GHz~18GHz	Oct. 18, 2019	Aug. 24, 2020	Oct. 17, 2020	Radiation (03CH05-KS)
Amplifier	Keysight	83017A	MY53270316	500MHz~26.5GHz	Oct. 18, 2019	Aug. 24, 2020	Oct. 17, 2020	Radiation (03CH05-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Aug. 24, 2020	NCR	Radiation (03CH05-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Aug. 24, 2020	NCR	Radiation (03CH05-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Aug. 24, 2020	NCR	Radiation (03CH05-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 14, 2020	Aug. 13, 2020	Apr. 13, 2021	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 18, 2019	Aug. 13, 2020	Oct. 17, 2020	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Oct. 28, 2019	Aug. 13, 2020	Oct. 27, 2020	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 18, 2019	Aug. 13, 2020	Oct. 17, 2020	Conduction (CO01-KS)

NCR: No Calibration Required

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.9dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------



Appendix A. Conducted Test Results

Module 1

Report Number : FR072404B

Bluetooth Low Energy

Test Engineer:	Lex Wu	Temperature:	20~26	°C
Test Date:	2020/8/18~2020/8/20	Relative Humidity:	40~51	%

TEST RESULTS DATA **6dB and 99% Occupied Bandwidth**

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.025	0.67	0.50	Pass
BLE	1Mbps	1	19	2440	1.023	0.67	0.50	Pass
BLE	1Mbps	1	39	2480	1.025	0.67	0.50	Pass

TEST RESULTS DATA **Peak Power Table**

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	1.48	30.00	1.60	3.08	36.00	Pass
BLE	1Mbps	1	19	2440	0.73	30.00	1.60	2.33	36.00	Pass
BLE	1Mbps	1	39	2480	1.13	30.00	1.60	2.73	36.00	Pass

TEST RESULTS DATA **Average Power Table** **(Reporting Only)**

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	2.04	1.12
BLE	1Mbps	1	19	2440	2.04	0.62
BLE	1Mbps	1	39	2480	2.04	1.09

TEST RESULTS DATA **Peak Power Density**

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	-0.15	-14.66	1.60	8.00	Pass
BLE	1Mbps	1	19	2440	-1.03	-15.57	1.60	8.00	Pass
BLE	1Mbps	1	39	2480	-0.11	-14.69	1.60	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

Bluetooth Low Energy

Test Engineer:	Lex Wu	Temperature:	20~26	°C
Test Date:	2020/8/18~2020/8/20	Relative Humidity:	40~51	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.028	1.14	0.50	Pass
BLE	2Mbps	1	19	2440	2.028	1.15	0.50	Pass
BLE	2Mbps	1	39	2480	2.033	1.15	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	1.65	30.00	1.60	3.25	36.00	Pass
BLE	2Mbps	1	19	2440	0.95	30.00	1.60	2.55	36.00	Pass
BLE	2Mbps	1	39	2480	1.30	30.00	1.60	2.90	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	2Mbps	1	0	2402	4.83	1.05
BLE	2Mbps	1	19	2440	4.83	0.52
BLE	2Mbps	1	39	2480	4.83	0.78

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	-0.35	-18.63	1.60	8.00	Pass
BLE	2Mbps	1	19	2440	-1.15	-19.24	1.60	8.00	Pass
BLE	2Mbps	1	39	2480	-0.22	-18.42	1.60	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

Module 2

Report Number : FR072404B

Bluetooth Low Energy

Test Engineer:	Kib shi	Temperature:	20~26	°C
Test Date:	2020/8/18~2020/8/20	Relative Humidity:	40~51	%

TEST RESULTS DATA 6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.041	0.65	0.50	Pass
BLE	1Mbps	1	19	2440	1.041	0.65	0.50	Pass
BLE	1Mbps	1	39	2480	1.041	0.65	0.50	Pass

TEST RESULTS DATA Peak Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	4.85	30.00	1.60	6.45	36.00	Pass
BLE	1Mbps	1	19	2440	4.78	30.00	1.60	6.38	36.00	Pass
BLE	1Mbps	1	39	2480	3.57	30.00	1.60	5.17	36.00	Pass

TEST RESULTS DATA Average Power Table (Reporting Only)

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	2.04	4.72
BLE	1Mbps	1	19	2440	2.04	4.36
BLE	1Mbps	1	39	2480	2.04	3.54

TEST RESULTS DATA Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	-10.67	-17.14	1.60	8.00	Pass
BLE	1Mbps	1	19	2440	-11.89	-18.54	1.60	8.00	Pass
BLE	1Mbps	1	39	2480	-11.63	-18.35	1.60	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

Bluetooth Low Energy

Test Engineer:	Kib shi	Temperature:	20~26	°C
Test Date:	2020/8/18~2020/8/20	Relative Humidity:	40~51	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.028	0.85	0.50	Pass
BLE	2Mbps	1	19	2440	2.038	0.86	0.50	Pass
BLE	2Mbps	1	39	2480	2.033	0.85	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	4.85	30.00	1.60	6.45	36.00	Pass
BLE	2Mbps	1	19	2440	4.84	30.00	1.60	6.44	36.00	Pass
BLE	2Mbps	1	39	2480	5.12	30.00	1.60	6.72	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	2Mbps	1	0	2402	4.83	4.78
BLE	2Mbps	1	19	2440	4.83	4.65
BLE	2Mbps	1	39	2480	4.83	5.45

TEST RESULTS DATA
Peak Power Density


Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	-8.67	-19.19	1.60	8.00	Pass
BLE	2Mbps	1	19	2440	-10.23	-20.75	1.60	8.00	Pass
BLE	2Mbps	1	39	2480	-11.60	-22.09	1.60	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.



Appendix B. AC Conducted Emission Test Results

Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS
Condition : 15C RSS247-QP LISN-L-191028-CN02 LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	0.150	41.85	-24.15	66.00	31.30	0.07	10.48	QP
2 *	0.150	36.05	-19.95	56.00	25.50	0.07	10.48	Average
3	0.192	33.06	-30.87	63.93	22.59	0.09	10.38	QP
4	0.192	24.06	-29.87	53.93	13.59	0.09	10.38	Average
5	0.497	33.27	-22.78	56.05	22.90	0.13	10.24	QP
6	0.497	24.67	-21.38	46.05	14.30	0.13	10.24	Average
7	20.377	30.88	-29.12	60.00	18.20	2.18	10.50	QP
8	20.377	19.78	-30.22	50.00	7.10	2.18	10.50	Average
9	21.260	31.69	-28.31	60.00	18.89	2.28	10.52	QP
10	21.260	20.99	-29.01	50.00	8.19	2.28	10.52	Average
11	25.591	33.36	-26.64	60.00	20.20	2.59	10.57	QP
12	25.591	23.46	-26.54	50.00	10.30	2.59	10.57	Average



Test Engineer :	Amos Zhang	Temperature :	25.3~26.2℃
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : 15C RSS247-QP LISN-N-191028-CN02 NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1 *	0.507	42.97	-13.03	56.00	32.50	0.23	10.24	QP
2	0.507	32.57	-13.43	46.00	22.10	0.23	10.24	Average
3	1.487	33.25	-22.75	56.00	22.60	0.42	10.23	QP
4	1.487	22.15	-23.85	46.00	11.50	0.42	10.23	Average
5	2.884	32.78	-23.22	56.00	21.90	0.64	10.24	QP
6	2.884	21.48	-24.52	46.00	10.60	0.64	10.24	Average
7	18.328	35.58	-24.42	60.00	22.60	2.52	10.46	QP
8	18.328	24.28	-25.72	50.00	11.30	2.52	10.46	Average
9	19.845	36.15	-23.85	60.00	22.90	2.76	10.49	QP
10	19.845	25.45	-24.55	50.00	12.20	2.76	10.49	Average
11	22.180	34.84	-25.16	60.00	21.30	3.01	10.53	QP
12	22.180	25.74	-24.26	50.00	12.20	3.01	10.53	Average

Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix C. Radiated Spurious Emission

Module 1

Bluetooth v4.2 LE

15C 2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2388.91	54.73	-19.27	74	47.68	31.2	7.5	31.65	328	177	P	H
		2361.87	45.16	-8.84	54	38.2	31.18	7.44	31.66	328	177	A	H
		2402	95.49	-	-	88.44	31.2	7.5	31.65	328	177	P	H
		2402	94.5	-	-	87.45	31.2	7.5	31.65	328	177	A	H
		2355.11	54.83	-19.17	74	47.88	31.18	7.44	31.67	259	237	P	V
		2329.24	45.13	-8.87	54	38.26	31.16	7.38	31.67	259	237	A	V
		2402	97.05	-	-	90	31.2	7.5	31.65	259	237	P	V
		2402	96.47	-	-	89.42	31.2	7.5	31.65	259	237	A	V
BLE CH 39 2480MHz		2486.92	55.91	-18.09	74	48.08	31.77	7.64	31.58	348	184	P	H
		2494.18	46.2	-7.8	54	38.2	31.89	7.67	31.56	348	184	A	H
		2480	93.29	-	-	85.46	31.77	7.64	31.58	348	184	P	H
		2480	92.77	-	-	84.94	31.77	7.64	31.58	348	184	A	H
		2497	55.97	-18.03	74	47.97	31.89	7.67	31.56	284	217	P	V
		2483.5	46.15	-7.85	54	38.32	31.77	7.64	31.58	284	217	A	V
		2480	95.37	-	-	87.54	31.77	7.64	31.58	284	217	P	V
		2480	94.83	-	-	87	31.77	7.64	31.58	284	217	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		4806	38.44	-35.56	74	54	33.7	10.78	60.04	300	0	P	H
		4806	39.03	-34.97	74	54.59	33.7	10.78	60.04	300	0	P	V
BLE CH 19 2440MHz		4878	38.63	-35.37	74	54.02	33.77	10.87	60.03	300	0	P	H
		7320	42.17	-31.83	74	53.4	35.89	13.4	60.52	300	0	P	H
		4878	38.52	-35.48	74	53.91	33.77	10.87	60.03	300	0	P	V
		7320	42.6	-31.4	74	53.83	35.89	13.4	60.52	300	0	P	V
BLE CH 39 2480MHz		4962	38.61	-35.39	74	53.79	33.85	10.98	60.01	100	360	P	H
		7440	41.74	-32.26	74	52.66	36.11	13.51	60.54	100	360	P	H
		4962	38.58	-35.42	74	53.76	33.85	10.98	60.01	100	360	P	V
		7440	41.32	-32.68	74	52.24	36.11	13.51	60.54	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		63.95	20.52	-19.48	40	39.69	12.14	1.81	33.12	-	-	P	H
		98.87	19.87	-23.63	43.5	34.73	15.97	2.25	33.08	-	-	P	H
		111.48	19.77	-23.73	43.5	33.4	17.11	2.38	33.12	-	-	P	H
		161.92	20.32	-23.18	43.5	34.3	16.34	2.88	33.2	-	-	P	H
		186.17	20.35	-23.15	43.5	35.55	14.92	3.08	33.2	-	-	P	H
		954.41	29.78	-16.22	46	23.9	30.96	6.93	32.01	100	0	P	H
		50.37	25.99	-14.01	40	43.19	14.4	1.6	33.2	-	-	P	V
		66.86	26.33	-13.67	40	45.3	12.32	1.85	33.14	100	0	P	V
		95.96	26.81	-16.69	43.5	42.04	15.58	2.21	33.02	-	-	P	V
		109.54	26.98	-16.52	43.5	40.73	17	2.37	33.12	-	-	P	V
		184.23	24.91	-18.59	43.5	40.07	14.98	3.06	33.2	-	-	P	V
		915.61	28.49	-17.51	46	24.06	29.7	6.8	32.07	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Bluetooth v5.0 LE

15C 2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2381.24	54.79	-19.21	74	47.78	31.19	7.47	31.65	328	173	P	H
		2348.48	45.69	-8.31	54	38.78	31.17	7.41	31.67	328	173	A	H
		2402	94.87	-	-	87.82	31.2	7.5	31.65	328	173	P	H
		2402	93.94	-	-	86.89	31.2	7.5	31.65	328	173	A	H
		2360.7	55.55	-18.45	74	48.59	31.18	7.44	31.66	258	237	P	V
		2384.36	45.74	-8.26	54	38.73	31.19	7.47	31.65	258	237	A	V
		2402	96.98	-	-	89.93	31.2	7.5	31.65	258	237	P	V
		2402	95.58	-	-	88.53	31.2	7.5	31.65	258	237	A	V
BLE CH 39 2480MHz		2497.66	55.99	-18.01	74	47.99	31.89	7.67	31.56	352	187	P	H
		2483.5	46.88	-7.12	54	39.05	31.77	7.64	31.58	352	187	A	H
		2480	93.36	-	-	85.53	31.77	7.64	31.58	352	187	P	H
		2480	91.8	-	-	83.97	31.77	7.64	31.58	352	187	A	H
		2497.66	56.06	-17.94	74	48.06	31.89	7.67	31.56	285	216	P	V
		2483.5	47.54	-6.46	54	39.71	31.77	7.64	31.58	285	216	A	V
		2480	95.47	-	-	87.64	31.77	7.64	31.58	285	216	P	V
		2480	94.04	-	-	86.21	31.77	7.64	31.58	285	216	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		4806	39.09	-34.91	74	54.65	33.7	10.78	60.04	300	0	P	H
		4806	40.64	-33.36	74	56.2	33.7	10.78	60.04	300	0	P	V
BLE CH 19 2440MHz		4878	39.72	-34.28	74	55.11	33.77	10.87	60.03	100	360	P	H
		7320	42.72	-31.28	74	53.95	35.89	13.4	60.52	100	360	P	H
		4878	39.88	-34.12	74	55.27	33.77	10.87	60.03	100	360	P	V
		7320	42.06	-31.94	74	53.29	35.89	13.4	60.52	100	360	P	V
BLE CH 39 2480MHz		4962	40.68	-33.32	74	55.86	33.85	10.98	60.01	300	0	P	H
		7440	42.29	-31.71	74	53.21	36.11	13.51	60.54	300	0	P	H
		4962	39.5	-34.5	74	54.68	33.85	10.98	60.01	300	0	P	V
		7440	41.3	-32.7	74	52.22	36.11	13.51	60.54	300	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		30	18.86	-21.14	40	25.82	25.1	1.24	33.3	-	-	P	H
		62.98	14.96	-25.04	40	34.23	12.08	1.79	33.14	-	-	P	H
		128.94	17.76	-25.74	43.5	30.76	17.6	2.56	33.16	-	-	P	H
		186.17	22.67	-20.83	43.5	37.87	14.92	3.08	33.2	-	-	P	H
		258.92	18.64	-27.36	46	27.87	20.26	3.63	33.12	-	-	P	H
		959.26	29.59	-16.41	46	23.74	30.92	6.95	32.02	100	0	P	H
		51.34	27.28	-12.72	40	44.69	14.15	1.62	33.18	100	0	P	V
		97.9	28.1	-15.4	43.5	43.08	15.84	2.24	33.06	-	-	P	V
		110.51	28.49	-15.01	43.5	42.18	17.05	2.38	33.12	-	-	P	V
		166.77	29.3	-14.2	43.5	43.64	15.94	2.92	33.2	-	-	P	V
		186.17	26.64	-16.86	43.5	41.84	14.92	3.08	33.2	-	-	P	V
		956.35	29.02	-16.98	46	23.14	30.95	6.94	32.01	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Module 2

Bluetooth v4.2 LE

15C 2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2329.76	54.7	-19.3	74	47.83	31.16	7.38	31.67	389	157	P	H
		2376.69	45.01	-8.99	54	38.01	31.19	7.47	31.66	389	157	A	H
		2402	99.42	-	-	92.37	31.2	7.5	31.65	389	157	P	H
		2402	98.67	-	-	91.62	31.2	7.5	31.65	389	157	A	H
		2375.91	54.99	-19.01	74	47.99	31.19	7.47	31.66	102	128	P	V
		2369.67	45.21	-8.79	54	38.21	31.19	7.47	31.66	102	128	A	V
		2402	97.23	-	-	90.18	31.2	7.5	31.65	102	128	P	V
		2402	96.45	-	-	89.4	31.2	7.5	31.65	102	128	A	V
BLE CH 39 2480MHz		2483.68	57.2	-16.8	74	49.37	31.77	7.64	31.58	324	163	P	H
		2483.5	46.87	-7.13	54	39.04	31.77	7.64	31.58	324	163	A	H
		2480	96.65	-	-	88.82	31.77	7.64	31.58	324	163	P	H
		2480	95.88	-	-	88.05	31.77	7.64	31.58	324	163	A	H
		2483.86	56.11	-17.89	74	48.28	31.77	7.64	31.58	104	17	P	V
		2483.56	46.27	-7.73	54	38.44	31.77	7.64	31.58	104	17	A	V
		2480	93.63	-	-	85.8	31.77	7.64	31.58	104	17	P	V
		2480	92.84	-	-	85.01	31.77	7.64	31.58	104	17	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		4806	37.81	-36.19	74	53.37	33.7	10.78	60.04	100	360	P	H
		4806	38.78	-35.22	74	54.34	33.7	10.78	60.04	100	360	P	V
BLE CH 19 2440MHz		4878	41.06	-32.94	74	56.45	33.77	10.87	60.03	100	360	P	H
		7320	50.54	-23.46	74	61.77	35.89	13.4	60.52	100	360	P	H
		4878	39.87	-34.13	74	55.26	33.77	10.87	60.03	100	360	P	V
		7320	46.24	-27.76	74	57.47	35.89	13.4	60.52	100	360	P	V
BLE CH 39 2480MHz		4962	39.94	-34.06	74	55.12	33.85	10.98	60.01	300	0	P	H
		7440	48.09	-25.91	74	59.01	36.11	13.51	60.54	300	0	P	H
		4962	39.17	-34.83	74	54.35	33.85	10.98	60.01	300	0	P	V
		7440	45.71	-28.29	74	56.63	36.11	13.51	60.54	300	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		33.88	30.45	-9.55	40	39.37	22.98	1.32	33.22	100	0	P	H
		39.7	28.53	-11.47	40	40.42	19.8	1.43	33.12	-	-	P	H
		56.19	25.49	-14.51	40	44.02	12.9	1.69	33.12	-	-	P	H
		93.05	27.3	-16.2	43.5	43.01	15.19	2.18	33.08	-	-	P	H
		314.21	19.45	-26.55	46	29.08	19.54	4	33.17	-	-	P	H
		772.05	27.48	-18.52	46	25.4	28.2	6.24	32.36	-	-	P	H
		33.88	20.3	-19.7	40	29.22	22.98	1.32	33.22	-	-	P	V
		62.01	20.62	-19.38	40	39.98	12.02	1.78	33.16	-	-	P	V
		94.02	23.08	-20.42	43.5	38.61	15.32	2.19	33.04	-	-	P	V
		526.64	23.28	-22.72	46	26.18	24.74	5.16	32.8	-	-	P	V
		929.19	28.66	-17.34	46	23.64	30.22	6.84	32.04	100	0	P	V
		962.17	28.42	-25.58	54	22.58	30.9	6.96	32.02	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Bluetooth v5.1 LE

15C 2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2357.71	54.85	-19.15	74	47.9	31.18	7.44	31.67	307	141	P	H
		2371.62	45.52	-8.48	54	38.52	31.19	7.47	31.66	307	141	A	H
		2402	99.41	-	-	92.36	31.2	7.5	31.65	307	141	P	H
		2402	97.65	-	-	90.6	31.2	7.5	31.65	307	141	A	H
		2370.58	54.63	-19.37	74	47.63	31.19	7.47	31.66	133	139	P	V
		2361.61	45.54	-8.46	54	38.58	31.18	7.44	31.66	133	139	A	V
		2402	96.83	-	-	89.78	31.2	7.5	31.65	133	139	P	V
		2402	95.12	-	-	88.07	31.2	7.5	31.65	133	139	A	V
BLE CH 39 2480MHz		2483.56	58.71	-15.29	74	50.88	31.77	7.64	31.58	325	156	P	H
		2483.5	49.02	-4.98	54	41.19	31.77	7.64	31.58	325	156	A	H
		2480	97.52	-	-	89.69	31.77	7.64	31.58	325	156	P	H
		2480	95.7	-	-	87.87	31.77	7.64	31.58	325	156	A	H
		2483.5	56.33	-17.67	74	48.5	31.77	7.64	31.58	339	268	P	V
		2483.5	47.74	-6.26	54	39.91	31.77	7.64	31.58	339	268	A	V
		2480	94.5	-	-	86.67	31.77	7.64	31.58	339	268	P	V
		2480	92.69	-	-	84.86	31.77	7.64	31.58	339	268	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		4806	38.16	-35.84	74	53.72	33.7	10.78	60.04	100	360	P	H
		4806	38.55	-35.45	74	54.11	33.7	10.78	60.04	100	360	P	V
BLE CH 19 2440MHz		4878	39.86	-34.14	74	55.25	33.77	10.87	60.03	100	360	P	H
		7320	49.63	-24.37	74	60.86	35.89	13.4	60.52	100	360	P	H
		4878	40.28	-33.72	74	55.67	33.77	10.87	60.03	100	360	P	V
		7320	45.12	-28.88	74	56.35	35.89	13.4	60.52	100	360	P	V
BLE CH 39 2480MHz		4962	39.35	-34.65	74	54.53	33.85	10.98	60.01	100	360	P	H
		7440	47.07	-26.93	74	57.99	36.11	13.51	60.54	100	360	P	H
		4962	41.23	-32.77	74	56.41	33.85	10.98	60.01	100	360	P	V
		7440	44.95	-29.05	74	55.87	36.11	13.51	60.54	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		33.88	30.45	-9.55	40	39.37	22.98	1.32	33.22	100	0	P	H
		39.7	28.53	-11.47	40	40.42	19.8	1.43	33.12	-	-	P	H
		56.19	25.49	-14.51	40	44.02	12.9	1.69	33.12	-	-	P	H
		93.05	27.3	-16.2	43.5	43.01	15.19	2.18	33.08	-	-	P	H
		314.21	19.45	-26.55	46	29.08	19.54	4	33.17	-	-	P	H
		772.05	27.48	-18.52	46	25.4	28.2	6.24	32.36	-	-	P	H
		33.88	20.3	-19.7	40	29.22	22.98	1.32	33.22	-	-	P	V
		62.01	20.62	-19.38	40	39.98	12.02	1.78	33.16	-	-	P	V
		94.02	23.08	-20.42	43.5	38.61	15.32	2.19	33.04	-	-	P	V
		526.64	23.28	-22.72	46	26.18	24.74	5.16	32.8	-	-	P	V
		929.19	28.66	-17.34	46	23.64	30.22	6.84	32.04	100	0	P	V
		962.17	28.42	-25.58	54	22.58	30.9	6.96	32.02	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



For Co-location

15C 2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 39 2480MHz & LTE Band 13		2490.76	56.12	-17.88	74	48.14	31.89	7.67	31.58	100	182	P	H
		2483.5	46.92	-7.08	54	39.09	31.77	7.64	31.58	100	182	A	H
		2480	92.37	-	-	84.54	31.77	7.64	31.58	100	182	P	H
		2480	90.95	-	-	83.12	31.77	7.64	31.58	100	182	A	H
		2490.82	55.72	-18.28	74	47.74	31.89	7.67	31.58	313	217	P	V
		2483.5	47.43	-6.57	54	39.6	31.77	7.64	31.58	313	217	A	V
		2480	95.01	-	-	87.18	31.77	7.64	31.58	313	217	P	V
		2480	93.59	-	-	85.76	31.77	7.64	31.58	313	217	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



BLE (Harmonic @ 3m)

WIFI Ant. 1+2	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 39 2480MHz & LTE Band 13		4962	39.91	-34.09	74	55.09	33.85	10.98	60.01	300	0	P	H
		7440	42.17	-31.83	74	53.09	36.11	13.51	60.54	300	0	P	H
		4962	39.52	-34.48	74	54.7	33.85	10.98	60.01	300	0	P	V
		7440	42.58	-31.42	74	53.5	36.11	13.51	60.54	300	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)


= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
BLE 1Mbps	62.50	0.391	2.556	2.7kHz
BLE 2Mbps	32.87	0.206	4.859	5.1kHz

BLE 1Mbps





BLE 2Mbps

