

FCC SAR Test Report

Report No. : W7L-P21080009SA02

Applicant : Honeywell International Inc
Honeywell Safety and Productivity Solutions

Address : 9680 Old Bailes Road, Fort Mill, SC 29707 United States

Manufacturer : Honeywell International Inc
Honeywell Safety and Productivity Solutions

Address : 9680 Old Bailes Road, Fort Mill, SC 29707 United States

Product : Mobile Computer

FCC ID : HD5-CT45PL1NE

Brand : Honeywell

Model No. : CT45P-L1N-E

Standards : FCC 47 CFR Part 2 (2.1093) / IEEE C95.1:1992 / IEEE 1528:2013
KDB 865664 D01 v01r04 / KDB 865664 D02 v01r02 / KDB 248227 D01 v02r02
KDB 447498 D01 v06 / KDB 648474 D04 v01r03 / KDB 941225 D01 v03r01
KDB 941225 D05 v02r05 / KDB 941225 D05A v01r02 / KDB 941225 D06 v02r01


Sample Received Date : Jul. 26, 2021

Date of Testing : Sep. 06, 2021 ~ Sep. 08, 2021

FCC Designation No. : CN1171

CERTIFICATION: The above equipment have been tested by **BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by A2LA or any government agencies.

Prepared By :



Jerry Chen / Engineer

Approved By :



Luke Lu / Manager



This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	3
1. Summary of Maximum SAR Value	4
2. Description of Equipment Under Test	5
3. SAR Measurement System	7
3.1 Definition of Specific Absorption Rate (SAR)	7
3.2 SPEAG DASY System	7
3.2.1 Robot.....	8
3.2.2 Probes.....	9
3.2.3 Data Acquisition Electronics (DAE)	9
3.2.4 Phantoms	10
3.2.5 Device Holder.....	11
3.2.6 System Validation Dipoles.....	11
3.2.7 Tissue Simulating Liquids.....	12
3.3 SAR System Verification	14
3.4 SAR Measurement Procedure	15
3.4.1 Area & Zoom Scan Procedure	15
3.4.2 Volume Scan Procedure.....	15
3.4.3 Power Drift Monitoring.....	16
3.4.4 Spatial Peak SAR Evaluation	16
3.4.5 SAR Averaged Methods	16
4. SAR Measurement Evaluation	17
4.1 EUT Configuration and Setting.....	17
4.2 EUT Testing Position	25
4.2.1 Head Exposure Conditions.....	25
4.2.2 Body-worn Accessory Exposure Conditions.....	27
4.2.3 Hotspot Mode Exposure Conditions	28
4.2.4 Extremity Exposure Conditions	29
4.2.5 Simultaneous Transmission Possibilities.....	29
4.3 Tissue Verification	30
4.4 System Verification.....	30
4.5 Maximum Output Power.....	31
4.5.1 Maximum Conducted Power	31
4.5.2 Measured Conducted Power Result.....	38
4.6 SAR Testing Results	65
4.6.1 SAR Test Reduction Considerations	65
4.6.2 SAR Results for Head Exposure Condition	67
4.6.3 SAR Results for Body-worn Exposure Condition (Separation Distance is 1.0 cm Gap).....	68
4.6.4 SAR Results for Hotspot Exposure Condition (Separation Distance is 1.0 cm Gap).....	69
4.6.5 SAR Results for Extremity Exposure Condition (Separation Distance is 0 cm Gap)	70
4.6.6 SAR Measurement Variability.....	71
4.6.7 Simultaneous Multi-band Transmission Evaluation	72
5. Calibration of Test Equipment.....	94
6. Measurement Uncertainty	95
7. Information on the Testing Laboratories	97
Appendix A. SAR Plots of System Verification	
Appendix B. SAR Plots of SAR Measurement	
Appendix C. Calibration Certificate for Probe and Dipole	
Appendix D. Photographs of EUT and Setup	

Release Control Record

Report No.	Reason for Change	Date Issued
W7L-P21080006SA02	Initial release	Sep. 06, 2021
W7L-P21080009SA02	Based on the original report W7L-P21080006SA02 (FCC ID: HD5-CT45PL1N2), change the SIM to 1 Nano SIM and 1 E-SIM and FCC ID, model name. The worse cases of original report was verified.	Sep. 12, 2021

FCC SAR Test Report

1. Summary of Maximum SAR Value

Equipment Class	Mode	Highest Reported Head SAR _{1g} (W/kg)	Highest Reported Body-worn SAR _{1g} (1.0 cm Gap) (W/kg)	Highest Reported Hotspot SAR _{1g} (1.0 cm Gap) (W/kg)	Highest Reported Extremity SAR _{10g} (0 cm Gap) (W/kg)
PCE	GSM850	0.49	0.32	0.32	N/A
	GSM1900	0.11	1.19	1.19	N/A
	WCDMA II	0.29	1.19	1.19	N/A
	WCDMA IV	0.24	1.18	1.18	N/A
	WCDMA V	0.40	0.35	0.35	N/A
	LTE 2	N/A	N/A	N/A	N/A
	LTE 4	N/A	N/A	N/A	N/A
	LTE 5	0.59	0.48	0.48	N/A
	LTE 7	0.15	0.93	1.21	1.77
	LTE 12	0.20	0.26	0.26	N/A
	LTE 13	0.43	0.52	0.52	N/A
	LTE 14	0.30	0.37	0.37	N/A
	LTE 17	N/A	N/A	N/A	N/A
	LTE 25	0.18	0.89	0.89	N/A
	LTE 26	0.29	0.31	0.31	N/A
	LTE 30	0.28	1.00	1.19	N/A
	LTE 38	N/A	N/A	N/A	N/A
	LTE 41	0.17	0.66	0.70	N/A
	LTE 66	0.14	1.02	1.02	N/A
	LTE 71	0.29	0.49	0.49	N/A
DTS	2.4G WLAN	0.54	0.12	0.12	N/A
NII	5.2G WLAN	N/A	N/A	1.10	N/A
	5.3G WLAN	0.91	0.57	N/A	1.42
	5.6G WLAN	1.13	0.52	N/A	1.35
	5.8G WLAN	1.25	0.50	0.50	N/A
DSS	Bluetooth	0.10	0.02	0.03	N/A
DXX	NFC	N/A	N/A	N/A	N/A
Highest Simultaneous Transmission SAR		Head (W/kg)	Body-worn (W/kg)	Hotspot (W/kg)	Extremity (W/kg)
		1.55	1.56	1.59	1.77

Note:

- The SAR limit (Head & Body: SAR_{1g} 1.6 W/kg, Extremity: SAR_{10g} 4.0 W/kg) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.

2. Description of Equipment Under Test

EUT Type	Mobile Computer
FCC ID	HD5-CT45PL1NE
Brand Name	Honeywell
Model Name	CT45P-L1N-E
HW Version	1.0
SW Version	OS.11.002-HON.11.002
Tx Frequency Bands (Unit: MHz)	GSM850 : 824.2 ~ 848.8 GSM1900 : 1850.2 ~ 1909.8 WCDMA Band II : 1852.4 ~ 1907.6 WCDMA Band IV : 1712.4 ~ 1752.6 WCDMA Band V : 826.4 ~ 846.6 LTE Band 2 : 1850.7 ~ 1909.3 (1.4M), 1851.5 ~ 1908.5 (3M), 1852.5 ~ 1907.5 (5M), 1855 ~ 1905 (10M), 1857.5 ~ 1902.5 (15M), 1860 ~ 1900 (20M) LTE Band 4 : 1710.7 ~ 1754.3 (1.4M), 1711.5 ~ 1753.5 (3M), 1712.5 ~ 1752.5 (5M), 1715 ~ 1750 (10M), 1717.5 ~ 1747.5 (15M), 1720 ~ 1745 (20M) LTE Band 5 : 824.7 ~ 848.3 (1.4M), 825.5 ~ 847.5 (3M), 826.5 ~ 846.5 (5M), 829 ~ 844 (10M) LTE Band 7 : 2502.5 ~ 2567.5 (5M), 2505 ~ 2565 (10M), 2507.5 ~ 2562.5 (15M), 2510 ~ 2560 (20M) LTE Band 12 : 699.7 ~ 715.3 (1.4M), 700.5 ~ 714.5 (3M), 701.5 ~ 713.5 (5M), 704 ~ 711 (10M) LTE Band 13 : 779.5 ~ 784.5 (5M), 782 (10M) LTE Band 14 : 790.5 ~ 795.5 (5M), 793 (10M) LTE Band 17 : 706.5 ~ 713.5 (5M), 709 ~ 711 (10M) LTE Band 25 : 1850.7 ~ 1914.3 (1.4M), 1851.5 ~ 1913.5 (3M), 1852.5 ~ 1912.5 (5M), 1855 ~ 1910 (10M), 1857.5 ~ 1907.5 (15M), 1860 ~ 1905 (20M) LTE Band 26 : 814.7 ~ 848.3 (1.4M), 815.5 ~ 847.5 (3M), 816.5 ~ 846.5 (5M), 819 ~ 844 (10M), 821.5 ~ 841.5 (15M) LTE Band 30 : 2307.5 ~ 2312.5 (5M), 2310 (10M) LTE Band 38 : 2572.5 ~ 2617.5 (5M), 2575 ~ 2615 (10M), 2577.5 ~ 2612.5 (15M), 2580 ~ 2610 (20M) LTE Band 41 : 2498.5 ~ 2687.5 (5M), 2501 ~ 2685 (10M), 2503.5 ~ 2682.5 (15M), 2506 ~ 2680 (20M) LTE Band 66 : 1710.7 ~ 1779.3 (1.4M), 1711.5 ~ 1778.5 (3M), 1712.5 ~ 1777.5 (5M), 1715 ~ 1775 (10M), 1717.5 ~ 1772.5 (15M), 1720 ~ 1770 (20M) LTE Band 71 : 665.5 ~ 695.5 (5M), 668 ~ 693 (10M), 670.5 ~ 690.5 (15M), 673 ~ 688 (20M) WLAN : 2412 ~ 2462, 5180 ~ 5240, 5260 ~ 5320, 5500 ~ 5720, 5745 ~ 5825 Bluetooth : 2402 ~ 2480 NFC : 13.56
Uplink Modulations	GSM & GPRS & EDGE : GMSK, 8PSK WCDMA : BPSK, QPSK CDMA : QPSK LTE : QPSK, 16QAM, 64QAM 802.11b : DSSS 802.11a/g/n/ac : OFDM Bluetooth : GFSK, $\pi/4$ -DQPSK, 8-DPSK NFC : ASK
Maximum Tune-up Conducted Power (Unit: dBm)	Please refer to section 4.6.1 of this report.
Antenna Type	WLAN: PIFA Antenna WWAN: PIFA Antenna
EUT Stage	Identical Prototype

Note:

- The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.
- This device supports both LTE B2/B4/B38 and B25/B66/B41. Since the supported frequency span for LTE B2/B4/B38 falls completely within the LTE B25/B66/B41, they have the same target power, and share the same transmission path, therefore SAR was only assessed for LTE B25/B66/B41.

FCC SAR Test Report

3. According to the product equivalence statement provided by the manufacturer for model CT45P-L1N-2 and CT45P-L1N-E, Model CT45P-L1N-E Verify the conducted power and worst case of the original report (W7L-P21080006SA02, FCC ID: HD5-CT45PL1N2).
4. This product includes the following four SKU which hardware is exactly same, the difference is described as following, Sample 1 was full test, sample 2 verify the worst case.

SAMPLE	EUT CONFIGURATION INFORMATION
1	SKU ID:CT45-L1N-37D1E0G ,Assembled Scanner Imager: 7-S0703
2	SKU ID:CT45-L1N-38D1E0G ,Assembled Scanner Imager: 8 – N6803/S0803
3	SKU ID: CT45-L1N-38D1E0T , Assembled Scanner Imager: 8 – N6803/S0803 for Turkey Only
4	SKU ID: CT45-L1N-37D1E0T , Assembled with Scanner: 7-S0703 for Turkey Only

List of Accessory:

Battery	Brand Name	Honeywell
	Model Name	CT50-BTSC
	Power Rating	3.85 Vdc, 4020mAh
	Type	Li-ion

3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.




Fig-3.1 DASY System Setup

3.2.1 Robot

The DASY system uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ± 0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)



Fig-3.2 DASY5

FCC SAR Test Report

3.2.2 Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

Model	EX3DV4	
Construction	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μ W/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

Model	ES3DV3	
Construction	Symmetrical design with triangular core. Interleaved sensors. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 4 GHz Linearity: ± 0.2 dB	
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	5 μ W/g to 100 mW/g Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm	

3.2.3 Data Acquisition Electronics (DAE)

Model	DAE3, DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	$< 5\mu$ V (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	

FCC SAR Test Report

3.2.4 Phantoms

Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	

Model	ELI	
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	

FCC SAR Test Report

3.2.5 Device Holder

Model	Mounting Device	
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	


Model	Laptop Extensions Kit	
Construction	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
Material	POM, Acrylic glass, Foam	

3.2.6 System Validation Dipoles

Model	D-Serial	
Construction	Symmetrical dipole with 1/4 balun. Enables measurement of feed point impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	750 MHz to 5800 MHz	
Return Loss	> 20 dB	
Power Capability	> 100 W (f < 1GHz), > 40 W (f > 1GHz)	

3.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.



The dielectric properties of the head tissue simulating liquids are defined in IEEE 1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

FCC SAR Test Report

Table-3.1 Targets of Tissue Simulating Liquid

Frequency (MHz)	Target Permittivity	Range of $\pm 5\%$	Target Conductivity	Range of $\pm 5\%$
For Head				
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26
1640	40.3	38.3 ~ 42.3	1.29	1.23 ~ 1.35
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2300	39.5	37.5 ~ 41.5	1.67	1.59 ~ 1.75
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89
5300	35.9	34.1 ~ 37.7	4.76	4.52 ~ 5.00
5500	35.6	33.8 ~ 37.4	4.96	4.71 ~ 5.21
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53

The following table gives the recipes for tissue simulating liquids.

Table-3.2 Recipes of Tissue Simulating Liquid

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
H750	0.2	-	0.2	1.5	56.0	-	42.1	-
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H900	0.2	-	0.2	1.4	58.0	-	40.2	-
H1450	-	43.3	-	0.6	-	-	56.1	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1800	-	44.5	-	0.3	-	-	55.2	-
H1900	-	44.5	-	0.2	-	-	55.3	-
H2000	-	44.5	-	0.1	-	-	55.4	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	28.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.5	17.3

3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.




Fig-3.4 System Verification Setup

The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- Power reference measurement
- Area scan
- Zoom scan
- Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- Make EUT to transmit maximum output power
- Measure conducted output power through RF cable
- Place the EUT in the specific position of phantom
- Perform SAR testing steps on the DASY system
- Record the SAR value

3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664 D01, the resolution for Area and Zoom scan is specified in the table below.

Items	<= 2 GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan ($\Delta x, \Delta y$)	<= 15 mm	<= 12 mm	<= 12 mm	<= 10 mm	<= 10 mm
Zoom Scan ($\Delta x, \Delta y$)	<= 8 mm	<= 5 mm	<= 5 mm	<= 4 mm	<= 4 mm
Zoom Scan (Δz)	<= 5 mm	<= 5 mm	<= 4 mm	<= 3 mm	<= 2 mm
Zoom Scan Volume	>= 30 mm	>= 30 mm	>= 28 mm	>= 25 mm	>= 22 mm

Note:

When zoom scan is required and report SAR is <= 1.4 W/kg, the zoom scan resolution of $\Delta x / \Delta y$ (2-3GHz: <= 8 mm, 3-4GHz: <= 7 mm, 4-6GHz: <= 5 mm) may be applied.

3.4.2 Volume Scan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

3.4.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

4. SAR Measurement Evaluation

4.1 EUT Configuration and Setting

<Connections between EUT and System Simulator>

For WWAN SAR testing, the EUT was linked and controlled by base station emulator (Agilent E5515C is used for GSM/WCDMA/CDMA, and Anritsu MT8820C is used for LTE). Communication between the EUT and the emulator was established by air link. The distance between the EUT and the communicating antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of EUT. The EUT was set from the emulator to radiate maximum output power during SAR testing.

<Considerations Related to GSM / GPRS / EDGE for Setup and Testing>

The maximum multi-slot capability supported by this device is as below.

1. This EUT is class B device
2. This EUT supports GPRS multi-slot class 12 (max. uplink: 4, max. downlink: 4, total timeslots: 5)
3. This EUT supports EDGE multi-slot class 12 (max. uplink: 4, max. downlink: 4, total timeslots: 5)

For GSM850 frequency band, the power control level is set to 5 for GSM mode and GPRS (GMSK: CS1), and set to 8 for EDGE (GMSK: MCS1, 8PSK: MCS9). For GSM1900 frequency band, the power control level is set to 0 for GSM mode and GPRS (GMSK: CS1), and set to 2 for EDGE (GMSK: MCS1, 8PSK: MCS9).

SAR test reduction for GPRS and EDGE modes is determined by the source-based time-averaged output power specified for production units, including tune-up tolerance. The data mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested.

<Considerations Related to WCDMA for Setup and Testing>

WCDMA Handsets Head SAR

SAR for next to the ear head exposure is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to AMR configurations with 12.2 kbps RMC as the primary mode.

WCDMA Handsets Body-worn SAR

SAR for body-worn configurations is measured using a 12.2 kbps RMC with TPC bits configured to all "1's". The 3G SAR test reduction procedure is applied to other spreading codes and multiple DPDCH_n configurations supported by the handset with 12.2 kbps RMC as the primary mode.

Handsets with Release 5 HSDPA

The 3G SAR test reduction procedure is applied to HSDPA body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSDPA using the HSDPA body SAR procedures in the "Release 5 HSDPA Data Devices", for the highest reported SAR body-worn exposure configuration in 12.2 kbps RMC. Handsets with both HSDPA and HSUPA are tested according to Release 6 HSPA test procedures.

FCC SAR Test Report

Handsets with Release 6 HSPA

The 3G SAR test reduction procedure is applied to HSPA (HSPA/HSDPA with RMC) body-worn configurations with 12.2 kbps RMC as the primary mode. Otherwise, SAR is measured for HSPA using the HSPA body SAR procedures in the "Release 6 HSPA Data Devices", for the highest reported body-worn exposure SAR configuration in 12.2 kbps RMC. When VOIP is applicable for next to the ear head exposure in HSPA, the 3G SAR test reduction procedure is applied to HSPA with 12.2 kbps RMC as the primary mode; otherwise, the same HSPA configuration used for body-worn measurements is tested for next to the ear head exposure.

Release 5 HSDPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSDPA is measured using an FRC with H-Set 1 in Sub-test 1 and a 12.2 kbps RMC configured in Test Loop Mode 1, for the highest reported SAR configuration in 12.2 kbps RMC without HSDPA. HSDPA is configured according to the applicable UE category of a test device. The number of HS-DSCH / HS-PDSCHs, HARQ processes, minimum inter-TTI interval, transport block sizes and RV coding sequence are defined by the H-set. To maintain a consistent test configuration and stable transmission conditions, QPSK is used in the H-set for SAR testing. HS-DPCCH should be configured with a CQI feedback cycle of 4 ms and a CQI repetition factor of 2 to maintain a constant rate of active CQI slots. DPCCH and DPDCH gain factors (β_c , β_d), and HS-DPCCH power offset parameters (Δ_{ACK} , Δ_{NACK} , Δ_{CQI}) are set according to values indicated in below. The CQI value is determined by the UE category, transport block size, number of HS-PDSCHs and modulation used in the H-set.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	$\beta_{hs}^{(1)}$	CM (dB) ⁽²⁾	MPR
1	2 / 15	15 / 15	64	2 / 15	4 / 15	0.0	0
2	12 / 15 ⁽³⁾	15 / 15 ⁽³⁾	64	12 / 15 ⁽³⁾	24 / 15	1.0	0
3	15 / 15	8 / 15	64	15 / 8	30 / 15	1.5	0.5
4	15 / 15	4 / 15	64	15 / 4	30 / 15	1.5	0.5

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$.
Note 2: CM = 1 for $\beta_c / \beta_d = 12 / 15$, $\beta_{hs} / \beta_c = 24 / 15$.
Note 3: For subtest 2 the β_c / β_d ratio of 12 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11 / 15$ and $\beta_d = 15 / 15$.

Release 6 HSPA Data Devices

The 3G SAR test reduction procedure is applied to body SAR with 12.2 kbps RMC as the primary mode. Otherwise, body SAR for HSPA is measured with E-DCH Sub-test 5, using H-Set 1 and QPSK for FRC and a 12.2 kbps RMC configured in Test Loop Mode 1 and power control algorithm 2, according to the highest reported body SAR configuration in 12.2 kbps RMC without HSPA. When VOIP applies to head exposure, the 3G SAR test reduction procedure is applied with 12.2 kbps RMC as the primary mode. Otherwise, the same HSPA configuration used for body SAR measurements are applied to head exposure testing. Due to inner loop power control requirements in HSPA, a communication test set is required for output power and SAR tests. The 12.2 kbps RMC, FRC H-set 1 and E-DCH configurations for HSPA are configured according to the β values indicated in below.

Sub-test	β_c	β_d	β_d (SF)	β_c / β_d	$\beta_{hs}^{(1)}$	β_{ec}	β_{ed}	β_{ed} (SF)	β_{ed} (codes)	CM ⁽²⁾ (dB)	MPR (dB)	AG ⁽⁴⁾ Index	E-TFCI
1	11 / 15 ⁽³⁾	15 / 15 ⁽³⁾	64	11 / 15 ⁽³⁾	22 / 15	209 / 225	1039 / 225	4	1	1.0	0.0	20	75

FCC SAR Test Report

2	6 / 15	15 / 15	64	6 / 15	12 / 15	12 / 15	94 / 75	4	1	3.0	2.0	12	67
3	15 / 15	9 / 15	64	15 / 9	30 / 15	30 / 15	$\beta_{ed1}: 47/15$ $\beta_{ed2}: 47/15$	4	2	2.0	1.0	15	92
4	2 / 15	15 / 15	64	2 / 15	4 / 15	2 / 15	56 / 75	4	1	3.0	2.0	17	71
5	15 / 15 (4)	15 / 15 (4)	64	15 / 15 (4)	30 / 15	24 / 15	134 / 15	4	1	1.0	0.0	21	81

Note 1: Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 8 \Leftrightarrow A_{hs} = \beta_{hs} / \beta_c = 30 / 15 \Leftrightarrow \beta_{hs} = 30 / 15 * \beta_c$.

Note 2: CM = 1 for $\beta_c / \beta_d = 12 / 15$, $\beta_{hs} / \beta_c = 24 / 15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c / β_d ratio of 11 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10 / 15$ and $\beta_d = 15 / 15$.

Note 4: For subtest 5 the β_c / β_d ratio of 15 / 15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signaled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 14 / 15$ and $\beta_d = 15 / 15$.

Note 5: Testing UE using E-DPDCH Physical Layer category 1 Sub-test 3 is not required according to TS 25.306 Table 5.1g.

Note 6: β_{ed} cannot be set directly; it is set by Absolute Grant Value.

HSPA+ SAR Guidance

The 3G SAR test reduction procedure is applied to HSPA+ (uplink) with 12.2 kbps RMC as the primary mode. Otherwise, when SAR is required for Rel. 6 HSPA, SAR is required for Rel. 7 HSPA+. Power is measured for HSPA+ that supports uplink 16QAM according to configurations in Table C.11.1.4 of 3GPP TS 34.121-1 to determine SAR test reduction.

DC-HSDPA SAR Guidance

The 3G SAR test reduction procedure is applied to DC-HSDPA with 12.2 kbps RMC as the primary mode. Otherwise, when SAR is required for Rel. 5 HSDPA, SAR is required for Rel. 8 DC-HSDPA. Power is measured for DC-HSDPA according to the H-Set 12, FRC configuration in Table C.8.1.12 of 3GPP TS 34.121-1 to determine SAR test reduction. A primary and a secondary serving HS-DSCH Cell are required to perform the power measurement and for the results to be acceptable.

<Considerations Related to LTE for Setup and Testing>

This device contains LTE transmitter which follows 3GPP standards, is category 5, supports both QPSK 16QAM and 64QAM modulations, and supported LTE band and channel bandwidth is listed in below. The output power was tested per 3GPP TS 36.521-1 maximum transmit procedures for both QPSK 16QAM and 64QAM modulation. The results please refer to section 4.6 of this report.

EUT Supported LTE Band and Channel Bandwidth						
LTE Band	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz
2	V	V	V	V	V	V
4	V	V	V	V	V	V
5	V	V	V	V		
7			V	V	V	V
12	V	V	V	V		
13			V	V		
14			V	V		
17			V	V		
25	V	V	V	V	V	V
26	V	V	V	V	V	
30			V	V		
38			V	V	V	V
41			V	V	V	V
66	V	V	V	V	V	V
71			V	V	V	V

FCC SAR Test Report

The LTE maximum power reduction (MPR) in accordance with 3GPP TS 36.101 is active all times during LTE operation. The allowed MPR for the maximum output power is specified in below.

Modulation	Channel Bandwidth / RB Configurations						LTE MPR Setting (dB)
	BW 1.4 MHz	BW 3 MHz	BW 5 MHz	BW 10 MHz	BW 15 MHz	BW 20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	1
16QAM	<= 5	<= 4	<= 8	<= 12	<= 16	<= 18	1
16QAM	> 5	> 4	> 8	> 12	> 16	> 18	2
64QAM	<= 5	<= 4	<= 8	<= 12	<= 16	<= 18	2
64QAM	> 5	> 4	> 8	> 12	> 16	> 18	3


Note: MPR is according to the standard and implemented in the circuit (mandatory).

In addition, the device is compliant with additional maximum power reduction (A-MPR) requirements defined in 3GPP TS 36.101 section 6.2.4 that was disabled for all FCC compliance testing.

During LTE SAR testing, the related parameters of operating band, channel bandwidth, uplink channel number, modulation type, and RB was set in base station simulator. When the EUT has registered and communicated to base station simulator, the simulator set to make EUT transmitting the maximum radiated power.

TDD-LTE Setup Configurations

According to KDB 941225 D05, SAR testing for TDD-LTE device must be tested using a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by the defined 3GPP TDD-LTE configurations. The TDD-LTE of this device supports frame structure type 2 defined in 3GPP TS 36.211 section 4.2, and the frame structure configuration can be referred to below.



3GPP TS 36.211 Figure 4.2-1: Frame Structure Type 2

Special Subframe Configuration	Normal Cyclic Prefix in Downlink			Extended Cyclic Prefix in Downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink		Normal Cyclic Prefix in Uplink	Extended Cyclic Prefix in Uplink
0	6592·Ts	2192·Ts	2560·Ts	7680·Ts	2192·Ts	2560·Ts
1	19760·Ts			20480·Ts		
2	21952·Ts			23040·Ts		
3	24144·Ts			25600·Ts		
4	26336·Ts			7680·Ts	4384·Ts	5120·Ts

FCC SAR Test Report

5	6592-Ts	4384-Ts	5120-Ts	20480-Ts		
6	19760-Ts			23040-Ts		
7	21952-Ts			12800-Ts		
8	24144-Ts			-	-	-
9	13168-Ts			-	-	-

3GPP TS 36.211 Table 4.2-1: Configuration of Special Subframe

Uplink-Downlink Configuration	Downlink-to-Uplink Switch-Point Periodicity	Subframe Number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

3GPP TS 36.211 Table 4.2-2: Uplink-Downlink Configurations

The variety of different TD-LTE uplink-downlink configurations allows a network operator to allocate the network's capacity between uplink and downlink traffic to meet the needs of the network. The uplink duty cycle of these seven configurations can readily be computed and shown in below.

UL-DL Configuration	0	1	2	3	4	5	6
Highest Duty-Cycle	63.33%	43.33%	23.33%	31.67%	21.67%	11.67%	53.33%

Considering the highest transmission duty cycle, TDD-LTE was tested using Uplink-Downlink Configuration 0 with 6 uplink subframe and 2 special subframe. The special subframe was set to special subframe configuration 7 using extended cyclic prefix uplink. Therefore, SAR testing for TDD-LTE was performed at the maximum output power with highest transmission duty cycle of 63.33%.

Considering the highest transmission duty cycle, TDD-LTE was tested using Uplink-Downlink Configuration 6 with 5 uplink subframe and 2 special subframe. The special subframe was set to special subframe configuration 7 using extended cyclic prefix uplink. Therefore, SAR testing for TDD-LTE was performed at the maximum output power with highest transmission duty cycle of 53.33%.

<Considerations Related to WLAN for Setup and Testing>

In general, various vendor specific external test software and chipset based internal test modes are typically used for SAR measurement. These chipset based test mode utilities are generally hardware and manufacturer dependent, and often include substantial flexibility to reconfigure or reprogram a device. A Wi-Fi device must be configured to transmit continuously at the required data rate, channel bandwidth and signal modulation, using the highest transmission duty factor supported by the test mode tools for SAR measurement. The test frequencies established using test mode must correspond to the actual channel frequencies. When 802.11 frame gaps are accounted for in the transmission, a maximum transmission duty factor of 92 - 96% is typically achievable in most test mode configurations. A minimum transmission duty factor of 85% is required to avoid certain hardware and device implementation issues related to wide range SAR scaling. In addition, a periodic transmission duty factor is required for current generation SAR systems to measure SAR correctly. The reported SAR must be scaled to 100% transmission duty factor to determine compliance at the maximum tune-up tolerance limit.

According to KDB 248227 D01, this device has installed WLAN engineering testing software which can provide continuous transmitting RF signal. During WLAN SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

Initial Test Configuration

An initial test configuration is determined for OFDM transmission modes in 2.4 GHz and 5 GHz bands according to the channel bandwidth, modulation and data rate combination(s) with the highest maximum output power specified for production units in each standalone and aggregated frequency band. When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel in the initial test configuration, for each frequency band.

Subsequent Test Configuration

SAR measurement requirements for the remaining 802.11 transmission mode configurations that have not been tested in the initial test configuration are determined separately for each standalone and aggregated frequency band, in each exposure condition, according to the maximum output power specified for production units. Additional power measurements may be required to determine if SAR measurements are required for subsequent highest output power channels in a subsequent test configuration. When the highest reported SAR for the initial test configuration according to the initial test position or fixed exposure position requirements, is adjusted by the ratio of the subsequent test configuration to initial test configuration specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for that subsequent test configuration.

SAR Test Configuration and Channel Selection

When multiple channel bandwidth configurations in a frequency band have the same specified maximum output power, the initial test configuration is using largest channel bandwidth, lowest order modulation, lowest data rate, and lowest order 802.11 mode (i.e., 802.11a is chosen over 802.11n then 802.11ac or 802.11g is chosen over 802.11n). After an initial test configuration is determined, if multiple test channels have the same measured maximum output power, the channel chosen for SAR measurement is determined according to the following.

1) The channel closest to mid-band frequency is selected for SAR measurement.

FCC SAR Test Report

2) For channels with equal separation from mid-band frequency; for example, high and low channels or two mid-band channels, the higher frequency (number) channel is selected for SAR measurement.

Test Reduction for U-NII-1 (5.2 GHz) and U-NII-2A (5.3 GHz) Bands

For devices that operate in both U-NII bands using the same transmitter and antenna(s), SAR test reduction is determined according to the following.

- 1) When the same maximum output power is specified for both bands, begin SAR measurement in U-NII-2A band by applying the OFDM SAR requirements. If the highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band for that configuration (802.11 mode and exposure condition).
- 2) When different maximum output power is specified for the bands, begin SAR measurement in the band with higher specified maximum output power. The highest reported SAR for the tested configuration is adjusted by the ratio of lower to higher specified maximum output power for the two bands. When the adjusted SAR is ≤ 1.2 W/kg, SAR is not required for the band with lower maximum output power in that test configuration.

<Considerations Related to Bluetooth for Setup and Testing>

This device has installed Bluetooth engineering testing software which can provide continuous transmitting RF signal. During Bluetooth SAR testing, this device was operated to transmit continuously at the maximum transmission duty with specified transmission mode, operating frequency, lowest data rate, and maximum output power.

FCC SAR Test Report

<Duty Cycle of Test Signal>

WLAN2.4G 802.11b: Duty cycle = 1.000

WLAN5G (5180MHz ~ 5720 MHz) 802. 11a: Duty cycle = 2.06 / 2.119 = 0.972

WLAN5G (5745MHz ~ 5825 MHz) 802. 11a: Duty cycle = 2.061 / 2.101 = 0.981

BT_GFSK: Duty cycle = 2.880 / 3.750 = 0.768



4.2 EUT Testing Position

This variant report is made for verification. All the worst SAR configurations specified in the original SAR report was repeated and verified to ensure the device remains compliant.

According to KDB 648474 D04, handsets are tested for SAR compliance in head, body-worn accessory and other use configurations described in the following subsections.

4.2.1 Head Exposure Conditions

Head exposure is limited to next to the ear voice mode operations. Head SAR compliance is tested according to the test positions defined in IEEE Std 1528-2013 using the SAM phantom illustrated as below.

1. Define two imaginary lines on the handset
 - (a) The vertical centerline passes through two points on the front side of the handset - the midpoint of the width w_t of the handset at the level of the acoustic output, and the midpoint of the width w_b of the bottom of the handset.
 - (b) The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
 - (c) The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Fig-4.1 Illustration for Handset Vertical and Horizontal Reference Lines

2. Cheek Position

- (a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.

FCC SAR Test Report

- (b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig-4.2).




Fig-4.2 Illustration for Cheek Position

3. Tilted Position

- (a) To position the device in the “cheek” position described above.
- (b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig-4.3).




Fig-4.3 Illustration for Tilted Position

4.2.2 Body-worn Accessory Exposure Conditions

Body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in KDB 447498 D01 are used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode. When the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.

Body-worn accessories that do not contain metallic or conductive components may be tested according to worst-case exposure configurations, typically according to the smallest test separation distance required for the group of body-worn accessories with similar operating and exposure characteristics. All body-worn accessories containing metallic components are tested in conjunction with the host device.

Body-worn accessory SAR compliance is based on a single minimum test separation distance for all wireless and operating modes applicable to each body-worn accessory used by the host, and according to the relevant voice and/or data mode transmissions and operations. If a body-worn accessory supports voice only operations in its normal and expected use conditions, testing of data mode for body-worn compliance is not required.

A conservative minimum test separation distance for supporting off-the-shelf body-worn accessories that may be acquired by users of consumer handsets is used to test for body-worn accessory SAR compliance. This distance is determined by the handset manufacturer, according to the requirements of Supplement C 01-01. Devices that are designed to operate on the body of users using lanyards and straps, or without requiring additional body-worn accessories, will be tested using a conservative minimum test separation distance $\leq 5 \text{ mm}$ to support compliance.





Fig-4.4 Illustration for Body Worn Position

4.2.3 Hotspot Mode Exposure Conditions

For handsets that support hotspot mode operations, with wireless router capabilities and various web browsing functions, the relevant hand and body exposure conditions are tested according to the hotspot SAR procedures in KDB 941225 D06. A test separation distance of 10 mm is required between the phantom and all surfaces and edges with a transmitting antenna located within 25 mm from that surface or edge. When the form factor of a handset is smaller than 9 cm x 5 cm, a test separation distance of 5 mm (instead of 10 mm) is required for testing hotspot mode. When the separation distance required for body-worn accessory testing is larger than or equal to that tested for hotspot mode, in the same wireless mode and for the same surface of the phone, the hotspot mode SAR data may be used to support body-worn accessory SAR compliance for that particular configuration (surface).



Based on the antenna location shown on appendix D of this report, the SAR testing required for hotspot mode is listed as below.

Antenna	Front Face	Rear Face	Left Side	Right Side	Top Side	Bottom Side
WWAN	V	V	V	V		V
WLAN / BT	V	V		V	V	

4.2.4 Extremity Exposure Conditions

For smart phones with a display diagonal dimension > 15 cm or an overall diagonal dimension > 16 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance.

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions. The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g SAR > 1.2 W/kg. The normal tablet procedures in KDB 616217 are required when the over diagonal dimension of the device is > 20 cm. Hotspot mode SAR is not required when normal tablet procedures are applied. Extremity 10-g SAR is also not required for the front (top) surface of large form factor full size tablets. The more conservative tablet SAR results can be used to support the 10-g extremity SAR for phablet mode.
3. The simultaneous transmission operating configurations applicable to voice and data transmissions for both phone and mini-tablet modes must be taken into consideration separately for 1-g and 10-g SAR to determine the simultaneous transmission SAR test exclusion and measurement requirements for the relevant wireless modes and exposure conditions.

4.2.5 Simultaneous Transmission Possibilities

The simultaneous transmission possibilities for this device are listed as below.

Simultaneous TX Combination	Capable Transmit Configurations	Head	Body-worn	Hotspot	Extremity
1	WWAN + WLAN2.4G		Yes		
2	WWAN + WLAN5G		Yes		
3	WWAN + BT		Yes		
4	WLAN5G + BT		Yes		
5	WWAN+WLAN5G + BT		Yes		

Note :

1. The 2.4G WLAN and 5G WLAN cannot transmit simultaneously.
2. The 2.4G WLAN and BT cannot transmit simultaneously.

FCC SAR Test Report

4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Liquid Temp. (°C)	Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Target Conductivity (σ)	Target Permittivity (ϵ_r)	Conductivity Deviation (%)	Permittivity Deviation (%)
Sep. 07, 2021	Head	750	22.6	0.892	41.542	0.89	41.90	0.22	-0.85
Sep. 07, 2021	Head	835	22.6	0.889	40.759	0.90	41.50	-1.22	-1.79
Sep. 06, 2021	Head	1750	22.7	1.325	40.765	1.37	40.10	-3.28	1.66
Sep. 06, 2021	Head	1900	22.7	1.374	39.599	1.40	40.00	-1.86	-1.00
Sep. 08, 2021	Head	2300	22.7	1.665	39.075	1.67	39.50	-0.30	-1.08
Sep. 08, 2021	Head	2450	22.7	1.782	40.200	1.80	39.20	-1.00	2.55
Sep. 07, 2021	Head	2600	22.6	1.984	37.444	1.96	39.00	1.22	-3.99
Sep. 08, 2021	Head	5250	22.7	4.638	37.088	4.71	35.90	-1.53	3.31
Sep. 08, 2021	Head	5600	22.7	5.048	36.534	5.07	35.50	-0.43	2.91
Sep. 08, 2021	Head	5750	22.6	5.220	36.277	5.22	35.40	0.00	2.48

Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within $\pm 5\%$ of the target values. Liquid temperature during the SAR testing must be within $\pm 2^\circ\text{C}$.

4.4 System Verification

The measuring result for system verification is tabulated as below.

Test Date	Mode	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
Sep. 07, 2021	Head	750	8.58	2.08	8.32	-3.03	1078	7612	1633
Sep. 07, 2021	Head	835	9.49	2.37	9.48	-0.11	4d092	7612	1633
Sep. 06, 2021	Head	1750	36.40	9.21	36.84	1.21	1111	7612	1633
Sep. 06, 2021	Head	1900	40.10	9.97	39.88	-0.55	5d142	7612	1633
Sep. 08, 2021	Head	2300	49.10	12.40	49.60	1.02	1091	7612	1633
Sep. 08, 2021	Head	2450	52.50	13.30	53.20	1.33	735	7612	1633
Sep. 07, 2021	Head	2600	55.30	14.80	59.20	7.05	1077	7612	1633
Sep. 08, 2021	Head	5250	78.50	8.27	82.70	5.35	1203	7612	1633
Sep. 08, 2021	Head	5600	81.60	8.64	86.40	5.88	1203	7612	1633
Sep. 08, 2021	Head	5750	76.70	8.26	82.60	7.69	1203	7612	1633

Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

FCC SAR Test Report

4.5 Maximum Output Power

4.5.1 Maximum Conducted Power

The maximum conducted average power (Unit: dBm) including tune-up tolerance is shown as below.

Mode	GSM850	GSM1900
GSM (GMSK, 1Tx-slot)	32.0	29.5
GPRS (GMSK, 1Tx-slot)	32.0	29.5
GPRS (GMSK, 2Tx-slot)	30.5	28.0
GPRS (GMSK, 3Tx-slot)	28.0	26.5
GPRS (GMSK, 4Tx-slot)	25.5	24.5
EDGE (8PSK, 1Tx-slot)	26.5	26.0
EDGE (8PSK, 2Tx-slot)	25.0	24.0
EDGE (8PSK, 3Tx-slot)	23.0	22.0
EDGE (8PSK, 4Tx-slot)	20.5	21.0

Mode	WCDMA Band II	WCDMA Band IV	WCDMA Band V
RMC 12.2K	22.0	21.5	24.0
HSDPA	21.0	20.5	23.0
DC-HSDPA	21.0	20.5	23.0
HSUPA	21.0	20.5	23.0

Mode	LTE 2	LTE 4	LTE 5	LTE 7
QPSK / 16QAM / 64QAM	21.5 / 20.5 / 19.5	21.0 / 20.0 / 19.0	24.5 / 23.5 / 22.5	22.0 / 21.0 / 20.0

Mode	LTE 12	LTE 13	LTE 14	LTE 17
QPSK / 16QAM / 64QAM	23.5 / 22.5 / 21.5	24.0 / 23.0 / 22.0	24.0 / 23.0 / 22.0	23.5 / 22.5 / 21.5

Mode	LTE 25	LTE 26	LTE 30	LTE 38
QPSK / 16QAM / 64QAM	21.5 / 20.5 / 19.5	24.5 / 23.5 / 22.5	24.0 / 23.0 / 22.0	23.0 / 22.0 / 21.0

Mode	LTE 41	LTE 66	LTE 71
QPSK / 16QAM / 64QAM	23.0 / 22.0 / 21.0	21.0 / 20.0 / 19.0	23.0 / 22.0 / 21.0

FCC SAR Test Report

2.4GHz WLAN	Mode	Channel	Frequency (MHz)	Tune-Up Limit
	802.11b 1Mbps	1	2412	13.50
		6	2437	14.50
		11	2462	15.50
	802.11g 6Mbps	1	2412	15.00
		6	2437	15.50
		11	2462	15.00
	802.11n-HT20 MCS0	1	2412	14.50
		6	2437	15.00
		11	2462	14.50
	802.11n-HT40 MCS0	3	2422	15.00
		6	2437	16.50
		9	2452	14.50

FCC SAR Test Report

Bluetooth			
Mode	Channel	Frequency (MHz)	Tune up limit (dBm)
BR / EDR	0	2402	4.00
	39	2441	4.00
	78	2480	6.00
BLE 1Mbps	0	2402	3.00
	19	2440	3.00
	39	2480	5.00
BLE 2Mbps	0	2402	0.50
	19	2440	0.50
	39	2480	2.00
BLE S2	0	2402	3.00
	19	2440	3.00
	39	2480	4.50
BLE S8	0	2402	4.00
	19	2440	4.50
	39	2480	6.00
2 nd BLE 1Mbps	0	2402	3.50
	19	2440	4.50
	39	2480	5.00
2 nd BLE 2Mbps	0	2402	2.00
	19	2440	3.00
	39	2480	3.50
2 nd BLE S2	0	2402	4.00
	19	2440	4.50
	39	2480	5.00
2 nd BLE S8	0	2402	4.00
	19	2440	5.00
	39	2480	5.50

FCC SAR Test Report

5.2GHz WLAN	Mode	Channel	Frequency (MHz)	Tune-Up Limit
	802.11a 6Mbps	36	5180	14.00
		40	5200	16.00
		44	5220	16.00
		48	5240	16.00
	802.11n-HT20 MCS0	36	5180	14.00
		40	5200	16.00
		44	5220	16.00
		48	5240	16.00
	802.11n-HT40 MCS0	38	5190	10.00
		46	5230	15.50
	802.11ac-VHT20 MCS0	36	5180	14.00
		40	5200	16.00
		44	5220	16.00
		48	5240	16.00
	802.11ac-VHT40 MCS0	38	5190	10.00
		46	5230	15.50
	802.11ac-VHT80 MCS0	42	5210	8.00

5.3GHz WLAN	Mode	Channel	Frequency (MHz)	Tune-Up Limit
	802.11a 6Mbps	52	5260	16.00
		56	5280	16.00
		60	5300	16.00
		64	5320	16.00
	802.11n-HT20 MCS0	52	5260	16.00
		56	5280	16.00
		60	5300	16.00
		64	5320	14.00
	802.11n-HT40 MCS0	54	5270	15.50
		62	5310	10.00
	802.11ac-VHT20 MCS0	52	5260	16.00
		56	5280	16.00
		60	5300	16.00
		64	5320	14.00
	802.11ac-VHT40 MCS0	54	5270	15.50
		62	5310	11.00
	802.11ac-VHT80 MCS0	58	5290	10.00

FCC SAR Test Report

5.6GHz WLAN	Mode	Channel	Frequency (MHz)	Tune-Up Limit
	802.11a 6Mbps	100	5500	15.00
		116	5580	15.00
		124	5620	17.00
		132	5660	17.00
		140	5700	15.00
		144	5720	17.00
	802.11n-HT20 MCS0	100	5500	15.00
		116	5580	15.00
		124	5620	16.00
		132	5660	16.00
		140	5700	15.00
		144	5720	16.00
	802.11n-HT40 MCS0	102	5510	14.00
		110	5550	14.50
		126	5630	16.50
		134	5670	14.00
		142	5710	16.00
	802.11ac-VHT20 MCS0	100	5500	14.50
		116	5580	15.00
		124	5620	16.00
		132	5660	16.00
		140	5700	14.00
		144	5720	16.00
	802.11ac-VHT40 MCS0	102	5510	13.50
		110	5550	14.50
		126	5630	16.00
		134	5670	16.00
		142	5710	15.00
	802.11ac-VHT80 MCS0	106	5530	11.00
		122	5610	15.00
		138	5690	14.00

FCC SAR Test Report

5.8GHz WLAN	Mode	Channel	Frequency (MHz)	Tune-Up Limit
	802.11a 6Mbps	149	5745	18.00
		157	5785	18.00
		165	5825	17.00
	802.11n-HT20 MCS0	149	5745	17.00
		157	5785	17.00
		165	5825	17.00
	802.11n-HT40 MCS0	151	5755	17.00
		159	5795	17.00
	802.11ac-VHT20 MCS0	149	5745	17.00
		157	5785	17.00
		165	5825	17.00
	802.11ac-VHT40 MCS0	151	5755	17.00
		159	5795	17.00
	802.11ac-VHT80 MCS0	155	5775	15.00

FCC SAR Test Report

4.5.2 Measured Conducted Power Result

The measuring conducted average power (Unit: dBm) is shown as below.

Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency (MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8
Maximum Burst-Averaged Output Power						
GSM (GMSK, 1Tx-slot)	31.82	31.75	31.84	29.35	29.30	29.20
GPRS (GMSK, 1Tx-slot)	31.80	31.74	31.82	29.34	29.28	29.16
GPRS (GMSK, 2Tx-slot)	30.30	30.09	30.44	27.80	27.76	27.59
GPRS (GMSK, 3Tx-slot)	27.38	27.13	27.38	26.03	26.22	26.30
GPRS (GMSK, 4Tx-slot)	25.25	25.17	25.30	23.76	23.88	24.00
EDGE (8PSK, 1Tx-slot)	25.88	26.16	25.90	25.72	25.74	25.80
EDGE (8PSK, 2Tx-slot)	24.50	24.58	24.58	23.31	23.58	23.60
EDGE (8PSK, 3Tx-slot)	22.71	22.54	22.66	21.40	21.72	21.74
EDGE (8PSK, 4Tx-slot)	20.75	20.86	20.76	20.51	20.83	20.69
Maximum Frame-Averaged Output Power						
GSM (GMSK, 1Tx-slot)	22.82	22.75	22.84	20.35	20.30	20.20
GPRS (GMSK, 1Tx-slot)	22.80	22.74	22.82	20.34	20.28	20.16
GPRS (GMSK, 2Tx-slot)	24.30	24.09	24.44	21.80	21.76	21.59
GPRS (GMSK, 3Tx-slot)	23.12	22.87	23.12	21.77	21.96	22.04
GPRS (GMSK, 4Tx-slot)	22.25	22.17	22.30	20.76	20.88	21.00
EDGE (8PSK, 1Tx-slot)	16.88	17.16	16.90	16.72	16.74	16.80
EDGE (8PSK, 2Tx-slot)	18.50	18.58	18.58	17.31	17.58	17.60
EDGE (8PSK, 3Tx-slot)	18.45	18.28	18.40	17.14	17.46	17.48
EDGE (8PSK, 4Tx-slot)	17.75	17.86	17.76	17.51	17.83	17.69

Note:

- SAR testing was performed on the maximum frame-averaged power mode.
- The frame-averaged power is linearly proportion to the slot number configured and it is linearly scaled the maximum burst-averaged power based on time slots. The calculated method is shown as below:

Frame-averaged power = 10 x log (Burst-averaged power mW x Slot used / 8)

Band	WCDMA Band II			WCDMA Band IV			WCDMA Band V			3GPP MPR (dB)
Channel	9262	9400	9538	1312	1413	1513	4132	4182	4233	
Frequency (MHz)	1852.4	1880.0	1907.6	1712.4	1732.6	1752.6	826.4	836.4	846.6	
RMC 12.2K	21.81	21.63	21.83	21.41	21.45	21.38	23.66	23.75	23.78	-
HSDPA Subtest-1	20.84	20.65	20.88	20.43	20.46	20.34	22.68	22.78	22.83	0
HSDPA Subtest-2	20.85	20.64	20.86	20.41	20.45	20.33	22.69	22.77	22.81	0
HSDPA Subtest-3	20.33	20.14	20.33	19.91	19.91	19.81	22.22	22.36	22.35	0.5
HSDPA Subtest-4	20.25	20.03	20.36	19.88	19.89	19.80	22.15	22.22	22.37	0.5
DC-HSDPA Subtest-1	20.87	20.64	20.85	20.47	20.56	20.24	22.66	22.80	22.79	0
DC-HSDPA Subtest-2	20.86	20.63	20.82	20.45	20.46	20.26	22.70	22.74	22.76	0
DC-HSDPA Subtest-3	20.30	20.14	20.33	19.91	20.07	19.75	22.13	22.30	22.29	0.5
DC-HSDPA Subtest-4	20.30	20.09	20.32	19.98	19.94	19.78	22.21	22.23	22.31	0.5
HSUPA Subtest-1	20.92	20.68	20.94	20.43	20.56	20.27	22.67	22.86	22.87	0
HSUPA Subtest-2	18.88	18.75	19.00	18.43	18.50	18.33	20.72	20.82	20.92	2
HSUPA Subtest-3	20.05	19.78	20.06	19.51	19.50	19.24	21.78	21.88	21.94	1
HSUPA Subtest-4	18.99	18.79	18.97	18.45	18.59	18.32	20.70	20.89	20.84	2
HSUPA Subtest-5	20.90	20.74	20.90	20.49	20.59	20.24	22.79	22.88	22.88	0

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 18607	Mid CH 18900	High CH 19193		Low CH 18607	Mid CH 18900	High CH 19193		Low CH 18607	Mid CH 18900	High CH 19193	
			1850.7 MHz	1880.0 MHz	1909.3 MHz		1850.7 MHz	1880.0 MHz	1909.3 MHz		1850.7 MHz	1880.0 MHz	1909.3 MHz	
2 / 1.4M	1	0	20.65	20.90	21.05	0	19.96	20.23	20.43	1	18.66	19.07	19.20	2
	1	2	20.47	20.75	20.93	0	19.87	20.20	20.28	1	18.64	18.99	19.00	2
	1	5	20.12	20.38	20.54	0	19.33	19.71	19.88	1	18.22	18.59	18.61	2
	3	0	20.65	20.90	21.10	0	19.58	19.94	19.88	1	18.54	18.77	18.95	2
	3	1	20.51	20.95	20.89	0	19.48	19.96	20.02	1	18.51	18.92	18.92	2
	3	3	20.37	20.81	20.81	0	19.44	19.80	19.84	1	18.43	18.71	18.92	2
	6	0	19.57	19.83	19.93	1	18.53	18.78	18.89	2	17.54	17.90	17.84	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 18615	Mid CH 18900	High CH 19185		Low CH 18615	Mid CH 18900	High CH 19185		Low CH 18615	Mid CH 18900	High CH 19185	
			1851.5 MHz	1880.0 MHz	1908.5 MHz		1851.5 MHz	1880.0 MHz	1908.5 MHz		1851.5 MHz	1880.0 MHz	1908.5 MHz	
2 / 3M	1	0	20.67	20.92	21.04	0	19.93	20.29	20.46	1	18.72	19.10	19.14	2
	1	7	20.43	20.76	20.93	0	19.84	20.23	20.26	1	18.67	18.93	18.99	2
	1	14	20.08	20.38	20.54	0	19.36	19.71	19.88	1	18.23	18.61	18.61	2
	8	0	19.64	19.93	20.10	1	18.54	18.95	18.88	2	17.57	17.81	17.96	3
	8	3	19.44	19.95	19.91	1	18.53	18.91	19.05	2	17.55	17.86	17.97	3
	8	7	19.34	19.88	19.85	1	18.46	18.78	18.80	2	17.40	17.75	17.88	3
	15	0	19.54	19.84	19.87	1	18.53	18.72	18.92	2	17.56	17.87	17.88	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 18625	Mid CH 18900	High CH 19175		Low CH 18625	Mid CH 18900	High CH 19175		Low CH 18625	Mid CH 18900	High CH 19175	
			1852.5 MHz	1880.0 MHz	1907.5 MHz		1852.5 MHz	1880.0 MHz	1907.5 MHz		1852.5 MHz	1880.0 MHz	1907.5 MHz	
2 / 5M	1	0	20.68	20.87	21.05	0	19.94	20.25	20.46	1	18.66	19.07	19.20	2
	1	12	20.48	20.73	20.93	0	19.81	20.26	20.25	1	18.64	18.99	18.99	2
	1	24	20.09	20.37	20.58	0	19.36	19.71	19.87	1	18.16	18.66	18.61	2
	12	0	19.67	19.93	20.07	1	18.54	18.93	18.85	2	17.58	17.78	17.95	3
	12	6	19.44	19.96	19.92	1	18.50	18.95	19.01	2	17.49	17.93	17.96	3
	12	13	19.38	19.84	19.86	1	18.41	18.80	18.83	2	17.44	17.74	17.85	3
	25	0	19.52	19.87	19.90	1	18.53	18.73	18.89	2	17.52	17.93	17.86	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 18650	Mid CH 18900	High CH 19150		Low CH 18650	Mid CH 18900	High CH 19150		Low CH 18650	Mid CH 18900	High CH 19150	
			1855.0 MHz	1880.0 MHz	1905.0 MHz		1855.0 MHz	1880.0 MHz	1905.0 MHz		1855.0 MHz	1880.0 MHz	1905.0 MHz	
2 / 10M	1	0	20.65	20.90	21.05	0	19.94	20.22	20.42	1	18.65	19.08	19.17	2
	1	24	20.48	20.73	20.94	0	19.86	20.22	20.28	1	18.69	18.95	19.03	2
	1	49	20.06	20.41	20.54	0	19.36	19.72	19.84	1	18.22	18.60	18.58	2
	25	0	19.68	19.92	20.10	1	18.56	18.91	18.91	2	17.56	17.75	18.01	3
	25	12	19.50	19.90	19.92	1	18.54	18.89	19.06	2	17.56	17.92	17.90	3
	25	25	19.36	19.81	19.85	1	18.40	18.81	18.80	2	17.43	17.71	17.87	3
	50	0	19.57	19.87	19.87	1	18.57	18.72	18.93	2	17.57	17.89	17.87	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 18675 1857.5 MHz	Mid CH 18900 1880.0 MHz	High CH 19125 1902.5 MHz		Low CH 18675 1857.5 MHz	Mid CH 18900 1880.0 MHz	High CH 19125 1902.5 MHz		Low CH 18675 1857.5 MHz	Mid CH 18900 1880.0 MHz	High CH 19125 1902.5 MHz	
2 / 15M	1	0	20.72	20.90	21.02	0	19.98	20.29	20.42	1	18.67	19.09	19.18	2
	1	37	20.46	20.78	20.89	0	19.85	20.23	20.28	1	18.70	18.94	19.00	2
	1	74	20.12	20.44	20.55	0	19.32	19.77	19.86	1	18.18	18.59	18.61	2
	36	0	19.65	19.93	20.11	1	18.60	18.91	18.92	2	17.61	17.81	17.95	3
	36	19	19.51	19.95	19.92	1	18.48	18.93	19.02	2	17.50	17.86	17.92	3
	36	39	19.34	19.82	19.85	1	18.45	18.79	18.83	2	17.46	17.78	17.89	3
	75	0	19.57	19.85	19.92	1	18.58	18.75	18.86	2	17.56	17.87	17.88	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 18700 1860.0 MHz	Mid CH 18900 1880.0 MHz	High CH 19100 1900.0 MHz		Low CH 18700 1860.0 MHz	Mid CH 18900 1880.0 MHz	High CH 19100 1900.0 MHz		Low CH 18700 1860.0 MHz	Mid CH 18900 1880.0 MHz	High CH 19100 1900.0 MHz	
2 / 20M	1	0	20.73	20.94	21.10	0	20.01	20.30	20.48	1	18.73	19.12	19.22	2
	1	50	20.50	20.81	20.95	0	19.89	20.28	20.30	1	18.72	19.01	19.05	2
	1	99	20.14	20.45	20.59	0	19.38	19.79	19.89	1	18.24	18.67	18.63	2
	50	0	19.71	19.98	20.12	1	18.62	18.99	18.93	2	17.62	17.83	18.03	3
	50	25	19.52	19.97	19.97	1	18.56	18.97	19.07	2	17.57	17.94	17.98	3
	50	50	19.42	19.89	19.87	1	18.48	18.85	18.85	2	17.48	17.79	17.93	3
	100	0	19.58	19.89	19.95	1	18.59	18.80	18.94	2	17.58	17.95	17.89	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 19957	Mid CH 20175	High CH 19193		Low CH 19957	Mid CH 20175	High CH 19193		Low CH 19957	Mid CH 20175	High CH 19193	
			1710.7 MHz	1732.5 MHz	1754.3 MHz		1710.7 MHz	1732.5 MHz	1754.3 MHz		1710.7 MHz	1732.5 MHz	1754.3 MHz	
4 / 1.4M	1	0	20.66	20.58	20.55	0	19.75	19.66	19.65	1	18.61	18.57	18.61	2
	1	2	20.52	20.41	20.44	0	19.92	19.76	19.87	1	18.77	18.69	18.70	2
	1	5	20.60	20.47	20.48	0	19.79	19.71	19.79	1	18.75	18.58	18.72	2
	3	0	20.64	20.54	23.24	0	19.68	19.52	19.61	1	18.64	17.56	17.50	2
	3	1	20.73	20.62	20.55	0	19.59	19.61	19.58	1	18.64	17.58	17.58	2
	3	3	20.56	20.45	20.54	0	19.63	19.50	19.60	1	18.61	17.50	17.56	2
	6	0	19.76	19.59	19.66	1	18.74	18.65	18.61	2	17.76	17.60	17.69	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 19965	Mid CH 20175	High CH 20385		Low CH 19965	Mid CH 20175	High CH 20385		Low CH 19965	Mid CH 20175	High CH 20385	
			1711.5 MHz	1732.5 MHz	1753.5 MHz		1711.5 MHz	1732.5 MHz	1753.5 MHz		1711.5 MHz	1732.5 MHz	1753.5 MHz	
4 / 3M	1	0	20.68	20.60	20.54	0	19.72	19.72	19.68	1	18.67	18.60	18.55	2
	1	7	20.48	20.42	20.44	0	19.89	19.79	19.85	1	18.80	18.63	18.69	2
	1	14	20.56	20.47	20.48	0	19.82	19.71	19.79	1	18.76	18.60	18.72	2
	8	0	19.63	19.57	19.66	1	18.64	18.53	18.61	2	17.67	17.60	17.51	3
	8	3	19.66	19.62	19.57	1	18.64	18.56	18.61	2	17.68	17.52	17.63	3
	8	7	19.53	19.52	19.58	1	18.65	18.48	18.56	2	17.58	17.54	17.52	3
	15	0	19.73	19.60	19.60	1	18.74	18.59	18.64	2	17.78	17.57	17.73	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 19975	Mid CH 20175	High CH 20375		Low CH 19975	Mid CH 20175	High CH 20375		Low CH 19975	Mid CH 20175	High CH 20375	
			1712.5 MHz	1732.5 MHz	1752.5 MHz		1712.5 MHz	1732.5 MHz	1752.5 MHz		1712.5 MHz	1732.5 MHz	1752.5 MHz	
4 / 5M	1	0	20.69	20.55	20.55	0	19.73	19.68	19.68	1	18.61	18.57	18.61	2
	1	12	20.53	20.39	20.44	0	19.86	19.82	19.84	1	18.77	18.69	18.69	2
	1	24	20.57	20.46	20.52	0	19.82	19.71	19.78	1	18.69	18.65	18.72	2
	12	0	19.66	19.57	19.63	1	18.64	18.51	18.58	2	17.68	17.57	17.50	3
	12	6	19.66	19.63	19.58	1	18.61	18.60	18.57	2	17.62	17.59	17.62	3
	12	13	19.57	19.48	19.59	1	18.60	18.50	18.59	2	17.62	17.53	17.49	3
	25	0	19.71	19.63	19.63	1	18.74	18.60	18.61	2	17.74	17.63	17.71	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20000	Mid CH 20175	High CH 20350		Low CH 20000	Mid CH 20175	High CH 20350		Low CH 20000	Mid CH 20175	High CH 20350	
			1715.0 MHz	1732.5 MHz	1750.0 MHz		1715.0 MHz	1732.5 MHz	1750.0 MHz		1715.0 MHz	1732.5 MHz	1750.0 MHz	
4 / 10M	1	0	20.66	20.58	20.55	0	19.73	19.65	19.64	1	18.60	18.58	18.58	2
	1	24	20.53	20.39	20.45	0	19.91	19.78	19.87	1	18.82	18.65	18.73	2
	1	49	20.54	20.50	20.48	0	19.82	19.72	19.75	1	18.75	18.59	18.69	2
	25	0	19.67	19.56	19.66	1	18.66	18.49	18.64	2	17.66	17.54	17.56	3
	25	12	19.72	19.57	19.58	1	18.65	18.54	18.62	2	17.69	17.58	17.56	3
	25	25	19.55	19.45	19.58	1	18.59	18.51	18.56	2	17.61	17.50	17.51	3
	50	0	19.76	19.63	19.60	1	18.78	18.59	18.65	2	17.79	17.59	17.72	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20025	Mid CH 20175	High CH 20325		Low CH 20025	Mid CH 20175	High CH 20325		Low CH 20025	Mid CH 20175	High CH 20325	
			1717.5 MHz	1732.5 MHz	1747.5 MHz		1717.5 MHz	1732.5 MHz	1747.5 MHz		1717.5 MHz	1732.5 MHz	1747.5 MHz	
4 / 15M	1	0	20.73	20.58	20.52	0	19.77	19.72	19.64	1	18.62	18.59	18.59	2
	1	37	20.51	20.44	20.40	0	19.90	19.79	19.87	1	18.83	18.64	18.70	2
	1	74	20.60	20.53	20.49	0	19.78	19.77	19.77	1	18.71	18.58	18.72	2
	36	0	19.64	19.57	19.67	1	18.70	18.49	18.65	2	17.71	17.60	17.50	3
	36	19	19.73	19.62	19.58	1	18.59	18.58	18.58	2	17.63	17.52	17.58	3
	36	39	19.53	19.46	19.58	1	18.64	18.49	18.59	2	17.64	17.57	17.53	3
	75	0	19.76	19.61	19.65	1	18.79	18.62	18.58	2	17.78	17.57	17.73	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20050	Mid CH 20175	High CH 20300		Low CH 20050	Mid CH 20175	High CH 20300		Low CH 20050	Mid CH 20175	High CH 20300	
			1720.0 MHz	1732.5 MHz	1745.0 MHz		1720.0 MHz	1732.5 MHz	1745.0 MHz		1720.0 MHz	1732.5 MHz	1745.0 MHz	
4 / 20M	1	0	20.74	20.62	20.60	0	19.80	19.73	19.70	1	18.68	18.62	18.63	2
	1	50	20.55	20.47	20.46	0	19.94	19.84	19.89	1	18.85	18.71	18.75	2
	1	99	20.62	20.54	20.53	0	19.84	19.79	19.80	1	18.77	18.66	18.74	2
	50	0	19.70	19.62	19.68	1	18.72	18.57	18.66	2	17.72	17.62	17.58	3
	50	25	19.74	19.64	19.63	1	18.67	18.62	18.63	2	17.70	17.60	17.64	3
	50	50	19.61	19.53	19.60	1	18.67	18.55	18.61	2	17.66	17.58	17.57	3
	100	0	19.77	19.65	19.68	1	18.80	18.67	18.66	2	17.80	17.65	17.74	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20407	Mid CH 20525	High CH 20643		Low CH 20407	Mid CH 20525	High CH 20643		Low CH 20407	Mid CH 20525	High CH 20643	
			824.7 MHz	836.5 MHz	848.3 MHz		824.7 MHz	836.5 MHz	848.3 MHz		824.7 MHz	836.5 MHz	848.3 MHz	
5 / 1.4M	1	0	22.92	22.82	22.88	0	22.30	22.18	22.28	1	21.09	21.01	21.12	2
	1	2	22.79	22.58	22.73	0	22.02	21.90	21.98	1	20.87	20.87	20.85	2
	1	5	23.18	22.98	23.12	0	22.42	22.21	22.39	1	21.28	21.17	21.27	2
	3	0	22.97	22.82	22.93	0	21.82	21.71	21.74	1	20.80	20.69	20.69	2
	3	1	22.91	22.85	22.80	0	21.87	21.86	21.83	1	20.84	20.83	20.83	2
	3	3	22.91	22.75	22.86	0	21.88	21.77	21.89	1	20.92	20.76	20.85	2
	6	0	21.89	21.76	21.82	1	20.92	20.83	20.87	2	19.90	19.81	19.85	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20415	Mid CH 20525	High CH 20635		Low CH 20415	Mid CH 20525	High CH 20635		Low CH 20415	Mid CH 20525	High CH 20635	
			825.5 MHz	836.5 MHz	847.5 MHz		825.5 MHz	836.5 MHz	847.5 MHz		825.5 MHz	836.5 MHz	847.5 MHz	
5 / 3M	1	0	22.94	22.84	22.87	0	22.27	22.24	22.31	1	21.15	21.04	21.06	2
	1	7	22.75	22.59	22.73	0	21.99	21.93	21.96	1	20.90	20.81	20.84	2
	1	14	23.14	22.98	23.12	0	22.45	22.21	22.39	1	21.29	21.19	21.27	2
	8	0	21.96	21.85	21.93	1	20.78	20.72	20.74	2	19.83	19.73	19.70	3
	8	3	21.84	21.85	21.82	1	20.92	20.81	20.86	2	19.88	19.77	19.88	3
	8	7	21.88	21.82	21.90	1	20.90	20.75	20.85	2	19.89	19.80	19.81	3
	15	0	21.86	21.77	21.76	1	20.92	20.77	20.90	2	19.92	19.78	19.89	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20425	Mid CH 20525	High CH 20625		Low CH 20425	Mid CH 20525	High CH 20625		Low CH 20425	Mid CH 20525	High CH 20625	
			826.5 MHz	836.5 MHz	846.5 MHz		826.5 MHz	836.5 MHz	846.5 MHz		826.5 MHz	836.5 MHz	846.5 MHz	
5 / 5M	1	0	22.95	22.79	22.88	0	22.28	22.20	22.31	1	21.09	21.01	21.12	2
	1	12	22.80	22.56	22.73	0	21.96	21.96	21.95	1	20.87	20.87	20.84	2
	1	24	23.15	22.97	23.16	0	22.45	22.21	22.38	1	21.22	21.24	21.27	2
	12	0	21.99	21.85	21.90	1	20.78	20.70	20.71	2	19.84	19.70	19.69	3
	12	6	21.84	21.86	21.83	1	20.89	20.85	20.82	2	19.82	19.84	19.87	3
	12	13	21.92	21.78	21.91	1	20.85	20.77	20.88	2	19.93	19.79	19.78	3
	25	0	21.84	21.80	21.79	1	20.92	20.78	20.87	2	19.88	19.84	19.87	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20450	Mid CH 20525	High CH 20600		Low CH 20450	Mid CH 20525	High CH 20600		Low CH 20450	Mid CH 20525	High CH 20600	
			829.0 MHz	836.5 MHz	844.0 MHz		829.0 MHz	836.5 MHz	844.0 MHz		829.0 MHz	836.5 MHz	844.0 MHz	
5 / 10M	1	0	23.00	22.86	22.93	0	22.35	22.25	22.33	1	21.16	21.06	21.14	2
	1	24	22.82	22.64	22.75	0	22.04	21.98	22.00	1	20.95	20.89	20.90	2
	1	49	23.20	23.05	23.17	0	22.47	22.29	22.40	1	21.30	21.25	21.29	2
	25	0	22.03	21.90	21.95	1	20.86	20.76	20.79	2	19.88	19.75	19.77	3
	25	12	21.92	21.87	21.88	1	20.95	20.87	20.88	2	19.90	19.85	19.89	3
	25	25	21.96	21.83	21.92	1	20.92	20.82	20.90	2	19.97	19.84	19.86	3
	50	0	21.90	21.82	21.84	1	20.98	20.85	20.92	2	19.94	19.86	19.90	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20775	Mid CH 21100	High CH 21425		Low CH 20775	Mid CH 21100	High CH 21425		Low CH 20775	Mid CH 21100	High CH 21425	
			2502.5 MHz	2535.0 MHz	2567.5 MHz		2502.5 MHz	2535.0 MHz	2567.5 MHz		2502.5 MHz	2535.0 MHz	2567.5 MHz	
7 / 5M	1	0	21.45	21.73	21.50	0	20.71	21.08	20.85	1	19.56	19.94	19.75	2
	1	12	21.33	21.61	21.43	0	20.53	20.91	20.70	1	19.42	19.76	19.53	2
	1	24	21.38	21.69	21.52	0	20.68	20.99	20.83	1	19.51	19.89	19.73	2
	12	0	20.32	20.65	20.48	1	19.29	19.58	19.42	2	18.30	18.61	18.31	3
	12	6	20.28	20.67	20.39	1	19.22	19.63	19.37	2	18.24	18.63	18.43	3
	12	13	20.26	20.59	20.47	1	19.28	19.60	19.46	2	18.32	18.65	18.38	3
	25	0	20.30	20.64	20.41	1	19.30	19.58	19.36	2	18.27	18.58	18.43	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20800	Mid CH 21100	High CH 21400		Low CH 20800	Mid CH 21100	High CH 21400		Low CH 20800	Mid CH 21100	High CH 21400	
			2505.0 MHz	2535.0 MHz	2565.0 MHz		2505.0 MHz	2535.0 MHz	2565.0 MHz		2505.0 MHz	2535.0 MHz	2565.0 MHz	
7 / 10M	1	0	21.42	21.76	21.50	0	20.71	21.05	20.81	1	19.55	19.95	19.72	2
	1	24	21.33	21.61	21.44	0	20.58	20.87	20.73	1	19.47	19.72	19.57	2
	1	49	21.35	21.73	21.48	0	20.68	21.00	20.80	1	19.57	19.83	19.70	2
	25	0	20.33	20.64	20.51	1	19.31	19.56	19.48	2	18.28	18.58	18.37	3
	25	12	20.34	20.61	20.39	1	19.26	19.57	19.42	2	18.31	18.62	18.37	3
	25	25	20.24	20.56	20.46	1	19.27	19.61	19.43	2	18.31	18.62	18.40	3
	50	0	20.35	20.64	20.38	1	19.34	19.57	19.40	2	18.32	18.54	18.44	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20825	Mid CH 21100	High CH 21375		Low CH 20825	Mid CH 21100	High CH 21375		Low CH 20825	Mid CH 21100	High CH 21375	
			2507.5 MHz	2535.0 MHz	2562.5 MHz		2507.5 MHz	2535.0 MHz	2562.5 MHz		2507.5 MHz	2535.0 MHz	2562.5 MHz	
7 / 15M	1	0	21.49	21.76	21.47	0	20.75	21.12	20.81	1	19.57	19.96	19.73	2
	1	37	21.31	21.66	21.39	0	20.57	20.88	20.73	1	19.48	19.71	19.54	2
	1	74	21.41	21.76	21.49	0	20.64	21.05	20.82	1	19.53	19.82	19.73	2
	36	0	20.30	20.65	20.52	1	19.35	19.56	19.49	2	18.33	18.64	18.31	3
	36	19	20.35	20.66	20.39	1	19.20	19.61	19.38	2	18.25	18.56	18.39	3
	36	39	20.22	20.57	20.46	1	19.32	19.59	19.46	2	18.34	18.69	18.42	3
	75	0	20.35	20.62	20.43	1	19.35	19.60	19.33	2	18.31	18.52	18.45	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 20850	Mid CH 21100	High CH 21350		Low CH 20850	Mid CH 21100	High CH 21350		Low CH 20850	Mid CH 21100	High CH 21350	
			2510.0 MHz	2535.0 MHz	2560.0 MHz		2510.0 MHz	2535.0 MHz	2560.0 MHz		2510.0 MHz	2535.0 MHz	2560.0 MHz	
7 / 20M	1	0	21.50	21.80	21.55	0	20.78	21.13	20.87	1	19.63	19.99	19.77	2
	1	50	21.35	21.69	21.45	0	20.61	20.93	20.75	1	19.50	19.78	19.59	2
	1	99	21.43	21.77	21.53	0	20.70	21.07	20.85	1	19.59	19.90	19.75	2
	50	0	20.36	20.70	20.53	1	19.37	19.64	19.50	2	18.34	18.66	18.39	3
	50	25	20.36	20.68	20.44	1	19.28	19.65	19.43	2	18.32	18.64	18.45	3
	50	50	20.30	20.64	20.48	1	19.35	19.65	19.48	2	18.36	18.70	18.46	3
	100	0	20.36	20.66	20.46	1	19.36	19.65	19.41	2	18.33	18.60	18.46	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 23017	Mid CH 23095	High CH 23173		Low CH 23017	Mid CH 23095	High CH 23173		Low CH 23017	Mid CH 23095	High CH 23173	
			699.7 MHz	707.5 MHz	715.3 MHz		699.7 MHz	707.5 MHz	715.3 MHz		699.7 MHz	707.5 MHz	715.3 MHz	
12 / 1.4M	1	0	23.14	22.59	22.74	0	22.30	21.73	21.92	1	21.32	20.79	20.99	2
	1	2	23.14	22.48	22.72	0	22.25	21.68	21.85	1	21.12	20.67	20.74	2
	1	5	22.59	21.94	22.17	0	22.18	21.52	21.79	1	21.34	20.78	20.97	2
	3	0	23.02	22.42	22.62	0	22.32	21.76	21.88	1	21.28	20.72	20.81	2
	3	1	23.32	22.81	22.85	0	22.14	21.68	21.74	1	21.17	20.71	20.80	2
	3	3	22.67	22.72	22.92	0	22.07	21.51	21.72	1	21.18	20.57	20.75	2
	6	0	22.40	21.82	21.97	1	21.32	20.78	20.91	2	20.38	19.84	19.97	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 23025	Mid CH 23095	High CH 23165		Low CH 23025	Mid CH 23095	High CH 23165		Low CH 23025	Mid CH 23095	High CH 23165	
			700.5 MHz	707.5 MHz	714.5 MHz		700.5 MHz	707.5 MHz	714.5 MHz		700.5 MHz	707.5 MHz	714.5 MHz	
12 / 3M	1	0	23.16	22.61	22.73	0	22.27	21.79	21.95	1	21.38	20.82	20.93	2
	1	7	23.10	22.49	22.72	0	22.22	21.71	21.83	1	21.15	20.61	20.73	2
	1	14	22.55	21.94	22.17	0	22.21	21.52	21.79	1	21.35	20.80	20.97	2
	8	0	22.01	21.45	21.62	1	21.28	20.77	20.88	2	20.31	19.76	19.82	3
	8	3	22.25	21.81	21.87	1	21.19	20.63	20.77	2	20.21	19.65	19.85	3
	8	7	22.30	21.79	21.96	1	21.09	20.49	20.68	2	20.15	19.61	19.71	3
	15	0	22.37	21.83	21.91	1	21.32	20.72	20.94	2	20.40	19.81	20.01	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 23035	Mid CH 23095	High CH 23155		Low CH 23035	Mid CH 23095	High CH 23155		Low CH 23035	Mid CH 23095	High CH 23155	
			701.5 MHz	707.5 MHz	713.5 MHz		701.5 MHz	707.5 MHz	713.5 MHz		701.5 MHz	707.5 MHz	713.5 MHz	
12 / 5M	1	0	23.17	22.56	22.74	0	22.28	21.75	21.95	1	21.32	20.79	20.99	2
	1	12	23.15	22.46	22.72	0	22.19	21.74	21.82	1	21.12	20.67	20.73	2
	1	24	22.56	21.93	22.21	0	22.21	21.52	21.78	1	21.28	20.85	20.97	2
	12	0	22.04	21.45	21.59	1	21.28	20.75	20.85	2	20.32	19.73	19.81	3
	12	6	22.25	21.82	21.88	1	21.16	20.67	20.73	2	20.15	19.72	19.84	3
	12	13	22.34	21.75	21.97	1	21.04	20.51	20.71	2	20.19	19.60	19.68	3
	25	0	22.35	21.86	21.94	1	21.32	20.73	20.91	2	20.36	19.87	19.99	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 23060	Mid CH 23095	High CH 23130		Low CH 23060	Mid CH 23095	High CH 23130		Low CH 23060	Mid CH 23095	High CH 23130	
			704.0 MHz	707.5 MHz	711.0 MHz		704.0 MHz	707.5 MHz	711.0 MHz		704.0 MHz	707.5 MHz	711.0 MHz	
12 / 10M	1	0	23.22	22.63	22.79	0	22.35	21.80	21.97	1	21.39	20.84	21.01	2
	1	24	23.17	22.54	22.74	0	22.27	21.76	21.87	1	21.20	20.69	20.79	2
	1	49	22.61	22.01	22.22	0	22.23	21.60	21.80	1	21.36	20.86	20.99	2
	25	0	22.08	21.50	21.64	1	21.36	20.81	20.93	2	20.36	19.78	19.89	3
	25	12	22.33	21.83	21.93	1	21.22	20.69	20.79	2	20.23	19.73	19.86	3
	25	25	22.38	21.80	21.98	1	21.11	20.56	20.73	2	20.23	19.65	19.76	3
	50	0	22.41	21.88	21.99	1	21.38	20.80	20.96	2	20.42	19.89	20.02	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 23205	Mid CH 23230	High CH 23255		Low CH 23205	Mid CH 23230	High CH 23255		Low CH 23205	Mid CH 23230	High CH 23255	
			779.5 MHz	782.0 MHz	784.5 MHz		779.5 MHz	782.0 MHz	784.5 MHz		779.5 MHz	782.0 MHz	784.5 MHz	
13 / 5M	1	0	23.51	23.49	23.51	0	22.50	22.52	22.55	1	21.62	21.64	21.67	2
	1	12	23.49	23.43	23.49	0	22.68	22.74	22.71	1	21.71	21.77	21.73	2
	1	24	23.48	23.45	23.52	0	22.78	22.72	22.78	1	21.69	21.76	21.75	2
	12	0	22.75	22.74	22.74	1	21.75	21.77	21.75	2	20.76	20.75	20.72	3
	12	6	22.51	22.58	22.54	1	21.61	21.65	21.61	2	20.61	20.68	20.67	3
	12	13	22.58	22.57	22.61	1	21.58	21.60	21.63	2	20.58	20.57	20.54	3
	25	0	22.66	22.70	22.67	1	21.74	21.73	21.75	2	20.69	20.73	20.72	3

LTE Band / BW	RB Size	RB Offset	QPSK	3GPP MPR (dB)	16QAM	3GPP MPR (dB)	64QAM	3GPP MPR (dB)
			Mid CH 23230		Mid CH 23230		Mid CH 23230	
			782.0 MHz		782.0 MHz		782.0 MHz	
13 / 10M	1	0	23.56	0	22.57	1	21.69	2
	1	24	23.51	0	22.76	1	21.79	2
	1	49	23.53	0	22.80	1	21.77	2
	25	0	22.79	1	21.83	2	20.80	3
	25	12	22.59	1	21.67	2	20.69	3
	25	25	22.62	1	21.65	2	20.62	3
	50	0	22.72	1	21.80	2	20.75	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 23305	Mid CH 23330	High CH 23355		Low CH 23305	Mid CH 23330	High CH 23355		Low CH 23305	Mid CH 23330	High CH 23355	
			790.5 MHz	793.0 MHz	795.5 MHz		790.5 MHz	793.0 MHz	795.5 MHz		790.5 MHz	793.0 MHz	795.5 MHz	
14 / 5M	1	0	23.60	23.58	23.60	0	22.69	22.71	22.74	1	21.62	21.64	21.67	2
	1	12	23.52	23.46	23.52	0	22.73	22.79	22.76	1	21.81	21.87	21.83	2
	1	24	22.82	22.79	22.86	0	22.20	22.14	22.20	1	21.09	21.16	21.15	2
	12	0	22.91	22.90	22.90	1	21.81	21.83	21.81	2	20.79	20.78	20.75	3
	12	6	22.72	22.79	22.75	1	21.70	21.74	21.70	2	20.69	20.76	20.75	3
	12	13	22.66	22.65	22.69	1	21.71	21.73	21.76	2	20.79	20.78	20.75	3
	25	0	22.76	22.80	22.77	1	21.77	21.76	21.78	2	20.72	20.76	20.75	3

LTE Band / BW	RB Size	RB Offset	QPSK	3GPP MPR (dB)	16QAM	3GPP MPR (dB)	64QAM	3GPP MPR (dB)
			Mid CH 23330		Mid CH 23330		Mid CH 23330	
			793.0 MHz		793.0 MHz		793.0 MHz	
14 / 10M	1	0	23.65	0	22.76	1	21.69	2
	1	24	23.54	0	22.81	1	21.89	2
	1	49	22.87	0	22.22	1	21.17	2
	25	0	22.95	1	21.89	2	20.83	3
	25	12	22.80	1	21.76	2	20.77	3
	25	25	22.70	1	21.78	2	20.83	3
	50	0	22.82	1	21.83	2	20.78	3



FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 23755	Mid CH 23790	High CH 23825		Low CH 23755	Mid CH 23790	High CH 23825		Low CH 23755	Mid CH 23790	High CH 23825	
			706.5 MHz	710.0 MHz	713.5 MHz		706.5 MHz	710.0 MHz	713.5 MHz		706.5 MHz	710.0 MHz	713.5 MHz	
17 / 5M	1	0	22.97	22.98	23.07	0	21.53	21.66	21.73	1	20.51	20.64	20.71	2
	1	12	22.17	22.18	22.27	0	22.14	22.35	22.30	1	21.07	21.28	21.21	2
	1	24	22.59	22.62	22.77	0	22.08	22.05	22.18	1	20.79	21.02	21.01	2
	12	0	22.20	22.27	22.28	1	21.02	21.15	21.12	2	20.08	20.15	20.10	3
	12	6	21.93	22.16	22.09	1	21.12	21.29	21.22	2	20.07	20.30	20.29	3
	12	13	21.97	22.04	22.13	1	21.13	21.26	21.33	2	20.24	20.31	20.26	3
	25	0	21.99	22.16	22.11	1	20.62	20.69	20.74	2	19.99	20.16	20.15	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 23780	Mid CH 23790	High CH 23800		Low CH 23780	Mid CH 23790	High CH 23800		Low CH 23780	Mid CH 23790	High CH 23800	
			709.0 MHz	710.0 MHz	711.0 MHz		709.0 MHz	710.0 MHz	711.0 MHz		709.0 MHz	710.0 MHz	711.0 MHz	
17 / 10M	1	0	23.02	23.05	23.12	0	21.60	21.71	21.75	1	20.58	20.69	20.73	2
	1	24	22.19	22.26	22.29	0	22.22	22.37	22.35	1	21.15	21.30	21.27	2
	1	49	22.64	22.70	22.78	0	22.10	22.13	22.20	1	20.87	21.03	21.03	2
	25	0	22.24	22.32	22.33	1	21.10	21.21	21.20	2	20.12	20.20	20.18	3
	25	12	22.01	22.17	22.14	1	21.18	21.31	21.28	2	20.15	20.31	20.31	3
	25	25	22.01	22.09	22.14	1	21.20	21.31	21.35	2	20.28	20.36	20.34	3
	50	0	22.05	22.18	22.16	1	20.68	20.76	20.79	2	20.05	20.18	20.18	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 26047	Mid CH 26365	High CH 26683		Low CH 26047	Mid CH 26365	High CH 26683		Low CH 26047	Mid CH 26365	High CH 26683	
			1850.7 MHz	1882.5 MHz	1914.3 MHz		1850.7 MHz	1882.5 MHz	1914.3 MHz		1850.7 MHz	1882.5 MHz	1914.3 MHz	
25 / 1.4M	1	0	20.64	21.15	21.09	0	19.85	20.35	20.31	1	18.81	19.36	19.37	2
	1	2	20.64	21.12	21.12	0	20.08	20.55	20.59	1	18.85	19.36	19.34	2
	1	5	20.15	20.61	20.59	0	19.60	20.11	20.16	1	18.82	19.24	19.35	2
	3	0	20.63	21.12	21.21	0	19.67	20.10	20.16	1	18.64	19.15	19.06	2
	3	1	20.65	21.23	21.03	0	19.53	20.14	20.08	1	18.42	18.95	18.92	2
	3	3	20.56	21.04	21.10	0	19.65	20.11	20.18	1	18.53	19.01	19.04	2
	6	0	19.82	20.24	20.28	1	18.50	19.00	18.93	2	17.55	17.98	18.04	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 26055	Mid CH 26365	High CH 26675		Low CH 26055	Mid CH 26365	High CH 26675		Low CH 26055	Mid CH 26365	High CH 26675	
			1851.5 MHz	1882.5 MHz	1913.5 MHz		1851.5 MHz	1882.5 MHz	1913.5 MHz		1851.5 MHz	1882.5 MHz	1913.5 MHz	
25 / 3M	1	0	20.66	21.17	21.08	0	19.82	20.41	20.34	1	18.87	19.39	19.31	2
	1	7	20.60	21.13	21.12	0	20.05	20.58	20.57	1	18.88	19.30	19.33	2
	1	14	20.11	20.61	20.59	0	19.63	20.11	20.16	1	18.83	19.26	19.35	2
	8	0	19.62	20.15	20.21	1	18.63	19.11	19.16	2	17.67	18.19	18.07	3
	8	3	19.58	20.23	20.05	1	18.58	19.09	19.11	2	17.46	17.89	17.97	3
	8	7	19.53	20.11	20.14	1	18.67	19.09	19.14	2	17.50	18.05	18.00	3
	15	0	19.79	20.25	20.22	1	18.50	18.94	18.96	2	17.57	17.95	18.08	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 26065	Mid CH 26365	High CH 26665		Low CH 26065	Mid CH 26365	High CH 26665		Low CH 26065	Mid CH 26365	High CH 26665	
			1852.5 MHz	1882.5 MHz	1912.5 MHz		1852.5 MHz	1882.5 MHz	1912.5 MHz		1852.5 MHz	1882.5 MHz	1912.5 MHz	
25 / 5M	1	0	20.67	21.12	21.09	0	19.83	20.37	20.34	1	18.81	19.36	19.37	2
	1	12	20.65	21.10	21.12	0	20.02	20.61	20.56	1	18.85	19.36	19.33	2
	1	24	20.12	20.60	20.63	0	19.63	20.11	20.15	1	18.76	19.31	19.35	2
	12	0	19.65	20.15	20.18	1	18.63	19.09	19.13	2	17.68	18.16	18.06	3
	12	6	19.58	20.24	20.06	1	18.55	19.13	19.07	2	17.40	17.96	17.96	3
	12	13	19.57	20.07	20.15	1	18.62	19.11	19.17	2	17.54	18.04	17.97	3
	25	0	19.77	20.28	20.25	1	18.50	18.95	18.93	2	17.53	18.01	18.06	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 26090	Mid CH 26365	High CH 26640		Low CH 26090	Mid CH 26365	High CH 26640		Low CH 26090	Mid CH 26365	High CH 26640	
			1855.0 MHz	1882.5 MHz	1910.0 MHz		1855.0 MHz	1882.5 MHz	1910.0 MHz		1855.0 MHz	1882.5 MHz	1910.0 MHz	
25 / 10M	1	0	20.64	21.15	21.09	0	19.83	20.34	20.30	1	18.80	19.37	19.34	2
	1	24	20.65	21.10	21.13	0	20.07	20.57	20.59	1	18.90	19.32	19.37	2
	1	49	20.09	20.64	20.59	0	19.63	20.12	20.12	1	18.82	19.25	19.32	2
	25	0	19.66	20.14	20.21	1	18.65	19.07	19.19	2	17.66	18.13	18.12	3
	25	12	19.64	20.18	20.06	1	18.59	19.07	19.12	2	17.47	17.95	17.90	3
	25	25	19.55	20.04	20.14	1	18.61	19.12	19.14	2	17.53	18.01	17.99	3
	50	0	19.82	20.28	20.22	1	18.54	18.94	18.97	2	17.58	17.97	18.07	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 26115	Mid CH 26365	High CH 26615		Low CH 26115	Mid CH 26365	High CH 26615		Low CH 26115	Mid CH 26365	High CH 26615	
			1857.5 MHz	1882.5 MHz	1907.5 MHz		1857.5 MHz	1882.5 MHz	1907.5 MHz		1857.5 MHz	1882.5 MHz	1907.5 MHz	
25 / 15M	1	0	20.71	21.15	21.06	0	19.87	20.41	20.30	1	18.82	19.38	19.35	2
	1	37	20.63	21.15	21.08	0	20.06	20.58	20.59	1	18.91	19.31	19.34	2
	1	74	20.15	20.67	20.60	0	19.59	20.17	20.14	1	18.78	19.24	19.35	2
	36	0	19.63	20.15	20.22	1	18.69	19.07	19.20	2	17.71	18.19	18.06	3
	36	19	19.65	20.23	20.06	1	18.53	19.11	19.08	2	17.41	17.89	17.92	3
	36	39	19.53	20.05	20.14	1	18.66	19.10	19.17	2	17.56	18.08	18.01	3
	75	0	19.82	20.26	20.27	1	18.55	18.97	18.90	2	17.57	17.95	18.08	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 26140	Mid CH 26365	High CH 26590		Low CH 26140	Mid CH 26365	High CH 26590		Low CH 26140	Mid CH 26365	High CH 26590	
			1860.0 MHz	1882.5 MHz	1905.0 MHz		1860.0 MHz	1882.5 MHz	1905.0 MHz		1860.0 MHz	1882.5 MHz	1905.0 MHz	
25 / 20M	1	0	20.72	21.19	21.14	0	19.90	20.42	20.36	1	18.88	19.41	19.39	2
	1	50	20.67	21.18	21.14	0	20.10	20.63	20.61	1	18.93	19.38	19.39	2
	1	99	20.17	20.68	20.64	0	19.65	20.19	20.17	1	18.84	19.32	19.37	2
	50	0	19.69	20.20	20.23	1	18.71	19.15	19.21	2	17.72	18.21	18.14	3
	50	25	19.66	20.25	20.11	1	18.61	19.15	19.13	2	17.48	17.97	17.98	3
	50	50	19.61	20.12	20.16	1	18.69	19.16	19.19	2	17.58	18.09	18.05	3
	100	0	19.83	20.30	20.30	1	18.56	19.02	18.98	2	17.59	18.03	18.09	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 26697	Mid CH 26865	High CH 27033		Low CH 26697	Mid CH 26865	High CH 27033		Low CH 26697	Mid CH 26865	High CH 27033	
			814.7 MHz	831.5 MHz	848.3 MHz		814.7 MHz	831.5 MHz	848.3 MHz		814.7 MHz	831.5 MHz	848.3 MHz	
26 / 1.4M	1	0	22.59	22.95	22.94	0	21.86	22.06	22.14	1	20.82	21.16	21.19	2
	1	2	22.37	22.56	22.68	0	21.81	21.93	22.09	1	20.40	20.64	20.71	2
	1	5	23.26	23.43	23.53	0	21.79	21.90	22.03	1	20.61	20.69	20.81	2
	3	0	22.82	22.98	23.14	0	21.76	21.95	22.09	1	20.70	20.92	21.04	2
	3	1	22.53	22.66	22.66	0	21.51	21.70	21.82	1	20.54	20.80	20.66	2
	3	3	22.34	22.51	22.67	0	21.27	21.58	21.62	1	20.37	20.52	20.65	2
	6	0	21.74	21.87	21.89	1	20.65	20.81	20.94	2	19.65	19.78	19.88	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 26705	Mid CH 26865	High CH 27025		Low CH 26705	Mid CH 26865	High CH 27025		Low CH 26705	Mid CH 26865	High CH 27025	
			815.5 MHz	831.5 MHz	847.5 MHz		815.5 MHz	831.5 MHz	847.5 MHz		815.5 MHz	831.5 MHz	847.5 MHz	
26 / 3M	1	0	22.61	22.97	22.93	0	21.83	22.12	22.17	1	20.88	21.19	21.13	2
	1	7	22.33	22.57	22.68	0	21.78	21.96	22.07	1	20.43	20.58	20.70	2
	1	14	23.22	23.43	23.53	0	21.82	21.90	22.03	1	20.62	20.71	20.81	2
	8	0	21.81	22.01	22.14	1	20.72	20.96	21.09	2	19.73	19.96	20.05	3
	8	3	21.46	21.66	21.68	1	20.56	20.65	20.85	2	19.58	19.74	19.71	3
	8	7	21.31	21.58	21.71	1	20.29	20.56	20.58	2	19.34	19.56	19.61	3
	15	0	21.71	21.88	21.83	1	20.65	20.75	20.97	2	19.67	19.75	19.92	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 26715	Mid CH 26865	High CH 27015		Low CH 26715	Mid CH 26865	High CH 27015		Low CH 26715	Mid CH 26865	High CH 27015	
			816.5 MHz	831.5 MHz	846.5 MHz		816.5 MHz	831.5 MHz	846.5 MHz		816.5 MHz	831.5 MHz	846.5 MHz	
26 / 5M	1	0	22.62	22.92	22.94	0	21.84	22.08	22.17	1	20.82	21.16	21.19	2
	1	12	22.38	22.54	22.68	0	21.75	21.99	22.06	1	20.40	20.64	20.70	2
	1	24	23.23	23.42	23.57	0	21.82	21.90	22.02	1	20.55	20.76	20.81	2
	12	0	21.84	22.01	22.11	1	20.72	20.94	21.06	2	19.74	19.93	20.04	3
	12	6	21.46	21.67	21.69	1	20.53	20.69	20.81	2	19.52	19.81	19.70	3
	12	13	21.35	21.54	21.72	1	20.24	20.58	20.61	2	19.38	19.55	19.58	3
	25	0	21.69	21.91	21.86	1	20.65	20.76	20.94	2	19.63	19.81	19.90	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 26740	Mid CH 26865	High CH 26990		Low CH 26740	Mid CH 26865	High CH 26990		Low CH 26740	Mid CH 26865	High CH 26990	
			819.0 MHz	831.5 MHz	844.0 MHz		819.0 MHz	831.5 MHz	844.0 MHz		819.0 MHz	831.5 MHz	844.0 MHz	
26 / 10M	1	0	22.67	22.99	22.99	0	21.91	22.13	22.19	1	20.89	21.21	21.21	2
	1	24	22.40	22.62	22.70	0	21.83	22.01	22.11	1	20.48	20.66	20.76	2
	1	49	23.28	23.50	23.58	0	21.84	21.98	22.04	1	20.63	20.77	20.83	2
	25	0	21.88	22.06	22.16	1	20.80	21.00	21.14	2	19.78	19.98	20.12	3
	25	12	21.54	21.68	21.74	1	20.59	20.71	20.87	2	19.60	19.82	19.72	3
	25	25	21.39	21.59	21.73	1	20.31	20.63	20.63	2	19.42	19.60	19.66	3
	50	0	21.75	21.93	21.91	1	20.71	20.83	20.99	2	19.69	19.83	19.93	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 26765	Mid CH 26865	High CH 26965		Low CH 26765	Mid CH 26865	High CH 26965		Low CH 26765	Mid CH 26865	High CH 26965	
			821.5 MHz	831.5 MHz	841.5 MHz		821.5 MHz	831.5 MHz	841.5 MHz		821.5 MHz	831.5 MHz	841.5 MHz	
26 / 15M	1	0	22.75	23.03	23.04	0	21.98	22.21	22.25	1	20.97	21.25	21.26	2
	1	37	22.42	22.70	22.71	0	21.86	22.07	22.13	1	20.51	20.72	20.78	2
	1	74	23.36	23.54	23.63	0	21.86	22.05	22.09	1	20.65	20.84	20.88	2
	36	0	21.91	22.12	22.18	1	20.86	21.08	21.16	2	19.84	20.06	20.14	3
	36	19	21.56	21.75	21.79	1	20.61	20.79	20.88	2	19.61	19.84	19.80	3
	36	39	21.45	21.67	21.75	1	20.39	20.67	20.68	2	19.47	19.68	19.72	3
	75	0	21.76	21.95	21.99	1	20.73	20.91	21.00	2	19.70	19.89	19.95	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 27685	Mid CH 27710	High CH 27735		Low CH 27685	Mid CH 27710	High CH 27735		Low CH 27685	Mid CH 27710	High CH 27735	
			2307.5 MHz	2310.0 MHz	2312.5 MHz		2307.5 MHz	2310.0 MHz	2312.5 MHz		2307.5 MHz	2310.0 MHz	2312.5 MHz	
30 / 5M	1	0	22.60	22.58	22.60	0	21.75	21.77	21.80	1	20.78	20.80	20.83	2
	1	12	22.41	22.35	22.41	0	21.58	21.64	21.61	1	20.50	20.56	20.52	2
	1	24	22.53	22.50	22.57	0	21.80	21.74	21.80	1	20.65	20.72	20.71	2
	12	0	21.49	21.48	21.48	1	20.39	20.41	20.39	2	19.39	19.38	19.35	3
	12	6	21.42	21.49	21.45	1	20.45	20.49	20.45	2	19.41	19.48	19.47	3
	12	13	21.44	21.43	21.47	1	20.43	20.45	20.48	2	19.47	19.46	19.43	3
	25	0	21.42	21.46	21.43	1	20.40	20.39	20.41	2	19.38	19.42	19.41	3

LTE Band / BW	RB Size	RB Offset	QPSK	3GPP MPR (dB)	16QAM	3GPP MPR (dB)	64QAM	3GPP MPR (dB)
			Mid CH 27710		Mid CH 27710		Mid CH 27710	
			2310.0 MHz		2310.0 MHz		2310.0 MHz	
30 / 10M	1	0	22.65	0	21.82	1	20.85	2
	1	24	22.43	0	21.66	1	20.58	2
	1	49	22.58	0	21.82	1	20.73	2
	25	0	21.53	1	20.47	2	19.43	3
	25	12	21.50	1	20.51	2	19.49	3
	25	25	21.48	1	20.50	2	19.51	3
	50	0	21.48	1	20.46	2	19.44	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 37775	Mid CH 38000	High CH 38225		Low CH 37775	Mid CH 38000	High CH 38225		Low CH 37775	Mid CH 38000	High CH 38225	
			2572.5 MHz	2595.0 MHz	2617.5 MHz		2572.5 MHz	2595.0 MHz	2617.5 MHz		2572.5 MHz	2595.0 MHz	2617.5 MHz	
38 / 5M	1	0	21.93	21.87	22.02	0	20.92	20.95	21.10	1	19.54	19.58	19.77	2
	1	12	21.66	21.60	21.80	0	20.73	20.77	20.94	1	19.48	19.48	19.63	2
	1	24	21.93	21.90	22.11	0	21.08	21.05	21.27	1	19.74	19.78	20.00	2
	12	0	20.78	20.77	20.98	1	19.91	19.86	20.08	2	18.95	18.92	19.00	3
	12	6	20.76	20.81	20.91	1	19.82	19.89	20.01	2	18.75	18.80	18.98	3
	12	13	20.87	20.86	21.12	1	19.94	19.92	20.16	2	18.94	18.93	19.04	3
	25	0	20.91	20.91	21.06	1	19.88	19.82	19.98	2	18.88	18.85	19.08	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 37800	Mid CH 38000	High CH 38200		Low CH 37800	Mid CH 38000	High CH 38200		Low CH 37800	Mid CH 38000	High CH 38200	
			2575.0 MHz	2595.0 MHz	2615.0 MHz		2575.0 MHz	2595.0 MHz	2615.0 MHz		2575.0 MHz	2595.0 MHz	2615.0 MHz	
38 / 10M	1	0	21.90	21.90	22.02	0	20.92	20.92	21.06	1	19.53	19.59	19.74	2
	1	24	21.66	21.60	21.81	0	20.78	20.73	20.97	1	19.53	19.44	19.67	2
	1	49	21.90	21.94	22.07	0	21.08	21.06	21.24	1	19.80	19.72	19.97	2
	25	0	20.79	20.76	21.01	1	19.93	19.84	20.14	2	18.93	18.89	19.06	3
	25	12	20.82	20.75	20.91	1	19.86	19.83	20.06	2	18.82	18.79	18.92	3
	25	25	20.85	20.83	21.11	1	19.93	19.93	20.13	2	18.93	18.90	19.06	3
	50	0	20.96	20.91	21.03	1	19.92	19.81	20.02	2	18.93	18.81	19.09	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 37825	Mid CH 38000	High CH 38175		Low CH 37825	Mid CH 38000	High CH 38175		Low CH 37825	Mid CH 38000	High CH 38175	
			2577.5 MHz	2595.0 MHz	2612.5 MHz		2577.5 MHz	2595.0 MHz	2612.5 MHz		2577.5 MHz	2595.0 MHz	2612.5 MHz	
38 / 15M	1	0	21.97	21.90	21.99	0	20.96	20.99	21.06	1	19.55	19.60	19.75	2
	1	37	21.64	21.65	21.76	0	20.77	20.74	20.97	1	19.54	19.43	19.64	2
	1	74	21.96	21.97	22.08	0	21.04	21.11	21.26	1	19.76	19.71	20.00	2
	36	0	20.76	20.77	21.02	1	19.97	19.84	20.15	2	18.98	18.95	19.00	3
	36	19	20.83	20.80	20.91	1	19.80	19.87	20.02	2	18.76	18.73	18.94	3
	36	39	20.83	20.84	21.11	1	19.98	19.91	20.16	2	18.96	18.97	19.08	3
	75	0	20.96	20.89	21.08	1	19.93	19.84	19.95	2	18.92	18.79	19.10	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 37850	Mid CH 38000	High CH 38150		Low CH 37850	Mid CH 38000	High CH 38150		Low CH 37850	Mid CH 38000	High CH 38150	
			2580.0 MHz	2595.0 MHz	2610.0 MHz		2580.0 MHz	2595.0 MHz	2610.0 MHz		2580.0 MHz	2595.0 MHz	2610.0 MHz	
38 / 20M	1	0	21.98	21.94	22.07	0	20.99	21.00	21.12	1	19.61	19.63	19.79	2
	1	50	21.68	21.68	21.82	0	20.81	20.79	20.99	1	19.56	19.50	19.69	2
	1	99	21.98	21.98	22.12	0	21.10	21.13	21.29	1	19.82	19.79	20.02	2
	50	0	20.82	20.82	21.03	1	19.99	19.92	20.16	2	18.99	18.97	19.08	3
	50	25	20.84	20.82	20.96	1	19.88	19.91	20.07	2	18.83	18.81	19.00	3
	50	50	20.91	20.91	21.13	1	20.01	19.97	20.18	2	18.98	18.98	19.12	3
	100	0	20.97	20.93	21.11	1	19.94	19.89	20.03	2	18.94	18.87	19.11	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK					3GPP MPR (dB)	16QAM					3GPP MPR (dB)
			L-CH 39675	M-CH 40148	M-CH 40620	M-CH 41093	H-CH 41565		L-CH 39675	M-CH 40148	M-CH 40620	M-CH 41093	H-CH 41565	
			2498.5 MHz	2545.8 MHz	2593.0 MHz	2640.3 MHz	2687.5 MHz		2498.5 MHz	2545.8 MHz	2593.0 MHz	2640.3 MHz	2687.5 MHz	
41 / 5M	1	0	22.13	22.10	22.30	22.17	22.13	0	21.18	21.24	21.44	21.18	21.27	1
	1	12	22.07	22.04	22.29	22.06	22.10	0	21.34	21.41	21.63	21.39	21.44	1
	1	24	21.40	21.40	21.66	21.38	21.41	0	20.86	20.86	21.13	20.89	20.91	1
	12	0	21.07	21.09	21.35	21.14	21.15	1	20.13	20.11	20.38	20.20	20.26	2
	12	6	21.08	21.16	21.31	21.15	21.08	1	20.04	20.14	20.31	20.11	20.14	2
	12	13	20.91	20.93	21.24	20.96	21.01	1	19.97	19.98	20.27	20.09	20.09	2
	25	0	21.02	21.05	21.25	21.03	21.08	1	20.11	20.08	20.29	20.10	20.17	2

LTE Band / BW	RB Size	RB Offset	64QAM					3GPP MPR (dB)
			L-CH 39675	M-CH 40148	M-CH 40620	M-CH 41093	H-CH 41565	
			2498.5 MHz	2545.8 MHz	2593.0 MHz	2640.3 MHz	2687.5 MHz	
41 / 5M	1	0	19.86	19.93	20.17	19.96	19.99	2
	1	12	19.72	19.75	19.95	19.85	19.75	2
	1	24	19.33	19.40	19.67	19.41	19.51	2
	12	0	19.15	19.15	19.28	19.20	19.21	3
	12	6	19.06	19.14	19.37	19.20	19.18	3
	12	13	19.00	19.02	19.18	19.04	19.06	3
	25	0	19.07	19.07	19.35	19.10	19.10	3

LTE Band / BW	RB Size	RB Offset	QPSK					3GPP MPR (dB)	16QAM					3GPP MPR (dB)
			L-CH 39700	M-CH 40160	M-CH 40620	M-CH 41080	H-CH 41540		L-CH 39700	M-CH 40160	M-CH 40620	M-CH 41080	H-CH 41540	
			2501.0 MHz	2547.0 MHz	2593.0 MHz	2639.0 MHz	2685.0 MHz		2501.0 MHz	2547.0 MHz	2593.0 MHz	2639.0 MHz	2685.0 MHz	
41 / 10M	1	0	22.10	22.13	22.30	22.15	22.11	0	21.18	21.21	21.40	21.24	21.27	1
	1	24	22.07	22.04	22.30	22.02	22.15	0	21.39	21.37	21.66	21.38	21.43	1
	1	49	21.37	21.44	21.62	21.44	21.39	0	20.86	20.87	21.10	20.95	20.88	1
	25	0	21.08	21.08	21.38	21.10	21.19	1	20.15	20.09	20.44	20.16	20.22	2
	25	12	21.14	21.10	21.31	21.15	21.14	1	20.08	20.08	20.36	20.14	20.13	2
	25	25	20.89	20.90	21.23	21.02	21.02	1	19.96	19.99	20.24	20.08	20.04	2
	50	0	21.07	21.05	21.22	21.06	21.08	1	20.15	20.07	20.33	20.09	20.10	2

LTE Band / BW	RB Size	RB Offset	64QAM					3GPP MPR (dB)
			L-CH 39700	M-CH 40160	M-CH 40620	M-CH 41080	H-CH 41540	
			2501.0 MHz	2547.0 MHz	2593.0 MHz	2639.0 MHz	2685.0 MHz	
41 / 10M	1	0	19.85	19.94	20.14	19.99	20.02	2
	1	24	19.77	19.71	19.99	19.78	19.72	2
	1	49	19.39	19.34	19.64	19.44	19.46	2
	25	0	19.13	19.12	19.34	19.14	19.16	3
	25	12	19.13	19.13	19.31	19.22	19.20	3
	25	25	18.99	18.99	19.20	19.01	19.08	3
	50	0	19.12	19.03	19.36	19.16	19.12	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK					3GPP MPR (dB)	16QAM					3GPP MPR (dB)
			L-CH 39725	M-CH 40173	M-CH 40620	M-CH 41068	H-CH 41515		L-CH 39725	M-CH 40173	M-CH 40620	M-CH 41068	H-CH 41515	
			2503.5 MHz	2548.3 MHz	2593.0 MHz	2637.8 MHz	2682.5 MHz		2503.5 MHz	2548.3 MHz	2593.0 MHz	2637.8 MHz	2682.5 MHz	
41 / 15M	1	0	22.17	22.13	22.27	22.20	22.13	0	21.22	21.28	21.40	21.19	21.30	1
	1	37	22.05	22.09	22.25	22.02	22.15	0	21.38	21.38	21.66	21.35	21.38	1
	1	74	21.43	21.47	21.63	21.40	21.41	0	20.82	20.92	21.12	20.95	20.92	1
	36	0	21.05	21.09	21.39	21.14	21.21	1	20.19	20.09	20.45	20.20	20.27	2
	36	19	21.15	21.15	21.31	21.20	21.09	1	20.02	20.12	20.32	20.11	20.14	2
	36	39	20.87	20.91	21.23	20.98	21.05	1	20.01	19.97	20.27	20.08	20.09	2
	75	0	21.07	21.03	21.27	21.08	21.05	1	20.16	20.10	20.26	20.07	20.12	2

LTE Band / BW	RB Size	RB Offset	64QAM					3GPP MPR (dB)
			L-CH 39725	M-CH 40173	M-CH 40620	M-CH 41068	H-CH 41515	
			2503.5 MHz	2548.3 MHz	2593.0 MHz	2637.8 MHz	2682.5 MHz	
41 / 15M	1	0	19.87	19.95	20.15	19.98	20.03	2
	1	37	19.78	19.70	19.96	19.85	19.72	2
	1	74	19.35	19.33	19.67	19.40	19.51	2
	36	0	19.18	19.18	19.28	19.19	19.20	3
	36	19	19.07	19.07	19.33	19.24	19.19	3
	36	39	19.02	19.06	19.22	19.01	19.08	3
	75	0	19.11	19.01	19.37	19.16	19.15	3

LTE Band / BW	RB Size	RB Offset	QPSK					3GPP MPR (dB)	16QAM					3GPP MPR (dB)
			L-CH 39750	M-CH 40185	M-CH 40620	M-CH 41055	H-CH 41490		L-CH 39750	M-CH 40185	M-CH 40620	M-CH 41055	H-CH 41490	
			2506.0 MHz	2549.5 MHz	2593.0 MHz	2636.5 MHz	2680.0 MHz		2506.0 MHz	2549.5 MHz	2593.0 MHz	2636.5 MHz	2680.0 MHz	
41 / 20M	1	0	22.18	22.17	22.35	22.22	22.19	0	21.25	21.29	21.46	21.26	21.32	1
	1	50	22.09	22.12	22.31	22.10	22.17	0	21.42	21.43	21.68	21.43	21.45	1
	1	99	21.45	21.48	21.67	21.46	21.47	0	20.88	20.94	21.15	20.97	20.96	1
	50	0	21.11	21.14	21.40	21.18	21.22	1	20.21	20.17	20.46	20.24	20.28	2
	50	25	21.16	21.17	21.36	21.21	21.16	1	20.10	20.16	20.37	20.17	20.19	2
	50	50	20.95	20.98	21.25	21.03	21.07	1	20.04	20.03	20.29	20.10	20.11	2
	100	0	21.08	21.07	21.30	21.11	21.10	1	20.17	20.15	20.34	20.15	20.18	2

LTE Band / BW	RB Size	RB Offset	64QAM					3GPP MPR (dB)
			L-CH 39750	M-CH 40185	M-CH 40620	M-CH 41055	H-CH 41490	
			2506.0 MHz	2549.5 MHz	2593.0 MHz	2636.5 MHz	2680.0 MHz	
41 / 20M	1	0	19.93	19.98	20.19	20.01	20.04	2
	1	50	19.80	19.77	20.01	19.86	19.80	2
	1	99	19.41	19.41	19.69	19.46	19.52	2
	50	0	19.19	19.20	19.36	19.22	19.23	3
	50	25	19.14	19.15	19.39	19.25	19.23	3
	50	50	19.04	19.07	19.26	19.06	19.10	3
	100	0	19.13	19.09	19.38	19.18	19.18	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 131979	Mid CH 132322	High CH 132665		Low CH 131979	Mid CH 132322	High CH 132665		Low CH 131979	Mid CH 132322	High CH 132665	
			1710.7 MHz	1745.0 MHz	1779.3 MHz		1710.7 MHz	1745.0 MHz	1779.3 MHz		1710.7 MHz	1745.0 MHz	1779.3 MHz	
66 / 1.4M	1	0	20.24	20.34	20.28	0	19.54	19.63	19.59	1	18.35	18.49	18.50	2
	1	2	20.64	20.71	20.71	0	19.69	19.71	19.79	1	18.27	18.37	18.35	2
	1	5	20.40	20.45	20.43	0	19.65	19.75	19.80	1	18.72	18.73	18.84	2
	3	0	20.29	20.41	20.46	0	19.02	19.04	19.10	1	18.24	18.34	18.25	2
	3	1	20.33	20.40	20.30	0	19.26	19.46	19.40	1	18.24	18.36	18.33	2
	3	3	20.27	20.34	20.40	0	19.37	19.42	19.49	1	18.33	18.40	18.43	2
	6	0	19.37	19.38	19.42	1	18.32	18.41	18.34	2	17.33	17.35	17.41	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 131987	Mid CH 132322	High CH 132657		Low CH 131987	Mid CH 132322	High CH 132657		Low CH 131987	Mid CH 132322	High CH 132657	
			1711.5 MHz	1745.0 MHz	1778.5 MHz		1711.5 MHz	1745.0 MHz	1778.5 MHz		1711.5 MHz	1745.0 MHz	1778.5 MHz	
66 / 3M	1	0	20.26	20.36	20.27	0	19.51	19.69	19.62	1	18.41	18.52	18.44	2
	1	7	20.60	20.72	20.71	0	19.66	19.74	19.77	1	18.30	18.31	18.34	2
	1	14	20.36	20.45	20.43	0	19.68	19.75	19.80	1	18.73	18.75	18.84	2
	8	0	19.28	19.44	19.46	1	17.98	18.05	18.10	2	17.27	17.38	17.26	3
	8	3	19.26	19.40	19.32	1	18.31	18.41	18.43	2	17.28	17.30	17.38	3
	8	7	19.24	19.41	19.44	1	18.39	18.40	18.45	2	17.30	17.44	17.39	3
	15	0	19.34	19.39	19.36	1	18.32	18.35	18.37	2	17.35	17.32	17.45	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 131997	Mid CH 132322	High CH 132647		Low CH 131997	Mid CH 132322	High CH 132647		Low CH 131997	Mid CH 132322	High CH 132647	
			1712.5 MHz	1745.0 MHz	1777.5 MHz		1712.5 MHz	1745.0 MHz	1777.5 MHz		1712.5 MHz	1745.0 MHz	1777.5 MHz	
66 / 5M	1	0	20.27	20.31	20.28	0	19.52	19.65	19.62	1	18.35	18.49	18.50	2
	1	12	20.65	20.69	20.71	0	19.63	19.77	19.76	1	18.27	18.37	18.34	2
	1	24	20.37	20.44	20.47	0	19.68	19.75	19.79	1	18.66	18.80	18.84	2
	12	0	19.31	19.44	19.43	1	17.98	18.03	18.07	2	17.28	17.35	17.25	3
	12	6	19.26	19.41	19.33	1	18.28	18.45	18.39	2	17.22	17.37	17.37	3
	12	13	19.28	19.37	19.45	1	18.34	18.42	18.48	2	17.34	17.43	17.36	3
	25	0	19.32	19.42	19.39	1	18.32	18.36	18.34	2	17.31	17.38	17.43	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 132022	Mid CH 132322	High CH 132622		Low CH 132022	Mid CH 132322	High CH 132622		Low CH 132022	Mid CH 132322	High CH 132622	
			1715.0 MHz	1745.0 MHz	1775.0 MHz		1715.0 MHz	1745.0 MHz	1775.0 MHz		1715.0 MHz	1745.0 MHz	1775.0 MHz	
66 / 10M	1	0	20.24	20.34	20.28	0	19.52	19.62	19.58	1	18.34	18.50	18.47	2
	1	24	20.65	20.69	20.72	0	19.68	19.73	19.79	1	18.32	18.33	18.38	2
	1	49	20.34	20.48	20.43	0	19.68	19.76	19.76	1	18.72	18.74	18.81	2
	25	0	19.32	19.43	19.46	1	18.00	18.01	18.13	2	17.26	17.32	17.31	3
	25	12	19.32	19.35	19.33	1	18.32	18.39	18.44	2	17.29	17.36	17.31	3
	25	25	19.26	19.34	19.44	1	18.33	18.43	18.45	2	17.33	17.40	17.38	3
	50	0	19.37	19.42	19.36	1	18.36	18.35	18.38	2	17.36	17.34	17.44	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 132047	Mid CH 132322	High CH 132597		Low CH 132047	Mid CH 132322	High CH 132597		Low CH 132047	Mid CH 132322	High CH 132597	
			1717.5 MHz	1745.0 MHz	1772.5 MHz		1717.5 MHz	1745.0 MHz	1772.5 MHz		1717.5 MHz	1745.0 MHz	1772.5 MHz	
66 / 15M	1	0	20.31	20.34	20.25	0	19.56	19.69	19.58	1	18.36	18.51	18.48	2
	1	37	20.63	20.74	20.67	0	19.67	19.74	19.79	1	18.33	18.32	18.35	2
	1	74	20.40	20.51	20.44	0	19.64	19.81	19.78	1	18.68	18.73	18.84	2
	36	0	19.29	19.44	19.47	1	18.04	18.01	18.14	2	17.31	17.38	17.25	3
	36	19	19.33	19.40	19.33	1	18.26	18.43	18.40	2	17.23	17.30	17.33	3
	36	39	19.24	19.35	19.44	1	18.38	18.41	18.48	2	17.36	17.47	17.40	3
	75	0	19.37	19.40	19.41	1	18.37	18.38	18.31	2	17.35	17.32	17.45	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 132072	Mid CH 132322	High CH 132572		Low CH 132072	Mid CH 132322	High CH 132572		Low CH 132072	Mid CH 132322	High CH 132572	
			1720.0 MHz	1745.0 MHz	1770.0 MHz		1720.0 MHz	1745.0 MHz	1770.0 MHz		1720.0 MHz	1745.0 MHz	1770.0 MHz	
66 / 20M	1	0	20.32	20.38	20.33	0	19.59	19.70	19.64	1	18.42	18.54	18.52	2
	1	50	20.67	20.77	20.73	0	19.71	19.79	19.81	1	18.35	18.39	18.40	2
	1	99	20.42	20.52	20.48	0	19.70	19.83	19.81	1	18.74	18.81	18.86	2
	50	0	19.35	19.49	19.48	1	18.06	18.09	18.15	2	17.32	17.40	17.33	3
	50	25	19.34	19.42	19.38	1	18.34	18.47	18.45	2	17.30	17.38	17.39	3
	50	50	19.32	19.42	19.46	1	18.41	18.47	18.50	2	17.38	17.48	17.44	3
	100	0	19.38	19.44	19.44	1	18.38	18.43	18.39	2	17.37	17.40	17.46	3

FCC SAR Test Report

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 133147	Mid CH 133247	High CH 133447		Low CH 133147	Mid CH 133247	High CH 133447		Low CH 133147	Mid CH 133247	High CH 133447	
			665.5 MHz	675.5 MHz	695.5 MHz		665.5 MHz	675.5 MHz	695.5 MHz		665.5 MHz	675.5 MHz	695.5 MHz	
71 / 5M	1	0	21.25	21.19	21.14	0	20.17	20.25	19.99	1	19.69	19.79	19.61	2
	1	12	21.68	21.66	21.47	0	20.87	20.93	20.77	1	19.81	19.88	19.60	2
	1	24	21.57	21.58	21.40	0	20.86	20.90	20.75	1	19.70	19.75	19.67	2
	12	0	20.50	20.53	20.42	0	19.70	19.62	19.55	1	18.82	18.81	18.47	2
	12	6	20.45	20.52	20.23	0	19.43	19.57	19.32	1	18.72	18.79	18.63	2
	12	13	20.37	20.40	20.35	0	19.56	19.54	19.46	1	18.81	18.84	18.56	2
	25	0	20.52	20.57	20.32	1	19.47	19.40	19.17	2	18.81	18.75	18.69	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 133172	Mid CH 133272	High CH 133422		Low CH 133172	Mid CH 133272	High CH 133422		Low CH 133172	Mid CH 133272	High CH 133422	
			668 MHz	678 MHz	693 MHz		668 MHz	678 MHz	693 MHz		668 MHz	678 MHz	693 MHz	
71 / 10M	1	0	21.22	21.22	21.14	0	20.17	20.22	19.95	1	19.68	19.80	19.58	2
	1	24	21.68	21.66	21.48	0	20.92	20.89	20.80	1	19.86	19.84	19.64	2
	1	49	21.54	21.62	21.36	0	20.86	20.91	20.72	1	19.76	19.69	19.64	2
	25	0	20.51	20.52	20.45	1	19.72	19.60	19.61	2	18.80	18.78	18.53	3
	25	12	20.51	20.46	20.23	1	19.47	19.51	19.37	2	18.79	18.78	18.57	3
	25	25	20.35	20.37	20.34	1	19.55	19.55	19.43	2	18.80	18.81	18.58	3
	50	0	20.57	20.57	20.29	1	19.51	19.39	19.21	2	18.86	18.71	18.70	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 133197	Mid CH 133297	High CH 133397		Low CH 133197	Mid CH 133297	High CH 133397		Low CH 133197	Mid CH 133297	High CH 133397	
			670.5 MHz	680.5 MHz	690.5 MHz		670.5 MHz	680.5 MHz	690.5 MHz		670.5 MHz	680.5 MHz	690.5 MHz	
71 / 15M	1	0	21.29	21.22	21.11	0	20.21	20.29	19.95	1	19.70	19.81	19.59	2
	1	37	21.66	21.71	21.43	0	20.91	20.90	20.80	1	19.87	19.83	19.61	2
	1	74	21.60	21.65	21.37	0	20.82	20.96	20.74	1	19.72	19.68	19.67	2
	36	0	20.48	20.53	20.46	1	19.76	19.60	19.62	2	18.85	18.84	18.47	3
	36	19	20.52	20.51	20.23	1	19.41	19.55	19.33	2	18.73	18.72	18.59	3
	36	39	20.33	20.38	20.34	1	19.60	19.53	19.46	2	18.83	18.88	18.60	3
	75	0	20.57	20.55	20.34	1	19.52	19.42	19.14	2	18.85	18.69	18.71	3

LTE Band / BW	RB Size	RB Offset	QPSK			3GPP MPR (dB)	16QAM			3GPP MPR (dB)	64QAM			3GPP MPR (dB)
			Low CH 133222	Mid CH 133322	High CH 133372		Low CH 133222	Mid CH 133322	High CH 133372		Low CH 133222	Mid CH 133322	High CH 133372	
			673 MHz	683 MHz	688 MHz		673 MHz	683 MHz	688 MHz		673 MHz	683 MHz	688 MHz	
71 / 20M	1	0	21.30	21.26	21.19	0	20.24	20.30	20.01	1	19.76	19.84	19.63	2
	1	50	21.70	21.74	21.49	0	20.95	20.95	20.82	1	19.89	19.90	19.66	2
	1	99	21.62	21.66	21.41	0	20.88	20.98	20.77	1	19.78	19.76	19.69	2
	50	0	20.54	20.58	20.47	1	19.78	19.68	19.63	2	18.86	18.86	18.55	3
	50	25	20.53	20.53	20.28	1	19.49	19.59	19.38	2	18.80	18.80	18.65	3
	50	50	20.41	20.45	20.36	1	19.63	19.59	19.48	2	18.85	18.89	18.64	3
	100	0	20.58	20.59	20.37	1	19.53	19.47	19.22	2	18.87	18.77	18.72	3

FCC SAR Test Report

<Power for LTE Uplink CA>

The conducted power for uplink CA active was measured on the highest reported SAR configuration for each exposure condition with both two carrier components was set to largest channel bandwidth.

7C							
Combination 20MHz+20MHz (100RB+100RB)							
PCC Channel	SCC Channel	Modulation	PCC		SCC		Measured Power (dBm)
			RB Size	RB offset	RB Size	RB offset	
20850	21048	QPSK	1	0	0	0	19.28
			1	99	1	0	21.45
		16QAM	1	0	0	0	18.73
			1	99	1	0	20.76
		64QAM	1	0	0	0	18.47
			1	99	1	0	19.79
21001	21199	QPSK	1	0	0	0	19.17
			1	99	1	0	21.07
		16QAM	1	0	0	0	18.52
			1	99	1	0	20.60
		64QAM	1	0	0	0	18.17
			1	99	1	0	19.51
21152	21350	QPSK	1	0	0	0	19.21
			1	99	1	0	21.64
		16QAM	1	0	0	0	18.52
			1	99	1	0	20.92
		64QAM	1	0	0	0	18.03
			1	99	1	0	19.87

FCC SAR Test Report

2.4GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)
	802.11b 1Mbps	1	2412	12.75
		6	2437	13.64
		11	2462	14.21
	802.11g 6Mbps	1	2412	14.02
		6	2437	14.32
		11	2462	13.70
	802.11n-HT20 MCS0	1	2412	13.75
		6	2437	14.24
		11	2462	13.85
	802.11n-HT40 MCS0	3	2422	13.99
		6	2437	16.02
		9	2452	13.38

FCC SAR Test Report

Bluetooth			
Mode	Channel	Frequency (MHz)	Average Power (dBm)
BR / EDR	0	2402	3.41
	39	2441	2.72
	78	2480	4.51
BLE 1Mbps	0	2402	2.42
	19	2440	1.81
	39	2480	3.49
BLE 2Mbps	0	2402	-0.42
	19	2440	-0.62
	39	2480	0.91
BLE S2	0	2402	2.01
	19	2440	1.96
	39	2480	2.90
BLE S8	0	2402	3.67
	19	2440	3.15
	39	2480	4.71
2 nd BLE 1Mbps	0	2402	2.88
	19	2440	3.71
	39	2480	4.42
2 nd BLE 2Mbps	0	2402	1.43
	19	2440	2.33
	39	2480	3.05
2 nd BLE S2	0	2402	3.18
	19	2440	3.54
	39	2480	4.31
2 nd BLE S8	0	2402	3.37
	19	2440	4.17
	39	2480	4.73

FCC SAR Test Report

5.2GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)
	802.11a 6Mbps	36	5180	13.38
		40	5200	15.58
		44	5220	15.78
		48	5240	15.80
	802.11n-HT20 MCS0	36	5180	12.65
		40	5200	15.38
		44	5220	15.52
		48	5240	15.58
	802.11n-HT40 MCS0	38	5190	8.80
		46	5230	15.40
	802.11ac-VHT20 MCS0	36	5180	12.60
		40	5200	15.35
		44	5220	15.48
		48	5240	15.52
	802.11ac-VHT40 MCS0	38	5190	8.94
		46	5230	15.16
	802.11ac-VHT80 MCS0	42	5210	7.43

5.3GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)
	802.11a 6Mbps	52	5260	15.30
		56	5280	15.88
		60	5300	15.90
		64	5320	15.36
	802.11n-HT20 MCS0	52	5260	15.60
		56	5280	15.40
		60	5300	15.42
		64	5320	13.45
	802.11n-HT40 MCS0	54	5270	14.78
		62	5310	9.18
	802.11ac-VHT20 MCS0	52	5260	15.72
		56	5280	15.52
		60	5300	15.60
		64	5320	13.40
	802.11ac-VHT40 MCS0	54	5270	15.12
		62	5310	10.18
	802.11ac-VHT80 MCS0	58	5290	9.22

FCC SAR Test Report

5.6GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)
	802.11a 6Mbps	100	5500	14.30
		116	5580	14.58
		124	5620	16.70
		132	5660	16.29
		140	5700	14.30
		144	5720	16.38
	802.11n-HT20 MCS0	100	5500	14.10
		116	5580	14.32
		124	5620	15.85
		132	5660	15.35
		140	5700	14.20
		144	5720	15.42
	802.11n-HT40 MCS0	102	5510	13.46
		110	5550	13.90
		126	5630	16.08
		134	5670	13.42
		142	5710	15.40
	802.11ac-VHT20 MCS0	100	5500	14.08
		116	5580	14.32
		124	5620	15.80
		132	5660	15.37
		140	5700	13.23
		144	5720	15.41
	802.11ac-VHT40 MCS0	102	5510	12.58
		110	5550	13.92
		126	5630	15.28
		134	5670	15.30
		142	5710	14.60
	802.11ac-VHT80 MCS0	106	5530	10.35
		122	5610	14.24
		138	5690	13.35

FCC SAR Test Report

5.8GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)
	802.11a 6Mbps	149	5745	17.28
		157	5785	17.45
		165	5825	16.80
	802.11n-HT20 MCS0	149	5745	16.28
		157	5785	16.60
		165	5825	15.80
	802.11n-HT40 MCS0	151	5755	16.65
		159	5795	16.69
	802.11ac-VHT20 MCS0	149	5745	16.26
		157	5785	16.60
		165	5825	15.82
	802.11ac-VHT40 MCS0	151	5755	15.58
		159	5795	15.85
	802.11ac-VHT80 MCS0	155	5775	14.72

4.6 SAR Testing Results

4.6.1 SAR Test Reduction Considerations

<KDB 447498 D01, General RF Exposure Guidance>

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1) ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- (2) ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- (3) ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

<KDB 941225 D01, 3G SAR Measurement Procedures>

The mode tested for SAR is referred to as the primary mode. The equivalent modes considered for SAR test reduction are denoted as secondary modes. Both primary and secondary modes must be in the same frequency band. When the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq 1/4$ dB higher than the primary mode or when the highest reported SAR of the primary mode is scaled by the ratio of specified maximum output power and tune-up tolerance of secondary to primary mode and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for the secondary mode.

<KDB 941225 D05, SAR Evaluation Considerations for LTE Devices>

(1) QPSK with 1 RB and 50% RB allocation

Start with the largest channel bandwidth and measure SAR, using the RB offset and required test channel combination with the highest maximum output power among RB offsets at the upper edge, middle and lower edge of each required test channel. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required; otherwise, SAR is required for the remaining required test channels and only for the RB offset configuration with the highest output power for that channel. When the reported SAR of a required test channel is > 1.45 W/kg, SAR is required for all three RB offset configurations for that required test channel.

(2) QPSK with 100% RB allocation

SAR is not required when the highest maximum output power for 100% RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.

(3) Higher order modulations

SAR is required only when the highest maximum output power for the configuration in the higher order modulation is $> 1/2$ dB higher than the same configuration in QPSK or when the reported SAR for the QPSK configuration is > 1.45 W/kg.

(4) Other channel bandwidth

SAR is required when the highest maximum output power of the smaller channel bandwidth is $> 1/2$ dB higher than the equivalent channel configurations in the largest channel bandwidth configuration or the reported SAR of a configuration for the largest channel bandwidth is > 1.45 W/kg.

<KDB 248227 D01, SAR Guidance for Wi-Fi Transmitters>

- (1) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is ≤ 0.4 W/kg, SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
- (2) For WLAN 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is ≤ 0.8 W/kg, no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is ≤ 1.2 W/kg.
- (3) For WLAN 5 GHz, the initial test configuration was selected according to the transmission mode with the highest maximum output power. When the reported SAR of initial test configuration is > 0.8 W/kg, SAR is required for the subsequent highest measured output power channel until the reported SAR result is ≤ 1.2 W/kg or all required channels are measured. For other transmission modes, SAR is not required when the highest reported SAR for initial test configuration is adjusted by the ratio of subsequent test configuration to initial test configuration specified maximum output power and it is ≤ 1.2 W/kg.
- (4) For WLAN MIMO mode, the power-based standalone SAR test exclusion or the sum of SAR provision in KDB 447498 to determine simultaneous transmission SAR test exclusion should be applied. Otherwise, SAR for MIMO mode will be measured with all applicable antennas transmitting simultaneously at the specified maximum output power of MIMO operation.

FCC SAR Test Report

4.6.2 SAR Results for Head Exposure Condition

Plot No.	Band	Mode	Test Position	Ch.	Sample	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Tune-up Scaling Factor	Scaled SAR-1g (W/kg)
1	GSM850	GPRS10	Right Cheek	128	1	30.5	30.30	0.19	0.464	1.05	0.49
	GSM850	GPRS10	Right Cheek	128	2	30.5	30.30	0.12	0.440	1.05	0.46
2	GSM1900	GPRS11	Right Cheek	810	1	26.5	26.30	0.12	0.106	1.05	0.11
	GSM1900	GPRS11	Right Cheek	810	2	26.5	26.30	0.02	0.074	1.05	0.08
3	WCDMA II	RMC12.2K	Right Cheek	9538	1	22.0	21.83	0.12	0.275	1.04	0.29
	WCDMA II	RMC12.2K	Right Cheek	9538	2	22.0	21.83	0.123	0.271	1.04	0.28
4	WCDMA IV	RMC12.2K	Right Cheek	1312	1	21.5	21.41	0.13	0.235	1.02	0.24
	WCDMA IV	RMC12.2K	Right Cheek	1312	2	21.5	21.41	0.07	0.200	1.02	0.20
5	WCDMA V	RMC12.2K	Right Cheek	4132	1	24.0	23.66	-0.04	0.370	1.08	0.40
	WCDMA V	RMC12.2K	Right Cheek	4132	2	24.0	23.66	-0.02	0.278	1.08	0.30

Plot No.	Band	Mode	Test Position	Ch.	RB#	RB Offset	Sample	Duty Cycle %	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Duty Cycle Scaling Factor	Tune-up Scaling Factor	Scaled SAR-1g (W/kg)
6	LTE 5	QPSK10M	Left Cheek	20525	1	49	1	-	24.5	23.05	0.04	0.420	1.00	1.40	0.59
	LTE 5	QPSK10M	Left Cheek	20525	1	49	2	-	24.5	23.05	0.02	0.367	1.00	1.40	0.51
7	LTE 7	QPSK20M	Left Cheek	21100	1	0	1	-	22.0	21.80	0.11	0.140	1.00	1.05	0.15
	LTE 7	QPSK20M	Left Cheek	21100	1	0	2	-	22.0	21.80	0.04	0.102	1.00	1.05	0.11
8	LTE 12	QPSK10M	Left Cheek	23060	1	0	1	-	23.5	23.22	0.08	0.186	1.00	1.07	0.20
	LTE 12	QPSK10M	Left Cheek	23060	1	0	2	-	23.5	23.22	0.14	0.160	1.00	1.07	0.17
9	LTE 13	QPSK10M	Right Cheek	23230	1	0	1	-	24.0	23.56	0.02	0.385	1.00	1.11	0.43
	LTE 13	QPSK10M	Right Cheek	23230	1	0	2	-	24.0	23.56	0.07	0.359	1.00	1.11	0.40
10	LTE 14	QPSK10M	Right Cheek	23330	1	0	1	-	24.0	23.65	0.16	0.274	1.00	1.08	0.30
	LTE 14	QPSK10M	Right Cheek	23330	1	0	2	-	24.0	23.65	0.13	0.252	1.00	1.08	0.27
11	LTE 25	QPSK20M	Right Cheek	26590	1	0	1	-	21.5	21.14	0.13	0.167	1.00	1.09	0.18
	LTE 25	QPSK20M	Right Cheek	26590	1	0	2	-	21.5	21.14	0.05	0.159	1.00	1.09	0.17
12	LTE 26	QPSK15M	Left Cheek	26965	1	74	1	-	24.5	23.63	0.07	0.240	1.00	1.22	0.29
	LTE 26	QPSK15M	Left Cheek	26965	1	74	2	-	24.5	23.63	0.08	0.191	1.00	1.22	0.23
13	LTE 30	QPSK10M	Left Cheek	27710	1	0	1	-	24.0	22.65	0.12	0.206	1.00	1.36	0.28
	LTE 30	QPSK10M	Left Cheek	27710	1	0	2	-	24.0	22.65	0.03	0.203	1.00	1.36	0.28
14	LTE 41	QPSK20M	Left Cheek	41055	1	0	1	62.9	23.0	22.22	0.06	0.138	1.01	1.20	0.17
	LTE 41	QPSK20M	Left Cheek	41055	1	0	2	62.9	23.0	22.22	0.12	0.102	1.01	1.20	0.12
15	LTE 66	QPSK20M	Right Cheek	132072	1	50	1	-	21.0	20.67	0.11	0.132	1.00	1.08	0.14
	LTE 66	QPSK20M	Right Cheek	132072	1	50	2	-	21.0	20.67	0.03	0.117	1.00	1.08	0.13
16	LTE 71	QPSK20M	Right Cheek	133222	1	50	1	-	23.0	21.70	0.13	0.217	1.00	1.35	0.29
	LTE 71	QPSK20M	Right Cheek	133222	1	50	2	-	23.0	21.70	0.06	0.179	1.00	1.35	0.24

Plot No.	Band	Mode	Test Position	Ch.	Sample	Duty Cycle %	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Duty Cycle Scaling Factor	Tune-up Scaling Factor	Scaled SAR-1g (W/kg)
17	WLAN2.4G	802.11b	Left Cheek	11	1	100	15.5	14.21	0.06	0.399	1.00	1.35	0.54
	WLAN2.4G	802.11b	Left Cheek	11	2	100	15.5	14.21	0.17	0.259	1.00	1.35	0.35
18	WLAN5G	802.11a	Left Cheek	60	1	97.2	16.0	15.90	0.06	0.869	1.03	1.02	0.91
	WLAN5G	802.11a	Left Cheek	52	1	97.2	16.0	15.30	0.05	0.712	1.03	1.17	0.86
	WLAN5G	802.11a	Left Cheek	56	1	97.2	16.0	15.88	0.05	0.762	1.03	1.03	0.81
	WLAN5G	802.11a	Left Cheek	64	1	97.2	16.0	15.36	0.07	0.767	1.03	1.16	0.91
	WLAN5G	802.11a	Left Cheek	60	2	97.2	16.0	15.90	0.04	0.732	1.03	1.02	0.77
19	WLAN5G	802.11a	Left Cheek	144	1	97.2	17.0	16.38	0.05	0.956	1.03	1.15	1.13
	WLAN5G	802.11a	Left Cheek	100	1	97.2	15.0	14.30	0.1	0.511	1.03	1.17	0.62
	WLAN5G	802.11a	Left Cheek	116	1	97.2	15.0	14.58	0.1	0.488	1.03	1.10	0.55
	WLAN5G	802.11a	Left Cheek	124	1	97.2	17.0	16.70	0.06	0.847	1.03	1.07	0.93
	WLAN5G	802.11a	Left Cheek	132	1	97.2	17.0	16.29	0.09	0.757	1.03	1.18	0.92
	WLAN5G	802.11a	Left Cheek	140	1	97.2	15.0	14.30	0.02	0.575	1.03	1.17	0.70
	WLAN5G	802.11a	Left Cheek	144	2	97.2	17.0	16.38	0.06	0.891	1.03	1.15	1.06
20	WLAN5G	802.11a	Left Cheek	157	1	100	18.0	17.45	0.12	1.100	1.00	1.14	1.25
	WLAN5G	802.11a	Left Cheek	149	1	100	18.0	17.28	0.16	0.969	1.00	1.18	1.14
	WLAN5G	802.11a	Left Cheek	165	1	100	17.0	16.80	0.07	1.150	1.00	1.05	1.20

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	Sample	Duty Cycle %	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Duty Cycle Scaling Factor	Tune-up Scaling Factor	Scaled SAR-1g (W/kg)
	WLAN5G	802.11a	Left Cheek	157	2	100	18.0	17.45	0.13	1.020	1.00	1.14	1.16
21	BT	GFSK	Left Cheek	78	1	76.8	6.0	4.51	-0.05	0.053	1.30	1.41	0.10
	BT	GFSK	Left Cheek	78	2	76.8	6.0	4.51	0.01	0.042	1.30	1.41	0.08

4.6.3 SAR Results for Body-worn Exposure Condition (Separation Distance is 1.0 cm Gap)

Plot No.	Band	Mode	Test Position	Ch.	Sample	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Tune-up Scaling Factor	Scaled SAR-1g (W/kg)
22	GSM850	GPRS10	Rear Face	128	1	30.5	30.30	-0.06	0.304	1.05	0.32
	GSM850	GPRS10	Rear Face	128	2	30.5	30.30	0.03	0.266	1.05	0.28
	GSM1900	GPRS11	Rear Face	810	1	26.5	26.30	0.13	1.070	1.05	1.12
23	GSM1900	GPRS11	Rear Face	512	1	26.5	26.03	0.19	1.070	1.11	1.19
	GSM1900	GPRS11	Rear Face	661	1	26.5	26.22	0.07	1.010	1.07	1.08
	GSM1900	GPRS11	Rear Face	512	2	26.5	26.03	0.04	0.988	1.11	1.10
	WCDMA II	RMC12.2K	Rear Face	9400	1	22.0	21.63	0.14	1.080	1.09	1.18
	WCDMA II	RMC12.2K	Rear Face	9262	1	22.0	21.81	0.05	1.110	1.04	1.16
24	WCDMA II	RMC12.2K	Rear Face	9538	1	22.0	21.83	0.04	1.140	1.04	1.19
	WCDMA II	RMC12.2K	Rear Face	9538	2	22.0	21.83	-0.15	0.944	1.04	0.98
25	WCDMA IV	RMC12.2K	Rear Face	1312	1	21.5	21.41	0.12	1.160	1.02	1.18
	WCDMA IV	RMC12.2K	Rear Face	1413	1	21.5	21.45	-0.04	1.160	1.01	1.17
	WCDMA IV	RMC12.2K	Rear Face	1513	1	21.5	21.38	0.13	1.120	1.03	1.15
	WCDMA IV	RMC12.2K	Rear Face	1312	2	21.5	21.41	0.11	0.936	1.02	0.96
26	WCDMA V	RMC12.2K	Rear Face	4132	1	24.0	23.66	-0.14	0.324	1.08	0.35
	WCDMA V	RMC12.2K	Rear Face	4132	2	24.0	23.66	0.12	0.293	1.08	0.32

Plot No.	Band	Mode	Test Position	Ch.	RB#	RB Offset	Sample	Duty Cycle %	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Duty Cycle Scaling Factor	Tune-up Scaling Factor	Scaled SAR-1g (W/kg)
27	LTE 5	QPSK10M	Rear Face	20525	1	49	1	-	24.5	23.20	-0.13	0.358	1.00	1.35	0.48
	LTE 5	QPSK10M	Rear Face	20525	1	49	2	-	24.5	23.20	-0.03	0.331	1.00	1.35	0.45
28	LTE 7	QPSK20M	Rear Face	21350	1	0	1	-	22.0	21.55	0.07	0.834	1.00	1.11	0.93
	LTE 7	QPSK20M	Rear Face	20850	1	0	1	-	22.0	21.50	0.06	0.629	1.00	1.12	0.71
	LTE 7	QPSK20M	Rear Face	21100	1	0	1	-	22.0	21.80	0.14	0.812	1.00	1.05	0.85
	LTE 7	QPSK20M	Rear Face	21350	1	0	2	-	22.0	21.55	0.04	0.718	1.00	1.11	0.80
29	LTE 12	QPSK10M	Rear Face	23060	1	0	1	-	23.5	23.22	0.11	0.245	1.00	1.07	0.26
	LTE 12	QPSK10M	Rear Face	23060	1	0	2	-	23.5	23.22	-0.03	0.207	1.00	1.07	0.22
30	LTE 13	QPSK10M	Rear Face	23230	1	0	1	-	24.0	23.56	-0.09	0.472	1.00	1.11	0.52
	LTE 13	QPSK10M	Rear Face	23230	1	0	2	-	24.0	23.56	0.03	0.420	1.00	1.11	0.46
31	LTE 14	QPSK10M	Rear Face	23330	1	0	1	-	24.0	23.65	0.07	0.338	1.00	1.08	0.37
	LTE 14	QPSK10M	Rear Face	23330	1	0	2	-	24.0	23.65	0.01	0.318	1.00	1.08	0.34
	LTE 25	QPSK20M	Rear Face	26365	1	0	1	-	21.5	21.19	-0.08	0.806	1.00	1.07	0.87
	LTE 25	QPSK20M	Rear Face	26140	1	0	1	-	21.5	20.72	0.05	0.630	1.00	1.20	0.75
32	LTE 25	QPSK20M	Rear Face	26590	1	0	1	-	21.5	21.14	0.03	0.815	1.00	1.09	0.89
	LTE 25	QPSK20M	Rear Face	26590	1	0	2	-	21.5	21.14	0.17	0.773	1.00	1.09	0.84
33	LTE 26	QPSK15M	Rear Face	26865	1	74	1	-	24.5	23.54	0	0.246	1.00	1.25	0.31
	LTE 26	QPSK15M	Rear Face	26865	1	74	2	-	24.5	23.54	0.05	0.237	1.00	1.25	0.30
34	LTE 30	QPSK10M	Rear Face	27710	1	0	1	-	24.0	22.65	-0.05	0.731	1.00	1.36	1.00
	LTE 30	QPSK10M	Rear Face	27710	1	0	2	-	24.0	22.65	0.07	0.700	1.00	1.36	0.96
35	LTE 41	QPSK20M	Rear Face	40185	1	0	1	62.9	23.0	22.17	0.14	0.545	1.01	1.21	0.66
	LTE 41	QPSK20M	Rear Face	40185	1	0	2	62.9	23.0	22.17	0.05	0.474	1.01	1.21	0.58
36	LTE 66	QPSK20M	Rear Face	132072	1	50	1	-	21.0	20.67	-0.19	0.947	1.00	1.08	1.02
	LTE 66	QPSK20M	Rear Face	132322	1	50	1	-	21.0	20.77	0.12	0.874	1.00	1.05	0.92
	LTE 66	QPSK20M	Rear Face	132572	1	50	1	-	21.0	20.73	0.07	0.808	1.00	1.06	0.86
	LTE 66	QPSK20M	Rear Face	132072	1	50	2	-	21.0	20.67	0.07	0.635	1.00	1.08	0.69
37	LTE 71	QPSK20M	Rear Face	133372	1	50	1	-	23.0	21.49	-0.07	0.347	1.00	1.42	0.49
	LTE 71	QPSK20M	Rear Face	133372	1	50	2	-	23.0	21.49	-0.13	0.285	1.00	1.42	0.40

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	Sample	Duty Cycle %	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Duty Cycle Scaling Factor	Tune-up Scaling Factor	Scaled SAR-1g (W/kg)
38	WLAN2.4G	802.11b	Front Face	11	1	100	15.5	14.21	-0.15	0.091	1.00	1.35	0.12
	WLAN2.4G	802.11b	Front Face	11	2	100	15.5	14.21	0.04	0.059	1.00	1.35	0.08
39	WLAN5G	802.11a	Rear Face	60	1	97.2	16.0	15.90	0.07	0.543	1.03	1.02	0.57
	WLAN5G	802.11a	Rear Face	60	2	97.2	16.0	15.90	0.04	0.388	1.03	1.02	0.41
40	WLAN5G	802.11a	Rear Face	144	1	97.2	17.0	16.38	0.03	0.438	1.03	1.15	0.52
	WLAN5G	802.11a	Rear Face	144	2	97.2	17.0	16.38	-0.15	0.358	1.03	1.15	0.42
41	WLAN5G	802.11a	Rear Face	149	1	100	18.0	17.28	0.03	0.425	1.00	1.18	0.50
	WLAN5G	802.11a	Rear Face	149	2	100	18.0	17.28	-0.06	0.411	1.00	1.18	0.49
42	BT	GFSK	Rear Face	78	1	76.8	6.0	4.51	0.12	0.010	1.30	1.41	0.02
	BT	GFSK	Rear Face	78	2	76.8	6.0	4.51	0.09	0.009	1.30	1.41	0.02

4.6.4 SAR Results for Hotspot Exposure Condition (Separation Distance is 1.0 cm Gap)

Plot No.	Band	Mode	Test Position	Ch.	Sample	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Tune-up Scaling Factor	Scaled SAR-1g (W/kg)
43	GSM850	GPRS10	Rear Face	128	1	30.5	30.30	-0.06	0.304	1.05	0.32
	GSM850	GPRS10	Rear Face	128	2	30.5	30.30	0.03	0.266	1.05	0.28
	GSM1900	GPRS11	Rear Face	810	1	26.5	26.30	0.13	1.070	1.05	1.12
45	GSM1900	GPRS11	Rear Face	512	1	26.5	26.03	0.19	1.070	1.11	1.19
	GSM1900	GPRS11	Rear Face	661	1	26.5	26.22	0.07	1.010	1.07	1.08
	GSM1900	GPRS11	Rear Face	512	2	26.5	26.03	0.04	0.988	1.11	1.10
	WCDMA II	RMC12.2K	Rear Face	9400	1	22.0	21.63	0.14	1.080	1.09	1.18
	WCDMA II	RMC12.2K	Rear Face	9262	1	22.0	21.81	0.05	1.110	1.04	1.16
46	WCDMA II	RMC12.2K	Rear Face	9538	1	22.0	21.83	0.04	1.140	1.04	1.19
	WCDMA II	RMC12.2K	Rear Face	9538	2	22.0	21.83	-0.15	0.944	1.04	0.98
46	WCDMA IV	RMC12.2K	Rear Face	1312	1	21.5	21.41	0.12	1.160	1.02	1.18
	WCDMA IV	RMC12.2K	Rear Face	1413	1	21.5	21.45	-0.04	1.160	1.01	1.17
	WCDMA IV	RMC12.2K	Rear Face	1513	1	21.5	21.38	0.13	1.120	1.03	1.15
	WCDMA IV	RMC12.2K	Rear Face	1312	2	21.5	21.41	0.11	0.936	1.02	0.96
47	WCDMA V	RMC12.2K	Rear Face	4132	1	24.0	23.66	-0.14	0.324	1.08	0.35
	WCDMA V	RMC12.2K	Rear Face	4132	2	24.0	23.66	0.12	0.293	1.08	0.32

Plot No.	Band	Mode	Test Position	Ch.	RB#	RB Offset	Sample	Duty Cycle %	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Duty Cycle Scaling Factor	Tune-up Scaling Factor	Scaled SAR-1g (W/kg)
48	LTE 5	QPSK10M	Rear Face	20525	1	49	1	-	24.5	23.20	-0.13	0.358	1.00	1.35	0.48
	LTE 5	QPSK10M	Rear Face	20525	1	49	2	-	24.5	23.20	-0.03	0.331	1.00	1.35	0.45
49	LTE 7	QPSK20M	Bottom Side	21350	1	0	1	-	22.0	21.55	0.15	1.090	1.00	1.11	1.21
	LTE 7	QPSK20M	Bottom Side	20850	1	0	1	-	22.0	21.50	0.03	0.854	1.00	1.12	0.96
	LTE 7	QPSK20M	Bottom Side	21100	1	0	1	-	22.0	21.80	-0.02	1.090	1.00	1.05	1.14
	LTE 7	QPSK20M	Bottom Side	21350	1	0	2	-	22.0	21.55	-0.15	0.903	1.00	1.11	1.00
50	LTE 12	QPSK10M	Rear Face	23060	1	0	1	-	23.5	23.22	0.11	0.245	1.00	1.07	0.26
	LTE 12	QPSK10M	Rear Face	23060	1	0	2	-	23.5	23.22	-0.03	0.207	1.00	1.07	0.22
51	LTE 13	QPSK10M	Rear Face	23230	1	0	1	-	24.0	23.56	-0.09	0.472	1.00	1.11	0.52
	LTE 13	QPSK10M	Rear Face	23230	1	0	2	-	24.0	23.56	0.03	0.420	1.00	1.11	0.46
52	LTE 14	QPSK10M	Rear Face	23330	1	0	1	-	24.0	23.65	0.07	0.338	1.00	1.08	0.37
	LTE 14	QPSK10M	Rear Face	23330	1	0	2	-	24.0	23.65	0.01	0.318	1.00	1.08	0.34
	LTE 25	QPSK20M	Rear Face	26365	1	0	1	-	21.5	21.19	-0.08	0.806	1.00	1.07	0.87
	LTE 25	QPSK20M	Rear Face	26140	1	0	1	-	21.5	20.72	0.05	0.630	1.00	1.20	0.75
53	LTE 25	QPSK20M	Rear Face	26590	1	0	1	-	21.5	21.14	0.03	0.815	1.00	1.09	0.89
	LTE 25	QPSK20M	Rear Face	26590	1	0	2	-	21.5	21.14	0.17	0.773	1.00	1.09	0.84
54	LTE 26	QPSK15M	Rear Face	26865	1	74	1	-	24.5	23.54	0	0.246	1.00	1.25	0.31
	LTE 26	QPSK15M	Rear Face	26865	1	74	2	-	24.5	23.54	0.05	0.237	1.00	1.25	0.30

FCC SAR Test Report

Plot No.	Band	Mode	Test Position	Ch.	RB#	RB Offset	Sample	Duty Cycle %	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Duty Cycle Scaling Factor	Tune-up Scaling Factor	Scaled SAR-1g (W/kg)
55	LTE 30	QPSK10M	Bottom Side	27710	1	0	1	-	24.0	22.65	-0.08	0.875	1.00	1.36	1.19
	LTE 30	QPSK10M	Bottom Side	27710	1	0	2	-	24.0	22.65	0.07	0.855	1.00	1.36	1.17
56	LTE 41	QPSK20M	Bottom Side	40620	1	0	1	62.9	23.0	22.35	0.01	0.575	1.01	1.21	0.70
	LTE 41	QPSK20M	Bottom Side	40620	1	0	2	62.9	23.0	22.35	0.06	0.504	1.01	1.21	0.61
57	LTE 66	QPSK20M	Rear Face	132072	1	50	1	-	21.0	20.67	-0.19	0.947	1.00	1.08	1.02
	LTE 66	QPSK20M	Rear Face	132322	1	50	1	-	21.0	20.77	0.12	0.874	1.00	1.05	0.92
	LTE 66	QPSK20M	Rear Face	132572	1	50	1	-	21.0	20.73	0.07	0.808	1.00	1.06	0.86
	LTE 66	QPSK20M	Rear Face	132072	1	50	2	-	21.0	20.67	0.07	0.635	1.00	1.08	0.69
58	LTE 71	QPSK20M	Rear Face	133372	1	50	1	-	23.0	21.49	-0.07	0.347	1.00	1.42	0.49
	LTE 71	QPSK20M	Rear Face	133372	1	50	2	-	23.0	21.49	-0.13	0.285	1.00	1.42	0.40

Plot No.	Band	Mode	Test Position	Ch.	Sample	Duty Cycle %	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-1g (W/kg)	Duty Cycle Scaling Factor	Tune-up Scaling Factor	Scaled SAR-1g (W/kg)
59	WLAN2.4G	802.11b	Right Side	11	1	100	15.5	14.21	0.05	0.088	1.00	1.35	0.12
	WLAN2.4G	802.11b	Right Side	11	2	100	15.5	14.21	0.05	0.063	1.00	1.35	0.09
	WLAN5G	802.11a	Right Side	48	1	97.2	16.0	15.80	0.04	1.000	1.03	1.05	1.08
	WLAN5G	802.11a	Right Side	36	1	97.2	14.0	13.38	0.18	0.708	1.03	1.15	0.84
	WLAN5G	802.11a	Right Side	40	1	97.2	16.0	15.58	0.17	0.958	1.03	1.10	1.09
60	WLAN5G	802.11a	Right Side	44	1	97.2	16.0	15.78	0.15	1.020	1.03	1.05	1.10
	WLAN5G	802.11a	Right Side	48	2	97.2	16.0	15.80	0.06	0.856	1.03	1.05	0.92
61	WLAN5G	802.11a	Rear Face	149	1	100	18.0	17.28	0.03	0.425	1.00	1.18	0.50
	WLAN5G	802.11a	Rear Face	149	2	100	18.0	17.28	-0.06	0.411	1.00	1.18	0.49
62	BT	GFSK	Right Side	78	1	76.8	6.0	4.51	0.11	0.014	1.30	1.41	0.03
	BT	GFSK	Right Side	78	2	76.8	6.0	4.51	0.02	0.012	1.30	1.41	0.02

4.6.5 SAR Results for Extremity Exposure Condition (Separation Distance is 0 cm Gap)

Plot No.	Band	Mode	Test Position	Ch.	RB#	RB Offset	Sample	Duty Cycle %	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-10g (W/kg)	Duty Cycle Scaling Factor	Tune-up Scaling Factor	Scaled SAR-10g (W/kg)
63	LTE 7	QPSK20M	Bottom Side	21350	1	0	1	-	22.0	21.55	0.14	1.600	1.00	1.11	1.77
	LTE 7	QPSK20M	Bottom Side	21350	1	0	2	-	22.0	21.55	0.04	1.310	1.00	1.11	1.45

Plot No.	Band	Mode	Test Position	Ch.	Sample	Duty Cycle %	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	Measured SAR-10g (W/kg)	Duty Cycle Scaling Factor	Tune-up Scaling Factor	Scaled SAR-10g (W/kg)
64	WLAN5G	802.11a	Right Side	60	1	97.2	16.0	15.90	0.04	1.350	1.03	1.02	1.42
	WLAN5G	802.11a	Right Side	60	2	97.2	16.0	15.90	0.15	0.979	1.03	1.02	1.03
65	WLAN5G	802.11a	Right Side	144	1	97.2	17.0	16.38	0.07	1.140	1.03	1.15	1.35
	WLAN5G	802.11a	Right Side	144	2	97.2	17.0	16.38	0.04	1.100	1.03	1.15	1.31

4.6.6 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probe calibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium may be used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Band	Test Position	Ch.	Original Measured SAR-1g (W/kg)	1st Repeated SAR-1g (W/kg)	L/S Ratio	2nd Repeated SAR-1g (W/kg)	L/S Ratio	3rd Repeated SAR-1g (W/kg)	L/S Ratio
WCDMA IV	Rear Face	1312	1.160	1.100	1.050	N/A	N/A	N/A	N/A
WCDMA II	Rear Face	9538	1.140	1.120	1.020	N/A	N/A	N/A	N/A
LTE 30	Bottom Side	27710	0.875	0.843	1.040	N/A	N/A	N/A	N/A
LTE 7	Bottom Side	21350	1.090	1.030	1.060	N/A	N/A	N/A	N/A
WLAN5G	Right Side	48	1.050	1.040	1.010	N/A	N/A	N/A	N/A
WLAN5G	Left Cheek	144	0.956	0.951	1.010	N/A	N/A	N/A	N/A
WLAN5G	Left Cheek	165	1.150	1.110	1.040	N/A	N/A	N/A	N/A

FCC SAR Test Report

4.6.7 Simultaneous Multi-band Transmission Evaluation

<SAR Summation Analysis>

Simultaneous transmission SAR test exclusion is determined for each operating configuration and exposure condition according to the reported standalone SAR of each applicable simultaneous transmitting antenna. When the sum of SAR_{1g} of all simultaneously transmitting antennas in an operating mode and exposure condition combination is within the SAR limit (SAR_{1g} 1.6 W/kg), the simultaneous transmission SAR is not required. When the sum of SAR_{1g} is greater than the SAR limit (SAR_{1g} 1.6 W/kg), SAR test exclusion is determined by the SPLSR.

<Head>

WWAN Band	Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)
		WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth		
		1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
GSM850	Right Cheek	0.49	0.13	0.62	0.02	0.62	1.14
	Right Tilted	0.24	0.08	0.58	0.02	0.31	0.84
	Left Cheek	0.34	0.54	1.25	0.10	0.88	1.69
	Left Tilted	0.22	0.15	0.74	0.03	0.38	0.99
GSM1900	Right Cheek	0.11	0.13	0.62	0.02	0.24	0.76
	Right Tilted	0.07	0.08	0.58	0.02	0.15	0.67
	Left Cheek	0.13	0.54	1.25	0.10	0.67	1.48
	Left Tilted	0.11	0.15	0.74	0.03	0.27	0.88
WCDMA II	Right Cheek	0.29	0.13	0.62	0.02	0.42	0.94
	Right Tilted	0.05	0.08	0.58	0.02	0.12	0.65
	Left Cheek	0.09	0.54	1.25	0.10	0.63	1.44
	Left Tilted	0.07	0.15	0.74	0.03	0.22	0.84
WCDMA IV	Right Cheek	0.24	0.13	0.62	0.02	0.37	0.89
	Right Tilted	0.10	0.08	0.58	0.02	0.17	0.70
	Left Cheek	0.12	0.54	1.25	0.10	0.66	1.47
	Left Tilted	0.09	0.15	0.74	0.03	0.24	0.86
WCDMA V	Right Cheek	0.24	0.13	0.62	0.02	0.37	0.89
	Right Tilted	0.31	0.08	0.58	0.02	0.39	0.91
	Left Cheek	0.42	0.54	1.25	0.10	0.96	1.77
	Left Tilted	0.31	0.15	0.74	0.03	0.46	1.08
LTE Band 5	Right Cheek	0.32	0.13	0.62	0.02	0.44	0.96
	Right Tilted	0.34	0.08	0.58	0.02	0.42	0.94
	Left Cheek	0.59	0.54	1.25	0.10	1.13	1.94
	Left Tilted	0.29	0.15	0.74	0.03	0.45	1.06
LTE Band 7	Right Cheek	0.10	0.13	0.62	0.02	0.22	0.74
	Right Tilted	0.04	0.08	0.58	0.02	0.11	0.64
	Left Cheek	0.15	0.54	1.25	0.10	0.69	1.50
	Left Tilted	0.06	0.15	0.74	0.03	0.21	0.83
LTE Band 12	Right Cheek	0.24	0.13	0.62	0.02	0.36	0.88
	Right Tilted	0.18	0.08	0.58	0.02	0.25	0.78

FCC SAR Test Report

WWAN Band	Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)
		WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth		
		1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
	Left Cheek	0.20	0.54	1.25	0.10	0.74	1.55
	Left Tilted	0.22	0.15	0.74	0.03	0.37	0.99
LTE Band 13	Right Cheek	0.43	0.13	0.62	0.02	0.56	1.08
	Right Tilted	0.27	0.08	0.58	0.02	0.35	0.87
	Left Cheek	0.36	0.54	1.25	0.10	0.90	1.71
	Left Tilted	0.25	0.15	0.74	0.03	0.41	1.02
LTE Band 14	Right Cheek	0.30	0.13	0.62	0.02	0.43	0.95
	Right Tilted	0.23	0.08	0.58	0.02	0.31	0.83
	Left Cheek	0.33	0.54	1.25	0.10	0.87	1.68
	Left Tilted	0.21	0.15	0.74	0.03	0.37	0.98
LTE Band 25	Right Cheek	0.18	0.13	0.62	0.02	0.31	0.83
	Right Tilted	0.04	0.08	0.58	0.02	0.12	0.64
	Left Cheek	0.10	0.54	1.25	0.10	0.64	1.45
	Left Tilted	0.07	0.15	0.74	0.03	0.23	0.84
LTE Band 26	Right Cheek	0.42	0.13	0.62	0.02	0.54	1.06
	Right Tilted	0.28	0.08	0.58	0.02	0.35	0.88
	Left Cheek	0.29	0.54	1.25	0.10	0.83	1.64
	Left Tilted	0.23	0.15	0.74	0.03	0.38	1.00
LTE Band 30	Right Cheek	0.17	0.13	0.62	0.02	0.29	0.81
	Right Tilted	0.06	0.08	0.58	0.02	0.14	0.66
	Left Cheek	0.28	0.54	1.25	0.10	0.82	1.63
	Left Tilted	0.08	0.15	0.74	0.03	0.24	0.85
LTE Band 41	Right Cheek	0.06	0.13	0.62	0.02	0.19	0.71
	Right Tilted	0.04	0.08	0.58	0.02	0.12	0.64
	Left Cheek	0.17	0.54	1.25	0.10	0.71	1.52
	Left Tilted	0.05	0.15	0.74	0.03	0.20	0.82
LTE Band 66	Right Cheek	0.14	0.13	0.62	0.02	0.27	0.79
	Right Tilted	0.08	0.08	0.58	0.02	0.16	0.68
	Left Cheek	0.12	0.54	1.25	0.10	0.66	1.47
	Left Tilted	0.09	0.15	0.74	0.03	0.24	0.86
LTE Band 71	Right Cheek	0.29	0.13	0.62	0.02	0.42	0.94
	Right Tilted	0.20	0.08	0.58	0.02	0.27	0.80
	Left Cheek	0.31	0.54	1.25	0.10	0.85	1.66
	Left Tilted	0.18	0.15	0.74	0.03	0.34	0.95

FCC SAR Test Report

<Body Worn>

WWAN Band	Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)
		WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth		
		1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
GSM850	Front	0.20	0.12	0.36	0.02	0.32	0.59
	Back	0.32	0.07	0.57	0.02	0.39	0.91
GSM1900	Front	0.68	0.12	0.36	0.02	0.80	1.06
	Back	1.19	0.07	0.57	0.02	1.26	1.78
WCDMA II	Front	0.62	0.12	0.36	0.02	0.74	1.01
	Back	1.19	0.07	0.57	0.02	1.26	1.78
WCDMA IV	Front	0.46	0.12	0.36	0.02	0.58	0.85
	Back	1.18	0.07	0.57	0.02	1.25	1.77
WCDMA V	Front	0.35	0.12	0.36	0.02	0.47	0.74
	Back	0.35	0.07	0.57	0.02	0.42	0.94
LTE Band 5	Front	0.33	0.12	0.36	0.02	0.45	0.71
	Back	0.48	0.07	0.57	0.02	0.55	1.07
LTE Band 7	Front	0.97	0.12	0.36	0.02	1.09	1.36
	Back	0.93	0.07	0.57	0.02	1.00	1.52
LTE Band 12	Front	0.28	0.12	0.36	0.02	0.40	0.67
	Back	0.26	0.07	0.57	0.02	0.33	0.85
LTE Band 13	Front	0.25	0.12	0.36	0.02	0.37	0.63
	Back	0.52	0.07	0.57	0.02	0.59	1.11
LTE Band 14	Front	0.26	0.12	0.36	0.02	0.38	0.64
	Back	0.37	0.07	0.57	0.02	0.44	0.96
LTE Band 25	Front	0.64	0.12	0.36	0.02	0.76	1.02
	Back	0.89	0.07	0.57	0.02	0.96	1.48
LTE Band 26	Front	0.30	0.12	0.36	0.02	0.42	0.68
	Back	0.31	0.07	0.57	0.02	0.38	0.90
LTE Band 30	Front	0.82	0.12	0.36	0.02	0.94	1.20
	Back	1.00	0.07	0.57	0.02	1.07	1.59
LTE Band 41	Front	0.57	0.12	0.36	0.02	0.69	0.95
	Back	0.66	0.07	0.57	0.02	0.73	1.25
LTE Band 66	Front	0.43	0.12	0.36	0.02	0.55	0.81
	Back	1.02	0.07	0.57	0.02	1.09	1.61
LTE Band 71	Front	0.29	0.12	0.36	0.02	0.41	0.67
	Back	0.49	0.07	0.57	0.02	0.56	1.08

FCC SAR Test Report

<Hotspot>

WWAN Band	Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)
		WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth		
		1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
GSM850	Front	0.20	0.12	0.31	0.02	0.32	0.53
	Back	0.32	0.07	0.50	0.02	0.39	0.84
	Left side	0.16				0.16	0.16
	Right side	0.30	0.12	1.10	0.03	0.42	1.43
	Top side		0.04	0.15	0.01	0.04	0.16
	Bottom side	0.26				0.26	0.26
GSM1900	Front	0.68	0.12	0.31	0.02	0.80	1.01
	Back	1.19	0.07	0.50	0.02	1.26	1.71
	Left side	0.09				0.09	0.09
	Right side	0.16	0.12	1.10	0.03	0.28	1.29
	Top side		0.04	0.15	0.01	0.04	0.16
	Bottom side	0.71				0.71	0.71
WCDMA II	Front	0.62	0.12	0.31	0.02	0.74	0.95
	Back	1.19	0.07	0.50	0.02	1.26	1.71
	Left side	0.07				0.07	0.07
	Right side	0.12	0.12	1.10	0.03	0.24	1.25
	Top side		0.04	0.15	0.01	0.04	0.16
	Bottom side	0.72				0.72	0.72
WCDMA IV	Front	0.46	0.12	0.31	0.02	0.58	0.79
	Back	1.18	0.07	0.50	0.02	1.25	1.70
	Left side	0.06				0.06	0.06
	Right side	0.12	0.12	1.10	0.03	0.24	1.25
	Top side		0.04	0.15	0.01	0.04	0.16
	Bottom side	0.64				0.64	0.64
WCDMA V	Front	0.35	0.12	0.31	0.02	0.47	0.68
	Back	0.35	0.07	0.50	0.02	0.42	0.87
	Left side	0.22				0.22	0.22
	Right side	0.34	0.12	1.10	0.03	0.46	1.47
	Top side		0.04	0.15	0.01	0.04	0.16
	Bottom side	0.37				0.37	0.37
LTE Band 5	Front	0.33	0.12	0.31	0.02	0.45	0.65
	Back	0.48	0.07	0.50	0.02	0.55	1.00
	Left side	0.20				0.20	0.20
	Right side	0.35	0.12	1.10	0.03	0.47	1.48
	Top side		0.04	0.15	0.01	0.04	0.16
	Bottom side	0.33				0.33	0.33
LTE Band 7	Front	0.97	0.12	0.31	0.02	1.09	1.30
	Back	0.93	0.07	0.50	0.02	1.00	1.45

FCC SAR Test Report

WWAN Band	Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3+4 Summed 1g SAR (W/kg)
		WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth		
		1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)		
	Left side	0.25				0.25	0.25
	Right side	0.17	0.12	1.10	0.03	0.29	1.30
	Top side		0.04	0.15	0.01	0.04	0.16
	Bottom side	1.21				1.21	1.21
LTE Band 12	Front	0.28	0.12	0.31	0.02	0.40	0.61
	Back	0.26	0.07	0.50	0.02	0.33	0.78
	Left side	0.28				0.28	0.28
	Right side	0.43	0.12	1.10	0.03	0.55	1.56
	Top side		0.04	0.15	0.01	0.04	0.16
	Bottom side	0.14				0.14	0.14
LTE Band 13	Front	0.25	0.12	0.31	0.02	0.37	0.58
	Back	0.52	0.07	0.50	0.02	0.59	1.04
	Left side	0.15				0.15	0.15
	Right side	0.32	0.12	1.10	0.03	0.44	1.45
	Top side		0.04	0.15	0.01	0.04	0.16
	Bottom side	0.27				0.27	0.27
LTE Band 14	Front	0.26	0.12	0.31	0.02	0.38	0.58
	Back	0.37	0.07	0.50	0.02	0.44	0.89
	Left side	0.14				0.14	0.14
	Right side	0.29	0.12	1.10	0.03	0.41	1.42
	Top side		0.04	0.15	0.01	0.04	0.16
	Bottom side	0.20				0.20	0.20
LTE Band 25	Front	0.64	0.12	0.31	0.02	0.76	0.96
	Back	0.89	0.07	0.50	0.02	0.96	1.41
	Left side	0.07				0.07	0.07
	Right side	0.12	0.12	1.10	0.03	0.24	1.25
	Top side		0.04	0.15	0.01	0.04	0.16
	Bottom side	0.77				0.77	0.77
LTE Band 26	Front	0.30	0.12	0.31	0.02	0.42	0.63
	Back	0.31	0.07	0.50	0.02	0.38	0.83
	Left side	0.29				0.29	0.29
	Right side	0.40	0.12	1.10	0.03	0.52	1.53
	Top side		0.04	0.15	0.01	0.04	0.16
	Bottom side	0.31				0.31	0.31
LTE Band 30	Front	0.82	0.12	0.31	0.02	0.94	1.15
	Back	1.00	0.07	0.50	0.02	1.07	1.52
	Left side	0.21				0.21	0.21
	Right side	0.12	0.12	1.10	0.03	0.24	1.25
	Top side		0.04	0.15	0.01	0.04	0.16