Date: 2022-11-02

01_LTE Band 12_10M_QPSK_1RB_0Offset_Right Cheek_0mm_Ch23095

Communication System: Band 12, E-UTRA/FDD; Frequency: 707.5
Medium: HSL. Medium parameters used: f= 707.5 MHz; σ= 0.863 S/m; ε_r = 42.5
Ambient Temperature: 23.3°C; Liquid Temperature: 22.6°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(10.35, 10.35, 10.35); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.524 W/kg; SAR (10g) = 0.349 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = -0.05 dB
SAR (1g) = 0.544 W/kg; SAR (10g) = 0.322 W/kg;



Date: 2022-11-02

02_LTE Band 17_10M_1RB_0Offset_Right Cheek_0mm_Ch23790

Communication System: Band 17, E-UTRA/FDD; Frequency: 710.0
Medium: HSL. Medium parameters used: f= 710.0 MHz; σ= 0.864 S/m; ε_r = 42.5
Ambient Temperature: 23.3°C; Liquid Temperature: 22.6°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(10.35, 10.35, 10.35); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.754 W/kg; SAR (10g) = 0.451 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = 0.05 dB
SAR (1g) = 0.685 W/kg; SAR (10g) = 0.417 W/kg;



Date: 2022-11-02

03_LTE Band 13_10M_QPSK_1RB_0Offset_Right Cheek_0mm_Ch23230

Communication System: Band 13, E-UTRA/FDD; Frequency: 782.0
Medium: HSL. Medium parameters used: f= 782.0 MHz; σ= 0.896 S/m; ε_r = 42.4
Ambient Temperature: 23.3°C; Liquid Temperature: 22.6°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(10.35, 10.35, 10.35); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.449 W/kg; SAR (10g) = 0.290 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = 0.02 dB
SAR (1g) = 0.468 W/kg; SAR (10g) = 0.266 W/kg;



Date: 2022-11-02

04_LTE Band 14_10M_QPSK_1RB_0Offset_Right Cheek_0mm_Ch23330

Communication System: Band 14, E-UTRA/FDD; Frequency: 793.0
Medium: HSL. Medium parameters used: f= 793.0 MHz; σ= 0.895 S/m; ε_r = 42.4
Ambient Temperature: 23.3°C; Liquid Temperature: 22.6°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(10.35, 10.35, 10.35); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.377 W/kg; SAR (10g) = 0.240 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = 0.04 dB
SAR (1g) = 0.392 W/kg; SAR (10g) = 0.222 W/kg;



Date: 2022-11-02

05_LTE Band 71_20M_QPSK_1RB_0Offset_Right Cheek_0mm_Ch133322

Communication System: Band 71, E-UTRA/FDD; Frequency: 683.0
Medium: HSL. Medium parameters used: f= 683.0 MHz; σ= 0.862 S/m; ε_r = 42.7
Ambient Temperature: 23.3°C; Liquid Temperature: 22.6°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(10.35, 10.35, 10.35); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.270 W/kg; SAR (10g) = 0.182 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = 0.01 dB
SAR (1g) = 0.284 W/kg; SAR (10g) = 0.168 W/kg;



Date: 2022-11-02

06_FR1 n12_15M_QPSK_1RB_1Offset_Right Cheek_0mm_Ch141500

Communication System: Band n12; Frequency: 707.5
Medium: HSL. Medium parameters used: f= 707.5 MHz; σ= 0.863 S/m; ε_r = 42.5
Ambient Temperature: 23.3°C; Liquid Temperature: 22.6°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(10.35, 10.35, 10.35); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.647 W/kg; SAR (10g) = 0.412 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = 0.01 dB
SAR (1g) = 0.632 W/kg; SAR (10g) = 0.397 W/kg;



Date: 2022-11-02

07_FR1 n14_10M_QPSK_1RB_1Offset_Right Cheek_0mm_Ch158600

Communication System: Band n14; Frequency: 793.0
Medium: HSL. Medium parameters used: f= 793.0 MHz; σ= 0.895 S/m; ε_r = 42.4
Ambient Temperature: 23.3°C; Liquid Temperature: 22.6°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(10.35, 10.35, 10.35); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.696 W/kg; SAR (10g) = 0.463 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = 0.02 dB
SAR (1g) = 0.787 W/kg; SAR (10g) = 0.422 W/kg;



Date: 2022-11-02

08_FR1 n71_20M_50RB_28Offset_Left Cheek_0mm_Ch136100

Communication System: Band n71; Frequency: 680.5
Medium: HSL. Medium parameters used: f= 680.5 MHz; σ= 0.862 S/m; ε_r = 42.7
Ambient Temperature: 23.3°C; Liquid Temperature: 22.6°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(10.35, 10.35, 10.35); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.549 W/kg; SAR (10g) = 0.352 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = 0.09 dB
SAR (1g) = 0.316 W/kg; SAR (10g) = 0.229 W/kg;



Date: 2022-11-04

09_GSM850_GPRS (3 Tx slots)_Left Cheek_0mm_Ch189

Communication System: GSM 850; Frequency: 836.4
Medium: HSL. Medium parameters used: f= 836.4 MHz; σ= 0.913 S/m; ε_r = 41.9
Ambient Temperature: 23.1°C; Liquid Temperature: 22.8°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(10.05, 10.05, 10.05); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.243 W/kg; SAR (10g) = 0.183 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = -0.08 dB
SAR (1g) = 0.246 W/kg; SAR (10g) = 0.187 W/kg;



Date: 2022-11-04

10_WCDMA V_RMC 12.2Kbps_Left Cheek_0mm_Ch4182

Communication System: Band 5, UTRA/FDD; Frequency: 836.4
Medium: HSL. Medium parameters used: f= 836.4 MHz; σ= 0.913 S/m; ε_r = 41.9
Ambient Temperature: 23.1°C; Liquid Temperature: 22.8°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(10.05, 10.05, 10.05); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.225 W/kg; SAR (10g) = 0.172 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = -0.04 dB
SAR (1g) = 0.236 W/kg; SAR (10g) = 0.178 W/kg;



Date: 2022-11-04

11_LTE Band 26_15M_QPSK_1RB_0Offset_Right Cheek_0mm_Ch26865

Communication System: Band 26 E-UTRA/FDD; Frequency: 831.5
Medium: HSL. Medium parameters used: f= 831.5 MHz; σ= 0.910 S/m; ε_r = 41.9
Ambient Temperature: 23.1°C; Liquid Temperature: 22.8°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(10.05, 10.05, 10.05); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.721 W/kg; SAR (10g) = 0.466 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = 0.04 dB
SAR (1g) = 0.775 W/kg; SAR (10g) = 0.446 W/kg;



Date: 2022-11-04

12_FR1 n5_20M_50RB_28Offset_Right Cheek_0mm_Ch167300

Communication System: Band n5; Frequency: 836.5
Medium: HSL. Medium parameters used: f= 836.5 MHz; σ= 0.914 S/m; ε_r = 41.9
Ambient Temperature: 23.1°C; Liquid Temperature: 22.8°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(10.05, 10.05, 10.05); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.549 W/kg; SAR (10g) = 0.352 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = -0.04 dB
SAR (1g) = 0.568 W/kg; SAR (10g) = 0.329 W/kg;



Date: 2022-11-06

13_WCDMA IV_RMC 12.2Kbps_Right Cheek_0mm_Ch1513

Communication System: Band 4, UTRA/FDD; Frequency: 1752.6
Medium: HSL. Medium parameters used: f= 1752.6 MHz; σ= 1.30 S/m; ε_r = 40.2
Ambient Temperature: 23.2°C; Liquid Temperature: 22.8°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(8.97, 8.97, 8.97); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.875 W/kg; SAR (10g) = 0.490 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = 0.01 dB
SAR (1g) = 0.892 W/kg; SAR (10g) = 0.494 W/kg;



Date: 2022-11-06

14_LTE Band 66_20M_1RB_0Offset_Right Cheek_0mm_Ch132572

Communication System: Band 66, E-UTRA/FDD; Frequency: 1770.0
Medium: HSL. Medium parameters used: f= 1770.0 MHz; σ= 1.34 S/m; ε_r = 40.2
Ambient Temperature: 23.2°C; Liquid Temperature: 22.8°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(8.97, 8.97, 8.97); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.814 W/kg; SAR (10g) = 0.463 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = 0.04 dB
SAR (1g) = 0.845 W/kg; SAR (10g) = 0.486 W/kg;



Date: 2022-11-06

15_FR1 n66_40M_108RB_54Offset_Right Cheek_0mm_Ch349000

Communication System: Band n66; Frequency: 1745.0
Medium: HSL. Medium parameters used: f= 1745.0 MHz; σ= 1.31 S/m; ε_r = 40.2
Ambient Temperature: 23.2°C; Liquid Temperature: 22.8°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(8.97, 8.97, 8.97); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.709 W/kg; SAR (10g) = 0.439 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = 0.06 dB
SAR (1g) = 0.780 W/kg; SAR (10g) = 0.445 W/kg;



Date: 2022-11-07

16_GSM1900_GPRS (4 Tx slots)_Right Cheek_0mm_Ch661

Communication System: GSM 1900; Frequency: 1880.0
Medium: HSL. Medium parameters used: f= 1880.0 MHz; σ= 1.40 S/m; ε_r = 40.1
Ambient Temperature: 23.3°C; Liquid Temperature: 22.7°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(8.51, 8.51, 8.51); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.243 W/kg; SAR (10g) = 0.583 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = -0.04 dB
SAR (1g) = 0.797 W/kg; SAR (10g) = 0.382 W/kg;



Date: 2022-11-07

17_WCDMA II_RMC 12.2Kbps_Right Cheek_0mm_Ch9538

Communication System: Band 2, E-UTRA/FDD; Frequency: 1907.6
Medium: HSL. Medium parameters used: f= 1907.6 MHz; σ= 1.40 S/m; ε_r = 40.1
Ambient Temperature: 23.3°C; Liquid Temperature: 22.7°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(8.51, 8.51, 8.51); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.874 W/kg; SAR (10g) = 0.475 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = -0.01 dB
SAR (1g) = 0.876 W/kg; SAR (10g) = 0.490 W/kg;



Date: 2022-11-07

18_LTE Band 25_20M_1RB_0Offset_Right Cheek_0mm_Ch26140

Communication System: Band 2, E-UTRA/FDD; Frequency: 1860.0
Medium: HSL. Medium parameters used: f= 1860.0 MHz; σ= 1.38 S/m; ε_r = 40.0
Ambient Temperature: 23.3°C; Liquid Temperature: 22.7°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(8.51, 8.51, 8.51); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.814 W/kg; SAR (10g) = 0.462 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = 0.06 dB
SAR (1g) = 0.863 W/kg; SAR (10g) = 0.487 W/kg;



Date: 2022-11-07

19_FR1 n25_40M_108RB_54Offset_Right Cheek_0mm_Ch376500

Communication System: Band n25; Frequency: 1882.5
Medium: HSL. Medium parameters used: f= 1882.5 MHz; σ= 1.40 S/m; ε_r = 40.1
Ambient Temperature: 23.3°C; Liquid Temperature: 22.7°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(8.51, 8.51, 8.51); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.749 W/kg; SAR (10g) = 0.332 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = -0.17 dB
SAR (1g) = 0.757 W/kg; SAR (10g) = 0.349 W/kg;



Date: 2022-11-07

20_LTE Band 2_20M_1RB_0Offset_Right Cheek_0mm_Ch19100

Communication System: Band 2, E-UTRA/FDD; Frequency: 1900.0
Medium: HSL. Medium parameters used: f= 1900.0 MHz; σ= 1.40 S/m; ε_r = 40.2
Ambient Temperature: 23.3°C; Liquid Temperature: 22.7°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(8.51, 8.51, 8.51); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 15.0 mm x 15.0 mm
SAR (1g) = 0.781 W/kg; SAR (10g) = 0.427 W/kg;

Zoom Scan (32.0 mm x 32.0 mm x 30.0 mm): Measurement Grid: 8.0 mm x 8.0 mm x 5.0 mm
Power Drift = 0.06 dB
SAR (1g) = 0.807 W/kg; SAR (10g) = 0.447 W/kg;



Date: 2022-11-08

21_LTE Band 30_10M_1RB_0Offset_Right Cheek_0mm_Ch27710

Communication System: Band 30, E-UTRA/FDD; Frequency: 2310.0
Medium: HSL. Medium parameters used: f= 2310.0 MHz; σ= 1.65 S/m; ε_r = 39.6
Ambient Temperature: 23.2°C; Liquid Temperature: 22.7°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(8.37, 8.37, 8.37); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.754 W/kg; SAR (10g) = 0.405 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 5.0 mm
Power Drift = 0.05 dB
SAR (1g) = 0.840 W/kg; SAR (10g) = 0.427 W/kg;



Date: 2022-11-08

22_FR1 n30_10M_25RB_14Offset_Right Cheek_0mm_Ch462000

Communication System: Band n30; Frequency: 2310.0
Medium: HSL. Medium parameters used: f= 2310.0 MHz; σ= 1.65 S/m; ε_r = 39.6
Ambient Temperature: 23.2°C; Liquid Temperature: 22.7°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(8.37, 8.37, 8.37); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.749 W/kg; SAR (10g) = 0.332 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 5.0 mm
Power Drift = -0.09 dB
SAR (1g) = 0.799 W/kg; SAR (10g) = 0.381 W/kg;



Date: 2022-11-09

23_LTE Band 7_20M_1RB_0Offset_Right Cheek_0mm_Ch21350

Communication System: Band 7, E-UTRA/FDD; Frequency: 2560.0
Medium: HSL. Medium parameters used: f= 2560.0 MHz; σ= 1.98 S/m; ε_r = 40.6
Ambient Temperature: 23.4°C; Liquid Temperature: 22.6°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(7.82, 7.82, 7.82); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.894 W/kg; SAR (10g) = 0.505 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 5.0 mm
Power Drift = -0.02 dB
SAR (1g) = 0.902 W/kg; SAR (10g) = 0.529 W/kg;



Date: 2022-11-09

24_LTE Band 41 HPUE_20M_1RB_0Offset_Right Cheek_0mm_Ch40620

Communication System: Band 41, E-UTRA/TDD; Frequency: 2593.0
Medium: HSL. Medium parameters used: f= 2593.0 MHz; σ= 2.00 S/m; ε_r = 40.6
Ambient Temperature: 23.4°C; Liquid Temperature: 22.6°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(7.82, 7.82, 7.82); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.094 W/kg; SAR (10g) = 0.055 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 5.0 mm
Power Drift = 0.05 dB
SAR (1g) = 0.140 W/kg; SAR (10g) = 0.059 W/kg;



Date: 2022-11-09

25_FR1 n7_40M_1RB_1Offset_Right Cheek_0mm_Ch507000

Communication System: Band n7; Frequency: 2535.0
Medium: HSL. Medium parameters used: f= 2535.0 MHz; σ= 1.96 S/m; ε_r = 40.7
Ambient Temperature: 23.4°C; Liquid Temperature: 22.6°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(7.82, 7.82, 7.82); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.939 W/kg; SAR (10g) = 0.532 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 5.0 mm
Power Drift = -0.13 dB
SAR (1g) = 0.930 W/kg; SAR (10g) = 0.541 W/kg;



Date: 2022-11-09

26_FR1 n41 HPUE_100M_270RB_0Offset_Right Cheek_0mm_Ch518598

Communication System: Band n41; Frequency: 2593.0
Medium: HSL. Medium parameters used: f= 2593.0 MHz; σ= 2.00 S/m; ε_r = 40.6
Ambient Temperature: 23.4°C; Liquid Temperature: 22.6°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(7.82, 7.82, 7.82); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.901 W/kg; SAR (10g) = 0.534 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 5.0 mm
Power Drift = 0.15 dB
SAR (1g) = 0.919 W/kg; SAR (10g) = 0.542 W/kg;



Date: 2022-11-11

27_FR1 n48 Part96_40M_50RB_28Offset_Right Cheek_0mm_Ch641666

Communication System: Band n48; Frequency: 3625.0
Medium: HSL. Medium parameters used: f= 3625.0 MHz; σ= 2.92 S/m; ε_r = 38.5
Ambient Temperature: 23.2°C; Liquid Temperature: 22.9°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(7.33, 7.33, 7.33); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.683 W/kg; SAR (10g) = 0.325 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm
Power Drift = -0.17 dB
SAR (1g) = 0.890 W/kg; SAR (10g) = 0.436 W/kg;



Date: 2022-11-12

28_FR1 n77 Part27O_100M_1RB_1Offset_Left Cheek_0mm_Ch656000

Communication System: Band n77; Frequency: 3840.0
Medium: HSL. Medium parameters used: f= 3840.0 MHz; σ= 3.22 S/m; ε_r = 37.7
Ambient Temperature: 23.2°C; Liquid Temperature: 22.8°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7764; ConvF(6.66, 6.66, 6.66); Calibrated: 2022-09-30
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1279; Calibrated: 2022-10-26
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.786 W/kg; SAR (10g) = 0.343 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm
Power Drift = 0.02 dB
SAR (1g) = 0.821 W/kg; SAR (10g) = 0.367 W/kg;



Date: 2022-11-10

29_LTE Band 42 Part27Q HPUE_20M_1RB_0Offset_Left Cheek_0mm_Ch42590

Communication System: Band 42, E-UTRA/TDD; Frequency: 3500.0
Medium: HSL. Medium parameters used: f= 3500.0 MHz; σ= 2.81 S/m; εr= 38.7
Ambient Temperature: 23.3°C; Liquid Temperature: 22.6°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(7.34, 7.34, 7.34); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.223 W/kg; SAR (10g) = 0.100 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm
Power Drift = 0.03 dB
SAR (1g) = 0.297 W/kg; SAR (10g) = 0.137 W/kg;



Date: 2022-11-11

30_LTE Band 48_20M_1RB_0Offset_Left Cheek_0mm_Ch55830

Communication System: Band 48, E-UTRA/TDD; Frequency: 3609.0
Medium: HSL. Medium parameters used: f= 3609.0 MHz; σ= 2.91 S/m; ε_r = 38.5
Ambient Temperature: 23.2°C; Liquid Temperature: 22.9°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7630; ConvF(7.33, 7.33, 7.33); Calibrated: 2022-03-04
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1305; Calibrated: 2022-04-27
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 210.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.199 W/kg; SAR (10g) = 0.068 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm
Power Drift = -0.19 dB
SAR (1g) = 0.213 W/kg; SAR (10g) = 0.087 W/kg;



Date: 2022-12-08

31_WLAN2.4GHz_802.11b 1Mbps_Left Cheek_0mm_Ch1

Communication System: WLAN 2.4GHz; Frequency: 2412.0
Medium: HSL. Medium parameters used: f= 2412.0 MHz; σ= 1.72 S/m; ε_r = 39.4
Ambient Temperature: 23.2°C; Liquid Temperature: 22.8°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7764; ConvF(8.25, 8.25, 8.25); Calibrated: 2022-09-30
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1279; Calibrated: 2022-10-26
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 216.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.576 W/kg; SAR (10g) = 0.280 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 5.0 mm
Power Drift = -0.09 dB
SAR (1g) = 0.584 W/kg; SAR (10g) = 0.291 W/kg;



Date: 2022-12-08

32_Bluetooth_1Mbps_Left Cheek_0mm_Ch39

Communication System: ISM 2.4 GHz Band; Frequency: 2441.0
Medium: HSL. Medium parameters used: f= 2441.0 MHz; σ= 1.73 S/m; ε_r = 39.3
Ambient Temperature: 23.2°C; Liquid Temperature: 22.8°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7764; ConvF(8.25, 8.25, 8.25); Calibrated: 2022-09-30
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1279; Calibrated: 2022-10-26
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

Area Scan (120.0 mm x 216.0 mm): Measurement Grid: 12.0 mm x 12.0 mm
SAR (1g) = 0.059 W/kg; SAR (10g) = 0.027 W/kg;

Zoom Scan (30.0 mm x 30.0 mm x 30.0 mm): Measurement Grid: 5.0 mm x 5.0 mm x 5.0 mm
Power Drift = -0.11 dB
SAR (1g) = 0.061 W/kg; SAR (10g) = 0.026 W/kg;



Date: 2022-12-08

33_WLAN5GHz_802.11a 6Mbps_Left Cheek_0mm_Ch64

Communication System: WLAN 5GHz; Frequency: 5320.0
Medium: HSL. Medium parameters used: f= 5320.0 MHz; σ= 4.66 S/m; ε_r = 35.6
Ambient Temperature: 23.2°C; Liquid Temperature: 22.9°C

DASY6 Configuration:
- Probe: EX3DV4 - SN7764; ConvF(5.65, 5.65, 5.65); Calibrated: 2022-09-30
- Sensor-Surface: 1.4 mm
- Electronics: DAE4 Sn1279; Calibrated: 2022-10-26
- Phantom: Twin-SAM V8.0 (30deg probe tilt); Serial: 2022
- Measurement Software: cDASY6 V6.6.0.13926

rea Scan (120.0 mm x 200.0 mm): Measurement Grid: 10.0 mm x 10.0 mm
SAR (1g) = 0.626 W/kg; SAR (10g) = 0.255 W/kg;

Zoom Scan (24.0 mm x 24.0 mm x 22.0 mm): Measurement Grid: 4.0 mm x 4.0 mm x 1.4 mm
Power Drift = 0.05 dB
SAR (1g) = 0.657 W/kg; SAR (10g) = 0.263 W/kg;