

7.7. Band-edge Compliance Measurement

7.7.1. Test Limit

The maximum permissible emission level is 20dBc. Any emissions were lying outside of the emission bandwidth and in authorized band edges to a field strength limit specified in Section 15.209 of the Title 47 CFR.


7.7.2. Test Procedure Used

ANSI C63.10-2013 - Section 6.10.4

7.7.3. Test Setting

1. Span = wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products which fall outside of the authorized band of operation.
2. RBW $\geq$ 1% of spectrum analyzer display span
3. VBW $\geq$ RBW
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize
8. Allow the trace to stabilize. Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, then use the marker-to-peak function to move the marker to the peak of the in-band emission.

7.7.4. Test Setup




7.7.5.Test Result


Test Mode	Channel No.	Frequency (MHz)	Limit	Result
DH5	00	2402	20dBc	Pass
DH5	78	2480	20dBc	Pass
2DH5	00	2402	20dBc	Pass
2DH5	78	2480	20dBc	Pass
3DH5	00	2402	20dBc	Pass
3DH5	78	2480	20dBc	Pass

DH5 Band-edge Compliance

Channel 00 (2402MHz)




Channel 78 (2480MHz)




2DH5 Band-edge Compliance

Channel 00 (2402MHz)




Channel 78 (2480MHz)




3DH5 Band-edge Compliance

Channel 00 (2402MHz)




Channel 78 (2480MHz)




DH5 Operation Frequency Range of 20dB Bandwidth within Hopping Mode

Channel 00 (2402MHz)




Channel 78 (2480MHz)




2DH5 Operation Frequency Range of 20dB Bandwidth within Hopping Mode

Channel 00 (2402MHz)




Channel 78 (2480MHz)




3DH5 Operation Frequency Range of 20dB Bandwidth within Hopping Mode

Channel 00 (2402MHz)



Channel 78 (2480MHz)



7.8. Conducted Spurious Emissions Measurement

7.8.1. Test Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.


7.8.2. Test Procedure Used

ANSI C63.10-2013 - Section 7.8.8

7.8.3. Test Setting


1. Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.
2. RBW = 100 KHz
3. VBW $\geq$ RBW
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize
8. Set the marker on the peak of any spurious emission recorded. The level displayed must comply with the limit specified in this section.

7.8.4.Test Setup




7.8.5. Test Result

Test Mode	Channel No.	Frequency (MHz)	Limit (MHz)	Result
DH5	00	2402	20dBc	Pass
DH5	39	2441	20dBc	Pass
DH5	78	2480	20dBc	Pass
2DH5	00	2402	20dBc	Pass
2DH5	39	2441	20dBc	Pass
2DH5	78	2480	20dBc	Pass
3DH5	00	2402	20dBc	Pass
3DH5	39	2441	20dBc	Pass
3DH5	78	2480	20dBc	Pass



2DH5 Conducted Spurious Emissions

Channel 00 (2402MHz)



Channel 39 (2441MHz)




Channel 78 (2480MHz)




3DH5 Conducted Spurious Emissions

Channel 00 (2402MHz)



Channel 39 (2441MHz)



Channel 78 (2480MHz)



7.9. Radiated Spurious Emission Measurement

7.9.1. Test Limit

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR must not exceed the limits shown in Table per Section 15.209.

FCC Part 15 Subpart C Paragraph 15.209		
Frequency [MHz]	Field Strength [uV/m]	Measured Distance [Meters]
0.009 - 0.490	2400/F (kHz)	300
0.490 - 1.705	24000/F (kHz)	30
1.705 – 30	30	30
30 – 88	100	3
88 – 216	150	3
216 – 960	200	3
Above 960	500	3

7.9.2. Test Procedure Used

ANSI C63.10-2013 - Section 11.12.1

7.9.3. Test Setting

Peak Field Strength Measurements

Analyzer center frequency was set to the frequency of the radiated spurious emission of interest

RBW = as specified in Table 1

VBW = 3 * RBW

Detector = peak

Sweep time = auto couple

Trace mode = max hold

Trace was allowed to stabilize

Table 1 - RBW as a function of frequency

Frequency	RBW
9 ~ 150 kHz	200 ~ 300 Hz
0.15 ~ 30 MHz	9 ~ 10 kHz
30 ~ 1000 MHz	100 ~ 120 kHz
> 1000 MHz	1 MHz

Average Field Strength Measurements

Analyzer center frequency was set to the frequency of the radiated spurious emission of interest

RBW = 1MHz

VBW $\geq 1/T$

De As an alternative, the instrument may be set to linear detector mode. Ensure that video filtering is applied in linear voltage domain (rather than in a log or dB domain). Some instruments require linear display mode in order to accomplish this. Others have a setting for Average-VBW Type, which can be set to "Voltage" regardless of the display mode

Detector = Peak


Sweep time = auto

Trace mode = max hold


Allow max hold to run for at least 50 times (1/duty cycle) traces

7.9.4. Test Setup


9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:



1GHz ~ 18GHz Test Setup:



18GHz ~ 25GHz Test Setup:



7.9.5. Test Result

Test Mode:	DH5	Test Site:	AC1
Test Channel:	00	Test Engineer:	Bruce Wang
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	3898.5	35.2	0.2	35.4	74.0	-38.6	Peak	Horizontal
	4765.5	36.7	2.6	39.3	74.0	-34.7	Peak	Horizontal
*	6508.0	35.0	6.0	41.0	83.8	-42.8	Peak	Horizontal
*	7842.5	36.1	8.4	44.5	83.8	-39.3	Peak	Horizontal
	3796.5	35.7	-0.2	35.5	74.0	-38.5	Peak	Vertical
	4748.5	37.1	2.5	39.6	74.0	-34.4	Peak	Vertical
*	6584.5	35.2	6.0	41.2	83.8	-42.6	Peak	Vertical
*	9755.0	35.3	11.4	46.7	83.8	-37.1	Peak	Vertical

Note 1: "*" is not in restricted band, its limit is 20dBc of the fundamental emission level (103.8dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	DH5	Test Site:	AC1
Test channel:	39	Test Engineer:	Bruce Wang
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	3796.5	35.4	-0.2	35.2	74.0	-38.8	Peak	Horizontal
	4757.0	35.4	2.6	38.0	74.0	-36.0	Peak	Horizontal
*	6814.0	35.3	6.1	41.4	83.7	-42.3	Peak	Horizontal
*	9925.0	35.3	11.5	46.8	83.7	-36.9	Peak	Horizontal
	3745.5	35.7	-0.4	35.3	74.0	-38.7	Peak	Vertical
	4774.0	35.5	2.6	38.1	74.0	-35.9	Peak	Vertical
*	6414.5	35.1	5.5	40.6	83.7	-43.1	Peak	Vertical
*	10350.0	35.0	12.2	47.2	83.7	-36.5	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (103.7dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	DH5	Test Site:	AC1
Test channel:	78	Test Engineer:	Bruce Wang
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	3847.5	34.2	0.0	34.2	74.0	-39.8	Peak	Horizontal
	4765.5	36.4	2.6	39.0	74.0	-35.0	Peak	Horizontal
*	6516.5	35.2	6.0	41.2	83.7	-42.5	Peak	Horizontal
*	10401.0	33.7	12.3	46.0	83.7	-37.7	Peak	Horizontal
	3839.0	35.0	0.0	35.0	74.0	-39.0	Peak	Vertical
	4782.5	36.5	2.7	39.2	74.0	-34.8	Peak	Vertical
*	6584.5	35.2	6.0	41.2	83.7	-42.5	Peak	Vertical
*	10494.5	33.4	12.4	45.8	83.7	-37.9	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (103.7dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	2DH5	Test Site:	AC1
Test channel:	00	Test Engineer:	Bruce Wang
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	3711.5	35.8	-0.5	35.3	74.0	-38.7	Peak	Horizontal
	4740.0	35.2	2.5	37.7	74.0	-36.3	Peak	Horizontal
*	6533.5	35.5	5.9	41.4	83.1	-41.7	Peak	Horizontal
*	10205.5	34.7	11.8	46.5	83.1	-36.6	Peak	Horizontal
	3881.5	35.0	0.1	35.1	74.0	-38.9	Peak	Vertical
	4731.5	35.2	2.5	37.7	74.0	-36.3	Peak	Vertical
*	6678.0	35.9	5.9	41.8	83.1	-41.3	Peak	Vertical
*	10562.5	35.2	12.5	47.7	83.1	-35.4	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (103.1dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	2DH5	Test Site:	AC1
Test channel:	39	Test Engineer:	Bruce Wang
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	3796.5	34.0	-0.2	33.8	74.0	-40.2	Peak	Horizontal
	4765.5	35.3	2.6	37.9	74.0	-36.1	Peak	Horizontal
*	6584.5	36.7	6.0	42.7	83.1	-40.4	Peak	Horizontal
*	10350.0	35.4	12.2	47.6	83.1	-35.5	Peak	Horizontal
	3745.5	36.3	-0.4	35.9	74.0	-38.1	Peak	Vertical
	4774.0	35.7	2.6	38.3	74.0	-35.7	Peak	Vertical
*	6550.5	34.9	5.9	40.8	83.1	-42.3	Peak	Vertical
*	10435.0	35.3	12.0	47.3	83.1	-35.8	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (103.1dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	2DH5	Test Site:	AC1
Test channel:	78	Test Engineer:	Bruce Wang
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	3813.5	35.2	-0.2	35.0	74.0	-39.0	Peak	Horizontal
	4714.5	36.0	2.4	38.4	74.0	-35.6	Peak	Horizontal
*	6499.5	36.2	6.0	42.2	83.1	-40.9	Peak	Horizontal
*	10180.0	34.7	11.7	46.4	83.1	-36.7	Peak	Horizontal
	3762.5	35.8	-0.3	35.5	74.0	-38.5	Peak	Vertical
	4757.0	35.5	2.6	38.1	74.0	-35.9	Peak	Vertical
*	5972.5	36.3	4.3	40.6	83.1	-42.5	Peak	Vertical
*	10494.5	35.3	12.4	47.7	83.1	-35.4	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (103.1dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	3DH5	Test Site:	AC1
Test channel:	00	Test Engineer:	Bruce Wang
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	3796.5	35.4	-0.2	35.2	74.0	-38.8	Peak	Horizontal
	4791.0	35.1	2.7	37.8	74.0	-36.2	Peak	Horizontal
*	6525.0	35.1	5.9	41.0	83.2	-42.2	Peak	Horizontal
*	10290.5	34.8	12.0	46.8	83.2	-36.4	Peak	Horizontal
	3890.0	34.8	0.2	35.0	74.0	-39.0	Peak	Vertical
	4782.5	36.7	2.7	39.4	74.0	-34.6	Peak	Vertical
*	6652.5	35.2	6.0	41.2	83.2	-42.0	Peak	Vertical
*	9823.0	35.1	11.6	46.7	83.2	-36.5	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (103.2dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	3DH5	Test Site:	AC1
Test channel:	39	Test Engineer:	Bruce Wang
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	3796.5	34.8	-0.2	34.6	74.0	-39.4	Peak	Horizontal
	4765.5	35.2	2.6	37.8	74.0	-36.2	Peak	Horizontal
*	6406.0	35.0	5.5	40.5	83.3	-42.8	Peak	Horizontal
*	9619.0	35.6	10.9	46.5	83.3	-36.8	Peak	Horizontal
	3907.0	35.1	0.2	35.3	74.0	-38.7	Peak	Vertical
	4765.5	35.2	2.6	37.8	74.0	-36.2	Peak	Vertical
*	6601.5	35.6	6.0	41.6	83.3	-41.7	Peak	Vertical
*	10367.0	34.3	12.2	46.5	83.3	-36.8	Peak	Vertical

Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (103.3dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Test Mode:	3DH5	Test Site:	AC1
Test channel:	78	Test Engineer:	Bruce Wang
Remark:	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBμV)	Factor (dB)	Measure Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector	Polarization
	3788.0	34.5	-0.3	34.2	74.0	-39.8	Peak	Horizontal
	4706.0	35.5	2.4	37.9	74.0	-36.1	Peak	Horizontal
*	6508.0	34.7	6.0	40.7	83.4	-42.7	Peak	Horizontal
*	9814.5	34.7	11.6	46.3	83.4	-37.1	Peak	Horizontal
	3856.0	34.3	0.1	34.4	74.0	-39.6	Peak	Vertical
	4782.5	36.2	2.7	38.9	74.0	-35.1	Peak	Vertical
*	6474.0	34.7	5.8	40.5	83.4	-42.9	Peak	Vertical
*	10486.0	35.8	12.3	48.1	83.4	-35.3	Peak	Vertical


Note 1: “*” is not in restricted band, its limit is 20dBc of the fundamental emission level (103.4dBμV/m) or 15.209 which is higher.

Note 2: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

The worst case of Radiated Emission 9kHz ~ 1GHz and 18GHz ~ 25GHz:

Site: AC1	Time: 2017/06/11 - 17:39
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: VULB9168_20-2000MHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Worst Case Mode: Transmit at Channel 2402MHz by 2DH5	




No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		35.820	17.038	3.107	-22.962	40.000	13.931	QP
2		44.065	16.408	2.164	-23.592	40.000	14.244	QP
3		79.955	18.714	8.630	-21.286	40.000	10.084	QP
4		161.920	17.092	2.070	-26.408	43.500	15.022	QP
5		480.080	22.160	3.967	-23.840	46.000	18.193	QP
6	*	556.710	22.681	3.104	-23.319	46.000	19.577	QP

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.

Site: AC1	Time: 2017/06/11 - 17:40
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: VULB9168_20-2000MHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Worst Case Mode: Transmit at Channel 2402MHz by 2DH5	



No	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		36.790	24.800	10.719	-15.200	40.000	14.081	QP
2		44.065	26.412	12.168	-13.588	40.000	14.244	QP
3		74.620	19.323	8.519	-20.677	40.000	10.804	QP
4	*	79.955	31.823	21.739	-8.177	40.000	10.084	QP
5		154.645	16.761	1.575	-26.739	43.500	15.186	QP
6		574.170	23.954	4.026	-22.046	46.000	19.928	QP

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)


Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.

7.10. Radiated Restricted Band Edge Measurement

7.10.1. Test Result

Site: AC1	Time: 2017/06/02 - 03:12
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2372.890	59.378	28.144	-14.622	74.000	31.234	PK
2			2390.000	58.147	26.944	-15.853	74.000	31.203	PK
3		*	2401.770	103.786	72.602	N/A	N/A	31.184	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:15
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	45.164	13.961	-8.836	54.000	31.203	AV
2		*	2401.913	91.334	60.150	N/A	N/A	31.184	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:15
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2371.845	60.347	29.111	-13.653	74.000	31.236	PK
2			2390.000	58.661	27.458	-15.339	74.000	31.203	PK
3		*	2401.722	101.867	70.683	N/A	N/A	31.184	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:18
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	45.164	13.961	-8.836	54.000	31.203	AV
2		*	2401.913	89.457	58.273	N/A	N/A	31.184	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:19
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2479.784	103.709	72.525	N/A	N/A	31.184	PK
2			2483.500	58.755	27.562	-15.245	74.000	31.194	PK
3			2484.329	59.760	28.564	-14.240	74.000	31.195	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:25
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2480.042	91.314	60.130	N/A	N/A	31.184	AV
2			2483.500	45.527	14.334	-8.473	54.000	31.194	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:26
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2479.941	101.956	70.772	N/A	N/A	31.184	PK
2			2483.500	58.052	26.859	-15.948	74.000	31.194	PK
3			2487.647	60.338	29.134	-13.662	74.000	31.204	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:28
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2480.087	89.853	58.669	N/A	N/A	31.184	AV
2			2483.500	45.422	14.229	-8.578	54.000	31.194	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:29
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 2DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2381.298	59.471	28.252	-14.529	74.000	31.218	PK
2			2390.000	58.189	26.986	-15.811	74.000	31.203	PK
3		*	2402.103	103.129	71.945	N/A	N/A	31.184	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:32
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 2DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	45.121	13.918	-8.879	54.000	31.203	AV
2		*	2401.865	88.196	57.012	N/A	N/A	31.184	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:33
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 2DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2377.782	59.908	28.683	-14.092	74.000	31.226	PK
2			2390.000	57.564	26.361	-16.436	74.000	31.203	PK
3		*	2401.770	101.386	70.202	N/A	N/A	31.184	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:36
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 2DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	45.142	13.939	-8.858	54.000	31.203	AV
2		*	2401.865	86.676	55.492	N/A	N/A	31.184	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:36
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 2DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2479.975	103.129	71.945	N/A	N/A	31.184	PK
2			2483.500	58.844	27.651	-15.156	74.000	31.194	PK
3			2487.929	59.958	28.753	-14.042	74.000	31.205	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:39
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 2DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2480.042	88.481	57.297	N/A	N/A	31.184	AV
2			2483.500	45.485	14.292	-8.515	54.000	31.194	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:40
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 2DH5 at Channel 2480MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2479.941	100.938	69.754	N/A	N/A	31.184	PK
2			2483.500	58.683	27.490	-15.317	74.000	31.194	PK
3			2486.748	59.769	28.567	-14.231	74.000	31.201	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:42
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 2DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2480.110	86.627	55.443	N/A	N/A	31.184	AV
2			2483.500	45.353	14.160	-8.647	54.000	31.194	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:43
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 3DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2380.538	59.947	28.727	-14.053	74.000	31.220	PK
2			2390.000	57.359	26.156	-16.641	74.000	31.203	PK
3		*	2401.865	103.181	71.997	N/A	N/A	31.184	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:45
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 3DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	45.124	13.921	-8.876	54.000	31.203	AV
2		*	2401.913	88.201	57.017	N/A	N/A	31.184	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:45
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 3DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2377.782	59.731	28.506	-14.269	74.000	31.226	PK
2			2390.000	57.639	26.436	-16.361	74.000	31.203	PK
3		*	2401.865	101.304	70.120	N/A	N/A	31.184	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:47
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 3DH5 at Channel 2402MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1			2390.000	45.162	13.959	-8.838	54.000	31.203	AV
2		*	2401.865	86.313	55.129	N/A	N/A	31.184	AV

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:48
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 3DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2479.941	103.404	72.220	N/A	N/A	31.184	PK
2			2483.500	58.193	27.000	-15.807	74.000	31.194	PK
3			2486.815	59.310	28.108	-14.690	74.000	31.202	PK

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:50
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Horizontal
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 3DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2479.964	88.426	57.242	N/A	N/A	31.184	AV
2			2483.500	45.429	14.236	-8.571	54.000	31.194	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:50
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 3DH5 at Channel 2480MHz	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2479.952	101.610	70.426	N/A	N/A	31.184	PK
2			2483.500	57.931	26.738	-16.069	74.000	31.194	PK
3			2485.667	60.839	29.640	-13.161	74.000	31.199	PK

Note: Measure Level (dBμV/m) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Site: AC1	Time: 2017/06/02 - 03:52
Limit: FCC_Part15.209_RE(3m)	Engineer: Bruce Wang
Probe: BBHA9120D_1-18GHz	Polarity: Vertical
EUT: Tablet	Power: By Battery
Test Mode: Transmit by 3DH5 at Channel 2480MHz	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV/m)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV/m)	Factor (dB)	Type
1		*	2480.042	87.035	55.851	N/A	N/A	31.184	AV
2			2483.500	45.450	14.257	-8.550	54.000	31.194	AV

Note: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

7.11. AC Conducted Emissions Measurement


7.11.1. Test Limit

FCC Part 15 Subpart C Paragraph 15.207 / RSS-Gen Limits		
Frequency (MHz)	QP (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note 1: The lower limit shall apply at the transition frequencies.


Note 2: The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.5MHz.

7.11.2. Test Setup



7.11.3. Test Result

Site: SR2	Time: 2017/06/12 - 21:11
Limit: FCC_Part15.207_CE_AC Power	Engineer: Vince Yu
Probe: ENV216_101683_Filter On	Polarity: Line
EUT: Tablet	Power: AC 120V/60Hz
Test Mode: Transmit at Channel 2402MHz By 2DH5	




No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1		*	0.162	54.054	43.957	-11.307	65.361	10.097	QP
2			0.162	20.088	9.991	-35.273	55.361	10.097	AV
3			0.182	50.174	40.125	-14.220	64.394	10.048	QP
4			0.182	21.348	11.299	-33.046	54.394	10.048	AV
5			0.202	49.863	39.870	-13.665	63.528	9.993	QP
6			0.202	23.518	13.525	-30.010	53.528	9.993	AV
7			0.274	46.776	36.793	-14.220	60.996	9.983	QP
8			0.274	21.590	11.607	-29.406	50.996	9.983	AV
9			0.550	34.103	23.962	-21.897	56.000	10.141	QP
10			0.550	18.952	8.811	-27.048	46.000	10.141	AV
11			18.550	33.840	23.724	-26.160	60.000	10.115	QP
12			18.550	21.006	10.890	-28.994	50.000	10.115	AV

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB).

Site: SR2	Time: 2017/06/12 - 21:15
Limit: FCC_Part15.207_CE_AC Power	Engineer: Vince Yu
Probe: ENV216_101683_Filter On	Polarity: Neutral
EUT: Tablet	Power: AC 120V/60Hz
Test Mode: Transmit at Channel 2402MHz By 2DH5	



No	Flag	Mark	Frequency (MHz)	Measure Level (dBuV)	Reading Level (dBuV)	Over Limit (dB)	Limit (dBuV)	Factor (dB)	Type
1		*	0.158	50.421	40.131	-15.148	65.568	10.290	QP
2			0.158	22.369	12.079	-33.200	55.568	10.290	AV
3			0.194	43.002	32.981	-20.861	63.864	10.021	QP
4			0.194	17.720	7.699	-36.144	53.864	10.021	AV
5			0.250	41.621	31.620	-20.136	61.757	10.001	QP
6			0.250	26.111	16.110	-25.646	51.757	10.001	AV
7			0.362	34.780	24.696	-23.903	58.682	10.084	QP
8			0.362	20.545	10.461	-28.137	48.682	10.084	AV
9			0.566	34.512	24.362	-21.488	56.000	10.150	QP
10			0.566	18.566	8.416	-27.434	46.000	10.150	AV
11			18.446	34.118	23.981	-25.882	60.000	10.137	QP
12			18.446	23.736	13.599	-26.264	50.000	10.137	AV

Note: Measure Level (dBμV) = Reading Level (dBμV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + LISN Factor (dB).

8. CONCLUSION

The data collected relate only the item(s) tested and show that the **Tablet** is in compliance with Part 15C of the FCC Rules and IC Rules.

The End