

 ESTECH Co., Ltd. Rm 1015, World Venture Center II, 426-5 Gasan-dong, Guncheon-gu, Seoul, 158-803, Korea	   	Electromagnetic Interference Test Report
---	--	---

Test Report for FCC

FCC ID:HD5610001
IC:1693B-61E

Report Number		ESTF150908-005		
Applicant	Company name	Honeywell International Inc.		
	Address	700 Visions Drive, P.O.Box 208 Skaneateles Falls, NY, 13153-0208		
	Telephone	803-835-8190		
Product	Product name	Mobile Computer		
	Model No.	Dolphin 6100	Manufacturer	BG Electronic Co.
	Serial No.	NONE	Country of origin	CHINA
Test date	2009-08-20 ~ 2009-08-21		Date of issue	24-Aug-09
Testing location	ESTECH. Co., Ltd. 97-1 Hoiuk-Ri Majang-Myon, Icheon-city, KyungKi-Do, Korea			
Standard	FCC PART 15 2007 , ANSI C 63.4 2003 , RSS-210			
Measurement facility registration number		94696		
Tested by	Engineer H.H.Lee  (Signature)			
Reviewed by	Engineering Manager J.M.Yang  (Signature)			
Abbreviation	OK, Pass = Passed, Fail = Failed, N/A = not applicable			
* Note - BT only = HD5610001 - This test report is not permitted to copy partly without our permission - This test result is dependent on only equipment to be used - This test result based on a single evaluation of one sample of the above mentioned				

Contents 1

1. Laboratory Information	4
2. Description of EUT	5
3. Test Standards	6
4. Measurement condition	7
5. Carrier Frequency Separation	10
5.1 Test procedure	10
5.2 Test instruments and measurement setup	10
5.3 Measurement results	10
5.4 Trace data	12
6. Maximum Peak Output Power	16
6.1 Test procedure	16
6.2 Measurement results	16
7. Number of Hopping Frequency	17
7.1 Test procedure	17
7.2 Test instruments and measurement setup	17
7.3 Measurement results	17
7.4 Trace data	18
8. Time of Occupancy (Dwell Time)	20
8.1 Test procedure	20
8.2 Test instruments and measurement setup	20
8.3 Measurement results	20
8.4 Trace Data	21
8.5 Trace Data	23

Contents 2

9. Band -edge and Out of band emissions	25
9.1 Test procedure	25
9.2 Test instruments and measurement setup	25
9.3 Measurement results of band -edge & out of emission	25
9.4 Trace data of band -edge & out of emission	26
10. Measurement of radiated emission	36
10.1 Measurement equipment	36
10.2 Environmental conditions	36
10.3 Test data(bluetooth)	37
10.4 Restricted Band Edges	41
10.5 Test data(bluetooth)	45
10.6 Restricted Band Edges	48
11. Measurement of conducted emission	52
11.1 Measurement equipment	52
11.2 Environmental conditions	52
11.3 Test data	53
12. Photographs of test setup	54
12.1.Setup for Radiated Test : 30 ~ 1000 MHz	54
12.2. Setup for Radiated Test :Above 1000 MHz	55
12.3. Setup for Conducted Test : 0.15 ~ 30 MHz	56
12.4. Photographs of EUT.....	57

Appendix 1. Spectral diagram

Appendix 2. Antenna Requirement

1. Laboratory Information

1.1 General

This EUT (Equipment Under Test) has been shown to be capable of compliance with the applicable technical standards and is tested in accordance with the measurement procedures as indicated in this report.

ESTECH Lab attests to accuracy of test data. All measurement reported herein were performed by ESTECH Co., Ltd.

ESTECH Lab assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

1.2 Test Lab.

Corporation Name : ESTECH Co., Ltd.

Head Office : Rm 1015, World Venture Center II, 426-5, Gasan-dong, Geumcheon-gu, Seoul, Korea
(Safety & Telecom. Test Lab)

EMC Test Lab : 97-1, Hoeok-ri, Majang-myun, Ichion-city, Kyonggi-do, South Korea

1.3 Official Qualification(s)

KCC : Granted Accreditation from Ministry of Information & Communication for EMC, Safety and Telecommunication

KOLAS : Accredited Lab By Korea Laboratory Accreditation Schema base on CENELEC requirements

FCC : Filed Laboratory at Federal Communications Commission

VCCI : Granted Accreditation from Voluntary Control Council for Interference from ITE

2. Description of EUT

2.1 Summary of Equipment Under Test (Bluetooth)

Product Name	: Mobile Computer
Model Number	: Dolphin 6100
Modulation Type	: GFSK(FHSS) , DQPSK, 8DPSK
Transfer Rate	: 3Mbps
Number of Channel	: 79 ch
Channel Spacing	: 1MHz
Output Power	: 0.42dBm
Serial Number	: NONE
Manufacturer	: BG Electronic Co.
Country of origin	: CHINA
Rating	: Adapter :(100-240) V a.c. (50/60) Hz , 0.3A : DC input : 5 Vd.c. , 2.0 A
Receipt Date	: 2009-08-20
X-tal list(s)	: 13 MHz

2.2 General descriptions of EUT

The Bluetooth frequency hopping transceiver is designed to operate between 2400 and 2483.5MHz.

For the detailed features, please refer to the manufacturer's specifications or User's Manual.

- the system is designed to comply with all of the regulations in Section 15.247 when the transmitter is presented with a continuous data (or information) stream. It is also comply with FHSS requirements in Section 15.247(a)(1).

: Its hopping sequence is pseudo random, all channels used equally on average.

The receiver input bandwidth approximately equal the transmit band bandwidth, and its hop in sequence with the transmit signal.

- the system does not coordinate its channel selection/hopping sequence with other frequency hopping systems for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters.

3. Test Standards

Test Standard : FCC PART 15 (2007) & RSS-210

This Standard sets out the regulations under which an intentional, unintentional, or incidental radiator may be operated without an individual license. It also contains the technical specifications, administrative requirements and other conditions relating to the marketing of Part 15 devices.

Test Method : ANSI C 63.4 (2003)

This standard sets forth uniform methods of measurement of radio-frequency (RF) signals and noise emitted from both unintentional and intentional emitters of RF energy in the frequency range 9 kHz to 40 GHz. Methods for the measurement of radiated and AC power-line conducted radio noise are covered and may be applied to any such equipment unless otherwise specified by individual equipment requirements. These methods cover measurement of certain devices that deliberately radiate energy, such as intentional emitters, but does not cover licensed transmitters. This standard is not intended for certification/approval of avionic equipment or for industrial, scientific, and medical (ISM) equipment. These methods apply to the measurement of individual units or systems comprised of multiple units.

Summary of Test Results

Applied Standard : 47 CFR Part 15, Subpart C				
Standard	Test Type	Result	Remark	Limit
15.207	AC Power Conducted Emission	Pass	Meet the requirement	
15.209	Intentional Radiated Emission	Pass	Meet the requirement	
15.247(a)(1)	Carrier Frequency Separation &	Pass	Meet the requirement	>25kHz
	20 Bandwidth			
15.247(b)	Maximum Peak output power	Pass	Meet the requirement	30dBm(1W)
15.247(a)(1)(ii)	Number of Hopping Frequency	Pass	Meet the requirement	>75
15.247(c)	Transmitter Radiated Emission	Pass	Meet the requirement	
15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Pass	Meet the requirement	<400ms
15.247(d)	Band Edge Measurement	Pass	Meet the requirement	

4. Measurement Condition

4.1 EUT Operation

a. Channel

Ch.	Frequency	Ch.	Frequency
0	2402 MHz	40	2442 MHz
1	2403 MHz	41	2443 MHz
2	2404 MHz	42	2444 MHz
3	2405 MHz	43	2445 MHz
4	2406 MHz	...	...
...	...	78	2480 MHz
39	2441 MHz		

b. Measurement Channel :Low(2402MHz), Middle(2441MHz),High(2480MHz)


c. Test Mode : DQPSK, 8DPSK, GFSK(worst case)

d. Test rate :3Mbps

4.2 EUT Operation.

- * The EUT was in the following operation mode during all testing
- * The operational conditions of the EUT was determined by the manufacturer according to the typical use of the EUT with respect to the expected highest level of emission
- * The computer system ran a test program to enable EUT under transmission/receiving condition continuously at specific channel frequency.

4.3 Configuration and Peripherals



4.4 EUT and Support equipment

Equipment Name	Model Name	S/N	Manufacturer	Remark (FCC ID)
Mobile Computer	Dolphin 6100	NONE	BG Electronic Co.	EUT
ADAPTER	PSC11R-050	P92900007A2	Phihong(Dongguan)Electronics Co.,Ltd	
EARPHONE	NONE	NONE	NONE	

4.5 Cable Connecting

Start Equipment		End Equipment		Cable Standard		Remark
Name	I/O port	Name	I/O port	Length	Shielded	
Mobile Computer	Line	Ear - phone	Line	1	N	
Mobile Computer	POWER	Adapter	-	2	N	

5. Carrier Frequency Separation

5.1 Test procedure

According to §15.247(a)(1), Frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater.

5.2 Test instruments and measurement setup

The spectrum analyzer is set to as following.

- . RBW= 30KHz
- . VBW= 300KHz
- . Span= 3MHz
- . Sweep= suitable duration based on the EUT specification.

20dB Bandwidth Test Instruments

Description	Model	Serial Number	Cal. Due Date
Spectrum Analyzer	E4407B	US42041281	2009-09-11
RF Cable:	Length: 7cm	-	-
-Spectrum Analyzer <=> EUT	Loss: 1.5dB	-	-

5.3 Measurement results

EUT	Mobile Computer	MODEL	Dolphin 6100
MODE	FHSS	ENVIRONMENTAL CONDITION	25 , 43%RH
INPUT POWER	5Vdc		


CHANNEL	Channel Frequency (MHz)	Bandwidth at 20dB below(kHz)	Channel Separation (MHz)	Limit (kHz)	PASS/FAIL
0	2402	942	-	-	-
39	2441	961	1.0	>25	PASS
78	2480	919	-	-	-

(8DPSK)


CHANNEL	Channel Frequency (MHz)	Bandwidth at 20dB below(MHz)	Channel Separation (MHz)	Limit (MHz)	PASS/FAIL
0	2402	1.245	-	-	-
39	2441	1.255	1MHz	>0.84	PASS
78	2480	1.266	-	-	-

5.4 Trace data (GFSK)

Channel Separation



20dB bandwidth(Ch 0)






ESTECH Co., Ltd.

Rm 1015, World Venture Center II,
426-5 Gasan-dong, Guncheon-gu,
Seoul, 158-803, Korea




**Electromagnetic
Interference
Test Report**

20dB bandwidth(CH 39)



20dB bandwidth(CH 78)





ESTECH Co., Ltd.


Rm 1015, World Venture Center II,
426-5 Gasan-dong, Guncheon-gu,
Seoul, 158-803, Korea




Electromagnetic
Interference
Test Report

(8DPSK)

Channel Separation



20dB bandwidth(Ch 0)






ESTECH Co., Ltd.

Rm 1015, World Venture Center II,
426-5 Gasan-dong, Guncheon-gu,
Seoul, 158-803, Korea




**Electromagnetic
Interference
Test Report**

20dB bandwidth(CH 39)



20dB bandwidth(CH 78)



6. MAXIMUM PEAK OUTPUT POWER

6.1 Test procedure

The transmitter antenna terminal is connected to the input of a Power Sensor. Measurement is made while EUT is operating in transmission mode at the appropriate center frequency. The maximum peak output power measurement is 30dBm.

Description	Model	Serial Number	Cal. Due Date
Power Meter	NRVS	849622/045	2010-02-11
Power Sensor	NRV-251	325948/013	2010-02-11
RF Cable:	Length: 7cm	-	-
- Spectrum Analyzer <=> EUT	Loss: 1.5dB	-	-

6.2 Measurement results

EUT	Mobile Computer	MODEL	Dolphin 6100
MODE	GFSK,8DPSK DH5	ENVIRONMENTAL CONDITION	25 , 43%RH
INPUT POWER	5Vdc		

GFSK

CHANNEL	Channel Frequency (MHz)	Peak Power Output(dBm)		Limit[1W] (dBm)	PASS/ FAIL
		(dBm)	(W)		
0	2402	0.42	0.0011	30.0	PASS
39	2441	-2.03	0.0006	30.0	PASS
78	2480	-3.76	0.0004	30.0	PASS

8DPSK

CHANNEL	Channel Frequency (MHz)	Peak Power Output(dBm)		Limit[1W] (dBm)	PASS/ FAIL
		(dBm)	(W)		
0	2402	-4.51	0.0004	30.0	PASS
39	2441	-5.89	0.0003	30.0	PASS
78	2480	-6.80	0.0002	30.0	PASS

Note:GFSK mode is max power in three different modulations.

7. Number of Hopping Frequency

7.1 Test procedure

According to §15.247(a)(1)(ii), Frequency hopping systems operating in the 2400MHz-2483.5MHz bands shall use at least 75 hopping frequencies.

7.2 Test instruments and measurement setup

The spectrum analyzer is set to as following.

- . RBW= 100KHz
- . VBW= 100KHz
- . Span= the frequency band of operation
- . Sweep= suitable duration based on the EUT specification.

The Number of Hopping Frequency Test Instruments

Description	Model	Serial Number	Cal. Due Date
Spectrum Analyzer	E4407B	US42041281	2009-09-11
RF Cable:	Length: 7cm	-	-
- Spectrum Analyzer <=> EUT	Loss: 1.5dB	-	-

7.3 Measurement results

EUT	Mobile Computer	MODEL	Dolphin 6100
MODE	FHSS	ENVIRONMENTAL CONDITION	25 , 43%RH
INPUT POWER	5Vdc		
Number of CH	Limit (Number of CH)	PASS/FAIL	
79	>75	PASS	





ESTECH Co., Ltd.

Rm 1015, World Venture Center II,
426-5 Gasan-dong, Guncheon-gu,
Seoul, 158-803, Korea



**Electromagnetic
Interference
Test Report**

7.4 Trace data







ESTECH Co., Ltd.

Rm 1015, World Venture Center II,
426-5 Gasan-dong, Gancheon-gu,
Seoul, 158-803, Korea



**Electromagnetic
Interference
Test Report**

7.4 Trace data



8. Time of Occupancy (Dwell Time)

8.1 Test procedure

According to §15.247(a)(1)(iii), Frequency hopping systems operating in the 2400MHz-2483.5 MHz bands. The average time of occupancy on any channels shall not greater than 0.4 s within a period 0.4 s multiplied by the number of hopping channels employed.

8.2 Test instruments and measurement setup

The spectrum analyzer is set to as following.

- . RBW= 1MHz
- . VBW $\geq$ RBW
- . Span= zero span, centered on a hopping channel
- . Sweep = as necessary to capture the entire dwell time per hopping channel
- . Detector function = Peak
- . Trace = Max hold

The Time of Occupancy Test Instruments

Description	Model	Serial Number	Cal. Due Date
Spectrum Analyzer	E4407B	US42041281	2009-09-11
RF Cable:	Length: 7cm	-	-
- Spectrum Analyzer <=> EUT	Loss:1.5dB	-	

8.3 Measurement results

EUT	Mobile Computer	MODEL	Dolphin 6100
MODE	FHSS	ENVIRONMENTAL CONDITION	25 , 43%RH
INPUT POWER	5Vdc		

A. DH1 Mode

One period for each particular channel : $0.400 \text{ ms} \times 320.1 = 128.04 \text{ ms}$

Channel	Pulse Time(ms)	Limit (ms)	PASS/FAIL
0	128.04	400	PASS

B. DH3 Mode

One period for each particular channel : $1.508 \text{ ms} \times 159.9 = 241.13 \text{ ms}$

Channel	Pulse Time(ms)	Limit (ms)	PASS/FAIL
39	241.13	400	PASS


C. DH5 Mode

One period for each particular channel : $2.876 \text{ ms} \times 106.81 = 307.19 \text{ ms}$

Channel	Pulse Time(ms)	Limit (ms)	PASS/FAIL
78	307.19	400	PASS

8.4 Trace data

DH1






ESTECH Co., Ltd.

Rm 1015, World Venture Center II,
426-5 Gasan-dong, Gancheon-gu,
Seoul, 158-803, Korea




**Electromagnetic
Interference
Test Report**

DH3



DH5



8DPSK

A. DH1 Mode

One period for each particular channel : $0.414 \text{ ms} \times 320.1 = 132.5 \text{ ms}$

Channel	Pulse Time(ms)	Limit (ms)	PASS/FAIL
0	132.5	400	PASS

B. DH3 Mode

One period for each particular channel : $1.677 \text{ ms} \times 159.9 = 268.15 \text{ ms}$

Channel	Pulse Time(ms)	Limit (ms)	PASS/FAIL
39	268.15	400	PASS


C. DH5 Mode

One period for each particular channel : $2.911 \text{ ms} \times 106.81 = 310.92 \text{ ms}$

Channel	Pulse Time(ms)	Limit (ms)	PASS/FAIL
78	310.91	400	PASS


8.5 Trace data

DH1




8DPSK

DH3



DH5



9. band-edge and out of band emissions.

9.1 Test procedure

The radio frequency power at 20dB down from the highest inband power level is measured with a spectrum analyzer connected to the antenna terminal, while EUT is operating in transmission mode at the appropriate center frequency. The band edge&out of band emission shall be at least 20dB below of the highest inband power level.

9.2 Test instruments and measurement setup

The spectrum analyzer is set to as following.

- . RBW= 100KHz
- . VBW= 100KHz
- . Span= suitable frequency span
- . Sweep= suitable duration based on the EUT specification.

Band Edge&Out of Emission Test Instruments

Description	Model	Serial Number	Cal. Due Date
Spectrum Analyzer	E4407B	US42041281	2009-09-11
RF Cable:	Length: 5cm	-	-
- Spectrum Analyzer <=> EUT	Loss: 1.5dB	-	-


9.3 Measurement results of band-edge & out of emission

EUT	Mobile Computer	MODEL	Dolphin 6100
MODE	GFSK	ENVIRONMENTAL CONDITION	25 , 43%RH
INPUT POWER	5Vdc		


* Refer to attach spectrum analyzer data chart.

9.4 Trace data of band -edge & Out of Emission

CH0



CH78






ESTECH Co., Ltd.

Rm 1015, World Venture Center II,
426-5 Gasan-dong, Guncheon-gu,
Seoul, 158-803, Korea




**Electromagnetic
Interference
Test Report**

Hopping on CH0



CH78





ESTECH Co., Ltd.


Rm 1015, World Venture Center II,
426-5 Gasan-dong, Guncheon-gu,
Seoul, 158-803, Korea




**Electromagnetic
Interference
Test Report**

8DPSK

CH 0



CH78






ESTECH Co., Ltd.

Rm 1015, World Venture Center 11,
426-5 Gasan-dong, Guncheon-gu,
Seoul, 158-803, Korea




**Electromagnetic
Interference
Test Report**

Hopping on CH 0



CH78





ESTECH Co., Ltd.



Rm 1015, World Venture Center 11,
426-5 Gasan-dong, Guncheon-gu,
Seoul, 158-803, Korea



**Electromagnetic
Interference
Test Report**

GFSK

CH 0







ESTECH Co., Ltd.

Rm 1015, World Venture Center II,
426-5 Gasan-dong, Guncheon-gu,
Seoul, 158-803, Korea



**Electromagnetic
Interference
Test Report**

CH 39







ESTECH Co., Ltd.

Rm 1015, World Venture Center II,
426-5 Gasan-dong, Guncheon-gu,
Seoul, 158-803, Korea



**Electromagnetic
Interference
Test Report**

CH 78





ESTECH Co., Ltd.



Rm 1015, World Venture Center II,
426-5 Gasan-dong, Guncheon-gu,
Seoul, 158-803, Korea



**Electromagnetic
Interference
Test Report**

8DPSK

CH 0







ESTECH Co., Ltd.

Rm 1015, World Venture Center II,
426-5 Gasan-dong, Guncheon-gu,
Seoul, 158-803, Korea



**Electromagnetic
Interference
Test Report**

CH 39







ESTECH Co., Ltd.

Rm 1015, World Venture Center II,
426-5 Gasan-dong, Guncheon-gu,
Seoul, 158-803, Korea



**Electromagnetic
Interference
Test Report**

CH 78



10. Measurement of radiated disturbance

Above 30 MHz Electric Field strength was measured in accordance with FCC Part 15 (2007) & RSS-210. The test setup was made according to ANSI C 63.4 (2003) on an open test site, which allows a 3m distance measurement. The EUT was placed in the center of wooden turntable. The height of this table was 0.8m. The measurement was conducted with both horizontal and vertical antenna polarization. The turntable has fully rotated. For further description of the configuration refer to the picture of the test setup.

10.1 Measurement equipments

Equipment Name	Type	Manufacturer	Serial No.	Next Calibration date
TEST Receiver	ESVS10	Rohde & Schwarz	838562/002	2010. 1. 29
Spectrum Analyzer	R3273	ADVANTEST	110600592	2010. 6. 04
LogBicon Antenna	VULB 9160	Schwarzbeck	3142	2010. 5. 13
Amplifier	8447F	HP	2805A02972	2010. 6. 24
PREAMPLIFIER	8449B	HP	3008A00581	2010. 3. 06
Horn Antenna	BBHA 9120 D	Schwarzbeck	352	2010. 6. 17
Turn Table	2087	EMCO	2129	-
Antenna Mast	2070-01	EMCO	9702-203	-
ANT Mast Controller	2090	EMCO	1535	-
Turn Table Controller	2090	EMCO	1535	-

10.2 Environmental Condition

Test Place : Open site(3m)
 Temperature (°C) : 27
 Humidity (%) : 40 %

10.3 Test Data for Bluetooth

Test Date : 20-Aug-09

Measurement Distance : 3 m

Frequency (MHz)	Reading (dBμV)	Position (V/H)	Height (m)	Correction Factor		Result Value		
				Ant Factor (dB)	Cable (dB)	Limit (dBμV/m)	Result (dBμV/m)	Margin (dB)
80.00	13.20	H	4.0	8.15	1.4	40.0	22.72	-17.28
120.32	17.00	V	1.0	11.21	1.8	43.5	29.97	-13.53
137.91	5.70	H	2.0	12.60	2.0	43.5	20.26	-23.24
150.36	10.80	H	1.8	12.75	2.0	43.5	25.54	-17.96
168.44	17.40	H	1.4	12.04	2.2	43.5	31.62	-11.88
226.55	8.10	H	1.0	10.59	2.6	43.5	21.26	-22.24
240.99	9.40	V	1.0	11.09	2.7	46.0	23.19	-22.81
315.01	10.10	H	1.0	13.27	3.3	46.0	26.71	-19.29
384.07	17.10	H	1.0	14.78	3.9	46.0	35.77	-10.23
403.59	12.40	H	1.0	15.24	4.0	46.0	31.68	-14.32
470.34	7.40	H	1.0	16.76	4.6	46.0	28.74	-17.26
756.17	6.10	V	1.4	21.84	6.8	46.0	34.69	-11.31
Remark	H : Horizontal, V : Vertical Bluetooth(39CH) *Checked in all 3 axis and the maximum measured data were reported. *CL = Cable Loss-Amplifier Gain(In case of above1000Mhz) *CL = Cable Loss(In case of below1000Mhz) *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120KHz for Quasi-peak detection at frequency below 1GHz. *The resolution bandwidth and video bandwidth of spectrum analyzer is 1MHz and 10Hz for average detection at frequency above 1GHz.							

10.3-1 Test Data for Bluetooth(1.0)

Test Date : 21-Aug-09

Measurement Distance : 3 m

Frequency (MHz)	Reading (dBμV)	Position (V/H)	Height (m)	Correction Factor		Result Value		
				Ant Factor (dB)	Cable (dB)	Limit (dBμV/m)	Result (dBμV/m)	Margin (dB)
PEAK(RBW:1Mhz VBW:1MHz)								
2402	72.49	H	1.3	27.62	4.5	*OB	104.61	-
4804	59.00	H	1.2	31.27	-28.9	74.0	61.38	-12.62
2402	69.17	V	1.4	27.62	4.5	*OB	101.29	-
4804	56.39	V	1.5	31.27	-28.9	74.0	58.77	-15.23
AV(RBW:1Mhz VBW:10Hz)								
2402	59.75	H	1.3	27.62	4.5	*OB	91.87	-
4804	48.40	H	1.2	31.27	-28.9	54.0	50.78	-3.22
2402	57.11	V	1.4	27.62	4.5	*OB	89.23	-
4804	44.37	V	1.5	31.27	-28.9	54.0	46.75	-7.25
Remark	H : Horizontal, V : Vertical TEST MODE : Bluetooth-CH0(2402MHz) *The TX signal isn't detected from 3th harmonics. *OB = Operating band *Checked in all 3 axis and the maximum measured data were reported. *CL = Cable Loss-Amplifier Gain(In case of above1000Mhz) *CL = Cable Loss(In case of below1000Mhz) *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120KHz for Quasi-peak detection at frequency below 1GHz. *The resolution bandwidth and video bandwidth of spectrum analyzer is 1MHz and 10Hz for average detection at frequency above 1GHz.							

10.3-2 Test Data for Bluetooth(1.0)

Test Date : 21-Aug-09

Measurement Distance : 3 m

Frequency (MHz)	Reading (dBμV)	Position (V/H)	Height (m)	Correction Factor		Result Value		
				Ant Factor (dB)	Cable (dB)	Limit (dBμV/m)	Result (dBμV/m)	Margin (dB)
PEAK(RBW:1Mhz VBW:1MHz)								
2441	70.78	H	1.0	27.60	4.5	*OB	102.88	-
4882	58.60	H	1.0	31.38	-28.7	74.0	61.31	-12.69
2441	70.03	V	1.0	27.60	4.5	*OB	102.13	-
4882	56.65	V	1.1	31.38	-28.7	74.0	59.36	-14.64
AV(RBW:1Mhz VBW:10Hz)								
2441	58.17	H	1.0	27.60	4.5	*OB	90.27	-
4882	43.58	H	1.0	31.38	-28.7	54.0	46.29	-7.71
2441	57.43	V	1.0	27.60	4.5	*OB	89.53	-
4882	42.03	V	1.1	31.38	-28.7	54.0	44.74	-9.26
Remark	H : Horizontal, V : Vertical TEST MODE : Bluetooth-CH39(2441MHz) *The TX signal isn't detected from 3th harmonics. *OB = Operating band *Checked in all 3 axis and the maximum measured data were reported. *CL = Cable Loss-Amplifier Gain(In case of above1000Mhz) *CL = Cable Loss(In case of below1000Mhz) *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120KHz for Quasi-peak detection at frequency below 1GHz. *The resolution bandwidth and video bandwidth of spectrum analyzer is 1MHz and 10Hz for average detection at frequency above 1GHz.							

10.3-3 Test Data for Bluetooth(1.0)

Test Date : 21-Aug-09

Measurement Distance : 3 m


Frequency (MHz)	Reading (dBμV)	Position (V/H)	Height (m)	Correction Factor		Result Value		
				Ant Factor (dB)	Cable (dB)	Limit (dBμV/m)	Result (dBμV/m)	Margin (dB)
PEAK(RBW:1Mhz VBW:1MHz)								
2480	69.45	H	1.2	27.59	4.5	*OB	101.54	-
4960	61.02	H	1.0	31.49	-28.5	74.0	63.98	-10.02
2480	66.38	V	1.1	27.59	4.5	*OB	98.47	-
4960	56.75	V	1.0	31.49	-28.5	74.0	59.71	-14.29
AV(RBW:1Mhz VBW:10Hz)								
2480	57.36	H	1.2	27.59	4.5	*OB	89.45	-
4960	42.00	H	1.0	31.49	-28.5	54.0	44.96	-9.04
2480	54.84	V	1.1	27.59	4.5	*OB	86.93	-
4960	38.57	V	1.0	31.49	-28.5	54.0	41.53	-12.47
Remark	H : Horizontal, V : Vertical TEST MODE : Bluetooth-CH78(2480MHz) *The TX signal isn't detected from 3th harmonics. *OB = Operating band *Checked in all 3 axis and the maximum measured data were reported. *CL = Cable Loss-Amplifier Gain(In case of above1000Mhz) *CL = Cable Loss(In case of below1000Mhz) *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120KHz for Quasi-peak detection at frequency below 1GHz. *The resolution bandwidth and video bandwidth of spectrum analyzer is 1MHz and 10Hz for average detection at frequency above 1GHz.							

10.4 Restricted Band Edges for BT(1.0)

Band Edges(CH Low)

Detector mode:Peak


Polarity:Horizontal



Comment: 6100_BT(1.0)_CH0_PEAK_HOR
Date: 21.AUG.2009 12:53:49

Detector mode:Average

Polarity:Horizontal




Comment: 6100_BT(1.0)_CH0_AV_HOR
Date: 21.AUG.2009 12:55:22

Band Edges(CH Low)

Detector mode:Peak


Polarity:Vertical



Comment: 6100_BT(1.0)_CH0_PEAK_VER
Date: 21.AUG.2009 13:01:59

Detector mode:Average

Polarity:Vertical




Comment: 6100_BT(1.0)_CH0_AV_VER
Date: 21.AUG.2009 13:02:46

Band Edges(CH High)

Detector mode:Peak


Polarity:Horizontal



Comment : 6100_BT(1.0)_CH78_PEAK_HOR
Date: 21.AUG.2009 12:40:14

Detector mode:Average

Polarity:Horizontal




Comment : 6100_BT(1.0)_CH78_AV_HOR
Date: 21.AUG.2009 12:41:45

Band Edges(CH High)

Detector mode:Peak


Polarity:Vertical



Comment: 6100_BT(1.0)_CH78_PEAK_VER
 Date: 21.AUG.2009 12:36:27

Detector mode:Average

Polarity:Vertical



Comment: 6100_BT(1.0)_CH78_AV_VER
 Date: 21.AUG.2009 12:36:59

10.5 Test Data for Bluetooth(2.0)

Test Date : 21-Aug-09

Measurement Distance : 3 m

Frequency (MHz)	Reading (dB μ V)	Position (V/H)	Height (m)	Correction Factor		Result Value		
				Ant Factor (dB)	Cable (dB)	Limit (dB μ V/m)	Result (dB μ V/m)	Margin (dB)
PEAK(RBW:1Mhz VBW:1MHz)								
2402	68.43	H	1.3	27.62	4.5	*OB	100.55	-
4804	51.59	H	1.0	31.27	-28.9	74.00	53.97	-20.03
2402	64.81	V	1.4	27.62	4.5	*OB	96.93	-
4804	50.89	V	1.1	31.27	-28.9	74.00	53.27	-20.73
AV(RBW:1Mhz VBW:10Hz)								
2402	54.55	H	1.3	27.62	4.5	*OB	86.67	-
4804	34.72	H	1.0	31.27	-28.9	54.0	37.10	-16.90
2402	51.59	V	1.4	27.62	4.5	*OB	83.71	-
4804	35.03	V	1.1	31.27	-28.9	54.0	37.41	-16.59
Remark	H : Horizontal, V : Vertical TEST MODE : Bluetooth-CH0(2402MHz) *The TX signal isn't detected from 3th harmonics. *OB = Operating band *Checked in all 3 axis and the maximum measured data were reported. *CL = Cable Loss-Amplifier Gain(In case of above1000Mhz) *CL = Cable Loss(In case of below1000Mhz) *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120KHz for Quasi-peak detection at frequency below 1GHz. *The resolution bandwidth and video bandwidth of spectrum analyzer is 1MHz and 10Hz for average detection at frequency above 1GHz.							

10.5 - 1 Test Data for Bluetooth(2.0)

Test Date : 21-Aug-09

Measurement Distance : 3 m

Frequency (MHz)	Reading (dBμV)	Position (V/H)	Height (m)	Correction Factor		Result Value		
				Ant Factor (dB)	Cable (dB)	Limit (dBμV/m)	Result (dBμV/m)	Margin (dB)
PEAK(RBW:1Mhz VBW:1MHz)								
2441	68.31	H	1.2	27.60	4.5	*OB	100.41	-
4882	50.76	H	1.2	31.38	-28.7	74.0	53.47	-20.53
2441	66.07	V	1.2	27.60	4.5	*OB	98.17	-
4882	49.47	V	1.0	31.38	-28.7	74.0	52.18	-21.82
AV(RBW:1Mhz VBW:10Hz)								
2441	55.46	H	1.2	27.60	4.5	*OB	87.56	-
4882	33.38	H	1.2	31.38	-28.7	54.0	36.09	-17.91
2441	51.76	V	1.2	27.60	4.5	*OB	83.86	-
4882	33.00	V	1.0	31.38	-28.7	54.0	35.71	-18.29
Remark	H : Horizontal, V : Vertical TEST MODE : Bluetooth-CH39(2441MHz) *The TX signal isn't detected from 3th harmonics. *OB = Operating band *Checked in all 3 axis and the maximum measured data were reported. *CL = Cable Loss-Amplifier Gain(In case of above1000Mhz) *CL = Cable Loss(In case of below1000Mhz) *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120KHz for Quasi-peak detection at frequency below 1GHz. *The resolution bandwidth and video bandwidth of spectrum analyzer is 1MHz and 10Hz for average detection at frequency above 1GHz.							

10.5-2 Test Data for Bluetooth(2.0)

Test Date : 21-Aug-09

Measurement Distance : 3 m


Frequency (MHz)	Reading (dBμV)	Position (V/H)	Height (m)	Correction Factor		Result Value		
				Ant Factor (dB)	Cable (dB)	Limit (dBμV/m)	Result (dBμV/m)	Margin (dB)
PEAK(RBW:1Mhz VBW:1MHz)								
2480	66.09	H	1.2	27.59	4.5	*OB	98.18	-
4960	52.13	H	1.1	31.49	-28.5	74.0	55.09	-18.91
2480	64.31	V	1.1	27.59	4.5	*OB	96.40	-
4960	48.84	V	1.0	31.49	-28.5	74.0	51.80	-22.20
AV(RBW:1Mhz VBW:10Hz)								
2480	52.68	H	1.2	27.59	4.5	*OB	84.77	-
4960	31.05	H	1.1	31.49	-28.5	54.0	34.01	-19.99
2480	52.35	V	1.1	27.59	4.5	*OB	84.44	-
4960	30.74	V	1.0	31.49	-28.5	54.0	33.70	-20.30
Remark	H : Horizontal, V : Vertical TEST MODE : Bluetooth-CH78(2480MHz) *The TX signal isn't detected from 3th harmonics. *OB = Operating band *Checked in all 3 axis and the maximum measured data were reported. *CL = Cable Loss-Amplifier Gain(In case of above1000Mhz) *CL = Cable Loss(In case of below1000Mhz) *The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120KHz for Quasi-peak detection at frequency below 1GHz. *The resolution bandwidth and video bandwidth of spectrum analyzer is 1MHz and 10Hz for average detection at frequency above 1GHz.							

10.6 Restricted Band Edges for BT(2.0)

Band Edges(CH Low)

Detector mode:Peak


Polarity:Horizontal



Comment: 6100_BT EDR_CH0_PEAK_HOR_
Date: 21.AUG.2009 17:37:53

Detector mode:Average

Polarity:Horizontal




Comment: 6100_BT EDR_CH0_AV_HOR_
Date: 21.AUG.2009 17:38:54

Band Edges(CH Low)

Detector mode:Peak

Polarity:Vertical




Comment: 6100_BT EDR_CH0_PEAK_VER_

Date: 21.AUG.2009 17:45:57

Detector mode:Average

Polarity:Vertical




Comment: 6100_BT EDR_CH0_AV_VER_

Date: 21.AUG.2009 17:47:22

Band Edges(CH High)

Detector mode:Peak


Polarity:Horizontal



Comment : 6100_BT EDR_CH78_PEAK_HOR
Date : 21.AUG.2009 17:56:57

Detector mode:Average

Polarity:Horizontal




Comment : 6100_BT EDR_CH78_AV_HOR
Date : 21.AUG.2009 17:58:24

Band Edges(CH High)

Detector mode:Peak


Polarity:Vertical



Comment : 6100_BT EDR_CH78_PEAK_VER
Date: 21.AUG.2009 17:11:52

Detector mode:Average

Polarity:Vertical



Comment : 6100_BT EDR_CH78_AV_VER
Date: 21.AUG.2009 17:12:59

11. Measurement of conducted disturbance

The continuous disturbance voltage of AC Mains in the frequency from 0.15 to 30 MHz was measured in accordance to FCC Part 15 (2007) & RSS-210. The test setup was made according to ANSI C 63.4 (2003) in a shielded. The EUT was placed on a non-conductive table at least 80 above the ground plan. A grounded vertical reference plane was positioned in a distance of 40cm from the EUT. The distance from the EUT to other metal surfaces was at least 0.8m. The EUT was only earthen by its power cord through the line impedance stabilizing network. The power cord has been bundled to a length of 1.0m.. The test receiver with Quasi Peak detector complies with CISPR 16.

11.1 Measurement equipments

Equipment Name	Type	Manufacturer	Serial No.	Next Calibration date
LISN	ESH3-Z5	Schwarzbeck	838979/010	2010. 2. 21
LISN	NNLA8120A	Schwarzbeck	8120161	2010. 2. 21
TEST Receiver	ESPI7	Rohde & Schwarz	100185	2009. 8. 27
Pulse Limiter	ESH3Z2	Rohde & Schwarz	NONE	2009. 9. 10

11.2 Environmental Condition

Test Place : Shield Room
 Temperature (°C) : 24
 Humidity (%) : 50 %

11.3 Test Data for Bluetooth

Test Date : 20-Aug-09

Frequency (MHz)	Correction Factor		Line (H/N)	Quasi-peak Value			Average Value		
	Lisn (dB)	Cable (dB)		Limit (dB μ V)	Reading (dB μ V)	Result (dB μ V)	Limit (dB μ V)	Reading (dB μ V)	Result (dB)
0.15	0.09	0.2	N	65.84	41.63	41.95	55.84	27.74	28.06
0.16	0.09	0.2	H	65.67	40.35	40.67	55.67	26.36	26.68
0.18	0.09	0.2	N	64.35	38.75	39.07	54.35	25.99	26.31
0.32	0.09	0.2	H	59.84	36.91	37.24	49.84	24.60	24.93
0.38	0.09	0.3	N	58.19	38.20	38.58	48.19	25.94	26.32
0.47	0.10	0.3	H	56.44	37.45	37.89	46.44	26.85	27.29
0.51	0.10	0.4	N	56.00	36.93	37.39	46.00	30.06	30.52
0.56	0.10	0.4	H	56.00	36.78	37.25	46.00	26.20	26.67
0.57	0.10	0.4	H	56.00	35.85	36.32	46.00	24.43	24.90
0.62	0.10	0.4	N	56.00	36.47	36.95	46.00	26.26	26.74
0.65	0.11	0.4	N	56.00	36.94	37.43	46.00	22.45	22.94
0.89	0.11	0.5	N	56.00	35.38	35.94	46.00	22.13	22.69
6.85	0.30	0.7	N	60.00	32.35	33.40	50.00	24.79	25.84
7.57	0.32	0.8	H	60.00	30.19	31.29	50.00	23.94	25.04
7.77	0.32	0.8	N	60.00	33.07	34.19	50.00	24.73	25.85
8.04	0.33	0.8	N	60.00	33.43	34.56	50.00	25.10	26.23
9.34	0.35	0.9	N	60.00	32.16	33.37	50.00	24.52	25.73
10.76	0.41	0.9	N	60.00	30.45	31.76	50.00	20.83	22.14
Remark	H : Hot Line, N : Neutral Line TEST MODE : Bluetooth-CH39(2441MHz)								

12. Photographs of test setup

12.1. Setup for Radiated Test : 30 ~ 1000 MHz

[Front]




[Rear]



12.2. Setup for Radiated Test :Above 1000 MHz

[Front]




12.3. Setup for Conducted Test : 0.15 ~ 30 MHz

[Front]



[Rear]



12.4. Photographs of EUT

[Front]




[Rear]



Appendix 1. Spectral diagram for Bluetooth

Bluetooth - CH 39


*HOT



Comment: 6100_BT_HOT

Date: 20.AUG.2009 10:19:23

*NEUTRAL



Comment: 6100_BT_NEUTRAL

Date: 20.AUG.2009 10:03:42

Appendix 2. Antenna Requirement

1. Antenna Requirement

1.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.24

1.2 Antenna Connected Construction

The antenna types used in this product are Intergrated Sandwich antenna . The maximum Gain of this antenna is 1.48dBi.