



FCC Test Report

Test report no.: EMC_662FCC15.247_2004_BT

FCC Part 15.247 for FHSS systems / CANADA RSS-210

Model: 7900L0P

FCC ID: HD57900L0P

IC: 1693B79L0P



TTI-P-G 081/94-A0

Accredited according to ISO/IEC 17025



FCC listed # 101450

IC recognized # 3925

CETECOM Inc.

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: info@ceteconusa.com • <http://www.cetecon.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2113686
Board of Directors: Dr. Harald Ansorge, Dr. Klaus Matkey, Hans Peter May

Table of Contents**1 General information****1.1 Notes****1.2 Testing laboratory****1.3 Details of applicant****1.4 Application details****1.5 Test item****1.6 Test standards****2 Technical test****2.1 Summary of test results****2.2 Test report****1 General information****1.1 Notes**

The test results of this test report relate exclusively to the test item specified in 1.5. The CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM Inc USA.

TEST REPORT PREPARED BY:

EMC Engineer: Harpreet Sidhu

1.2 Testing laboratory

CETECOM Inc.

411 Dixon Landing Road, Milpitas, CA-95035, USA

Phone: +1 408 586 6200 Fax: +1 408 586 6299

E-mail: lothar.schmidt@cetecomusa.com

Internet: www.cetecom.com

1.3 Details of applicant

Name : Hand Held Products, Inc.
Street : 700 Vision Drive
City / Zip Code : Skaneateles Falls, NY 13153
Country : U.S.A
Contact : Naveen Velagapudi
Telephone : +1 315 685 2931
Tele-fax : +1 315 685 1210
e-mail : velagapudin@hhp.com

1.4 Application details

Date of receipt test item : 2004-08-16
Date of test : 2004-08-16/17/18

1.5 Test item

Manufacturer : Applicant
Marketing Name : D7900
Model No. : **7900L0P**
Description : Hand held computer with BT and WLAN
FCC-ID : HD57900L0P
IC ID : 1693B79L0P

Additional information

Test Sample for BT : s/n 32598
Frequency : 2402MHz – 2480MHz for BT
Type of modulation : GFSK
Number of channels : 79
Antenna : Internal
Power supply : Battery or Charger (AC Adaptor)
Output power : -11.4dBm (0.00007W) max. conducted peak power

1.6 Test standards:

FCC Part 15 §15.247 (DA00-705) / RSS 210

Note: All radiated measurements were made in all three orthogonal planes. The values reported are the maximum values.

PROJECT OVERVIEW:

NOTE: This test report covers all radiated measurements as per FCC15.247 for BT module in HHP handheld computer model#7900L0P. For all conducted measurements please refer to *test report# BT_cond_Socket*.

2 Technical test**2.1 Summary of test results**

No deviations from the technical specification(s) were ascertained in the course of the tests
Performed

Final Verdict: (only "passed" if all single measurements are "passed")	Passed
---	---------------

Technical responsibility for area of testing:2004-10-04 EMC & Radio Lothar Schmidt (Manager)**Date****Section****Name****Signature****Responsible for test report and project leader:**2004-10-04 EMC & Radio Harpreet Sidhu (EMC Engineer)**Date****Section****Name****Signature**

2.2 Test report

TEST REPORT

Test report no.: EMC_662FCC15.247_2004_BT_7900L0P

TEST REPORT REFERENCE

LIST OF MEASUREMENTS		PAGE
MAXIMUM PEAK OUTPUT POWER	§ 15.247 (b) (1)	8
BAND EDGE COMPLIANCE	§15.247 (c)	13
CONDUCTED EMISSIONS	§ 15.107/207	28
RECEIVER SPURIOUS RADIATION	§ 15.209	30
TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS		35
BLOCK DIAGRAMS		36

**MAXIMUM PEAK OUTPUT POWER
(CONDUCTED)****§ 15.247 (b) (1)**

TEST CONDITIONS		MAXIMUM PEAK OUTPUT POWER (dBm)		
Frequency (MHz)		Error! Reference source not found.	Error! Reference source not found.	Error! Reference source not found.
$T_{\text{nom}}(23)^{\circ}\text{C}$	V_{nom}	-13.6	-12.7	-11.4
Measurement uncertainty		$\pm 0.5\text{dBm}$		

RBW/VBW: 3 MHz

LIMIT**SUBCLAUSE § 15.247 (b) (1)**

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt conducted

**MAXIMUM PEAK OUTPUT POWER
(RADIATED)****§ 15.247 (b) (1)****EIRP:**

TEST CONDITIONS		MAXIMUM PEAK OUTPUT POWER (dBm)		
Frequency (MHz)		Error! Reference source not found.	Error! Reference source not found.	Error! Reference source not found.
T _{nom} (23)°C	V _{nom}	-19.99	-21.63	-22.65
Measurement uncertainty		±0.5dBm		

RBW/VBW: 3 MHz


LIMIT**SUBCLAUSE § 15.247 (b) (1)**

Frequency range	RF power output
2400-2483.5 MHz	1.0 Watt conducted

PEAK OUTPUT POWER (RADIATED)**§15.247 (b) (1)****Lowest Channel:** Error! Reference source not found. **MHz**

SWEEP TABLE: "EIRP BT low channel"


Start Frequency	Stop Frequency	Detector	Meas.	IF
2.397GHz	2.407GHz	MaxPeak	Coupled	3 MHz



PEAK OUTPUT POWER (RADIATED)**§15.247 (b) (1)****Mid Channel:** Error! Reference source not found. **MHz**

SWEEP TABLE: "EIRP BT Mid channel"


Start Frequency	Stop Frequency	Detector	Meas.	IF
2.436GHz	2.446GHz	MaxPeak	Time Coupled	BW 3 MHz



PEAK OUTPUT POWER (RADIATED)**§15.247 (b) (1)****Highest Channel:** Error! Reference source not found. **MHz**

SWEEP TABLE: "EIRP BT High channel"


Short Description:	EIRP Bluetooth channel-2480MHz			
Start Frequency	Stop Frequency	Detector	Meas.	IF
2.475GHz	2.485GHz	MaxPeak	Time Coupled	3 MHz



BAND EDGE COMPLIANCE**§15.247 (c)****Low frequency section (spurious in the restricted band 2310 – 2390 MHz)****Average Measurement****(This plot is valid for both Hopping ON & OFF)**

Operating condition : Tx at 2402MHz
SWEEP TABLE : "FCC15.247 LBE_AVG"
Short Description : FCC15.247 BT Low-band-edge
Limit Line : 54dB μ V


Start Frequency	Stop Frequency	Detector Time	Meas. Bandw.	RBW	VBW	Transducer
2.31 GHz	2.412 GHz	MaxPeak	Coupled	1 MHz	10Hz	#326 horn (dBi)



BAND EDGE COMPLIANCE**§15.247 (c)****Low frequency section (spurious in the restricted band 2310 – 2390 MHz)****Peak Measurement****(This plot is valid for both Hopping ON & OFF)**

Operating condition : Tx at 2402MHz
SWEEP TABLE : "FCC15.247 LBE_Pk"
Short Description : FCC15.247 BT Low-band-edge
Limit Line : 74dB μ V


Start Frequency	Stop Frequency	Detector Time	Meas. Bandw.	RBW	VBW	Transducer
2.31 GHz	2.412 GHz	MaxPeak	Coupled	1 MHz	1MHz	#326 horn (dBi)



BAND EDGE COMPLIANCE**§15.247 (c)****High frequency section (spurious in the restricted band 2483.5 – 2500 MHz)****Average Measurement****(This plot is valid for both Hopping ON & OFF)**

Operating condition : Tx at 2480MHz
SWEEP TABLE : "FCC15.247 HBE_AVG"
Short Description : FCC15.247 BT High-band-edge
Limit Line : 54dB μ V


Start Frequency	Stop Frequency	Detector Time	Meas. Bandw.	RBW	VBW	Transducer
2.462 GHz	2.5 GHz	MaxPeak	Coupled	1 MHz	10Hz	#326 horn (dBi)



BAND EDGE COMPLIANCE**§15.247 (c)****High frequency section (spurious in the restricted band 2483.5 – 2500 MHz)****Peak Measurement****(This plot is valid for both Hopping ON & OFF)**

Operating condition : Tx at 2480MHz
SWEEP TABLE : "FCC15.247 HBE_PK"
Short Description : FCC15.247 BT High-band-edge
Limit Line : 74dB μ V

Start Frequency	Stop Frequency	Detector Time	Meas. Bandw.	RBW	VBW	Transducer
2.462 GHz	2.5 GHz	MaxPeak	Coupled	1 MHz	1MHz	#326 horn (dBi)



**EMISSION LIMITATIONS
Transmitter (Radiated)****§ 15.247 (c) (1)****LIMITS**

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions that fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

NOTE:

1. The radiated emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels. In the range between 3 and 26.5 GHz very short cable connections to the antenna was used to minimize the noise level.
2. Frequency resolution is not fine enough to show the exact frequency of the carrier, refer to plots under EIRP.
3. All measurements are done in peak mode unless specified with plots.

Results for the radiated measurements below 30MHz according § 15.33

Frequency	Measured values	Remarks
9KHz – 30MHz	No emissions found, caused by the EUT	This is valid for all the tested channels

EMISSION LIMITATIONS - Radiated (Transmitter)**§ 15.247 (c) (1)**

Note: All radiated measurements were made in all three orthogonal planes. The values reported are the maximum values.

Transmit at Lowest channel Frequency 2402MHz			
Frequency (MHz)	Level (dB μ V/m)		
	Peak	Quasi-Peak	Average
SEE PLOTS			
Transmit at Middle channel Frequency 2441MHz			
Frequency (MHz)	Level (dB μ V/m)		
	Peak	Quasi-Peak	Average
SEE PLOTS			
Transmit at Highest channel Frequency 2480MHz			
Frequency (MHz)	Level (dB μ V/m)		
	Peak	Quasi-Peak	Average
SEE PLOTS			

EMISSION LIMITATIONS - Radiated (Transmitter)**§ 15.247 (c) (1)****30MHz – 1GHz****Antenna: vertical****Note: This plot is valid for low, mid & high channels (worst-case plot)**


SWEEP TABLE: "BT Spuri hi 30-1G"

Short Description: Bluetooth 30MHz-1GHz

Start Stop Detector Meas. RBW Transducer

Frequency Frequency Time VBW


30.0 MHz 1.0 GHz MaxPeak Coupled 100 kHz 3141-#1186



EMISSION LIMITATIONS - Radiated (Transmitter)**§ 15.247 (c) (1)****30MHz – 1GHz****Antenna: horizontal****Note: This plot is valid for low, mid & high channels (worst-case plot)**

SWEEP TABLE: "BT Spuri hi 30-1G"
Short Description: Bluetooth 30MHz-1GHz

Start Frequency	Stop Frequency	Detector	Meas.	RBW	Transducer
30.0 MHz	1.0 GHz	MaxPeak	Time Coupled	100 kHz	3141-#1186




EMISSION LIMITATIONS - Radiated (Transmitter) **§ 15.247 (c) (1)**
Lowest Channel (Error! Reference source not found. MHz): 1GHz – 3GHz**NOTE: The peak is the carrier frequency.**

SWEEP TABLE: "BT Spuri hi 1-3G"

Short Description: Bluetooth Spurious 1-3GHz


Start Frequency	Stop Frequency	Detector	Meas.	RBW	Transducer
1.0 GHz	3.0 GHz	Time	Bandw.	VBW	
		MaxPeak	Coupled	1 MHz	#326 horn (dBi)



EMISSION LIMITATIONS - Radiated (Transmitter) § 15.247 (c) (1)
Lowest Channel (Error! Reference source not found. MHz): 3GHz – 18GHz

SWEEP TABLE: "BT Spuri hi 3-18G"
Short Description: Bluetooth Spurious 3-18 GHz


Start Frequency	Stop Frequency	Detector Time	Meas. Bandw.	RBW	VBW	Transducer
3.0 GHz	18.0 GHz	MaxPeak	Coupled	1 MHz		#326 horn (dBi)



EMISSION LIMITATIONS - Radiated (Transmitter) **§ 15.247 (c) (1)**
Middle Channel (Error! Reference source not found. MHz): 1GHz – 3GHz**NOTE: The peak is the carrier frequency.**

SWEEP TABLE: "BT Spuri hi 1-3G"
Short Description: Bluetooth Spurious 1-3GHz


Start Frequency	Stop Frequency	Detector	Meas.	RBW	Transducer
1.0 GHz	3.0 GHz	Time	Bandw.	VBW	
		MaxPeak	Coupled	1 MHz	#326 horn (dBi)



EMISSION LIMITATIONS - Radiated (Transmitter) § 15.247 (c) (1)
Middle Channel (Error! Reference source not found. MHz): 3GHz – 18GHz

SWEEP TABLE: "BT Spuri hi 3-18G"
Short Description: Bluetooth Spurious 3-18GHz

Start Frequency	Stop Frequency	Detector	Meas.	RBW	Transducer
3.0 GHz	18.0 GHz	Time	Bandw.	VBW	
		MaxPeak	Coupled	1 MHz	#326 horn (dBi)




EMISSION LIMITATIONS - Radiated (Transmitter) § 15.247 (c) (1)
Highest Channel (Error! Reference source not found. MHz): 1GHz – 3GHz**NOTE: The peak is the carrier frequency.**

SWEEP TABLE: "BT Spuri hi 1-3G"

Short Description: Bluetooth Spurious 1-3GHz


Start Frequency	Stop Frequency	Detector	Meas.	RBW	Transducer
1.0 GHz	3.0 GHz	Time	Bandw.	VBW	
		MaxPeak	Coupled	1 MHz	#326 horn (dBi)



EMISSION LIMITATIONS - Radiated (Transmitter) § 15.247 (c) (1)
Highest Channel (Error! Reference source not found. MHz): 3GHz – 18GHz

SWEEP TABLE: "BT Spuri hi 3-18G"
Short Description: Bluetooth Spurious 3-18GHz

Start Frequency	Stop Frequency	Detector	Meas.	RBW	Transducer
3.0 GHz	18.0 GHz	Time	Bandw.	VBW	
		MaxPeak	Coupled	1 MHz	#326 horn (dBi)



EMISSION LIMITATIONS - Radiated (Transmitter)**§ 15.247 (c) (1)****18GHz – 26.5GHz****Note: This plot is valid for low, mid & high channels (worst-case plot)**


SWEEP TABLE:

"BT Spuri hi 18-26.5G"

Short Description:

Bluetooth Spurious 18-26.5GHz


Start Frequency	Stop Frequency	Detector	Meas.	RBW	Transducer
18 GHz	26.5 GHz	Time	Bandw.	VBW	
		MaxPeak	Coupled	1 MHz	#141 horn (dBi)



CONDUCTED EMISSIONS
§ 15.107/207
Technical specification: 15.107 / 15.207 (Revised as of August 20, 2002)
Limit

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

* Decreases with logarithm of the frequency

ANALYZER SETTINGS: RBW = 10KHz
VBW = 10KHz


MEASUREMENT RESULT: "test_fin AV"


Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
4.190000	35.80	0.0	46	10.2	N	GND
4.260000	37.90	0.0	46	8.1	N	GND
4.325000	35.40	0.0	46	10.6	N	GND
4.935000	36.90	0.0	46	9.1	N	GND
5.000000	34.00	0.0	46	12.0	N	GND
22.110000	39.90	0.0	50	10.1	N	GND

RECEIVER SPURIOUS RADIATION**§ 15.209****Limits**

Frequency (MHz)	Field strength (μ V/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
above 960	500	3

NOTE:


1. The radiated emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels. In the range between 3 and 26.5 GHz very short cable connections to the antenna was used to minimize the noise level.
2. All measurements are done in peak mode unless specified with the plots.

RECEIVER SPURIOUS RADIATION**§ 15.209****30MHz – 1GHz****Antenna: vertical (worst-case plot)**SWEEP TABLE: "BT Spuri hi 30-1G"
Short Description: Bluetooth 30MHz-1GHzStart Stop Detector Meas. RBW Transducer
Frequency Frequency Time VBW
30.0 MHz 1.0 GHz MaxPeak Coupled 100 kHz 3141-#1186

**RECEIVER SPURIOUS RADIATION
1GHz – 3GHz****§ 15.209**

SWEEP TABLE: "BT Spuri hi 1-3G"
Short Description: Bluetooth Spurious 1-3GHz


Start Frequency	Stop Frequency	Detector	Meas.	RBW	Transducer
1.0 GHz	3.0 GHz	Time	Bandw.	VBW	#326 horn (dBi)
		MaxPeak	Coupled	1 MHz	



**RECEIVER SPURIOUS RADIATION
3GHz – 18GHz****§ 15.209**


SWEEP TABLE: "BT Spuri hi 3-18G"
Short Description: Bluetooth Spurious 3-18 GHz

Start Frequency	Stop Frequency	Detector	Meas.	RBW	Transducer
3.0 GHz	18.0 GHz	Time	Bandw.	VBW	#326 horn (dBi)
		MaxPeak	Coupled	1 MHz	



**RECEIVER SPURIOUS RADIATION
18GHz – 26.5GHz****§ 15.209**

SWEET TABLE: "BT Spuri hi 18-26.5G"
Short Description: Bluetooth Spurious 18-26.5GHz
Start Stop Detector Meas. RBW Transducer
Frequency Frequency Time Bandw. VBW
18.0 GHz 26.5 GHz MaxPeak Coupled 1 MHz #326 horn (dBi)




TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

No	Instrument/Ancillary	Type	Manufacturer	Serial No.
01	Spectrum Analyzer	ESIB 40	Rohde & Schwarz	100107
02	Spectrum Analyzer	FSEM 30	Rohde & Schwarz	826880/010
03	Biconilog Antenna	3141	EMCO	0005-1186
04	Horn Antenna (700M-18GHz)	SAS-200/571	AH Systems	325
05	Horn Antenna (18-26.5GHz)	3160-09	EMCO	1240
06	2-3GHz Band reject filter	BRM50701	Microtronics	6
07	Pre-Amplifier	TS-ANA	Rohde & Schwarz	--
08	Pre-Amplifier	JS4-00102600	Miteq	00616

BLOCK DIAGRAMS

Conducted Testing



Radiated Testing**ANECHOIC CHAMBER**