



Radio Exposure Evaluation Report

| | |
|--------------|--|
| FCC ID | : HDC-649B |
| Equipment | : WiFi6 module |
| Brand Name | : ADTRAN ® |
| Model Name | : W649bYYYYYY(Y can be 0-9, a-z, A-Z, blank, "+" or "-" or "#") |
| Applicant | : Adtran 901 Explorer Blvd., Huntsville, AL 35806, USA |
| Manufacturer | : XAVi Technologies Corporation 22F., No.69, Sec. 2, Guangfu Rd., Sanchong Dist., New Taipei City 241, Taiwan (R.O.C.) |
| Standard | : 47 CFR FCC Part 2 Subpart J, section 2.1091 |

The product was received on Nov. 18, 2024, and testing was started from Dec. 23, 2024 and completed on Jan. 07, 2025. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR FCC Part 2 Subpart J, section 2.1091 and shown compliance with the applicable technical standards.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.

Approved by: Jackson Tsai

SPORTON INTERNATIONAL INC. Hsinhua Laboratory
No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



Table of Contents

| | |
|---|----------|
| HISTORY OF THIS TEST REPORT | 3 |
| SUMMARY OF TEST RESULT | 4 |
| 1 GENERAL DESCRIPTION | 5 |
| 1.1 Information..... | 5 |
| 1.2 Applicable Standards | 6 |
| 1.3 Testing Location | 6 |
| 2 MAXIMUM PERMISSIBLE EXPOSURE | 7 |
| 2.1 Limit of Maximum Permissible Exposure | 7 |
| 2.2 RF Exposure Exempt Measurement | 7 |
| 2.3 Multiple RF Sources Exposure..... | 8 |
| 2.4 MPE Calculation Method..... | 9 |
| 2.5 Calculated Result and Limit..... | 10 |
| Photographs of EUT V01 | |



History of this test report



Summary of Test Result

| Report Clause | Ref Std. Clause | Test Items | Result (PASS/FAIL) | Remark |
|---------------|-----------------|---------------------|--------------------|--------|
| 2 | - | Exposure evaluation | PASS | - |

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

None

Reviewed by: Terry Chang

Report Producer: Julie Tseng



1 General Description

1.1 Information

1.1.1 EUT General Information

| RF General Information | | | |
|------------------------|------------------------|---------------------------|--|
| Evaluation Mode | Frequency Range (MHz) | Operating Frequency (MHz) | Modulation Type |
| 5GHz WLAN | 5470-5725 5725-5850 | 5500-5720 5745-5825 | 802.11a/n: OFDM (BPSK, QPSK, 16QAM, 64QAM) 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM) 802.11ax: OFDMA (BPSK, QPSK, 16QAM, 64QAM, 256QAM, 1024QAM) |

1.1.2 Antenna Information

| Ant. | Brand | Model Name | Antenna Type | Connector | Gain (dBi) |
|------|------------|--------------|--------------|-----------|------------|
| 1 | GALTRONICS | 60-3523-03-2 | PCB | U.FL | 3.99 |
| 2 | GALTRONICS | 60-2888-03-2 | PCB | U.FL | 3.99 |
| 3 | GALTRONICS | 60-2791-03 | PCB | U.FL | 2.12 |
| 4 | GALTRONICS | 60-2808-03 | PCB | U.FL | 2.12 |

Note 1: The EUT has four antennas.

For 5GHz function:

For IEEE 802.11 a/n/ac/ax mode (4TX/4RX)

Ant. 1~4 could transmit/receive simultaneously.

1.1.3 Table for Multiple Listing

The model names in the following table are all refer to the identical product.

| Model Name | Description |
|--|--|
| W649bYYYYYY (Y can be 0-9, a-z, A-Z, blank, "+" or "-" or "#") | All the models are identical, the difference model served as marketing strategy. |

1.1.4 Table for Permissive Change

This product is an extension of original one reported under Sporton project number: FA182708-03
Below is the table for the change of the product with respect to the original one.

| Modifications | Performance Checking |
|--|----------------------|
| The 841 motherboard 5G filter and 5G module filter were replaced with Qorvo alternative materials. | MPE was evaluated. |



1.2 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 2 Subpart J, section 2.1091
- ♦ KDB 447498 D04 Interim General RF Exposure Guidance v01

The following reference test guidance is not within the scope of accreditation of TAF.

- ♦ 47 CFR Part 1.1307
- ♦ 47 CFR Part 1.1310

1.3 Testing Location

| Test Lab. : Sporton International Inc. Hsinhua Laboratory | | | |
|--|--|----------------------------|--|
| <input checked="" type="checkbox"/> Hsinhua (TAF: 3785) | ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.) TEL: 886-3-327-3456 | FAX: 886-3-327-0973 | |
| Test site Designation No. TW3785 with FCC. | | | |
| <input type="checkbox"/> Wen 33rd.St. (TAF: 3785) | ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: 886-3-318-0787 | FAX: 886-3-318-0287 | |
| Test site Designation No. TW0008 with FCC. | | | |



2 Maximum Permissible Exposure

2.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|--|--|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 |
| 3.0-30 | 1842 / f | 4.89 / f | (900 / f ²)* | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | - | - | F/300 | 6 |
| 1500-100,000 | - | - | 5 | 6 |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|--|--|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f ²)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | - | - | F/1500 | 30 |
| 1500-100,000 | - | - | 1.0 | 30 |

Note: f = frequency in MHz ; *Plane-wave equivalent power density

2.2 RF Exposure Exempt Measurement

| Option | Refer Std. | Exemption Exposure Thresholds (TL) |
|--------|---------------------|--|
| A | §1.1307(b)(3)(i)(A) | Available maximum time-averaged power is no more than 1 mW |
| B | §1.1307(b)(3)(i)(B) | $P_{th}(mW) = \begin{cases} ERP_{20cm}(d / 20cm)^x \rightarrow d \leq 20cm \\ ERP_{20cm} \rightarrow 20cm < d \leq 40cm \end{cases}$ $x = -\log_{10}\left(\frac{60}{ERP_{20cm}\sqrt{f}}\right) \text{ and f is in GHz}$ $\begin{cases} ERP_{20cm} : 0.3GHz \leq f < 1.5GHz \rightarrow 2040f(mW) \\ ERP_{20cm} : 1.5GHz \leq f \leq 6GHz \rightarrow 3060(mW) \end{cases}$ |
| C | §1.1307(b)(3)(i)(C) | $\begin{cases} 0.3 \sim 1.34MHz \rightarrow ERP(W) = 1920R^2 \\ 1.34 \sim 30MHz \rightarrow ERP(W) = 3450R^2 / f^2 \\ 30 \sim 300MHz \rightarrow ERP(W) = 3.83R^2 \\ 300 \sim 1500MHz \rightarrow ERP(W) = 0.0128R^2 f \\ 1500 \sim 100000MHz \rightarrow ERP(W) = 19.2R^2 \end{cases}$ <p>f is in MHz; R is in m; $R > \lambda / 2\pi$</p> |



2.3 Multiple RF Sources Exposure

| Refer Std. | Exemption Exposure Thresholds (TL) |
|----------------------|--|
| §1.1307(b)(3)(ii)(A) | <p>The available maximum time-averaged power of each source is no more than 1 mW and there is a separation distance of two centimeters between any portion of a radiating structure operating and the nearest portion of any other radiating structure in the same device, except if the sum of multiple sources is less than 1 mW during the time-averaging period, in which case they may be treated as a single source (separation is not required)</p> |
| §1.1307(b)(3)(ii)(B) | $\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{ExposureLimit_k} \leq 1$ <p>a = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(B) of this section for P_i, including existing exempt transmitters and those being added.</p> <p>b = number of fixed, mobile, or portable RF sources claiming exemption using paragraph §1.1307(b)(3)(i)(C) of this section for Threshold ERP, including existing exempt transmitters and those being added.</p> <p>c = number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance including existing evaluated transmitters.</p> <p>P_i = the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).</p> <p>P_{th,i} = the exemption threshold power (P_{th}) according to paragraph §1.1307(b)(3)(i)(B) of this section for fixed, mobile, or portable RF source i.</p> <p>ERP_j = the ERP of fixed, mobile, or portable RF source j.</p> <p>ERP_{th,j} = exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least $\lambda/2\pi$ according to the applicable formula of paragraph §1.1307(b)(3)(i)(C) of this section.</p> <p>Evaluated_k = the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation at the location of exposure.</p> <p>Evaluated Limit_k = either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable RF source k, as applicable from § 1.1310 of this chapter.</p> |



2.4 MPE Calculation Method

The MPE was calculated at 20 cm to show compliance with the power density limit.
The following formula was used to calculate the Power Density:

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$



2.5 Calculated Result and Limit

Exposure Environment: General Population / Uncontrolled Exposure

| Mode | DG (dBi) | Power (dBm) | ERP (dBm) | Tolerance (dB) | Tune-up ERP (mW) | Distance (cm) | Option | TL ERP (mW) | TL Ratio |
|----------|----------|-------------|-----------|----------------|------------------|---------------|--------|-------------|----------|
| 5.8G;D1D | 3.99 | 29.57 | 31.41 | 0.50 | 1552.387 | 20 | B | 3060.0 | 0.5075 |
| 5.6G;D1D | 3.99 | 23.59 | 25.43 | 0.50 | 391.742 | 20 | B | 3060.0 | 0.1281 |

Note 1: Option A, B and C refer as clause 2.2

Note 2: For option B, Pth(mW) convert to TL ERP(mW); For option C, ERP(W) convert to TL ERP(mW)

Note 3: TL Ratio=Tune-up ERP(mW)/TL ERP(mW)

—————THE END—————