

Test Engineer:	osolemio Chang and Luffy Lin	Temperature:	21~25	°C
Test Date:	2016/01/23 ~ 2016/02/03	Relative Humidity:	58~61	%

TEST RESULTS DATA
Peak Output Power

2.4GHz Band																
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	2	1	2412	26.67	25.92	29.32	30.00		3.52		32.84		36.00		Pass
11b	1Mbps	2	6	2437	26.21	25.78	29.01	30.00		3.52		32.53		36.00		Pass
11b	1Mbps	2	11	2462	26.07	25.82	28.96	30.00		3.52		32.48		36.00		Pass
11g	6Mbps	2	1	2412	26.79	26.72	29.77	30.00		3.52		33.29		36.00		Pass
11g	6Mbps	2	6	2437	26.62	26.43	29.54	30.00		3.52		33.06		36.00		Pass
11g	6Mbps	2	11	2462	26.39	26.47	29.44	30.00		3.52		32.96		36.00		Pass
HT20	MCS0	2	1	2412	25.83	25.57	28.71	30.00		3.52		32.23		36.00		Pass
HT20	MCS0	2	6	2437	26.90	26.74	29.83	30.00		3.52		33.35		36.00		Pass
HT20	MCS0	2	11	2462	26.38	26.26	29.33	30.00		3.52		32.85		36.00		Pass
HT40	MCS0	2	3	2422	23.46	24.22	26.87	30.00		3.52		30.39		36.00		Pass
HT40	MCS0	2	6	2437	25.85	25.72	28.80	30.00		3.52		32.32		36.00		Pass
HT40	MCS0	2	9	2452	24.81	25.33	28.09	30.00		3.52		31.61		36.00		Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band										
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2		
11b	1Mbps	2	1	2412	12.00	12.05	7.08	7.08	0.50	Pass
11b	1Mbps	2	6	2437	11.95	11.90	7.08	7.08	0.50	Pass
11b	1Mbps	2	11	2462	11.80	11.80	7.08	7.08	0.50	Pass
11g	6Mbps	2	1	2412	18.20	18.80	16.44	16.36	0.50	Pass
11g	6Mbps	2	6	2437	18.25	18.50	16.40	16.36	0.50	Pass
11g	6Mbps	2	11	2462	18.00	18.45	16.34	16.32	0.50	Pass
HT20	MCS0	2	1	2412	19.05	19.25	17.56	17.56	0.50	Pass
HT20	MCS0	2	6	2437	19.55	19.65	17.64	17.64	0.50	Pass
HT20	MCS0	2	11	2462	19.15	19.35	17.56	17.58	0.50	Pass
HT40	MCS0	2	3	2422	37.00	37.00	36.28	36.32	0.50	Pass
HT40	MCS0	2	6	2437	37.20	37.20	36.32	36.32	0.50	Pass
HT40	MCS0	2	9	2452	37.20	37.10	36.32	36.16	0.50	Pass

TEST RESULTS DATA
Average Output Power

2.4GHz Band									
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)		
					Ant 1	Ant 2	Ant 1	Ant 2	SUM
11b	1Mbps	2	1	2412	0.00	0.00	23.37	23.08	26.24
11b	1Mbps	2	6	2437	0.00	0.00	23.15	22.83	26.00
11b	1Mbps	2	11	2462	0.00	0.00	23.08	22.81	25.96
11g	6Mbps	2	1	2412	0.14	0.14	17.40	17.21	20.31
11g	6Mbps	2	6	2437	0.14	0.14	17.33	16.83	20.09
11g	6Mbps	2	11	2462	0.14	0.14	16.52	16.47	19.50
HT20	MCS0	2	1	2412	0.14	0.15	15.66	15.60	18.64
HT20	MCS0	2	6	2437	0.14	0.15	17.68	17.38	20.54
HT20	MCS0	2	11	2462	0.14	0.15	16.37	16.04	19.22
HT40	MCS0	2	3	2422	0.18	0.23	12.69	13.45	16.10
HT40	MCS0	2	6	2437	0.18	0.23	16.13	15.94	19.05
HT40	MCS0	2	9	2452	0.18	0.23	14.54	15.15	17.87

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band												
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant 1	Ant 2	Worse + 3.01	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	2	1	2412	1.29	1.32	4.33	6.35		7.65		Pass
11b	1Mbps	2	6	2437	1.13	1.48	4.49	6.35		7.65		Pass
11b	1Mbps	2	11	2462	0.69	1.44	4.45	6.35		7.65		Pass
11g	6Mbps	2	1	2412	-8.70	-7.41	-4.40	6.35		7.65		Pass
11g	6Mbps	2	6	2437	-8.16	-8.06	-5.05	6.35		7.65		Pass
11g	6Mbps	2	11	2462	-7.95	-8.06	-4.94	6.35		7.65		Pass
HT20	MCS0	2	1	2412	-9.52	-9.92	-6.51	6.35		7.65		Pass
HT20	MCS0	2	6	2437	-8.56	-9.31	-5.55	6.35		7.65		Pass
HT20	MCS0	2	11	2462	-9.09	-9.22	-6.08	6.35		7.65		Pass
HT40	MCS0	2	3	2422	-16.09	-14.53	-11.52	6.35		7.65		Pass
HT40	MCS0	2	6	2437	-9.30	-12.72	-6.29	6.35		7.65		Pass
HT40	MCS0	2	9	2452	-13.77	-12.37	-9.36	6.35		7.65		Pass

Measured power density (dBm) has offset with cable loss.