

FCC RADIO TEST REPORT

Applicant's company	Accton Technology Corporation
Applicant Address	No. 1 Creation Rd., III, Science-based Industrial Park, Hsinchu 300, Taiwan, R.O.C.
FCC ID	HED2555WAG2
Manufacturer's company	Accton Technology Corporation
Manufacturer Address	No. 1 Creation Rd., III, Science-based Industrial Park, Hsinchu 300, Taiwan, R.O.C.

Product Name	Dual Band Access Point
Brand Name	Motorola
Model Name	AirDefense Model 520
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Received Date	Jan. 04, 2006
Final Test Date	Mar. 31, 2009
Submission Type	Class II Change



Statement

Test result included is only for the 802.11b/g part and 802.11a (5725 ~ 5850MHz) of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.

Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details.....	3
3.2. Accessories.....	3
3.3. Table for Filed Antenna.....	3
3.4. Table for Carrier Frequencies	4
3.5. Table for Test Modes	5
3.6. Table for Testing Locations.....	5
3.7. Table for Supporting Units	5
3.8. Table for Parameters of Test Software Setting	6
3.9. Test Configurations	7
4. TEST RESULT	10
4.1. AC Power Line Conducted Emissions Measurement.....	10
4.2. Maximum Conducted Output Power Measurement.....	14
4.3. Power Spectral Density Measurement	16
4.4. 6dB Spectrum Bandwidth Measurement	24
4.5. Radiated Emissions Measurement	32
4.6. Band Edge Emissions Measurement	62
4.7. Antenna Requirements	71
5. LIST OF MEASURING EQUIPMENTS	72
6. TEST LOCATION.....	74
7. TAF CERTIFICATE OF ACCREDITATION	75
APPENDIX A. PHOTOGRAPHS OF EUT.....	A1 ~ A18
APPENDIX B. TEST PHOTOS.....	B1 ~ B5
APPENDIX C. MAXIMUM PERMISSIBLE EXPOSURE.....	C1 ~ C3

History of This Test Report

Original Issue Date: Apr. 14, 2009

Report No.: FR610403-05AB

- ☒ No additional attachment.
- ☐ Additional attachment were issued as following record:

Attachment No.	Issue Date	Description



1. CERTIFICATE OF COMPLIANCE

Product Name : Dual Band Access Point
Brand Name : Motorola
Model Name : AirDefense Model 520
Applicant : Accton Technology Corporation
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Jan. 04, 2006 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.


Wayne Hsu
SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	14.51 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	5.50 dB
4.3	15.247(e)	Power Spectral Density	Complies	13.49 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.95 dB
4.6	15.247(d)	Band Edge Emissions	Complies	0.15 dB
4.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

Items	Description
Power Type	From Power Adapter
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11a/g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54/108)
Frequency Range	2400 ~ 2483.5MHz / 5725 ~ 5850MHz
Channel Number	11b/g: 11 ; 11a: 7
Channel Band Width (99%)	11b: 15.64 MHz ; 11g: 16.52 MHz ; 11a: 16.56 MHz ; 11g Turbo: 32.96 MHz ; 11a Turbo: 32.88 MHz
Conducted Output Power	11b: 19.50 dBm ; 11g: 23.30 dBm ; 11a: 24.50 dBm ; 11g Turbo: 22.70 dBm ; 11a Turbo: 23.87 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

3.2. Accessories

Power	Brand	Model	Rating
Adapter	Leader	NU20-8050300-11	Input: 100-240V, 50/60Hz, 1A Output: 5V, 3.0A

3.3. Table for Filed Antenna

For 2.4GHz Band

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	-	-	Dipole Antenna	Reversed-SMA	2.00

For 5GHz Band

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	-	-	Dipole Antenna	Reversed-SMA	5.00

3.4. Table for Carrier Frequencies

Frequency Allocation for 802.11b/g

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz		

Frequency Allocation for 802.11a

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz	149	5745 MHz	165	5825 MHz
	153	5765 MHz	Turbo 152	5760 MHz
	157	5785 MHz	Turbo 160	5800 MHz
	161	5805 MHz		

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Antenna
AC Power Line Conducted Emissions	Normal Link	Auto	-	-
Max. Peak Conducted Output Power Power Spectral Density 6dB Spectrum Bandwidth	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
	11g/BPSK Turbo	12 Mbps	6	1
	11a/BPSK	6 Mbps	149/157/165	1
	11a/BPSK Turbo	12 Mbps	152/160	1
Radiated Emissions Below 1GHz	Normal Link	Auto	-	-
Radiated Emissions Above 1GHz	11b/CCK	1 Mbps	1/6/11	1
	11g/BPSK	6 Mbps	1/6/11	1
	11g/BPSK Turbo	12 Mbps	6	1
	11a/BPSK	6 Mbps	149/157/165	1
	11a/BPSK Turbo	12 Mbps	152/160	1
Band Edge Emissions	11b/CCK	1 Mbps	1/11	1
	11g/BPSK	6 Mbps	1/11	1
	11g/BPSK Turbo	12 Mbps	6	1
	11a/BPSK	6 Mbps	149/165	1
	11a/BPSK Turbo	12 Mbps	152/160	1

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
CO04-HY	Conduction	Hwa Ya	-	-	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	D520	E2KWM3945ABG
Notebook	DELL	D400	E2K24GBRL

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11b/g

Test Software Version	ART		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	19	20	20
IEEE 802.11g	17	20	19
IEEE 802.11g Turbo	-	19	-

Power Parameters of IEEE 802.11a

Test Software Version	ART		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	22	22	21
Frequency	5760 MHz	5800 MHz	-
IEEE 802.11a Turbo	21	21	-


During the test, the following programs under WIN XP were executed:

At the same time, " ART " was executed to control the EUT continuously transmit RF signal.


3.9. Test Configurations

3.9.1. Radiation Emissions Test Configuration


Test Configuration: 9kHz~1GHz



Test Configuration: Above 1GHz



3.9.2. AC Power Line Conduction Emissions Test Configuration



4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

[illegible]


- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

There is no deviation with the original standard.

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	23°C	Humidity	51%
Test Engineer	Howar Sung	Phase	Line
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.18838	46.83	-17.27	64.11	46.58	0.05	0.20	QP
2	0.18838	33.67	-20.43	54.11	33.42	0.05	0.20	AVERAGE
3	0.25211	40.90	-20.78	61.69	40.66	0.04	0.20	QP
4	0.25211	29.55	-22.13	51.69	29.31	0.04	0.20	AVERAGE
5	3.081	29.11	-26.89	56.00	28.81	0.08	0.22	QP
6	3.081	21.48	-24.52	46.00	21.18	0.08	0.22	AVERAGE
7	9.809	28.56	-31.44	60.00	27.92	0.34	0.30	QP
8	9.809	18.79	-31.21	50.00	18.15	0.34	0.30	AVERAGE
9	19.708	37.83	-22.17	60.00	36.52	0.81	0.50	QP
10	19.708	35.00	-15.00	50.00	33.69	0.81	0.50	AVERAGE
11	22.457	35.49	-14.51	50.00	34.00	0.99	0.50	AVERAGE
12	22.457	37.44	-22.56	60.00	35.95	0.99	0.50	QP
13	28.750	28.50	-21.50	50.00	26.53	1.37	0.60	AVERAGE
14	28.750	33.35	-26.65	60.00	31.38	1.37	0.60	QP

Temperature	23°C	Humidity	51%
Test Engineer	Howar Sung	Phase	Neutral
Configuration	Normal Link		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.18938	46.47	-17.59	64.06	46.19	0.08	0.20	QP
2	0.18938	33.47	-20.59	54.06	33.19	0.08	0.20	AVERAGE
3	0.25211	40.55	-21.14	61.69	40.27	0.08	0.20	QP
4	0.25211	29.10	-22.59	51.69	28.82	0.08	0.20	AVERAGE
5	3.207	29.76	-26.24	56.00	29.39	0.12	0.24	QP
6	3.207	18.24	-27.76	46.00	17.87	0.12	0.24	AVERAGE
7	3.522	20.97	-25.03	46.00	20.54	0.13	0.30	AVERAGE
8	3.522	31.02	-24.98	56.00	30.59	0.13	0.30	QP
9	9.449	28.37	-31.63	60.00	27.70	0.37	0.30	QP
10	9.449	20.01	-29.99	50.00	19.34	0.37	0.30	AVERAGE
11	19.710	35.28	-14.72	50.00	33.99	0.79	0.50	AVERAGE
12	19.710	38.62	-21.38	60.00	37.33	0.79	0.50	QP
13	28.749	33.75	-26.25	60.00	31.74	1.41	0.60	QP
14	28.749	28.80	-21.20	50.00	26.79	1.41	0.60	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limit has to be reduced by the amount in dB that the gain of the antenna exceeds 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi. Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter conducted output power.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1MHz
VB	3MHz
Detector	RMS
Trace	Max Hold
Sweep Time	Auto

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. Test was performed in accordance with Measurement of Digital Transmission Systems Operating under Section 15.247 March 23, 2005.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	20°C	Humidity	61%
Test Engineer	Steven Lu	Configurations	802.11a/b/g

Configuration IEEE 802.11b

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	18.20	30.00	Complies
6	2437 MHz	19.50	30.00	Complies
11	2462 MHz	19.50	30.00	Complies

Configuration IEEE 802.11g

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	21.20	30.00	Complies
6	2437 MHz	23.30	30.00	Complies
11	2462 MHz	22.60	30.00	Complies

Configuration IEEE 802.11g Turbo

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
6	2437 MHz	22.70	30.00	Complies

Configuration IEEE 802.11a

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	24.50	30.00	Complies
157	5785 MHz	24.40	30.00	Complies
165	5825 MHz	23.96	30.00	Complies

Configuration IEEE 802.11a Turbo

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
152	5760 MHz	23.73	30.00	Complies
160	5800 MHz	23.87	30.00	Complies

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	30kHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	10s

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 30kHz and the sweep time to 10s and record the maximum peak value.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	20°C	Humidity	61%
Test Engineer	Steven Lu	Configurations	802.11a/b/g

Configuration IEEE 802.11b

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-8.07	8.00	Complies
6	2437 MHz	-6.98	8.00	Complies
11	2462 MHz	-6.16	8.00	Complies

Configuration IEEE 802.11g

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-11.02	8.00	Complies
6	2437 MHz	-8.50	8.00	Complies
11	2462 MHz	-9.40	8.00	Complies

Configuration IEEE 802.11g Turbo

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
6	2437 MHz	-10.43	8.00	Complies


Configuration IEEE 802.11a

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
149	5745 MHz	-5.49	8.00	Complies
157	5785 MHz	-6.04	8.00	Complies
165	5825 MHz	-6.17	8.00	Complies

Configuration IEEE 802.11a Turbo


Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
152	5760 MHz	-9.01	8.00	Complies
160	5800 MHz	-9.05	8.00	Complies

Power Density Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 11.JAN.2006 22:30:58

Power Density Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 11.JAN.2006 22:29:18

Power Density Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 11.JAN.2006 22:28:36

Power Density Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 23.JAN.2006 17:46:51

Power Density Plot on Configuration IEEE 802.11g / 2437 MHz




Date: 11.JAN.2006 22:25:04

Power Density Plot on Configuration IEEE 802.11g / 2462 MHz




Date: 11.JAN.2006 22:25:45

Power Density Plot on Configuration IEEE 802.11g Turbo / 2437 MHz




Date: 11.JAN.2006 22:34:51

Power Density Plot on Configuration IEEE 802.11a / 5745 MHz




Date: 20.JAN.2006 00:08:48

Power Density Plot on Configuration IEEE 802.11a / 5785 MHz




Date: 20.JAN.2006 00:07:33

Power Density Plot on Configuration IEEE 802.11a / 5825 MHz




Date: 20.JAN.2006 00:06:34

Power Density Plot on Configuration IEEE 802.11a Turbo / 5760 MHz



Date: 20.JAN.2006 00:17:28

Power Density Plot on Configuration IEEE 802.11a Turbo / 5800 MHz



Date: 20.JAN.2006 00:18:36

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	20°C	Humidity	61%
Test Engineer	Steven Lu	Configurations	802.11a/b/g

Configuration IEEE 802.11b

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	12.00	15.56	500	Complies
6	2437 MHz	12.00	15.64	500	Complies
11	2462 MHz	12.04	15.56	500	Complies

Configuration IEEE 802.11g

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	16.40	16.52	500	Complies
6	2437 MHz	16.40	16.52	500	Complies
11	2462 MHz	16.40	16.48	500	Complies

Configuration IEEE 802.11g Turbo

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
6	2437 MHz	32.00	32.96	500	Complies


Configuration IEEE 802.11a

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.48	16.56	500	Complies
157	5785 MHz	16.44	16.56	500	Complies
165	5825 MHz	16.40	16.56	500	Complies

Configuration IEEE 802.11a Turbo


Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
152	5760 MHz	32.64	32.88	500	Complies
160	5800 MHz	32.64	32.88	500	Complies

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 11.JAN.2006 22:30:34

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz




Date: 11.JAN.2006 22:29:02

6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 11.JAN.2006 22:28:21

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 23.JAN.2006 17:46:26

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz




Date: 11.JAN.2006 22:24:48

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2462 MHz




Date: 11.JAN.2006 22:25:30

6 dB Bandwidth Plot on Configuration IEEE 802.11g Turbo / 2437 MHz




Date: 11.JAN.2006 22:34:35

6 dB Bandwidth Plot on Configuration IEEE 802.11a / 5745 MHz




Date: 20.JAN.2006 00:03:21

6 dB Bandwidth Plot on Configuration IEEE 802.11a / 5785 MHz




Date: 20.JAN.2006 00:04:22

6 dB Bandwidth Plot on Configuration IEEE 802.11a / 5825 MHz




Date: 20.JAN.2006 00:05:18

6 dB Bandwidth Plot on Configuration IEEE 802.11a Turbo / 5760 MHz



Date: 20.JAN.2006 00:20:25

6 dB Bandwidth Plot on Configuration IEEE 802.11a Turbo / 5800 MHz



Date: 20.JAN.2006 00:19:34

4.5. Radiated Emissions Measurement

4.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 3MHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1.5m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	26°C	Humidity	56%
Test Engineer	Johnson Chang		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	26°C	Humidity	56%
Test Engineer	Johnson Chang	Configurations	Normal Link

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna	Preamp	Cable	Remark	Pol/Phase	Table Pos	Ant Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB			deg	cm
1	40.670	25.48	-14.52	40.00	40.02	12.55	27.80	0.70 Peak	HORIZONTAL	0	100
2	159.980	29.06	-14.44	43.50	42.83	12.03	27.30	1.50 Peak	HORIZONTAL	0	100
3	198.780	28.85	-14.65	43.50	45.00	9.25	27.11	1.70 Peak	HORIZONTAL	0	100
4	319.060	31.24	-14.76	46.00	42.25	13.88	27.03	2.14 Peak	HORIZONTAL	0	100
5	439.340	39.33	-6.67	46.00	47.91	16.68	27.80	2.54 Peak	HORIZONTAL	0	100
6	770.110	36.54	-9.46	46.00	41.27	19.57	27.72	3.42 Peak	HORIZONTAL	0	100
7	917.550	31.93	-14.07	46.00	34.99	20.66	27.33	3.60 Peak	HORIZONTAL	0	100

Vertical



	Freq	Level	Over	Limit	Read	Antenna	Preamp	Cable		Table	Ant
	MHz	dBuV/m	Limit	Line	Level	Factor	Factor	Loss	Remark	Pos	Pos
			dB	dBuV/m	dBuV	dB/m	dB	dB		deg	cm
1	32.910	35.79	-4.21	40.00	45.94	17.15	27.80	0.50	Peak	0	400
2	43.640	38.25	-1.75	40.00	52.80	12.55	27.80	0.70	QP	189	100
3	51.340	39.05	-0.95	40.00	57.77	8.35	27.79	0.72	QP	188	100
4	59.100	32.94	-7.06	40.00	52.96	6.95	27.76	0.80	QP	187	100
5	153.190	36.51	-6.99	43.50	50.47	11.90	27.33	1.47	Peak	0	400
6	295.780	26.00	-20.00	46.00	37.52	13.31	26.91	2.08	Peak	0	400
7	439.340	35.20	-10.80	46.00	43.78	16.68	27.80	2.54	Peak	0	400
8	770.110	37.94	-8.06	46.00	42.67	19.57	27.72	3.42	Peak	0	400
9	904.940	36.86	-9.14	46.00	40.07	20.57	27.38	3.60	Peak	0	400

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)


Temperature	22°C	Humidity	64%
Test Engineer	Rush Kao	Configurations	802.11b Channel 1

Horizontal



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1	4824.000	31.41	-22.59	54.00	33.22	4.68	35.10	28.61	AVERAGE	100	0
2	4824.000	42.15	-31.85	74.00	33.22	4.68	35.10	39.36	PEAK	100	0


Vertical



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBUV/m	dB	dBUV/m	dB/m	dB	dB	dBUV		cm	deg
1	4824.000	31.41	-22.59	54.00	33.22	4.68	35.10	28.62	AVERAGE	100	0
2	4824.000	42.69	-31.31	74.00	33.22	4.68	35.10	39.90	PEAK	100	0


Temperature	22°C	Humidity	64%
Test Engineer	Rush Kao	Configurations	802.11b Channel 6

Horizontal



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1	4878.360	31.89	-22.11	54.00	33.33	4.69	35.10	28.96	AVERAGE	126	0
2	4878.360	43.00	-31.00	74.00	33.33	4.69	35.10	40.08	PEAK	126	0


Vertical



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1	4874.000	32.76	-21.24	54.00	33.33	4.69	35.10	29.83	AVERAGE	126	360
2	4874.000	42.51	-31.49	74.00	33.33	4.69	35.10	39.58	PEAK	126	360


Temperature	22°C	Humidity	64%
Test Engineer	Rush Kao	Configurations	802.11b Channel 11

Horizontal



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1	4924.660	31.37	-22.63	54.00	33.45	4.73	35.10	28.29	AVERAGE	105	13
2	4924.660	41.83	-32.17	74.00	33.45	4.73	35.10	38.76	PEAK	105	13


Vertical



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1 @	4923.980	34.34	-19.66	54.00	33.45	4.73	35.10	31.27	AVERAGE	105	5
2	4923.980	43.98	-30.02	74.00	33.45	4.73	35.10	40.91	PEAK	105	5


Temperature	22°C	Humidity	64%
Test Engineer	Rush Kao	Configurations	802.11g Channel 1

Horizontal



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1	4816.640	31.52	-22.48	54.00	33.22	4.68	35.10	28.72	AVERAGE	100	360
2	4816.640	42.97	-31.03	74.00	33.22	4.68	35.10	40.17	PEAK	100	360


Vertical



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1	4817.240	31.75	-22.25	54.00	33.22	4.68	35.10	28.96	AVERAGE	100	0
2	4817.240	41.90	-32.10	74.00	33.22	4.68	35.10	39.10	PEAK	100	0


Temperature	22°C	Humidity	64%
Test Engineer	Rush Kao	Configurations	802.11g Channel 6

Horizontal



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1	4922.000	30.40	-23.60	54.00	33.45	4.73	35.10	27.33	AVERAGE	100	0
2	4922.000	41.40	-32.60	74.00	33.45	4.73	35.10	38.33	PEAK	100	0


Vertical



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1	4930.680	31.31	-22.69	54.00	33.45	4.73	35.10	28.24	AVERAGE	100	0
2	4930.680	41.42	-32.58	74.00	33.45	4.73	35.10	38.34	PEAK	100	0


Temperature	22°C	Humidity	64%
Test Engineer	Rush Kao	Configurations	802.11g Channel 11

Horizontal



	Freq	Level	Over Limit	Antenna Line	Antenna Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1	4922.000	30.51	-23.49	54.00	33.45	4.73	35.10	27.44	AVERAGE	100	0
2	4922.000	41.72	-32.28	74.00	33.45	4.73	35.10	38.65	PEAK	100	0


Vertical



	Freq	Level	Over Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV	cm	deg
1	4922.000	30.57	-23.43	54.00	33.45	4.73	35.10	27.50 AVERAGE	100	0
2	4922.000	42.05	-31.95	74.00	33.45	4.73	35.10	38.98 PEAK	100	0


Temperature	22°C	Humidity	64%
Test Engineer	Rush Kao	Configurations	802.11g Turbo Channel 6

Horizontal



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1	4879.520	31.52	-22.48	54.00	33.33	4.69	35.10	28.59	AVERAGE	100	0
2	4879.520	41.99	-32.01	74.00	33.33	4.69	35.10	39.07	PEAK	100	0

Vertical



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1	4879.800	31.58	-22.42	54.00	33.33	4.69	35.10	28.65	AVERAGE	100	0
2	4879.800	42.61	-31.39	74.00	33.33	4.69	35.10	39.68	PEAK	100	0

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Pol. : V is Vertical Polarization ; H is Horizontal Polarization.


Temperature	22°C	Humidity	64%
Test Engineer	Rush Kao	Configurations	802.11a Channel 149

Horizontal



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1 @	11488.720	48.97	-11.03	60.00	39.20	6.96	35.10	37.91	AVERAGE	124	41
2 @	11488.720	59.54	-20.46	80.00	39.20	6.96	35.10	48.48	PEAK	124	41


Vertical



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1 @	11486.960	47.91	-12.09	60.00	39.20	6.96	35.10	36.85	AVERAGE	102	138
2	11486.960	58.34	-21.66	80.00	39.20	6.96	35.10	47.28	PEAK	102	138


Temperature	22°C	Humidity	64%
Test Engineer	Rush Kao	Configurations	802.11a Channel 157

Horizontal



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1 @	11569.660	44.11	-15.89	60.00	39.21	7.06	35.12	32.97	AVERAGE	100	290
2	11569.660	54.14	-25.86	80.00	39.21	7.06	35.12	42.99	PEAK	100	290


Vertical



	Freq	Level	Over Limit	Antenna Line	Antenna Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1 @	11569.660	44.40	-15.60	60.00	39.21	7.06	35.12	33.25	AVERAGE	101	140
2	11569.660	55.16	-24.84	80.00	39.21	7.06	35.12	44.01	PEAK	101	140


Temperature	22°C	Humidity	64%
Test Engineer	Rush Kao	Configurations	802.11a Channel 165

Horizontal



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1 @	11650.400	43.29	-16.71	60.00	39.23	7.15	35.16	32.07	AVERAGE	101	290
2	11650.400	54.64	-25.36	80.00	39.23	7.15	35.16	43.43	PEAK	101	290


Vertical



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1 @	11650.400	43.52	-16.48	60.00	39.23	7.15	35.16	32.31	AVERAGE	101	150
2	11650.400	54.01	-25.99	80.00	39.23	7.15	35.16	42.79	PEAK	101	150


Temperature	22°C	Humidity	64%
Test Engineer	Rush Kao	Configurations	802.11a Turbo Channel 152

Horizontal



	Freq	Level	Over Limit	Antenna Line	Antenna Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1 @	11521.400	42.59	-17.41	60.00	39.20	7.01	35.11	31.49	AVERAGE	118	351
2	11521.400	53.98	-26.02	80.00	39.20	7.01	35.11	42.88	PEAK	118	351


Vertical



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1 @	11521.280	43.05	-16.95	60.00	39.20	7.01	35.11	31.95	AVERAGE	102	132
2	11521.280	55.38	-24.62	80.00	39.20	7.01	35.11	44.28	PEAK	102	132


Temperature	22°C	Humidity	64%
Test Engineer	Rush Kao	Configurations	802.11a Turbo Channel 160

Horizontal



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1 @	11598.840	40.85	-19.15	60.00	39.22	7.10	35.14	29.67	AVERAGE	116	302
2	11598.840	51.95	-28.05	80.00	39.22	7.10	35.14	40.77	PEAK	116	302

Vertical



	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1 @	11596.200	41.95	-18.05	60.00	39.22	7.10	35.14	30.77	AVERAGE	107	336
2	11596.200	53.34	-26.66	80.00	39.22	7.10	35.14	42.16	PEAK	107	336

Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Pol. : V is Vertical Polarization ; H is Horizontal Polarization.

4.6. Band Edge Emissions Measurement

4.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1 MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

4.6.3. Test Procedures

1. The test procedure is the same as section 4.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	22°C	Humidity	64%
Test Engineer	Rush Kao	Configurations	802.11b Channel 1, 11

Channel 1

	Freq	Level	Over Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV	cm	deg
1 @	2386.400	60.47	-13.53	74.00	28.13	2.58	0.00	29.76	100	242
2 @	2386.400	53.73	-0.27	54.00	28.13	2.58	0.00	23.02	100	242
3 @	2413.200	108.62			28.18	2.58	0.00	77.87	100	242
4 @	2414.700	104.87			28.18	2.58	0.00	74.12	---	---

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 11

	Freq	Level	Over Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV	cm	deg
1 @	2459.400	105.81			28.31	2.60	0.00	74.90	---	---
2 @	2460.600	109.40			28.31	2.60	0.00	78.49	101	74
3 @	2487.700	59.41	-14.59	74.00	28.40	2.62	0.00	28.39	101	74
4 @	2487.700	51.96	-2.04	54.00	28.40	2.62	0.00	20.94	101	74

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	22°C	Humidity	64%
Test Engineer	Rush Kao	Configurations	802.11g Channel 1, 11

Channel 1

	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1 !	2390.000	72.68	-1.32	74.00	28.13	2.58	0.00	41.98	PEAK	100	100
2 !	2390.000	53.23	-0.77	54.00	28.13	2.58	0.00	22.52	AVERAGE	100	100
3 @	2414.700	98.67			28.18	2.58	0.00	67.91	Average	---	---
4 over	2414.800	108.26			28.18	2.58	0.00	77.51	PEAK	100	100

Item 3, 4 are the fundamental frequency at 2412 MHz.

Channel 11

	Freq	Level	Over Limit	Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV		cm	deg
1 @	2460.600	101.06			28.31	2.60	0.00	70.15	Average	---	---
2 @	2464.800	111.21			28.31	2.62	0.00	80.28	PEAK	108	236
3 @	2483.500	67.42	-6.58	74.00	28.36	2.62	0.00	36.44	PEAK	108	236
4 @	2483.500	53.85	-0.15	54.00	28.36	2.62	0.00	22.88	AVERAGE	108	236

Item 1, 2 are the fundamental frequency at 2462 MHz.

Temperature	22°C	Humidity	64%
Test Engineer	Rush Kao	Configurations	802.11g Turbo Channel 6

Channel 6

	Freq	Level	Over Limit	Antenna Line Factor	Cable Loss	Preamp Factor	Read Level	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	dBuV	cm	deg
1 @	2390.000	51.99	-2.01	54.00	28.13	2.58	0.00	21.28 AVERAGE	107	237
2 @	2390.000	65.97	-8.03	74.00	28.13	2.58	0.00	35.26 PEAK	107	237
3 @	2433.800	108.06			28.22	2.60	0.00	77.25 PEAK	107	237
4 @	2446.800	98.79			28.27	2.60	0.00	67.93 Average	---	---
5 @	2483.500	67.24	-6.76	74.00	28.36	2.62	0.00	36.26 PEAK	107	237
6 @	2483.500	53.57	-0.43	54.00	28.36	2.62	0.00	22.59 AVERAGE	107	237

Item 1, 2 are the fundamental frequency at 2437 MHz.

Note:


Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Receiving maximum band edge emissions are Vertical Polarization /Horizontal Polarization.


For Emission not in Restricted Band

Low Band Edge Plot on Configuration IEEE 802.11b / 2412 MHz




Date: 11.JAN.2006 22:31:05

High Band Edge Plot on Configuration IEEE 802.11b / 2462 MHz




Date: 11.JAN.2006 22:28:43

Low Band Edge Plot on Configuration IEEE 802.11g / 2412 MHz




Date: 23.JAN.2006 17:46:58

High Band Edge Plot on Configuration IEEE 802.11g / 2462 MHz




Date: 11.JAN.2006 22:25:52

Low Band Edge Plot on Configuration IEEE 802.11g Turbo / 2437 MHz




Date: 23.JAN.2006 17:53:57

High Band Edge Plot on Configuration IEEE 802.11g Turbo/ 2437 MHz




Date: 23.JAN.2006 17:55:13

Low Band Edge Plot on Configuration IEEE 802.11a / 5745 MHz




Date: 20.JAN.2006 00:10:48

High Band Edge Plot on Configuration IEEE 802.11a / 5825 MHz




Date: 20.JAN.2006 00:11:58

Low Band Edge Plot on Configuration IEEE 802.11a Turbo / 5760 MHz



Date: 20.JAN.2006 00:16:12

High Band Edge Plot on Configuration IEEE 802.11a Turbo / 5800 MHz



Date: 20.JAN.2006 00:15:10

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Feb. 22, 2006	Conduction (CO04-HY)
EMC Receiver	R&S	ESCS 30	100174	9kHz – 2.75GHz	Apr. 16, 2008	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Dec. 19, 2005	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Mar. 31, 2008	Conduction (CO04-HY)
LISN	MessTec	NNB-2/16Z	99079	9kHz – 30MHz	Mar. 31, 2009	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9708-1839	9kHz – 30MHz	Mar. 18, 2006	Conduction (CO04-HY)
LISN (Support Unit)	EMCO	3810/2NM	9703-1839	9kHz – 30MHz	Mar. 22, 2009	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2006	Conduction (CO04-HY)
RF Cable-CON	UTIFLEX	3102-26886-4	CB049	9kHz – 30MHz	Apr. 20, 2008	Conduction (CO04-HY)
ISN	SCHAFFNER	ISN ST08	21653	9kHz – 30MHz	Mar. 27, 2008	Conduction (CO04-HY)
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	N/A	Conduction (CO04-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 15, 2006	Radiation (03CH03-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 14, 2008	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	CPA9231A	3565	9 kHz - 2 GHz	Jan. 18, 2006	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	COA9231A	18667	9 kHz - 2 GHz	Jan. 23, 2009	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	May 29, 2006	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	Jul. 21, 2008	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100004/040	9 kHz - 40 GHz	Sep. 30, 2005	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100004	9 kHz - 30 GHz	Oct. 06, 2008	Radiation (03CH03-HY)
Biconical Antenna	SCHWARZBECK	VHBB 9124	301	30 MHz - 200 MHz	Jul. 22, 2005	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz – 1 GHz	Jul. 12, 2008	Radiation (03CH03-HY)
Log Antenna	SCHWARZBECK	VUSLP 9111	221	200 MHz - 1 GHz	Jul. 22, 2005	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6903	1GHz ~ 18GHz	Mar. 15, 2006	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	Apr. 29, 2008	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	NCR	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Dec.02, 2005	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Jan. 05, 2009	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Dec.02, 2005	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Jan. 05, 2009	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 – 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Amplifier	MITEQ	AMF-6F-260400	923364	26.5 GHz - 40 GHz	Jan. 24, 2006*	Radiation (03CH03-HY)
Amplifier	MITEQ	AMF-6F-260400	9121372	26.5 GHz - 40 GHz	Jan. 22, 2009*	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	May 23, 2006*	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	Jul. 28, 2008*	Radiation (03CH03-HY)
Spectrum analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Nov. 26, 2005	Conducted (TH01-HY)
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Jan. 09, 2009	Conducted (TH01-HY)
Power meter	R&S	NRVS	100444	DC ~ 40GHz	Jun. 10, 2006	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100444	DC ~ 40GHz	Jul. 11, 2008	Conducted (TH01-HY)
Power sensor	R&S	NRV-Z55	100049	DC ~ 40GHz	Jul. 05, 2006	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100458	DC ~ 30GHz	Jul. 11, 2008	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jun. 10, 2006	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jul. 11, 2008	Conducted (TH01-HY)
AC power source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Apr. 21, 2005*	Conducted (TH01-HY)
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	May 30, 2008*	Conducted (TH01-HY)
DC power source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Dec. 28, 2005	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 13, 2009	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Oct. 01, 2005	Conducted (TH01-HY)
Temp. and Humidity Chamber	Giant Force	GTH-225-20-S	MAB0103-001	N/A	Jul. 18, 2008	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 30, 2005	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 01, 2008	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 30, 2005	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 01, 2008	Conducted (TH01-HY)
Oscilloscope	Tektronix	TDS1012	CO38515	100MHz / 1GS/s	Jun. 20, 2006	Conducted (TH01-HY)
Oscilloscope	Tektronix	TDS380	B016197	400MHz/ 2GS/s	Jun. 27, 2008	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Dec. 30, 2005	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 10, 2009	Conducted (TH01-HY)
Data Generator	Tektronix	DG2030	063-2920-50	0.1Hz~400MHz	Jun. 16, 2006	Conducted (TH01-HY)
Vector Signal Generator	R&S	SMU200A	102098	100kHz ~ 6GHz	Dec. 14, 2008	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year. NCR: Non-Calibration required.

Note: Calibration Interval of instruments listed above is two year.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 728, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : LI190-070110

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2007 to January 09, 2010
Accredited Scope	: Testing Field, see described in the Appendix Accreditation Program for Designated Testing Laboratory for Commodities Inspection
Specific Accreditation Program	: Accreditation Program for Telecommunication Equipment Testing Laboratory



Jay-San Chen
President, Taiwan Accreditation Foundation
Date : January 10, 2007

PI, total 9 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when used without the Appendix.