




CHANNEL 1



CHANNEL 2



CHANNEL 3




15.57 dBm

Power

60.96 MHz

Tx Channel
Bandwidth


CHANNEL 1




FCC ID: HEDSMC2555WA



CHANNEL 2



CHANNEL 3



5.4 PEAK POWER EXCURSION MEASUREMENT

5.4.1 LIMITS OF PEAK POWER EXCURSION MEASUREMENT

| Frequency Band | Limit |
|-------------------|-------|
| 5.15 – 5.25 GHz | 13dB |
| 5.25 – 5.35 GHz | 13dB |
| 5.725 – 5.825 GHz | 13dB |

5.4.2 TEST INSTRUMENTS

| Description & Manufacturer | Model No. | Serial No. | Calibrated Until |
|----------------------------|-----------|------------|------------------|
| R&S SPECTRUM ANALYZER | FSP30 | 100019 | Dec. 19, 2003 |

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


5.4.3 TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer.
2. Set the spectrum bandwidth span to view the entire spectrum.
3. Using peak detector and Max-hold function for Trace 1 (RB=1MHz, VB=3MHz) and 2 (RB=1MHz, VB=30KHz).
4. The largest difference between Trace 1 and Trace 2 in any 1MHz band on any frequency was recorded.

5.4.4 DEVIATION FROM TEST STANDARD

No deviation

5.4.5 TEST SETUP



5.4.6 EUT OPERATING CONDITIONS


The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.

5.4.7 TEST RESULTS


| | | | |
|-------------------------------------|--|---------------------------------|---------------|
| EUT | EliteConnect Universal 2.4GHz/5GHz Wireless Access Point | MODEL | SMC2555W-AG |
| MODE | Normal | INPUT POWER (SYSTEM) | 120Vac, 60 Hz |
| ENVIRONMENTAL CONDITIONS | 21eg. C, 58RH, 974 hPa | TESTED BY | Eric Lee |

| CHANNEL | CHANNEL FREQUENCY (MHz) | PEAK POWER EXCURSION (dB) | PEAK to AVERAGE EXCURSION LIMIT (dB) | PASS/FAIL |
|----------------|--|--|---|------------------|
| 1 | 5180 | 7.74 | 13 | PASS |
| 4 | 5240 | 6.58 | 13 | PASS |
| 5 | 5260 | 8.78 | 13 | PASS |
| 8 | 5320 | 7.36 | 13 | PASS |


CHANNEL 1



CHANNEL 4




CHANNEL 5



FCC ID: HEDSMC2555WA



CHANNEL 8




Report No.: RF920725H01A
ADT No.: 921013H02


| | | | |
|-------------------------------------|--|---------------------------------|---------------|
| EUT | EliteConnect Universal 2.4GHz/5GHz Wireless Access Point | MODEL | SMC2555W-AG |
| MODE | Turbo | INPUT POWER (SYSTEM) | 120Vac, 60 Hz |
| ENVIRONMENTAL CONDITIONS | 21eg. C, 58RH, 974 hPa | TESTED BY | Eric Lee |

| CHANNEL | CHANNEL FREQUENCY (MHz) | PEAK POWER EXCURSION (dB) | PEAK to AVERAGE EXCURSION LIMIT (dB) | PASS/FAIL |
|---------|-------------------------------|---------------------------------|---|-----------|
| 1 | 5210 | 8.88 | 13 | PASS |
| 2 | 5250 | 8.73 | 13 | PASS |
| 3 | 5290 | 7.32 | 13 | PASS |


CHANNEL 1



CHANNEL 2



CHANNEL 3



5.5 PEAK POWER SPECTRAL DENSITY MEASUREMENT

5.5.1 LIMITS OF PEAK POWER SPECTRAL DENSITY MEASUREMENT

| Frequency Band | Limit |
|-------------------|-------|
| 5.15 – 5.25 GHz | 4dBm |
| 5.25 – 5.35 GHz | 11dBm |
| 5.725 – 5.825 GHz | 17dBm |

5.5.2 TEST INSTRUMENTS

| Description & Manufacturer | Model No. | Serial No. | Calibrated Until |
|----------------------------|-----------|------------|------------------|
| R&S SPECTRUM ANALYZER | FSP30 | 100019 | Dec. 19, 2003 |

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.5.3 TEST PROCEDURES

1. The transmitter output was connected to the spectrum analyzer.
2. Set RBW=1MHz, VBW=3MHz. The PPSD is the highest level found across the emission in any 1MHz band.

5.5.4 DEVIATION FROM TEST STANDARD

No deviation

5.5.5 TEST SETUP



5.5.6 EUT OPERATING CONDITIONS


Same as 5.3.6

5.5.7 TEST RESULTS


| | | | |
|-------------------------------------|--|---------------------------------|-----------------|
| EUT | EliteConnect Universal 2.4GHz/5GHz Wireless Access Point | MODEL | SMC2555W- AG |
| MODE | Normal | INPUT POWER (SYSTEM) | 120Vac, 60 Hz |
| ENVIRONMENTAL CONDITIONS | 21eg. C, 58RH, 974 hPa | TESTED BY | Eric Lee |

| CHANNEL NUMBER | CHANNEL FREQUENCY (MHz) | RF POWER LEVEL IN 1 MHz BW (dBm) | MAXIMUM LIMIT (dBm) | PASS/FAIL |
|-------------------|--------------------------------|--|---------------------------|-----------|
| 1 | 5180 | -1.12 | 4 | PASS |
| 4 | 5240 | -0.84 | 4 | PASS |
| 5 | 5260 | 3.93 | 11 | PASS |
| 8 | 5320 | -0.23 | 11 | PASS |


CHANNEL 1



CHANNEL 4




CHANNEL 5



FCC ID: HEDSMC2555WA




CHANNEL 8



| | | | |
|-------------------------------------|--|---------------------------------|---------------|
| EUT | EliteConnect Universal 2.4GHz/5GHz Wireless Access Point | MODEL | SMC2555W-AG |
| MODE | Turbo | INPUT POWER (SYSTEM) | 120Vac, 60 Hz |
| ENVIRONMENTAL CONDITIONS | 21eg. C, 58RH, 974 hPa | TESTED BY | Eric Lee |

| CHANNEL NUMBER | CHANNEL FREQUENCY (MHz) | RF POWER LEVEL IN 1 MHz BW (dBm) | MAXIMUM LIMIT (dBm) | PASS/FAIL |
|-------------------|--------------------------------|--|---------------------------|-----------|
| 1 | 5210 | -4.93 | 4 | PASS |
| 2 | 5250 | -3.70 | 4 | PASS |
| 3 | 5290 | -3.81 | 11 | PASS |


CHANNEL 1




FCC ID: HEDSMC2555WA



CHANNEL 2



CHANNEL 3



5.6 FREQUENCY STABILITY

5.6.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT

The frequency tolerance of the carrier signal shall be maintained within +/- 0.02% of the operating frequency over a temperature variation of -30 degrees to 50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C.

5.6.2 TEST INSTRUMENTS

| Description & Manufacturer | Model No. | Serial No. | Calibrated Until |
|----------------------------|-----------|------------|------------------|
| R&S SPECTRUM ANALYZER | FSP30 | 100019 | Dec. 19, 2003 |

NOTE:

The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.


5.6.3 TEST PROCEDURE

1. The EUT was placed inside the environmental test chamber and powered by nominal AC voltage.
2. Turn the EUT on and couple its output to a spectrum analyzer.
3. Turn the EUT off and set the chamber to the highest temperature specified.
4. Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
5. Repeat step 2 and 3 with the temperature chamber set to the lowest temperature.
6. The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

5.6.4 DEVIATION FROM TEST STANDARD

No deviation

5.6.5 TEST SETUP



5.6.6 EUT OPERATING CONDITION

Same as Item 4.1.6