



## FCC 47 CFR PART 15 SUBPART C

### TEST REPORT

For

**Accton Technology Corporation**

**WLAN 11a+b/g Access Point**

**Model: WA6102X, WA6102Y, SS-200-AT**

**Trade Name: Accton, AirTight Networks**

*Prepared for*

**Accton Technology Corporation  
1 Creation 3rd Rd., Science-based Industrial Park,  
Hsinchu 300, Taiwan, R.O.C.**

*Prepared by*

**Compliance Certification Services Inc.  
No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang,  
Taoyuan Hsien, (338) Taiwan, R.O.C.  
TEL: 886-3-324-0332  
FAX: 886-3-324-5235**



---

**Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.

**TABLE OF CONTENTS**

<b>1. TEST RESULT CERTIFICATION.....</b>	<b>3</b>
<b>2. EUT DESCRIPTION .....</b>	<b>4</b>
<b>3. TEST METHODOLOGY .....</b>	<b>5</b>
3.1 EUT CONFIGURATION .....	5
3.2 EUT EXERCISE.....	5
3.3 GENERAL TEST PROCEDURES.....	5
3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS.....	6
3.5 DESCRIPTION OF TEST MODES .....	6
<b>4. INSTRUMENT CALIBRATION.....</b>	<b>7</b>
<b>5. FACILITIES AND ACCREDITATIONS .....</b>	<b>8</b>
5.1 FACILITIES.....	8
5.2 EQUIPMENT.....	8
5.3 LABORATORY ACCREDITATIONS AND LISTING.....	8
5.4 TABLE OF ACCREDITATIONS AND LISTINGS.....	9
<b>6. SETUP OF EQUIPMENT UNDER TEST .....</b>	<b>10</b>
6.1 SETUP CONFIGURATION OF EUT.....	10
6.2 SUPPORT EQUIPMENT .....	10
<b>7. FCC PART 15.247 REQUIREMENTS.....</b>	<b>11</b>
7.1 6DB BANDWIDTH.....	11
7.2 PEAK POWER.....	20
7.3 BAND EDGES MEASUREMENT.....	54
7.4 PEAK POWER SPECTRAL DENSITY.....	67
7.5 RADIO FREQUENCY EXPOSURE .....	85
7.6 SPURIOUS EMISSIONS .....	87
7.7 POWERLINE CONDUCTED EMISSIONS.....	128
<b>APPENDIX 1 PHOTOGRPHS OF TEST SETUP .....</b>	<b>131</b>



## 1. TEST RESULT CERTIFICATION

**Applicant:** Aceton Technology Corporation  
1 Creation 3rd Rd., Science-based Industrial Park,  
Hsinchu 300, Taiwan, R.O.C.

**Equipment Under Test:** WLAN 11a+b/g Access Point

**Trade Name:** Aceton, AirTight Networks

**Model:** WA6102X, WA6102Y, SS-200-AT

**Date of Test:** August 23 ~ September 19, 2004

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC Part 15 Subpart C	No non-compliance noted

### We hereby certify that:


The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

*Approved by:*

  
Harris W. Lai  
Executive Vice President  
Compliance Certification Services Inc.

*Reviewed by:*

  
Devin Chang  
Section Manager  
Compliance Certification Services Inc.



## 2. EUT DESCRIPTION

<b>Product</b>	WLAN 11a+b/g Access Point
<b>Trade Name</b>	Accton, AirTight Networks
<b>Model Number</b>	WA6102X, WA6102Y, SS-200-AT
<b>Model Discrepancy</b>	The difference among three models are as below: 1. Different trade name: WA6102X, WA6102Y (Accton), SS-200-AT (AirTight Networks) 2. Housing material: WA6102X, SS-200-AT: metal WA6102Y: Plastic
<b>Power Supply</b>	<b>Power Adapter</b> DELTA / ADP-15KB I/P: 100-240V, 0.5A, 50-60Hz O/P: 5.1V, 3.0A <b>Power Over Ethernet</b> VDC 48V
<b>Frequency Range</b>	IEEE 802.11a: Base mode: 5.15~5.35 GHz Turbo mode: 5210 GHz / 5250 GHz / 5290 GHz Base mode: 5.725~5.85 GHz Turbo mode: 5760 GHz / 5800 GHz IEEE 802.11b/g: 2412~2462 MHz IEEE 802.11g Turbo mode: 2437 MHz
<b>Transmit Power</b>	IEEE 802.11a: 5.15 ~ 5.35 GHz: 20.78 dBm 5.725~5.85 GHz: 24.50dBm IEEE 802.11b: 22.97 dBm IEEE 802.11g: 23.54 dBm
<b>Modulation Technique</b>	IEEE 802.11a: DSSS+ OFDM IEEE 802.11b: DSSS IEEE 802.11g: OFDM
<b>Transmit Data Rate</b>	IEEE802.11a: 54Mbps, 108Mbps IEEE 802.11b: 11Mbps IEEE 802.11g: 54Mbps, 108Mbps
<b>Number of Channels</b>	IEEE802.11a: 5.15 ~5.35 GHz: 8 Channels 5.725~5.85 GHz: 5 Channels IEEE802.11b/g: 11 Channels
<b>Enclosure Material Type:</b>	Plastic, metal
<b>Antenna Specification</b>	Antenna A: Trade name / Model name: Accton / EWP6021E Antenna Type: dual-band one feeder antenna Antenna Gain: IEEE 802.11a: 6.72dBi IEEE 802.11b/g: 2.35dBi  Antenna B: Trade name / Model name: LCT / FIB204504-93, FIB204503-93 Antenna Type: Swivel antenna Antenna Gain: IEEE 802.11a: 4.28dBi IEEE 802.11b/g: 1.82dBi

**Note:** This submittal(s) (test report) is intended for FCC ID: HEDWA6102X filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



### **3. TEST METHODOLOGY**

The tests documented in this report were performed in accordance with ANSI C63.4 and FCC CFR 47 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057, 15.207, 15.209 and 15.247.

#### **3.1 EUT CONFIGURATION**

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

#### **3.2 EUT EXERCISE**

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

#### **3.3 GENERAL TEST PROCEDURES**

##### **Conducted Emissions**

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

##### **Radiated Emissions**

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this hand-held transmitter (EUT) was rotated through three orthogonal axes according to the requirements in Section 13.1.4.1 of ANSI C63.4.

### 3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	( <sup>2</sup> )
13.36 - 13.41	322 - 335.4		

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

<sup>2</sup> Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

### 3.5 DESCRIPTION OF TEST MODES

The EUT has been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting and receiving mode is programmed.

Two enclosure material types, antennas and power supply are applied as list in section 2.

After pre-test, the configuration chosen for final testing is plastic material with power adapter and Accton antenna.

IEEE802.11a: Base mode: Channel 1(5745MHz), Channel 3(5785MHz) and Channel 5(5825MHz) with 54Mbps and Turbo mode Channel 1(5760MHz), Channel 2(5800MHz) with 108 Mbps highest data rate (the worst case) are chosen for the final testing.

IEEE802.11b: Channel 1(2412MHz), Channel 6(2437MHz) and Channel 11(2462MHz) with 11Mbps highest data rate (the worst case) are chosen for the final testing.

IEEE802.11g: Base mode: Channel 1(2412MHz), Channel 6(2437MHz) and Channel 11(2462MHz) with 54Mbps and Turbo mode: Channel 6(2437MHz) with 108 Mbps data rate (the worst case) are chosen for the final testing.



#### **4. INSTRUMENT CALIBRATION**

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.



## **5. FACILITIES AND ACCREDITATIONS**

### **5.1 FACILITIES**

All measurement facilities used to collect the measurement data are located at

- No. 81-1, Lane 210, Bade Rd. 2, Luchu Hsiang, Taoyuan Hsien, Taiwan, R.O.C.
- No. 199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

### **5.2 EQUIPMENT**

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

### **5.3 LABORATORY ACCREDITATIONS AND LISTING**

The test facilities used to perform radiated and conducted emissions tests are accredited by National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code: 200600-0 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government. In addition, the test facilities are listed with Federal Communications Commission (Registration no: 93105 and 90471).

## 5.4 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	NVLAP*	EN 55011, EN 55014-1, AS/NZS 1044, CNS 13783-1, EN 55022, CNS 13438, EN 61000-3-2, EN 61000-3-3, ANSI C63.4, FCC OST/MP-5, AS/NZS CISPR 22, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11	 200600-0
USA	FCC	3/10 meter Open Area Test Sites to perform FCC Part 15/18 measurements	 93105, 90471
Japan	VCCI	4 3/10 meter Open Area Test Sites to perform conducted/radiated measurements	 R-393/1066/725/879 C-402/747/912
Norway	NEMKO	EN 50081-1/2, EN 50082-1/2, IEC 61000-6-1/2, EN 50091-2, EN 50130-4, EN 55011, EN 55013, EN 55014-1/2, EN 55015, EN 55022, EN 55024, EN 61000-3-2/3, EN 61326-1, IEC 61000-4-2/3/4/5/6/8/11, EN 60601-1-2, EN 300 328-2, EN 300 422-2, EN 301 419-1, EN 301 489-01/03/07/08/09/17, EN 301 419-2/3, EN 300 454-2, EN 301 357-2	 ELA 124a ELA 124b ELA 124c
Taiwan	CNLA	EN 300 328-1/2, EN 300 220-1/2/3, EN 300 440-1/2, EN 61000-3-2, EN 61000-3-3, 47 CFR FCC Part 15 Subpart C/D/E, EN 55013, CNS 13439, EN 55014-1, CNS 13783-1, EN 55022, CNS 13438, CISPR 22, AS/NZS 3548, EN 61000-4-2/3/4/5/6/8/11, ENV 50204, IEEE Std 1528, FCC OET Bulletin, 65+Supplement C, EN50360, EN50361, EN50371, RSS102	 0 3 6 3 ILAC MRA
Taiwan	BSMI	CNS 13438, CNS 13783-1, CNS 13439, CNS 14115	 SL2-IS-E-0014 SL2-IN-E-0014 SL2-A1-E-0014 SL2-R1-E-0014 SL2-R2-E-0014 SL2-L1-E-0014
Canada	Industry Canada	RSS212, Issue 1	 IC 3991-3 IC 3991-4

\* No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government.



## 6. SETUP OF EQUIPMENT UNDER TEST

### 6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

### 6.2 SUPPORT EQUIPMENT

Device Type	Brand	Model	Series No.	FCC ID	Data Cable	Power Cord
Notebook PC (Remote)	IBM	2672 (X31)	99PBTKB	FCC DoC	N/A	Unshielded, 1.8m
Power Hub (Remote)	Symbol Technologies Inc.	WS3507-D8	00A0F85EC1B	N/A	N/A	Unshielded, 1.8m

**Notes:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

## 7. FCC PART 15.247 REQUIREMENTS

### 7.1 6dB BANDWIDTH

#### LIMIT


For the direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz.

#### MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360131	01/10/2005
Spectrum Analyzer	R&S	FSP30	100112	08/03/2005

*Remark: Each piece of equipment is scheduled for calibration once a year.*

#### Test Configuration



#### TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 100kHz, VBW = RBW, Span = Base mode: 25MHz / Turbo mode: 50MHz, Sweep = auto.
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.



## TEST RESULTS

*No non-compliance noted*

### Test Data

#### Test mode: IEEE 802.11b

Channel	Frequency (MHz)	Bandwidth (kHz)	Limit (kHz)	Margin (kHz)
Low	2412	12040	>500	PASS
Mid	2437	12120		PASS
High	2462	12420		PASS

#### Test mode: IEEE 802.11g

Channel	Frequency (MHz)		Bandwidth (kHz)	Limit (kHz)	Margin (kHz)
Low	Base mode	2412	16540	>500	PASS
Mid		2437	16460		PASS
High		2462	16500		PASS
Mid	Turbo mode	2437	32830		PASS

#### Test mode: IEEE 802.11a


Channel	Frequency (MHz)		Bandwidth (kHz)	Limit (kHz)	Margin (kHz)
Low	Base mode	5745	16580	>500	PASS
Mid		5785	16620		PASS
High		5825	16620		PASS
Low	Turbo mode	5760	32750		PASS
High		5800	32750		PASS

## Test Plot

## IEEE 802.11b mode


## 6dB Bandwidth (CH Low)

\* Agilent 14:30:53 Sep 11, 2004




### 6dB Bandwidth (CH Mid)

\* Agilent 14:32:03 Sep 11, 2004




**6dB Bandwidth (CH High)**

Agilent 14:34:19 Sep 11, 2004




## IEEE 802.11g Base mode

### 6dB Bandwidth (CH Low)




### 6dB Bandwidth (CH Mid)



### 6dB Bandwidth (CH High)


Agilent 14:42:44 Sep 11, 2004



### IEEE 802.11g Turbo mode


#### 6dB Bandwidth (CH Mid)

Agilent 14:44:39 Sep 11, 2004




**IEEE 802.11a Base mode****6dB Bandwidth (CH Low)**

\* Agilent 18:30:17 Sep 11, 2004


**6dB Bandwidth (CH Mid)**

\* Agilent 18:32:31 Sep 11, 2004



## 6dB Bandwidth (CH High)


\* Agilent 18:38:18 Sep 11, 2004



## IEEE 802.11a Turbo mode


### 6dB Bandwidth (CH Low)

\* Agilent 18:41:21 Sep 11, 2004



**6dB Bandwidth (CH High)**

Agilent 18:46:00 Sep 11, 2004



## 7.2 PEAK POWER

### LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:


1. For systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 watt.
2. Except as shown in paragraphs (b)(3) (i), (ii) and (iii) of this section, if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1) or (b)(2) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360131	01/10/2005
Spectrum Analyzer	R&S	FSP30	100112	08/03/2005

*Remark: Each piece of equipment is scheduled for calibration once a year.*

### Test Configuration



### TEST PROCEDURE

The transmitter output is connected to the Spectrum analyzer. The Spectrum analyzer is set to the peak power detection.



## TEST RESULTS

*No non-compliance noted*

### Test Data

#### Test mode: IEEE 802.11b mode



Channel	Frequency (MHz)	Detector	Output Power (dBm)	Factor (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
1	2412	Peak	14.45	7.90	22.35	0.17179		1 PASS
		Average	11.65	7.90	19.55	0.09016		
2	2417	Peak	14.85	7.90	22.75	0.18836		1 PASS
		Average	12.07	7.90	19.97	0.09931		
3	2422	Peak	14.69	7.90	22.59	0.18155		1 PASS
		Average	11.64	7.90	19.54	0.08995		
4	2427	Peak	14.19	7.90	22.09	0.16181		1 PASS
		Average	11.82	7.90	19.72	0.09376		
5	2432	Peak	14.14	7.90	22.04	0.15996		1 PASS
		Average	11.81	7.90	19.71	0.09354		
6	2437	Peak	15.07	7.90	22.97	0.19815		1 PASS
		Average	12.40	7.90	20.30	0.10715		
7	2442	Peak	14.91	7.90	22.81	0.19099		1 PASS
		Average	11.93	7.90	19.83	0.09616		
8	2447	Peak	14.31	7.90	22.21	0.16634		1 PASS
		Average	12.02	7.90	19.92	0.09817		
9	2452	Peak	14.14	7.90	22.04	0.15996		1 PASS
		Average	11.79	7.90	19.69	0.09311		
10	2457	Peak	13.40	7.90	21.30	0.13490		1 PASS
		Average	10.55	7.90	18.45	0.06998		
11	2462	Peak	13.56	7.90	21.46	0.13996		1 PASS
		Average	10.33	7.90	18.23	0.06653		



**Test mode: IEEE 802.11g mode**



Channel	Frequency (MHz)	Detector	Output Power (dBm)	Factor (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
1	Base Mode	2412	Peak	11.57	7.90	19.47	0.08851	1 PASS
			Average	8.27	7.90	16.17	0.04140	
2		2417	Peak	14.09	7.90	21.99	0.15812	
			Average	10.30	7.90	18.20	0.06607	
3		2422	Peak	15.31	7.90	23.21	0.20941	
			Average	11.88	7.90	19.78	0.09506	
4		2427	Peak	15.33	7.90	23.23	0.21038	
			Average	11.89	7.90	19.79	0.09528	
5		2432	Peak	15.32	7.90	23.22	0.20989	
			Average	11.91	7.90	19.81	0.09572	
6		2437	Peak	15.33	7.90	23.23	0.21038	
			Average	11.89	7.90	19.79	0.09528	
7		2442	Peak	15.64	7.90	23.54	0.22594	
			Average	12.11	7.90	20.01	0.10023	
8		2447	Peak	15.35	7.90	23.25	0.21135	
			Average	11.91	7.90	19.81	0.09572	
9		2452	Peak	14.18	7.90	22.08	0.16144	
			Average	10.77	7.90	18.67	0.07362	
10		2457	Peak	13.61	7.90	21.51	0.14158	
			Average	9.94	7.90	17.84	0.06081	
11		2462	Peak	9.88	7.90	17.78	0.05998	
			Average	6.45	7.90	14.35	0.02723	
1	Turbo Mode	2437	Peak	11.42	7.90	19.32	0.08551	
			Average	8.09	7.90	15.99	0.03972	


**Test mode: IEEE 802.11a mode**

Channel	Frequency (MHz)	Detector	Output Power (dBm)	Factor (dB)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
1	Base Mode	5745	Peak	9.90	23.70	0.23442	1	PASS
			Average	9.90	20.34	0.10814		
2		5765	Peak	9.90	23.59	0.22856		
			Average	9.90	20.26	0.10617		
3		5785	Peak	9.90	23.35	0.21627		
			Average	9.90	19.93	0.09840		
4		5805	Peak	9.90	23.86	0.24322		
			Average	9.90	20.48	0.11169		
5		5825	Peak	9.90	23.58	0.22803		
			Average	9.90	20.16	0.10375		
1	Turbo Mode	5760	Peak	9.90	24.50	0.28184		
			Average	9.90	20.89	0.12274		
2		5800	Peak	9.90	24.41	0.27606		
			Average	9.90	21.09	0.12853		

**Test Plot****IEEE 802.11b mode****Peak power (CH 2412-Peak)** Agilent 09:55:50 Sep 19, 2004**Peak power (CH 2412-Average)** Agilent 09:55:18 Sep 19, 2004

**Peak power (CH 2417-Peak)****Agilent** 09:57:01 Sep 19, 2004**Peak power (CH 2417-Average)****Agilent** 09:56:39 Sep 19, 2004


**Peak power (CH 2422-Peak)****Agilent** 09:58:11 Sep 19, 2004**Peak power (CH 2422-Average)****Agilent** 09:57:49 Sep 19, 2004

**Peak power (CH 2427-Peak)** Agilent 16:08:45 Sep 16, 2004**Channel Power**

22.09 dBm /20.0000 MHz

**Power Spectral Density**


-50.92 dBm/Hz

**Peak power (CH 2427-Average)** Agilent 16:08:25 Sep 16, 2004**Channel Power**

19.72 dBm /20.0000 MHz

**Power Spectral Density**


-53.29 dBm/Hz

**Peak power (CH 2432-Peak)** Agilent 16:11:15 Sep 16, 2004**Channel Power**

22.04 dBm /20.0000 MHz

**Power Spectral Density**


-50.97 dBm/Hz

**Peak power (CH 2432-Average)** Agilent 16:11:42 Sep 16, 2004**Channel Power**

19.71 dBm /20.0000 MHz

**Power Spectral Density**


-53.31 dBm/Hz

**Peak power (CH 2437-Peak)** Agilent 17:15:39 Sep 16, 2004**Channel Power**

22.97 dBm /20.0000 MHz

**Power Spectral Density**


-50.04 dBm/Hz

**Peak power (CH 2437-Average)** Agilent 17:17:26 Sep 16, 2004**Channel Power**

20.30 dBm /20.0000 MHz

**Power Spectral Density**


-52.71 dBm/Hz

**Peak power (CH 2442-Peak)****Agilent 16:21:07 Sep 16, 2004****Channel Power**

22.81 dBm /20.0000 MHz

**Power Spectral Density**


-50.20 dBm/Hz

**Peak power (CH 2442-Average)****Agilent 16:21:36 Sep 16, 2004****Channel Power**

19.83 dBm /20.0000 MHz

**Power Spectral Density**


-53.18 dBm/Hz

**Peak power (CH 2447-Peak)** Agilent 16:50:25 Sep 16, 2004**Channel Power**

22.21 dBm /20.0000 MHz

**Power Spectral Density**


-50.80 dBm/Hz

**Peak power (CH 2447-Average)** Agilent 16:49:56 Sep 16, 2004**Channel Power**

19.92 dBm /20.0000 MHz

**Power Spectral Density**


-53.09 dBm/Hz

**Peak power (CH 2452-Peak)** Agilent 16:52:17 Sep 16, 2004**Channel Power**

22.04 dBm /20.0000 MHz

**Power Spectral Density**



-50.97 dBm/Hz



**Peak power (CH 2452-Average)** Agilent 16:52:37 Sep 16, 2004**Channel Power**


19.69 dBm /20.0000 MHz

**Power Spectral Density**

-53.32 dBm/Hz

**Peak power (CH 2457-Peak)** **Agilent** 09:59:36 Sep 19, 2004**Peak power (CH 2457-Average)** **Agilent** 09:59:10 Sep 19, 2004


**Peak power (CH 2462-Peak)** Agilent 10:01:07 Sep 19, 2004**Peak power (CH 2462-Average)** Agilent 10:00:42 Sep 19, 2004

**IEEE 802.11g Base mode****Peak power (CH 2412-Peak)** Agilent 19:25:16 Sep 16, 2004**Channel Power**

19.47 dBm /20.0000 MHz

**Power Spectral Density**


-53.54 dBm/Hz

**Peak power (CH 2412-Average)** Agilent 19:24:24 Sep 16, 2004**Channel Power**

16.17 dBm /20.0000 MHz

**Power Spectral Density**


-56.84 dBm/Hz

**Peak power (CH 2417-Peak)****Agilent** 09:36:22 Sep 17, 2004**Channel Power**

21.99 dBm /20.0000 MHz

**Power Spectral Density**


-51.02 dBm/Hz

**Peak power (CH 2417-Average)****Agilent** 09:35:47 Sep 17, 2004**Channel Power**

18.20 dBm /20.0000 MHz

**Power Spectral Density**


-54.81 dBm/Hz

**Peak power (CH 2422-Peak)** Agilent 19:39:27 Sep 16, 2004**Channel Power**

23.21 dBm /20.0000 MHz

**Power Spectral Density**


-49.80 dBm/Hz

**Peak power (CH 2422-Average)** Agilent 19:39:00 Sep 16, 2004**Channel Power**

19.78 dBm /20.0000 MHz

**Power Spectral Density**


-53.23 dBm/Hz

**Peak power (CH 2427-Peak)** Agilent 19:45:53 Sep 16, 2004**Channel Power**

23.23 dBm /20.0000 MHz

**Power Spectral Density**

-49.78 dBm/Hz

**Peak power (CH 2427-Average)** Agilent 19:45:33 Sep 16, 2004**Channel Power**


19.79 dBm /20.0000 MHz

**Power Spectral Density**

-53.22 dBm/Hz

### Peak power (CH 2432-Peak)

\* Agilent 19:47:55 Sep 16, 2004



### Channel Power


23.22 dBm /20.0000 MHz

### Power Spectral Density

-49.79 dBm/Hz

### Peak power (CH 2432-Average)

\* Agilent 19:47:33 Sep 16, 2004







### Channel Power



19.81 dBm /20.0000 MHz


### Power Spectral Density

-53.20 dBm/Hz

**Peak power (CH 2437-Peak)** Agilent 19:55:39 Sep 16, 2004**Peak power (CH 2437-Average)** Agilent 19:54:48 Sep 16, 2004

**Peak power (CH 2442-Peak)****Agilent** 20:09:22 Sep 16, 2004**Peak power (CH 2442-Average)****Agilent** 20:08:58 Sep 16, 2004


**Peak power (CH 2447-Peak)** Agilent 20:24:11 Sep 16, 2004**Peak power (CH 2447-Average)** Agilent 20:23:40 Sep 16, 2004

**Peak power (CH 2452-Peak)****Agilent** 09:38:04 Sep 17, 2004**Channel Power**

22.08 dBm /20.0000 MHz

**Power Spectral Density**



-50.93 dBm/Hz



**Peak power (CH 2452-Average)****Agilent** 09:37:37 Sep 17, 2004**Channel Power**



18.67 dBm /20.0000 MHz

**Power Spectral Density**

-54.34 dBm/Hz


**Peak power (CH 2457-Peak)****Agilent** 09:39:14 Sep 17, 2004**Peak power (CH 2457-Average)****Agilent** 09:38:51 Sep 17, 2004

**Peak power (CH 2462-Peak)****Agilent** 20:28:23 Sep 16, 2004**Channel Power****17.78 dBm /20.0000 MHz****Power Spectral Density****-55.23 dBm/Hz****Peak power (CH 2462-Average)****Agilent** 20:28:05 Sep 16, 2004**Channel Power****14.35 dBm /20.0000 MHz****Power Spectral Density****-58.66 dBm/Hz**


**IEEE 802.11g Turbo mode****Peak power (CH 2437-Peak)** Agilent 21:11:21 Sep 16, 2004**Peak power (CH 2437-Average)** Agilent 21:10:50 Sep 16, 2004


**IEEE 802.11a Base mode****Peak power (CH 5745-Peak)**

Agilent 23:57:07 Sep 16, 2004

**Peak power (CH 5745-Average)**

Agilent 23:56:17 Sep 16, 2004




**Peak power (CH 5765-Peak)** **Agilent** 00:08:09 Sep 17, 2004**Channel Power**

23.59 dBm /20.0000 MHz

**Power Spectral Density**


-49.42 dBm/Hz

**Peak power (CH 5765-Average)** **Agilent** 00:05:53 Sep 17, 2004**Channel Power**

20.26 dBm /20.0000 MHz

**Power Spectral Density**


-52.75 dBm/Hz

**Peak power (CH 5785-Peak)****Agilent 00:10:29 Sep 17, 2004****Channel Power**

23.35 dBm /20.0000 MHz

**Power Spectral Density**



-49.66 dBm/Hz



**Peak power (CH 5785-Average)****Agilent 00:10:03 Sep 17, 2004****Channel Power**



19.93 dBm /20.0000 MHz



**Power Spectral Density**

-53.08 dBm/Hz

**Peak power (CH 5805-Peak)** **Agilent** 00:21:24 Sep 17, 2004**Peak power (CH 5805-Average)** **Agilent** 00:20:42 Sep 17, 2004

**Peak power (CH 5825-Peak)****Agilent 00:23:50 Sep 17, 2004****Peak power (CH 5825-Average)****Agilent 00:23:23 Sep 17, 2004**

**IEEE 802.11a Turbo mode****Peak power (CH 5760-Peak)****Agilent 00:26:56 Sep 17, 2004****Channel Power****24.50 dBm /40.0000 MHz****Power Spectral Density****-51.52 dBm/Hz****Peak power (CH 5760-Average)****Agilent 00:26:13 Sep 17, 2004****Channel Power****20.89 dBm /40.0000 MHz****Power Spectral Density****-55.13 dBm/Hz**

**Peak power (CH 5800-Peak)****Agilent 00:29:24 Sep 17, 2004****Peak power (CH 5800-Average)****Agilent 00:28:55 Sep 17, 2004**

## 7.3 BAND EDGES MEASUREMENT

### LIMIT


According to §15.247(c), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

### MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	R&S	FSP30	1093.4495.30	07/22/2005

*Remark: Each piece of equipment is scheduled for calibration once a year.*

### Test Configuration




### TEST PROCEDURE


1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
  - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
  - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

### TEST RESULTS


Refer to attach spectrum analyzer data chart.

**Band Edges (IEEE 802.11b / CH Low)****Detector mode: Peak****Polarity: Vertical**


Date: 18.SEP.2004 06:15:14

**Detector mode: Average****Polarity: Vertical**

Date: 18.SEP.2004 06:14:03

**Detector mode: Peak**
**Polarity: Horizontal**


Date: 23.AUG.2004 11:40:19


**Detector mode: Average**
**Polarity: Horizontal**


Date: 23.AUG.2004 11:39:04

## Band Edges (IEEE 802.11b / CH High)

**Detector mode: Peak**


**Polarity: Vertical**




Date: 18.SEP.2004 08:10:20

**Detector mode: Average**


**Polarity: Vertical**




Date: 18.SEP.2004 08:07:26

**Detector mode: Peak**
**Polarity: Horizontal**



Date: 23.AUG.2004 11:44:16

**Detector mode: Average**
**Polarity: Horizontal**



Date: 23.AUG.2004 11:43:07

**Band Edges (IEEE 802.11g Base mode / CH Low)**
**Detector mode: Peak**
**Polarity: Vertical**



Date: 15.SEP.2004 10:42:39

**Detector mode: Average**
**Polarity: Vertical**


Date: 15.SEP.2004 10:44:14

**Detector mode: Peak**
**Polarity: Horizontal**


Date: 23.AUG.2004 09:59:39


**Detector mode: Average**
**Polarity: Horizontal**


Date: 23.AUG.2004 10:01:08

### Band Edges (IEEE 802.11g Base mode / CH High)

**Detector mode: Peak**


**Polarity: Vertical**




Date: 15.SEP.2004 11:08:10

**Detector mode: Average**


**Polarity: Vertical**




Date: 15.SEP.2004 11:06:17

**Detector mode: Peak****Polarity: Horizontal**


Date: 23.AUG.2004 10:28:53

**Detector mode: Average****Polarity: Horizontal**


Date: 23.AUG.2004 10:24:25

**Band Edges (IEEE 802.11g Turbo mode / CH 2390MHz)**
**Detector mode: Peak**
**Polarity: Vertical**



Date: 15.SEP.2004 11:37:36

**Detector mode: Average**
**Polarity: Vertical**



Date: 15.SEP.2004 11:32:46

**Detector mode: Peak**
**Polarity: Horizontal**



Date: 23.AUG.2004 11:29:46

**Detector mode: Average**
**Polarity: Horizontal**



Date: 23.AUG.2004 11:28:29

**Band Edges (IEEE 802.11g Turbo mode / CH 2483.5MHz)**
**Detector mode: Peak**
**Polarity: Vertical**



Date: 23.AUG.2004 10:54:25

**Detector mode: Average**
**Polarity: Vertical**


Date: 23.AUG.2004 10:52:49

**Detector mode: Peak**
**Polarity: Horizontal**


Date: 23.AUG.2004 11:04:39

**Detector mode: Average**
**Polarity: Horizontal**


Date: 23.AUG.2004 11:03:25

## 7.4 PEAK POWER SPECTRAL DENSITY

### LIMIT


1. For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
2. The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

### MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360131	01/10/2005
Spectrum Analyzer	R&S	FSP30	100112	08/03/2005

*Remark: Each piece of equipment is scheduled for calibration once a year.*

### Test Configuration



### TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.  
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 300kHz, Sweep=100s
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.



## TEST RESULTS

*No non-compliance noted*

### Test Data

#### Test mode: IEEE 802.11b mode

Channel	Frequency (MHz)	Reading (dBm)	Factor (dB)	PPSD (dBm)	Limit (dBm)	Result
1	2412	-13.62	7.90	-5.72	8	PASS
2	2417	-8.86	7.90	-0.96		
3	2422	-8.43	7.90	-0.53		
4	2427	-9.36	7.90	-1.46		
5	2432	-8.28	7.90	-0.38		
6	2437	-9.58	7.90	-1.68		
7	2442	-9.05	7.90	-1.15		
8	2447	-9.25	7.90	-1.35		
9	2452	-10.05	7.90	-2.15		
10	2457	-8.75	7.90	-0.85		
11	2462	-9.89	7.90	-1.99		

#### Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)	Reading (dBm)	Factor (dB)	PPSD (dBm)	Limit (dBm)	Result
1	Base Mode	2412	-13.35	7.90	-5.45	PASS
2		2417	-10.72	7.90	-2.82	
3		2422	-10.10	7.90	-2.20	
4		2427	-10.46	7.90	-2.56	
5		2432	-10.52	7.90	-2.62	
6		2437	-10.52	7.90	-2.62	
7		2442	-10.34	7.90	-2.44	
8		2447	-10.28	7.90	-2.38	
9		2452	-10.23	7.90	-2.33	
10		2457	-11.51	7.90	-3.61	
11		2462	-15.34	7.90	-7.44	
1	Turbo Mode	2437	-17.30	7.90	-9.40	

**Test mode: IEEE 802.11a mode**


Channel	Frequency (MHz)		Reading (dBm)	Factor (dB)	PPSD (dBm)	Limit (dBm)	Result
1	Base Mode	5745	-12.86	9.90	-2.96	8	PASS
2		5765	-12.71	9.90	-2.81		
3		5785	-9.01	9.90	0.89		
4		5805	-7.27	9.90	2.63		
5		5825	-7.80	9.90	2.10		
1		5760	-6.81	9.90	3.09		
2	Turbo Mode	5800	-7.42	9.90	2.48		

## Test Plot

### **IEEE 802.11b mode**


## PPSD (CH 2412)



 **Agilent** 15:43:10 Sep 16, 2004



## PPSD (CH 2417)


 **Agilent** 15:50:41 Sep 16, 2004




**PPSD (CH 2422)****PPSD (CH 2427)**

**PPSD (CH 2432)**

\* Agilent 16:14:12 Sep 16, 2004


**PPSD (CH 2437)**

\* Agilent 16:18:13 Sep 16, 2004






**PPSD (CH 2442)**

\* Agilent 16:24:13 Sep 16, 2004

**PPSD (CH 2447)**


\* Agilent 16:47:05 Sep 16, 2004



**PPSD (CH 2452)****PPSD (CH 2457)**

### PPSD (CH 2462)


Agilent 17:07:53 Sep 16, 2004





### IEEE 802.11g Base mode

#### PPSD (CH 2412)


Agilent 19:28:19 Sep 16, 2004




**PPSD (CH 2417)****PPSD (CH 2422)**



**PPSD (CH 2427)**

\* Agilent 20:44:06 Sep 16, 2004


**PPSD (CH 2432)**

\* Agilent 20:48:41 Sep 16, 2004




**PPSD (CH 2437)****PPSD (CH 2442)**

### PPSD (CH 2447)




### PPSD (CH 2452)






**PPSD (CH 2457)**



\* Agilent 21:01:13 Sep 16, 2004



**PPSD (CH 2462)**



\* Agilent 21:03:36 Sep 16, 2004



**IEEE 802.11g Turbo mode****PPSD (CH 2437)****IEEE 802.11a Base mode****PPSD (CH 5745)**

**PPSD (CH 5765)****PPSD (CH 5785)**

**PPSD (CH 5805)****PPSD (CH 5825)**

**IEEE 802.11a Turbo mode****PPSD (CH 5760)****PPSD (CH 5800)**



## 7.5 RADIO FREQUENCY EXPOSURE

### LIMIT

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §15.247(b)(4) and §1.1307(b)(1) of this chapter.

### EUT Specification

EUT	WLAN 11a+b/g Access Point
Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input checked="" type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input type="checkbox"/> Others
Device category	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm <sup>2</sup> ) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm <sup>2</sup> )
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
Max. output power	IEEE 802.11a: 24.41 dBm (276.05mW) IEEE 802.11b: 22.97 dBm (198.15mW) IEEE 802.11g: 23.54 dBm (225.94mW)
Antenna gain (Max)	IEEE 802.11a: 6.72 dBi (Numeric gain: 4.698) IEEE 802.11b/g: 2.35 dBi (Numeric gain: 1.717)
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation* <input type="checkbox"/> SAR Evaluation
<b>Note:</b>	
1. The maximum output power is <u>23.79dBm (239.33mW)</u> at <u>5800Hz</u> (with <u>4.698 numeric antenna gain</u> .)	
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.	
3. For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser.	

### TEST RESULTS

No non-compliance noted.

**Calculation**

$$\text{Given } E = \sqrt{\frac{30 \times P \times G}{d}} \quad \& \quad S = \frac{E^2}{3770}$$

Where  $E$  = Field Strength in Volts / meter

$P$  = Power in Watts

$G$  = Numeric antenna gain

$d$  = Distance in meters

$S$  = Power Density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$d = \sqrt{\frac{30 \times P \times G}{3770 \times S}}$$

Changing to units of mW and cm, using:

$$P (\text{mW}) = P (\text{W}) / 1000 \text{ and}$$

$$d (\text{cm}) = 100 * d (\text{m})$$

Yields

$$d = 100 \times \sqrt{\frac{30 \times (P/1000) \times G}{3770 \times S}} = 0.282 \times \sqrt{\frac{P \times G}{S}}$$

Where  $d$  = distance in cm

$P$  = Power in mW

$G$  = Numeric antenna gain

$S$  = Power Density in mW / cm<sup>2</sup>

Substituting the logarithmic form of power and gain using:

$$P (\text{mW}) = 10^{(P (\text{dBm}) / 10)} \text{ and}$$

$$G (\text{numeric}) = 10^{(G (\text{dBi}) / 10)}$$

Yields

$$d = 0.282 \times \frac{10^{(P+G)/20}}{\sqrt{20}}$$

**Equation 1**

Where  $d$  = MPE safe distance in cm

$P$  = Power in dBm

$G$  = Antenna Gain in dBi

$S$  = Power Density Limit in mW / cm<sup>2</sup>



**Maximum Permissible Exposure (2.4 GHz Band)**

EUT output power = 239.33mW

Antenna Gain = 4.698 (Numeric gain)

S = 1.0 mW / cm<sup>2</sup> from 1.1310 Table 1

Substituting these parameters into the above Equation 1:

→ MPE Safe Distance = 9.46 cm

*(For mobile or fixed location transmitters, the minimum separation distance is 20 cm, even if calculations indicate that the MPE distance would be less.)*

## 7.6 SPURIOUS EMISSIONS

### 7.6.1 Conducted Measurement

#### LIMIT


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

#### MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360131	01/10/2005
Spectrum Analyzer	R&S	FSP30	100112	08/03/2005

*Remark: Each piece of equipment is scheduled for calibration once a year.*

#### Test Configuration



#### TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 KHz. The video bandwidth is set to 100 KHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

#### TEST RESULTS


*No non-compliance noted*

## Test Plot

### IEEE 802.11b / CH Low


#### **30MHz ~ 3.0GHz**

\* Agilent 14:50:59 Sep 11, 2004




#### **3.0GHz ~ 25GHz**

\* Agilent 14:51:56 Sep 11, 2004




**IEEE 802.11b / CH Mid****30MHz ~ 3GHz**

\* Agilent 14:53:24 Sep 11, 2004


**3GHz ~ 25GHz**

\* Agilent 14:53:58 Sep 11, 2004




**IEEE 802.11b / CH High****30MHz ~ 3GHz**

\* Agilent 14:55:17 Sep 11, 2004


**3GHz ~ 25GHz**

\* Agilent 14:55:48 Sep 11, 2004






**IEEE 802.11g Base mode / CH Low****30MHz ~ 3GHz**

\* Agilent 15:55:51 Sep 11, 2004

**3GHz ~ 25GHz**


\* Agilent 15:56:29 Sep 11, 2004




**IEEE 802.11g Base mode / CH Mid****30MHz ~ 3GHz****\* Agilent 16:00:04 Sep 11, 2004****3GHz ~ 25GHz****\* Agilent 16:01:34 Sep 11, 2004**



**IEEE 802.11g Base mode / CH High****30MHz ~ 3GHz**

\* Agilent 16:04:24 Sep 11, 2004

**3GHz ~ 25GHz**


\* Agilent 16:05:50 Sep 11, 2004




**IEEE 802.11g Turbo mode / CH Mid****30MHz ~ 3GHz****\* Agilent 16:07:53 Sep 11, 2004****3GHz ~ 25GHz****\* Agilent 16:09:01 Sep 11, 2004**

**IEEE 802.11a Base mode / CH Low****30MHz ~ 8GHz**

\* Agilent 18:57:46 Sep 11, 2004


**8GHz ~ 40GHz**

\* Agilent 18:58:29 Sep 11, 2004






**IEEE 802.11a Base mode / CH Mid****30MHz ~ 8GHz**



\* Agilent 19:01:40 Sep 11, 2004

**8GHz ~ 40GHz**

\* Agilent 19:02:47 Sep 11, 2004




**IEEE 802.11a Base mode / CH High****30MHz ~ 8GHz****\* Agilent 19:04:22 Sep 11, 2004****8GHz ~ 40GHz****\* Agilent 19:05:40 Sep 11, 2004**


**IEEE 802.11a Turbo mode / CH Low****30MHz ~ 8GHz****\* Agilent 19:11:58 Sep 11, 2004****8GHz ~ 40GHz****\* Agilent 19:10:20 Sep 11, 2004**

**IEEE 802.11a Turbo mode / CH High****30MHz ~ 8GHz**

Agilent 19:09:25 Sep 11, 2004

**8GHz ~ 40GHz**

Agilent 19:15:43 Sep 11, 2004





## 7.6.2 Radiated Emissions

### LIMIT

1. Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (mV/m)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3

*Note: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.*

2. In the above emission table, the tighter limit applies at the band edges.

Frequency (Hz)	Field Strength ( $\mu$ V/m at 3-meter)	Field Strength (dB $\mu$ V/m at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54


## MEASUREMENT EQUIPMENT USED


Open Area Test Site # 3				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	ADVANTEST	R3261A	N/A	03/18/2005
EMI Test Receiver	R&S	ESVS20	838804/004	01/04/2005
Pre-Amplifier	HP	8447D	2944A09173	03/03/2005
Bilog Antenna	SCHWAZBECK	VULB9163	145	07/05/2005
Turn Table	EMCO	2081-1.21	9709-1885	N.C.R
Antenna Tower	EMCO	2075-2	9707-2060	N.C.R
Controller	EMCO	2090	9709-1256	N.C.R
RF Switch	ANRITSU	MP59B	M53867	N.C.R
Site NSA	C&C	N/A	N/A	09/06/2005
Horn antenna	Schwarzbeck	BBHA 9120	D210	02/23/2005
Loop Antenna	EMCO	6502	2356	07/10/2005
Pre-Amplifier	HP	8449B	3008B00965	10/02/2004

**Remark:** Each piece of equipment is scheduled for calibration once a year.

## Test Configuration

### Below 1 GHz



**Above 1 GHz****TEST PROCEDURE**

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:

Below 1GHz:

RBW=100kHz / VBW=300kHz / Sweep=AUTO

Above 1GHz:

(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO

(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO

7. Repeat above procedures until the measurements for all frequencies are complete.



## TEST RESULTS

### Below 1 GHz

**Operation Mode:** TX IEEE 802.11b / CH Low

**Test Date:** September 17, 2004

**Temperature:** 28°C

**Tested by:** Jason Chang

**Humidity:** 60% RH

**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
110.10	V	Peak	18.92	12.84	31.76	43.50	-11.74
160.50	V	Peak	25.55	11.42	36.97	43.50	-6.53
169.95	V	Peak	25.19	12.15	37.34	43.50	-6.16
500.67	V	Peak	11.12	22.53	33.65	46.00	-12.35
550.83	V	Peak	11.24	24.30	35.54	46.00	-10.46
770.17	V	Peak	8.39	25.98	34.37	46.00	-11.63
81.75	H	Peak	19.91	9.96	29.87	40.00	-10.13
487.83	H	Peak	12.36	21.94	34.30	46.00	-11.70
500.67	H	Peak	13.12	22.53	35.65	46.00	-10.35
549.67	H	Peak	11.94	24.27	36.21	46.00	-9.79
660.50	H	Peak	10.58	25.07	35.65	46.00	-10.35
770.17	H	Peak	10.05	25.98	36.03	46.00	-9.97

**Notes:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Operation Mode:** TX IEEE 802.11b / CH Mid**Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
87.60	V	Peak	19.61	11.47	31.08	40.00	-8.92
98.40	V	Peak	16.53	13.80	30.33	43.50	-13.17
330.33	V	Peak	14.45	17.50	31.95	46.00	-14.05
500.67	V	Peak	11.45	22.53	33.98	46.00	-12.02
550.83	V	Peak	9.57	24.30	33.87	46.00	-12.13
770.17	V	Peak	8.22	25.98	34.20	46.00	-11.80
240.15	H	Peak	19.21	15.92	35.13	46.00	-10.87
270.30	H	Peak	19.08	15.82	34.90	46.00	-11.10
500.67	H	Peak	13.95	22.53	36.48	46.00	-9.52
549.67	H	Peak	10.44	24.27	34.71	46.00	-11.29
660.50	H	Peak	12.58	25.07	37.65	46.00	-8.35
772.50	H	Peak	8.24	26.00	34.24	46.00	-11.76

**Notes:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Operation Mode:** TX IEEE 802.11b / CH High**Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
36.30	V	Peak	20.00	13.13	33.13	40.00	-6.87
51.60	V	Peak	17.21	15.15	32.36	40.00	-7.64
500.67	V	Peak	11.95	22.53	34.48	46.00	-11.52
549.67	V	Peak	10.27	24.27	34.54	46.00	-11.46
659.33	V	Peak	9.09	25.05	34.14	46.00	-11.86
770.17	V	Peak	8.89	25.98	34.87	46.00	-11.13
240.15	H	Peak	18.88	15.92	34.80	46.00	-11.20
478.50	H	Peak	18.33	21.50	39.83	46.00	-6.17
500.67	H	Peak	12.95	22.53	35.48	46.00	-10.52
549.67	H	Peak	12.94	24.27	37.21	46.00	-8.79
660.50	H	Peak	10.74	25.07	35.81	46.00	-10.19
770.17	H	Peak	9.05	25.98	35.03	46.00	-10.97

**Notes:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Operation Mode:** TX IEEE 802.11g Base mode / CH Low**Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
141.15	V	Peak	18.51	10.90	29.41	43.50	-14.09
240.00	V	Peak	14.88	15.92	30.80	46.00	-15.20
500.67	V	Peak	14.28	22.53	36.81	46.00	-9.19
549.67	V	Peak	11.10	24.27	35.37	46.00	-10.63
659.33	V	Peak	9.42	25.05	34.47	46.00	-11.53
769.00	V	Peak	11.71	25.98	37.69	46.00	-8.31
240.15	H	Peak	18.38	15.92	34.30	46.00	-11.70
277.05	H	Peak	19.23	15.79	35.02	46.00	-10.98
500.67	H	Peak	12.62	22.53	35.15	46.00	-10.85
549.67	H	Peak	12.94	24.27	37.21	46.00	-8.79
659.33	H	Peak	10.75	25.05	35.80	46.00	-10.20
770.17	H	Peak	7.89	25.98	33.87	46.00	-12.13

**Notes:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Operation Mode:** TX IEEE 802.11g Base mode / CH Mid      **Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
141.15	V	Peak	17.18	10.90	28.08	43.50	-15.42
240.15	V	Peak	15.55	15.92	31.47	46.00	-14.53
330.33	V	Peak	13.95	17.50	31.45	46.00	-14.55
499.50	V	Peak	13.49	22.49	35.98	46.00	-10.02
549.67	V	Peak	10.94	24.27	35.21	46.00	-10.79
770.17	V	Peak	9.22	25.98	35.20	46.00	-10.80
240.15	H	Peak	18.55	15.92	34.47	46.00	-11.53
330.33	H	Peak	15.61	17.50	33.11	46.00	-12.89
499.50	H	Peak	13.82	22.49	36.31	46.00	-9.69
549.67	H	Peak	15.44	24.27	39.71	46.00	-6.29
659.33	H	Peak	11.92	25.05	36.97	46.00	-9.03
769.00	H	Peak	8.38	25.98	34.36	46.00	-11.64

**Notes:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Operation Mode:** TX IEEE 802.11g Base mode / CH High**Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
240.15	V	Peak	15.71	15.92	31.63	46.00	-14.37
330.33	V	Peak	15.11	17.50	32.61	46.00	-13.39
500.67	V	Peak	13.28	22.53	35.81	46.00	-10.19
549.67	V	Peak	11.27	24.27	35.54	46.00	-10.46
769.00	V	Peak	9.88	25.98	35.86	46.00	-10.14
879.83	V	Peak	4.58	27.80	32.38	46.00	-13.62
240.15	H	Peak	18.38	15.92	34.30	46.00	-11.70
330.33	H	Peak	15.45	17.50	32.95	46.00	-13.05
499.50	H	Peak	13.16	22.49	35.65	46.00	-10.35
550.83	H	Peak	10.74	24.30	35.04	46.00	-10.96
660.50	H	Peak	11.24	25.07	36.31	46.00	-9.69
770.17	H	Peak	6.89	25.98	32.87	46.00	-13.13

**Notes:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Operation Mode:** TX IEEE 802.11g Turbo mode / CH Mid**Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
240.15	V	Peak	14.88	15.92	30.80	46.00	-15.20
330.33	V	Peak	13.28	13.28	26.56	46.00	-19.44
549.67	V	Peak	11.10	24.27	35.37	46.00	-10.63
660.50	V	Peak	7.08	25.07	32.15	46.00	-13.85
772.50	V	Peak	8.57	26.00	34.57	46.00	-11.43
879.83	V	Peak	7.58	27.80	35.38	46.00	-10.62
141.60	H	Peak	22.95	10.91	33.86	43.50	-9.64
240.15	H	Peak	21.05	15.92	36.97	46.00	-9.03
330.33	H	Peak	18.28	17.50	35.78	46.00	-10.22
549.67	H	Peak	14.10	24.27	38.37	46.00	-7.63
660.50	H	Peak	13.41	25.07	38.48	46.00	-7.52
763.17	H	Peak	10.16	25.95	36.11	46.00	-9.89

**Notes:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Operation Mode:** TX IEEE 802.11a Base mode / CH 5745**Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
500.67	V	Peak	8.95	22.53	31.48	46.00	-14.52
550.83	V	Peak	10.57	24.30	34.87	46.00	-11.13
660.50	V	Peak	6.24	25.07	31.31	46.00	-14.69
770.17	V	Peak	7.39	25.98	33.37	46.00	-12.63
879.83	V	Peak	5.08	27.80	32.88	46.00	-13.12
990.67	V	Peak	4.56	29.62	34.18	54.00	-19.82
329.17	H	Peak	16.10	17.47	33.57	46.00	-12.43
499.50	H	Peak	10.99	22.49	33.48	46.00	-12.52
549.67	H	Peak	13.77	24.27	38.04	46.00	-7.96
659.33	H	Peak	13.09	25.05	38.14	46.00	-7.86
770.17	H	Peak	8.22	25.98	34.20	46.00	-11.80
903.17	H	Peak	2.74	28.19	30.93	46.00	-15.07

**Notes:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Operation Mode:** TX IEEE 802.11a Base mode / CH 5785**Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
330.33	V	Peak	12.95	17.50	30.45	46.00	-15.55
500.67	V	Peak	8.12	22.53	30.65	46.00	-15.35
549.67	V	Peak	10.44	24.27	34.71	46.00	-11.29
660.50	V	Peak	8.24	25.07	33.31	46.00	-12.69
770.17	V	Peak	10.22	25.98	36.20	46.00	-9.80
879.83	V	Peak	5.92	27.80	33.72	46.00	-12.28
330.33	H	Peak	16.28	17.50	33.78	46.00	-12.22
499.50	H	Peak	12.82	22.49	35.31	46.00	-10.69
549.67	H	Peak	13.44	24.27	37.71	46.00	-8.29
659.33	H	Peak	12.09	25.05	37.14	46.00	-8.86
766.67	H	Peak	8.36	25.97	34.33	46.00	-11.67
878.67	H	Peak	3.08	27.78	30.86	46.00	-15.14

**Notes:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Operation Mode:** TX IEEE 802.11a Base mode / CH 5825**Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
330.33	V	Peak	12.45	17.50	29.95	46.00	-16.05
500.67	V	Peak	8.95	22.53	31.48	46.00	-14.52
549.67	V	Peak	10.10	24.27	34.37	46.00	-11.63
660.50	V	Peak	5.08	25.07	30.15	46.00	-15.85
770.17	V	Peak	7.55	25.98	33.53	46.00	-12.47
879.83	V	Peak	6.58	27.80	34.38	46.00	-11.62
279.75	H	Peak	17.44	15.89	33.33	46.00	-12.67
330.33	H	Peak	16.45	17.50	33.95	46.00	-12.05
500.67	H	Peak	11.12	22.53	33.65	46.00	-12.35
550.83	H	Peak	13.57	24.30	37.87	46.00	-8.13
660.50	H	Peak	12.58	25.07	37.65	46.00	-8.35
770.17	H	Peak	12.22	25.98	38.20	46.00	-7.80

**Notes:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Operation Mode:** TX IEEE 802.11a Turbo mode / CH 5760    **Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
141.60	V	Peak	19.45	10.91	30.36	43.50	-13.14
321.00	V	Peak	15.13	17.25	32.38	46.00	-13.62
440.00	V	Peak	13.84	20.28	34.12	46.00	-11.88
549.66	V	Peak	11.44	24.27	35.71	46.00	-10.29
659.33	V	Peak	6.42	25.05	31.47	46.00	-14.53
770.17	V	Peak	8.22	25.98	34.20	46.00	-11.80
141.60	H	Peak	21.62	10.91	32.53	43.50	-10.97
330.33	H	Peak	15.28	17.50	32.78	46.00	-13.22
500.67	H	Peak	13.12	22.53	35.65	46.00	-10.35
550.83	H	Peak	13.07	24.30	37.37	46.00	-8.63
659.33	H	Peak	15.09	25.05	40.14	46.00	-5.86
766.67	H	Peak	13.02	25.97	38.99	46.00	-7.01

**Notes:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Operation Mode:** TX IEEE 802.11a Turbo mode / CH 5800    **Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant.Pol. H/V	Detector Mode (PK/QP)	Reading (dBuV)	Factor (dB)	Actual FS (dBuV/m)	Limit 3m (dBuV/m)	Safe Margin (dB)
330.33	V	Peak	13.11	17.50	30.61	46.00	-15.39
499.50	V	Peak	8.49	22.49	30.98	46.00	-15.02
549.67	V	Peak	10.60	24.27	34.87	46.00	-11.13
659.33	V	Peak	7.75	25.05	32.80	46.00	-13.20
770.17	V	Peak	11.55	25.98	37.53	46.00	-8.47
879.83	V	Peak	5.58	27.80	33.38	46.00	-12.62
141.60	H	Peak	22.12	10.91	33.03	43.50	-10.47
291.90	H	Peak	17.16	16.37	33.53	46.00	-12.47
500.67	H	Peak	12.78	22.53	35.31	46.00	-10.69
550.83	H	Peak	14.07	24.30	38.37	46.00	-7.63
660.50	H	Peak	13.91	25.07	38.98	46.00	-7.02
770.17	H	Peak	8.39	25.98	34.37	46.00	-11.63

**Notes:**

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using Peak detector mode.
3. Data of measurement within this frequency range shown “ --- ” in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. The IF bandwidth of SPA between 30MHz to 1GHz was 100kHz.

**Above 1 GHz****Operation Mode:** TX IEEE 802.11b / CH Low**Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1836.67	V	50.84	---	-5.49	45.35	---	74.00	54.00	-8.65	Peak
4824.00	V	47.88	47.61	1.69	53.51	49.30	74.00	54.00	-4.70	AVG
7236.00	V	50.39	41.95	5.63	56.02	47.58	74.00	54.00	-6.42	AVG
9648.00	V	44.55	35.22	9.30	53.84	44.51	74.00	54.00	-9.49	AVG
12060.00	V	45.02	33.34	10.57	55.59	43.91	74.00	54.00	-10.09	AVG
N/A										
4824.00	H	51.06	46.08	1.69	52.75	47.77	74.00	54.00	-6.23	AVG
7236.00	H	51.49	44.18	5.63	57.12	49.81	74.00	54.00	-4.19	AVG
9648.00	H	43.83	32.33	9.30	53.12	41.62	74.00	54.00	-12.38	AVG
12060.00	H	45.24	33.10	10.57	55.81	43.67	74.00	54.00	-10.33	AVG
N/A										

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
  - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto

**Operation Mode:** TX IEEE 802.11b / CH Mid**Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1836.67	V	50.50	---	-5.49	45.01	---	74.00	54.00	-8.99	Peak
4874.00	V	50.18	45.33	1.84	52.02	47.17	74.00	54.00	-6.83	AVG
7311.00	V	51.59	44.97	5.84	57.43	50.81	74.00	54.00	-3.19	AVG
9748.00	V	44.80	33.64	9.53	54.33	43.17	74.00	54.00	-10.83	AVG
12185.00	V	44.88	33.74	10.35	55.23	44.09	74.00	54.00	-9.91	AVG
N/A										
4874.00	H	49.06	---	1.84	50.90	---	74.00	54.00	-3.10	Peak
7311.00	H	53.26	53.26	5.84	59.10	49.58	74.00	54.00	-4.42	AVG
9748.00	H	42.44	---	9.53	51.97	---	74.00	54.00	-2.03	Peak
12185.00	H	44.99	44.99	10.35	55.34	42.97	74.00	54.00	-11.03	AVG
N/A										

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
  - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto

**Operation Mode:** TX IEEE 802.11b / CH High**Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
4924.00	V	49.44	---	1.99	51.43	---	74.00	54.00	-2.57	Peak
7386.00	V	52.23	45.98	6.02	58.24	51.99	74.00	54.00	-2.01	AVG
9848.00	V	43.62	32.33	9.76	53.38	42.09	74.00	54.00	-11.91	AVG
12310.00	V	45.28	30.11	10.12	55.40	40.23	74.00	54.00	-13.77	AVG
N/A										
4924.00	H	47.82	---	1.99	49.81	---	74.00	54.00	-4.19	Peak
7386.00	H	51.41	43.63	6.02	57.42	49.64	74.00	54.00	-4.36	AVG
9848.00	H	42.18	---	9.76	51.94	---	74.00	54.00	-2.06	Peak
12310.00	H	43.76	29.82	10.12	53.88	39.94	74.00	54.00	-14.06	AVG
N/A										

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
  - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto

**Operation Mode:** TX IEEE 802.11g Base mode / CH Low**Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1836.67	V	52.17	---	-5.49	46.68	---	74.00	54.00	-7.32	Peak
4824.00	V	51.85	37.93	1.69	53.54	39.62	74.00	54.00	-14.38	AVG
7236.00	V	61.75	44.77	5.63	67.38	50.40	74.00	54.00	-3.60	AVG
9648.00	V	43.08	29.71	9.30	52.38	39.01	74.00	54.00	-14.99	AVG
12060.00	V	51.39	34.18	10.57	61.96	44.75	74.00	54.00	-9.25	AVG
N/A										
4824.00	H	47.69	33.96	1.69	49.38	35.65	74.00	54.00	-18.35	AVG
7236.00	H	59.49	42.53	5.63	65.12	48.16	74.00	54.00	-5.84	AVG
N/A										

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
  - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto

**Operation Mode:** TX IEEE 802.11g Base mode / CH Mid      **Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1836.67	V	51.34	---	-5.49	45.85	---	74.00	54.00	-8.15	Peak
4874.00	V	51.03	37.33	1.84	52.87	39.17	74.00	54.00	-14.83	AVG
7311.00	V	64.81	45.74	5.84	70.65	51.58	74.00	54.00	-2.42	AVG
9748.00	V	43.35	28.88	9.53	52.88	38.41	74.00	54.00	-15.59	AVG
12185.00	V	51.58	35.11	10.35	61.93	45.46	74.00	54.00	-8.54	AVG
N/A										
4874.00	H	51.68	36.84	1.84	53.52	38.68	74.00	54.00	-15.32	AVG
7311.00	H	61.49	45.88	5.84	67.33	51.72	74.00	54.00	-2.28	AVG
9748.00	H	52.51	35.86	9.53	62.04	45.39	74.00	54.00	-8.61	AVG
N/A										

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
  - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto

**Operation Mode:** TX IEEE 802.11g Base mode / CH High**Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
1836.67	V	51.84	---	-5.49	46.35	---	74.00	54.00	-7.65	Peak
4924.00	V	52.57	38.67	1.99	54.56	40.66	74.00	54.00	-13.34	AVG
7386.00	V	67.75	45.38	6.02	73.76	51.39	74.00	54.00	-2.61	AVG
9848.00	V	42.08	30.00	9.76	51.84	39.76	74.00	54.00	-14.24	AVG
12310.00	V	48.84	33.56	10.12	58.96	43.68	74.00	54.00	-10.32	AVG
N/A										
4924.00	H	50.79	37.01	1.99	52.78	39.00	74.00	54.00	-15.00	AVG
7386.00	H	61.52	46.38	6.02	67.53	52.39	74.00	54.00	-1.61	AVG
N/A										

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
  - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto

**Operation Mode:** TX IEEE 802.11g Turbo mode / CH Mid**Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
4874.00	V	47.69	33.75	1.84	49.53	35.59	74.00	54.00	-18.41	AVG
7311.00	V	59.72	43.64	5.84	65.56	49.48	74.00	54.00	-4.52	AVG
N/A										
7311.00	H	55.04	39.29	5.84	60.88	45.13	74.00	54.00	-8.87	AVG
N/A										

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
  - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto

**Operation Mode:** TX IEEE 802.11a Base mode / CH 5745**Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
11490.00	V	57.03	42.38	9.80	66.83	52.18	74.00	54.00	-1.82	AVG
17235.00	V	54.27	40.37	12.26	66.53	52.63	74.00	54.00	-1.37	AVG
N/A										
11490.00	H	52.74	38.03	9.80	62.54	47.83	74.00	54.00	-6.17	AVG
17235.00	H	56.23	41.61	12.26	68.49	53.87	74.00	54.00	-0.13	AVG
N/A										

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
  - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto

**Operation Mode:** TX IEEE 802.11a Base mode / CH 5785**Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
11570.00	V	57.06	42.40	9.91	66.97	52.31	74.00	54.00	-1.69	AVG
17355.00	V	53.87	39.62	12.86	66.73	52.48	74.00	54.00	-1.52	AVG
N/A										
11570.00	H	48.75	34.99	9.91	58.66	44.90	74.00	54.00	-9.10	AVG
17355.00	H	54.45	40.52	12.86	67.31	53.38	74.00	54.00	-0.62	AVG
N/A										

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
  - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto

**Operation Mode:** TX IEEE 802.11a Base mode / CH 5825**Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
11650.00	V	55.58	40.82	10.05	65.63	50.87	74.00	54.00	-3.13	AVG
17475.00	V	55.33	39.52	13.45	68.78	52.97	74.00	54.00	-1.03	AVG
N/A										
11650.00	H	54.87	41.15	10.05	64.92	51.20	74.00	54.00	-2.80	AVG
17475.00	H	54.81	40.22	13.45	68.26	53.67	74.00	54.00	-0.33	AVG
N/A										

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
  - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto

**Operation Mode:** TX IEEE 802.11a Turbo mode / CH 5765    **Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
11520.00	V	56.30	42.16	9.82	66.12	51.98	74.00	54.00	-2.02	AVG
17280.00	V	53.34	39.62	12.51	65.85	52.13	74.00	54.00	-1.87	AVG
N/A										
11520.00	H	54.85	40.52	9.82	64.67	50.34	74.00	54.00	-3.66	AVG
17280.00	H	49.03	36.02	12.51	61.54	48.53	74.00	54.00	-5.47	AVG
N/A										

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
  - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto

**Operation Mode:** TX IEEE 802.11a Turbo mode / CH 5800    **Test Date:** September 17, 2004**Temperature:** 28°C**Tested by:** Jason Chang**Humidity:** 60% RH**Polarity:** Ver. / Hor.

Freq. (MHz)	Ant. Pol H/V	Peak Reading (dBuV)	AV Reading (dBuV)	Ant. / CL CF (dB)	Actual Fs		Peak Limit (dBuV/m)	AV Limit (dBuV/m)	Margin (dB)	Remark
					Peak (dBuV/m)	AV (dBuV/m)				
11600.00	V	53.96	39.31	9.96	63.92	49.27	74.00	54.00	-4.73	AVG
17400.00	V	50.22	35.35	13.10	63.32	48.45	74.00	54.00	-5.55	AVG
N/A										
11600.00	H	54.71	40.38	9.96	64.67	50.34	74.00	54.00	-3.66	AVG
17400.00	H	48.44	35.43	13.10	61.54	48.53	74.00	54.00	-5.47	AVG
N/A										

**Notes:**

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Spectrum setting:
  - a. Peak Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 1MHz, Sweep time = Auto.
  - b. AV Setting 1GHz to 10th harmonics of fundamental, RBW = 1MHz, VBW = 10Hz, Sweep time = Auto



## 7.7 POWERLINE CONDUCTED EMISSIONS

### LIMIT

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dB $\mu$ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

### MEASUREMENT EQUIPMENT USED

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCS30	847793/012	12/20/2004
LISN	R&S	ESH2-Z5	843285/010	12/15/2004
LISN	EMCO	3825/2	9003-1628	07/25/2005

*Remark: Each piece of equipment is scheduled for calibration once a year.*

### Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

### TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.



## **TEST RESULTS**

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

### **Test Data**

<b>Operation Mode:</b>	TX + RX mode	<b>Test Date:</b>	September 20, 2004
<b>Temperature:</b>	25°C	<b>Tested by:</b>	Joan Liu
<b>Humidity:</b>	55% RH		

Freq. (MHz)	Q.P. Raw (dBuV)	AVG Raw (dBuV)	Q.P. Limit (dBuV)	AVG Limit (dBuV)	Q.P. Margin (dB)	AVG Margin (dB)	Note
0.225	41.352	31.392	62.632	52.632	-21.280	-21.240	L1
0.191	42.305	25.995	63.993	53.993	-21.688	-27.998	L1
0.150	47.000	23.290	66.000	56.000	-19.000	-32.710	L1
0.447	28.059	23.129	56.931	46.931	-28.871	-23.801	L1
0.676	28.310	21.210	56.000	46.000	-27.690	-24.790	L1
0.901	30.430	23.300	56.000	46.000	-25.570	-22.700	L1
0.150	42.800	21.250	66.000	56.000	-23.200	-34.750	L2
0.223	43.025	28.775	62.706	52.706	-19.682	-23.932	L2
0.676	30.666	24.106	56.000	46.000	-25.334	-21.894	L2
0.901	32.032	26.292	56.000	46.000	-23.968	-19.708	L2
1.126	34.313	26.953	56.000	46.000	-21.687	-19.047	L2
7.384	19.307	9.867	60.000	50.000	-40.693	-40.133	L2


#### **Note:**

1. Measuring frequencies from 0.15 MHz to 30MHz.
2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Quasi-peak detector and average detector.
3. “---” denotes the emission level was or more than 2dB below the Average limit
4. The IF bandwidth of SPA between 0.15MHz to 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz to 30MHz was 9kHz;
5. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)

## Test Plots


### Conducted emissions (Line 1)

Result Graph



### Conducted emissions (Line 2)



Result Graph



## APPENDIX 1

### PHOTOGRPHS OF TEST SETUP

#### Radiated Emission Set up Photos



## Conducted Emission Set Up Photos

