

样品承认书

SAMPLE SPECIFICATION FOR APPROVAL

供应商名称 SUPPLIER	Shenzhen Deman Electronics Technology Co.,Ltd.
客户名称 CUSTOMER	FAIOT Co., LTD
物料名称 DESCRIPTION	FH22-NFC-Antenna-F2096
物料规格 SPECIFICATION	
物料编码 CUSTOMER PART NO	
供应商审核(公章) SUPPLIER APPROVAL	
客户审核 CUSTOMER APPROVAL	
承认日期 APPROVAL DATE	

Confirm and sign off			
Base band	RF	ME	ID
Resource	SQE	PQM	

Contents

1、 Sample

need ☒ ; no need ☐

2、 Specification sheet, drawings, material report, physical property table, and SOP for fixture inspection

paper archive ☒ ; electronic document ☒

3、 Appearance Inspection report

paper archive ☒ ; electronic document ☒

4、 dimension report

paper archive ☒ ; electronic document ☒

5、 functional test report

paper archive ☐ ; electronic document ☒

6、 Reliability Test Report

paper archive ☒ ; electronic document ☒

7、 Key dimension CPK

paper archive ☒ ; electronic document ☒

8、 Flow chart

paper archive ☐ ; electronic document ☒

9、 manner of packing


paper archive ☒ ; electronic document ☒

10、 Environmental protection materials (only electronic files are required)

Material composition questionnaire ☒ ; RoHS ☒ ; Reach ☒ ; HF ☒

Remark: ☒ Provide as needed ; ☐ It is not necessary to provide

Drawing



Visual inspection

Deman

file type: Homework instructions

Document Number	Appendix 1
WI-042-012	NFC Finished Product Inspection Sampling and Judgment Standards (General)

Inspection items	inspection content	tool	Sampling standard	Judgment criteria	Accept Standard
appearance	Paste off center	Film ruler	General Level I	$W \leq 0.2\text{mm}$.	The appearance sampling standard follows the general standard of GB2828.1-2003, Level II (MA=0.4, MI=0.65); Size data, electrical properties, and reliability: 0 accepted and 1 rejected.
	Surface scratches			$L \leq 5\text{mm}$ or $W \leq 0.2\text{mm}$.	
	Dirty and shiny marks			$L \leq 3\text{mm}$ or $W \leq 2\text{mm}$ and not visible to the naked eye at 30cm; Wipe off dirt and bright marks are not allowed.	
	Defects and excess materials			$L \leq 0.3\text{mm}$ or $W \leq 0.1\text{mm}$.	
	surface scratch			$L \leq 3\text{mm}$ or $W \leq 0.2\text{mm}$, exposed substrate is not allowed.	
	Surface point defects (particles, bubbles, pits)			$D \leq 0.3\text{mm}$, Excessive thickness of the product is not allowed.	
	Surface foreign matter			$L \leq 1\text{mm}$ or $W \leq 0.15\text{mm}$, excessive product thickness is not allowed.	
	Positioning hole offset			Deviation $\leq 0.2\text{mm}$, hole blockage is not allowed.	
	sawtooth			$W \leq 0.15\text{mm}$.	
	Adhesive tape attachment deviation			$W \leq 0.2\text{mm}$.	
	Golden Finger Embossing			轻微压点 $D \leq 0.25\text{mm}$, $H \leq 0.02\text{mm}$, $N \leq 2$.	
	Scratches on golden fingers	see	General Level I	The coating is undamaged, $L \leq 3\text{mm}$, $W \leq 0.03\text{mm}$, Not counted; $0.05\text{mm} < W \leq 0.05\text{mm}$, $L \leq 3\text{mm}$, $N \leq 2$, $DS \geq 15\text{mm}$; $W > 0.05\text{mm}$ or $L > 3\text{mm}$ are not allowed.	
	Crease			The deformation, warping, and delamination of the product caused by wrinkles are not allowed. For slight wrinkles, refer to the	
	Incomplete circuit and residual copper			Do not allow/reference limit samples.	
	Silkscreen			Visually identifiable.	
	crack			Not visible to the naked eye.	
	Product color difference			Do not allow/reference limit samples.	
	adhesive residue			Do not allow/reference limit samples.	
	Copper leakage (surface, side, via)			Do not allow/reference limit samples.	
	Post backwards			Do not allow/reference limit samples.	
	Multiple stickers (ferrite, FPC)			Do not allow/reference limit samples.	
	Cutting off the gap			Exceeding the size limit is not allowed/reference limit sample	
	layering			Do not allow/reference limit samples.	
	Gold Finger Ink Overflow			Exceeding the size limit is not allowed/reference limit sample	
	Golden finger defect			$D \leq 0.15\text{mm}$.	
	Golden finger oxidation			Do not allow/reference limit samples.	
	According to the drawings of each model, inspect the key dimensions	Calipers/ image measuring	5pcs/batch	If the size exceeds the tolerance on the drawing, it will be rejected; Otherwise, proceed to the next step of verification.	
	According to the drawings of each model, mark the "ST" dimension	Calipers/ image measuring	35pcs/PO	CPK needs to be greater than 1.33. If it is not met, feedback should be given for improvement.	
Electrical properties	According to the product dependency book, measure the electrical properties	LCR tester	35pcs/day	Electrical properties exceeding the range, rejected; Otherwise, proceed to the next step of verification.	
reliability	Temperature shock	Thermal Shock Chamber	2pcs/time/month	Refer to reliability testing standards	
	Steady damp-heat	Humidity Chamber	2pcs/time/month	Refer to reliability testing standards	
	high temperature storage	High temperature	2pcs/time/month	Refer to reliability testing standards	
	low temperature storage	Low temperature	2pcs/time/month	Refer to reliability testing standards	

Note: 1. L represents length, W represents width, H represents height, D represents diameter, S represents area, DS represents spacing, and N represents quantity.

2. When customers have special requirements/specific models, the signed limit sample shall be used as the standard.

Antenna performance

1. Electrical Specifications.

Test item	Test environment	FH22 specification				
		Min	Typ	Max	Units	Notes
IC	—	—		—	—	THN31FGB1N
Antenna frequency	—	—	13.56	—	MHz	-
Antenna inductance	1 MHz	1.433	1.473	1.513	μH	±0.04
Antenna resistance	1 MHz	0.98	1.18	1.38	Ω	±0.2
Ferrite permeability	13.56 MHz	135	150	165		±10%
Magnetic loss of ferrite	13.56 MHz	—	—	5		≤5


LCR control


Scope of control: 1MHz inductance: : ±0.04
1MHz resistance: ±0.2

S11 control

Scope of control: 13.56±0.15MHz

S11 Management and control mode






Scope of control: $13.56 \pm 0.15 \text{ MHz}$

2. Parameter test screenshot and test method diagram

Antenna free space test



3. Read/write mode Distance test data and scene photos

读卡类型	Tag1	Tag2	Tag3	Tag4A	Tag5
读卡距离	42mm	43mm	42mm	20mm	60mm



Tag1(Topaz-512)



Tag 2 (Ultralight)



Tag3(Sony-Felica)



Tag 4 (Desfire)

Note: The above reading distance is the reading distance of the debugging machine, and the reading distance of the trial production and mass production machine shall be subject to the actual situation.

Reliability Test Report

		Shenzhen Haiderman Electronics Co., Ltd					
可靠性测试记录							
customer	Guangyi	applicant	Xuehua Kang	application date	2025/2/11	date of observation	2025/2/11
Task Number		Sample name	FH22	sample attribute	NFC	Sample model	F2096
Test items	Experimental conditions			Judgment criteria	Number of samples	Decision outcome	notes
1	Temperature shock	Take the product and store it at a low temperature of $-40\text{ }^{\circ}\text{C}\pm 2\text{ }^{\circ}\text{C}$ for 0.5 hours. Within 1 minute, store it at a high temperature of $85\pm 2\text{ }^{\circ}\text{C}$ for 0.5 hours. This is one cycle, with a total of 48 cycles. Let it stand for 2 hours		Check the appearance of the coating for any abnormalities, such as detachment,	3	OK	
2	high temperature storage	85 $^{\circ}\text{C}$, stored for 48 hours, left to stand for 2 hours		Check the appearance of the coating for any abnormalities, such as detachment,	3	OK	
3	low temperature storage	-40 $^{\circ}\text{C}$, stored for 48 hours, left to stand for 2 hours		Check the appearance of the coating for any abnormalities, such as detachment,	3	OK	
4	Steady damp-heat	Take the product at a temperature of $60\text{ }^{\circ}\text{C}\pm 2\text{ }^{\circ}\text{C}$ and a humidity of $95\pm 2\%$; Maintain for 48 hours, let it stand for 2 hours		Check the appearance of the coating for any abnormalities, such as detachment,	3	OK	
5	Salt spray test	Take the product, in the environment of $35\pm 3\text{ }^{\circ}\text{C}$, the PH value is in the range of 6.5-7.2, the salt water concentration is $5\pm 1\%$, and continuous spray for 48H		Check the appearance of the coating for any abnormalities, such as detachment, cracks	3	OK	
Comprehensive judgment	OK		surveyor	Chen Hongwei	to examine		Xu Shuangquan

Key dimensions CPK

Deman				file type: table				version: /			
Table Number	table name										
F-042-005-21	Size CPK Inspection Report										
PRODUCT MODEL	F2096-NFC			Product batch number			\				
Time of observation	2025/2/25			Test sample size			32PCS				
Test equipment	projector			Tested by			Xuehuang Kang				
Size number	1	9	14								
Standard size	39.75	26.59	0.23								
Tolerance	0.15	0.15	0.03								
negative tolerance	(0.15)	(0.15)	(0.03)								
specification	39.90	26.74	0.26								
Specification	39.60	26.44	0.20								
1	39.76	26.58	0.22								
2	39.75	26.58	0.22								
3	39.76	26.59	0.23								
4	39.76	26.58	0.22								
5	39.79	26.58	0.22								
6	39.77	26.56	0.22								
7	39.76	26.58	0.22								
8	39.76	26.59	0.23								
9	39.76	26.59	0.23								
10	39.77	26.58	0.23								
11	39.79	26.58	0.23								
12	39.76	26.58	0.23								
13	39.76	26.62	0.22								
14	39.76	26.58	0.23								
15	39.76	26.59	0.24								
16	39.77	26.58	0.22								
17	39.76	26.58	0.23								
18	39.74	26.62	0.23								
19	39.76	26.58	0.22								
20	39.76	26.56	0.22								
21	39.77	26.58	0.24								
22	39.76	26.62	0.22								
23	39.74	26.59	0.22								
24	39.78	26.58	0.22								
25	39.79	26.59	0.23								
26	39.74	26.58	0.22								
27	39.81	26.62	0.23								
28	39.73	26.56	0.23								
29	39.76	26.62	0.22								
30	39.77	26.58	0.23								
31	39.76	26.56	0.22								
32	39.78	26.58	0.22								
MAX	39.81	26.62	0.24								
MIN	39.73	26.56	0.22								
AVERAGE	39.76	26.59	0.23								
STDEV	0.02	0.02	0.01								
CP	3.08	2.90	1.61								
Cpk	2.79	2.82	1.36								
judge	OK	OK	OK								
notes: CPK≥1.33. The customer has requested to execute according to the requirements											
Shenzhen Haiderman Electronics Co., Ltd											
Page 1 of 1											

Flow chart















 NFC Antenna process flow chart		
Model : F2096		
Process description	process flow chart	note
Incoming inspection		
Put in storage		
Prepare raw materials		
Molded ferrite A		
appearance A		Inspect the appearance of the mold slice
Molded ferrite B		
appearance B		Inspect the appearance of the mold slice
Attach ferrite A		Positive side, ferrite is the outside surface
Attach ferrite B		Positive side, ferrite is the outside surface
pressing		Rolling
Peel the film		
Electrical test		LCR test
appearance		Inspect the appearance of the finished product
Point bagging		Open mouth PE bag, 50pcs/bag
packaging		
Stock in		
Process Identifier: Production process Inspection process Stock in Preparation process		

Table number: F-023-085B

Packaging method

Document number		File name	Approval	Audit	Make
HDT-25-02-15		F2096 Packaging Specification		-	HuZhengtian 2025/2/24
Effective date: 2025/2/24					
			Product part number	TFPA02F20960011	
1: Single-piece shipment or other		Figure 2: Bag packaging method	Product name	NFC-F2096 Finished product (Z) black	
			packaging method	Opening bag+inner box+outer box	
Figure 3: Packaging inner box (250*185*33mm)		Figure 4: Arrangement of boxes (Tape the box with transparent tape)	Bagged	Quantity	50PCS/bag
			Inner box	Number of layers	6 rows*5 columns; 30 bags total 1500 pcs
Box placement form inside the		Figure 6: Outer box shipping label	Outer box	Number of inner boxes	2 boxes * 5 layers, 15Kpcs
			Note		
			1. Products judged as OK by QC shall be placed neatly in an open bag, with each 50 pieces as a unit, and the bag should be tied tightly;		
			2. Fill the inner box with 6 bags * 5 columns, a total of 30 bags with 1500 pieces;		
			3. The shipping label (material code, material name, supplier name, quantity, production date, etc.), RoHS label, and weight label shall be attached to the surface of the inner box;		
			4. The actual shipping label on the outer box shall be subject to the format and content required by the customer;		
			5. If the quantity is less than one open bag or one inner box, it shall be packed according to the original packaging of one open bag or one box, and if the quantity is less than one box, it shall be placed according to the actual number of boxes, and the remaining space shall be filled with foam or bubble bags and sealed with tape;		
			6. Seal the carton with tape in the shape		
			Storage conditions	Temperature: 10-30° C; Humidity: 30-70% RH Room temperature and humidity, avoid direct.	
Figure 7: Packaging outer box (NFC blank carton, sealed with transparent tape)		Figure 8: Outer box with shipping label, RoHS label, weight label	Validity period	Production date 6 month	
henzhen Hydemen Electronics Co., Ltd.					

Environmental Information

Deman							版本: A																						
表格编号							环境有害物质符合性清单																						
F2096-NFC																													
供应商	物料种类	项目	零件名称	零件供应商	均质材料名称	材料重量 (mg)	物质名称	CAS No	物质重量 (mg)	物质含量 (%)	限用物质含量PPM (ROHS 2.0/卤素)																		
											测试机构	报告编号	测试日期	有效日期	Pb <90	Cd <5	Hg <5	Cr6 + <10	PBB 0	PBD E 0	DEH P <10	BBP <10	DBP <10	DIB P <10	Cl <500	Br <500	Cl+Br <900		
FPC	F2096-NFC		基材	锦荣	半对半双面电解铜	67.1	Polyimide Film	25038-81-7	12.51	18.64%	CTI	A2240123200101001E	2024/3/15	2025/3/14	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND		
							Electrode Posited copper	7440-50-8	39.16	58.36%																			
							Epoxy Resin	25036-25-3	5.96	8.88%																			
							CTBN	9003-18-3	5.21	7.76%																			
							AIH3O3	21645-51-2	4.27	6.36%																			
			背胶	晶华	MTM303	30.5	PET	25038-59-9	27.45	90.00%	CTI	A224078050710100208C	2024/12/16	2025/12/15	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
							Acrylate Copolymer Adhesive	Trade Secret	3.05	10.00%																			
			阻焊油墨	优力	PSM-800FSMBL6	18.3	環氧丙烯酸酯基聚物	28064-14-4	8.42	46.00%	SGS	ETR24600712 ETR24600713	2024/6/14	2025/6/13	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	450	ND	ND
							二氧化矽	7631-86-9	2.47	13.50%																			
							芳香族溶剂	64742-94-5	0.92	5.00%																			
							二丙二醇甲基醚	34590-94-8	0.92	5.00%																			
							碳黑	1333-86-4	0.73	4.00%																			
							硫酸鋇 BaSO4	13462-86-7	4.58	25.00%																			
			字符油墨	高仕	白油UM-300 WMI1	3.66	光敏剂及其它	5495-84-1	0.27	1.50%	CTI	A2240363801101001E A2240363801101004E	2024/6/26	2025/6/25	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
							丙烯酸单体	13048-33-4	3.26	89.00%																			
							钛白粉	13463-67-7	0.37	10.00%																			
			镍/金	博永凯	镍/金	2.44	银	7440-02-0	2.32	95.00%	CTI	A2240634006101005E	2024/10/22	2025/10/21	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND	ND
							金	7440-57-5	0.12	5.00%																			



F2096-NFC环保报告.zip