

FCC RADIO TEST REPORT

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment	: PDA Scanner
Model No.	: PA600BTG
Brand Name	: Unitech
Filing Type	: New Application
Applicant	: Unitech Co., Ltd. 3F, No.236, Sinhu 2 nd Rd., Neihu Chiu, Taipei, Taiwan114, R.O.C.
FCC ID	: HLEPA600BTG
Manufacturer	: Unitech Co., Ltd. 5F, No.136, Lan 235, Pao-Chiao Rd., Hsin-Tien City, Taipei Hsien, Taiwan, R.O.C.
Received Date	: Nov. 24, 2006
Test Date	: Mar. 30, 2007
Multiple Listing	: Please refer to section 2.7

Statement

Test result included is only for the 802.11b/g part of the product (collocated with Bluetooth).

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.4-2003** and **47 CFR FCC Part 15 Subpart C**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



SPORTON International Inc.

Lab Code: 200079-0

6F, No. 106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

SPORTON International Inc.

Report Format Version: 2007-4-12

Table of Contents

1. SUMMARY OF THE TEST RESULT	2
2. GENERAL INFORMATION.....	3
2.1. Product Details	3
2.2. Accessories	3
2.3. Table for Filed Antenna	3
2.4. Table for Carrier Frequencies	3
2.5. Table for Test Modes	4
2.6. Table for Testing Locations	4
2.7. Table for Multiple Listing	5
2.8. Table for Supporting Units.....	6
2.9. Table for Parameters of Test Software Setting	6
2.10. Test Configurations	7
3. TEST RESULT	8
3.1. AC Power Line Conducted Emissions Measurement.....	8
3.2. Maximum Peak Output Power Measurement.....	12
3.3. Power Spectral Density Measurement.....	14
3.4. 6dB Spectrum Bandwidth Measurement.....	19
3.5. Radiated Emissions Measurement.....	24
3.6. Band Edge Emissions Measurement	42
3.7. Antenna Requirements.....	47
4. LIST OF MEASURING EQUIPMENTS	48
5. TEST LOCATION.....	49
6. NVLAP CERTIFICATE OF ACCREDITATION.....	50
APPENDIX A. TEST PHOTOS	A1 ~ A5
APPENDIX B. PHOTOGRAPHS OF EUT	B1 ~ B34

History of This Test Report

Original Issue Date: Apr. 12, 2007

Report No.: FR6N2315-02

☒ No additional attachment.

☐ Additional attachment were issued as following record:

Attachment No.	Issue Date	Description

CERTIFICATE OF COMPLIANCE

according to

47 CFR FCC Part 15 Subpart C § 15.247

Equipment : PDA Scanner
Model No. : PA600BTG
Brand Name : Unitech
Applicant : **Unitech Co., Ltd.**
3F, No.236, Sinhu 2nd Rd., Neihu Chiu, Taipei, Taiwan114,
R.O.C.

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Nov. 24, 2006 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.



Wayne Hsu

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

1. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
3.1	15.207	AC Power Line Conducted Emissions	Complies	7.28 dB
3.2	15.247(b)(3)	Maximum Peak Conducted Output Power	Complies	20.82 dB
3.3	15.247(e)	Power Spectral Density	Complies	22.22 dB
3.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
3.5	15.247(d)	Radiated Emissions	Complies	3.04 dB
3.6	15.247(d)	Band Edge Emissions	Complies	7.59 dB
3.7	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Maximum Peak Conducted Output Power	±0.8dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
6dB Spectrum Bandwidth	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

2. GENERAL INFORMATION

2.1. Product Details

EUT is a PDA Scanner with IEEE 802.11b/g and Bluetooth radio function. Only the radio detail of WLAN is shown in the table below. For more detailed features description, please refer to the manufacturer's specifications or user's manual.

Items	Description
Power Type	5V DC from adapter; 3.7V DC from battery
Modulation	DSSS for IEEE 802.11b ; OFDM for IEEE 802.11g
Data Modulation	DSSS (BPSK / QPSK / CCK) ; OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	DSSS (1/ 2/ 5.5/11) ; OFDM (6/9/12/18/24/36/48/54)
Frequency Range	2400 ~ 2483.5MHz
Channel Number	11
Channel Band Width (99%)	11b: 13.78 MHz ; 11g: 16.60 MHz
Conducted Output Power	11b: 9.18 dBm ; 11g: 2.16 dBm

2.2. Accessories

Power	Brand	Model	Rating
Adapter 1	ENG	3A-181WP05	INPUT: 100-240V AC OUTPUT: 5V DC
Li-ion Battery	-	HNP-120	3.7V DC
Others			
Cradle / Earphone / Charging Cables			

2.3. Table for Filed Antenna

Ant.	Antenna Type	Connector	Gain (dBi)
1	PIFA Antenna	UFL	-3.10

2.4. Table for Carrier Frequencies

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
2400~2483.5MHz	1	2412 MHz	7	2442 MHz
	2	2417 MHz	8	2447 MHz
	3	2422 MHz	9	2452 MHz
	4	2427 MHz	10	2457 MHz
	5	2432 MHz	11	2462 MHz
	6	2437 MHz		

2.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	WLAN Antenna
AC Power Line Conducted Emissions	Mode 1	-	-	1
Maximum Peak Conducted Output Power Power Spectral Density 6dB Spectrum Bandwidth	11b/CCK	1 Mbps	1/6/11	NA
	11g/BPSK	6 Mbps	1/6/11	NA
Radiated Emissions 9kHz~1GHz	BT+ 802.11bg	1 Mbps / 6 Mbps	6	1
Radiated Emissions 1GHz~10 th Harmonic	802.11b on	1 Mbps	1/6/11	1
	BT on	1 Mbps	0/39/78	
	802.11g on	6 Mbps	1/6/11	1
	BT on	1 Mbps	0/39/78	
Band Edge Emissions	802.11b on	1 Mbps	1/11	1
	BT on	1 Mbps	0/78	
	802.11g on	6 Mbps	1/11	1
	BT on	1 Mbps	0/78	

When measuring the radiated spurious emission of WLAN function, the Bluetooth function was turned on to evaluate the collocation effect.

For EMI test, the following modes were pre-scanned:

Mode 1. BT Link +Auto Scan +Charging + Earphone + Scanner only

Mode 2. BT Link +Auto Scan +Charging + Earphone + USB Link + Scanner only

Mode 3. BT Link +Auto Scan +Charging +Adapter + Cradle + Earphone + SD Card Play MP3

Mode 4. BT Link +Auto Scan +Charging +Adapter + Cradle + Earphone + USB Link + SD Card Play MP3

Conducted-Cause "mode 1" generated the worst test result; it was reported as final data.

2.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.	VCCI Reg. No
03CH03-HY	SAC	Hwa Ya	101377	IC 4088	-
CO02-LK	Conduction	Lin Kou	93596	IC 4087	-
TH01-HY	OVEN Room	Hwa Ya	-	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC); Fully Anechoic Chamber (FAC).

2.7. Table for Multiple Listing

The model names in the following table are all refer to the identical product.

Model No.		Description	Remark 1	Remark 2	
1	PA600-066ADG	PA600 w/o engine, 128MB, 64MB, Com. BTRF, Mobile 5.0 ENG, Disbributor Package, Green Product	W/O Engineer	Mobile, BT+WiFi	
2	PA600-066CDG	PA600 w/o engine, 128MB, 64MB, Com. BTRF, Mobile 5.0 Sim-CHT, Disbributor Package, Green Product			
3	PA600-066JDG	PA600 w/o engine, 128MB, 64MB, Com. BTRF, Mobile 5.0 JPN, Disbributor Package, Green Product			
4	PA600-066TDG	PA600 w/o engine, 128MB, 64MB, Com. BTRF, Mobile 5.0 TRI-CHT, Disbributor Package, Green Product			
5	PA600-966ADG	PA600 w/laser engine, 128MB, 64MB, Com. BTRF, Mobile 5.0 ENG, Disbributor Package, Green Product	W/laser Engineer		
6	PA600-966CDG	PA600 w/laser engine, 128MB, 64MB, Com. BTRF, Mobile 5.0 Sim-CHT, Disbributor Package, Green Product			
7	PA600-966JDG	PA600 w/laser engine, 128MB, 64MB, Com. BTRF, Mobile 5.0 JPN, Disbributor Package, Green Product			
8	PA600-966TDG	PA600 w/laser engine, 128MB, 64MB, Com. BTRF, Mobile 5.0 TRI-CHT, Disbributor Package, Green Product			
9	PA600-056ADG	PA600 w/o engine, 128MB, 64MB, Com. BTRF, WinCE 5.0 ENG, Disbributor Package, Green Product	W/O Engineer	WinCE, BT+WiFi	
10	PA600-056CDG	PA600 w/o engine, 128MB, 64MB, Com. BTRF, WinCE 5.0 Sim-CHT, Disbributor Package, Green Product			
11	PA600-056JDG	PA600 w/o engine, 128MB, 64MB, Com. BTRF, WinCE 5.0 JPN, Disbributor Package, Green Product			
12	PA600-056TDG	PA600 w/o engine, 128MB, 64MB, Com. BTRF, WinCE 5.0 TRI-CHT, Disbributor Package, Green Product			
13	PA600-956ADG	PA600 w/laser engine, 128MB, 64MB, Com. BTRF, WinCE 5.0 ENG, Disbributor Package, Green Product	W/laser EGINEER		
14	PA600-956CDG	PA600 w/laser engine, 128MB, 64MB, Com. BTRF, WinCE 5.0 Sim-CHT, Disbributor Package, Green Product			
15	PA600-956JDG	PA600 w/laser engine, 128MB, 64MB, Com. BTRF, WinCE 5.0 JPN, Disbributor Package, Green Product			
16	PA600-956TDG	PA600 w/laser engine, 128MB, 64MB, Com. BTRF, WinCE 5.0 TRI-CHT, Disbributor Package, Green Product			
Remark 3 : A - English, C - Simplified Chinese, J - Japanese, T - Taiwanese					

2.8. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Modem	ACEEX	DM1414	IFAXDM1414
PS/2 Mouse	COMPAQ	M-S69	-
PS/2 Keyboard	COMPAQ	6511-VA	-
CRT Monitor	COMPAQ	S510	-
Printer	HP	DJ 400	B94C2642X
USB Keyboard	BTC	7932	-
Personal Computer	COMPAQ	Evo D380mx	-
SD Card	PQI	-	-
GSM Phone (Remote Workstation)	Sony Ericsson	W800i	PY7-A1022013
Notebook (Remote Workstation)	DELL	PP01L	DOC
Earphone	Provide by customer		

2.9. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11b/g

Test Software Version	Marvell		
Frequency	2412 MHz	2437 MHz	2462 MHz
IEEE 802.11b	13	13	13
IEEE 802.11g	13	13	13

<EMI>--For PC

Two executive programs, EMCTEST.EXE & EMITEST.EXE under WIN XP, which generate a complete line of continuously repeating " H " pattern were used as the test software.

The programs were executed as follows :

- Turn on the power of all equipment.
- The PC reads the test program from the hard disk drive and runs it.
- The PC sends " H " messages to the monitor, and the monitor displays " H " patterns on the screen.
- The PC sends " H " messages to the printer, then the printer prints them on the paper.
- The PC sends " H " messages to the modem.
- The PC sends " H " messages to the internal Hard Disk, and the Hard Disk reads and writes the message.
- Repeat the steps from c to f.

At the same time, the following programs were executed:

Executed "Active Sync" to link with the EUT to receive data by USB cable.


Executed "Media player" to play music.

--For EUT


During the test, the EUT executed "Bluetooth.test" under WIN CE to link with the remote workstation transmit data via wireless.

2.10. Test Configurations

2.10.1. Radiation Emissions Test Configuration



2.10.2. Conduction Emissions Test Configuration



3. TEST RESULT

3.1. AC Power Line Conducted Emissions Measurement

3.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

3.1.2. Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

3.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.4. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

3.1.5. Test Deviation


There is no deviation with the original standard.

3.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


3.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	23	Humidity	51%
Test Engineer	Josh	Phase	Line
Configuration	Mode1		



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	LISN Factor	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.156	48.44	-17.23	65.67	38.37	0.06	10.01	QP
2	0.156	35.17	-20.50	55.67	25.10	0.06	10.01	Average
3	0.213	43.06	-20.03	63.09	32.94	0.10	10.02	QP
4	0.213	32.04	-21.05	53.09	21.92	0.10	10.02	Average
5	0.379	20.80	-27.50	48.30	10.67	0.10	10.03	Average
6	0.379	30.58	-27.72	58.30	20.45	0.10	10.03	QP
7	0.683	40.12	-15.88	56.00	29.98	0.10	10.04	QP
8	0.683	38.72	-7.28	46.00	28.58	0.10	10.04	Average
9	1.260	36.90	-9.10	46.00	26.71	0.13	10.06	Average
10	1.260	38.74	-17.26	56.00	28.55	0.13	10.06	QP
11	2.563	36.44	-19.56	56.00	26.17	0.20	10.07	QP
12	2.563	31.13	-14.87	46.00	20.86	0.20	10.07	Average

Temperature	23	Humidity	51%
Test Engineer	Josh	Phase	Neutral
Configuration	Mode1		



	Freq	Level	Over Limit	Limit Line	Read Level	Cable Loss	LISN Factor	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.164	47.39	-17.87	65.26	37.28	0.07	10.04	QP
2	0.164	34.74	-20.52	55.26	24.63	0.07	10.04	Average
3	0.216	42.35	-20.62	62.97	32.17	0.10	10.08	QP
4	0.216	31.04	-21.93	52.97	20.86	0.10	10.08	Average
5	0.377	30.63	-27.72	58.35	20.39	0.10	10.14	QP
6	0.377	23.55	-24.80	48.35	13.31	0.10	10.14	Average
7	0.866	27.80	-28.20	56.00	17.45	0.10	10.25	QP
8	0.866	17.05	-28.95	46.00	6.70	0.10	10.25	Average
9	1.430	31.23	-24.77	56.00	20.77	0.15	10.31	QP
10	1.430	26.11	-19.89	46.00	15.65	0.15	10.31	Average
11	2.550	32.36	-23.64	56.00	21.78	0.20	10.38	QP
12	2.550	25.71	-20.29	46.00	15.13	0.20	10.38	Average

Note:

Level = Read Level + LISN Factor + Cable Loss.

3.2. Maximum Peak Output Power Measurement

3.2.1. Limit

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. The limited has to be reduced by the amount in dB that the gain of the antenna exceed 6dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2. Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Filter No.	Auto
Measurement time	0.135 s ~ 26 s
Used Peak Sensor	NRV-Z32 (model 04)

3.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Turn on the EUT and power meter and then record the peak power value.
3. Repeat above procedures on all channels needed to be tested.

3.2.4. Test Setup Layout



3.2.5. Test Deviation

There is no deviation with the original standard.

3.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.2.7. Test Result of Maximum Peak Output Power

Temperature	26.8	Humidity	54%
Test Engineer	Murphy	Configurations	802.11b/g

Configuration IEEE 802.11b

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	7.59	30.00	Complies
6	2437 MHz	8.71	30.00	Complies
11	2462 MHz	9.18	30.00	Complies

Configuration IEEE 802.11g

Channel	Frequency	Conducted Power (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	2.16	30.00	Complies
6	2437 MHz	1.82	30.00	Complies
11	2462 MHz	1.94	30.00	Complies

3.3. Power Spectral Density Measurement

3.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

3.3.2. Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	1.5MHz
RB	3 kHz
VB	30 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	500s

3.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser.
2. Set RBW of spectrum analyzer to 3kHz and VBW to 30kHz. Set Detector to Peak, Trace to Max Hold.
3. Mark the frequency with maximum peak power as the center of the display of the spectrum.
4. Set the span to 1.5MHz and the sweep time to 500s and record the maximum peak value.

3.3.4. Test Setup Layout



3.3.5. Test Deviation

There is no deviation with the original standard.

3.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.3.7. Test Result of Power Spectral Density

Temperature	26.8	Humidity	54%
Test Engineer	Murphy	Configurations	802.11b/g


Configuration IEEE 802.11b

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-21.90	8.00	Complies
6	2437 MHz	-20.84	8.00	Complies
11	2462 MHz	-19.62	8.00	Complies

Configuration IEEE 802.11g

Channel	Frequency	Power Density (dBm)	Max. Limit (dBm)	Result
1	2412 MHz	-14.49	8.00	Complies
6	2437 MHz	-14.57	8.00	Complies
11	2462 MHz	-14.22	8.00	Complies


Power Density Plot on Configuration IEEE 802.11b / 2412 MHz



1

Date: 30.MAR.2007 16:18:22


Power Density Plot on Configuration IEEE 802.11b / 2437 MHz



1

Date: 30.MAR.2007 16:02:46


Power Density Plot on Configuration IEEE 802.11b / 2462 MHz



1

Date: 30.MAR.2007 15:53:21


Power Density Plot on Configuration IEEE 802.11g / 2412 MHz



1

Date: 30.MAR.2007 14:17:19


Power Density Plot on Configuration IEEE 802.11g / 2437 MHz



1

Date: 30.MAR.2007 15:17:05

Power Density Plot on Configuration IEEE 802.11g / 2462 MHz



1

Date: 30.MAR.2007 15:35:40

3.4. 6dB Spectrum Bandwidth Measurement

3.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

3.4.2. Measuring Instruments and Setting


Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RB	100 kHz
VB	100 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

3.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.
2. The resolution bandwidth of 100 kHz and the video bandwidth of 100 kHz were used.
3. Measured the spectrum width with power higher than 6dB below carrier.

3.4.4. Test Setup Layout



3.4.5. Test Deviation

There is no deviation with the original standard.

3.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	26.8	Humidity	54%
Test Engineer	Murphy	Configurations	802.11b/g


Configuration IEEE 802.11b

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	10.06	13.78	500	Complies
6	2437 MHz	10.06	13.78	500	Complies
11	2462 MHz	10.06	13.75	500	Complies

Configuration IEEE 802.11g

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
1	2412 MHz	15.83	16.60	500	Complies
6	2437 MHz	16.28	16.60	500	Complies
11	2462 MHz	16.28	16.60	500	Complies


6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2412 MHz



1

Date: 30.MAR.2007 16:13:44


6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2437 MHz



1

Date: 30.MAR.2007 16:07:25


6 dB Bandwidth Plot on Configuration IEEE 802.11b / 2462 MHz



1

Date: 30.MAR.2007 15:47:43


6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2412 MHz



1

Date: 30.MAR.2007 13:50:05


6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2437 MHz



1

Date: 30.MAR.2007 15:20:59

6 dB Bandwidth Plot on Configuration IEEE 802.11g / 2462 MHz



1

Date: 30.MAR.2007 15:29:31

3.5. Radiated Emissions Measurement

3.5.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2. Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100KHz / 100KHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

3.5.4. Test Setup Layout

For radiated emissions below 30MHz



For radiated emissions above 30MHz



Above 10 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor [9.54 dB].

3.5.5. Test Deviation

There is no deviation with the original standard.

3.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	23	Humidity	55%
Test Engineer	Vic		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

3.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	23	Humidity	55%
Test Engineer	Vic	Configurations	BT+ 802.11g

Horizontal



	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant. Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	97.900	29.14	-14.36	43.50	44.81	10.86	1.32	27.85	Peak	---	---
2	175.500	37.65	-5.85	43.50	54.10	9.38	2.19	28.02	Peak	---	---
3	288.020	41.01	-4.99	46.00	53.47	13.37	2.71	28.54	Peak	---	---
4	335.550	39.43	-6.57	46.00	50.28	14.67	3.27	28.79	Peak	---	---
5	420.910	43.20	-2.80	46.00	51.36	17.26	3.51	28.94	QP	---	---
6	451.950	42.41	-3.59	46.00	50.90	17.15	3.67	29.30	Peak	---	---

Vertical



	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp			Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Remark	Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	97.900	33.37	-10.13	43.50	49.04	10.86	1.32	27.85	Peak	---	---
2	175.500	31.94	-11.56	43.50	48.39	9.38	2.19	28.02	Peak	---	---
3	288.020	34.91	-11.09	46.00	47.37	13.37	2.71	28.54	Peak	---	---
4	462.620	42.96	-3.04	46.00	51.33	17.37	3.72	29.46	Peak	---	---
5	648.860	37.05	-8.95	46.00	42.99	19.62	4.51	30.07	Peak	---	---
6	912.700	34.81	-11.19	46.00	38.29	21.11	5.35	29.94	Peak	---	---

Note:


The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.


3.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	23	Humidity	55%
Test Engineer	Vic	Configurations	BT Ch0 +802.11b Ch01

Horizontal


	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant. Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4824.000	47.97	-26.03	74.00	42.87	33.09	4.34	32.32	PEAK	---	---
2	7236.000	51.51	-22.49	74.00	42.92	35.98	5.18	32.57	PEAK	---	---
3	9652.000	54.15	-19.85	74.00	41.93	38.58	6.43	32.80	PEAK	---	---

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4824.000	46.22	-27.78	74.00	41.11	33.09	4.34	32.32	PEAK	---	---
2	7236.000	50.85	-23.15	74.00	42.25	35.98	5.18	32.57	PEAK	---	---
3	9648.000	54.16	-19.84	74.00	41.95	38.58	6.43	32.80	PEAK	---	---

Temperature	23	Humidity	55%
Test Engineer	Vic	Configurations	BT Ch39 +802.11b Ch06

Horizontal


	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp			Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Remark	Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4874.000	46.88	-27.12	74.00	41.62	33.18	4.38	32.30	PEAK	---	---
2	7311.000	50.65	-23.35	74.00	41.80	36.14	5.29	32.59	PEAK	---	---
3	9744.000	54.00	-20.00	74.00	41.45	38.73	6.61	32.80	PEAK	---	---

Vertical




	Freq	Level	Over	Limit	Read&antenna	Cable	Preamp		Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	4874.000	45.31	-28.69	74.00	40.05	33.18	4.38	32.30	PEAK	---
2	7307.000	50.97	-23.03	74.00	42.13	36.14	5.29	32.59	PEAK	---
3	9740.000	54.01	-19.99	74.00	41.46	38.73	6.61	32.80	PEAK	---

Temperature	23	Humidity	55%
Test Engineer	Vic	Configurations	BT Ch78 +802.11b Ch011

Horizontal


	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp			Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Remark	Pos	Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4924.000	46.58	-27.42	74.00	41.19	33.28	4.39	32.28	PEAK	---	---
2	7382.000	50.25	-23.75	74.00	41.16	36.31	5.41	32.63	PEAK	---	---
3	9852.000	54.61	-19.39	74.00	41.66	38.95	6.78	32.79	PEAK	---	---

Vertical




	Freq	Level	Over	Limit	Read&Antenna	Cable	Preamp			Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Remark	Pos	Pos
			dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4928.000	46.16	-27.84	74.00	40.77	33.28	4.39	32.28	PEAK	---	---
2	7386.000	49.55	-24.45	74.00	40.42	36.35	5.41	32.63	PEAK	---	---
3	9848.000	54.03	-19.97	74.00	41.18	38.92	6.73	32.79	PEAK	---	---

Temperature	23	Humidity	55%
Test Engineer	Vic	Configurations	BT Ch0 +802.11g Ch01

Horizontal


	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4824.000	45.74	-28.26	74.00	40.63	33.09	4.34	32.32	Peak	---	---
2	7232.000	51.25	-22.75	74.00	42.64	35.98	5.18	32.55	PEAK	---	---
3	9648.000	54.94	-19.06	74.00	42.72	38.58	6.43	32.80	PEAK	---	---

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4824.000	44.89	-29.11	74.00	39.78	33.09	4.34	32.32	PEAK	---	---
2	7232.000	50.55	-23.45	74.00	41.95	35.98	5.18	32.55	PEAK	---	---
3	9652.000	54.38	-19.62	74.00	42.16	38.58	6.43	32.80	PEAK	---	---

Temperature	23	Humidity	55%
Test Engineer	Vic	Configurations	BT Ch39 +802.11g Ch06

Horizontal


	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp		Ant	Table
	MHz	dBUV/m	Limit	Line	Level	Factor	Loss	Factor	Pos	Pos
	MHz	dBUV/m	dB	dBUV/m	dBuV	dB/m	dB	dB	cm	deg
1	4924.000	45.87	-28.13	74.00	40.48	33.28	4.39	32.28	Peak	---
2	7311.000	49.72	-24.28	74.00	40.88	36.14	5.29	32.59	PEAK	---
3	9748.000	54.35	-19.65	74.00	41.77	38.77	6.61	32.80	PEAK	---

Vertical




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4878.000	45.48	-28.52	74.00	40.22	33.18	4.38	32.30	PEAK	---	---
2	7311.000	50.53	-23.47	74.00	41.68	36.14	5.29	32.59	PEAK	---	---
3	9748.000	54.04	-19.96	74.00	41.46	38.77	6.61	32.80	PEAK	---	---

Temperature	23	Humidity	55%
Test Engineer	Vic	Configurations	BT Ch78 +802.11g Ch11

Horizontal

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp			Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	Remark	Pos	Pos
			dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	4924.000	45.88	-28.12	74.00	40.49	33.28	4.39	32.28	Peak	---	---
2	7382.000	49.97	-24.03	74.00	40.89	36.31	5.41	32.63	PEAK	---	---
3	9852.000	54.51	-19.49	74.00	41.56	38.95	6.78	32.79	PEAK	---	---

Vertical

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	4924.000	45.71	-28.29	74.00	40.32	33.28	4.39	32.28	PEAK	---
2	7386.000	49.93	-24.07	74.00	40.80	36.35	5.41	32.63	PEAK	---
3	9844.000	54.29	-19.71	74.00	41.43	38.92	6.73	32.79	PEAK	---

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

3.6. Band Edge Emissions Measurement

3.6.1. Limit

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.6.2. Measuring Instruments and Setting

Please refer to section 4 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 1MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	100 KHz /100 KHz for Peak

3.6.3. Test Procedures

1. The test procedure is the same as section 3.5.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

3.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 3.5.4.

3.6.5. Test Deviation

There is no deviation with the original standard.

3.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

3.6.7. Test Result of Band Edge and Fundamental Emissions

Temperature	26.8	Humidity	54%
Test Engineer	Murphy	Configurations	BT Ch0, Ch78 + 802.11b Ch1, Ch11

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2357.500	57.11	-16.89	74.00	26.10	28.22	2.79	0.00	Peak	---	---
2 #	2410.890	100.42				28.33	2.81	0.00	Peak	---	---
1	2357.500	46.41	-7.59	54.00	15.40	28.22	2.79	0.00	Average	---	---
2 @	2410.890	96.63				28.33	2.81	0.00	Average	---	---

Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamplifier	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 #	2461.050	99.86				28.43	2.85	0.00	Peak	---	---
2	2483.500	56.17	-17.83	74.00	24.85	28.47	2.85	0.00	Peak	---	---
1 @	2461.050	96.19				28.43	2.85	0.00	Average	---	---
2	2483.500	44.77	-9.23	54.00	13.45	28.47	2.85	0.00	Average	---	---

Temperature	26.8	Humidity	54%
Test Engineer	Murphy	Configurations	BT Ch0, Ch78 + 802.11g Ch1, Ch11

Channel 1

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1	2390.000	56.46	-17.54	74.00	25.36	28.29	2.81	0.00	Peak	---	---
2 #	2413.930	94.31				28.33	2.81	0.00	Peak	---	---
1	2390.000	44.84	-9.16	54.00	13.74	28.29	2.81	0.00	Average	---	---
2 @	2418.300	87.72				28.33	2.81	0.00	Average	---	---

Channel 11

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 #	2464.090	94.72				28.43	2.85	0.00	Peak	---	---
2	2483.500	56.24	-17.76	74.00	24.92	28.47	2.85	0.00	Peak	---	---
1 @	2468.460	88.08				28.43	2.85	0.00	Average	---	---
2	2483.500	44.64	-9.36	54.00	13.32	28.47	2.85	0.00	Average	---	---


Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

For Emission not in Restricted Band


Low Band Edge Plot on Configuration IEEE 802.11b / 2412 MHz



1

Date: 30.MAR.2007 16:16:24


High Band Edge Plot on Configuration IEEE 802.11b / 2462 MHz



1

Date: 30.MAR.2007 15:50:45


Low Band Edge Plot on Configuration IEEE 802.11g / 2412 MHz



1

Date: 30.MAR.2007 13:53:06

High Band Edge Plot on Configuration IEEE 802.11g / 2462 MHz



1

Date: 30.MAR.2007 15:32:28

3.7. Antenna Requirements

3.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

3.7.2. Antenna Connector Construction

Please refer to section 2.3 in this test report; antenna connector complied with the requirements.

4. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Receiver	R&S	ESCS 30	100168	9 kHz - 2.75 GHz	Dec. 15, 2006	Conduction (CO02-LK)
LISN	Schaffner	NNB-41	06/10024	9 kHz - 30 MHz	May. 11, 2006	Conduction (CO02-LK)
RF Cable-CON	Suhner Switzerland	RG223/U	CB018	9 kHz - 30 MHz	Nov. 15, 2006	Conduction (CO02-LK)
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Dec. 17, 2006	Conducted (TH01-HY)
Power Meter	R&S	NRVS	100764	DC ~ 40GHz	Jul. 20, 2006	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z51	100666	DC ~ 40GHz	Jul. 20, 2006	Conducted (TH01-HY)
Power Sensor	R&S	NRV-Z32	100057	30MHz ~ 6GHz	Jun. 10, 2006	Conducted (TH01-HY)
DC Power Source	G.W.	GPC-6030D	C671845	DC 1V ~ 60V	Mar. 03, 2007	Conducted (TH01-HY)
Temp. and Humidity Chamber	KSON	THS-C3L	612	N/A	Oct. 02, 2006	Conducted (TH01-HY)
RF CABLE-1m	Jye Bao	RG142	CB034-1m	20MHz ~ 7GHz	Dec. 01, 2006	Conducted (TH01-HY)
RF CABLE-2m	Jye Bao	RG142	CB035-2m	20MHz ~ 1GHz	Dec. 01, 2006	Conducted (TH01-HY)
Oscilloscope	Tektronix	TDS1012	CO38515	100MHz / 1GS/s	Jun. 20, 2006	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Mar. 07, 2007	Conducted (TH01-HY)
Data Generator	Tektronix	DG2030	063-2920-50	0.1Hz~400MHz	Jun. 16, 2006	Conducted (TH01-HY)
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30 MHz - 1 GHz 3m	Jun. 15, 2006	Radiation (03CH03-HY)
Amplifier	SCHAFFNER	CPA9231A	1886	9 kHz - 2 GHz	Jan. 22, 2007	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1 GHz - 26.5 GHz	May 29, 2006	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP40	100004/040	9 kHz - 40 GHz	Sep. 21, 2006	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30 MHz - 1 GHz	Jul. 24, 2006	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	Apr. 27, 2006	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15 GHz - 40 GHz	NCR	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30 MHz - 1 GHz	Dec. 02, 2006	Radiation (03CH03-HY)
RF Cable-HIGH	SUHNER	SUCOFLEX 106	03CH03-HY	1 GHz - 40 GHz	Dec. 02, 2006	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 - 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is one year. NCR: Non-Calibration required.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
AC Power Source	HPC	HPA-500W	HPA-9100024	AC 0 ~ 300V	Apr. 21, 2005*	Conducted (TH01-HY)
Amplifier	MITEQ	AMF-6F-260400	923364	26.5 GHz - 40 GHz	Jan. 22, 2007*	Radiation (03CH03-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz - 30 MHz	May 23, 2006*	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is two year.

5. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

6. NVLAP CERTIFICATE OF ACCREDITATION

United States Department of Commerce
National Institute of Standards and Technology

NVLAP[®]

Certificate of Accreditation to ISO/IEC 17025:2005

NVLAP LAB CODE: 200079-0

Sporton International, Inc. Hwa Ya EMC Laboratory
Tao Yuan Hsien 333
TAIWAN


*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,
listed on the Scope of Accreditation, for:*

ELECTROMAGNETIC COMPATIBILITY AND TELECOMMUNICATIONS

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality
management system (refer to joint ISO-ILAC-IAF Communique dated 18 June 2005).*

2007-01-01 through 2007-12-31
Effective dates




For the National Institute of Standards and Technology

NVLAP-01C (REV. 2006-09-13)