

# TEST REPORT

For

**Wearable Data Terminal**

**Model Number: WD100**

**FCC ID: HLEWD100BTNL**

**Report Number : WT1188005271**

Test Laboratory : Shenzhen Academy of Metrology and Quality  
Inspection  
National Digital Electronic Product Testing Center  
Site Location : NETC Building, No.4 Tongfa Rd., Xili, Nanshan,  
Shenzhen, China  
Tel : 0086-755-86928965  
Fax : 0086-755-86009898-31396  
Web : [www.smq.com.cn](http://www.smq.com.cn)  
E-mail : [emcrf@smq.com.cn](mailto:emcrf@smq.com.cn)

## TEST REPORT DECLARATION

Applicant : unitech Electronics Co., LTD.

Address : 5F., No.136, Ln. 235, Baoqiao Rd., Xindian Dist., New Taipei City, Taiwan

Manufacturer : unitech Electronics Co., LTD.

Address : 5F., No.136, Ln. 235, Baoqiao Rd., Xindian Dist., New Taipei City, Taiwan

EUT Description : Wearable Data Terminal

Model No. : WD100

Trade mark : unitech

Serial Number : /


FCC ID : HLEWD100BTNL

### Test Standards:

### FCC Part 15 15.207, 15.209, 15.247(2016)

The EUT described above is tested by Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory to determine the maximum emissions from the EUT. Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory is assumed full responsibility for the accuracy of the test results.

The test report is valid for above tested sample only and shall not be reproduced in part without written approval of the laboratory.

Project Engineer:		Date:	Nov.14, 2018
	(Zhou Fangai 周芳媛)		
Checked by:		Date:	Nov.14, 2018
	(Lin Yixiang 林奕翔)		
Approved by:		Date:	Nov.14, 2018
	(Lin Bin 林斌)		

## TABLE OF CONTENTS

<b>TEST REPORT DECLARATION</b> .....	<b>2</b>
1. <b>TEST RESULTS SUMMARY</b> .....	<b>5</b>
2. <b>GENERAL INFORMATION</b> .....	<b>6</b>
2.1. Report information.....	6
2.2. Laboratory Accreditation and Relationship to Customer.....	6
2.3. Measurement Uncertainty .....	6
3. <b>PRODUCT DESCRIPTION</b> .....	<b>7</b>
3.1. EUT Description .....	7
3.2. Related Submittal(s) / Grant (s).....	7
3.3. Block Diagram of EUT Configuration .....	7
3.4. Operating Condition of EUT .....	7
3.5. Directional Antenna Gain .....	8
3.6. Support Equipment List.....	8
3.7. Test Conditions .....	8
3.8. Special Accessories .....	8
3.9. Equipment Modifications .....	8
4. <b>TEST EQUIPMENT USED</b> .....	<b>9</b>
5. <b>6DB BANDWIDTH MEASUREMENT</b> .....	<b>10</b>
5.1. LIMITS OF 6dB BANDWIDTH MEASUREMENT.....	10
5.2. TEST PROCEDURE .....	10
5.3. TEST SETUP .....	10
6. <b>MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT</b> .....	<b>12</b>
6.1. LIMITS OF Maximum Conducted Output Power Measurement.....	12
6.2. TEST PROCEDURE .....	12
6.3. TEST SETUP .....	12
6.4. TEST DATA .....	12
7. <b>MAXIMUM POWER SPECTRAL DENSITY LEVEL MEASUREMENT</b> .....	<b>14</b>
7.1. LIMITS OF Maximum Power Spectral Density Level Measurement.....	14
7.2. TEST PROCEDURE .....	14
7.3. TEST DATA .....	14
8. <b>CONDUCTED BANDEdge AND SPURIOUS MEASURMENT</b> .....	<b>16</b>
8.1. LIMITS OF Conducted Bandedge and Spurious Measurement.....	16
8.2. TEST PROCEDURE .....	16
8.3. TEST DATA .....	17
9. <b>RADIATED BANDEdge AND SPURIOUS MEASUREMENT</b> .....	<b>20</b>
9.1. LIMITS OF Radiated Bandedge and Spurious Measurement.....	20
9.2. TEST PROCEDURE .....	20
9.3. TEST DATA .....	20
10. <b>CONDUCTED EMISSION TEST FOR AC POWER PORT MEASUREMENT</b> .....	<b>39</b>
10.1. Test Standard and Limit .....	39
10.2. Test Procedure .....	39
10.3. Test Arrangement .....	39

10.4.	Test Data .....	39
<b>11.</b>	<b>ANTENNA REQUIREMENTS .....</b>	<b>43</b>
11.1.	Applicable requirements .....	43
11.2.	Antenna Connector.....	43
11.3.	Antenna Gain.....	43

## 1. TEST RESULTS SUMMARY

Table 1 Test Results Summary

Test Items	FCC Rules	Test Results
6dB DTS bandwidth measurement	15.247 (a) (2)	Pass
Maximum Peak Conducted Power	15.247 (b) (3)	Pass
Maximum Power Spectral Density Level	15.247 (3)	Pass
Conducted Bandedge and Spurious	15.247 (d)	Pass
Radiated Bandedge and Spurious	15.247 (d) 15.209 15.205	Pass
Conducted emission test for AC power port	15.207	Pass
Antenna Requirement	15.203	Pass

Remark: "N/A" means "Not applicable."

## 2. GENERAL INFORMATION

### 2.1. Report information

This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that SMQ approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that SMQ in any way guarantees the later performance of the product/equipment.

The sample/s mentioned in this report is/are supplied by Applicant, SMQ therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.

Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through SMQ, unless the applicant has authorized SMQ in writing to do so.

### 2.2. Laboratory Accreditation and Relationship to Customer

The testing report were performed by the Shenzhen Academy of Metrology and quality Inspection EMC Laboratory (Guangdong EMC compliance testing center), in their facilities located at NETC Building, No.4 Tongfa Rd., Xili, Nanshan, Shenzhen, China. At the time of testing, Laboratory is accredited by the following organizations:

China National Accreditation Service for Conformity Assessment (CNAS) accredits the Laboratory for conformance to FCC standards, EMC international standards and EN standards. The Registration Number is CNAS L0579.

The Laboratory is Accredited Testing Laboratory of FCC with Designation number CN1165 and Site registration number 582918.

The Laboratory is registered to perform emission tests with Innovation, Science and Economic Development (ISED), and the registration number is 11177A.

### 2.3. Measurement Uncertainty

Conducted Emission  
9 kHz~30MHz 2.9dB

Radiated Emission  
30MHz~1000MHz 5.1dB  
1GHz~6GHz 5.04dB  
6GHz~18GHz 5.54dB  
18GHz~26.5GHz 5.54dB

### 3. PRODUCT DESCRIPTION

#### 3.1. EUT Description

Description : Wearable Data Terminal  
Manufacturer : unitech Electronics Co., LTD.  
Model Number : WD100  
Operate Frequency : 2.402GHz~2.480GHz  
Antenna Designation : BT: PIFA ANTENNA -1.6dBi  
Operating voltage : 3.5V (Low)/3.7V (Nominal)/ 4.35V (Max)  
Software Version : SQ46W\_P1\_00AX\_YBUTE\_AU1616\_404\_R\_0\_181009\_01  
Hardware Version : V03  
Remark: --

Bluetooth Low Energy:

Table 2 Working Frequency List

Regulatory Range	RF Channels
2.400-2.4835 GHz	$f=2402+k*2$ MHz, $k=0, \dots, 39$

#### 3.2. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: **HLEWD100BTNL** filing to comply with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules.

#### 3.3. Block Diagram of EUT Configuration



Figure 1 EUT setup

#### 3.4. Operating Condition of EUT

Worst-case mode and channel used for 30-1000 MHz radiated and power line conducted emissions was the mode and channel with the highest output power.  
Worst-case data rates as provided by the client were:  
Bluetooth low energy

Test mode is configured to be with duty cycle >98%

### 3.5. Directional Antenna Gain

The EUT does NOT support a WIFI MIMO function.  
Directional gain need NOT to be considered.

### 3.6. Support Equipment List

Table 3 Support Equipment List

Name	Model No	S/N	Manufacturer
Adaptor for EUT	ZAU-A050150A-02	--	ShenZhen Zhongling Electronics Technology CO.,Ltd
Battery for EUT	HBLU2	--	ICON ENERGY SYSTEM(SHEN ZHEN) CO.,LTD.
USB for EUT	--	--	--
Earphone	--	--	--

### 3.7. Test Conditions

Date of test : Sep.06, 2018- Nov.07, 2018

Date of EUT Receive : Sep.04, 2018

Temperature: 18-25 °C

Relative Humidity: 42-51%

### 3.8. Special Accessories

Not available for this EUT intended for grant.

### 3.9. Equipment Modifications

Not available for this EUT intended for grant.

## 4. TEST EQUIPMENT USED

Table 4 Test Equipment

No.	Equipment	Manufacturer	Model No.	Last Cal.	Cal. Interval
SB2603	EMI Test Receiver	R&S	ESCS30	Mar.05,2018	1 Year
SB2604	AMN	R&S	ESH3-Z5	Mar.05,2018	1 Year
SB3436	EMI Test Receiver	R&S	ESI26	Nov.28,2017	1 Year
SB4538	ESI Test Receiver	R&S	ESI7	Mar.08,2018	1 Year
SB8501/15	Amplifier	R&S	SCU-03	Mar.09,2018	1 Year
SB9054/07	Broad-band Antenna	Schwarzbeck	VULB 9163	Jun.12,2018	1 Year
SB8501/04	Bilog Antenna	Schwarzbeck	VULB9163	Jun.12,2018	1 Year
SB3435	Horn Antenna	Rohde & Schwarz	HF906	Jan.02, 2018	1 Year
SB8501/01	Horn Antenna	Rohde & Schwarz	HF907	Mar.08,2018	1 Year
SB8501/11	Horn Antenna	ETS-Lindgren	3160-09	Mar.21,2017	3 Years
SB8501/12	Horn Antenna	ETS-Lindgren	3160-10	Mar.21,2017	3 Years
SB3345	Loop Antenna	Schwarzbeck	FMZB1516	Mar.22, 2017	2 Years
SB8501/14	Preamplifier	Rohde & Schwarz	SCU-03	Mar.08,2018	1 Year
SB8501/16	Preamplifier	Rohde & Schwarz	SCU-26	Mar.05,2018	1 Year
SB8501/17	Preamplifier	Rohde & Schwarz	SCU-18	Mar.05,2018	1 Year
SB12827/01	Power Sensor	Rohde & Schwarz	NRP-Z22	Jun.06, 2018	1 Year
SB11873/01	Power Sensor	Rohde & Schwarz	OSP120+OSP-B157	Feb.27, 2018	1 Year
--	Test Software	Rohde & Schwarz	Power Viewer Plus	--	--
SB7941/02	Signal Analyzer	Rohde & Schwarz	FSU26	Jun.06,2018	1 Year

## 5. 6DB BANDWIDTH MEASUREMENT

### 5.1. LIMITS OF 6dB BANDWIDTH MEASUREMENT

CFR 47 (FCC) part 15.247 (a) (2) , 558074 D01 DTS Meas Guidance v03r05

### 5.2. TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer.

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.

g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



### 5.3. TEST SETUP




## Test Data

Table 5 6dB Bandwidth Test Data BLE

CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	results
2402	0.6923	Pass
2440	0.6603	Pass
2480	0.6923	Pass



Date: 7.NOV.2018 16:37:05



Date: 7.NOV.2018 16:39:38

Date: 7.NOV.2018 16:41:52

## 6. MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT

### 6.1. LIMITS OF Maximum Conducted Output Power Measurement


CFR 47 (FCC) part 15.247 (b) (3), 558074 D01 DTS Meas Guidance v03r05

### 6.2. TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer.

- a) Set the RBW  $\geq$  DTS bandwidth.
- b) Set VBW  $\geq 3 \times$  RBW.
- c) Set span  $\geq 3 \times$  RBW
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.




### 6.3. TEST SETUP



### 6.4. TEST DATA

Table 6 Maximum Conducted Output Power Test Data BLE

Center Freq.[MHz]	Meas. Level (Cond.) [dBm]	Limit [dBm]	Result
2402	-4.46	< 30	Pass
2440	-3.89	< 30	Pass
2480	-3.25	< 30	Pass



Date: 7.NOV.2018 16:22:49

Date: 7.NOV.2018 16:23:25

## 7. MAXIMUM POWER SPECTRAL DENSITY LEVEL MEASUREMENT

### 7.1. LIMITS OF Maximum Power Spectral Density Level Measurement

CFR 47 (FCC) part 15.247 (e) , 558074 D01 DTS Meas Guidance v03r05

### 7.2. TEST PROCEDURE




The transmitter output was connected to the spectrum analyzer.

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set RBW to:  $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$ .
- d) Set VBW  $\geq 3 \times \text{RBW}$ .
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### 7.3. TEST DATA

Table 7 Maximum Power Spectral Density Level Test Data BLE

Freq.[MHz]	PSD [dBm]	Limit [dBm]	Result
2402	-6.13	8	Pass
2440	-5.66	8	Pass
2480	-4.63	8	Pass



Date: 7.NOV.2018 16:44:54

Date: 7.NOV.2018 16:45:48

## 8. CONDUCTED BANDEDGE AND SPURIOUS MEASUREMENT

### 8.1. LIMITS OF Conducted Bandedge and Spurious Measurement

CFR 47 (FCC) part 15.247 (d) and 558074 D01 DTS Meas Guidance v03r05

### 8.2. TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer.

Establish a reference level by using the following procedure:


- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to  $\geq 1.5$  times the DTS bandwidth.
- c) Set the RBW = 100 kHz.
- d) Set the VBW  $\geq 3 \times$  RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.

Emission level measurement


- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW  $\geq 3 \times$  RBW.
- d) Detector = peak.
- e) Ensure that the number of measurement points  $\geq$  span/RBW
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level.

### 8.3. TEST DATA


BLE CH0



BLE CH19



## BLE CH39



## 9. RADIATED BANDEDGE AND SPURIOUS MEASUREMENT

### 9.1. LIMITS OF Radiated Bandedge and Spurious Measurement

CFR 47 (FCC) part 15.247 (d) and 558074 D01 DTS Meas Guidance v03r05

### 9.2. TEST PROCEDURE

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. For measurement below 1GHz, the EUT was placed on a turntable with 0.8 meter, above ground. For measurement above 1 GHz, test at FAR, the EUT is placed on a non-conductive table, which is 1.5 meter above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold;
  - (3) Set RBW = 1 MHz, VBW= 3MHz for  $f > 1$  GHz for peak measurement.  
Set RBW = 1 MHz, and 1/T (on time) for average measurement.

### 9.3. TEST DATA

### 9KHz-30MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Table 8 Radiated Emission Test Data 9k Hz-30MHz

Frequency MHz	Cable Loss(dB)	Antenna Factor(dB)	Readings(dB $\mu$ V/m)	Level(dB $\mu$ V/m)	Polarity(H/V)	Turntable Angle(de g)	Antenna Height(m)	Limits(dB $\mu$ V/m)	Margin(dB)
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--

### 30MHz-1GHz

Worst case is shown below for 30MHz-1GHz only.

The emissions don't show in following result tables are more than 20dB below the limits.

Table 9 Radiated Emission Test Data 30MHz-1GHz


Frequency (MHz)	Cable Loss +preamp (dB)	Antenna Factor (dB)	Readings (dB $\mu$ V/m)	Level (dB $\mu$ V/m)	Polarity (H/V)	Limits (dB $\mu$ V/m)	Margin (dB)	Note
31.573	0.6	12.3	21.3	34.2	V	40	5.8	QP
38.269	0.7	12.3	14.6	27.6	V	40	12.4	QP
45.571	0.8	13.6	12.7	27.1	V	40	12.9	QP
57.161	0.8	13.0	12.4	26.2	V	40	13.8	QP
103.816	1.2	13.2	1.7	16.1	V	43.5	27.4	QP
119.416	1.3	12.3	5.8	19.4	V	43.5	24.1	QP
30.171	0.6	12.3	5.7	18.6	H	40	21.4	QP
38.190	0.7	12.3	2.5	15.5	H	40	24.5	QP
45.526	0.8	13.6	0.5	14.9	H	40	25.1	QP
103.877	1.3	13.2	0.5	15.0	H	43.5	28.5	QP
119.410	1.3	12.3	-0.4	13.2	H	43.5	30.3	QP
193.210	1.7	10.6	0.1	12.4	H	43.5	31.1	QP

REMARK: Emission level(dBuV)=Read Value(dBuV/m) + Antenna Factor(dB)+ Cable Loss +preamp(dB)

## Radiated Emission


EUT Name: WD100  
Operating Condition: Charging and Transmitting  
Test site: SMQ NETC EMC Lab.  
Antenna Position: Vertical & Horizontal  
Comment: AC 120V/60Hz

Normal\_R E\_TT 3m distance



(Horizontal)

Normal\_R E\_TT 3m distance



(Vertical)

1-18G

BLE CH0

## Radiated Emission


### EUT Information

EUT Model Name: WD100  
Operation mode: BT BLE CH0 TX  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



# Radiated Emission


## EUT Information

EUT Model Name: WD100  
Operation mode: BT BLE CH0 TX  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



1-18G

BLE CH19

## Radiated Emission


### EUT Information

EUT Model Name: WD100  
Operation mode: BT BLE CH19 TX  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



# Radiated Emission


## EUT Information

EUT Model Name: WD100  
Operation mode: BT BLE CH19 TX  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



1-18G

BLE CH39

## Radiated Emission


### EUT Information

EUT Model Name: WD100  
Operation mode: BT BLE CH39 TX  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization:  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



# Radiated Emission


## EUT Information

EUT Model Name: WD100  
Operation mode: BT BLE CH39 TX  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:

FCC Electric Field Strength 1-18GHz operate on 2.4GHz



18-25G

No Peak found in pre-scan, only worst case result is listed in this report.

## Radiated Emission


### EUT Information

EUT Model Name: WD100  
Operation mode: BLE  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:

FCC Electric Field Strength 18-26.5GHz



# Radiated Emission


## EUT Information

EUT Model Name: WD100  
Operation mode: BLE  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:

FCC Electric Field Strength 18-26.5GHz



Band edge

BLE CH0

## Radiated Emission


### EUT Information

EUT Model Name: WD100  
Operation mode: BT BLE CH0 TX  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:

FCC Electric Field Strength 2.4GHz Bandedge-PK



# Radiated Emission


## EUT Information

EUT Model Name: WD100  
Operation mode: BT BLE CH0 TX  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:

FCC Electric Field Strength 2.4GHz Bandedge-PK



# Radiated Emission


## EUT Information

EUT Model Name: WD100  
Operation mode: BT BLE CH0 TX  
Test Voltage:   
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:

FCC Electric Field Strength 2.4GHz Bandedge-AV



# Radiated Emission


## EUT Information

EUT Model Name: WD100  
Operation mode: BT BLE CH0 TX  
Test Voltage:   
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:

FCC Electric Field Strength 2.4GHz Bandedge-AV



Band edge

BLE CH39

## Radiated Emission


### EUT Information

EUT Model Name: WD100  
Operation mode: BT BLE CH39 TX  
Test Voltage:  
Comment:

### Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:

FCC Electric Field Strength 2.4GHz Bandedge-PK



# Radiated Emission


## EUT Information

EUT Model Name: WD100  
Operation mode: BT BLE CH39 TX  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:

FCC Electric Field Strength 2.4GHz Bandedge-PK



# Radiated Emission


## EUT Information

EUT Model Name: WD100  
Operation mode: BT BLE CH39 TX  
Test Voltage:   
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Horizontal  
Operator Name:  
Comment:

FCC Electric Field Strength 2.4GHz Bandedge-AV



# Radiated Emission


## EUT Information

EUT Model Name: WD100  
Operation mode: BT BLE CH39 TX  
Test Voltage:  
Comment:

## Common Information

Test Site: SMQ EMC Lab.  
Environment  
Antenna Polarization: Vertical  
Operator Name:  
Comment:

FCC Electric Field Strength 2.4GHz Bandedge-AV



## 10. CONDUCTED EMISSION TEST FOR AC POWER PORT MEASUREMENT

### 10.1. Test Standard and Limit

#### 10.1.1. Test Standard

FCC Part 15.207

#### 10.1.2. Test Limit

Table 10 Conducted Disturbance Test Limit

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50

\* Decreasing linearly with logarithm of the frequency

\* The lower limit shall apply at the transition frequency.

### 10.2. Test Procedure

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver (R&S Test Receiver ESCS30) is used to test the emissions form both sides of AC line. According to the requirements of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-Peak and average detector mode.

The bandwidth of EMI test receiver is set at 9kHz.

### 10.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

### 10.4. Test Data

The emissions don't show in below are too low against the limits. Refer to the test curves.

Table 11 Conducted Disturbance Test Data


Model No.: WD100								
Test mode: Charging and Transmitting								
	Frequency (MHz)	Correction Factor (dB)	Quasi-Peak			Average		
			Reading (dB $\mu$ V)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)	Reading (dB $\mu$ V)	Emission Level (dB $\mu$ V)	Limits (dB $\mu$ V)
Line	0.150	9.7	34.5	44.2	66	21.5	31.2	56
	0.186	9.7	36.2	45.9	64.2	21.9	31.6	54.2
	0.206	9.7	35.0	44.7	63.4	23.8	33.5	53.4
	0.238	9.7	27.2	36.9	62.2	12.0	21.7	52.2
	0.398	9.7	21.5	31.2	57.9	9.9	19.6	47.9
	1.666	9.8	27.4	37.2	56	7.9	17.7	46
Neutral	0.150	9.7	35.4	45.1	66	21.2	30.9	56
	0.190	9.7	37.3	47.0	64.0	25.6	35.3	54.0
	0.210	9.7	35.4	45.1	63.2	22.4	32.1	53.2
	0.250	9.7	27.4	37.1	61.8	15.5	25.2	51.8
	0.318	9.7	25.6	35.3	59.8	14.1	23.8	49.8
	1.622	9.8	26.4	36.2	56	16.9	26.7	46

REMARKS: 1. Emission level(dBuV)=Read Value(dBuV) + Correction Factor(dB)


2. Correction Factor(dB) =LISN Factor (dB) + Cable Factor (dB)+Limiter Factor(dB)

3. The other emission levels were very low against the limit.

EUT: WD100  
Manufacturer:  
Operating Condition: Charging and Transmitting  
Test Site:  
Operator:  
Test Specification: L  
Comment: AC 120V/60Hz



EUT: WD100  
Manufacturer:  
Operating Condition: Charging and Transmitting  
Test Site:  
Operator:  
Test Specification: N  
Comment: AC 120V/60Hz



## **11. ANTENNA REQUIREMENTS**

### **11.1.Applicable requirements**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

### **11.2.Antenna Connector**

Antenna Connector is on the PCB within enclosure and not accessible to user.

### **11.3.Antenna Gain**

The antenna gain of EUT is less than 6 dBi.