

FCC TEST REPORT

For

Wearable Data Terminal

Model Number: WD100

FCC ID: HLEWD100BTNL

Report Number : WT188005264

Test Laboratory : Shenzhen Academy of Metrology and Quality Inspection
Site Location : NETC Building, No.4 Tongfa Rd., Xili, Nanshan, Shenzhen, China
Tel : 0086-755-86928965
Fax : 0086-755-86009898-31396
Web : www.smq.com.cn
E-mail : emcrf@smq.com.cn

TEST REPORT DECLARATION

Applicant : unitech Electronics Co., LTD.
Address : 5F., No.136, Ln. 235, Baoqiao Rd., Xindian Dist., New Taipei City, Taiwan
Manufacturer : unitech Electronics Co., LTD.
Address : 5F., No.136, Ln. 235, Baoqiao Rd., Xindian Dist., New Taipei City, Taiwan
EUT Description : Wearable Data Terminal
Model No. : WD100
Trade mark : unitech
Serial Number : /
FCC ID : HLEWD100BTNL


Test Standards:

FCC Part 15 Subpart B 15.107, 15.109 (2017)

The EUT described above is tested by Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory to determine the maximum emissions from the EUT. Shenzhen Academy of Metrology and Quality Inspection EMC Laboratory is assumed full responsibility for the accuracy of the test results.

The test report is valid for above tested sample only and shall not be reproduced in part without written approval of the laboratory.

Project Engineer:  Date: Nov.14, 2018
(Zhou Fangai 周芳媛)

Checked by:  Date: Nov.14, 2018
(Lin Yixiang 林奕翔)

Approved by:  Date: Nov.14, 2018
(Lin Bin 林斌)

TABLE OF CONTENTS

TEST REPORT DECLARATION.....	2
1. TEST RESULTS SUMMARY	4
2. GENERAL INFORMATION.....	5
2.1. Report information.....	5
2.2. Laboratory Accreditation and Relationship to Customer	5
2.3. Measurement Uncertainty	5
3. PRODUCT DESCRIPTION	6
3.1. EUT Description	6
3.2. Block Diagram of EUT Configuration	7
3.3. Operating Condition of EUT	7
3.4. Support Equipment List	7
3.5. Test Conditions	7
3.6. Modifications	7
4. TEST EQUIPMENT USED.....	8
4.1. Test Equipment Used to Measure Conducted Disturbance	8
4.2. Test Equipment Used to Measure Radiated Disturbance	8
5. CONDUCTED DISTURBANCE TEST	9
5.1. Test Standard and Limit	9
5.2. Test Procedure.....	9
5.3. Test Arrangement	9
5.4. Test Data.....	9
6. RADIATION DISTURBANCE TEST	13
6.1. Test Standard and Limit	13
6.2. Test Procedure.....	13
6.3. Test Arrangement	13
6.4. Test Data.....	14

1. TEST RESULTS SUMMARY

Table 1 Test Results Summary

Test Items	FCC Rules	Test Results
Conducted Disturbance	15.107	Pass
Radiation Emission	15.109	Pass

Remark: "N/A" means "Not applicable."

2. GENERAL INFORMATION

2.1. Report information

This report is not a certificate of quality; it only applies to the sample of the specific product/equipment given at the time of its testing. The results are not used to indicate or imply that they are application to the similar items. In addition, such results must not be used to indicate or imply that SMQ approves recommends or endorses the manufacture, supplier or use of such product/equipment, or that SMQ in any way guarantees the later performance of the product/equipment.

The sample/s mentioned in this report is/are supplied by Applicant, SMQ therefore assumes no responsibility for the accuracy of information on the brand name, model number, origin of manufacture or any information supplied.

Additional copies of the report are available to the Applicant at an additional fee. No third part can obtain a copy of this report through SMQ, unless the applicant has authorized SMQ in writing to do so.

2.2. Laboratory Accreditation and Relationship to Customer

The testing report were performed by the Shenzhen Academy of Metrology and quality Inspection EMC Laboratory (Guangdong EMC compliance testing center), in their facilities located at NETC Building, No.4 Tongfa Rd., Xili, Nanshan, Shenzhen, China. At the time of testing, Laboratory is accredited by the following organizations:

China National Accreditation Service for Conformity Assessment (CNAS) accredits the Laboratory for conformance to FCC standards, EMC international standards and EN standards. The Registration Number is CNAS L0579.

The Laboratory is Accredited Testing Laboratory of FCC with Designation number CN1165 and Site registration number 582918.

The Laboratory is registered to perform emission tests with Innovation, Science and Economic Development (ISED), and the registration number is 11177A.

2.3. Measurement Uncertainty

Conducted Emission
9 kHz~30MHz 2.9dB

Radiated Emission
30MHz~1000MHz 5.1dB
1GHz~6GHz 5.04dB
6GHz~18GHz 5.54dB

3. PRODUCT DESCRIPTION


3.1. EUT Description

Table 2 Specification of the Equipment under Test

Product Type:	Wearable Data Terminal
Hardware Version:	V03
Software Version :	SQ46W_P1_00AX_YBUTE_AU1616_404_R_0_181009_01
FCC-ID:	HLEWD100BTNL
Frequency:	<p>GSM850: TX 824MHz~849MHz RX 869MHz~894MHz</p> <p>PCS1900: TX 1850MHz~1910MHz RX 1930MHz~1990MHz</p> <p>WCDMA 850: TX 824MHz~849MHz RX 869MHz~894MHz</p> <p>WCDMA 1700: TX: 1710MHz~1755MHz RX 2110MHz~2155MHz</p> <p>WCDMA 1900: TX 1850MHz~1910MHz RX 1930MHz~1990MHz</p> <p>LTE Band 2: TX 1850MHz~1910MHz RX 1930MHz~1990MHz</p> <p>LTE Band 4: TX: 1710MHz~1755MHz RX 2110MHz~2155MHz</p> <p>LTE Band 5: TX 824MHz~849MHz RX 869MHz~894MHz</p> <p>LTE Band 7: TX 2500MHz~2570MHz RX 2620MHz~2690MHz</p> <p>WiFi: 2412MHz~2462MHz</p> <p>BT: 2402MHz~2480MHz</p>
Type(s) of Modulation:	<p>GSM850/PCS1900: GMSK 8PSK</p> <p>WCDMA: QPSK</p> <p>LTE: QPSK, 16QAM</p> <p>DSSS (DBPSK, DQPSK, CCK) for 802.11b</p> <p>OFDM (BPSK, QPSK, 16QAM, 64QAM) for 802.11a/g/n</p> <p>BT: GFSK, pi/4-DQPSK, 8DPSK</p>
Antenna Type:	<p>GSM/WCDMA/LTE: PIFA ANTENNA</p> <p>824MHz~849MHz: -2dBi</p> <p>1710MHz~1780MHz: -1 dBi</p> <p>1850MHz~1910MHz: -1 dBi</p> <p>2500MHz~2570MHz: -1 dBi</p> <p>WiFi: PIFA ANTENNA -1dBi</p> <p>BT: PIFA ANTENNA -1.6dBi</p>
Operating voltage:	Internal battery, 120V AC Adapter 3.5V (Low)/3.7V (Nominal)/ 4.35V (Max)

Remark: --

3.2. Block Diagram of EUT Configuration



3.3. Operating Condition of EUT

Test mode 1: connected to a pc and data transmission.

The test mode mentioned above is identified as worst case for this EUT and the test results for this mode are recorded in this report.

The Radiated emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission (X plane).

3.4. Support Equipment List

Table 3 Support Equipment List

Name	Model No	S/N	Manufacturer
Battery for EUT	HBLWD100	--	ICON ENERGY SYSTEM(SHEN ZHEN) CO.,LTD
USB for EUT	--	--	--
Earphone	--	--	--

Table 4 Support Equipment List

Name	Model No	S/N	Manufacturer	FCC
Notebook	P35G	--	DELL	DOC
Mouse	MSU1465	--	HP	DOC
Earphone	--	--	--	DOC

3.5. Test Conditions

Date of test : Oct.23, 2018- Nov.01, 2018

Date of EUT Receive : Sep.04, 2018

Temperature: 23-25 °C

Relative Humidity: 38-51%

3.6. Modifications

No modification was made.

4. TEST EQUIPMENT USED

4.1. Test Equipment Used to Measure Conducted Disturbance

Table 3 Conducted Disturbance Test Equipment

No.	Equipment	Manufacturer	Model No.	LAST CALIB	Period
SB2603	EMI Test Receiver	R&S	ESCS30	Mar.05,2018	1 Year
SB2604	AMN	R&S	ESH3-Z5	Mar.05,2018	1 Year

4.2. Test Equipment Used to Measure Radiated Disturbance

Table 4 Radiated Disturbance Test Equipment

No.	Equipment	Manufacturer	Model No.	LAST CALIB	Period
SB3436	EMI Test Receiver	R&S	ESI26	Nov.28,2017	1 Year
SB3955	Trilog Broadband Antenna (30M-3GHz)	Schwarzbeck	VULB9163	Mar.05,2018	1 Year
SB9422/16	Double-Ridged Waveguide Horn Antenna (1G~18GHz)	R&S	HF907	Mar.08,2018	1 Year
SB8501/16	Preamplifier	Rohde & Schwarz	SCU-26	Mar.05,2018	1 Year
SB8501/17	Preamplifier	Rohde & Schwarz	SCU-18	Mar.05,2018	1 Year
SB9059	Preamplifier	Rohde & Schwarz	SCU-40	Aug.29,2018	1 Year
SB8501/11	Horn Antenna	ETS-Lindgren	3160-09	Mar.21,2017	3 Years
SB8501/12	Horn Antenna	ETS-Lindgren	3160-10	Mar.21,2017	3 Years

5. CONDUCTED DISTURBANCE TEST

5.1. Test Standard and Limit

5.1.1. Test Standard

FCC Part 15: Section 15.107

5.1.2. Test Limit

Table 5 Conducted Disturbance Test Limit (Class B)

Frequency	Power Port limits (dB μ V)	
	Quasi-peak	Average
0.15MHz ~ 0.5MHz	66~56*	56~46*
0.5MHz ~ 5 MHz	56	46
5 MHz ~ 30MHz	60	50

* Decreasing linearly with logarithm of the frequency

5.2. Test Procedure

The EUT is put on a table of non-conducting material that is 80cm high. The vertical conducting wall of shielding is located 40cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI test receiver (R&S Test Receiver ESCS30) is used to test the emissions form both sides of AC line. The bandwidth of EMI test receiver is set at 9kHz.

5.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application. The detailed information refers to test picture.

5.4. Test Data

The emissions don't show in following result tables are more than 20dB below the limits, the test curves are shown in the next page.

Table 6 Conducted Disturbance Test Data at mains Port


Model No.: WD100							
Test mode: Test Mode 1							
	Frequency (MHz)	Correction Factor (dB)	Quasi-Peak			Average	
			Reading (dB μ V)	Emission Level (dB μ V)	Limits (dB μ V)	Reading (dB μ V)	Emission Level (dB μ V)
Line	0.186	9.7	44.1	53.8	64.2	30.2	39.9
	0.250	9.7	37.4	47.1	61.8	26.9	36.6
	0.626	9.8	34.8	44.6	56	27.3	37.1
	0.862	9.8	33.0	42.8	56	24.4	34.2
	1.102	9.8	34.3	44.1	56	26.7	36.5
	2.038	9.9	32.5	42.4	56	25.2	35.1
Neutral	0.182	9.7	37.9	47.6	64.4	25.5	35.2
	0.434	9.7	35.8	45.5	57.2	27.8	37.5
	0.526	9.8	37.2	47.0	56	24.4	34.2
	0.610	9.8	38.3	48.1	56	26.7	36.5
	0.794	9.8	37.4	47.2	56	25.8	35.6
	2.630	9.9	38.7	48.6	56	30.5	40.4

REMARKS: 1. Emission level(dBuV)=Read Value(dBuV) + Correction Factor(dB)


2. Correction Factor(dB) =LISN Factor (dB) + Cable Factor (dB)+Limiter Factor(dB)

3. The other emission levels were are more than 20dB below the limits.

EUT: WD100
Operating Condition: Test mode 1
Test Specification: L
Comment: AC 120V/60Hz
Comment:



EUT: WD100
Operating Condition: Test mode 1
Test Specification: N
Comment: AC 120V/60Hz
Comment:



6. RADIATION DISTURBANCE TEST

6.1. Test Standard and Limit

6.1.1. Test Standard

FCC Part 15: Section 15.109

6.1.2. Test Limit

Table 7 Radiation Disturbance Test Limit for FCC (Class B)(9KHz-1GHz)

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

Table 8 Radiation Disturbance Test Limit for FCC (Class B)(Above 1G)

Frequency (MHz)	(dBuV/m) (at 3 meters)	
	PEAK	AVERAGE
Above 1000	74	54

* The lower limit shall apply at the transition frequency.

* The test distance is 3m.

6.2. Test Procedure

The EUT is placed on a turntable, which is 0.8 meter above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set **3 meters** away from the receiving antenna, which is mounted on an antenna tower. The antenna can move up and down between 1 to 4 meters to find out the maximum emission level. Broadband antenna is used as a receiving antenna. Both horizontal and vertical polarization of the antenna is set on test.

RBW = 100 kHz (less than or equal to 1 GHz); 1 MHz (above 1 GHz)

VBW \geq 3 x RBW

Detector = Peak & Quasi-Peak (frequency range 30 MHz to 1 GHz);
Peak & Average (frequency range above 1 GHz);
Changing VBW to 10 Hz for average measurement

The use of a higher-than-specified video bandwidth produces a conservative measurement result.

6.3. Test Arrangement

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal

application. The detailed information refers to test picture.

6.4. Test Data

The emissions don't show in following result tables are more than 20dB below the limits, the test curves are shown in the next page.

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Table 6 Radiated Disturbance Test Data


Model No.: WD100								
Test mode: 1								
Frequency (MHz)	Cable Loss +preamp (dB)	Antenna Factor (dB)	Readings (dB μ V/m)	Level (dB μ V/m)	Polarity (H/V)	Limits (dB μ V/m)	Margin (dB)	Note
77.918	1.1	7.8	6.8	29.6	H	40	10.4	QP
203.048	1.6	10.6	3.6	30.4	H	43.5	13.1	QP
224.970	1.8	11.2	3.2	28.1	H	46	17.9	QP
242.721	1.8	12.1	7.6	38.9	H	46	7.1	QP
719.961	3.4	18.8	5.1	43.9	H	46	2.1	QP
83.350	1.0	8.5	20.6	28.3	V	40	11.7	QP
240.008	1.9	12.1	17.4	33.1	V	46	12.9	QP
341.661	2.2	14.1	18.9	29.6	V	46	16.4	QP
1593.500	-40.6	25.1	49.6	60.1	V	74	13.9	PK
2396.500	-40.2	28.3	44.3	50.6	V	74	23.4	PK
3197.500	-39.0	30.4	49.2	50.2	V	74	23.8	PK
2309.000	-40.3	28.3	50.6	46.1	H	74	27.9	PK
1593.500	-40.6	25.1	54.1	35.6	V	54	18.4	AV
2396.500	-40.2	28.3	50.5	26.6	V	54	27.4	AV
3197.500	-39.0	30.4	47.2	26.1	V	54	27.9	AV
2309.000	-40.3	28.3	50.6	20.5	H	54	33.5	AV

Emission level (dB μ V)=Read Value(dB μ V/m) + Antenna Factor(dB)+ Cable Loss +preamp(dB)

Radiated Emission


EUT Name: WD100
Operating Condition: Test Mode 1
Test site: SMQ NETC EMC Lab.3m Chamber
Antenna Position: Horizontal & Vertical
Comment: AC 120V60Hz

Field strength 30M-1GHz 1F 3m chamber



(Horizontal)

Field strength 30M-1GHz 1F 3m chamber




(Vertical)

Radiated Emission


EUT Name: WD100
Operating Condition: Test Mode 1
Test site: SMQ NETC EMC Lab.3m Chamber
Antenna Position: Vertical & Horizontal
Comment: AC 120V/60Hz

Field strength 1-6GHz 1F 3m chamber



(Horizontal)

Field strength 1-6GHz 1F 3m chamber



(Vertical)

Radiated Emission


EUT Information

EUT Model name: WD100
Operator Mode: Test Mode 1
Comment:

Common Information

Test Description: SMQ NETC EMC Lab.3m Chamber
Customer
Antenna Position: Horizontal
Operator Name:
Comment1: AC 120V/60Hz
Comment2:

Copy (2) of FCC Electric Field Strength 1-18GHz operate on 2.4GHz



Radiated Emission

EUT Information

EUT Model name: WD100
Operator Mode: Test Mode 1
Comment:

Common Information

Test Description: SMQ NETC EMC Lab.3m Chamber
Customer
Antenna Position: Vertical
Operator Name:
Comment1: AC 120V/60Hz
Comment2:

Copy (2) of FCC Electric Field Strength 1-18GHz operate on 2.4GHz

