

FCC RF Test Report

APPLICANT : Acer Incorporated
EQUIPMENT : Smart HandHeld
BRAND NAME : Acer
MODEL NAME : E120
FCC ID : HLZDME120
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : Digital Transmission System (DTS)

The product was received on May 19, 2010 and completely tested on Jun. 09, 2010. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Roy Wu / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Feature of Equipment Under Test	5
1.4 Testing Site	6
1.5 Applied Standards	6
1.6 Ancillary Equipment List	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	7
2.1 RF Power	7
2.2 Test Mode	8
2.3 Connection Diagram of Test System	9
2.4 RF Utility	9
3 TEST RESULT	10
3.1 6dB and 99% Bandwidth Measurement	10
3.2 Output Power Measurement	19
3.3 Band Edges Measurement	21
3.4 Spurious Emission Measurement	27
3.5 Power Spectral Density Measurement	34
3.6 AC Conducted Emission Measurement	39
3.7 Radiated Emission Measurement	43
3.8 Antenna Requirements	58
4 LIST OF MEASURING EQUIPMENT	59
5 UNCERTAINTY OF EVALUATION	60
APPENDIX A. PHOTOGRAPHS OF EUT	
APPENDIX B. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR051810-01B	Rev. 01	Initial issue of report	Jun. 22, 2010

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	A8.2(a)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	Gen 4.4.1	99% Bandwidth	-	Pass	-
3.2	15.247(b)	A8.4	Power Output	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(d)	A8.5	Frequency Band Edges	$\leq 20\text{dBc}$	Pass	-
3.4	15.247(d)	A8.5	Spurious Emission	$< 20\text{ dBc}$	Pass	-
3.5	15.247(e)	A8.2(b)	Power Spectral Density	$\leq 8\text{dBm}$	Pass	-
3.6	15.207	Gen 7.2.2	AC Conducted Emission	15.207(a)	Pass	Under limit 16.7 dB at 0.398 MHz
3.7	15.247(d)	A8.5	Transmitter Radiated Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.93 dB at 2383.50 MHz
3.8	15.203 & 15.247(b)	A8.4	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

Acer Incorporated

8F., No. 88, Sec. 1, Hsin Tai Wu Rd., Hsichih, Taipei Hsien 221, Taiwan

1.2 Manufacturer

Futaijing Precision Electronics (Beijing) Co., Ltd.

No. 9, Jinxiu Street, Beijing Economic Technology Development Area

1.3 Feature of Equipment Under Test

Product Feature & Specification	
Equipment	Smart HandHeld
Brand Name	Acer
Model Name	E120
FCC ID	HLZDME120
Tx/Rx Frequency Range	2400 MHz ~ 2483.5 MHz
Number of Channels	11
Carrier Frequency of Each Channel	2412+(n-1)*5 MHz; n=1~11
Channel Spacing	5 MHz
Maximum Output Power to Antenna	802.11b : 15.76 dBm (37.67 mW) 802.11g : 20.61 dBm (115.08 mW)
Antenna Type	PIFA Antenna with gain 3.1 dBi
HW Version	1.0 (PR2)
SW Version	Firmware version : 1.6 Baseband version : 40000000E22E1105 Build number : Acer_E120_V0.180.00_AAP_GEN2
Type of Modulation	802.11b : DSSS (BPSK / QPSK / CCK) 802.11g : OFDM (BPSK / QPSK / 16QAM / 64QAM)
EUT Stage	Identical Prototype

Remark:

1. For other wireless features of this EUT, test report will be issued separately.
2. This test report recorded only product characteristics and test results of Digital Transmission System (DTS).
3. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	CO05-HY	03CH07-HY	TW1022/4086B-1

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 (Measurement Guidelines of DTS)
- ANSI C63.4-2003
- IC RSS-210 Issue 7

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.

1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Vostro 1510	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A

2 Test Configuration of Equipment Under Test

2.1 RF Power

Preliminary tests were performed in different data rate and recorded the RF power output in the following table:

Channel	Frequency	2.4GHz 802.11b RF Power (dBm)			
		At DSSS Data Rate			
		1 Mbps	2 Mbps	5.5 Mbps	11 Mbps
CH 01	2412 MHz	15.53	15.63	15.42	15.61
CH 06	2437 MHz	14.99	15.04	14.85	15.15
CH 11	2462 MHz	15.71	15.66	15.62	15.76

Channel	Frequency	2.4GHz 802.11g RF Power (dBm)							
		At OFDM Data Rate							
		6 Mbps	9 Mbps	12 Mbps	18 Mbps	24 Mbps	36 Mbps	48 Mbps	54 Mbps
CH 01	2412 MHz	20.08	20.00	19.92	19.74	19.86	19.71	19.63	19.79
CH 06	2437 MHz	19.81	20.07	19.84	19.89	19.60	19.84	19.64	19.46
CH 11	2462 MHz	20.61	20.48	20.59	20.49	20.59	20.59	20.41	20.47

Remark:

1. The data rates of WLAN 802.11b/g were set in 11Mbps for 802.11b and 6Mbps for 802.11g, for all the test cases due to the highest RF output power.
2. The EUT is programmed to transmit signals continuously for all testing.


2.2 Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz), radiated emission (30 MHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). Pre-scanned tests were conducted to determine the final configuration from all possible combinations. The following tables are showing the test modes as the worst cases and recorded in this report.


Test Cases		
Test Item	802.11b	802.11g
Conducted TCs	Mode 1 : 802.11b CH01_2412 MHz	Mode 4 : 802.11g CH01_2412 MHz
	Mode 2 : 802.11b CH06_2437 MHz	Mode 5 : 802.11g CH06_2437 MHz
	Mode 3 : 802.11b CH11_2462 MHz	Mode 6 : 802.11g CH11_2462 MHz
Radiated TCs	Mode 1 : 802.11b CH01_2412 MHz	Mode 4 : 802.11g CH01_2412 MHz
	Mode 2 : 802.11b CH06_2437 MHz	Mode 5 : 802.11g CH06_2437 MHz
	Mode 3 : 802.11b CH11_2462 MHz	Mode 6 : 802.11g CH11_2462 MHz
AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + Adapter	

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<EUT with Adapter Mode>



2.4 RF Utility

The programmed RF utility, "Nanoloader.exe" is installed in EUT to provide channel selection, power level, data rate and the application type. RF Utility can send transmitting signal for all testing. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz.
In order to make an accurate measurement, set the span greater than RBW. The 6 dB bandwidth must be greater than 500 kHz.
4. The marker-delta reading at this point is the 6 dB bandwidth of the emission.

3.1.4 Test Setup




3.1.5 Test Result of 6dB Bandwidth

Test Mode :	Mode 1, 2, 3	Temperature :	24~26℃
Test Engineer :	Lancelot Chen	Relative Humidity :	49~52%

Channel	Frequency (MHz)	802.11b 6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
01	2412	9.40	0.5	Pass
06	2437	9.80	0.5	Pass
11	2462	9.68	0.5	Pass

Mode 1 : 6 dB Bandwidth Plot on 802.11b Channel 01



Date: 7.JUN.2010 12:30:57



Mode 3 : 6 dB Bandwidth Plot on 802.11b Channel 11






Test Mode :	Mode 4, 5, 6	Temperature :	24~26°C
Test Engineer :	Lancelot Chen	Relative Humidity :	49~52%

Channel	Frequency (MHz)	802.11g 6dB Bandwidth (MHz)	6dB Bandwidth Min. Limit (MHz)	Pass/Fail
01	2412	16.56	0.5	Pass
06	2437	16.60	0.5	Pass
11	2462	16.60	0.5	Pass


Mode 4 : 6 dB Bandwidth Plot on 802.11g Channel 01



Date: 8.JUN.2010 05:33:35




Mode 5 : 6 dB Bandwidth Plot on 802.11g Channel 06



Date: 8.JUN.2010 05:57:21

Mode 6 : 6 dB Bandwidth Plot on 802.11g Channel 11




Date: 8.JUN.2010 06:00:49

3.1.6 Test Result of 99% Occupied Bandwidth

Test Mode :	Mode 1, 2, 3	Temperature :	24~26℃
Test Engineer :	Lancelot Chen	Relative Humidity :	49~52%

Channel	Frequency (MHz)	802.11b 99% Occupied Bandwidth (MHz)	Pass/Fail
01	2412	14.36	Pass
06	2437	14.36	Pass
11	2462	14.36	Pass

Mode 1 : 99% Occupied Bandwidth Plot on 802.11b Channel 01



Date: 8.JUN.2010 04:46:54



Mode 3 : 99% Occupied Bandwidth Plot on 802.11b Channel 11






Test Mode :	Mode 4, 5, 6	Temperature :	24~26°C
Test Engineer :	Lancelot Chen	Relative Humidity :	49~52%

Channel	Frequency (MHz)	802.11g 99% Occupied Bandwidth (MHz)	Pass/Fail
01	2412	16.84	Pass
06	2437	16.80	Pass
11	2462	16.80	Pass


Mode 4 : 99% Occupied Bandwidth Plot on 802.11g Channel 01



Date: 8.JUN.2010 05:36:23




Mode 5 : 99% Occupied Bandwidth Plot on 802.11g Channel 06



Date: 8.JUN.2010 05:58:24

Mode 6 : 99% Occupied Bandwidth Plot on 802.11g Channel 11



Date: 8.JUN.2010 05:59:33

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. The RF output of EUT was connected to the power meter by a low loss cable.
3. Measure the power by power meter.

3.2.4 Test Setup



3.2.5 Test Result of Output Power

Test Mode :	Mode 1, 2, 3	Temperature :	24~26℃
Test Engineer :	Lancelot Chen	Relative Humidity :	49~52%

Channel	Frequency (MHz)	802.11b Measured Output Power (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	15.61	30	Pass
06	2437	15.15	30	Pass
11	2462	15.76	30	Pass

Test Mode :	Mode 4, 5, 6	Temperature :	24~26℃
Test Engineer :	Lancelot Chen	Relative Humidity :	49~52%

Channel	Frequency (MHz)	802.11g Measured Output Power (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	20.08	30	Pass
06	2437	19.81	30	Pass
11	2462	20.61	30	Pass

3.3 Band Edges Measurement

3.3.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB.

3.3.2 Measuring Instruments


See list of measuring instruments of this test report.

3.3.3 Test Procedures


1. The testing follows the guidelines in ANSI C63.4-2003 and FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. Conducted emission test: Set RBW = 100 kHz, Video bandwidth (VBW) $\geq$ RBW. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW. Note: If the device complies with the use of power option 2 the attenuation under this paragraph shall be 30 dB instead of 20 dB.
3. Radiated emission test: Apply to band edge emissions that fall in the restricted bands listed in FCC Section 15.205. The maximum permitted average field strength is listed in FCC Section 15.209. A pre-amp is necessary for this measurement. For measurements above 1 GHz, set RBW = 1MHz, VBW = 10 Hz, Sweep=Auto. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation as in FCC Section 15.35(b) and (c).

3.3.4 Test Setup

<Radiated Band Edges>



<Conducted Band Edges>



3.3.5 Test Result of Radiated Band Edges

Test Mode :	Mode 1	Temperature :	23~24℃
Test Band :	802.11b	Relative Humidity :	45~46%
Test Channel :	01	Test Engineer :	Kai Wang and Cona Huang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2385.62	59.86	-14.14	74.00	56.43	32.13	5.46	34.16	105	12	Peak
2385.62	47.66	-6.34	54.00	44.22	32.13	5.46	34.15	105	12	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.61	54.93	-19.07	74.00	51.50	32.13	5.46	34.16	100	68	Peak
2389.61	41.74	-12.26	54.00	38.30	32.13	5.46	34.15	100	68	Average

Test Mode :	Mode 3	Temperature :	23~24℃
Test Band :	802.11b	Relative Humidity :	45~46%
Test Channel :	11	Test Engineer :	Kai Wang and Cona Huang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.50	58.29	-15.71	74.00	54.83	32.27	5.38	34.19	100	9	Peak
2483.50	46.33	-7.67	54.00	42.87	32.27	5.38	34.19	100	9	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2484.42	52.46	-21.54	74.00	49.00	32.27	5.38	34.19	100	62	Peak
2484.42	40.44	-13.56	54.00	36.98	32.27	5.38	34.19	100	62	Average



Test Mode :	Mode 4	Temperature :	23~24℃
Test Band :	802.11g	Relative Humidity :	45~46%
Test Channel :	01	Test Engineer :	Kai Wang and Cona Huang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.99	67.64	-6.36	74.00	64.21	32.13	5.46	34.16	103	7	Peak
2389.99	47.49	-6.51	54.00	44.06	32.13	5.46	34.16	103	7	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2389.42	63.19	-10.81	74.00	59.75	32.13	5.46	34.15	100	66	Peak
2389.42	44.29	-9.71	54.00	40.85	32.13	5.46	34.15	100	66	Average

Test Mode :	Mode 6	Temperature :	23~24℃
Test Band :	802.11g	Relative Humidity :	45~46%
Test Channel :	11	Test Engineer :	Kai Wang and Cona Huang


ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.50	69.07	-4.93	74.00	65.61	32.27	5.38	34.19	107	27	Peak
2483.50	48.43	-5.57	54.00	44.97	32.27	5.38	34.19	107	27	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.50	62.39	-11.61	74.00	58.93	32.27	5.38	34.19	188	98	Peak
2483.50	41.98	-12.02	54.00	38.52	32.27	5.38	34.19	188	98	Average

3.3.6 Test Plots of Conducted Band Edges


Test Mode :	Mode 1 and 3	Temperature :	24~26°C
Test Band :	802.11b	Relative Humidity :	49~52%
Test Channel :	01 and 11	Test Engineer :	Lancelot Chen

Low Band Edge Plot on 802.11b Channel 01



Date: 7.JUN.2010 12:32:06


High Band Edge Plot on 802.11b Channel 11




Date: 7.JUN.2010 15:37:22



Test Mode :	Mode 4 and 6	Temperature :	24~26°C
Test Band :	802.11g	Relative Humidity :	49~52%
Test Channel :	01 and 11	Test Engineer :	Lancelot Chen

Low Band Edge Plot on 802.11g Channel 01

Date: 8.JUN.2010 05:34:13

High Band Edge Plot on 802.11g Channel 11

Date: 8.JUN.2010 06:04:59

3.4 Spurious Emission Measurement

3.4.1 Limit of Spurious Emission Measurement

All harmonics/spurs must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedure

1. The transmitter output was connected to the spectrum analyzer via a low lose cable.
2. Set RBW = 100 kHz, Video bandwidth (VBW) $\geq$ RBW, scan up through 10th harmonic. All harmonics/spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.


3.4.4 Test Setup



3.4.5 Test Plots of Spurious Emission


Test Mode :	Mode 1	Temperature :	24~26°C
Test Band :	802.11b	Relative Humidity :	49~52%
Test Channel :	01	Test Engineer :	Lancelot Chen

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz



Date: 8.JUN.2010 04:59:29

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz




Date: 8.JUN.2010 04:59:44




Test Mode :	Mode 2	Temperature :	24~26°C
Test Band :	802.11b	Relative Humidity :	49~52%
Test Channel :	06	Test Engineer :	Lancelot Chen

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz




Date: 8.JUN.2010 05:00:43

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz




Date: 8.JUN.2010 05:01:14

Test Mode :	Mode 3	Temperature :	24~26°C
Test Band :	802.11b	Relative Humidity :	49~52%
Test Channel :	11	Test Engineer :	Lancelot Chen


Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz


Date: 8.JUN.2010 05:02:12


Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz


Date: 8.JUN.2010 05:02:42

Test Mode :	Mode 4	Temperature :	24~26°C
Test Band :	802.11g	Relative Humidity :	49~52%
Test Channel :	01	Test Engineer :	Lancelot Chen


Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz


Date: 8.JUN.2010 05:05:26


Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz


Date: 8.JUN.2010 05:05:54

Test Mode :	Mode 5	Temperature :	24~26°C
Test Band :	802.11g	Relative Humidity :	49~52%
Test Channel :	06	Test Engineer :	Lancelot Chen

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz



Date: 8.JUN.2010 05:06:40

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz



Date: 8.JUN.2010 05:07:01



Test Mode :	Mode 6	Temperature :	24~26°C
Test Band :	802.11g	Relative Humidity :	49~52%
Test Channel :	11	Test Engineer :	Lancelot Chen

Conducted Spurious Emission Plot between 9 kHz ~ 3 GHz

Date: 8.JUN.2010 05:07:29

Conducted Spurious Emission Plot between 1 GHz ~ 25 GHz

Date: 8.JUN.2010 05:07:56

3.5 Power Spectral Density Measurement

3.5.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The test follows FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Take the measured data from spectrum analyzer.

3.5.4 Test Setup





Test Mode :	Mode 1, 2, 3	Temperature :	24~26℃	
Test Engineer :	Lancelot Chen	Relative Humidity :	49~52%	

Channel	Frequency (MHz)	802.11b Measured PSD (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	-8.21	8	Pass
06	2437	-8.78	8	Pass
11	2462	-8.61	8	Pass


The screenshot shows a Spectrum Analyzer interface with the following details:

- Top Bar:**
 - Left: A red square icon with a white 'X' and a small red circle.
 - Center: A green status bar with the text "1. FM" and "CLAWW".
 - Right: A green status bar with the text "A SGL" and "LVL".
- Parameters:**
 - Ref: 20 dBm
 - Att: 20 dB
 - RBW: 3 kHz
 - VBW: 30 kHz
 - SWT: 500 s
 - Marker 1 [T1]: -8.21 dBm
 - 2.412339000 GHz
- Grid and Trace:**
 - The grid has a vertical axis from -80 to 20 dBm and a horizontal axis from 0 to 100 MHz.
 - A blue trace shows a noisy signal centered around 2.412 GHz.
 - A green vertical line marks the center frequency at 2.412 GHz.
 - A green horizontal line marks the noise floor at -8.21 dBm.
- Bottom Bar:**
 - Center: 2.412 GHz
 - 150 kHz/
 - Span: 1.5 MHz

Date: 7.JUN.2010 12:42:12




Mode 2 : PSD Plot on 802.11b Channel 06



Date: 7.JUN.2010 12:51:28


Mode 3 : PSD Plot on 802.11b Channel 11




Date: 7.JUN.2010 13:29:55

Test Mode :	Mode 4, 5, 6	Temperature :	24~26℃
Test Engineer :	Lancelot Chen	Relative Humidity :	49~52%


Channel	Frequency (MHz)	802.11g Measured PSD (dBm)	Max. Limits (dBm)	Pass/Fail
01	2412	-13.62	8	Pass
06	2437	-13.83	8	Pass
11	2462	-13.38	8	Pass

Mode 4 : PSD Plot on 802.11g Channel 01


Date: 8.JUN.2010 05:46:29

Mode 5 : PSD Plot on 802.11g Channel 06


Date: 8.JUN.2010 05:55:32

Mode 6 : PSD Plot on 802.11g Channel 11


Date: 8.JUN.2010 06:23:36

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The testing follows the guidelines in ANSI C63.4-2003.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 kHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Novic Jiang	Relative Humidity :	42~44%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + Adapter		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	37.1	Off	L1	19.5	28.5	65.6
0.198000	34.5	Off	L1	19.6	29.2	63.7
0.238000	32.8	Off	L1	19.5	29.4	62.2
0.398000	32.2	Off	L1	19.5	25.7	57.9
14.150000	32.9	Off	L1	19.7	27.1	60.0
16.590000	31.2	Off	L1	19.7	28.8	60.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	32.9	Off	L1	19.5	22.7	55.6
0.198000	30.1	Off	L1	19.6	23.6	53.7
0.238000	26.0	Off	L1	19.5	26.2	52.2
0.398000	27.4	Off	L1	19.5	20.5	47.9
14.150000	21.4	Off	L1	19.7	28.6	50.0
16.590000	24.0	Off	L1	19.7	26.0	50.0

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Novic Jiang	Relative Humidity :	42~44%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link + Earphone + Adapter		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		


Final Result 1

Frequency (MHz)	QuasiPeak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	35.0	Off	N	19.5	30.6	65.6
0.198000	32.1	Off	N	19.5	31.6	63.7
0.238000	30.0	Off	N	19.5	32.2	62.2
0.358000	32.0	Off	N	19.4	26.8	58.8
0.398000	32.4	Off	N	19.4	25.5	57.9
14.070000	27.7	Off	N	19.7	32.3	60.0

Final Result 2

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.158000	33.2	Off	N	19.5	22.4	55.6
0.198000	30.8	Off	N	19.5	22.9	53.7
0.238000	28.1	Off	N	19.5	24.1	52.2
0.358000	30.2	Off	N	19.4	18.6	48.8
0.398000	31.2	Off	N	19.4	16.7	47.9
14.070000	17.4	Off	N	19.7	32.6	50.0

3.7 Radiated Emission Measurement

3.7.1 Limit of Radiated Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.7.2 Measuring Instruments


See list of measuring instruments of this test report.

3.7.3 Test Procedures


- The testing follows the guidelines in FCC KDB Publication No. 558074 (Measurement Guidelines of DTS).
- Use the following spectrum analyzer settings:
 - Span = wide enough to fully capture the emission being measured; RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold.
 - Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.
Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB)
- Follow the guidelines in ANSI C63.4-2003 with respect to maximizing the emission by rotating the EUT, measuring the emission for three EUT orthogonal planes, and adjusting the measurement antenna height and polarization. A pre-amp and a high pass filter are used for this test in order to get the good signal level.

3.7.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



3.7.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

Test Engineer :	Kai Wang and Cona Huang	Temperature :	23~24℃	
		Relative Humidity :	45~46%	

Frequency (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

3.7.6 Test Result of Radiated Emission (30 MHz ~ 10th Harmonic)

Test Mode :	Mode 1	Temperature :	23~24℃
Test Channel :	01	Relative Humidity :	45~46%
Test Engineer :	Kai Wang and Cona Huang	Polarization :	Horizontal
Remark :	1. 2412 MHz is Fundamental Signals which can be ignored. 2. 9648 MHz is not within a restricted band.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
34.86	24.76	-15.24	40.00	38.92	16.73	0.58	31.47	-	-	Peak
104.25	30.47	-13.03	43.50	50.21	10.79	1.02	31.55	100	85	Peak
140.97	27.39	-16.11	43.50	46.09	11.65	1.20	31.55	-	-	Peak
358.10	22.28	-23.72	46.00	36.51	15.00	2.04	31.27	-	-	Peak
679.40	23.09	-22.91	46.00	30.35	20.68	2.90	30.84	-	-	Peak
889.40	25.46	-20.54	46.00	29.76	23.08	3.33	30.71	-	-	Peak
2385.62	59.86	-14.14	74.00	56.43	32.13	5.46	34.16	105	12	Peak
2385.62	47.66	-6.34	54.00	44.22	32.13	5.46	34.15	105	12	Average
2412.00	115.13	-	-	111.69	32.16	5.44	34.16	105	12	Peak
2412.00	107.37	-	-	103.93	32.16	5.44	34.16	105	12	Average
2492.00	51.78	-22.22	74.00	48.31	32.30	5.37	34.20	105	12	Peak
2492.00	40.71	-13.29	54.00	37.24	32.30	5.37	34.20	105	12	Average
8442.00	54.16	-19.84	74.00	43.12	36.00	10.14	35.10	100	92	Peak
8442.00	40.60	-13.40	54.00	29.56	36.00	10.14	35.10	100	92	Average
9648.00	37.32	-57.81	95.13	72.20	-10.32	10.74	35.30	100	0	Peak

Test Mode :	Mode 1	Temperature :	23~24°C
Test Channel :	01	Relative Humidity :	45~46%
Test Engineer :	Kai Wang and Cona Huang	Polarization :	Vertical
Remark :	1. 2412 MHz is Fundamental Signals which can be ignored. 2. 9648 MHz is not within a restricted band.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
38.37	32.32	-7.68	40.00	48.62	14.59	0.61	31.50	100	96	Peak
72.93	23.82	-16.18	40.00	47.66	6.86	0.85	31.55	-	-	Peak
196.05	30.83	-12.67	43.50	52.17	8.85	1.30	31.49	-	-	Peak
372.80	21.40	-24.60	46.00	35.18	15.39	2.08	31.25	-	-	Peak
629.70	22.68	-23.32	46.00	30.50	20.29	2.78	30.89	-	-	Peak
883.80	25.49	-20.51	46.00	29.86	23.02	3.32	30.71	-	-	Peak
2389.61	54.93	-19.07	74.00	51.50	32.13	5.46	34.16	100	68	Peak
2389.61	41.74	-12.26	54.00	38.30	32.13	5.46	34.15	100	68	Average
2412.00	108.75	-	-	105.31	32.16	5.44	34.16	100	68	Peak
2412.00	101.06	-	-	97.62	32.16	5.44	34.16	100	68	Average
2492.00	45.30	-28.70	74.00	41.83	32.30	5.37	34.20	100	68	Peak
2492.00	34.13	-19.87	54.00	30.66	32.30	5.37	34.20	100	68	Average
4824.00	52.73	-21.27	74.00	45.09	34.33	7.81	34.50	100	335	Peak
4824.00	40.89	-13.11	54.00	33.25	34.33	7.81	34.50	100	335	Average
8382.00	54.07	-19.93	74.00	43.07	36.00	10.10	35.10	100	265	Peak
8382.00	40.55	-13.45	54.00	29.55	36.00	10.10	35.10	100	265	Average
9648.00	40.42	-48.33	88.75	75.30	-10.32	10.74	35.30	100	0	Peak

Test Mode :	Mode 2	Temperature :	23~24°C
Test Channel :	06	Relative Humidity :	45~46%
Test Engineer :	Kai Wang and Cona Huang	Polarization :	Horizontal
Remark :	1. 2437 MHz is Fundamental Signals which can be ignored. 2. 9748 MHz is not within a restricted band.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
38.37	26.28	-13.72	40.00	42.58	14.59	0.61	31.50	-	-	Peak
105.06	31.25	-12.25	43.50	50.99	10.79	1.02	31.55	100	301	Peak
145.29	28.61	-14.89	43.50	47.53	11.43	1.21	31.56	-	-	Peak
449.80	22.61	-23.39	46.00	34.26	17.15	2.30	31.10	-	-	Peak
722.10	23.08	-22.92	46.00	29.71	21.15	2.99	30.77	-	-	Peak
867.00	25.53	-20.47	46.00	30.10	22.86	3.29	30.72	-	-	Peak
2316.00	51.39	-22.61	74.00	47.99	32.00	5.53	34.13	103	12	Peak
2316.00	40.68	-13.32	54.00	37.28	32.00	5.53	34.13	103	12	Average
2437.00	115.07	-	-	111.61	32.22	5.41	34.17	103	12	Peak
2437.00	107.58	-	-	104.12	32.22	5.41	34.17	103	12	Average
2484.00	52.15	-21.85	74.00	48.69	32.27	5.38	34.19	103	12	Peak
2484.00	40.60	-13.40	54.00	37.14	32.27	5.38	34.19	103	12	Average
8298.00	54.16	-19.84	74.00	43.22	36.00	10.04	35.10	100	172	Peak
8298.00	40.90	-13.10	54.00	29.96	36.00	10.04	35.10	100	172	Average
9748.00	36.88	-58.19	95.07	71.49	-10.12	10.81	35.30	100	0	Peak



Test Mode :	Mode 2	Temperature :	23~24°C
Test Channel :	06	Relative Humidity :	45~46%
Test Engineer :	Kai Wang and Cona Huang	Polarization :	Vertical
Remark :	1. 2437 MHz is Fundamental Signals which can be ignored. 2. 9748 MHz is not within a restricted band.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
38.10	32.61	-7.39	40.00	48.37	15.13	0.60	31.49	100	182	Peak
72.93	25.60	-14.40	40.00	49.44	6.86	0.85	31.55	-	-	Peak
199.02	30.42	-13.08	43.50	51.77	8.81	1.32	31.48	-	-	Peak
472.20	20.42	-25.58	46.00	31.53	17.60	2.36	31.07	-	-	Peak
679.40	22.81	-23.19	46.00	30.07	20.68	2.90	30.84	-	-	Peak
917.40	26.09	-19.91	46.00	29.92	23.44	3.38	30.65	-	-	Peak
2382.00	50.72	-23.28	74.00	47.29	32.11	5.47	34.15	106	55	Peak
2382.00	40.17	-13.83	54.00	36.74	32.11	5.47	34.15	106	55	Average
2437.00	110.25	-	-	106.79	32.22	5.41	34.17	106	55	Peak
2437.00	102.66	-	-	99.20	32.22	5.41	34.17	106	55	Average
2484.00	50.06	-23.94	74.00	46.60	32.27	5.38	34.19	106	55	Peak
2484.00	38.39	-15.61	54.00	34.93	32.27	5.38	34.19	106	55	Average
4874.00	53.97	-20.03	74.00	46.27	34.35	7.85	34.50	100	21	Peak
4874.00	41.91	-12.09	54.00	34.21	34.35	7.85	34.50	100	21	Average
8397.00	54.00	-20.00	74.00	42.99	36.00	10.11	35.10	100	281	Peak
8397.00	40.79	-13.21	54.00	29.78	36.00	10.11	35.10	100	281	Average
9748.00	40.79	-49.46	90.25	75.40	-10.12	10.81	35.30	100	0	Peak

Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	11	Relative Humidity :	45~46%
Test Engineer :	Kai Wang and Cona Huang	Polarization :	Horizontal
Remark :	1. 2462 MHz is Fundamental Signals which can be ignored. 2. 9848 MHz is not within a restricted band.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
36.21	24.62	-15.38	40.00	39.31	16.20	0.59	31.48	-	-	Peak
79.41	25.06	-14.94	40.00	48.23	7.48	0.88	31.53	-	-	Peak
106.41	32.19	-11.31	43.50	51.74	10.97	1.03	31.55	100	193	Peak
363.00	23.91	-22.09	46.00	37.98	15.13	2.07	31.27	-	-	Peak
690.60	23.12	-22.88	46.00	30.26	20.77	2.92	30.83	-	-	Peak
881.70	25.62	-20.38	46.00	30.02	23.00	3.31	30.71	-	-	Peak
2342.00	51.45	-22.55	74.00	48.04	32.05	5.50	34.14	100	9	Peak
2342.00	40.70	-13.30	54.00	37.29	32.05	5.50	34.14	100	9	Average
2462.00	115.72	-	-	112.26	32.24	5.40	34.18	100	9	Peak
2462.00	108.19	-	-	104.73	32.24	5.40	34.18	100	9	Average
2483.50	58.29	-15.71	74.00	54.83	32.27	5.38	34.19	100	9	Peak
2483.50	46.33	-7.67	54.00	42.87	32.27	5.38	34.19	100	9	Average
8385.00	53.92	-20.08	74.00	42.92	36.00	10.10	35.10	100	281	Peak
8385.00	40.95	-13.05	54.00	29.95	36.00	10.10	35.10	100	281	Average
9848.00	36.01	-59.71	95.72	70.32	-9.90	10.89	35.30	100	0	Peak

Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	11	Relative Humidity :	45~46%
Test Engineer :	Kai Wang and Cona Huang	Polarization :	Vertical
Remark :	1. 2462 MHz is Fundamental Signals which can be ignored. 2. 9848 MHz is not within a restricted band.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
38.10	33.42	-6.58	40.00	49.18	15.13	0.60	31.49	100	282	Peak
106.41	27.12	-16.38	43.50	46.67	10.97	1.03	31.55	-	-	Peak
192.81	30.81	-12.69	43.50	52.14	8.88	1.29	31.50	-	-	Peak
512.10	20.09	-25.91	46.00	30.27	18.40	2.47	31.05	-	-	Peak
694.10	23.04	-22.96	46.00	30.14	20.80	2.93	30.83	-	-	Peak
861.40	25.55	-20.45	46.00	30.17	22.81	3.29	30.72	-	-	Peak
2342.00	51.75	-22.25	74.00	48.34	32.05	5.50	34.14	100	62	Peak
2342.00	37.34	-16.66	54.00	33.93	32.05	5.50	34.14	100	62	Average
2462.00	110.09	-	-	106.63	32.24	5.40	34.18	100	62	Peak
2462.00	102.53	-	-	99.07	32.24	5.40	34.18	100	62	Average
2484.42	52.46	-21.54	74.00	49.00	32.27	5.38	34.19	100	62	Peak
2484.42	40.44	-13.56	54.00	36.98	32.27	5.38	34.19	100	62	Average
4924.00	54.11	-19.89	74.00	46.35	34.37	7.89	34.50	100	359	Peak
4924.00	42.02	-11.98	54.00	34.26	34.37	7.89	34.50	100	359	Average
8421.00	54.50	-19.50	74.00	43.47	36.00	10.13	35.10	100	321	Peak
8421.00	41.28	-12.72	54.00	30.25	36.00	10.13	35.10	100	321	Average
9848.00	38.87	-51.22	90.09	73.18	-9.90	10.89	35.30	100	0	Peak

Test Mode :	Mode 4	Temperature :	23~24°C
Test Channel :	01	Relative Humidity :	45~46%
Test Engineer :	Kai Wang and Cona Huang	Polarization :	Horizontal
Remark :	1. 2412 MHz is Fundamental Signals which can be ignored. 2. 9648 MHz is not within a restricted band.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
38.37	22.93	-17.07	40.00	39.23	14.59	0.61	31.50	-	-	Peak
106.14	29.32	-14.18	43.50	48.96	10.88	1.03	31.55	100	117	Peak
147.45	26.74	-16.76	43.50	45.75	11.34	1.21	31.56	-	-	Peak
363.00	20.70	-25.30	46.00	34.77	15.13	2.07	31.27	-	-	Peak
761.30	23.97	-22.03	46.00	29.91	21.68	3.08	30.70	-	-	Peak
911.80	26.29	-19.71	46.00	30.23	23.36	3.37	30.67	-	-	Peak
2389.99	47.49	-6.51	54.00	44.06	32.13	5.46	34.16	103	7	Average
2389.99	67.64	-6.36	74.00	64.21	32.13	5.46	34.16	103	7	Peak
2412.00	106.60	-	-	103.16	32.16	5.44	34.16	103	7	Peak
2412.00	96.69	-	-	93.25	32.16	5.44	34.16	103	7	Average
2484.00	48.55	-25.45	74.00	45.09	32.27	5.38	34.19	103	7	Peak
2484.00	37.54	-16.46	54.00	34.08	32.27	5.38	34.19	103	7	Average
8442.00	53.92	-20.08	74.00	42.88	36.00	10.14	35.10	100	121	Peak
8442.00	40.82	-13.18	54.00	29.78	36.00	10.14	35.10	100	121	Average
9648.00	39.19	-47.41	86.60	74.07	-10.32	10.74	35.30	100	0	Peak

Test Mode :	Mode 4	Temperature :	23~24°C
Test Channel :	01	Relative Humidity :	45~46%
Test Engineer :	Kai Wang and Cona Huang	Polarization :	Vertical
Remark :	1. 2412 MHz is Fundamental Signals which can be ignored. 2. 9648 MHz is not within a restricted band.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
37.29	31.55	-8.45	40.00	47.31	15.13	0.60	31.49	100	66	Peak
101.82	22.80	-20.70	43.50	42.82	10.52	1.00	31.54	-	-	Peak
199.02	29.59	-13.91	43.50	50.94	8.81	1.32	31.48	-	-	Peak
372.10	18.78	-27.22	46.00	32.56	15.39	2.08	31.25	-	-	Peak
744.50	23.68	-22.32	46.00	29.88	21.46	3.05	30.71	-	-	Peak
940.50	26.13	-19.87	46.00	29.48	23.80	3.44	30.59	-	-	Peak
2389.42	44.29	-9.71	54.00	40.85	32.13	5.46	34.15	100	66	Average
2389.42	63.19	-10.81	74.00	59.75	32.13	5.46	34.15	100	66	Peak
2412.00	102.64	-	-	99.20	32.16	5.44	34.16	100	66	Peak
2412.00	93.16	-	-	89.72	32.16	5.44	34.16	100	66	Average
2492.00	32.74	-21.26	54.00	29.27	32.30	5.37	34.20	100	66	Average
2492.00	43.94	-30.06	74.00	40.47	32.30	5.37	34.20	100	66	Peak
8433.00	53.68	-20.32	74.00	42.65	36.00	10.13	35.10	100	281	Peak
8433.00	40.46	-13.54	54.00	29.43	36.00	10.13	35.10	100	281	Average
9648.00	40.05	-42.59	82.64	74.93	-10.32	10.74	35.30	100	0	Peak

Test Mode :	Mode 5	Temperature :	23~24°C
Test Channel :	06	Relative Humidity :	45~46%
Test Engineer :	Kai Wang and Cona Huang	Polarization :	Horizontal
Remark :	1. 2437 MHz is Fundamental Signals which can be ignored. 2. 9748 MHz is not within a restricted band.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
105.06	29.25	-14.25	43.50	48.99	10.79	1.02	31.55	100	64	Peak
152.85	29.22	-14.28	43.50	48.61	10.95	1.21	31.55	-	-	Peak
238.98	24.88	-21.12	46.00	43.41	11.37	1.52	31.42	-	-	Peak
369.30	20.50	-25.50	46.00	34.37	15.31	2.08	31.26	-	-	Peak
643.00	22.09	-23.91	46.00	29.75	20.40	2.82	30.88	-	-	Peak
906.90	25.61	-20.39	46.00	29.65	23.28	3.36	30.68	-	-	Peak
2388.00	46.75	-27.25	74.00	43.31	32.13	5.46	34.15	102	8	Peak
2388.00	35.70	-18.30	54.00	32.26	32.13	5.46	34.15	102	8	Average
2437.00	106.75	-	-	103.30	32.19	5.43	34.17	102	8	Peak
2437.00	96.48	-	-	93.02	32.22	5.41	34.17	102	8	Average
2484.00	37.70	-16.30	54.00	34.24	32.27	5.38	34.19	102	8	Average
2484.00	48.42	-25.58	74.00	44.96	32.27	5.38	34.19	102	8	Peak
8325.00	53.81	-20.19	74.00	42.85	36.00	10.06	35.10	100	206	Peak
8325.00	40.71	-13.29	54.00	29.75	36.00	10.06	35.10	100	206	Average
9748.00	38.08	-48.67	86.75	72.66	-10.10	10.82	35.30	100	0	Peak

Test Mode :	Mode 5	Temperature :	23~24°C
Test Channel :	06	Relative Humidity :	45~46%
Test Engineer :	Kai Wang and Cona Huang	Polarization :	Vertical
Remark :	1. 2437 MHz is Fundamental Signals which can be ignored. 2. 9748 MHz is not within a restricted band.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
38.10	31.61	-8.39	40.00	47.37	15.13	0.60	31.49	100	288	Peak
101.82	23.91	-19.59	43.50	43.93	10.52	1.00	31.54	-	-	Peak
199.02	29.42	-14.08	43.50	50.77	8.81	1.32	31.48	-	-	Peak
472.20	20.42	-25.58	46.00	31.53	17.60	2.36	31.07	-	-	Peak
777.40	23.87	-22.13	46.00	29.55	21.91	3.10	30.69	-	-	Peak
856.50	26.51	-19.49	46.00	31.20	22.76	3.28	30.73	-	-	Peak
2390.00	48.84	-25.16	74.00	45.41	32.13	5.46	34.16	100	61	Peak
2390.00	35.67	-18.33	54.00	32.24	32.13	5.46	34.16	100	61	Average
2437.00	101.66	-	-	98.21	32.19	5.43	34.17	100	61	Peak
2437.00	93.16	-	-	89.70	32.22	5.41	34.17	100	61	Average
2484.00	33.53	-20.47	54.00	30.07	32.27	5.38	34.19	100	61	Average
2484.00	44.91	-29.09	74.00	41.45	32.27	5.38	34.19	100	61	Peak
8277.00	54.51	-19.49	74.00	43.58	36.00	10.03	35.10	100	109	Peak
8277.00	40.88	-13.12	54.00	29.95	36.00	10.03	35.10	100	109	Average
9748.00	39.16	-42.50	81.66	73.74	-10.10	10.82	35.30	100	0	Peak

Test Mode :	Mode 6	Temperature :	23~24°C
Test Channel :	11	Relative Humidity :	45~46%
Test Engineer :	Kai Wang and Cona Huang	Polarization :	Horizontal
Remark :	1. 2462 MHz is Fundamental Signals which can be ignored. 2. 9848 MHz is not within a restricted band.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
36.21	22.62	-17.38	40.00	37.31	16.20	0.59	31.48	-	-	Peak
106.41	30.19	-13.31	43.50	49.74	10.97	1.03	31.55	100	67	Peak
146.37	27.33	-16.17	43.50	46.30	11.38	1.21	31.56	-	-	Peak
357.40	21.37	-24.63	46.00	35.60	15.00	2.04	31.27	-	-	Peak
635.30	22.57	-23.43	46.00	30.31	20.34	2.80	30.88	-	-	Peak
841.80	26.10	-19.90	46.00	30.95	22.62	3.25	30.72	-	-	Peak
2390.00	49.33	-24.67	74.00	45.90	32.13	5.46	34.16	107	27	Peak
2390.00	37.53	-16.47	54.00	34.10	32.13	5.46	34.16	107	27	Average
2462.00	107.76	-	-	104.31	32.24	5.40	34.19	107	27	Peak
2462.00	98.15	-	-	94.69	32.24	5.40	34.18	107	27	Average
2483.50	69.07	-4.93	74.00	65.61	32.27	5.38	34.19	107	27	Peak
2483.50	48.43	-5.57	54.00	44.97	32.27	5.38	34.19	107	27	Average
8385.00	54.38	-19.62	74.00	43.38	36.00	10.10	35.10	100	59	Peak
8385.00	40.66	-13.34	54.00	29.66	36.00	10.10	35.10	100	59	Average
9848.00	36.31	-51.45	87.76	70.62	-9.90	10.89	35.30	100	0	Peak

Test Mode :	Mode 6	Temperature :	23~24°C
Test Channel :	11	Relative Humidity :	45~46%
Test Engineer :	Kai Wang and Cona Huang	Polarization :	Vertical
Remark :	1. 2462 MHz is Fundamental Signals which can be ignored. 2. 9848 MHz is not within a restricted band.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
38.10	31.42	-8.58	40.00	47.18	15.13	0.60	31.49	100	99	Peak
101.01	23.49	-20.01	43.50	43.60	10.43	1.00	31.54	-	-	Peak
199.29	29.95	-13.55	43.50	51.31	8.80	1.32	31.48	-	-	Peak
475.70	19.29	-26.71	46.00	30.32	17.66	2.37	31.06	-	-	Peak
747.30	24.40	-21.60	46.00	30.58	21.48	3.05	30.71	-	-	Peak
937.00	25.74	-20.26	46.00	29.17	23.74	3.43	30.60	-	-	Peak
2390.00	46.34	-27.66	74.00	42.91	32.13	5.46	34.16	188	98	Peak
2390.00	34.58	-19.42	54.00	31.15	32.13	5.46	34.16	188	98	Average
2462.00	103.17	-	-	99.71	32.24	5.40	34.18	188	98	Peak
2462.00	93.66	-	-	90.20	32.24	5.40	34.18	188	98	Average
2483.50	41.98	-12.02	54.00	38.52	32.27	5.38	34.19	188	98	Average
2483.50	62.39	-11.61	74.00	58.93	32.27	5.38	34.19	188	98	Peak
8397.00	53.87	-20.13	74.00	42.86	36.00	10.11	35.10	100	99	Peak
8397.00	40.99	-13.01	54.00	29.98	36.00	10.11	35.10	100	99	Average
9848.00	39.45	-43.72	83.17	73.76	-9.90	10.89	35.30	100	0	Peak

3.8 Antenna Requirements

3.8.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.8.2 Antenna Connected Construction

The antennas type used in this product is PIFA Antenna without connector and it is considered to meet antenna requirement.

3.8.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
Spectrum Analyzer	R&S	FSP40	100055	9kHz~40GHz	Jun. 23, 2009	Jun. 22, 2010	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	0932001	N/A	Sep. 17, 2009	Sep. 16, 2010	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	0846202	N/A	Sep. 10, 2009	Sep. 09, 2010	Conducted (TH02-HY)
EMI Test Receive	R&S	ESCS 30	100356	9KHz – 2.75GHz	Aug. 05, 2009	Aug. 04, 2010	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100081	9kHz~30MHz	Nov. 30, 2009	Nov. 29, 2010	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100080	9kHz~30MHz	Nov. 23, 2009	Nov. 22, 2010	Conduction (CO05-HY)
AC Power Source	APC	APC-1000W	N/A	N/A	N/A	N/A	Conduction (CO05-HY)
System Simulator	R&S	CMU200	105934	N/A	Nov. 11, 2008	Nov. 10, 2010	Conduction (CO05-HY)
Bilog Antenna	SCHAFFNER	CBL6111C	2726	30MHz ~ 1GHz	Oct. 31, 2009	Oct. 30, 2010	Radiation (03CH07-HY)
Spectrum Analyzer	R&S	FSP	101067	9KHz ~ 30GHz	Dec. 04, 2009	Dec. 03, 2010	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 20, 2009	Aug. 19, 2010	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	15GHz- 40GHz	Oct. 14, 2009	Oct. 13, 2010	Radiation (03CH07-HY)
Pre Amplifier	Agilent	8449B	3008A02362	1GHz~ 26.5GHz	Dec.09,2009	Dec. 08, 2010	Radiation (03CH07-HY)
Pre Amplifier	COM-POWER	PA-103A	161241	10-1000MHz.32dB.GAIN	Mar. 27, 2010	Mar. 26, 2011	Radiation (03CH07-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.10	Normal (k=2)	0.05
Cable Loss	0.10	Normal (k=2)	0.05
AMN Insertion Loss	2.50	Rectangular	0.63
Receiver Specification	1.50	Rectangular	0.43
Site Imperfection	1.39	Rectangular	0.80
Mismatch	+0.34 / -0.35	U-Shape	0.24
Combined Standard Uncertainty $U_c(y)$	1.13		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.26		

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty $U_c(y)$	1.27		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54		

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	± 0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	± 1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	± 0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	± 2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	± 1.50	Rectangular	0.87	1	0.87
Site Imperfection	± 2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty $U_c(y)$	2.36				
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72				



Appendix A. Photographs of EUT

Please refer to Sporton report number EP051810-01 as below.