



REPORT No.: SZ22080079E01

TEST REPORT

APPLICANT : Acer Incorporated

PRODUCT NAME : Acer Connect

MODEL NAME : M3

BRAND NAME : Acer

FCC ID : HLZM3

STANDARD(S) : 47 CFR Part 15 Subpart B

RECEIPT DATE : 2022-11-10

TEST DATE : 2022-11-15 to 2022-11-16

ISSUE DATE : 2023-03-07

Edited by: Chen Bilian
Chen Bilian(Rapporteur)

Approved by: Xiao Xiong
Xiao Xiong(Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.



Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen ,GuangDong Province, P. R. China

Tel: 86-755-36698555
Http://www.morlab.cn

Fax: 86-755-36698525
E-mail: service@morlab.cn





DIRECTORY

1. Technical Information	3
1.1. Applicant and Manufacturer Information	3
1.2. Equipment Under Test (EUT) Description	3
2. Test Results	6
2.1. Applied Reference Documents	6
2.2. EUT Setup and Operating Conditions	7
3. 47 CFR Part 15B Requirements	9
3.1. Conducted Emission	9
3.2. Radiated Emission	13
Annex A Test Uncertainty	20
Annex B Testing Laboratory Information	21

Change History		
Version	Date	Reason for change
1.0	2023-03-07	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	Acer Incorporated
Applicant Address:	8F, 88, Sec. 1, Xintai 5th Rd. Xizhi, New Taipei City 221 Taiwan
Manufacturer:	Acer Incorporated
Manufacturer Address:	8F, 88, Sec. 1, Xintai 5th Rd. Xizhi, New Taipei City 221 Taiwan

1.2. Equipment Under Test (EUT) Description

Product Name:	Acer Connect
EUT No.:	2#, 3#
Hardware Version:	L30-MB-V1.1
Software Version:	ASW2106_UN_1201_T0054
Tx Frequency:	LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 13: 777 MHz ~ 787 MHz LTE Band 14: 788 MHz ~ 798 MHz LTE Band 17: 704 MHz ~ 716 MHz LTE Band 25: 1850 MHz ~ 1915 MHz LTE Band 26: 814 MHz ~ 849 MHz LTE Band 30: 2305 MHz ~ 2315 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 41: 2496 MHz ~ 2690 MHz LTE Band 42: 3450 MHz ~ 3600 MHz LTE Band 48: 3550 MHz ~ 3700 MHz LTE Band 66: 1710 MHz ~ 1780 MHz LTE Band 71: 663 MHz ~ 698 MHz 5G NR n2: 1850 MHz ~ 1910 MHz 5G NR n5: 824 MHz ~ 849 MHz 5G NR n7: 2500 MHz ~ 2570 MHz 5G NR n38: 2570 MHz ~ 2620 MHz 5G NR n41: 2496 MHz ~ 2690 MHz 5G NR n66: 1710 MHz ~ 1780 MHz



	5G NR n71: 663 MHz ~ 698 MHz 5G NR n77: 3450 MHz ~ 3550 MHz, 3700 MHz ~ 3980 MHz 5G NR n78: 3450 MHz ~ 3550 MHz, 3700 MHz ~ 3800 MHz 802.11b/g/n/ax: 2412 MHz ~ 2462 MHz 802.11a/ac/n/ax: 5180 MHz ~ 5240 MHz; 5745 MHz ~ 5825 MHz
Rx Frequency:	LTE Band 2: 1930 MHz ~ 1990 MHz LTE Band 4: 2110 MHz ~ 2155 MHz LTE Band 5: 869 MHz ~ 894 MHz LTE Band 7: 2620 MHz ~ 2690 MHz LTE Band 12: 729 MHz ~ 746 MHz LTE Band 13: 746 MHz ~ 756 MHz LTE Band 14: 758 MHz ~ 768 MHz LTE Band 17: 734 MHz ~ 746 MHz LTE Band 25: 1930 MHz ~ 1995 MHz LTE Band 26: 859 MHz ~ 894 MHz LTE Band 29: 717 MHz ~ 728 MHz LTE Band 30: 2350 MHz ~ 2360 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 41: 2496 MHz ~ 2690 MHz LTE Band 42: 3450 MHz ~ 3600 MHz LTE Band 48: 3550 MHz ~ 3700 MHz LTE Band 66: 2110 MHz ~ 2200 MHz LTE Band 71: 617 MHz ~ 652 MHz 5G NR n2: 1930 MHz ~ 1990 MHz 5G NR n5: 869 MHz ~ 894 MHz 5G NR n7: 2620 MHz ~ 2690 MHz 5G NR n38: 2570 MHz ~ 2620 MHz 5G NR n41: 2496 MHz ~ 2690 MHz 5G NR n66: 2110 MHz ~ 2200 MHz 5G NR n71: 617 MHz ~ 652 MHz 5G NR n77: 3450 MHz ~ 3550 MHz, 3700 MHz ~ 3980 MHz 5G NR n78: 3450 MHz ~ 3550 MHz, 3700 MHz ~ 3800 MHz 802.11b/g/n/ax: 2412 MHz ~ 2462 MHz 802.11a/ac/n/ax: 5180 MHz ~ 5240 MHz; 5745 MHz ~ 5825 MHz
EN_DC:	DC_5A_n2, DC_12A_n2, DC_13A_n2, DC_66A_n2, DC_71A_n2, DC_2A_n7, DC_5A_n7, DC_12A_n7, DC_13A_n7, DC_2A_n66, DC_5A_n66, DC_12A_n66, DC_13A_n66, DC_71A_n66, DC_5A_n38, DC_12A_n38, DC_71A_n38, DC_2A_n41, DC_12A_n41, DC_26A_n41, DC_66A_n41, DC_71A_n41, DC_2A_n77, DC_5A_n77, DC_7A_n77, DC_12A_n77, DC_13A_n77, DC_14A_n77, DC_25A_n77, DC_26A_n77, DC_30A_n77, DC_2A_n78, DC_5A_n78, DC_7A_n78,



	DC_12A_n78, DC_13A_n78, DC_25A_n78, DC_26A_n78, DC_66A_n78, DC_71A_n78	
Accessory:	Battery:	
	Brand Name:	N/A
	Model No.:	765395
	Serial No.:	(N/A, marked #1 by test site)
	Capacity:	6500 mAh
	Rated Voltage:	3.85 V
	Charge Limit:	4.4 V
	Manufacturer:	Huizhou Highpower Technology Co., Ltd.

Note:

1. For a more detailed description, please refer to specification or user's manual supplied by the applicant and/or manufacturer.

2. Test Results

2.1. Applied Reference Documents

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination Remark
1	15.107	Conducted Emission	2022.11.15	Fan Zehang	PASS	No deviation
2	15.109	Radiated Emission	2022.11.16	Li Hanbin	PASS	No deviation

Note 1:The tests were performed according to the method of measurements prescribed in ANSI C63.4-2014.

Note 2:Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 3:When the test result is a critical value,we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.



2.2. EUT Setup and Operating Conditions

Test Item	
Mode 1	LTE Band 2 Idle + 5G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 2	LTE Band 4 Idle + 2.4G WLAN Idle + PC + PC Adapter + Battery + Working Mode
Mode 3	LTE Band 5 Idle + 5G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 4	LTE Band 7 Idle + 2.4G WLAN Idle + PC + PC Adapter + Battery + Working Mode
Mode 5	LTE Band 12 Idle + 5G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 6	LTE Band 13 Idle + 2.4G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 7	LTE Band 14 Idle + 5G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 8	LTE Band 17 Idle + 2.4G WLAN Idle + PC + PC Adapter + Battery + Working Mode
Mode 9	LTE Band 25 Idle + 5G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 10	LTE Band 26 Idle + 2.4G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 11	LTE Band 29 Idle + 5G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 12	LTE Band 30 Idle + 2.4G WLAN Idle + PC + PC Adapter + Battery + Working Mode
Mode 13	LTE Band 38 Idle + 5G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 14	LTE Band 41 Idle + 2.4G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 15	LTE Band 42 Idle + 5G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 16	LTE Band 48 Idle + 2.4G WLAN Idle + PC + PC Adapter + Battery + Working Mode
Mode 17	LTE Band 66 Idle + 5G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 18	LTE Band 71 Idle + 2.4G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 19	5G NR n2 Idle + 5G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 20	5G NR n5 Idle + 2.4G WLAN Idle + PC + PC Adapter + Battery + Working Mode
Mode 21	5G NR n7 Idle + 5G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 22	5G NR n38 Idle + 2.4G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 23	5G NR n41 Idle + 5G WLAN Idle + PC + PC Adapter + Battery + Working Mode
Mode 24	5G NR n66 Idle + 2.4G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 25	5G NR n71 Idle + 5G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 26	5G NR n77 Idle + 2.4G WLAN Idle + PC + PC Adapter + Battery + Working Mode
Mode 27	5G NR n78 Idle + 5G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 28	DC_5A_n2A Idle + 2.4G WLAN Idle + PC + PC Adapter + Battery + Working Mode
Mode 29	DC_2A_n7A Idle + 5G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 30	DC_12A_n77A Idle + 5G WLAN Idle + AC Adapter + Battery + Working Mode
Mode 31	LTE Band 29 Idle + 5G WLAN Idle + Mobile Phone + Reverse Charging Mode
Remark: The above test mode in boldface (Mode 1) was the worst case of conducted emission test, only the test data of these modes were reported. The above test mode in boldface (Mode 2) was the	



worst case of radiated emission test, only the test data of these modes were reported.
--

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15 - 35
Relative Humidity (%):	30 - 60
Atmospheric Pressure (kPa):	86 - 106

3. 47 CFR Part 15B Requirements

3.1. Conducted Emission

3.1.1. Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- The limit subjects to the Class B digital device.
- The lower limit shall apply at the band edges.
- The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.1.2. Test Setup

Please refer to Annex A for the photographs of the Test Configuration.






The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides $50\Omega/50\mu\text{H}$ of coupling impedance for the measuring instrument. A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

The power strip or extension cord has been investigated to make sure that the LISN integrity is maintained with respect to the impedance characteristics as prescribed in ANSI C63.4-2014 at Clause 4.3.


3.1.3. Test Result

Set RBW=9 kHz, VBW=30 kHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

A. Test Plot and Suspicious Points:



No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quasi-peak	Average	Quasi-peak	Average		
1	0.1635	53.94	31.99	65.28	55.28	Line	PASS
2	0.1950	50.84	32.60	63.82	53.82		PASS
3	0.2276	47.40	30.12	62.54	52.54		PASS
4	0.2393	48.89	30.82	62.12	52.12		PASS
5	0.3784	40.60	27.37	58.31	48.31		PASS
6	0.4740	33.03	25.64	56.44	46.44		PASS



No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quasi-peak	Average	Quasi-peak	Average		
1	0.1640	52.29	31.16	65.26	55.26	Neutral	PASS
2	0.1769	51.26	31.08	64.63	54.63		PASS
3	0.1956	53.76	32.87	63.79	53.79		PASS
4	0.2591	50.15	30.44	61.46	51.46		PASS
5	0.2755	48.00	30.16	60.95	50.95		PASS
6	0.5539	39.04	27.64	56.00	46.00		PASS



3.2. Radiated Emission

3.2.1. Requirement

According to FCC section 15.109 (a), the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency Range (MHz)	Field Strength Limitation at 3m Measurement Dist	
	($\mu\text{V/m}$)	(dB $\mu\text{V/m}$)
30.0 - 88.0	100	20log 100
88.0 - 216.0	150	20log 150
216.0 - 960.0	200	20log 200
Above 960.0	500	20log 500

As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

Note:

- 1) The tighter limit shall apply at the boundary between two frequency range.
- 2) Limitation expressed in dB $\mu\text{V/m}$ is calculated by 20log Emission Level($\mu\text{V/m}$).


3.2.2. Frequency Range of Measurement

According to 15.33(b)(1), the frequency range of radiated measurement for the EUT is listed in the following table:


Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30.
1.705-108	1000.
108-500	2000.
500-1000	5000.
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower.

3.2.3. Test Setup

- 1) For radiated emissions from 30MHz to 1GHz



- 2) For radiated emissions above 1GHz





The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower.

For the test Antenna:

In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

For measurements below 1GHz the resolution bandwidth is set to 120 kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.


For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video bandwidth is set to 3MHz for peak measurements and as applicable for average measurements.

3.2.4. Test Result


The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of emissions (6GHz-30GHz) which are attenuated more than 20 dB below the permissible value need not be reported.


Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.




No.	Fre. MHz	PK dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	31.9402	26.26	N.A.	N.A.	N.A.	40.00	N.A.	V	PASS
2	64.4384	30.01	N.A.	N.A.	N.A.	40.00	N.A.	V	PASS
3	77.1467	27.68	N.A.	N.A.	N.A.	40.00	N.A.	V	PASS
4	200.4460	22.95	N.A.	N.A.	N.A.	43.50	N.A.	V	PASS
5	718.4778	38.25	N.A.	N.A.	N.A.	46.00	N.A.	V	PASS
6	974.9715	38.37	N.A.	N.A.	N.A.	54.00	N.A.	V	PASS



No.	Fre. MHz	PK dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	1175.0350	47.59	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
2	1381.0762	45.10	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
3	1658.1316	46.35	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
4	2129.2258	46.89	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
5	3268.4537	46.43	N.A.	N.A.	74.00	N.A.	54.00	V	PASS
6	5997.9996	46.95	N.A.	N.A.	74.00	N.A.	54.00	V	PASS



No.	Fre. MHz	PK dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	32.2312	29.87	N.A.	N.A.	N.A.	40.00	N.A.	H	PASS
2	51.2451	22.85	N.A.	N.A.	N.A.	40.00	N.A.	H	PASS
3	194.0434	30.21	N.A.	N.A.	N.A.	43.50	N.A.	H	PASS
4	435.3065	29.07	N.A.	N.A.	N.A.	46.00	N.A.	H	PASS
5	801.9062	37.63	N.A.	N.A.	N.A.	46.00	N.A.	H	PASS
6	973.9044	37.96	N.A.	N.A.	N.A.	54.00	N.A.	H	PASS



No.	Fre. MHz	PK dBμV/m	QP dBμV/m	AV dBμV/m	Limit-PK dBμV/m	Limit-QP dBμV/m	Limit-AV dBμV/m	ANT	Verdict
1	1069.0138	49.88	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
2	1258.0516	46.18	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
3	1809.1618	44.42	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
4	2152.2304	47.82	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
5	4043.6087	45.94	N.A.	N.A.	74.00	N.A.	54.00	H	PASS
6	4991.7984	47.90	N.A.	N.A.	74.00	N.A.	54.00	H	PASS

Annex A Test Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission Measurement

Measuring Uncertainty for a Level of Confidence of 95%(U=2Uc(y))	9kHz-150kHz	±3.3dB
	150kHz-30MHz	±2.8dB

Uncertainty of Radiated Emission Measurement

Measuring Uncertainty for a Level of Confidence of 95%(U=2Uc(y))	30MHz-200MHz	±5.06dB
	200MHz-1000MHz	±5.04dB
	1GHz-6GHz	±5.18dB
	6GHz-18GHz	±5.48dB



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Accreditation Certificate

Accredited Testing Laboratory:	The FCC designation number is CN1192. Test firm registration number is 226174. (Shenzhen Morlab Communications Technology Co., Ltd.)
---------------------------------------	--

4. Test Software Utilized

Model	Version Number	Producer
TS+ -[JS32-RE]	Version 2.5.0.6	Tonscend
TS+ -[JS32-CE]	Version 2.5.0.0	Tonscend

**5. Test Equipments Utilized**

Description	Model	Serial No.	Manufacturer	Cal. Date	Due. Date
Bi-Log Antenna	VULB 9163	9163-519	SCHWARZBECK	2022/5/25	2025/5/24
Horn Antenna	BBHA 9120D	01774	SCHWARZBECK	2022/7/13	2025/7/12
Receiver	N9038A	MY564000 93	KEYSIGHT	2022/3/3	2023/3/2
6db Attenuator	BW-N6W5+	E191001	Mini-circuits	2022/10/11	2023/10/10
Preamplifier	S020180L3203	61171/611 72	LUCIX CORP.	2022/7/8	2023/7/7
Preamplifier	S10M100L3802	46732	LUCIX CORP.	2022/7/8	2023/7/7
Receiver	ESPI	101052	R&S	2022/7/7	2023/7/6
LISN	NSLK 8127	8127449	Schwarzbeck	2022/3/3	2023/3/2
10dB Pulse Limiter	VTSD 9561-F	VTSD 9561 F-B #206	SCHWARZBECK	2022/7/6	2023/7/5
RF Cable	PE330	MRE001	Pasternack	N/A	N/A
RF Cable	CLU18	MRE002	Pasternack	N/A	N/A
RF Cable	CLU18	MRE003	Pasternack	N/A	N/A
RF Cable	QA360-40-KK- 0.5	22290045	Qualwave	N/A	N/A
RF Cable	QA360-40-KKF -2	22290046	Qualwave	N/A	N/A
RF Cable	QA500-18-NN- 5	22120181	Qualwave	N/A	N/A
RF Coaxial Cable	BNC	MRE04	Qualwave	N/A	N/A
Receiver	N9038A	MY541300 16	Agilent	2022/7/7	2023/7/6
Horn Antenna	BBHA9170	BBHA9170 #773	SCHWARZBECK	2022/7/14	2025/7/13
Preamplifier	DCLNA0118-40 C-S	DS77209	Decentest	2022/7/23	2023/7/22



REPORT No.: SZ22080079E01

6.Ancillary Equipment Utilized

Equipment Name	Serial No.	Type	Manufacturer
PC	20210357	P144G	DELL
PC Adapter	N/A	HA65NM190	DELL
AC Adapter	K68249G6209896	HW-059200CHQ	HUAWEI

_____ END OF REPORT _____