



Global Product Certification
EMC-EMF Safety Approvals

EMC Technologies Pty Ltd
ABN 82 057 105 549
176 Harrick Road
Keilor Park Victoria Australia 3042

Ph: + 613 9365 1000
Fax: + 613 9331 7455
email: melb@emctech.com.au

EMI TEST REPORT for CERTIFICATION to FCC PART 15 Subpart B (Section 15.121)

FCC ID: HNL-G9E

Test Sample: Software-defined DDC-based Radio Receiver
Model Number: G3 Series
Manufacturer: Radixon Group Pty Ltd

Tested for: Robotron Pty Ltd

Report Number: M110931_Cert_G3_Series_USB

Issue Date: 14th November 2011

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

**EMI TEST REPORT FOR CERTIFICATION
of
Software-defined DDC-based Radio Receiver
to
FCC PART 15 Subpart B (Section 15.121)**

EMC Technologies Report No. M110931_Cert_G3_Series_USB

Issue Date: 14th November 2011

CONTENTS

- 1.0 INTRODUCTION**
- 2.0 GENERAL INFORMATION**
- 3.0 CONDUCTED EMI MEASUREMENTS**
- 4.0 RADIATED EMI MEASUREMENTS**
- 5.0 ANTENNA PORT MEASUREMENTS**
- 6.0 COMPLIANCE STATEMENT**
- 7.0 MEASUREMENT UNCERTAINTIES**

APPENDIX A: MEASUREMENT INSTRUMENT DETAILS

APPENDIX B: TEST SAMPLE PHOTOGRAPHS

APPENDIX C: BLOCK DIAGRAM

APPENDIX D: OPERATIONAL DESCRIPTIONS

APPENDIX E: SCHEMATICS

APPENDIX F: USER MANUAL

APPENDIX G: FCC ID LABELLING

APPENDIX H: GRAPHS of EMI MEASUREMENTS



Accreditation No. 5292

Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart B (Section 15.121)

Report Number: M110931_Cert_G3_Series_USB

Test Sample: Software-defined DDC-based Radio Receiver
Model Number: G3 Series
Serial Number: 11G18006
Part Number: G39DDCe

FCC ID: HNL-G9E

Manufacturer: Radixon Group Pty Ltd

Trading Name: WiNRADiO Communications

Tested for: Robotron Pty Ltd
Address: 15 Stamford Road,
Oakleigh, VIC 3166 Australia

Phone: +61 3 9568 2568
Fax: +61 3 9568 1377
Responsible Party: Milan Hudecek

Equipment Type: Unintentional Radiator (Scanning Receiver)

Test Standards: FCC Part 15 Section 101 Unintentional Radiators
FCC Part 15 Section 121 Scanning Receivers
FCC Part 15 Section 107 Conducted limits
FCC Part 15 Section 109 Radiated limits
ANSI C63.4-2009

Test Dates: 4th October to 2nd November 2011



Test Officers:
Matthew Grimwood
Chieu Huynh

Attestation: *I hereby certify that the device(s) described herein were tested as described in this report and that the data included is that which was obtained during such testing.*



Authorised Signature:
Chieu Huynh
EMC Technologies Pty Ltd



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart B (Section 15.121)
on the
Software-defined DDC-based Radio Receiver

1. INTRODUCTION

This report details the results of EMI tests and measurements performed on the Software-defined DDC-based Radio Receiver, model: G3 Series in accordance with the Federal Communications Commission (FCC) regulations as detailed in Title 47 CFR, Part 15 Subpart B Rules for Unintentional Radiators and Title 47 CFR, Part 15.121 for Scanning Receivers.

The results and technical details of the test sample are detailed in this report. The test sample was found to comply with the conducted and radiated emission requirements of Part 15.107 and Part 15.109 respectively.

1.1 Summary of Results

Conducted Emissions:

FCC Part 15.107

Complies Class B limit, margin of > 10 dB

Radiated Emissions:

FCC Part 15.109 (30 – 1000 MHz)

Config #1: (Tune Frequency - 30 MHz)

Complies Class B limit, margin of 0.4 dB

Config #2: (Tune Frequency - 475 MHz)

Complies Class B limit, margin of 2.5 dB

Config #3: (Tune Frequency - 960 MHz)

Complies Class B limit, margin of 3.8 dB

FCC Part 15.109 (1 GHz to 37 GHz):

Config #1: (Tune Frequency - 30 MHz)

Complies Class B limit, margin of > 10 dB

Config #2: (Tune Frequency - 475 MHz)

Complies Class B limit, margin of > 10 dB

Config #3: (Tune Frequency - 960 MHz)

Complies Class B limit, margin of 1.9 dB

The measurement procedure used was in accordance with ANSI C63.4-2009. The instrumentation conformed to the requirements of ANSI C63.2-1996.

1.2 EUT – Voltage Power Conditions

Testing was performed with the test sample powered off an AC/DC plug pack.

1.3 Modifications

Refer to Appendix B1 - Internal photos.



Accreditation No. 5292

Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

2. GENERAL INFORMATION

(Information supplied by Client)

2.1 Product Specifications

Test Sample:	Software-defined DDC-based Radio Receiver
Manufacturer:	Radixon Group Pty Ltd
Model Number:	G3 Series
Serial Number:	11G18006
Part Number:	G39DDCe
Microprocessors:	FPGA type EP3C10F256C7 is used as control unit and CY7C6801A USB interface
Crystal Frequencies:	10 MHz and 100 MHz
Input Supply:	11-13V at 1.2A
Equipment Type:	Unintentional Radiator (Scanning Receiver)

2.2 Test Sample Operational Description

This is a scanning radio receiver, which can tune from 9 kHz to 3500 MHz. The device is a computer peripheral which controlled by a PC via a USB cable. All user control is via the PC.

Refer to Appendix D – Operational Descriptions

2.3 Test sample configuration

The following cables were connected to the EUT: Receiving Antenna, USB and Power.

The EUT was set-up /configured as per below:

Below 1 GHz (30 MHz to 1000 MHz):

- Radiated emission measurement was performed with antenna port connected to a load
- Conducted spurious emission measurement was performed at an antenna port

Above 1 GHz (1 GHz to 37 GHz):

- Radiated emission measurement was performed with an antenna connected

Refer to Appendix B3 - Test Setup Photographs.

2.4 Test Sample Block Diagram

Refer to Appendix C - Test Sample Block Diagram

2.5 Test Procedure

Emissions measurements were performed in accordance with the procedures of ANSI C63.4-2009. Radiated emissions tests were performed at a distance of 3 metres from the EUT.

 Accreditation No. 5292	 Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.
<p>This document shall only be reproduced in full, with the exception of the certificate on p3</p>	

2.6 Test Facility

2.6.1 General

EMC Technologies Pty Ltd is listed by the FCC as a test laboratory able to perform compliance testing for the public. EMC Technologies is listed as an FCC part 47CFR2.948 test lab and may perform the testing required under Parts 15 and 18 – **FCC Registration Number 90560**

EMC Technologies Pty Ltd has also been accredited as a Conformity Assessment Body (CAB) by Australian Communications and Media Authority (ACMA) under the APECTEL MRA and is designated to perform compliance testing on equipment subject to Declaration of Conformity (DoC) and Certification under Parts 15 & 18 of the FCC Commission's rules – **Registration Number 494713 & Designation number AU0001**.

EMC Technologies has also been accepted by Industry Canada for the performance of radiated measurements in accordance with RSS 212, Issue 1 (Provisional) - **Industry Canada number 3569B**.

Measurements were performed at EMC Technologies' laboratory in Keilor Park, Victoria Australia.

2.6.2 NATA Accreditation

EMC Technologies is accredited in Australia to test to the following standards by the National Association of Testing Authorities (NATA).

“FCC Part 15 unintentional and intentional emitters in the frequency range 9kHz to 18 GHz excluding TV receivers (15.117 and 15.119), TV interface devices (15.115), cable ready consumer electronic equipment (15.118), cable locating equipment (15.213) and unlicensed national information infrastructure devices (Sub part E).”

The current full scope of accreditation can be found on the NATA website: www.nata.asn.au It also includes a large number of emissions, immunity, SAR, EMR and Safety standards.

NATA is the Australian national laboratory accreditation body and has accredited EMC Technologies to operate to the IEC/ISO17025 requirements. A major requirement for accreditation is the assessment of the company and its personnel as being technically competent in testing to the standards. This requires fully documented test procedures, continued calibration of all equipment to the National Standard at the National Measurements Institute (NMI) and an internal quality system to ISO 9002. NATA has mutual recognition agreements with the National Voluntary Laboratory Accreditation Program (NVLAP) and the American Association for Laboratory Accreditation (A²LA).

2.7 Units of Measurements

2.7.1 Conducted Emissions

Measurements are reported in units of dB relative to one microvolt. (dB μ V).

2.7.2 Radiated Emissions

Measurements are reported in units of dB relative to one microvolt per metre (dB μ V/m).



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

2.8 Test Equipment Calibration

Measurement instrumentation and transducers were calibrated in accordance with the applicable standards by an independent NATA registered laboratory such as Agilent Technologies (Australia) Pty Ltd or the National Measurement Institute (NMI). All equipment calibration is traceable to Australia national standards at the National Measurements Institute. The reference antenna calibration was performed by NMI and the working antennas (biconical, log-periodic and horns) calibrated by the EMC Technologies. The complete list of test equipment used for the measurements, including calibration dates and traceability is contained in the Measurement Instrument Details.

3.0 CONDUCTED EMISSION MEASUREMENTS

Testing was performed in accordance with the requirements of FCC Part 15.107

3.1 Test Procedure

The arrangement specified in ANSI C63.4-2009 was adhered to for the conducted EMI measurements. The EUT was placed in the RF screened enclosure and a CISPR EMI Receiver as defined in ANSI C63.2-1996 was used to perform the measurements.

The EMI Receiver was operated under program control using the Max-Hold function and automatic frequency scanning, measurement and data logging techniques. The specified 0.15 MHz to 30 MHz frequency range was sub-divided into sub-ranges to ensure that all short duration peaks were captured.

3.2 Peak Maximising Procedure

The various operating modes of the system were investigated. For each of the sub-ranges, the EMI receiver was set to continuous scan with the Peak detector set to Max-Hold mode. The Quasi-Peak detector and the Average detector were then invoked to measure the actual Quasi-Peak and Average level of the most significant peaks, which were detected.

3.3 Calculation of Voltage Levels

The voltage levels were automatically measured in software and compared to the test limit. The method of calculation was as follows:

$$VEMI = VRx + LBPF$$

Where: $VEMI$ = the Measured EMI voltage in dB μ V to be compared to the limit.

VRx = the Voltage in dB μ V read directly at the EMI receiver.

$LBPF$ = the loss in dB of the cables and the Limiter and Pass Filter.

3.4 Plotting of Conducted Emission Measurement Data

The measurement data pertaining to each frequency sub-range were then concatenated to form a single graph of (peak) amplitude versus frequency. This was performed for both Active and Neutral lines and the composite graph was subsequently plotted. A list of the highest relevant peaks and the respective Quasi-Peak and Average values were also plotted on the graph.

3.5 Results of Conducted Emission Measurement

Testing was performed with the EUT tuned to three different frequencies: 30 MHz, 475 MHz and 960 MHz.

The worst case conducted EMI complied with the quasi peak and average limits by margins of > 10 dB. Refer to Appendix H - Graphs 1 to 6.



Accreditation No. 5292

Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

4.0 RADIATED EMISSION MEASUREMENTS

Testing was performed in accordance with the requirements of FCC Part 15.109.

4.1 Test Procedure

The measurement of emissions was measured at a distance of 3 metres.

The EUT was set up on the table top (placed on turntable) of total height 80 cm above the ground plane, and operated as described in section 2 of this report. The EMI Receiver was operated under software control via the PC Controller through the IEEE.488 Interface Bus Card Adaptor. The test frequency range was sub-divided into smaller bands with sufficient frequency resolution to permit reliable display and identification of possible EMI peaks while also permitting fast frequency scan times. A calibrated Biconical antenna was used for measurements between 30 MHz to 200 MHz and a calibrated Logperiodic antenna used for measurements between 200 MHz to 1000 MHz. Calibrated EMCO 3115, EMCO 3116 and ETS standard gain horn antennas were used for measurements between 1 GHz to 37 GHz.

The measurement of emissions between 30 - 1000 MHz was measured with the resolution bandwidth of 120 kHz and the video bandwidth of 300 kHz.

The measurements of emissions above 1000 MHz were measured with the resolution bandwidth = 1 MHz and the video bandwidth = 10 Hz.

The EUT was slowly rotated with the Peak Detector set to Max-Hold. This was performed for two antenna heights. When an emission was located, it was positively identified and its maximum level found by rotating the automated turntable, and by varying the antenna height. Each significant peak was investigated with the Quasi-Peak/Average Detectors. The software for cable losses automatically corrected the measurement data for each frequency range, antenna factors and preamplifier gain and all data was then stored on disk in sequential data files. This process was performed for both horizontal and vertical antenna polarisations.

4.2 Calculation of field strength

The field strength was calculated automatically by the software using all the pre-stored calibration data. The method of calculation is shown below:

E = V + AF - G + L Where:

E = Radiated Field Strength in dB μ V/m.

V = EMI Receiver Voltage in dB μ V. (measured value)

AF = Antenna Factor in dB(m⁻¹). (stored as a data array)

G = Preamplifier Gain in dB. (stored as a data array)

L = Cable loss in dB. (stored as a data array of Insertion Loss versus frequency)

- Example Field Strength Calculation**

Assuming a receiver reading of 34.0 dB μ V is obtained at 90 MHz, the Antenna Factor at that frequency is 9.2 dB. The cable loss is 1.9 dB while the preamplifier gain is 20 dB. The resulting Field Strength is therefore as follows:

$$34.0 + 9.2 + 1.9 - 20 = 25.1 \text{ dB}\mu\text{V/m}$$



Accreditation No. 5292

Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

4.4 Radiated EMI Results

4.4.1 30 – 1000 MHz

Radiated emission measurement was performed with antenna port connected to a load

Testing was performed with the EUT tuned to 30 MHz (low), 475 MHz (middle) and 960 MHz (high) frequencies channels. All results are reported.

4.4.1.1 Configuration 1 - Tuned Frequency.: 30 MHz

Frequency MHz	Polarisation	QP Measured dB μ V	QP Limit dB μ V	Δ QP \pm dB
700.0	Horizontal	45.6	46.0	-0.4
700.0	Vertical	44.3	46.0	-1.7
480.0	Horizontal	43.6	46.0	-2.4
800.0	Vertical	41.6	46.0	-4.4

Result: The highest radiated emission complied with FCC Class B limit by a margin of 0.4 dB at 700.0 MHz. Refer to Appendix H - Graphs 7 and 8.

4.4.1.2 Configuration 2 - Tuned Frequency.: 475 MHz

Frequency MHz	Polarisation	QP Measured dB μ V	QP Limit dB μ V	Δ QP \pm dB
480.0	Horizontal	43.5	46.0	-2.5
799.99	Vertical	40.6	46.0	-5.4
700.0	Vertical	38.4	46.0	-7.6

Result: The highest radiated emission complied with FCC Class B limit by a margin of 2.5 dB at 480.0 MHz. Refer to Appendix H - Graphs 9 and 10.

4.4.1.3 Configuration 3 - Tuned Frequency.: 960 MHz

Frequency MHz	Polarisation	QP Measured dB μ V	QP Limit dB μ V	Δ QP \pm dB
480.0	Horizontal	42.2	46.0	-3.8

Result: The highest radiated emission complied with FCC Class B limit by a margin of 3.8 dB at 480.0 MHz. Refer to Appendix H - Graphs 11 and 12.

4.4.2 1 GHz to 37 GHz

Radiated emission measurement was performed with an antenna connected

Testing was performed with the EUT tuned to 30 MHz (low), 475 MHz (middle) and 960 MHz (high) frequencies channels. All results are reported.

Results: The highest radiated emission complied with FCC Class B average limit by a margin of greater than 10 dB when EUT tuned to 30 MHz and 475 MHz.

The highest radiated emission complied with FCC Class B average limit by a margin of 1.9 dB at 9740 MHz when EUT tuned to 960 MHz.



Accreditation No. 5292

Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall only be reproduced in full, with the exception of the certificate on p3

5.0 ANTENNA PORT MEASURMENTS – 30 MHz to 1000 MHz

Conducted spurious emission measurement was performed at an antenna port as per FCC Part 15.111

Testing was performed with the EUT tuned to 30 MHz (low), 475 MHz (middle) and 960 MHz (high) frequencies channels. All results are reported.

Results: The highest radiated emission complied with FCC limit by a margin of greater than 10 dB.

6.0 COMPLIANCE STATEMENT

The Software-defined DDC-based Radio Receiver, model: G3 Series, tested on behalf of Robotron Pty Ltd complied with the requirements of the FCC Part 15 Subpart B Rules for Unintentional Radiators and FCC Part 15.121 Rules for Scanning Receivers.

The compliance margins were as follows:

Conducted Emissions:

FCC Part 15.107

Complies Class B limit, margin of > 10 dB

Radiated Emissions:

FCC Part 15.109 (30 – 1000 MHz)

Config #1: (Tune Frequency - 30 MHz) Complies Class B limit, margin of 0.4 dB

Config #2: (Tune Frequency - 475 MHz) Complies Class B limit, margin of 2.5 dB

Config #3: (Tune Frequency - 960 MHz) Complies Class B limit, margin of 3.8 dB

FCC Part 15.109 (1 GHz to 37 GHz):

Config #1: (Tune Frequency - 30 MHz) Complies Class B limit, margin of > 10 dB

Config #2: (Tune Frequency - 475 MHz) Complies Class B limit, margin of > 10 dB

Config #3: (Tune Frequency - 960 MHz) Complies Class B limit, margin of 1.9 dB

7.0 MEASUREMENT UNCERTAINTIES

EMC Technologies has evaluated the equipment and the methods used to perform the emissions testing. The estimated measurement uncertainties for emissions tests shown within this report are as follows:

Conducted Emissions: 9 kHz to 30 MHz ±3.2 dB

Radiated Emissions: 9 kHz to 30 MHz ±4.1 dB

30 MHz to 300 MHz ±5.1 dB

300 MHz to 1000 MHz ±4.7 dB

1 GHz to 18 GHz ±4.6 dB

The above expanded uncertainties are based on standard uncertainties multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.



Accreditation No. 5292

Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall only be reproduced in full, with the exception of the certificate on p3