

FCC - TEST REPORTReport Number : **60.790.16.011.01R01** Date of Issue : February 24, 2016Model : **RDWL917A**Product Type : **Doorbell**Applicant : Honeywell International Inc.Address : 1985 Douglas Drive North, Golden Valley, U.S.AProduction Facility : Ansen Electronics CompanyAddress : Chen Tung Industrial Zone, Ning Tau Administrative District,
Qiao Tau Zhen, Dongguan, Guangdong, ChinaTest Result : ☒ **Positive** ☐ **Negative**Total pages
including
Appendices : 32

TÜV SÜD HONG KONG LTD. is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025. TÜV SÜD HONG KONG LTD. reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations TÜV SÜD HONG KONG LTD. shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD HONG KONG LTD. issued reports. This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.

1 Table of Contents

1 Table of Contents.....	2
2 Description of Equipment Under Test	3
3 Summary of Test Standards	4
4 Details about the Test Laboratory	5
4.1 Test Equipment Site List.....	6
4.2 Measurement System Uncertainty	7
5 Summary of Test Results.....	8
6 General Remarks.....	9
7 Emission Test Results	10
7.1 Radiated Emission.....	10
7.2 Conducted Emission.....	12
7.3 Bandedge Emission.....	14
7.4 20dB Bandwidth.....	16
8 Appendix A - Photographs of EUT	17
9 Appendix B - Setup Photographs of EUT.....	29
10 Appendix C - General Product Information	32

2 Description of Equipment Under Test

Description of the Equipment Under Test

Product:	Doorbell
Model no.:	RDWL917A
FCC ID:	HS9-RDWL917A
Rating:	1) 6.0VDC (4 x 1.5VDC size "C" batteries) 2) 5.0VDC (USB port)
Frequency:	916.8MHz
Antenna gain:	0 dBi
Number of operated channel:	1
Modulation:	FSK

3 Summary of Test Standards

Test Standards
FCC Part 15 Subpart C 10-1-14 Edition Federal Communications Commission, PART 15 — Radio Frequency Devices, Subpart C — Unintentional Radiators

4 Details about the Test Laboratory

Site 1

Company name: TÜV SÜD Hong Kong Ltd.
3/F, West Wing, Lakeside 2,
10 Science Park West Avenue,
Science Park, Shatin, Hong Kong

Site 2

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Building 12&13 Zhiheng Wisdomland Business Park,
Nantou Checkpoint Road 2,
Shenzhen 518052, P.R.China
FCC Registration Number: 502708

Emission Tests	
Test Item	Test Site
FCC Part 15 Subpart C	
FCC Title 47 Part 15.249 & 15.209 Radiated Emission	Site 2
FCC Title 47 Part 15.249 & 15.207 Conduct Emission	Site 2
FCC Title 47 Part 15.249 Bandedge Emission	Site 2
FCC Title 47 Part 15.215 20dB Bandwidth	Site 2

4.1 Test Equipment Site List

Radiated emission Test, Bandedge Emission – Site 2

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	101269	17-Aug-16
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9163	707	17-Aug-17
Horn Antenna	Rohde & Schwarz	HF907	102294	17-Aug-17
Pre-amplifier	Rohde & Schwarz	SCU 18	102230	17-Aug-16
3m Semi-anechoic chamber	TDK	9X6X6	----	29-May-19

Conducted emission Test – Site 2

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 3	101782	17-Aug-16
LISN	Rohde & Schwarz	ENV4200	100249	17-Aug-16
LISN	Rohde & Schwarz	ENV216	100326	17-Aug-16
ISN	Rohde & Schwarz	ENY81	100177	17-Aug-16
ISN	Rohde & Schwarz	ENY81-CAT6	101664	17-Aug-16
High Voltage Probe	Rohde & Schwarz	TK9420(VT9420)	9420-58	17-Aug-16
RF Current probe	Rohde & Schwarz	EZ-17	100816	17-Aug-16

20dB Bandwidth – Site 2

DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DUE DATE
Signal Generator	Rohde & Schwarz	SMB100A	108272	17-Aug-16
Signal Analyzer	Rohde & Schwarz	FSV40	101030	17-Aug-16
Vector Signal Generator	Rohde & Schwarz	SMU 200A	105324	17-Aug-16
RF Switch Module	Rohde & Schwarz	OSP120/OSP-B157	101226/100851	17-Aug-16

4.2 Measurement System Uncertainty

Measurement System Uncertainty Emissions

System Measurement Uncertainty	
Items	Extended Uncertainty
Uncertainty for Radiated Emission in 3m chamber 9kHz-30MHz	4.54dB
Uncertainty for Radiated Emission in 3m chamber 30MHz-1000MHz	Horizontal: 4.83dB; Vertical: 4.91dB;
Uncertainty for Radiated Emission in 3m chamber 1000MHz-25000MHz	Horizontal: 4.89dB; Vertical: 4.88dB;
Uncertainty for Conducted Emission 150kHz-30MHz	3.50dB
Uncertainty for Conducted RF test	2.04dB

5 Summary of Test Results

Emission Tests				
FCC Part 15 Subpart C				
Test Condition	Pages	Test Result		
		Pass	Fail	N/A
FCC Title 47 Part 15.249 & 15.209 Radiated Emission	10-11	☒	☐	☐
FCC Title 47 Part 15.249 & 15.207 Conduct Emission	12-13	☒	☐	☐
FCC Title 47 Part 15.249 Bandedge Emission	14-15	☒	☐	☐
FCC Title 47 Part 15.215 20dB Bandwidth	16	☒	☐	☐

6 General Remarks

Remarks

The following Auxiliary Equipment was connected during the testing:

AC/DC Adaptor:

Model: THK-050VD1000mA

Input: 120VAC, 60Hz | Output: 5.0VDC 1.0A

SUMMARY:

- All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

- The Equipment Under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.


Sample Received Date: February 1, 2016

Testing Start Date: February 2, 2016

Testing End Date: February 22, 2016

- TÜV SÜD HONG KONG LTD. -

Reviewed by:



TSENG Chi Kit
EMC Project Engineer



Prepared by:



CHAN Kwong Ngai
EMC Test Engineer

7 Emission Test Results

7.1 Radiated Emission

EUT: RDWL917A
 Op Condition: Operated, TX Mode
 Test Specification: FCC15.249 & 15.209, Antenna: Horizontal
 Comment: 6.0VDC
 Remark: 9kHz to 10GHz

Test Result

☒ Passed

☐ Not Passed

Frequency MHz	Result dB μ V/m	Limit dB μ V/m	Margin dB	Detector
50.428	16.01	40	-23.99	Quasi Peak
55.842	17.42	40	-22.58	Quasi Peak
92.128	15.48	43.5	-28.02	Quasi Peak
847.852	30.56	46	-15.44	Quasi Peak
*916.840	90.72	114	-23.28	Peak
*916.840	62.51	94	-31.49	Average
1828.525	49.46	74	-24.54	Peak
1828.525	36.42	54	-17.58	Average
2751.201	54.83	74	-19.17	Peak
2751.201	38.54	54	-15.46	Average
4577.724	58.89	74	-15.11	Peak
4577.724	40.21	54	-13.79	Average
6423.076	56.57	74	-17.43	Peak
6423.076	39.12	54	-14.88	Average

* 916.8MHz is fundamental frequency.

Radiated Emission

EUT: RDWL917A
 Op Condition: Operated, TX Mode
 Test Specification: FCC15.249 & 15.209, Antenna: Vertical
 Comment: 6.0VDC
 Remark: 9kHz to 10GHz

Test Result	
☒	Passed
☐	Not Passed


Frequency MHz	Result dBμV/m	Limit dBμV/m	Margin dB	Detector
58.625	15.88	40	-25.12	Quasi Peak
93.120	15.32	43.5	-28.18	Quasi Peak
160.472	15.67	43.5	-27.83	Quasi Peak
857.855	31.07	46	-14.93	Quasi Peak
*916.816	86.40	114	-27.60	Peak
*916.816	60.82	94	-33.18	Average
1828.525	50.57	74	-23.43	Peak
1828.525	36.72	54	-17.28	Average
2751.201	54.51	74	-19.49	Peak
2751.201	38.59	54	-15.41	Average
4577.724	56.62	74	-17.38	Peak
4577.724	39.22	54	-14.78	Average
6423.076	57.08	74	-16.92	Peak
6423.076	39.56	54	-14.44	Average

* 916.8MHz is fundamental frequency.

7.2 Conducted Emission

EUT: RDWL917A
 Op Condition: Operated, TX Mode
 Test Specification: FCC15.249 & 15.207, AC Mains, L Line
 Comment: 120VAC, 60Hz

Test Result


☒ Passed☐ Not Passed

TRACE	FREQUENCY	LEVEL dBμV	DELTA LIMIT dB
1 Quasi Peak	170 kHz	25.97	-38.98
2 Average	338 kHz	7.69	-41.55
1 Quasi Peak	686 kHz	26.24	-29.75
2 Average	702 kHz	9.46	-36.53
2 Average	938 kHz	8.71	-37.28
1 Quasi Peak	2.078 MHz	20.13	-35.86
1 Quasi Peak	3.606 MHz	18.54	-37.46
2 Average	3.606 MHz	6.67	-39.32
2 Average	12.158 MHz	9.31	-40.68
1 Quasi Peak	12.246 MHz	25.25	-34.74
1 Quasi Peak	13.626 MHz	28.85	-31.14
2 Average	24.086 MHz	20.69	-29.30

Conducted Emission

EUT: RDWL917A
 Op Condition: Operated, TX Mode
 Test Specification: FCC15.249 & 15.207, AC Mains, N Line
 Comment: 120VAC, 60Hz

Test Result

☒ Passed☐ Not Passed

TRACE	FREQUENCY	LEVEL dBμV	DELTA LIMIT dB
1 Quasi Peak	258 kHz	22.28	-39.20
1 Quasi Peak	850 kHz	30.22	-25.77
2 Average	850 kHz	10.74	-35.25
2 Average	990 kHz	6.56	-39.43
1 Quasi Peak	2.098 MHz	23.61	-32.38
1 Quasi Peak	2.138 MHz	22.59	-33.40
2 Average	2.39 MHz	6.34	-39.65
1 Quasi Peak	12.186 MHz	29.26	-30.73
2 Average	12.334 MHz	11.09	-38.90
1 Quasi Peak	13.678 MHz	34.93	-25.06
2 Average	13.678 MHz	14.25	-35.75

7.3 Bandedge Emission

EUT: RDWL917A
Op Condition: Operated, TX Mode
Test Specification: FCC15.249, Antenna: Horizontal
Comment: 6.0VDC

Test Result

☒ Passed☐ Not Passed

Band	Frequency MHz	Result dBμV/m	Limit dBμV/m	Margin dB	Detector
Low	902.000	32.32	46	-13.68	Quasi Peak
High	928.000	33.44	46	-12.56	Quasi Peak

Bandedge Emission

EUT: RDWL917A
Op Condition: Operated, TX Mode
Test Specification: FCC15.249, Antenna: Vertical
Comment: 6.0VDC


Test Result	
☒	Passed
☐	Not Passed

Band	Frequency MHz	Result dB μ V/m	Limit dB μ V/m	Margin dB	Detector
Low	902.000	32.12	46	-13.88	Quasi Peak
High	928.000	33.20	46	-12.80	Quasi Peak

7.4 20dB Bandwidth

EUT: RDWL917A
Op Condition: Operated, TX Mode
Test Specification: FCC15.215, 20dB Bandwidth
Comment: 6.0VDC
Remark: 20dB bandwidth is within frequency band 902MHz-928MHz

Test Result

☒ Passed☐ Not Passed**20dB bandwidth**

448.989kHz



8 Appendix A - Photographs of EUT





Appendix A





Appendix A





Appendix A





Appendix A





Appendix A





Appendix A





Appendix A





Appendix A





Appendix A



Appendix A




Appendix A




9 Appendix B - Setup Photographs of EUT

Radiated Emission (9kHz to 30MHz)



Radiated Emission (30MHz to 1GHz) / Bandedge Emission




Appendix B

Radiated Emission (1GHz to 10GHz)




Conducted Emission



Appendix B

20dB Bandwidth



10 Appendix C - General Product Information

Radiofrequency radiation exposure evaluation

According to KDB 447498 D01v06 section 4.3.1,

>> The 1-g SAR test exclusion thresholds, for 100MHz to 6GHz, at test separation distances ≤ 50 mm are determined by:

Power at 916.8MHz = 0.3265 mW EIRP

$[(0.3265 \text{ mW}) / (20 \text{ mm})] \cdot [\text{sqrt}(0.9168 \text{ GHz})] = 0.0156$ which is ≤ 3.0 for 1-g SAR.

Therefore the device is exempt from stand-alone SAR test requirements.

>> The fundamental frequency of the EUT is 916.8MHz, the test separation distance is smaller than 50mm. (Manufacturer specified the separation distance is 20mm)

>> The power of EUT measured is:

- For 916.8MHz: $0.3265\text{mW} = 10 \log(0.3265) \text{ dBm} \sim -4.86\text{dBm}$