

# Honeywell Home

## FCC / ISED Test Report

For

## Flycatcher Thermostat

Report #: 43868-1

FCC ID: HS9-THX321WF01

IC ID: 573R-THX321WF01

Report Completion Date: 2018-12-04

*Prepared by and for:*

**Ademco Inc.**

**2 Corporate Center Dr.**

**Suite 100 PO Box 9040**

**Melville, NY 11747**



Testing

NVLAP Lab Code: 600110

## **Document Introduction**

Ademco Inc. tested the above equipment in accordance with the requirements set forth in the listed standards. All indications of Pass/Fail in the report are opinions expressed by Ademco Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

This document is a record of the FCC/ISED Test Report for Ademco Inc. products. It demonstrates the data required to be analyzed to certify a product according to the requirements of the FCC & ISED.

The results in the report reflect only the model of the items under test unless noted otherwise. This document may not be altered or revised in any way unless done so by Ademco Inc. and all revisions are duly noted in the revisions section. Any alterations of this document not carried out by Ademco Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Ademco Inc. is the legal entity name for Honeywell Home / Resideo. All three names can be used synonymously within this test report.

| <b>Test Report Revision History</b> |                    |                    |                         |                     |
|-------------------------------------|--------------------|--------------------|-------------------------|---------------------|
| <b>Revision</b>                     | <b>Prepared By</b> | <b>Reviewed By</b> | <b>Revision Detail</b>  | <b>Release Date</b> |
| ---                                 | <b>M. Antola</b>   | <b>A. Roussin</b>  | <b>Original Release</b> | <b>2018-12-04</b>   |
|                                     |                    |                    |                         |                     |
|                                     |                    |                    |                         |                     |

### Report Authorization

**Report Prepared By:**



Michael Antola  
Hardware Engineer II  
RF & EMC / Wireless Certifications  
Ademco Inc.

**Reviewed & Approved By:**



Andrew Roussin  
Hardware Engineer II  
RF & EMC / Wireless Certifications  
Ademco Inc.

## **Contents**

|                                              |     |
|----------------------------------------------|-----|
| Applicable Test Standards/Limits.....        | 5   |
| Deviations from Test Methods .....           | 5   |
| Facilities and Accreditation .....           | 5   |
| Test Item Description .....                  | 5   |
| Worse-Case Configuration & Mode.....         | 6   |
| Calibration & Measurement Uncertainty.....   | 7   |
| Opinions / Interpretations .....             | 7   |
| Test Summary.....                            | 8   |
| Test & Measurement Equipment.....            | 9   |
| On Time and Duty Cycle.....                  | 11  |
| 6dB Emission Bandwidth (DTS Bandwidth) ..... | 13  |
| 99% Occupied Bandwidth.....                  | 26  |
| Maximum Conducted Output Power.....          | 39  |
| Maximum Power Spectral Density.....          | 40  |
| Out-of-Band Emissions .....                  | 53  |
| Radiated Emissions (Intentional) .....       | 81  |
| Conducted Emissions (Mains).....             | 149 |
| END OF REPORT.....                           | 151 |

### Applicable Test Standards/Limits

| Test Standards/Limits                      | Result    | Dates Tested        |
|--------------------------------------------|-----------|---------------------|
| ANSI C63.10: 2013                          | Compliant | 10/25/18 – 12/04/18 |
| RSS-247, Issue 2, Section 5                | Compliant | 10/25/18 – 12/04/18 |
| RSS-GEN, Issue 4                           | Compliant | 10/25/18 – 12/04/18 |
| CFR 47 Pt 15 Subpart C, Section 15.207/209 | Compliant | 10/25/18 – 12/04/18 |
| CFR 47 Pt 15 Subpart C, Section 15.247     | Compliant | 10/25/18 – 12/04/18 |

### Deviations from Test Methods

| # | Deviation Description |
|---|-----------------------|
| 0 | None                  |

### Facilities and Accreditation

The test site and measurement facility used to collect data are located at 2 Corporate Center Dr., Melville, NY 11747, USA. Ademco Inc. is accredited by NVLAP, Laboratory Code 600110-0. The full scope of accreditation can be viewed at the NVLAP website.

### Test Item Description

The EUT is a wireless thermostat that contains two (2) unique radios – a dual-band Wi-Fi radio and a 903-926MHz frequency hopping spread spectrum (i.e. RedLINK) radio. Each radio utilizes two (2) antennas, which are used for diversity only. Antenna gains are listed below:

2.4GHz Wi-Fi Antenna 1: -0.55dBi  
2.4GHz Wi-Fi Antenna 2: 0.65dBi  
5GHz Wi-Fi Antenna 1: -0.10dBi  
5GHz Wi-Fi Antenna 2: 0.94dBi  
900MHz RedLINK Antenna 1: 0.50dBi  
900MHz RedLINK Antenna 2: 1.45dBi

This report covers the 2.4GHz portion of the Wi-Fi radio only.

### **Worse-Case Configuration & Mode**

Radiated emissions was performed with the EUT set to transmit at the low/mid/high channels with the highest output power as worst-case scenario. The EUT was tested in all three orthogonal planes in order to determine the worst-case emissions. It was determined that the X axis orientation (standing upright) was the worst-case orientation. Therefore, all final radiated test was performed with the EUT in the X axis orientation. See setup photos for details.

### **Test Sample Identification**

| <b>Sample ID Number</b> | <b>Sample Serial Number</b>    | <b>Date Received</b> |
|-------------------------|--------------------------------|----------------------|
| MEL-583                 | Non-serialized production unit | 2018-10-18           |
| MEL-584                 | Non-serialized production unit | 2018-10-18           |
| MEL-585                 | Non-serialized production unit | 2018-10-18           |
|                         |                                |                      |
|                         |                                |                      |
|                         |                                |                      |

## Calibration & Measurement Uncertainty

- Measuring Instrument Calibration – The measuring equipment utilized to perform the tests documented in this report have been calibrated in accordance with the manufacturer’s recommendations and is traceable to recognized national standards.
- Sample Calculation – Where relevant, the following sample calculation is provided:

Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB)

[i.e.] 37 dBuV/m = 30 dBuV + 18.5 dB/m + 0.5 dB – 12 dB

- Uncertainty - Figures are valid to a confidence level of 95%.

| Test                                        | Standard Uncertainty |
|---------------------------------------------|----------------------|
| Radiated Emissions (30-200MHz Horizontal)   | +/- 5.05 dB          |
| Radiated Emissions (30-200MHz Vertical)     | +/- 5.28 dB          |
| Radiated Emissions (200-1000MHz Horizontal) | +/- 10.21 dB         |
| Radiated Emissions (200-1000MHz Vertical)   | +/- 10.36 dB         |
| Radiated Emissions (Above 1GHz)             | +/- 9.70 dB          |
| Conducted Emissions (150KHz-30MHz)          | +/- 4.36 dB          |

## Opinions / Interpretations

None

### **Test Summary**

All tests described below are required, unless otherwise noted. Notes should be described in detail in the "Additional notes" section.

| # | Test Description                 | Status |
|---|----------------------------------|--------|
| 1 | 99% Occupied Bandwidth           | PASS   |
| 2 | 6 dB Emission Bandwidth          | PASS   |
| 3 | Maximum Conducted Output Power   | PASS   |
| 4 | Maximum Power Spectral Density   | PASS   |
| 5 | Out-of-Band Emissions            | PASS   |
| 6 | Radiated Emissions (Intentional) | PASS   |
| 7 | Conducted Emissions (Mains)      | PASS   |



## Test & Measurement Equipment

The following test and measurement equipment was utilized for the tests documented in this report:

### Equipment List

| Instrument Type                            | ID #  | Serial #   | Manufacturer    | Model       | Cal Date | Cal Due Date |
|--------------------------------------------|-------|------------|-----------------|-------------|----------|--------------|
| RF Lab (RF Conducted & Power Measurements) |       |            |                 |             |          |              |
| Spectrum Analyzer                          | 11531 | MY41000078 | Agilent         | E4440A      | 06/06/17 | 06/06/19     |
| Power Sensor                               | 11568 | 105317     | Rohde & Schwarz | NRP-Z81     | 10/02/18 | 10/02/19     |
| Attenuator                                 | -     | 1624       | Pasternack      | PE7087-6    | *        | *            |
| RF Chamber                                 |       |            |                 |             |          |              |
| Spectrum Analyzer                          | 11496 | 100303     | Rohde & Schwarz | FSU26       | 04/11/18 | 04/11/19     |
| Loop Antenna (9kHz-30MHz)                  | 11535 | 121080     | Com-Power       | AL-130R     | 10/29/18 | 10/29/19     |
| Bilog Antenna (30MHz-5GHz)                 | 11311 | A022406    | Sunol           | JB5         | 02/01/18 | 02/01/19     |
| Horn Antenna (1-18GHz)                     | 2319  | 2317       | EMCO            | 3115        | 01/10/18 | 01/10/19     |
| Horn Antenna (18-40GHz)                    | 11472 | 151        | EMCO            | EM-6963     | 02/14/18 | 02/14/19     |
| Preamp (10-4200MHz)                        | 11537 | 1603006    | Mini Circuits   | TVA-11-422  | *        | *            |
| Preamp (500MHz-18GHz)                      | 11557 | 18040034   | Com-Power       | PAM-118A    | *        | *            |
| Preamp (18-40GHz)                          | 11541 | 160911     | Amplical        | AMP18G40-35 | *        | *            |
| Band Reject Filter                         | 11553 | G041       | Micro-tronics   | BRM50702-01 | *        | *            |
| RF Cable                                   | -     | -          | Mini-Circuits   | RDE#2       | *        | *            |
| RF Cable                                   | -     | -          | Insulated Wire  | SMA#8       | *        | *            |
| OATS                                       |       |            |                 |             |          |              |
| Spectrum Analyzer                          | 11545 | 103125     | Rohde & Schwarz | FSW26       | 02/21/18 | 02/21/19     |
| Bilog Antenna (30MHz-6GHz)                 | 11534 | A012816    | Sunol           | JB6         | 03/27/18 | 03/27/19     |
| Horn Antenna (1-18GHz)                     | 2973  | 3127       | EMCO            | RGA-60      | 01/22/18 | 01/22/19     |
| Horn Antenna (18-40GHz)                    | 11472 | 151        | EMCO            | EM-6963     | 02/14/18 | 02/14/19     |
| Preamp (100kHz-1.3GHz)                     | 11540 | 2443AUF555 | HP              | 8447D       | *        | *            |
| Preamp (1-18GHz)                           | 11539 | 160362     | Amplical        | AMP1G18-35  | *        | *            |
| Preamp                                     | 11541 | 160911     | Amplical        | AMP18G40-35 | *        | *            |

|                      |       |             |                    |               |          |          |
|----------------------|-------|-------------|--------------------|---------------|----------|----------|
| (18-40GHz)           |       |             |                    |               |          |          |
| High Pass Filter     | 11552 | G018        | Micro-tronics      | HPM50111-01   | *        | *        |
| RF Cable             | -     | -           | Pasternack         | RDE#1         | *        | *        |
| RF Cable             | -     | -           | MegaPhase          | EMC2-S1S1-360 | *        | *        |
| Shield Room          |       |             |                    |               |          |          |
| EMI Receiver         | 11566 | 102484      | Rohde & Schwarz    | ESR3          | 09/19/18 | 09/19/19 |
| LISN                 | 11527 | 241259      | Com-Power          | LIN-120A      | 01/10/18 | 01/10/19 |
| Misc.                |       |             |                    |               |          |          |
| Measurement Software | 11543 | Version 9.5 | UL                 | UL EMC        | N/A      | N/A      |
| Environmental Meter  | 11533 | A070144     | Extech Instruments | SD700         | 08/21/17 | 08/21/20 |

\*-Passive devices & Preamps are characterized in-house, not calibrated.

## On Time and Duty Cycle

### Test Description

Refer to KDB 558074 Zero-Span Analyzer Method.

### Test Criteria

| Reference             | Limit                    |
|-----------------------|--------------------------|
| KDB 558074, Section 6 | None, for reporting only |


### Test Information

| Tester | Test Location | Date     | Temperature (°C) | Humidity (%RH) | Pressure (mbar) | Results (P/F) |
|--------|---------------|----------|------------------|----------------|-----------------|---------------|
| MA     | RF Lab        | 12/03/18 | 22.6             | 37.2           | 1014            | P             |


### Test Results

| EUT Mode     | OFF Time (ms) | Period (ms) | Duty Cycle (linear) | Duty Cycle (%) | Duty Cycle Correction Factor (dB) | 1/ON Time Minimum VBW (kHz) |
|--------------|---------------|-------------|---------------------|----------------|-----------------------------------|-----------------------------|
| 802.11b      | 0.01658       | 1.222       | 0.986               | 98.6%          | 0.00                              | 0.01                        |
| 802.11g      | 0.02375       | 2.086       | 0.989               | 98.9%          | 0.00                              | 0.01                        |
| 802.11n HT20 | 0.0225        | 1.941       | 0.988               | 98.8%          | 0.00                              | 0.01                        |
| 802.11n HT40 | 0.02298       | 0.965       | 0.976               | 97.6%          | 0.10                              | 1.06                        |


# Duty Cycle Plot




802.11b Mode



802.11g Mode



802.11n HT20 Mode



802.11n HT40 Mode

## 6dB Emission Bandwidth (DTS Bandwidth)

### Test Description

Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission. Refer to KDB 558074 D01 DTS Meas Guidance v04.

### Test Criteria

| Reference                                              | Limit                |
|--------------------------------------------------------|----------------------|
| CFR 47 Subpart C 15.247 (2)<br>RSS-247 Section 5.2 (a) | $\geq 500\text{kHz}$ |

### Test Information

| Tester | Test Location | Date              | Temperature (°C) | Humidity (%RH) | Pressure (mbar) | Results (P/F) |
|--------|---------------|-------------------|------------------|----------------|-----------------|---------------|
| AG/CL  | RF Lab        | 11/13/18-11/16/18 | 21.7             | 27.2           | 993.6           | P             |

### Test Results

| Mode            | Channel | Frequency (GHz) | 6dB Bandwidth (in MHz) |           |
|-----------------|---------|-----------------|------------------------|-----------|
|                 |         |                 | Antenna 1              | Antenna 2 |
| 802.11b         | Low     | 2.412           | 8.862                  | 8.861     |
|                 | Mid     | 2.437           | 8.606                  | 8.582     |
|                 | High    | 2.462           | 8.549                  | 8.737     |
| 802.11g         | Low     | 2.412           | 16.376                 | 16.357    |
|                 | Mid     | 2.437           | 16.372                 | 16.357    |
|                 | High    | 2.462           | 16.363                 | 16.361    |
| 802.11n<br>HT20 | Low     | 2.412           | 17.633                 | 17.593    |
|                 | Mid     | 2.437           | 17.584                 | 17.584    |
|                 | High    | 2.462           | 17.614                 | 17.596    |
| 802.11n<br>HT40 | Low     | 2.422           | 36.328                 | 36.347    |
|                 | Mid     | 2.437           | 36.345                 | 36.345    |
|                 | High    | 2.452           | 36.359                 | 36.335    |

Agilent 03:14:44 Nov 15, 2018

Ref 36.5 dBm #Atten 40 dB

#Peak  
Log  
10  
dB/  
Offst  
6.5  
dB

LgAv

M1 S2

Center 2.412 000 00 GHz Span 25 MHz

#Res BW 100 kHz #VBW 300 kHz Sweep 2.4 ms (4001 pts)

Occupied Bandwidth 11.5867 MHz

Occ BW % Pwr 99.00 %  
x dB -6.00 dB

Transmit Freq Error -37.445 kHz  
x dB Bandwidth 8.862 MHz

Agilent 03:20:11 Nov 15, 2018

Ref 36.5 dBm #Atten 40 dB

#Peak Log 10 dB/ Offst 6.5 dB

LgAv

M1 S2

Center 2.437 000 00 GHz Span 25 MHz

#Res BW 100 kHz #VBW 300 kHz Sweep 2.4 ms (4001 pts)

Occupied Bandwidth 11.5668 MHz


Occ BW % Pwr 99.00 %

x dB -6.00 dB


Transmit Freq Error -16.726 kHz

x dB Bandwidth 8.606 MHz


**Document #: 800-23065, Revision B**  
**TEL: (516) 577-2000**




Antenna 1: High Channel – Plot



Antenna 2: Low Channel - Plot




Antenna 2: Mid Channel - Plot




Antenna 2: High Channel - Plot




**6dB Bandwidth – 802.11g Mode**




Antenna 1: Low Channel - Plot




Antenna 1: Mid Channel - Plot




Antenna 1: High Channel – Plot



Antenna 2: Low Channel - Plot




Antenna 2: Mid Channel - Plot




Antenna 2: High Channel - Plot


**6dB Bandwidth – 802.11n HT20 Mode**




Antenna 1: Low Channel - Plot




Antenna 1: Mid Channel - Plot




Antenna 1: High Channel – Plot



Antenna 2: Low Channel - Plot




Antenna 2: Mid Channel - Plot




Antenna 2: High Channel - Plot


**6dB Bandwidth – 802.11n HT40 Mode**




Antenna 1: Low Channel - Plot



Antenna 1: Mid Channel - Plot




Antenna 1: High Channel – Plot




Antenna 2: Low Channel - Plot





Antenna 2: Mid Channel - Plot



Antenna 2: High Channel - Plot

## 99% Occupied Bandwidth

### Test Description

The emission bandwidth (x dB) is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated x dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth.

When the occupied bandwidth limit is not stated in the applicable RSS or reference measurement method, the transmitted signal bandwidth shall be reported as the 99% emission bandwidth, as calculated or measured.

### Test Criteria

| Reference            | Limit |
|----------------------|-------|
| RSS-GEN, Section 6.6 | N/A   |


### Test Information

| Tester | Test Location | Date              | Temperature (°C) | Humidity (%RH) | Pressure (mbar) | Results (P/F) |
|--------|---------------|-------------------|------------------|----------------|-----------------|---------------|
| AG     | RF Lab        | 11/06/18-11/08/18 | 21.7             | 27.2           | 993.6           | P             |


### Test Results

| Mode            | Channel | Frequency (GHz) | 99% Bandwidth (in MHz) |           |
|-----------------|---------|-----------------|------------------------|-----------|
|                 |         |                 | Antenna 1              | Antenna 2 |
| 802.11b         | Low     | 2.412           | 11.860                 | 11.743    |
|                 | Mid     | 2.437           | 11.825                 | 11.808    |
|                 | High    | 2.462           | 11.737                 | 11.902    |
| 802.11g         | Low     | 2.412           | 16.552                 | 16.518    |
|                 | Mid     | 2.437           | 16.597                 | 16.589    |
|                 | High    | 2.462           | 16.666                 | 16.601    |
| 802.11n<br>HT20 | Low     | 2.412           | 17.819                 | 17.794    |
|                 | Mid     | 2.437           | 17.821                 | 17.811    |
|                 | High    | 2.462           | 17.819                 | 17.721    |
| 802.11n<br>HT40 | Low     | 2.422           | 36.338                 | 36.195    |
|                 | Mid     | 2.437           | 36.327                 | 36.277    |
|                 | High    | 2.452           | 36.275                 | 36.268    |


**99% Occupied Bandwidth – 802.11b Mode**




Antenna 1: Low Channel - Plot




Antenna 1: Mid Channel - Plot




Antenna 1: High Channel – Plot



Antenna 2: Low Channel - Plot




Antenna 2: Mid Channel - Plot




Antenna 2: High Channel - Plot


**99% Occupied Bandwidth – 802.11g Mode**




Antenna 1: Low Channel - Plot



Antenna 1: Mid Channel - Plot




Antenna 1: High Channel – Plot




Antenna 2: Low Channel - Plot






Antenna 2: Mid Channel - Plot




Antenna 2: High Channel - Plot




**99% Occupied Bandwidth – 802.11n HT20 Mode**




Antenna 1: Low Channel - Plot




Antenna 1: Mid Channel - Plot




Antenna 1: High Channel – Plot



Antenna 2: Low Channel - Plot




Antenna 2: Mid Channel - Plot




Antenna 2: High Channel - Plot


**99% Occupied Bandwidth – 802.11n HT40 Mode**




Antenna 1: Low Channel - Plot




Antenna 1: Mid Channel - Plot




Antenna 1: High Channel – Plot



Antenna 2: Low Channel - Plot



Antenna 2: Mid Channel - Plot



Antenna 2: High Channel - Plot



## Maximum Conducted Output Power

### Test Description

For systems using digital modulation in the 902-928MHz, 2400-2483,5MHz and 5725-5850MHz bands, the conducted output power limit (specified below) is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Maximum peak conducted output power was the method employed to determine fundamental emission output power.

Method PKPM1 per C63.10 and KDB 558074 was utilized for this test program.

### Test Criteria

| Reference                                                 | Limit      |
|-----------------------------------------------------------|------------|
| CFR 47 Subpart C 15.247 (b)(3)<br>RSS-247 Section 5.4 (d) | 1W (30dBm) |

### Test Information

| Tester | Test Location | Date     | Temperature (°C) | Humidity (%RH) | Pressure (mbar) | Results (P/F) |
|--------|---------------|----------|------------------|----------------|-----------------|---------------|
| MA     | RF Lab        | 12/03/18 | 21.7             | 27.2           | 993.6           | P             |

### Test Results

| Mode            | Channel | Frequency (GHz) | Tx Output Power (in dBm) |           |
|-----------------|---------|-----------------|--------------------------|-----------|
|                 |         |                 | Antenna 1                | Antenna 2 |
| 802.11b         | Low     | 2.412           | 22.6                     | 22.4      |
|                 | Mid     | 2.437           | 22.5                     | 22.3      |
|                 | High    | 2.462           | 22.4                     | 22.4      |
| 802.11g         | Low     | 2.412           | 23.4                     | 23.7      |
|                 | Mid     | 2.437           | 23.5                     | 24.2      |
|                 | High    | 2.462           | 24.0                     | 24.2      |
| 802.11n<br>HT20 | Low     | 2.412           | 23.8                     | 24.2      |
|                 | Mid     | 2.437           | 24.2                     | 24.4      |
|                 | High    | 2.462           | 24.2                     | 24.4      |
| 802.11n<br>HT40 | Low     | 2.422           | 23.3                     | 23.4      |
|                 | Mid     | 2.437           | 23.2                     | 23.2      |
|                 | High    | 2.452           | 22.6                     | 23.2      |

## Maximum Power Spectral Density

### Test Description

The DTS rules specify a conducted PSD limit within the *DTS bandwidth* during any time interval of continuous transmission. Such specifications require that the same method as used to determine the conducted output power shall also be used to determine the power spectral density. Therefore, if maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used.

Since maximum peak conducted output power was the method employed to determine fundamental emission output power, then the peak power spectral density method was utilized.

Method PKPSD per C63.10 and KDB 558074 was utilized for this test program.

### Test Criteria

| Reference                                              | Limit                     |
|--------------------------------------------------------|---------------------------|
| CFR 47 Subpart C 15.247 (e)<br>RSS-247 Section 5.2 (b) | < 8 dBm in any 3 kHz Band |

### Test Information


| Tester | Test Location | Date     | Temperature (°C) | Humidity (%RH) | Pressure (mbar) | Results (P/F) |
|--------|---------------|----------|------------------|----------------|-----------------|---------------|
| MA     | RF Lab        | 12/03/18 | 21.7             | 27.2           | 993.6           | P             |

### Test Results


| Mode         | Channel | Frequency (GHz) | Max PSD (in dBm) |           |
|--------------|---------|-----------------|------------------|-----------|
|              |         |                 | Antenna 1        | Antenna 2 |
| 802.11b      | Low     | 2.412           | 3.16             | 2.46      |
|              | Mid     | 2.437           | 2.24             | 2.36      |
|              | High    | 2.462           | 2.22             | 2.37      |
| 802.11g      | Low     | 2.412           | -3.19            | -4.09     |
|              | Mid     | 2.437           | -3.34            | -3.75     |
|              | High    | 2.462           | -3.56            | -3.59     |
| 802.11n HT20 | Low     | 2.412           | -3.92            | -3.74     |
|              | Mid     | 2.437           | -3.86            | -4.27     |
|              | High    | 2.462           | -3.54            | -4.00     |
| 802.11n HT40 | Low     | 2.422           | -7.68            | -8.10     |
|              | Mid     | 2.437           | -6.84            | -8.36     |
|              | High    | 2.452           | -7.67            | -8.21     |




**PSD – 802.11b Mode**




Antenna 1: Low Channel - Plot




Antenna 1: Mid Channel - Plot




Antenna 1: High Channel – Plot



Antenna 2: Low Channel - Plot




Antenna 2: Mid Channel - Plot




Antenna 2: High Channel - Plot


**PSD – 802.11g Mode**




Antenna 1: Low Channel - Plot




Antenna 1: Mid Channel - Plot




Antenna 1: High Channel – Plot



Antenna 2: Low Channel - Plot




Antenna 2: Mid Channel - Plot




Antenna 2: High Channel - Plot


PSD – 802.11n HT20 Mode




Antenna 1: Low Channel - Plot



Antenna 1: Mid Channel - Plot




Antenna 1: High Channel – Plot




Antenna 2: Low Channel - Plot






Antenna 2: Mid Channel - Plot




Antenna 2: High Channel - Plot


PSD – 802.11n HT40 Mode




Antenna 1: Low Channel - Plot




Antenna 1: Mid Channel - Plot




Antenna 1: High Channel – Plot



Antenna 2: Low Channel - Plot



Antenna 2: Mid Channel - Plot



Antenna 2: High Channel - Plot

## Out-of-Band Emissions

### Test Description

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

### Test Criteria

| Reference                                           | Limit                      |
|-----------------------------------------------------|----------------------------|
| CFR 47 Subpart C 15.247 (d)<br>RSS-247, Section 5.5 | 20dB Below the Fundamental |

### Test Information


| Tester | Test Location | Date              | Temperature (°C) | Humidity (%RH) | Pressure (mbar) | Results (P/F) |
|--------|---------------|-------------------|------------------|----------------|-----------------|---------------|
| AG/CL  | RF Lab        | 11/12/18-11/16/18 | 21.7             | 27.2           | 993.6           | P             |


### Test Results

| Authorized Band Edge |         |         |                 |                                  |            |             |
|----------------------|---------|---------|-----------------|----------------------------------|------------|-------------|
| Mode                 | Antenna | Channel | Frequency (GHz) | Delta from Peak to Bandedge (dB) | Limit (dB) | Margin (dB) |
| 802.11b              | 1       | Low     | 2.412           | 43.16                            | 20         | -23.16      |
|                      |         | High    | 2.462           | 55.16                            | 20         | -35.16      |
|                      | 2       | Low     | 2.412           | 43.15                            | 20         | -23.15      |
|                      |         | High    | 2.462           | 53.74                            | 20         | -33.74      |
| 802.11g              | 1       | Low     | 2.412           | 37.36                            | 20         | -17.36      |
|                      |         | High    | 2.483           | 45.49                            | 20         | -25.49      |
|                      | 2       | Low     | 2.412           | 37.05                            | 20         | -17.05      |
|                      |         | High    | 2.462           | 44.79                            | 20         | -24.79      |
| 802.11n HT20         | 1       | Low     | 2.412           | 38.85                            | 20         | -18.85      |
|                      |         | High    | 2.462           | 45.77                            | 20         | -25.77      |
|                      | 2       | Low     | 2.412           | 36.9                             | 20         | -16.9       |
|                      |         | High    | 2.462           | 43.72                            | 20         | -23.72      |
| 802.11n HT40         | 1       | Low     | 2.422           | 36.78                            | 20         | -16.78      |
|                      |         | High    | 2.452           | 38.21                            | 20         | -18.21      |
|                      | 2       | Low     | 2.422           | 37.85                            | 20         | -17.85      |
|                      |         | High    | 2.452           | 37.76                            | 20         | -17.76      |


| Conducted Spurious |         |                    |                                                                      |           |
|--------------------|---------|--------------------|----------------------------------------------------------------------|-----------|
| Mode               | Channel | Frequency<br>(GHz) | Highest Spurious Emission<br>Delta from the -20dB down<br>Limit (dB) |           |
|                    |         |                    | Antenna 1                                                            | Antenna 2 |
| 802.11b            | Low     | 2.412              | -46.44                                                               | -48.58    |
|                    | Mid     | 2.437              | -46.07                                                               | -47.18    |
|                    | High    | 2.462              | -40.54                                                               | -47.24    |
| 802.11g            | Low     | 2.412              | -41.24                                                               | -40.04    |
|                    | Mid     | 2.437              | -42.11                                                               | -40.82    |
|                    | High    | 2.462              | -40.03                                                               | -41.52    |
| 802.11n HT20       | Low     | 2.412              | -46.62                                                               | -47.89    |
|                    | Mid     | 2.437              | -48.43                                                               | -48.17    |
|                    | High    | 2.462              | -47.96                                                               | -48.04    |
| 802.11n HT40       | Low     | 2.422              | -48.18                                                               | -47.48    |
|                    | Mid     | 2.437              | -48.17                                                               | -47.42    |
|                    | High    | 2.452              | -47.41                                                               | -47.07    |

**Band Edge – 802.11b Mode**






Antenna 1: Low Channel - Plot




Antenna 1: High Channel – Plot






Antenna 2: Reference Measurement (Low Channel) – Plot




Antenna 2: Low Channel - Plot




Antenna 2: High Channel – Plot


**Band Edge – 802.11g Mode**




Antenna 1: Low Channel - Plot



Antenna 1: High Channel – Plot




Antenna 2: Low Channel - Plot




Antenna 2: High Channel - Plot


**Band Edge – 802.11n HT20 Mode**




Antenna 1: Reference Measurement (Mid Channel) – Plot




Antenna 1: Low Channel - Plot




Antenna 1: High Channel – Plot



Antenna 2: Reference Measurement (Low Channel) – Plot




Antenna 2: Low Channel - Plot




Antenna 2: High Channel - Plot




**Band Edge – 802.11n HT40 Mode**




Antenna 1: Reference Measurement (Low Channel) – Plot




Antenna 1: Low Channel - Plot




Antenna 1: High Channel – Plot



Antenna 2: Reference Measurement (Low Channel) – Plot




Antenna 2: Low Channel - Plot




Antenna 2: High Channel - Plot


**Conducted Spurious – 802.11b Mode**




Antenna 1: Low Channel - Plot




Antenna 1: Mid Channel - Plot




Antenna 1: High Channel – Plot



Antenna 2: Low Channel - Plot




Antenna 2: Mid Channel - Plot




Antenna 2: High Channel - Plot

**Conducted Spurious – 802.11g Mode**




Antenna 1: Low Channel - Plot




Antenna 1: Mid Channel - Plot







Antenna 1: High Channel – Plot



Antenna 2: Low Channel - Plot




Antenna 2: Mid Channel - Plot




Antenna 2: High Channel - Plot


**Conducted Spurious – 802.11n HT20 Mode**




Antenna 1: Low Channel - Plot




Antenna 1: Mid Channel - Plot




Antenna 1: High Channel – Plot



Antenna 2: Low Channel - Plot




Antenna 2: Mid Channel - Plot




Antenna 2: High Channel - Plot


**Conducted Spurious – 802.11n HT40 Mode**




Antenna 1: Low Channel - Plot




Antenna 1: Mid Channel - Plot




Antenna 1: High Channel – Plot



Antenna 2: Low Channel - Plot



Antenna 2: Mid Channel - Plot



Antenna 2: High Channel - Plot



## Radiated Emissions (Intentional)

### Test Description

Intentional Radiator Radiated Emissions are a test of the emissions, and harmonics on the EUT. The EUT is positioned to get the maximum emissions after a series of prescan measurements.

The EUT is placed on a non-conducting table 80 cm above the ground plane for below 1 GHz measurements and 1.5 m above the ground plane for above 1 GHz measurements. The antenna to EUT distance is 3 meters.

For measurements below 1 GHz the resolution bandwidth is set to 120 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz; the video bandwidth is set to 1 MHz for peak measurements and as applicable for average measurements.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in each applicable band.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

### Test Criteria

| Reference                                                       | Limit                 |                             |                               |
|-----------------------------------------------------------------|-----------------------|-----------------------------|-------------------------------|
|                                                                 | Frequency Range (MHz) | Field Strength Limit (uV/m) | Measurement distance (meters) |
| CFR 47 Subpart C, 15.205<br>CFR 47 Subpart C, 15.209<br>RSS-GEN | 0.009-0.490           | 2400/F(kHz)                 | 300                           |
|                                                                 | 0.490-1.705           | 24000/F(kHz)                | 30                            |
|                                                                 | 1.705-30.0            | 30                          | 30                            |
|                                                                 | 30-88                 | 100**                       | 3                             |
|                                                                 | 88-216                | 150**                       | 3                             |
|                                                                 | 216-960               | 200**                       | 3                             |
|                                                                 | Above 960             | 500                         | 3                             |

\*\*Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.


### Test Information

| Tester   | Test Location   | Date              | Temperature (°C) | Humidity (%RH) | Pressure (mbar) | Results (P/F) |
|----------|-----------------|-------------------|------------------|----------------|-----------------|---------------|
| JB/CL/MA | RF Chamber/OATS | 11/04/18-12/04/18 | 16.5             | 26.5           | 1012            | P             |

**NOTE:** Below 30MHz, pretesting showed that no emissions as a product of the EUT were detected within 20dB of the regulatory limit. Worse-case plot/data reported from 30MHz - 1GHz and above 18GHz. Prescans performed in an anechoic chamber, final measurements performed on an OATS. Since RedLINK/Wi-Fi radios can transmit simultaneously, additional spurious scans are provided with all radios on and transmitting in their worse-case state.

## Test Results

### Restricted Band Edge – 802.11b Mode



Antenna 1: Low Channel Horizontal – Plot

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.39          | 22.65                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 56.95                      | -                      | -           | 74                  | -17.05         | 150            | 135         | H        |
| 2      | * 2.39          | 23.67                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 57.97                      | -                      | -           | 74                  | -16.03         | 150            | 135         | H        |
| 3      | * 2.39          | 10.96                | RMS | 28.5      | .7          | 2.6       | 2.5       | 45.26                      | 54                     | -8.74       | -                   | -              | 150            | 135         | H        |
| 4      | * 2.39          | 12.12                | RMS | 28.5      | .7          | 2.6       | 2.5       | 46.42                      | 54                     | -7.58       | -                   | -              | 150            | 135         | H        |


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

NOTE: Emissions highlighted in the plot above is OATS ambient and not a product of the transmitter.

Data



Antenna 1: Low Channel Vertical - Plot

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.39          | 24.34                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 58.64                      | -                      | -           | 74                  | -15.36         | 36             | 106         | V        |
| 2      | * 2.39          | 25.53                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 59.83                      | -                      | -           | 74                  | -14.17         | 36             | 106         | V        |
| 3      | * 2.39          | 13.4                 | RMS | 28.5      | .7          | 2.6       | 2.5       | 47.7                       | 54                     | -6.3        | -                   | -              | 36             | 106         | V        |
| 4      | * 2.39          | 13.39                | RMS | 28.5      | .7          | 2.6       | 2.5       | 47.69                      | 54                     | -6.31       | -                   | -              | 36             | 106         | V        |


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

NOTE: Emissions highlighted in the plot above is OATS ambient and not a product of the transmitter.

Data



Antenna 1: High Channel Horizontal - Plot


| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.484         | 22.4                 | Pk  | 28.7      | .7          | 2.6       | 2.6       | 57                         | -                      | -           | 74                  | -17            | 167            | 111         | H        |
| 2      | * 2.484         | 24.6                 | Pk  | 28.7      | .7          | 2.6       | 2.6       | 59.2                       | -                      | -           | 74                  | -14.8          | 167            | 111         | H        |
| 3      | * 2.484         | 12.95                | RMS | 28.7      | .7          | 2.6       | 2.6       | 47.55                      | 54                     | -6.45       | -                   | -              | 167            | 111         | H        |
| 4      | * 2.484         | 13.14                | RMS | 28.7      | .7          | 2.6       | 2.6       | 47.74                      | 54                     | -6.26       | -                   | -              | 167            | 111         | H        |

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

Data



Antenna 1: High Channel Vertical - Plot


| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.484         | 23.49                | Pk  | 28.7      | .7          | 2.6       | 2.6       | 58.09                      | -                      | -           | 74                  | -15.91         | 31             | 102         | V        |
| 2      | * 2.485         | 25.73                | Pk  | 28.7      | .7          | 2.6       | 2.6       | 60.33                      | -                      | -           | 74                  | -13.67         | 31             | 102         | V        |
| 3      | * 2.484         | 12.56                | RMS | 28.7      | .7          | 2.6       | 2.6       | 47.16                      | 54                     | -6.84       | -                   | -              | 31             | 102         | V        |
| 4      | * 2.484         | 13.56                | RMS | 28.7      | .7          | 2.6       | 2.6       | 48.16                      | 54                     | -5.84       | -                   | -              | 31             | 102         | V        |

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

Data



Antenna 2: Low Channel Horizontal - Plot

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.39          | 21.59                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 55.89                      | -                      | -           | 74                  | -18.11         | 193            | 123         | H        |
| 2      | * 2.389         | 23.03                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 57.33                      | -                      | -           | 74                  | -16.67         | 193            | 123         | H        |
| 3      | * 2.39          | 9.45                 | RMS | 28.5      | .7          | 2.6       | 2.5       | 43.75                      | 54                     | -10.25      | -                   | -              | 193            | 123         | H        |
| 4      | * 2.39          | 10.27                | RMS | 28.5      | .7          | 2.6       | 2.5       | 44.57                      | 54                     | -9.43       | -                   | -              | 193            | 123         | H        |


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

NOTE: Emissions highlighted in the plot above is OATS ambient and not a product of the transmitter.

Data



Antenna 2: Low Channel Vertical - Plot

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.39          | 23.38                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 57.68                      | -                      | -           | 74                  | -16.32         | 27             | 116         | V        |
| 2      | * 2.388         | 24.9                 | Pk  | 28.5      | .7          | 2.6       | 2.5       | 59.2                       | -                      | -           | 74                  | -14.8          | 27             | 116         | V        |
| 3      | * 2.39          | 12.66                | RMS | 28.5      | .7          | 2.6       | 2.5       | 46.96                      | 54                     | -7.04       | -                   | -              | 27             | 116         | V        |
| 4      | * 2.39          | 12.03                | RMS | 28.5      | .7          | 2.6       | 2.5       | 46.33                      | 54                     | -7.67       | -                   | -              | 27             | 116         | V        |


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

NOTE: Emissions highlighted in the plot above is OATS ambient and not a product of the transmitter.

Data



Antenna 2: High Channel Horizontal - Plot

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.484         | 26.16                | Pk  | 28.7      | .7          | 2.6       | 2.6       | 60.76                      | -                      | -           | 74                  | -13.24         | 163            | 194         | H        |
| 2      | * 2.484         | 27.99                | Pk  | 28.7      | .7          | 2.6       | 2.6       | 62.59                      | -                      | -           | 74                  | -11.41         | 163            | 194         | H        |
| 3      | * 2.484         | 14.61                | RMS | 28.7      | .7          | 2.6       | 2.6       | 49.21                      | 54                     | -4.79       | -                   | -              | 163            | 194         | H        |
| 4      | * 2.484         | 15.74                | RMS | 28.7      | .7          | 2.6       | 2.6       | 50.34                      | 54                     | -3.66       | -                   | -              | 163            | 194         | H        |


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

Data





Antenna 2: High Channel Vertical - Plot

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.484         | 28.22                | Pk  | 28.7      | .7          | 2.6       | 2.6       | 62.82                      | -                      | -           | 74                  | -11.18         | 31             | 103         | V        |
| 2      | * 2.485         | 28.87                | Pk  | 28.7      | .7          | 2.6       | 2.6       | 63.47                      | -                      | -           | 74                  | -10.53         | 31             | 103         | V        |
| 3      | * 2.484         | 15.77                | RMS | 28.7      | .7          | 2.6       | 2.6       | 50.37                      | 54                     | -3.63       | -                   | -              | 31             | 103         | V        |
| 4      | * 2.484         | 16                   | RMS | 28.7      | .7          | 2.6       | 2.6       | 50.6                       | 54                     | -3.4        | -                   | -              | 31             | 103         | V        |


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

Data

**Restricted Band Edge – 802.11g Mode**



Antenna 1: Low Channel Horizontal – Plot

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.39          | 28.37                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 62.67                      | -                      | -           | 74                  | -11.33         | 152            | 223         | H        |
| 2      | * 2.389         | 29.5                 | Pk  | 28.5      | .7          | 2.6       | 2.5       | 63.8                       | -                      | -           | 74                  | -10.2          | 152            | 223         | H        |
| 3      | * 2.39          | 15.71                | RMS | 28.5      | .7          | 2.6       | 2.5       | 50.01                      | 54                     | -3.99       | -                   | -              | 152            | 223         | H        |
| 4      | * 2.39          | 15.81                | RMS | 28.5      | .7          | 2.6       | 2.5       | 50.11                      | 54                     | -3.89       | -                   | -              | 152            | 223         | H        |


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

NOTE: Emissions highlighted in the plot above is OATS ambient and not a product of the transmitter.

Data



Antenna 1: Low Channel Vertical - Plot

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.39          | 30.77                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 65.07                      | -                      | -           | 74                  | -8.93          | 126            | 196         | V        |
| 2      | * 2.39          | 30.94                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 65.24                      | -                      | -           | 74                  | -8.76          | 126            | 196         | V        |
| 3      | * 2.39          | 15.38                | RMS | 28.5      | .7          | 2.6       | 2.5       | 49.68                      | 54                     | -4.32       | -                   | -              | 126            | 196         | V        |
| 4      | * 2.39          | 16.11                | RMS | 28.5      | .7          | 2.6       | 2.5       | 50.41                      | 54                     | -3.59       | -                   | -              | 126            | 196         | V        |


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

NOTE: Emissions highlighted in the plot above is OATS ambient and not a product of the transmitter.

Data



Antenna 1: High Channel Horizontal - Plot


| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.484         | 29.68                | Pk  | 28.7      | .7          | 2.6       | 2.6       | 64.28                      | -                      | -           | 74                  | -9.72          | 130            | 296         | H        |
| 2      | * 2.484         | 35.29                | Pk  | 28.7      | .7          | 2.6       | 2.6       | 69.89                      | -                      | -           | 74                  | -4.11          | 130            | 296         | H        |
| 3      | * 2.484         | 15.89                | RMS | 28.7      | .7          | 2.6       | 2.6       | 50.49                      | 54                     | -3.51       | -                   | -              | 130            | 296         | H        |
| 4      | * 2.484         | 17.29                | RMS | 28.7      | .7          | 2.6       | 2.6       | 51.89                      | 54                     | -2.11       | -                   | -              | 130            | 296         | H        |

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

Data



Antenna 1: High Channel Vertical - Plot


| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.484         | 29.72                | Pk  | 28.7      | .7          | 2.6       | 2.6       | 64.32                      | -                      | -           | 74                  | -9.68          | 85             | 277         | V        |
| 2      | * 2.484         | 34.27                | Pk  | 28.7      | .7          | 2.6       | 2.6       | 68.87                      | -                      | -           | 74                  | -5.13          | 85             | 277         | V        |
| 3      | * 2.484         | 17.95                | RMS | 28.7      | .7          | 2.6       | 2.6       | 52.55                      | 54                     | -1.45       | -                   | -              | 85             | 277         | V        |
| 4      | * 2.484         | 17.62                | RMS | 28.7      | .7          | 2.6       | 2.6       | 52.22                      | 54                     | -1.78       | -                   | -              | 85             | 277         | V        |

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

Data



Antenna 2: Low Channel Horizontal - Plot

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.39          | 31.94                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 66.24                      | -                      | -           | 74                  | -7.76          | 314            | 321         | H        |
| 2      | * 2.389         | 31.73                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 66.03                      | -                      | -           | 74                  | -7.97          | 314            | 321         | H        |
| 3      | * 2.39          | 16.38                | RMS | 28.5      | .7          | 2.6       | 2.5       | 50.68                      | 54                     | -3.32       | -                   | -              | 314            | 321         | H        |
| 4      | * 2.39          | 16.62                | RMS | 28.5      | .7          | 2.6       | 2.5       | 50.92                      | 54                     | -3.08       | -                   | -              | 314            | 321         | H        |


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

NOTE: Emissions highlighted in the plot above is OATS ambient and not a product of the transmitter.

Data



Antenna 2: Low Channel Vertical - Plot

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.39          | 26.16                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 60.46                      | -                      | -           | 74                  | -13.54         | 33             | 112         | V        |
| 2      | * 2.39          | 29.32                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 63.62                      | -                      | -           | 74                  | -10.38         | 33             | 112         | V        |
| 3      | * 2.39          | 15.64                | RMS | 28.5      | .7          | 2.6       | 2.5       | 49.94                      | 54                     | -4.06       | -                   | -              | 33             | 112         | V        |
| 4      | * 2.39          | 15.56                | RMS | 28.5      | .7          | 2.6       | 2.5       | 49.86                      | 54                     | -4.14       | -                   | -              | 33             | 112         | V        |


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

NOTE: Emissions highlighted in the plot above is OATS ambient and not a product of the transmitter.

Data



Antenna 2: High Channel Horizontal - Plot

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.484         | 34.23                | Pk  | 28.7      | .7          | 2.6       | 2.6       | 68.83                      | -                      | -           | 74                  | -5.17          | 331            | 342         | H        |
| 2      | * 2.484         | 35.54                | Pk  | 28.7      | .7          | 2.6       | 2.6       | 70.14                      | -                      | -           | 74                  | -3.86          | 331            | 342         | H        |
| 3      | * 2.484         | 16.35                | RMS | 28.7      | .7          | 2.6       | 2.6       | 50.95                      | 54                     | -3.05       | -                   | -              | 331            | 342         | H        |
| 4      | * 2.484         | 17.23                | RMS | 28.7      | .7          | 2.6       | 2.6       | 51.83                      | 54                     | -2.17       | -                   | -              | 331            | 342         | H        |


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

Data





Antenna 2: High Channel Vertical - Plot

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.484         | 33.19                | Pk  | 28.7      | .7          | 2.6       | 2.6       | 67.79                      | -                      | -           | 74                  | -6.21          | 127            | 254         | V        |
| 2      | * 2.484         | 36.59                | Pk  | 28.7      | .7          | 2.6       | 2.6       | 71.19                      | -                      | -           | 74                  | -2.81          | 127            | 254         | V        |
| 3      | * 2.484         | 18.38                | RMS | 28.7      | .7          | 2.6       | 2.6       | 52.98                      | 54                     | -1.02       | -                   | -              | 127            | 254         | V        |
| 4      | * 2.484         | 18.64                | RMS | 28.7      | .7          | 2.6       | 2.6       | 53.24                      | 54                     | -.76        | -                   | -              | 127            | 254         | V        |


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

Data

**Restricted Band Edge – 802.11n HT20 Mode**



Antenna 1: Low Channel Horizontal – Plot

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.39          | 30.16                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 64.46                      | -                      | -           | 74                  | -9.54          | 149            | 106         | H        |
| 2      | * 2.39          | 34.57                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 68.87                      | -                      | -           | 74                  | -5.13          | 149            | 106         | H        |
| 3      | * 2.39          | 15.9                 | RMS | 28.5      | .7          | 2.6       | 2.5       | 50.2                       | 54                     | -3.8        | -                   | -              | 149            | 106         | H        |
| 4      | * 2.39          | 17.3                 | RMS | 28.5      | .7          | 2.6       | 2.5       | 51.6                       | 54                     | -2.4        | -                   | -              | 149            | 106         | H        |


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

NOTE: Emissions highlighted in the plot above is OATS ambient and not a product of the transmitter.

Data



Antenna 1: Low Channel Vertical - Plot

| Marker | Frequency (GHz) | Meter Reading (dBuV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBuV/m) | Average Limit (dBuV/m) | Margin (dB) | Peak Limit (dBuV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.39          | 37.01                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 71.31                      | -                      | -           | 74                  | -2.69          | 34             | 135         | V        |
| 2      | * 2.389         | 38.46                | Pk  | 28.5      | .7          | 2.6       | 2.5       | 72.76                      | -                      | -           | 74                  | -1.24          | 34             | 135         | V        |
| 3      | * 2.39          | 18.85                | RMS | 28.5      | .7          | 2.6       | 2.5       | 53.15                      | 54                     | -85         | -                   | -              | 34             | 135         | V        |
| 4      | * 2.39          | 19.37                | RMS | 28.5      | .7          | 2.6       | 2.5       | 53.67                      | 54                     | -33         | -                   | -              | 34             | 135         | V        |


\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

NOTE: Emissions highlighted in the plot above is OATS ambient and not a product of the transmitter.

Data



Antenna 1: High Channel Horizontal - Plot

| Marker | Frequency (GHz) | Meter Reading (dBUV) | Det | AF [dB/m] | SWBOX3 [dB] | SMA7 [dB] | SMA5 [dB] | Corrected Reading (dBUV/m) | Average Limit (dBUV/m) | Margin (dB) | Peak Limit (dBUV/m) | PK Margin (dB) | Azimuth (Degs) | Height (cm) | Polarity |
|--------|-----------------|----------------------|-----|-----------|-------------|-----------|-----------|----------------------------|------------------------|-------------|---------------------|----------------|----------------|-------------|----------|
| 1      | * 2.484         | 31.97                | Pk  | 28.7      | .7          | 2.6       | 2.6       | 66.57                      | -                      | -           | 74                  | -7.43          | 163            | 241         | H        |
| 2      | * 2.484         | 34.59                | Pk  | 28.7      | .7          | 2.6       | 2.6       | 69.19                      | -                      | -           | 74                  | -4.81          | 163            | 241         | H        |
| 3      | * 2.484         | 16.93                | RMS | 28.7      | .7          | 2.6       | 2.6       | 51.53                      | 54                     | -2.47       | -                   | -              | 163            | 241         | H        |
| 4      | * 2.484         | 17.23                | RMS | 28.7      | .7          | 2.6       | 2.6       | 51.83                      | 54                     | -2.17       | -                   | -              | 163            | 241         | H        |

\* - indicates frequency in CFR47 Pt 15 / IC RSS-Restricted Band

Pk - Peak detector

RMS - RMS detection

Data