



March 15, 2006

ATCB
McLean, VA

Dear Sirs:

Enclosed please find Cirronet Corporation's Application for FCC Part 15 Class II Permissive Change for the WIT 2450 Transceiver.

The EUT differs from the original Registration by removal of the inner shield, and replacement of the following components with Lead Free components:

Diode D3 – removed
Capacitor C201 – changed from 6.8 pF to 1 pF
Capacitors C18 and C19 – changed to 3.3 nH inductors
Inductors L6 and L7 changed from 2.4 nH to 1nH and 3.3 nH respectively
Replacement of U7 for a lead free equivalent, AM52-0024
Inductor L4 changed from 6.8 nH to 3.9 nH
Capacitor C31 replaced with a 0 ohm resistor
Capacitor C38 added @ 100 pF to replace o Ohm resistor
Inductor L8 changed from 8.7 nH to 22 nH

In order to show continuing compliance with the original registration, Conducted Output Power and Peak and Average Spurious Emissions with all antennas were repeated for Low, Mid and High Channel.

If you have any questions, please don't hesitate to call. Thank you for your consideration.

Sincerely,

Louis A. Feudi
Operations Manager

**3505 Francis Circle Alpharetta, GA 30004
PH: 770-740-0717 Fax: 770-740-1508
www.ustech-lab.com**