

## **§1.1307(b) (1) & §2.1091 - RF EXPOSURE**

---

According to §15.247(e)(1) & 15.407 and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
<b>Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

### **MPE Prediction**

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S = power density

P = power input to antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

5250 – 5350 MHz:

Maximum peak output power at antenna input terminal: 1.5 (dBm)

Maximum peak output power at antenna input terminal: 1.413 (mW)

Prediction frequency: 5300 (MHz)

Antenna Gain (typical): 28.5 (dBi)

antenna gain: 707.94 (numeric)

Prediction distance: 50 (cm)

Power density at prediction frequency at 50 cm: 0.03 (mW/cm<sup>2</sup>)

MPE limit for uncontrolled exposure at prediction frequency: 1.0 (mW/cm<sup>2</sup>)

**Result:** The EUT is of fixed outdoor installation, point -to-point or point-to-multipoint. 1mW/ cm<sup>2</sup> limit applies. The prediction distance for the 5GHz antenna is 50 cm.