

DIRECTIONAL (CPE) ANTENNAS

MT-466010/NVH

4.9 - 6.425 GHz 28 DBI DUAL POLARIZATION DIRECTIONAL ANTENNA



ELECTRICAL

REGULATORY COMPLIANCE	ETSI EN 302 326- V1.1.2 (2006-03) RoHS , CE 0682
FREQUENCY RANGE	4.9 - 6.425 GHz
GAIN	26.0dBi $\pm$ 1.0 dB @ 4.9-5.15GHz 28.0dBi $\pm$ 1.0 dB @ 5.15-6.25GHz 27.0dBi $\pm$ 1.0 dB @ 6.25-6.425GHz
VSWR	2.0 : 1 (max) @ 4.9-6.25GHz 2.3 : 1 (max) @ 6.25-6.425GHz
POLARIZATION	Dual Linear (Vertical and Horizontal)
3 dB BEAMWIDTH	5°(typ)
SIDELOBES LEVEL	ETSI EN 302 326-3 V1.1.2 DN3
F/B RATIO	-40 dB (max)
CROSS POLARIZATION	ETSI EN 302 326-3 V1.1.2 DN3
PORT TO PORT ISOLATION	-25 dB (max) , -30 dB (typ)
POWER	6W (max)
INPUT IMPEDANCE	50 (ohm)
LIGHTNING PROTECTION	DC Grounded


MECHANICAL

DIMENSIONS (LxWxD)	600 x 600 x 51 mm (max)
CONNECTOR	2 xN-Type Female
WEIGHT	5 kg (max)
MOUNTING KIT	SEE RD41191800C ,MT-120019
RADOME MATERIAL	Plastic
BASE PLATE MATERIAL	Aluminum with chemical conversion coating
OUTLINE DRAWING	RD43154500C


ENVIRONMENTAL

TEST	STANDARD	DURATION	TEMPERTURE	NOTES
LOW TEMPERATURE	IEC 68-2-1	72 h	-55°C	
HIGH TEMPERATURE	IEC 68-2-2	72 h	+71°C	
TEMP. CYCLING	IEC 68-2-14	1 h	-45°C +70°C	3 Cycles
VIBRATION	IEC 60721-3-4	30 min/axis		Random4M3
SHOCK MECHANICAL	IEC 60721-3-4			4M3
HUMIDITY	ETSI EN300-2-4 T4.1E	144 h		95%
WATER TIGHTNESS	IEC 529			IP67
SOLAR RADIATION	ASTM G53	2000h		
FLAMMABILITY	UL 94			Class HB
SALT SPRAY	IEC 68-2-11 Ka	500h		
ICE AND SNOW				25mm Radial
WIND SPEED SURVIVAL				220 Km/h
OPERATION				160 Km/h
WIND LOAD (SURVIVAL)				103.6 kg
FRONT THRUST				8.6 kg
SIDE THRUST				


AZIMUTH RADIATION PATTERN MIDBAND
FREQ. 5.7 GHZ






ELEVATION RADIATION PATTERN MIDBAND
FREQ. 5.7 GHZ



MT_466010NVH_PORT_V_AZ_PLANE Freq: 5.7 GHz



MT_466010NVH_PORT_V_EL_PLANE Freq: 5.7 GHz



WAIVER!

While the information contained in this document has been carefully compiled to the best of our present knowledge, it is not intended as presentation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.