

ZEBRA TECHNOLOGIES CORP.

THERMAL CARD PRINTER

Model: P330i

23 April 2008

Report No.: SL08012102-ZBR-007 Rev 4.0 (15.247) (P330i)
(This report supersedes NONE)



Modifications made to the product : None

This Test Report is Issued Under the Authority of:

	
Dan Coronia Test Engineer	Leslie Bai Engineering Reviewer

This test report may be reproduced in full only.
Test result presented in this test report is applicable to the representative sample only.





SIEMIC, INC.
Accessing global markets

Title: RF Test Report of Zebra Technologies Corp.
Model : P330i
To FCC 15.247 2007, IC RSS210 Issue 7: 2007

Serial# SL08012102-ZBR-007 Rev 4.0 (15.247)(P330i)
Issue Date 23 April 2008
Page 2 of 61
www.siemic.com

SIEMIC ACREDITATION DETAILS: NVLAP Lab Code: 200729-0

United States Department of Commerce
National Institute of Standards and Technology



Certificate of Accreditation to ISO/IEC 17025:2005

NVLAP LAB CODE: 200729-0

SIEMIC Laboratories
San Jose, CA

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,
listed on the Scope of Accreditation, for:*

ELECTROMAGNETIC COMPATIBILITY AND TELECOMMUNICATIONS

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality
management system (refer to joint ISO-IAC-IAF Communiqué dated 18 June 2005).*

2008-01-01 through 2008-12-31

Effective dates



Sally S. Bruce
For the National Institute of Standards and Technology



SIEMIC, INC.
Accessing global markets

Title: RF Test Report of Zebra Technologies Corp.
Model : P330i
To FCC 15.247 2007, IC RSS210 Issue 7: 2007

Serial# SL08012102-ZBR-007 Rev 4.0 (15.247)(P330i)
Issue Date 23 April 2008
Page 3 of 61
www.siemic.com

SIEMIC ACREDITATION DETAILS: FCC Registration No. 783147

FEDERAL COMMUNICATIONS COMMISSION

Laboratory Division
7435 Oakland Mills Road
Columbia, MD 21046

January 27, 2005

Registration Number: 783147

SIEMIC Laboratories
2206 Ringwood Avenue
San Jose, CA 95131

Attention: Leslie Bai

Re: Measurement facility located at San Jose
3 & 10 meter site
Date of Renewal: January 27, 2005


Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.


Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website www.fcc.gov under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,

Phyllis Parrish
Information Technician



SIEMIC ACREDITATION DETAILS: Industry of Canada Registration No. 4842-1



April 26, 2006

OUR FILE: 46405-4842
Submission No: 114591

Siemic Inc.
2106 Ringwood Ave.,
San Jose, CA 95131

Dear Sir/Madame:

The Bureau has received your application for the Alternate Test Site and the filing is satisfactory to Industry Canada.


Please reference to the file number (4842-1) in the body of all test reports containing measurements performed on the site.

Renewal of the filing is required every two years.

If you have any questions, you may contact the Bureau at the telephone number below or by e-mail at certification.bureau@ic.gc.ca. Please reference our file number above for all correspondence.

Yours sincerely,

Robert Corey
Manager Certification
Certification and Engineering Bureau
3701 Carling Ave., Building 94
Ottawa, Ontario
K2H 8S2
Tel. No. (613) 990-3869



SIEMIC ACREDITATION DETAILS: Japan VCCI Registration No. 2195



Voluntary Control Council for Interference
by Information Technology Equipment
7F NDA Bldg. 2-3-5, Azabudai,
Minato-Ku, Tokyo, Japan, 106-0041
Tel+81-3-5575-3138
Fax+81-3-5575-3137
<http://www.vcci.or.jp>

February 12, 2004

TO: SIEMIC, INC.

Membership NO: 2195

We confirmed your payment for annual membership fee and admission fee. Thank you very much for your remitting.

Please find enclosed VCCI documents. As admission fee and annual membership fee were confirmed, your company registered as VCCI official member.

From now on, it is possible for your company to submit conformity verification report or/and application for registration of measurement facilities.

Please find necessary forms for your submission from VCCI web-site.
www.vcci.or.jp

When you submit conformity verification report, please submit to Ms. Yoko Inagaki / inagaki@vcci.or.jp and application for registration of measurement facilities, please submit to Mr. Masaru Denda / denda@vcci.or.jp


Their address, phone and fax number are absolutely same as L. Please refer address indicated on top right-hand corner of this page.

If you have any other questions regarding membership, feel free to contact me.
Thank you very much.

Best Regards,

Naoko Hori (Ms.)
VCCI
hori@vcci.or.jp

Enclosure




SIEMIC ACREDITATION DETAILS: Japan RF Technologies Accreditation No. MRF050927



SIEMIC ACREDITATION DETAILS: Korea MIC Lab Code: KR0032





SIEMIC ACREDITATION DETAILS: Korea CAB ID: US0160

April 17, 2006

Mr. Leslie Bai
SIEMIC Laboratories
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

I am pleased to inform you that your laboratory has been recognized by the Ministry of Information and Communication's Radio Research Laboratory (RRL) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: **SIEMIC Laboratories**
Identification No.: **US0160**
Scope:

Coverage	Standards	Date of Recognition
Electro Magnetic Interference	1. RRL Notice No. 2005-82: Technical Requirements for Electromagnetic Interference 2. Annex 8(KN-22), RRL Notice No. 2005-131: Conformity Assessment Procedure for Electromagnetic Interference	April 13, 2006
Electro Magnetic Susceptibility	1. RRL Notice No. 2005-130: Technical Requirements for Electromagnetic Susceptibility 2. Annex 1-7(KN-61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11), RRL Notice No. 2005-132: Conformity Assessment Procedure for Electromagnetic Susceptibility	April 13, 2006

You may submit test data to RRL to verify that the equipment to be imported into Korea satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.


The names of all recognized CABs will be posted on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Mr. Jogindar (Joe) Dhillon at (301) 975-5521. We appreciate your continued interest in our international conformity assessment activities.

Sincerely,


David F. Alderman
Group Leader, Standards Coordination and Conformity Group

cc: Jogindar Dhillon





SIEMIC ACREDITATION DETAILS: Taiwan BSMI Accreditation No. SL2-IN-E-1130R



UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
Gaithersburg, Maryland 20883

May 3, 2006

Mr. Leslie Bai
SIEMIC Laboratories
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

I am pleased to inform you that your laboratory has been recognized by the Chinese Taipei's Bureau of Standards, Metrology, and Inspection (BSMI) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. You may submit test data to BSMI to verify that the equipment to be imported into Chinese Taipei satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. The pertinent designation information is as follows:

- BSMI number: **SL2-IN-E-1130R** (Must be applied to the test reports)
- U.S Identification No: **US0160**
- Scope of Designation: **CNS 13438**
- Authorized signatory: **Mr. Leslie Bai**


The names of all recognized CABs will be posted on the NIST website at <http://ts.nist.gov/mra>. If you have any questions, please contact Mr. Dhillon at 301-975-5521. We appreciate your continued interest in our international conformity assessment activities.

Sincerely,

David F. Alderman
Group Leader, Standards Coordination and Conformity Group

cc: Joginder Dhillon

NIST



SIEMIC ACREDITATION DETAILS: Taiwan NCC CAB ID: US0160



UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
Gaithersburg, Maryland 20885

August 8, 2006

Mr. Leslie Bai
SIEMIC Laboratories
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

I am pleased to inform you that SIEMIC Laboratories has been recognized by the Chinese Taipei's National Communications Commission (NCC) under the Asia Pacific Economic Cooperation for Telecommunications and Information, Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA.

You may submit test data to NCC to verify that the equipment to be imported into Chinese Taipei satisfies their applicable requirements using the following guidelines:

- Your laboratory's assigned 6-digit U.S. identification number is **US0160**. You should reference this number in your correspondence.
- The scope of designation is limited to **LP0002**. Your designation will remain in force as long as your accreditation remains valid for the scope of designation.


If you have any questions please contact Mr. Jogindar Dhillon via email at dhillon@nist.gov or via fax at 301-975-5414. The names of all recognized laboratories will be posted on the NIST website at <http://ts.nist.gov/mra>. We appreciate your continued interest in our international conformity assessment activities.

Sincerely,

David F. Alderman
Group Leader, Standards Coordination and Conformity Group

cc: Jogindar Dhillon

NIST



SIEMIC ACREDITATION DETAILS: Mexico NOM Recognition

Laboratorio Valentín V. Rivero

CANIETI
CÁMARA NACIONAL
DE LA INDUSTRIA
ELECTRÓNICA, DE
TELECOMUNICACIONES
E INFORMÁTICA

México D.F. a 16 de octubre de 2006.

LESLIE BAI
DIRECTOR OF CERTIFICATION
SIEMIC LABORATORIES, INC.
ACCESSING GLOBAL MARKETS
P R E S E N T E

En contestación a su escrito de fecha 5 de septiembre del año en curso, le comento que estamos muy interesados en su intención de firmar un Acuerdo de Reconocimiento Mutuo, para lo cual adjunto a este escrito encontrara el Acuerdo en idioma inglés y español prellenado de los cuales le pido sea revisado y en su caso corregido, para que si esta de acuerdo poder firmarlo para mandarlo con las autoridades Mexicanas para su visto bueno y así poder ejercer dicho acuerdo.

Aprovecho este escrito para mencionarle que nuestro intermediario gestor será la empresa Isabel de México, S. A. de C. V., empresa que ha colaborado durante mucho tiempo con nosotros en lo relacionado a la evaluación de la conformidad y que cuenta con amplia experiencia en la gestoría de la certificación de cumplimiento con Normas Oficiales Mexicanas de producto en México.


Me despido de usted enviándole un cordial saludo y esperando sus comentarios al Acuerdo que nos ocupa.

Atentamente:

[Handwritten signature of Ing. Faustino Bóquez González]

Ing. Faustino Bóquez González
Gerente Técnico del Laboratorio de
CANIETI.

Callejón 71
Hacienda Condessa
C.P. 11000 México, D.F.
Tel. 5264-0308 con 12 líneas
Fax 5264-0488
www.canieti.org



SIEMIC ACREDITATION DETAILS: Hong Kong OFTA Recognition No. D23/16V



Your Ref 来函檔號 : D23/16 V
Our Ref 本局檔號 :

Telephone 電話 : (852) 2961 6320
Fax No 圖文傳真 : (852) 2838 5004
E-mail 電郵地址 : 20 July 2005

Mr. Leslie Bai
Director of Certification,
SIEMIC Laboratories
2206 Ringwood Avenue
San Jose, California 95131
USA

Dear Mr. Bai,

Application of Recognised Testing Agency (RTA)

Referring your subenmission of 28 June 2005 in relation to the application of RTA, I am pleased to inform you that OFTA has appointed SIEMIC Laboratories (SIEMIC) as a Recognised Testing Agency (RTA) :

Please note that, under the Hong Kong Telecommunications Equipment Evaluation and Certification (HKTEC) Scheme, SIEMIC is authorized to conduct evaluation tests on telecommunications equipment against the following HKTA specifications :

Scope of recognition (HKTA Specifications):

1001, 1002, 1004, 1006, 1007, 1008
1010, 1015, 1016
1022, 1026, 1027, 1029
1030, 1031, 1032, 1033, 1034, 1035, 1039
1041, 1042, 1043, 1045, 1047, 1048
2001

You are requested to refer to and comply with the code of practice and guidelines for RTA as given in the Information Note OFTA I 411 "Recognised Testing Agency (RTA) for Conducting Evaluation Test of Telecommunications Equipment", which can be downloaded from OFTA's homepage at <http://www.ofta.gov.hk/tec/information-notes.html>.


If you have any queries, please do not hesitate to contact me.

Yours sincerely,

(K. K. Sin)
for Director-General
of Telecommunications

Office of the Telecommunications Authority
29/F Wu Chung House 213 Queen's Road East Wan Chai Hong Kong
電訊管理局
香港灣仔皇后大道東 213 號胡忠大廈 29 字樓


<http://www.ofta.gov.hk>



This page has been left blank intentionally.

CONTENTS

1	EXECUTIVE SUMMARY & EUT INFORMATION	10
2	TECHNICAL DETAILS.....	10
3	MODIFICATION.....	10
4	TEST SUMMARY.....	10
5	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	10
	ANNEX A. TEST INSTRUMENT & METHOD	10
	ANNEX B EUT AND TEST SETUP PHOTOGRAPHS	10
	ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT	10
	ANNEX D USER MANUAL, BLOCK & CIRCUIT DIAGRAM	10



This page has been left blank intentionally.

1 Executive Summary & EUT information

The purpose of this test programme was to demonstrate compliance of the Zebra Technologies Corp., model: P330i against the current Stipulated Standards. The Thermal Card Printer have demonstrated compliance with the FCC 15.247 2007 & IC RSS210 Issue 7: 2007.

EUT Information

EUT Description : The Zebra P330i is a single sided card printer that can print monochrome or full color images on a PVC card in one pass through the printer. The Zebra P330i uses color dye-sublimation ribbons or thermal transfer ribbons to transfer digital images to a PVC card. These cards can be used for identification, loyalty cards, or marketing purposes.

Options for this printer include Ethernet, magnetic card encoding, contact and contact-less smart card encoding, and UHF smart card encoding. Ribbon recognition and security is maintained through RFID technology within the printer. The RFID board and the contactless smartcards use separate transmitters each operating at a frequency of 13.56 MHz in the ISM band.

The RFID system uses an I•CODE1 format and conforms to ISO 15693 specifications. The RFID system is contained on a single PCBA which holds the loop antenna, impedance matching network, RF interface IC and digital controller IC. The design is optimized for short range lower power operation.


The Zebra ZM5e is a RFID reader that can read and encode RFID smart cards. Smart cards carry embedded ultra-thin UHF RFID transponders. Transponders contain thin antennas and integrated circuits that can be read, programmed, and reprogrammed using non-contact radio waves. RFID smart cards allow for non-line of sight reading of the data contained in the IC and feature anti-collision technology, which allows RFID readers to scan and identify several objects simultaneously, such as totes of supplies.

The RFID subsystem is comprised of a ThingMagic Mercury 5e multi protocol UHF RFID reader, a coupler/antenna connected to the reader via a coaxial cable and an adaptor PCB that provides the operating voltage and communications to the RFID reader.

The RFID reader powers and communicates with RFID smart cards via the coupler/antenna. The reader contains a digital processor and analog signal conditioning circuitry. Instructions from the host computer system to encode/read a smart label are sent to the RFID reader via a serial communication link on the adapter PCB. The reader responds to the host with data read and/or a status message. The UHF RF signals generated by the reader are turned on only during a host commanded read or encode operation. The RF signal is an amplitude-modulated frequency-hopping carrier operating between 902MHz and 928MHz. The modulation pattern is governed by the selected UHF RFID protocol. The reader supports EPC Class1 Gen 2/ISO18000-6C UHF RFID protocols.


The coupler/antenna is located in close proximity to the RFID transponder when the smart label is in the rest position prior to printing. The coupler/antenna is a single or dual strip-line transmission line fabricated on a two-sided printed circuit board with one side acting as a ground plane. The coupler/antenna is orientated with the ground-plane side down, roughly parallel to the base of the printer. The reader's transmitter and receiver are both connected directly to the coupler/antenna via the coaxial cable. Backscatter signals from the transponder are received via the same coupler/antenna as is used to transmit to the transponder.

The adapter PCB provides the correct operating voltage to the RFID reader and serves as a




communications interface between host and RFID reader. The adapter PCB down converts the host's voltage, 18 to 30Vdc, to 5.0V nominal at .5 to 1.0 Amp steady state current. The adapter PCB also buffers, both directions, the host and RFID readers RS232 TTL level receive and transmit lines. The adapter PCB provides power and com to the RFID reader though a single discrete cable assembly. The host connects to the adapter PCB via two discrete wire cable assemblies, one for power the other for com.

Model No : P330i
Serial No : N/A
Input Power : 100~240 VAC
Classification : Frequency Hopping Spread Spectrum / Device
Per Stipulated Test Standard :



2 TECHNICAL DETAILS

Purpose	Compliance testing of Thermal Card Printer with stipulated standard
Applicant / Client	ZEBRA TECHNOLOGIES CORP.
Manufacturer	Zebra Technologies Corp. 333 Corporate Woods Parkway Vernon Hills, IL 60061 USA
Laboratory performing the tests	SIEMIC Laboratories
Test report reference number	SL08012102-ZBR-007 Rev 4.0 (15.247) (P330i)
Date EUT received	25 February 2008
Standard applied	47 CFR §15.247: 2007 & RSS 210 Issue 7: 2007
Dates of test (from – to)	28 February 2008 – 03 March 2008
No of Units:	2
Equipment Category:	DSS
Trade Name:	Zebra Technologies Corp.
Model :	P330i
RF Operating Frequency (ies)	902.750 to 927.250 MHz
Number of Channels :	50
Modulation :	ISO 18000-6C
FCC ID :	I28-P330I-UHF
IC ID :	3798B-P330UHF



3 MODIFICATION

NONE

4 TEST SUMMARY

The product was tested in accordance with the following specifications. All testing has been performed according to below product classification:

Frequency Hopping Spread Spectrum / Device

Test Results Summary

Test Standard		Description	Pass / Fail
47 CFR Part 15.247: 2007	RSS 210 Issue 7: 2007		
15.203		Antenna Requirement	Pass
15.205	RSS210(A8.5)	Restricted Band of Operation	Pass
15.207(a)	RSS Gen (7.2.2)	AC Line Conducted Emissions Voltage	Pass
15.247(a) (1)	RSS210(A8.1)	Channel Separation	Pass
15.247(a)(1)	RSS210(A8.1)	Occupied Bandwidth	Pass
15.247(a) (2)	RSS210 (A8.2)	6dB Bandwidth	N/A
15.247(a) (1) (i)	RSS210(A8.1)	Number of Hopping Channels	Pass
15.247(a) (1) (i)	RSS210(A8.1)	Time of Occupancy	Pass
15.247(b) (2)	RSS210(A8.4)	Output Power	Pass
15.247(c)	RSS210(A8.4)	Antenna Gain > 6 dBi	Pass
15.247(d)	RSS210(A8.5)	Antenna Port Conducted Spurious Emissions	Pass
15.209; 15.247(d)	RSS210(A8.5)	Radiated Spurious Emissions	Pass
15.247(e)	RSS210(A8.3)	Power Spectral Density	N/A
15.247(f)	RSS210(A8.3)	Hybrid System Requirement	N/A
15.247(g)	RSS210(A8.1)	Hopping Capability	Pass
15.247(h)	RSS210(A8.1)	Hopping Coordination Requirement	Pass
15.247(i) §2.1091 & §2.1093	RSSGen(5.5)	Maximum Permissible Exposure	Pass
15.247 (d)		100 kHz Bandwidth of Frequency Band Edge	Pass
	RSSGen(4.8)	Receiver Spurious Emissions	Pass
ANSI C63.4: 2003/ RSS-Gen Issue 2: 2007			
PS: All measurement uncertainties are not taken into consideration for all presented test result.			

5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

5.1 Antenna Requirement

Requirement(s): 47 CFR §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna requirement must meet at least one of the following:

- a) Antenna must be permanently attached to the device.
- b) Antenna must use a unique type of connector to attach to the device.
- c) Device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device.

1) The UHF antenna has a unique connector and installed inside on the chassis with a gain of -8dBi which meets the requirement.

5.2 Conducted Emissions Voltage

Requirement:

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

*Decreases with the logarithm of the frequency.

Procedures:


1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz – 30MHz (Average & Quasi-peak) is ± 3.5 dB.
4. Environmental Conditions

Temperature	23°C - 25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar

Test Date : February 28 & 29 to March 03, 2008


Tested By :Dan Corona

Results: Note – Average Limit Quasi-Peak Limit



Phase Line Plot at 120Vac, 60Hz

Line Under Test	Frequency (MHz)	Corrected Amplitude (dBuV) QP	Limit (dBuV) QP	Margin (dB) QP	Corrected Amplitude (dBuV) AVG	Limit (dBuV) AVG	Margin (dB) AVG
Phase	13.55	40.10	60.00	-19.90	35.80	50.00	-14.20
Phase	0.41	36.70	57.75	-21.05	32.50	47.75	-15.25
Phase	0.44	35.10	57.06	-21.96	31.00	47.06	-16.06
Phase	0.37	32.40	58.50	-26.10	28.40	48.50	-20.10
Phase	0.16	36.50	65.46	-28.96	32.40	55.46	-23.06
Phase	0.20	32.40	63.61	-31.21	28.50	53.61	-25.11



Neutral Line Plot at 120Vac, 60Hz

Line Under Test	Frequency (MHz)	Corrected Amplitude (dBuV) QP	Limit (dBuV) QP	Margin (dB) QP	Corrected Amplitude (dBuV) AVG	Limit (dBuV) AVG	Margin (dB) AVG
Neutral	13.55	41.40	60.00	-18.60	37.10	50.00	-12.90
Neutral	0.41	36.40	57.75	-21.35	32.40	47.75	-15.35
Neutral	0.44	34.50	57.06	-22.56	30.30	47.06	-16.76
Neutral	0.16	38.40	65.46	-27.06	34.30	55.46	-21.16
Neutral	0.33	31.00	59.45	-28.45	27.10	49.45	-22.35
Neutral	1.36	24.40	56.00	-31.60	21.30	46.00	-24.70

5.3 Channel Separation

1. Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power.
The spectrum analyzer was connected to the antenna terminal.

2 Environmental Conditions

Temperature	23°C - 25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar

3 Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz - 20GHz is ± 1.5 dB.

4 Test Date : February 28 & 29 to March 03, 2008


Tested By : Dan Corona

Requirement(s): 47 CFR §15.247(a)(1)(i)


Procedures: The Channel Separation was measured conducted using a spectrum analyzer at low, mid, and hi channels.

Frequency hopping systems in the 902-928 MHz shall have, hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies.


Channel	Channel Frequency (MHz)	Channel Separation (MHz)	20 dB Channel Bandwidth (KHz)
Low	902.750	0.500	83.00
Mid	915.250	0.500	82.00
High	927.250	0.500	82.00




Channel Separation - Low Channel




Channel Separation – Mid Channel





Channel Separation – High Channel



5.4 20dB Occupied Bandwidth

1. Conducted Measurement

EUT was set for low, mid, high channel with modulated mode and highest RF output power.

The spectrum analyzer was connected to the antenna terminal.

2. Environmental Conditions

Temperature	23°C - 25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar

3. Conducted Emissions Measurement Uncertainty

All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 20GHz is ± 1.5 dB.

4. Test Date : February 28 & 29 to March 03, 2008

Tested By :Dan Corona


Requirement(s): 47 CFR §15.247(a)(1)(i)

Procedures: The 20dB bandwidths were measured conducted using a spectrum analyzer at low, mid, and hi channels.


Note: The maximum allowed 20 dB bandwidth of the hopping is 500 kHz.

Channel	Channel Frequency (MHz)	20 dB Channel Bandwidth (KHz)	99% Channel Bandwidth (KHz)
Low	902.750	83.00	73.00
Mid	915.250	82.00	73.00
High	927.250	82.00	73.00


Refer to the attached plots.




20dB Bandwidth - Low Channel




99% Bandwidth - Low Channel







20dB Bandwidth – Mid Channel




99% Bandwidth - Mid Channel






20dB Bandwidth - High Channel



99% Bandwidth - High Channel



5.5 Number of Hopping Channel

1. Conducted Measurement
EUT was set for low , mid, high channel with modulated mode and highest RF output power.
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 20GHz is ± 1.5 dB.
3. Environmental Conditions

Temperature	23°C - 25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
4. Test Date : February 28 & 29 to March 03, 2008
Tested By :Dan Corona

Standard Requirement: 47 CFR §15.247(a)(1)(iii)

For frequency hopping systems operating in the 902–928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period. The maximum allowed 20 dB bandwidth of the hopping channel is 500 kHz.

Procedures: The Number of Hopping Channel measurement was taken conducted using a spectrum analyzer.


RBW=30 KHz, VBW > RBW

Test Result:

Total Channel: 50 Channels

Number of Hopping Channel

902 – 928 MHz: 50 Channels



5.6 Time of Occupancy

1. Conducted Measurement
EUT was set for low , mid, high channel with modulated mode and highest RF output power.
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 20GHz is ± 1.5 dB.
3. Environmental Conditions

Temperature	23°C - 25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
4. Test Date : February 28 & 29 to March 03, 2008
Tested By :Dan Corona


Standard Requirement: 47 CFR §15.247(a)(1)

For frequency hopping systems operating in the 902–928 MHz band: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping frequencies and the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period.



Procedures: The Time of Occupancy measurement was taken conducted using a spectrum analyzer.


Test Result:

Channel	Channel Frequency (MHz)	Dwell Time (sec)	Limit (sec)
Low	902.750	0.23	0.4
Mid	915.250	0.23	0.4
High	927.250	0.25	0.4






Low Channel







Mid Channel





High Channel



5.7 Peak Output Power

1. Conducted Measurement
EUT was set for low , mid, high channel with modulated mode and highest RF output power.
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is ± 1.5 dB.
3. Environmental Conditions

Temperature	23°C - 25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
4. Test Date : February 28 & 29 to March 03, 2008
Tested By :Dan Corona


Standard Requirement : 47 CFR §15.247(b)

Procedures: The peak output power was measured conducted using a spectrum analyzer at low, mid, and hi channels. Peak detector was set to measure the power output. The power is converted from watt to dBm, therefore, 1 watt = 30 dBm. The highest antenna gain that will be used is -8dBi.


Note: For frequency hopping systems operating in the 902–928 MHz band: 1 watt for systems employing at least 50 hopping channels; and, 0.25 watts for systems employing less than 50 hopping channels, but at least 25 hopping channels, as permitted under paragraph (a)(1)(i) of this section.

Test Result :


Channel	Channel Frequency (MHz)	Measured Output Power (dBm)	Peak Output Power Limit (dBm)
Low	902.750	29.33	30
Mid	915.250	29.67	30
High	927.250	29.50	30




Output Power Low Channel




Output Power Mid Channel





Output Power High Channel




5.8 100 kHz Bandwidth of Frequency Band Edge

1. Conducted Measurement
EUT was set for low, mid, high channel with modulated mode and highest RF output power.
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 20GHz is ± 1.5 dB.
3. Environmental Conditions
Temperature 23°C - 25°C
Relative Humidity 50%
Atmospheric Pressure 1019mbar
4. Test Date : February 28 & 29 to March 03, 2008
Tested By :Dan Corona


Standard Requirement : 47 CFR §15.247(b)

Procedures: in any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in §15.209(a) is not required.


Test Result:



Low Channel



High Channel




5.9 Antenna Port Emission

1. Conducted Measurement
EUT was set for low, mid, high channel with modulated mode and highest RF output power.
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 20GHz is $\pm 1.5\text{dB}$.
3. Environmental Conditions Temperature 23°C - 25°C
 Relative Humidity 50%
 Atmospheric Pressure 1019mbar
4. Test Date : February 28 & 29 to March 03, 2008
Tested By :Dan Corona


Standard Requirement : 47 CFR §15.247(c)

Procedures: The conducted spurious emissions were measured using a spectrum analyzer at low, mid, and hi channels. The limit was determined by attenuating 20 dB of the RF peak power output


Test Result:




Low Channel -1




Low Channel -2







Mid Channel -1




Mid Channel - 2





High Channel -1



High Channel -2



5.10 Radiated Spurious Emission < 1GHz

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.

2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.

3. Radiated Emissions Measurement Uncertainty

4. All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 1GHz (QP only @ 3m & 10m) is +5.6dB/-4.5dB (for EUTs < 0.5m X 0.5m X 0.5m).

Environmental Conditions	Temperature	23°C - 25°C
	Relative Humidity	50%
	Atmospheric Pressure	1019mbar

Test Date : February 28 & 29 to March 03, 2008

Tested By :Dan Corona

Standard Requirement : 47 CFR §15.247(c)

Procedures: Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set to transmit at mid channel. Note that setting the channel other than mid, the spurious emissions are the same.


The limit is converted from microvolts/meter to decibel microvolts/meter.

Sample Calculation: Corrected Amplitude = Raw Amplitude (dBuV/m) + ACF(dB) + Cable Loss(dB)

NOTE: All the test was done when the both radio was turn on to simulate the Worst Case.

Test Result:


Radiated Emission Plot (Receive mode)



Test Data

Frequency (MHz)	Quasi-Peak (dB μ V/m)	Antenna height (cm)	Polarity	Turntable position (deg)	Limit (dB μ V/m)	Margin (dB)
825.07	40.10	99.00	V	8.00	46.00	-5.90
419.77	36.10	250.00	V	40.00	46.00	-9.90
128.17	26.12	248.00	H	144.00	43.50	-17.38
532.50	37.53	99.00	V	42.00	46.00	-8.47
279.80	39.94	99.00	H	319.00	46.00	-6.06
418.80	31.65	250.00	V	40.00	46.00	-14.35

Radiated Emission Plot (Transmit mode)



Test Data

Frequency (MHz)	Quasi-Peak (dB μ V/m)	Antenna height (cm)	Polarity	Turntable position (deg)	Limit (dB μ V/m)	Margin (dB)
400.00	34.31	178.00	H	6.00	46.00	-11.69
128.00	30.90	244.00	H	146.00	43.50	-12.60
933.34	31.70	102.00	V	308.00	46.00	-14.30
925.34	27.35	320.00	V	138.00	46.00	-18.65

5.12 Radiated Spurious Emissions > 1GHz

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 1GHz – 20GHz is +5.6dB/-4.5dB (for EUTs < 0.5m X 0.5m X 0.5m).
4. Environmental Conditions Temperature 23°C - 25°C
 Relative Humidity 50%
 Atmospheric Pressure 1019mbar

Test Date : February 28 & 29 to March 03, 2008

Tested By :Dan Corona

Standard Requirement : 47 CFR §15.247(d)


Procedures: Equipment was setup in a semi-anechoic chamber. For measurements above 1 GHz an average measurement was taken with a 10Hz video bandwidth. The EUT was tested at low, mid and high with the highest output power. Investigated up to 10th harmonics of the operating frequency.

Sample Calculation:

EUT Field Strength = Raw Amplitude(dB μ V/m) – Amplifier Gain(dB) + Antenna Factor(dB) + Cable Loss(dB) + Filter Attenuation(dB, if used)

Test Result:

NOTE: All the test was done when the both radio was turn on to simulate the Worst Case.



@ 902.750MHz @ 3 Meter


Frequency (GHz)	Azimuth (Degrees)	Antenna Polarity (H/V)	Height (m)	Raw Amp. @ 1m (dBuV)	Pre Amp. (dB)	Ant.Corr. Factor (dB)	Cable Loss (dB)	EUT Final Field Strength (dBuV/m)	Limit @ 3m (dBuV/m)	Delta (dBuV/m)	Detector (pk/avg)
1.8055	200	V	2.0	56.82	31.98	26.4	2.16	53.40	74	-20.60	Peak
1.8055	200	H	2.0	56.63	31.98	26.4	2.16	53.21	74	-20.79	Peak
1.8055	180	V	1.5	46.53	31.98	26.4	2.16	43.11	54	-10.89	Ave
1.8055	180	H	1.5	45.37	31.98	26.4	2.16	41.95	54	-12.05	Ave
2.7083	90	V	1.6	48.53	32.08	29.8	2.72	48.97	74	-25.03	Peak
2.7083	90	H	1.6	47.05	32.08	29.8	2.72	47.49	74	-26.51	Peak
2.7083	60	V	1.3	39.24	32.08	29.8	2.72	39.68	54	-14.32	Ave
2.7083	60	H	1.3	37.53	32.08	29.8	2.72	37.97	54	-16.03	Ave
3.6110	220	V	1.4	45.26	32.37	32.5	3.44	48.83	74	-25.18	Peak
3.6110	220	H	1.4	43.32	32.37	32.5	3.44	46.89	74	-27.12	Peak
3.6110	100	V	1.5	39.57	32.37	32.5	3.44	43.14	54	-10.87	Ave
3.6110	100	H	1.5	38.36	32.37	32.5	3.44	41.93	54	-12.08	Ave

Emission was scanned up to 10GHz.

@ 915.250MHz @ 3Meter

Frequency (GHz)	Azimuth (Degrees)	Antenna Polarity (H/V)	Height (m)	Raw Amp. @ 1m (dBuV)	Pre Amp. (dB)	Ant.Corr. Factor (dB)	Cable Loss (dB)	EUT Final Field Strength (dBuV/m)	Limit @ 3m (dBuV/m)	Delta (dBuV/m)	Detector (pk/avg)
1.8305	265	V	1.9	57.86	31.98	26.4	2.16	54.44	74	-19.56	Peak
1.8305	265	V	1.9	57.12	31.98	26.4	2.16	53.70	74	-20.30	Peak
1.8305	200	H	1.5	47.62	31.98	26.4	2.16	44.20	54	-9.80	Ave
1.8305	200	H	1.5	46.46	31.98	26.4	2.16	43.04	54	-10.96	Ave
2.7458	70	V	1.3	49.62	32.08	29.8	2.72	50.06	74	-23.94	Peak
2.7458	70	V	1.3	48.14	32.08	29.8	2.72	48.58	74	-25.42	Peak
2.7458	80	H	1.1	40.62	32.08	29.8	2.72	41.06	54	-12.94	Ave
2.7458	80	H	1.1	38.62	32.08	29.8	2.72	39.06	54	-14.94	Ave
3.6610	210	V	1.5	46.35	32.37	32.5	3.44	49.92	74	-24.09	Peak
3.6610	210	V	1.5	44.51	32.37	32.5	3.44	48.08	74	-25.93	Peak
3.6610	190	H	1.0	40.66	32.37	32.5	3.44	44.23	54	-9.78	Ave
3.6610	190	H	1.0	39.47	32.37	32.5	3.44	43.04	54	-10.97	Ave


Emission was scanned up to 10GHz.



@ 927.250MHz @ 3Meter

Frequency (GHz)	Azimuth (Degrees)	Antenna Polarity (H/V)	Height (m)	Raw Amp. @ 1m (dBuV)	Pre Amp. (dB)	Ant.Corr. Factor (dB)	Cable Loss (dB)	EUT Final Field Strength (dBuV/m)	Limit @ 3m (dBuV/m)	Delta (dBuV/m)	Detector (pk/avg)
1.8545	280	V	1.7	57.12	31.98	26.4	2.16	53.70	74	-20.30	Peak
1.8545	280	V	1.7	56.33	31.98	26.4	2.16	52.91	74	-21.09	Peak
1.8545	230	H	1.2	46.83	31.98	26.4	2.16	43.41	54	-10.59	Ave
1.8545	230	H	1.2	45.67	31.98	26.4	2.16	42.25	54	-11.75	Ave
2.7818	48	V	1.6	48.83	32.08	29.8	2.72	49.27	74	-24.73	Peak
2.7818	48	V	1.6	47.35	32.08	29.8	2.72	47.79	74	-26.21	Peak
2.7818	85	H	1.3	39.54	32.08	29.8	2.72	39.98	54	-14.02	Ave
2.7818	85	H	1.3	37.83	32.08	29.8	2.72	38.27	54	-15.73	Ave
3.7090	90	V	1.2	45.56	32.37	32.5	3.44	49.13	74	-24.88	Peak
3.7090	90	V	1.2	43.72	32.37	32.5	3.44	47.29	74	-26.72	Peak
3.7090	220	H	1.5	39.87	32.37	32.5	3.44	43.44	54	-10.57	Ave
3.7090	220	H	1.5	38.68	32.37	32.5	3.44	42.25	54	-11.76	Ave

Emission was scanned up to 10GHz.



Annex A. TEST INSTRUMENT & METHOD

Annex A.i. TEST INSTRUMENTATION & GENERAL PROCEDURES

Instrument	Manufacturer	Model	CAL Due Date
Spectrum Analyzer	HP	8564E	05/01/2008
EMI Receiver	Rohde & Schwarz	ESIB 40	04/25/2008
R&S LISN	R&S	ESH2-Z5	04/24/2008
CHASE LISN	Chase	MN2050B	04/26/2008
Antenna (1 ~18GHz)	Emco	3115	08/17/2008
Antenna (30MHz~2GHz)	Sunol Sciences	JB1	10/04/2008
Chamber	Lingren	3m	09/28/2008
Pre-Amplifier(1 ~ 26GHz)	HP	8449	05/01/2008
DMM	Fluke	73III	05/01/2008
Variac	KRM	AEEC-2090	See Note
DMM	Fluke	51II	See Note
Horn Antenna (18~40GHz)	Com Power	AH-840	5/21/2008
Microwave Pre-Amp (18~40GHz)	Com Power	PA-840	5/21/2008

Note: No calibration required.

Annex A.ii. CONDUCTED EMISSIONS TEST DESCRIPTION

Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B.
2. The power supply for the EUT was fed through a $50\Omega/50\mu\text{H}$ EUT LISN, connected to filtered mains.
3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.
4. All other supporting equipments were powered separately from another main supply.

Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
3. High peaks, relative to the limit line, were then selected.
4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 KHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

Sample Calculation Example

At 20 MHz

limit = $250 \mu\text{V} = 47.96 \text{ dB}\mu\text{V}$

Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB

Q-P reading obtained directly from EMI Receiver = $40.00 \text{ dB}\mu\text{V}$
(Calibrated for system losses)

Therefore, Q-P margin = $47.96 - 40.00 = 7.96$

i.e. **7.96 dB below limit**

Annex A. iii RADIATED EMISSIONS TEST DESCRIPTION


EUT Characterisation

EUT characterisation, over the frequency range from 30MHz to 10th Harmonic, was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer / receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred, clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS).

Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.



Test Method

The following procedure was performed to determine the maximum emission axis of EUT:

1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

Final Radiated Emission Measurement

1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	Peak	100 kHz	100 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Sample Calculation Example

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

$$\text{Peak} = \text{Reading} + \text{Corrected Factor}$$

where


$$\text{Corr. Factor} = \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain (if any)}$$

And the average value is

$$\text{Average} = \text{Peak Value} + \text{Duty Factor} \text{ or} \\ \text{Set RBW} = 1\text{MHz}, \text{VBW} = 10\text{Hz}.$$

Note :

If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function.



Annex B EUT AND TEST SETUP PHOTOGRAPHS

Please see the attachment

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT


EUT TEST CONDITIONS

Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION


The following is a description of supporting equipment and details of cables used with the EUT.


Equipment Description (Including Brand Name)	Model & Serial Number	Cable Description (List Length, Type & Purpose)
PC Laptop / DELL	Latitude DS520	USB Cable , 1meter From PC Laptop to EUT

Block Configuration Diagram for Radiated Emission



Block Configuration Diagram for Conducted Emission






Annex C.ii. EUT OPERATING CONDITIONS

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
Emissions Testing	The EUT was controlled via PC Laptop using Agency Testing Program provided by applicant.
Others Testing	The EUT was controlled via PC Laptop using Agency Testing Program provided by applicant.



Annex D USER MANUAL, BLOCK & CIRCUIT DIAGRAM

Please see attachment