

MPE CALCULATION

RF Exposure Requirements:	47 CFR §1.1307(b)
RF Radiation Exposure Limits:	47 CFR §1.1310
RF Radiation Exposure Guidelines:	FCC OST/OET Bulletin Number 65
EUT Frequency Band:	2402-2480 MHz, 2412 - 2462 MHz; 5180 - 5825MHz
Limits for General Population/Uncontrolled Exposure in the band of:	1500 - 100,000 MHz
Power Density Limit:	1 mW / cm ² ;

Equation: $S = PG / 4\pi R^2$ or $R = \sqrt{PG / 4\pi S}$

Where, S = Power Density

P = Power Input to Antenna

G = Antenna Gain

R = distance to the center of radiated antenna

Prediction distance 20cm

BT (2402-2480MHz): Power = 7.76 dBm, antenna gain = 3.81 dBi, Power density = 0.00286 mW/cm²

WLAN(2412-2462MHz): Power = 16.37 dBm , antenna gain = 3.81 dBi , Power density = 0.0207 mW/cm²

WLAN(5180-5825MHz): Power = 16.28 dBm, antenna gain = 5.0 dBi, Power density = 0.0267 mW/cm²

Maximum MPE is 0.0267 mW/cm², which is less than 1 .

The Above Result had shown that Device complied with MPE requirement.

Completed By : David Zhang

Date : Dec 14, 2011