










Test specification:	Plane_Body_Middle_HT20_2437_Back Touch			
Environ Conditions:	Temp(oC):	21.6	Result:	Pass
	Humidity(%):	43.1		
	Atmospheric(mPa):	1028.6		
Mains Power:	N/A			
Test Date:	07/06/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	2437.000000			
Relative permittivity (real part)	52.72			
Conductivity (S/m)	1.94			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.26			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=5mm, dy=5mm, dz=5mm			
Zoom Scan Size	30x30x34 mm			
Measurement Drifts (%)	2.21			
Highest Extrapolated SAR (W/Kg)	0.3859			
SAR 1g (W/Kg)	0.1688			
Peak SAR Location	5mm(x),72mm(y),4mm(z)			
				
SURFACE SAR		VOLUME SAR		
				
3D View Plot				


Test specification:	Plane_Body_High_HT20_2462_Back Touch			
Environ Conditions:	Temp(oC):	21.6	Result:	Pass
	Humidity(%):	43.1		
	Atmospheric(mPa):	1028.6		
Mains Power:	N/A			
Test Date:	07/06/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	2462.000000			
Relative permittivity (real part)	52.75			
Conductivity (S/m)	1.91			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.26			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=5mm, dy=5mm, dz=5mm			
Zoom Scan Size	30x30x34 mm			
Measurement Drifts (%)	0.59			
Highest Extrapolated SAR (W/Kg)	0.1904			
SAR 1g (W/Kg)	0.1560			
Peak SAR Location	5mm(x),-64mm(y),4mm(z)			
				
SURFACE SAR		VOLUME SAR		
				
3D View Plot				

Test specification:	Plane_Body_Middle_HT20_2437_Left Touch								
Environ Conditions:	Temp(oC):	21.6	Result:	Pass					
	Humidity(%):	43.1							
	Atmospheric(mPa):	1028.6							
Mains Power:	N/A								
Test Date:	07/06/2017								
Tested by:	Arthur Tie								
Remarks:									
Frequency (MHz)	2437.000000								
Relative permittivity (real part)	52.72								
Conductivity (S/m)	1.94								
Transmission Duty Factor	1.0								
Probe SN	2715_EPG0259								
Conversion Factor (dB)	3.26								
Area Scan Resolution	8 mm								
Zoom Scan Resolution	dx=5mm, dy=5mm, dz=5mm								
Zoom Scan Size	30x30x34 mm								
Measurement Drifts (%)	-0.82								
Highest Extrapolated SAR (W/Kg)	0.3323								
SAR 1g (W/Kg)	0.1230								
Peak SAR Location	5mm(x),-64mm(y),4mm(z)								
SAR Visualization Graphical Interface Surface Radiation Intensity Color Scale (W/Kg) 0.142955 0.135502 0.128770 0.122038 0.115306 0.108573 0.101841 0.095109 0.088377 0.081645 0.074913 0.068181 0.061449 0.054717 0.047985 0.041253 0.034521 0.027789 0.021057 0.014325 0.007593 0.000861 2-Data Control OK Upper Cut OK Lower Cut OK Cancel Zoom In/Out 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 X (mm) Y (mm) SAR Visualization Graphical Interface Volume Radiation Intensity Color Scale (W/Kg) 0.332325 0.327089 0.321853 0.316617 0.311381 0.306145 0.300909 0.295673 0.290437 0.285201 0.279965 0.274729 0.269493 0.264257 0.259021 0.253785 0.248549 0.243313 0.238077 0.232841 0.227605 0.222369 0.217133 0.211897 0.206661 0.201425 0.196189 0.190953 0.185717 0.180481 0.175245 0.169979 0.164743 0.159507 0.154271 0.149035 0.143799 0.138563 0.133327 0.128091 0.122855 0.117619 0.112383 0.107147 0.101911 0.096675 0.091439 0.086203 0.080967 0.075731 0.070495 0.065259 0.059973 0.054737 0.049501 0.044265 0.039029 0.033793 0.028557 0.023321 0.018085 0.012849 0.007613 0.002377 0.000000 2-Data Control OK Upper Cut OK Lower Cut OK Cancel Zoom In/Out 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 X (mm) Y (mm) Z (mm) SURFACE SAR VOLUME SAR <tr><td colspan="5"> </td></tr>									


Test specification:	Plane_Body_Middle_HT40_2437_Left Touch			
Environ Conditions:	Temp(oC):	21.6	Result:	Pass
	Humidity(%):	43.1		
	Atmospheric(mPa):	1028.6		
Mains Power:	N/A			
Test Date:	07/06/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	2437.000000			
Relative permittivity (real part)	52.72			
Conductivity (S/m)	1.94			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.26			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=5mm, dy=5mm, dz=5mm			
Zoom Scan Size	30x30x34 mm			
Measurement Drifts (%)	-3.26			
Highest Extrapolated SAR (W/Kg)	0.3864			
SAR 1g (W/Kg)	0.1120			
Peak SAR Location	21mm(x),-80mm(y),4mm(z)			
				
SURFACE SAR		VOLUME SAR		
				
3D View Plot				

802.11-a/n/ac 5G


Test specification:	Plane_Body_Low_802.11a_5180_Back Touch			
Environ Conditions:	Temp(oC):	22.1	Result:	Pass
	Humidity (%):	46		
	Atmospheric(mPa):	1157.5		
Mains Power:	N/A			
Test Date:	07/06/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5180.000000			
Relative permittivity (real part)	46.27			
Conductivity (S/m)	5.55			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	-0.60			
Highest Extrapolated SAR (W/Kg)	0.9939			
SAR 1g (W/Kg)	0.5619			
Peak SAR Location	21mm(x),-64mm(y),2mm(z)			



SURFACE SAR





VOLUME SAR





3D View Plot

Test specification:	Plane_Body_Middle_802.11a_5200_Back Touch			
Environ Conditions:	Temp(oC):	22.1	Result:	Pass
	Humidity (%):	46		
	Atmospheric(mPa):	1157.5		
Mains Power:	N/A			
Test Date:	07/06/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5200.000000			
Relative permittivity (real part)	46.18			
Conductivity (S/m)	5.56			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	3.40			
Highest Extrapolated SAR (W/Kg)	0.6690			
SAR 1g (W/Kg)	0.5533			
Peak SAR Location	-3mm(x),32mm(y),2mm(z)			




3D View Plot

Test specification:	Plane_Body_High_802.11a_5240_Back Touch			
Environ Conditions:	Temp(oC):	21.7	Result:	Pass
	Humidity (%):	45		
	Atmospheric(mPa):	1193.1		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5240.000000			
Relative permittivity (real part)	46.18			
Conductivity (S/m)	5.56			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	1.44			
Highest Extrapolated SAR (W/Kg)	0.7365			
SAR 1g (W/Kg)	0.5681			
Peak SAR Location	-27mm(x),-104mm(y),2mm(z)			




3D View Plot


Test specification:	Plane_Body_Middle_802.11a_5180_Left Touch			
Environ Conditions:	Temp(oC):	22.3	Result:	Pass
	Humidity (%):	49		
	Atmospheric(mPa):	1201.6		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5180.000000			
Relative permittivity (real part)	46.18			
Conductivity (S/m)	5.56			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	4.28			
Highest Extrapolated SAR (W/Kg)	0.6684			
SAR 1g (W/Kg)	0.4693			
Peak SAR Location	-35mm(x),80mm(y),2mm(z)			






SURFACE SAR



VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Middle_802.11a_5200_Left Touch								
Environ Conditions:	Temp(oC):	22.3	Result:	Pass					
	Humidity (%):	49							
	Atmospheric(mPa):	1201.6							
Mains Power:	N/A								
Test Date:	07/11/2017								
Tested by:	Arthur Tie								
Remarks:									
Frequency (MHz)	5200.000000								
Relative permittivity (real part)	46.18								
Conductivity (S/m)	5.56								
Transmission Duty Factor	1.0								
Probe SN	2715_EPGO259								
Conversion Factor (dB)	3.01								
Area Scan Resolution	8 mm								
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm								
Zoom Scan Size	24x24x24 mm								
Measurement Drifts (%)	4.28								
Highest Extrapolated SAR (W/Kg)	0.6684								
SAR 1g (W/Kg)	0.4947								
Peak SAR Location	-35mm(x),80mm(y),2mm(z)								
									
SURFACE SAR		VOLUME SAR							
									
3D View Plot									

Test specification:	Plane_Body_Middle_802.11a_5240_Left Touch			
Environ Conditions:	Temp(oC):	22.3	Result:	Pass
	Humidity (%):	49		
	Atmospheric(mPa):	1201.6		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5240.000000			
Relative permittivity (real part)	46.18			
Conductivity (S/m)	5.56			
Transmission Duty Factor	1.0			
Probe SN	2715_EPGO259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	4.28			
Highest Extrapolated SAR (W/Kg)	0.7684			
SAR 1g (W/Kg)	0.4581			
Peak SAR Location	-35mm(x),80mm(y),2mm(z)			
SAR Visualization Graphical Interface Surface Radiation Intensity Color Scale (W/Kg) 0.449858 0.190133 0.661770 0.610595 0.670285 0.531847 0.481788 0.445066 0.469073 0.362093 0.287820 0.270885 0.230242 0.192239 0.151106 0.103713 Z-Data Control At Upper Cut Zoom In/Out Z = 2.0 mm Source Data... Save Cancel Surface Radiation Intensity 150 100 50 0 -50 -100 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120 -150 150 120 90 60 30 0 -30 -60 -90 -120 -150 Y 150 100 50 0 -50 -100 -150 X 150 120 90 60 30 0 -30 -60 -90 -120				


Test specification:	Plane_Body_Low_802.11a_5260_Back Touch			
Environ Conditions:	Temp(oC):	21.3	Result:	Pass
	Humidity(%):	48		
	Atmospheric(mPa):	1102.2		
Mains Power:	N/A			
Test Date:	07/12/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5260.000000			
Relative permittivity (real part)	46.12			
Conductivity (S/m)	5.63			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	3.09			
Highest Extrapolated SAR (W/Kg)	1.1138			
SAR 1g (W/Kg)	0.5412			
Peak SAR Location	21mm(x),-64mm(y),2mm(z)			






SURFACE SAR






VOLUME SAR




3D View Plot

Test specification:	Plane_Body_Middle_802.11a_5280_Back Touch			
Environ Conditions:	Temp(oC):	22.1	Result:	Pass
	Humidity(%):	46		
	Atmospheric(mPa):	1157.5		
Mains Power:	N/A			
Test Date:	07/06/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5280.000000			
Relative permittivity (real part)	46.09			
Conductivity (S/m)	5.66			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	2.31			
Highest Extrapolated SAR (W/Kg)	1.1330			
SAR 1g (W/Kg)	0.5229			
Peak SAR Location	21mm(x),-64mm(y),2mm(z)			
				
SURFACE SAR		VOLUME SAR		
				
3D View Plot				


Test specification:	Plane_Body_High_802.11a_5320_Back Touch			
Environ Conditions:	Temp(oC):	22.1	Result:	Pass
	Humidity(%):	46		
	Atmospheric(mPa):	1157.5		
Mains Power:	N/A			
Test Date:	07/06/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5320.000000			
Relative permittivity (real part)	46.03			
Conductivity (S/m)	5.74			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.05			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	1.85			
Highest Extrapolated SAR (W/Kg)	1.1990			
SAR 1g (W/Kg)	0.4860			
Peak SAR Location	13mm(x),-56mm(y),2mm(z)			
				
SURFACE SAR		VOLUME SAR		
				
3D View Plot				

Test specification:	Plane_Body_Middle_802.11a_5260_Left Touch			
Environ Conditions:	Temp(oC):	21.7	Result:	Pass
	Humidity(%):	45		
	Atmospheric(mPa):	1193.1		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				


Frequency (MHz)	5260.000000
Relative permittivity (real part)	46.03
Conductivity (S/m)	5.74
Transmission Duty Factor	1.0
Probe SN	2715_EPG0259
Conversion Factor (dB)	3.01
Area Scan Resolution	8 mm
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm
Zoom Scan Size	24x24x24 mm
Measurement Drifts (%)	0.29
Highest Extrapolated SAR (W/Kg)	0.7699
SAR 1g (W/Kg)	0.4297
Peak SAR Location	-3mm(x),-80mm(y),2mm(z)



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Middle_802.11a_5280_Left Touch		
Environ Conditions:	Temp(oC):	21.7	Result: Pass
	Humidity(%):	45	
	Atmospheric(mPa):	1193.1	
Mains Power:	N/A		
Test Date:	07/11/2017		
Tested by:	Arthur Tie		
Remarks:			
Frequency (MHz)	5280.000000		
Relative permittivity (real part)	46.03		
Conductivity (S/m)	5.74		
Transmission Duty Factor	1.0		
Probe SN	2715_EPG0259		
Conversion Factor (dB)	3.01		
Area Scan Resolution	8 mm		
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm		
Zoom Scan Size	24x24x24 mm		
Measurement Drifts (%)	0.29		
Highest Extrapolated SAR (W/Kg)	0.7699		
SAR 1g (W/Kg)	0.4244		
Peak SAR Location	-3mm(x),-80mm(y),2mm(z)		



SURFACE SAR




VOLUME SAR




3D View Plot

Test specification:	Plane_Body_Middle_802.11a_5320_Left Touch			
Environ Conditions:	Temp(oC):	21.7	Result:	Pass
	Humidity(%):	45		
	Atmospheric(mPa):	1193.1		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				


Frequency (MHz)	5280.000000
Relative permittivity (real part)	46.03
Conductivity (S/m)	5.74
Transmission Duty Factor	1.0
Probe SN	2715_EPG0259
Conversion Factor (dB)	3.01
Area Scan Resolution	8 mm
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm
Zoom Scan Size	24x24x24 mm
Measurement Drifts (%)	0.29
Highest Extrapolated SAR (W/Kg)	0.8655
SAR 1g (W/Kg)	0.3809
Peak SAR Location	-3mm(x),-80mm(y),2mm(z)



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Low_802.11a_5500_Back Touch			
Environ Conditions:	Temp(oC):	22.3	Result:	Pass
	Humidity(%):	49		
	Atmospheric(mPa):	1201.6		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5500.000000			
Relative permittivity (real part)	46.03			
Conductivity (S/m)	5.74			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.05			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	0.95			
Highest Extrapolated SAR (W/Kg)	0.7298			
SAR 1g (W/Kg)	0.5016			
Peak SAR Location	5mm(x),-40mm(y),2mm(z)			



SURFACE SAR





VOLUME SAR




3D View Plot

Test specification:	Plane_Body_Middle_802.11a_5600_Back Touch			
Environ Conditions:	Temp(oC):	22.9	Result:	Pass
	Humidity (%):	50		
	Atmospheric(mPa):	1162.3		
Mains Power:	N/A			
Test Date:	09/22/2016			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5600.000000			
Relative permittivity (real part)	45.96			
Conductivity (S/m)	5.77			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.21			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	3.34			
Highest Extrapolated SAR (W/Kg)	1.3044			
SAR 1g (W/Kg)	0.4730			
Peak SAR Location	13mm(x),-64mm(y),2mm(z)			




3D View Plot


Test specification:	Plane_Body_High_802.11a_5700_Back Touch			
Environ Conditions:	Temp(oC):	22.9	Result:	Pass
	Humidity (%):	50		
	Atmospheric(mPa):	1162.3		
Mains Power:	N/A			
Test Date:	09/22/2016			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5700.000000			
Relative permittivity (real part)	45.16			
Conductivity (S/m)	6.04			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.21			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	2.12			
Highest Extrapolated SAR (W/Kg)	1.2277			
SAR 1g (W/Kg)	0.4518			
Peak SAR Location	13mm(x),-64mm(y),2mm(z)			



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Middle_802.11a_5500_Left Touch			
Environ Conditions:	Temp(oC):	22.9	Result:	Pass
	Humidity (%):	50		
	Atmospheric(mPa):	1162.3		
Mains Power:	N/A			
Test Date:	09/22/2016			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5500.000000			
Relative permittivity (real part)	44.97			
Conductivity (S/m)	6.17			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.21			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	0.50			
Highest Extrapolated SAR (W/Kg)	1.4057			
SAR 1g (W/Kg)	0.4207			
Peak SAR Location	13mm(x),-64mm(y),2mm(z)			
SAR Visualization Graphical Interface Surface: Relative Intensity Color Scale (W/Kg) 0.526237 0.437033 0.489743 0.670761 0.411763 0.283714 0.155645 0.135247 0.227448 0.267043 0.248221 0.211853 0.188463 0.154454 0.122658 0.097257 Z-Data Control Axis: X, Y, Z mm Zoom: 2.00 mm Save Data Cancel 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X 150 100 50 0 -50 -100 -150 150 100 50 0 -50 -100 -150 Y X				




Test specification:	Plane_Body_Middle_802.11a_5700_Left Touch		
Environ Conditions:	Temp(oC):	22.9	Result: Pass
	Humidity (%):	50	
	Atmospheric(mPa):	1162.3	
Mains Power:	N/A		
Test Date:	09/22/2016		
Tested by:	Arthur Tie		
Remarks:			
Frequency (MHz)	5700.000000		
Relative permittivity (real part)	44.97		
Conductivity (S/m)	6.17		
Transmission Duty Factor	1.0		
Probe SN	2715_EPG0259		
Conversion Factor (dB)	3.21		
Area Scan Resolution	8 mm		
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm		
Zoom Scan Size	24x24x24 mm		
Measurement Drifts (%)	0.50		
Highest Extrapolated SAR (W/Kg)	1.4057		
SAR 1g (W/Kg)	0.4518		
Peak SAR Location	13mm(x), -64mm(y), 2mm(z)		



SURFACE SAR




VOLUME SAR




3D View Plot

Test specification:	Plane_Body_Low_VHT20_5180_Back Touch			
Environ Conditions:	Temp(oC):	21.7	Result:	Pass
	Humidity(%):	45		
	Atmospheric(mPa):	1193.1		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5180.000000			
Relative permittivity (real part)	44.97			
Conductivity (S/m)	6.17			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	-0.73			
Highest Extrapolated SAR (W/Kg)	0.9794			
SAR 1g (W/Kg)	0.5134			
Peak SAR Location	-3mm(x),-80mm(y),2mm(z)			
SAR Visualization Graphical Interface Surface Radiation Intensity Color Scale (W/Kg) 0.000000				


Test specification:	Plane_Body_Middle_VHT20_5200_Back Touch		
Environ Conditions:	Temp(oC):	22.3	Result: Pass
	Humidity(%):	49	
	Atmospheric(mPa):	1201.6	
Mains Power:	N/A		
Test Date:	07/11/2017		
Tested by:	Arthur Tie		
Remarks:			
Frequency (MHz)	5200.000000		
Relative permittivity (real part)	44.97		
Conductivity (S/m)	6.17		
Transmission Duty Factor	1.0		
Probe SN	2715_EPG0259		
Conversion Factor (dB)	3.01		
Area Scan Resolution	8 mm		
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm		
Zoom Scan Size	24x24x24 mm		
Measurement Drifts (%)	3.42		
Highest Extrapolated SAR (W/Kg)	0.9129		
SAR 1g (W/Kg)	0.5183		
Peak SAR Location	-3mm(x),-88mm(y),2mm(z)		






SURFACE SAR



VOLUME SAR




3D View Plot


Test specification:	Plane_Body_High_VHT20_5240_Back Touch			
Environ Conditions:	Temp(oC):	21.3	Result:	Pass
	Humidity(%):	48		
	Atmospheric(mPa):	1102.2		
Mains Power:	N/A			
Test Date:	07/12/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5240.000000			
Relative permittivity (real part)	44.66			
Conductivity (S/m)	6.43			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	2.48			
Highest Extrapolated SAR (W/Kg)	1.5322			
SAR 1g (W/Kg)	0.5370			
Peak SAR Location	13mm(x),-64mm(y),2mm(z)			
				
SURFACE SAR		VOLUME SAR		
				
3D View Plot				

Test specification:	Plane_Body_Middle_VHT20_5180_Left Touch			
Environ Conditions:	Temp(oC):	21.7	Result:	Pass
	Humidity(%):	45		
	Atmospheric(mPa):	1193.1		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				


Frequency (MHz)	5q80.000000
Relative permittivity (real part)	44.50
Conductivity (S/m)	6.43
Transmission Duty Factor	1.0
Probe SN	2715_EPGO259
Conversion Factor (dB)	3.01
Area Scan Resolution	8 mm
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm
Zoom Scan Size	24x24x24 mm
Measurement Drifts (%)	4.95
Highest Extrapolated SAR (W/Kg)	1.2684
SAR 1g (W/Kg)	0.4535
Peak SAR Location	13mm(x),-64mm(y),2mm(z)



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Middle_VHT20_5200_Left Touch		
Environ Conditions:	Temp(oC):	21.7	Result: Pass
	Humidity(%):	45	
	Atmospheric(mPa):	1193.1	
Mains Power:	N/A		
Test Date:	07/11/2017		
Tested by:	Arthur Tie		
Remarks:			
Frequency (MHz)	5200.000000		
Relative permittivity (real part)	44.50		
Conductivity (S/m)	6.43		
Transmission Duty Factor	1.0		
Probe SN	2715_EPG0259		
Conversion Factor (dB)	3.01		
Area Scan Resolution	8 mm		
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm		
Zoom Scan Size	24x24x24 mm		
Measurement Drifts (%)	4.95		
Highest Extrapolated SAR (W/Kg)	1.2684		
SAR 1g (W/Kg)	0.4756		
Peak SAR Location	13mm(x),-64mm(y),2mm(z)		



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Middle_VHT20_5240_Left Touch			
Environ Conditions:	Temp(oC):	21.7	Result:	Pass
	Humidity(%):	45		
	Atmospheric(mPa):	1193.1		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5240.000000			
Relative permittivity (real part)	44.50			
Conductivity (S/m)	6.43			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	4.95			
Highest Extrapolated SAR (W/Kg)	1.2684			
SAR 1g (W/Kg)	0.4356			
Peak SAR Location	13mm(x),-64mm(y),2mm(z)			



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Low_VHT20_5260_Back Touch		
Environ Conditions:	Temp(oC):	21.7	Result: Pass
	Humidity(%):	45	
	Atmospheric(mPa):	1193.1	
Mains Power:	N/A		
Test Date:	07/11/2017		
Tested by:	Arthur Tie		
Remarks:			
Frequency (MHz)	5260.000000		
Relative permittivity (real part)	44.36		
Conductivity (S/m)	6.43		
Transmission Duty Factor	1.0		
Probe SN	2715_EPG0259		
Conversion Factor (dB)	3.01		
Area Scan Resolution	8 mm		
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm		
Zoom Scan Size	24x24x24 mm		
Measurement Drifts (%)	0.22		
Highest Extrapolated SAR (W/Kg)	1.2363		
SAR 1g (W/Kg)	0.5266		
Peak SAR Location	13mm(x), -64mm(y), 2mm(z)		



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Middle_VHT20_5280_Back Touch			
Environ Conditions:	Temp(oC):	21.7	Result:	Pass
	Humidity(%):	45		
	Atmospheric(mPa):	1193.1		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5280.000000			
Relative permittivity (real part)	44.36			
Conductivity (S/m)	6.43			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	-0.61			
Highest Extrapolated SAR (W/Kg)	0.9697			
SAR 1g (W/Kg)	0.5337			
Peak SAR Location	-27mm(x),72mm(y),2mm(z)			



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_High_VHT20_5320_Back Touch			
Environ Conditions:	Temp(oC):	22.3	Result:	Pass
	Humidity(%):	49		
	Atmospheric(mPa):	1201.6		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5320.000000			
Relative permittivity (real part)	44.36			
Conductivity (S/m)	6.43			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.05			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	3.60			
Highest Extrapolated SAR (W/Kg)	1.5172			
SAR 1g (W/Kg)	0.4868			
Peak SAR Location	29mm(x),-72mm(y),2mm(z)			



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Middle_VHT20_5260_Left Touch		
Environ Conditions:	Temp(oC):	21.7	Result: Pass
	Humidity(%):	45	
	Atmospheric(mPa):	1193.1	
Mains Power:	N/A		
Test Date:	07/11/2017		
Tested by:	Arthur Tie		
Remarks:			
Frequency (MHz)	5260.000000		
Relative permittivity (real part)	44.17		
Conductivity (S/m)	6.48		
Transmission Duty Factor	1.0		
Probe SN	2715_EPG0259		
Conversion Factor (dB)	3.01		
Area Scan Resolution	8 mm		
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm		
Zoom Scan Size	24x24x24 mm		
Measurement Drifts (%)	-4.19		
Highest Extrapolated SAR (W/Kg)	1.1900		
SAR 1g (W/Kg)	0.4065		
Peak SAR Location	13mm(x),-64mm(y),2mm(z)		



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Middle_VHT20_5280_Left Touch			
Environ Conditions:	Temp(oC):	21.7	Result:	Pass
	Humidity(%):	45		
	Atmospheric(mPa):	1193.1		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5280.000000			
Relative permittivity (real part)	44.17			
Conductivity (S/m)	6.48			
Transmission Duty Factor	1.0			
Probe SN	2715_EPGO259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	-4.19			
Highest Extrapolated SAR (W/Kg)	1.1900			
SAR 1g (W/Kg)	0.4935			
Peak SAR Location	13mm(x),-64mm(y),2mm(z)			



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Middle_VHT20_5320_Left Touch		
Environ Conditions:	Temp(oC):	21.7	Result: Pass
	Humidity(%):	45	
	Atmospheric(mPa):	1193.1	
Mains Power:	N/A		
Test Date:	07/11/2017		
Tested by:	Arthur Tie		
Remarks:			
Frequency (MHz)	5320.000000		
Relative permittivity (real part)	44.17		
Conductivity (S/m)	6.48		
Transmission Duty Factor	1.0		
Probe SN	2715_EPG0259		
Conversion Factor (dB)	3.01		
Area Scan Resolution	8 mm		
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm		
Zoom Scan Size	24x24x24 mm		
Measurement Drifts (%)	-4.19		
Highest Extrapolated SAR (W/Kg)	1.1900		
SAR 1g (W/Kg)	0.3643		
Peak SAR Location	13mm(x),-64mm(y),2mm(z)		



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Low_VHT20_5500_Back Touch			
Environ Conditions:	Temp(oC):	21.7	Result:	Pass
	Humidity(%):	45		
	Atmospheric(mPa):	1193.1		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5500.000000			
Relative permittivity (real part)	46.18			
Conductivity (S/m)	5.56			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.05			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	-2.58			
Highest Extrapolated SAR (W/Kg)	0.8143			
SAR 1g (W/Kg)	0.5199			
Peak SAR Location	21mm(x),-64mm(y),2mm(z)			



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Middle_VHT20_5600_Back Touch		
Environ Conditions:	Temp(oC):	23.5	Result: Pass
	Humidity (%):	47	
	Atmospheric(mPa):	1185.7	
Mains Power:	N/A		
Test Date:	09/28/2016		
Tested by:	Arthur Tie		
Remarks:			
Frequency (MHz)	5600.000000		
Relative permittivity (real part)	46.18		
Conductivity (S/m)	5.56		
Transmission Duty Factor	1.0		
Probe SN	2715_EPG0259		
Conversion Factor (dB)	3.21		
Area Scan Resolution	8 mm		
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm		
Zoom Scan Size	24x24x24 mm		
Measurement Drifts (%)	-2.44		
Highest Extrapolated SAR (W/Kg)	0.9045		
SAR 1g (W/Kg)	0.5095		
Peak SAR Location	-3mm(x),-24mm(y),2mm(z)		



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_High_VHT20_5700_Back Touch			
Environ Conditions:	Temp(oC):	22.3	Result:	Pass
	Humidity(%):	49		
	Atmospheric(mPa):	1201.6		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5700.000000			
Relative permittivity (real part)	46.18			
Conductivity (S/m)	5.56			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.21			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	0.17			
Highest Extrapolated SAR (W/Kg)	0.9874			
SAR 1g (W/Kg)	0.4712			
Peak SAR Location	5mm(x),-40mm(y),2mm(z)			



SURFACE SAR




VOLUME SAR




3D View Plot

Test specification:	Plane_Body_Middle_VHT20_5500_Left Touch			
Environ Conditions:	Temp(oC):	21.2	Result:	Pass
	Humidity (%):	52		
	Atmospheric(mPa):	1092.4		
Mains Power:	N/A			
Test Date:	07/122017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5500.000000			
Relative permittivity (real part)	46.03			
Conductivity (S/m)	5.74			
Transmission Duty Factor	1.0			
Probe SN	2715_EPGO259			
Conversion Factor (dB)	3.21			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	2.83			
Highest Extrapolated SAR (W/Kg)	0.9989			
SAR 1g (W/Kg)	0.3757			
Peak SAR Location	21mm(x),-64mm(y),2mm(z)			
SAR Visualization Graphical Interface Surface Reduced Intensity Color Scale (W/Kg) 0.490109 0.493833 0.441217 0.417777 0.381034 0.338980 0.327834 0.285968 0.250542 0.247865 0.213830 0.187085 0.159169 0.144013 0.098867 0.074421 Z-Data Control Zoom In/Out Zoom Out Zoom Reset 7 - 2.0 mm Save Data Save Cancel Surface SAR SAR Visualization Graphical Interface Volume Reduced Intensity Color Scale (W/Kg) 0.107071 0.105812 0.103128 0.101851 0.102845 0.101010 0.100874 0.100406 0.100866 0.101718 0.101800 0.101834 0.102116 0.100746 0.100771 0.111302 Z-Data Control Zoom In/Out Zoom Out Zoom Reset 7 - 2.0 mm Save Data Save Cancel Volume SAR				
3D View Plot				


Test specification:	Plane_Body_Middle_VHT20_5600_Left Touch			
Environ Conditions:	Temp(oC):	21.2	Result:	Pass
	Humidity (%):	52		
	Atmospheric(mPa):	1092.4		
Mains Power:	N/A			
Test Date:	07/122017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5600.000000			
Relative permittivity (real part)	46.03			
Conductivity (S/m)	5.74			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.21			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	2.83			
Highest Extrapolated SAR (W/Kg)	0.9989			
SAR 1g (W/Kg)	0.3652			
Peak SAR Location	21mm(x),-64mm(y),2mm(z)			



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Middle_VHT20_5700_Left Touch			
Environ Conditions:	Temp(oC):	21.2	Result:	Pass
	Humidity (%):	52		
	Atmospheric(mPa):	1092.4		
Mains Power:	N/A			
Test Date:	07/122017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5700.000000			
Relative permittivity (real part)	46.03			
Conductivity (S/m)	5.74			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.21			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	2.83			
Highest Extrapolated SAR (W/Kg)	0.9989			
SAR 1g (W/Kg)	0.3234			
Peak SAR Location	21mm(x),-64mm(y),2mm(z)			



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Middle_VHT20_5785_Back Touch			
Environ Conditions:	Temp(oC):	23.5	Result:	Pass
	Humidity (%):	47		
	Atmospheric(mPa):	1185.7		
Mains Power:	N/A			
Test Date:	07/122017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5785.000000			
Relative permittivity (real part)	46.03			
Conductivity (S/m)	5.74			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	2.99			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	0.34			
Highest Extrapolated SAR (W/Kg)	0.9228			
SAR 1g (W/Kg)	0.3464			
Peak SAR Location	-19mm(x),-72mm(y),2mm(z)			








SURFACE SAR



VOLUME SAR




3D View Plot

Test specification:	Plane_Body_Middle_VHT20_5785_Left Touch								
Environ Conditions:	Temp(oC):	22.3	Result:	Pass					
	Humidity(%):	49							
	Atmospheric(mPa):	1201.6							
Mains Power:	N/A								
Test Date:	07/11/2017								
Tested by:	Arthur Tie								
Remarks:									
Frequency (MHz)	5785.000000								
Relative permittivity (real part)	46.03								
Conductivity (S/m)	5.74								
Transmission Duty Factor	1.0								
Probe SN	2715_EPGO259								
Conversion Factor (dB)	2.99								
Area Scan Resolution	8 mm								
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm								
Zoom Scan Size	24x24x24 mm								
Measurement Drifts (%)	-0.24								
Highest Extrapolated SAR (W/Kg)	0.8394								
SAR 1g (W/Kg)	0.2640								
Peak SAR Location	5mm(x),-40mm(y),2mm(z)								
SAR Visualization Graphical Interface Color Scale (W/Kg) 0.429682 0.387105 0.479386 0.448795 0.416429 0.383113 0.359789 0.331487 0.302789 0.274784 0.249254 0.219219 0.189463 0.161567 0.132271 0.104284 Z-Data Control Min:Max:Cut 2 - 2.0 mm Source:Cut:off Save Cancel Surface Radiation Intensity Zoom In/Out  150 120 90 60 30 0 30 60 90 120 150 Y (mm) X (mm) SAR Visualization Graphical Interface Color Scale (W/Kg) 0.529142 0.453545 0.387105 0.421544 0.359789 0.302789 0.249254 0.189463 0.161567 0.132271 0.104284 Z-Data Control Min:Max:Cut 2 - 2.0 mm Source:Cut:off Save Cancel Volume Radiation Intensity Zoom In/Out  150 120 90 60 30 0 30 60 90 120 150 Y (mm) X (mm) SURFACE SAR VOLUME SAR <tr><td colspan="5">  3D View Plot </td></tr>					 3D View Plot				
 3D View Plot									


802.11-VHT40

Test specification:	Plane_Body_Low_VHT40_5190_Back Touch			
Environ Conditions:	Temp(oC):	21.2	Result:	Pass
	Humidity (%):	52		
	Atmospheric(mPa):	1092.4		
Mains Power:	N/A			
Test Date:	07/122017			
Tested by:	Arthur Tie			
Remarks:				


Frequency (MHz)	5190.000000
Relative permittivity (real part)	44.97
Conductivity (S/m)	6.17
Transmission Duty Factor	1.0
Probe SN	2715_EPGO259
Conversion Factor (dB)	3.01
Area Scan Resolution	8 mm
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm
Zoom Scan Size	24x24x24 mm
Measurement Drifts (%)	-2.22
Highest Extrapolated SAR (W/Kg)	1.1910
SAR 1g (W/Kg)	0.3515
Peak SAR Location	13mm(x),-64mm(y),2mm(z)








SURFACE SAR




VOLUME SAR




3D View Plot

Test specification:	Plane_Body_High_VHT40_5230_Back Touch								
Environ Conditions:	Temp(oC):	23.5	Result:	Pass					
	Humidity (%):	47							
	Atmospheric(mPa):	1185.7							
Mains Power:	N/A								
Test Date:	07/122017								
Tested by:	Arthur Tie								
Remarks:									
Frequency (MHz)	5230.000000								
Relative permittivity (real part)	44.97								
Conductivity (S/m)	6.17								
Transmission Duty Factor	1.0								
Probe SN	2715_EPGO259								
Conversion Factor (dB)	3.01								
Area Scan Resolution	8 mm								
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm								
Zoom Scan Size	24x24x24 mm								
Measurement Drifts (%)	-2.11								
Highest Extrapolated SAR (W/Kg)	0.7096								
SAR 1g (W/Kg)	0.3629								
Peak SAR Location	-3mm(x),-80mm(y),2mm(z)								
SAR Visualization Graphical Interface Color Scale (W/Kg) 0.523000 0.456000 0.477000 0.468000 0.471000 0.383000 0.382000 0.337000 0.329000 0.281000 0.263000 0.255000 0.191000 0.169000 0.141000 0.113000 Z-Data Control XY-Layout: Full Z: 2.0 mm Source: Full on Save Cancel Surface: Reduced Intensity Zoom In/Out  25 X (mm) 25 Y (mm) SAR Visualization Graphical Interface Color Scale (W/Kg) 0.523000 0.456000 0.477000 0.468000 0.471000 0.383000 0.382000 0.337000 0.329000 0.281000 0.263000 0.255000 0.191000 0.169000 0.141000 0.113000 Z-Data Control XY-Layout: Full Z: 2.0 mm Source: Full on Save Cancel Volume: Reduced Intensity Zoom In/Out  25 X (mm) 25 Y (mm) SURFACE SAR VOLUME SAR <tr><td colspan="5">  3D View Plot </td></tr>					 3D View Plot				
 3D View Plot									


Test specification:	Plane_Body_Low_VHT40_5190_Left Touch			
Environ Conditions:	Temp(oC):	22.3	Result:	Pass
	Humidity(%):	49		
	Atmospheric(mPa):	1201.6		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5190.000000			
Relative permittivity (real part)	44.97			
Conductivity (S/m)	6.17			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	-2.81			
Highest Extrapolated SAR (W/Kg)	0.9835			
SAR 1g (W/Kg)	0.4096			
Peak SAR Location	21mm(x),-32mm(y),2mm(z)			



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Low_VHT40_5230_Left Touch			
Environ Conditions:	Temp(oC):	22.3	Result:	Pass
	Humidity(%):	49		
	Atmospheric(mPa):	1201.6		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5230.000000			
Relative permittivity (real part)	44.97			
Conductivity (S/m)	6.17			
Transmission Duty Factor	1.0			
Probe SN	2715_EPGO259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	-2.81			
Highest Extrapolated SAR (W/Kg)	0.9835			
SAR 1g (W/Kg)	0.3392			
Peak SAR Location	21mm(x),-32mm(y),2mm(z)			






SURFACE SAR




VOLUME SAR




3D View Plot

Test specification:	Plane_Body_Low_VHT40_5270_Back Touch			
Environ Conditions:	Temp(oC):	21.7	Result:	Pass
	Humidity(%):	45		
	Atmospheric(mPa):	1193.1		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5270.000000			
Relative permittivity (real part)	44.36			
Conductivity (S/m)	6.43			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	2.47			
Highest Extrapolated SAR (W/Kg)	1.2030			
SAR 1g (W/Kg)	0.3597			
Peak SAR Location	13mm(x),-64mm(y),2mm(z)			
				
SURFACE SAR		VOLUME SAR		
				
3D View Plot				


Test specification:	Plane_Body_High_VHT40_5310_Back Touch			
Environ Conditions:	Temp(oC):	23.5	Result:	Pass
	Humidity (%):	47		
	Atmospheric(mPa):	1185.7		
Mains Power:	N/A			
Test Date:	07/122017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5310.000000			
Relative permittivity (real part)	44.36			
Conductivity (S/m)	6.43			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.05			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	2.27			
Highest Extrapolated SAR (W/Kg)	0.5093			
SAR 1g (W/Kg)	0.3651			
Peak SAR Location	-3mm(x),-80mm(y),2mm(z)			



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Low_VHT40_5270_Left Touch			
Environ Conditions:	Temp(oC):	22.3	Result:	Pass
	Humidity(%):	49		
	Atmospheric(mPa):	1201.6		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5270.000000			
Relative permittivity (real part)	44.36			
Conductivity (S/m)	6.43			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	-1.27			
Highest Extrapolated SAR (W/Kg)	0.5498			
SAR 1g (W/Kg)	0.3187			
Peak SAR Location	-27mm(x),-24mm(y),2mm(z)			



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Low_VHT40_5310_Left Touch		
Environ Conditions:	Temp(oC):	22.3	Result: Pass
	Humidity(%):	49	
	Atmospheric(mPa):	1201.6	
Mains Power:	N/A		
Test Date:	07/11/2017		
Tested by:	Arthur Tie		
Remarks:			
Frequency (MHz)	5310.000000		
Relative permittivity (real part)	44.36		
Conductivity (S/m)	6.43		
Transmission Duty Factor	1.0		
Probe SN	2715_EPG0259		
Conversion Factor (dB)	3.01		
Area Scan Resolution	8 mm		
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm		
Zoom Scan Size	24x24x24 mm		
Measurement Drifts (%)	-1.27		
Highest Extrapolated SAR (W/Kg)	0.5498		
SAR 1g (W/Kg)	0.3115		
Peak SAR Location	-27mm(x),-24mm(y),2mm(z)		






SURFACE SAR




VOLUME SAR




3D View Plot

Test specification:	Plane_Body_Low_VHT40_5510_Back Touch			
Environ Conditions:	Temp(oC):	21.7	Result:	Pass
	Humidity(%):	45		
	Atmospheric(mPa):	1193.1		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5510.000000			
Relative permittivity (real part)	46.22			
Conductivity (S/m)	5.55			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.21			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	-0.87			
Highest Extrapolated SAR (W/Kg)	0.9510			
SAR 1g (W/Kg)	0.4295			
Peak SAR Location	21mm(x), -64mm(y), 2mm(z)			
				
SURFACE SAR		VOLUME SAR		
				
3D View Plot				


Test specification:	Plane_Body_Middle_VHT40_5590_Back Touch			
Environ Conditions:	Temp(oC):	21.2	Result:	Pass
	Humidity(%):	52		
	Atmospheric(mPa):	1092.4		
Mains Power:	N/A			
Test Date:	07/122017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5590.000000			
Relative permittivity (real part)	46.13			
Conductivity (S/m)	5.61			
Transmission Duty Factor	1.0			
Probe SN	2715_EPGO259			
Conversion Factor (dB)	3.21			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	3.65			
Highest Extrapolated SAR (W/Kg)	1.0038			
SAR 1g (W/Kg)	0.2791			
Peak SAR Location	21mm(x),-64mm(y),2mm(z)			



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_High_VHT40_5670_Back Touch			
Environ Conditions:	Temp(oC):	23.5	Result:	Pass
	Humidity (%):	47		
	Atmospheric(mPa):	1185.7		
Mains Power:	N/A			
Test Date:	07/13/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5670.000000			
Relative permittivity (real part)	46.13			
Conductivity (S/m)	5.61			
Transmission Duty Factor	1.0			
Probe SN	2715_EPGO259			
Conversion Factor (dB)	3.21			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	3.28			
Highest Extrapolated SAR (W/Kg)	0.4048			
SAR 1g (W/Kg)	0.2779			
Peak SAR Location	-3mm(x),-80mm(y),2mm(z)			






SURFACE SAR




VOLUME SAR




3D View Plot

Test specification:	Plane_Body_Middle_VHT40_5510_Left Touch			
Environ Conditions:	Temp(oC):	22.3	Result:	Pass
	Humidity(%):	49		
	Atmospheric(mPa):	1201.6		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5510.000000			
Relative permittivity (real part)	46.13			
Conductivity (S/m)	5.61			
Transmission Duty Factor	1.0			
Probe SN	2715_EPGO259			
Conversion Factor (dB)	3.21			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	0.24			
Highest Extrapolated SAR (W/Kg)	0.4593			
SAR 1g (W/Kg)	0.1272			
Peak SAR Location	45mm(x),-48mm(y),2mm(z)			
				
SURFACE SAR		VOLUME SAR		
				
3D View Plot				


Test specification:	Plane_Body_Middle_VHT40_5590_Left Touch			
Environ Conditions:	Temp(oC):	22.3	Result:	Pass
	Humidity(%):	49		
	Atmospheric(mPa):	1201.6		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5590.000000			
Relative permittivity (real part)	46.13			
Conductivity (S/m)	5.61			
Transmission Duty Factor	1.0			
Probe SN	2715_EPGO259			
Conversion Factor (dB)	3.21			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	0.24			
Highest Extrapolated SAR (W/Kg)	0.4593			
SAR 1g (W/Kg)	0.2907			
Peak SAR Location	45mm(x), -48mm(y), 2mm(z)			



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Middle_VHT40_5670_Left Touch			
Environ Conditions:	Temp(oC):	22.3	Result:	Pass
	Humidity(%):	49		
	Atmospheric(mPa):	1201.6		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5670.000000			
Relative permittivity (real part)	46.13			
Conductivity (S/m)	5.61			
Transmission Duty Factor	1.0			
Probe SN	2715_EPGO259			
Conversion Factor (dB)	3.21			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	0.24			
Highest Extrapolated SAR (W/Kg)	0.4593			
SAR 1g (W/Kg)	0.2821			
Peak SAR Location	45mm(x),-48mm(y),2mm(z)			



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Low_VHT40_5755_Back Touch			
Environ Conditions:	Temp(oC):	21.7	Result:	Pass
	Humidity(%):	45		
	Atmospheric(mPa):	1193.1		
Mains Power:	N/A			
Test Date:	07/13/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5755.000000			
Relative permittivity (real part)	46.07			
Conductivity (S/m)	5.68			
Transmission Duty Factor	1.0			
Probe SN	2715_EPGO259			
Conversion Factor (dB)	2.99			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	0.08			
Highest Extrapolated SAR (W/Kg)	0.9916			
SAR 1g (W/Kg)	0.6963			
Peak SAR Location	21mm(x),-64mm(y),2mm(z)			






SURFACE SAR




VOLUME SAR




3D View Plot

Test specification:	Plane_Body_Low_VHT40_5755_Left Touch			
Environ Conditions:	Temp(oC):	23.5	Result:	Pass
	Humidity (%):	47		
	Atmospheric(mPa):	1185.7		
Mains Power:	N/A			
Test Date:	07/13/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5755.000000			
Relative permittivity (real part)	46.07			
Conductivity (S/m)	5.68			
Transmission Duty Factor	1.0			
Probe SN	2715_EPGO259			
Conversion Factor (dB)	2.99			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	1.15			
Highest Extrapolated SAR (W/Kg)	0.4030			
SAR 1g (W/Kg)	0.1516			
Peak SAR Location	-3mm(x),-80mm(y),2mm(z)			
				
SURFACE SAR		VOLUME SAR		
				
3D View Plot				


Test specification:	Plane_Body_Middle_VHT80_5210_Back Touch			
Environ Conditions:	Temp(oC):	22.3	Result:	Pass
	Humidity(%):	49		
	Atmospheric(mPa):	1201.6		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5210.000000			
Relative permittivity (real part)	46.07			
Conductivity (S/m)	5.68			
Transmission Duty Factor	1.0			
Probe SN	2715_EPGO259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	-1.14			
Highest Extrapolated SAR (W/Kg)	0.4440			
SAR 1g (W/Kg)	0.3998			
Peak SAR Location	5mm(x),-40mm(y),2mm(z)			



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Middle_VHT80_5210_Left Touch			
Environ Conditions:	Temp(oC):	21.7	Result:	Pass
	Humidity(%):	45		
	Atmospheric(mPa):	1193.1		
Mains Power:	N/A			
Test Date:	07/11/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5210.000000			
Relative permittivity (real part)	46.00			
Conductivity (S/m)	5.75			
Transmission Duty Factor	1.0			
Probe SN	2715_EPG0259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	0.44			
Highest Extrapolated SAR (W/Kg)	0.7793			
SAR 1g (W/Kg)	0.3692			
Peak SAR Location	13mm(x),-64mm(y),2mm(z)			



SURFACE SAR




VOLUME SAR




3D View Plot


Test specification:	Plane_Body_Middle_VHT80_5290_Back Touch			
Environ Conditions:	Temp(oC):	21.3	Result:	Pass
	Humidity(%):	48		
	Atmospheric(mPa):	1102.2		
Mains Power:	N/A			
Test Date:	07/12/2017			
Tested by:	Arthur Tie			
Remarks:				
Frequency (MHz)	5290.000000			
Relative permittivity (real part)	45.12			
Conductivity (S/m)	6.09			
Transmission Duty Factor	1.0			
Probe SN	2715_EPGO259			
Conversion Factor (dB)	3.01			
Area Scan Resolution	8 mm			
Zoom Scan Resolution	dx=4mm, dy=4mm, dz=2mm			
Zoom Scan Size	24x24x24 mm			
Measurement Drifts (%)	-0.20			
Highest Extrapolated SAR (W/Kg)	1.1487			
SAR 1g (W/Kg)	0.2169			
Peak SAR Location	13mm(x),-64mm(y),2mm(z)			



SURFACE SAR



VOLUME SAR



3D View Plot