

ZEBRA TECHNOLOGIES CORP.

RFID READER

Model: ZXP Series 8

14 July 2009

Report No.: SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
(This report supersedes NONE)



Modifications made to the product : None

This Test Report is Issued Under the Authority of:

Choon Sian Ooi Test Engineer	Leslie Bai Engineering Reviewer

This test report may be reproduced in full only.
Test result presented in this test report is applicable to the representative sample only.

EMC Test Report

To: FCC Part 15.225 & IC RSS210

SIEMIC, INC.
Accessing global markets

Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management through out a project. Our extensive experience with China, Asia Pacific, North America, European, and international compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Accreditation Body	Scope
USA	FCC, A2LA	EMC , RF/Wireless , Telecom
Canada	IC, A2LA, NIST	EMC, RF/Wireless , Telecom
Taiwan	BSMI , NCC , NIST	EMC, RF, Telecom , Safety
Hong Kong	OFTA , NIST	RF/Wireless , Telecom
Australia	NATA, NIST	EMC, RF, Telecom , Safety
Korea	KCC/RRA, NIST	EMI, EMS, RF , Telecom, Safety
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom
Mexico	NOM, COFETEL, Caniety	Safety, EMC , RF/Wireless, Telecom
Europe	A2LA, NIST	EMC, RF, Telecom , Safety


Accreditations for Product Certifications

Country	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC , RF , Telecom
Canada	IC FCB , NIST	EMC , RF , Telecom
Singapore	iDA, NIST	EMC , RF , Telecom

Title: RF Test Report of Zebra Technologies Corp.
Model : ZXP Series 8
To FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 3 of 57

This page has been left blank intentionally.



CONTENTS

1	EXECUTIVE SUMMARY & EUT INFORMATION	6
2	TECHNICAL DETAILS.....	7
3	MODIFICATION	8
4	TEST SUMMARY	9
5	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS.....	10
	ANNEX A. TEST INSTRUMENT & METHOD	33
	ANNEX B EUT AND TEST SETUP PHOTOGRAPHS	37
	ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	37
	ANNEX D USER MANUAL, BLOCK & CIRCUIT DIAGRAM.....	41
	ANNEX E SIEMIC ACCREDITATION	42

Title: RF Test Report of Zebra Technologies Corp.
Model : ZXP Series 8
To FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 5 of 57

This page has been left blank intentionally.



Title: RF Test Report of Zebra Technologies Corp.
Model : ZXP Series 8
To FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 6 of 57

1 Executive Summary & EUT information

The purpose of this test programmed was to demonstrate compliance of the Zebra Technologies Corp., model:ZXP Series 8 against the current Stipulated Standards. The 13.56MHZ RFID has demonstrated compliance with the FCC 15.225 2008 & IC RSS210 Issue 7: 2007.

The equipment under test operating frequency is 13.56 MHz.

The test has demonstrated that this unit complies with stipulated standards.

EUT Information

EUT Description	:	13.56MHz RFID
Model No	:	ZXP Series 8
Input Power	:	100~240 VAC
Classification	:	RFID Reader
Per Stipulated Test Standard	:	



2 TECHNICAL DETAILS

Purpose	Compliance testing of 13.56MHZ RFID with stipulated standard
Applicant / Client	ZEBRA TECHNOLOGIES CORP.
Manufacturer	Zebra Technologies Corp. 333 Corporate Woods Parkway Vernon Hills, IL 60061 USA
Laboratory performing the tests	SIEMIC Laboratories
Test report reference number	SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Date EUT received	20 May 2009
Standard applied	47 CFR §15.225: 2008 & RSS 210 Issue 7: 2007
Dates of test (from – to)	22 Jun 2009 – 30 Jun 2009
No of Units:	2
Equipment Category:	DXX
Trade Name:	Zebra Technologies Corp.
Model :	ZXP Series 8
RF Operating Frequency (ies)	13.56 MHz (RFID)
Number of Channels :	1
Modulation :	ASK
FCC ID :	I28RFID- MAICD-01
IC ID :	3798B-MAICD01



SIEMIC, INC.

Accessing global markets

Title: RF Test Report of Zebra Technologies Corp.
Model : ZXP Series 8
To FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 8 of 57

3 MODIFICATION

NONE

4 TEST SUMMARY

The product was tested in accordance with the following specifications. All testing has been performed according to below product classification:

RFID Reader

Test Results Summary

Test Standard		Description	Pass / Fail
47 CFR Part 15.225: 2009	RSS 210 Issue 7: 2007		
15.203		Antenna Requirement	Pass
15.207(a)	RSS Gen(7.2.2)	Conducted Emissions Voltage	Pass
15.225(a)	RSS210(A2.6)	Limit in the band of 13.553 – 13.567 MHz	Pass
15.225(b)	RSS210(A2.6)	Limit in the band of 13.410 – 13.553 MHz and 13.567 – 13.710 MHz	Pass
15.225(c)	RSS210(A2.6)	Limit in the band of 13.110 – 13.410 MHz and 13.710 – 14.010 MHz	Pass
15.225(d)	RSS210(A2.6)	Limit outside the band of 13.110 – 14.010 MHz	Pass
15.225(e)	RSS210(A2.6)	Frequency Stability	Pass
	RSS-210(5.9.1)	Occupied Bandwidth	Pass

ANSI C63.4: 2003/ RSS-Gen Issue 2: 2007

PS: All measurement uncertainties are not taken into consideration for all presented test result.

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of Zebra Technologies Corp.
Model : ZXP Series 8
To FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 10 of 57

5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

5.1 Antenna Requirement

Requirement(s): 47 CFR §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna requirement must meet at least one of the following:

- a) Antenna must be permanently attached to the device.
- b) Antenna must use a unique type of connector to attach to the device.
- c) Device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device.

1) The RFID antenna is attached permanently to the device which meets the requirement.

5.2 Conducted Emissions Voltage

Requirement:

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15–0.5	66 to 56*	56 to 46*
0.5–5	56	46
5–30	60	50

*Decreases with the logarithm of the frequency.

Procedures:

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR and Average detectors, are reported. All other emissions were relatively insignificant.
2. A "ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 9kHz – 30MHz (Average & Quasi-peak) is ± 3.5 dB.
4. Environmental Conditions

Temperature	23°C - 25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar

Test Date : Jun 22 to 30, 2009


Tested By :Choon Sian Ooi

Results:

Note: 2


Average Limit

Quasi-Peak Limit



Phase Line Plot at 120Vac, 60Hz

Line Under Test	Frequency (MHz)	Corrected Amplitude (dBuV) QP	Limit (dBuV) QP	Margin (dB) QP	Corrected Amplitude (dBuV) AVG	Limit (dBuV) AVG	Margin (dB) AVG
Phase	0.16	58.01	65.54	-7.53	39.01	55.54	-16.53
Phase	0.34	45.65	59.21	-13.56	24.42	49.21	-24.79
Phase	0.32	46.59	59.83	-13.24	30.08	49.83	-19.74
Phase	0.47	31.15	56.52	-25.37	19.43	46.52	-27.09
Phase	7.09	33.96	60.00	-26.04	22.83	50.00	-27.17
Phase	8.89	31.99	60.00	-28.01	26.70	50.00	-23.30



Neutral Line Plot at 120Vac, 60Hz

Line Under Test	Frequency (MHz)	Corrected Amplitude (dBuV) QP	Limit (dBuV) QP	Margin (dB) QP	Corrected Amplitude (dBuV) AVG	Limit (dBuV) AVG	Margin (dB) AVG
Neutral	0.21	51.81	63.18	-11.37	31.99	53.18	-21.19
Neutral	0.39	42.37	58.01	-15.64	22.50	48.01	-25.51
Neutral	7.66	29.29	60.00	-30.71	23.68	50.00	-26.32
Neutral	10.47	32.51	60.00	-27.49	27.32	50.00	-22.68
Neutral	10.66	32.81	60.00	-27.19	27.33	50.00	-22.67
Neutral	9.68	32.04	60.00	-27.96	26.75	50.00	-23.25

5.3 Radiated Emission within the Band of 13.110 – 14.010 MHz

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 1GHz (QP only @ 3m & 10m) is +5.6dB/-4.5dB (for EUTs < 0.5m X 0.5m X 0.5m).
4. Environmental Conditions

Temperature	23°C - 25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar

Test Date : Jun 22 to 30, 2009


Tested By :Choon Sian Ooi

Requirement(s): 47 CFR §15.225(a) – (c) & RSS-210 (A2.6)


Procedures: Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set 3 meter away from the measuring antenna. The loop antenna was positioned 1 meter above the ground from the center of the loop. The measuring bandwidth was set to 10 kHz.

The limit is converted from microvolt/meter to decibel microvolt/meter.

Sample Calculation: Corrected Amplitude = Raw Amplitude (dB μ V/m) + ACF(dB) + Cable Loss(dB) – Distance Correction Factor



Results: Loop Antenna Positioned at 0 degrees with Laminate RFID activated.




Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)	Reading @ 3m (dB μ V/m)	Limit @ 3m (dB μ V/m)	Margin (dB μ V/m)
13.56	35.62	0.28	69.50	124.00	-54.50

Radiated Emissions Table

Results: Loop Antenna Positioned at 90 degrees with Laminate RFID activated.

Limit




Radiated Emissions Plot

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)	Reading @ 3m (dBµV/m)	Limit @ 3m (dBµV/m)	Margin (dBµV/m)
13.56	35.62	0.28	61.83	124	-62.17

Radiated Emissions Table

Results: Loop Antenna Positioned at 0 degrees with Ribbon RFID activated.

Limit




Radiated Emissions Plot

Frequency	Antenna Factor	Cable Loss	Reading @ 3m	Limit @ 3m	Margin
(MHz)	(dB)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB μ V/m)
13.56	35.62	0.28	59.5	124	-64.50

Radiated Emissions Table

Results: Loop Antenna Positioned at 90 degrees with Ribbon RFID activated.



Radiated Emissions Plot

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)	Reading @ 3m (dB μ V/m)	Limit @ 3m (dB μ V/m)	Margin (dB μ V/m)
13.56	35.62	0.28	62.76	124	-61.24

Radiated Emissions Table

Radiated Emissions < 30 MHz (outside 13.110 – 14.010 MHz)

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 1GHz (OP only @ 3m & 10m) is +5.6dB/-4.5dB (for EUTs < 0.5m X 0.5m X 0.5m).
4. Environmental Conditions

Temperature	23°C - 25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar

Test Date : Jun 22 to 30, 2009

Tested By :Choon Sian Ooi


Requirement(s): 47 CFR §15.209; 47 CFR §15.225(d) & RSS-210 (A2.6)

Procedures: Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set 3 meter away from the measuring antenna. The loop antenna was positioned 1 meter above the ground from the center of the loop. The measuring bandwidth was set to 10 kHz.

The limit is converted from microvolt/meter to decibel microvolt/meter.

Sample Calculation: Corrected Amplitude = Raw Amplitude (dB μ V/m) + ACF(dB) + Cable Loss(dB) – Distance Correction Factor

Results: Loop Antenna Positioned at 0 degrees with Laminate RFID activated.




Radiated Emissions Plot

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)	Reading @ 3m (dB μ V/m)	Limit @ 3m (dB μ V/m)	Margin (dB μ V/m)
1.17	46.56	0.25	66.06	69.54	3.48

Radiated Emissions Table


Results: Loop Antenna Positioned at 90 degrees with Laminate RFID activated.



Radiated Emissions Plot


Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)	Reading @ 3m (dB μ V/m)	Limit @ 3m (dB μ V/m)	Margin (dB μ V/m)
1.17	46.56	0.25	65.24	69.54	-4.3

Radiated Emissions Table



Results: Loop Antenna Positioned at 0 degrees with Ribbon RFID activated.

Limit




Radiated Emissions Plot

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)	Reading @ 3m (dBµV/m)	Limit @ 3m (dBµV/m)	Margin (dBµV/m)
1.17	46.56	0.25	67.11	69.54	-1.66

Radiated Emissions Table

Results: Loop Antenna Positioned at 90 degrees with Ribbon RFID activated.



Radiated Emissions Plot

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)	Reading @ 3m (dB μ V/m)	Limit @ 3m (dB μ V/m)	Margin (dB μ V/m)
1.17	46.56	0.25	67.42	69.54	-2.12

Radiated Emissions Table

5.4 Radiated Emissions > 30 MHz

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz - 1GHz (QP only @ 3m & 10m) is +5.6dB/-4.5dB (for EUTs < 0.5m X 0.5m X 0.5m).
4. Environmental Conditions

Temperature	23°C - 25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar

Test Date : Jun 22 to 30, 2009


Tested By :Choon Sian Ooi

Requirement(s): 47 CFR §15.209; 47 CFR §15.225(d) & RSS-210 (A2.6)

Procedures: Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power.


The limit is converted from microvolt/meter to decibel microvolt/meter.

Sample Calculation: Corrected Amplitude = Raw Amplitude (dB μ V/m) + ACF(dB) + Cable Loss(dB)




Results:

Note: Laminate RFID is in transmitting mode.




Test Data

Frequency (MHz)	Quasi-Peak (dB μ V/m)	Antenna height (cm)	Polarity	Turntable position (deg)	Limit (dB μ V/m)	Margin (dB)
828.93	39.17	397.00	H	298.00	46.00	-6.83
108.10	37.49	107.00	V	135.00	43.50	-6.01
107.55	36.78	104.00	V	148.00	43.50	-6.72
874.99	45.28	101.00	V	178.00	46.00	-0.72
846.17	40.38	391.00	H	91.00	46.00	-5.62
239.99	44.75	120.00	H	137.00	46.00	-1.25




Results:

Note: Ribbon RFID is in transmitting mode.



Test Data

Frequency (MHz)	Quasi-Peak (dB μ V/m)	Antenna height (cm)	Polarity	Turntable position (deg)	Limit (dB μ V/m)	Margin (dB)
846.11	40.22	368.00	H	182.00	46.00	-5.78
828.99	40.02	366.00	H	256.00	46.00	-5.98
399.71	37.24	238.00	H	149.00	46.00	-8.76
109.84	34.20	305.00	H	55.00	43.50	-9.30
874.99	45.29	100.00	V	176.00	46.00	-0.71
239.99	45.32	126.00	H	135.00	46.00	-0.68



Radiated Emission above 1GHz

Laminate RFID is in transmitting mode

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.247/15.209	15.247/15.209	
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
1.340	34.6	360	1.2	v	25.2	1.82	31.99	29.63	74	-44.37	Peak
1.340	37.6	280	1.2	h	25.2	1.82	31.99	32.63	74	-41.37	Peak
1.340	26.8	360	1	v	25.2	1.82	31.99	21.83	54	-32.17	Ave
1.340	25.8	280	1.2	h	25.2	1.82	31.99	20.83	54	-33.17	Ave

Ribbon RFID is in transmitting mode

Frequency	Reading	Direction	Height	Polar	Antenna Loss	Cable loss	Amplifier	Corrected Reading	15.247/15.209	15.247/15.209	
GHz	(dBuV/m)	Degree	Meter	H / V	(dB)	(dB)	(dB)	(dBuV/m)	Limit (dBuV/m)	Margin	Comments
1.530	36.9	360	1.2	v	26.4	2.16	31.98	33.48	74	-40.52	Peak
1.530	33.6	280	1.2	h	26.4	2.16	31.98	30.18	74	-43.82	Peak
1.530	23.9	360	1	v	26.4	2.16	31.98	20.48	54	-33.52	Ave
1.530	24.9	280	1.2	h	26.4	2.16	31.98	21.48	54	-32.52	Ave

5.5 Frequency Stability

1. Conducted Measurement
EUT was set for low , mid, high channel with CW mode and manufacturer declared RF output power. The spectrum analyzer was connected to the antenna terminal. The EUT was set up inside an environmental chamber and placed in the centre of the environmental.
2. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), the measurement uncertainty is +/- 1.2dB.
3. Environmental Conditions

Temperature	23°C - 25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
4. Test Date : Jun 22 to 30, 2009
Tested By :Choon Sian Ooi

Requirement(s): 47 CFR §15.225(e) & RSS-210 (A2.6)

Procedures: Frequency Stability was measured according to 47 CFR §2.1055. Measurement was taken with spectrum analyzer. The spectrum analyzer bandwidth and span was set to read in hertz. A voltmeter was used to monitor when varying the voltage.

Limit: $\pm 0.01\%$ of 13.56 MHz = 1356 Hz

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of Zebra Technologies Corp.
Model : ZXP Series 8
To FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 29 of 57

Laminate RFID is in transmitting mode

Frequency versus Temperature


Reference Frequency: 13.5600 MHz

Temperature (Celsius)	Measured Freq. (MHz)	Freq. Drift (Hz)	Freq. Drift (%)
50	13.560143	143	0.00105
40	13.560133	133	0.00098
30	13.560132	132	0.00097
10	13.560152	152	0.00112
0	13.560163	163	0.00120
-10	13.560123	123	0.00091
-20	13.560132	132	0.00097
-30	13.560118	118.2	0.00087

Frequency versus Voltage

Reference Frequency: 13.56000 MHz

Measured Voltage ±15% of nominal (AC)	Measured Freq. (MHz)	Freq. Drift (Hz)	Freq. Drift (%)
138	13.560133	133	0.00098
102	13.560135	135	0.00100



Ribbon RFID is in transmitting mode

Frequency versus Temperature

Reference Frequency: 13.5600 MHz

Temperature (Celsius)	Measured Freq. (MHz)	Freq. Drift (Hz)	Freq. Drift (%)
50	13.560124	124	0.00091
40	13.560133	133	0.00098
30	13.560131	131	0.00097
10	13.560121	121	0.00089
0	13.560134	134	0.00099
-10	13.560136	136	0.00100
-20	13.560124	124	0.00091
-30	13.560112	111.5	0.00082

Frequency versus Voltage

Reference Frequency: 13.56000 MHz

Measured Voltage ±15% of nominal (AC)	Measured Freq. (MHz)	Freq. Drift (Hz)	Freq. Drift (%)
138	13.560144	144	0.00106
102	13.560132	132	0.00097

5.6 Occupied bandwidth


Requirement(s): RSS-210 (5.9.1)

Procedures: Occupied Bandwidth was measured according to RSS-210 (5.9.1). Measurement was taken with spectrum analyzer. The spectrum analyzer bandwidth and span was set to read in hertz.

Results: Pass


Ribbon

Plots: 13.56 MHz



Laminate

Plots: 13.56 MHz




Annex A. TEST INSTRUMENT & METHOD

Annex A.i. TEST INSTRUMENTATION & GENERAL PROCEDURES

Instrument	Model	Calibration Due
AC Conducted Emissions		
R&S EMI Test Receiver	ESIB40	04/25/2010
R&S LISN	ESH2-Z5	04/24/2010
CHASE LISN	MN2050B	04/24/2010
Radiated Emissions		
Spectrum Analyzer	8564E	04/26/2010
EMI Receiver	ESIB 40	4/25/2010
R&S LISN	ESH2-Z5	04/24/2010
CHASE LISN	MN2050B	04/24/2010
Antenna(1 ~18GHz)	3115	01/04/2010
Antenna (30MHz~2GHz)	JB1	01/04/2010
Chamber	3m	04/18/2010
Pre-Amplifier(1 ~ 26GHz)	8449	04/24/2010
Horn Antenna (18~40GHz)	AH-840	03/19/2010
Microwave Pre-Amp (18~40GHz)	PA-840	03/19/2010*

Note: Functional Verification



Annex A.ii. CONDUCTED EMISSIONS TEST DESCRIPTION

Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B.
2. The power supply for the EUT was fed through a $50\Omega/50\mu\text{H}$ EUT LISN, connected to filtered mains.
3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.
4. All other supporting equipments were powered separately from another main supply.

Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
3. High peaks, relative to the limit line, were then selected.
4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 KHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

Sample Calculation Example

At 20 MHz limit = $250 \mu\text{V} = 47.96 \text{ dB}\mu\text{V}$

Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB

Q-P reading obtained directly from EMI Receiver = $40.00 \text{ dB}\mu\text{V}$
(Calibrated for system losses)

Therefore, Q-P margin = $47.96 - 40.00 = 7.96$ i.e. **7.96 dB below limit**

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of Zebra Technologies Corp.
Model : ZXP Series 8
To FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 35 of 57

Annex A. iii RADIATED EMISSIONS TEST DESCRIPTION


EUT Characterisation

EUT characterisation, over the frequency range from 30MHz to 10th Harmonic , was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred, clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS).

Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.



Test Method

The following procedure was performed to determine the maximum emission axis of EUT:

1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

Final Radiated Emission Measurement

1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0° to 360° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	Peak	100 kHz	100 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

Sample Calculation Example

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

$$\text{Peak} = \text{Reading} + \text{Corrected Factor}$$

where

$$\text{Corr. Factor} = \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain (if any)}$$


And the average value is

$$\text{Average} = \text{Peak Value} + \text{Duty Factor or}$$

$$\text{Set RBW} = 1\text{MHz}, \text{VBW} = 10\text{Hz}.$$

Note :

If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function.



Annex B EUT AND TEST SETUP PHOTOGRAPHS

Please see the attachment

Annex C. TEST SETUP AND SUPPORTING EQUIPMENT


EUT TEST CONDITIONS

Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Equipment Description (Including Brand Name)	Model & Serial Number	Cable Description (List Length, Type & Purpose)
PC Laptop / DELL	Latitude DS520	USB Cable , 1meter From PC Laptop to EUT

Block Configuration Diagram for Radiated Emission






SIEMIC, INC.


Accessing global markets

Title: RF Test Report of Zebra Technologies Corp.
To Model : ZXP Series 8
FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 39 of 57

Block Configuration Diagram for Conducted Emission





Annex C.ii. EUT OPERATING CONDITIONS

The following is the description of how the EUT is exercised during testing.

Test	Description Of Operation
Emissions Testing	The EUT was controlled via PC Laptop using Agency Testing Program provided by applicant.
Others Testing	The EUT was controlled via PC Laptop using Agency Testing Program provided by applicant.



SIEMIC, INC.

Accessing global markets

Title: RF Test Report of Zebra Technologies Corp.
Model : ZXP Series 8
To FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 41 of 57


Annex D USER MANUAL, BLOCK & CIRCUIT DIAGRAM

Please see attachment

 SIEMIC, INC. <i>Accessing global markets</i>		FCC ID : I28RFID- MAICD-01 IC Number : 3798B-MAICD01 Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth) Issue Date 14 July 2009 Page 42 of 57	
Title: RF Test Report of Zebra Technologies Corp. Model : ZXP Series 8 To FCC 15.225 2008, RSS210 Issue 7: 2007 www.siemic.com			

Annex E SIEMIC ACCREDITATION

SIEMIC ACREDITATION DETAILS: A2LA 17025 & ISO Guide 65 : 2742.01 , 2742.2

  THE AMERICAN ASSOCIATION FOR LABORATORY ACCREDITATION	
ACCREDITED LABORATORY	
<p>A2LA has accredited</p> <p>SIEMIC LABORATORIES San Jose, CA</p> <p>for technical competence in the field of</p> <p>Electrical Testing</p>	
<p>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005 <i>General Requirements for the Competence of Testing and Calibration Laboratories</i>. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated 18 June 2005).</p>	
<p>Presented this 11th day of July 2008.</p> <p> <u>Peter Abrey</u> President For the Accreditation Council Certificate Number 2742.01 Valid to September 30, 2010</p>	
<p>For the tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical Scope of Accreditation.</p>	



THE AMERICAN ASSOCIATION FOR LABORATORY ACCREDITATION

ACCREDITED PRODUCT CERTIFICATION BODY

A2LA has accredited

SIEMIC INC.

San Jose, CA

for technical competence as a
Product Certification Body

This product certification body is accredited in accordance with the recognized International Standard ISO/IEC Guide 65:1996 *General requirements for bodies operating product certification systems*. This accreditation demonstrates technical competence for a defined scope and the operation of a quality management system for a Telecommunications Certification Body (TCB) meeting FCC (U.S.), IDA (Singapore) and IC (Canada) requirements.



Presented this 9th day of January 2009.

President
For the Accreditation Council
Certificate Number: 2742.02
Valid to: September 30, 2010

For the product certification schemes to which this accreditation applies,
please refer to the certification body's Scope of Accreditation.

SCOPE OF ACCREDITATION TO ISO/IEC GUIDE 65:1996

SIEMIC INC.
2206 Ringwood Ave.
San Jose, CA 95131
Mr. Snell Leong (Authorized Representative) Phone: 408 526 1188
www.siemic.com

PRODUCT CERTIFICATION CONFORMITY ASSESSMENT BODY (CAB)

Valid to: September 30, 2010

Certificate Number: 2742.02

In recognition of the successful completion of the A2LA Certification Body Accreditation Program evaluation, including the US Federal Communications Commission (FCC), Industry Canada (IC) and Singapore (IDA) requirements for the indicated types of product certifications, accreditation is granted to this organization to perform the following product certification schemes:

Economy **Scope****Federal Communication Commission - (FCC)**

Unlicensed Radio Frequency Devices	A1, A2, A3, A4
Licensed Radio Frequency Devices	B1, B2, B3, B4
Telephone Terminal Equipment	C

**Please refer to FCC TCB Program Roles and Responsibilities, v04, released February 14, 2008 detailing scopes, roles and responsibilities. <http://www.fcc.gov/oet/ea/FCC-Overview-TCB-Program.pdf>*

Industry Canada - (IC)

Radio	All Radio Standards Specifications (RSS) in Category I Equipment Standards List Radio
-------	---------------------------------------------------------------------------------------

**Please refer to Industry Canada (IC) website at: http://www.ic.gc.ca/epic/site/smt-gst.nsf/en/h_sf01342e.html*

IDA – Singapore

Line Terminal Equipment	All Technical Specifications for Line Terminal Equipment – Table 1 of IDA MRA Recognition Scheme: 2008, Annex 2
Radio-Communication Equipment	All Technical Specifications for Radio-Communication Equipment – Table 2 of IDA MRA Recognition Scheme: 2008, Annex 2

**Please refer to Info-Communication Development Authority (IDA) Singapore website at: http://www.ida.gov.sg/doc/Policies%20and%20Regulation/Policies_and_Regulation_Level2/20060609145118/MRA_RecScheme.pdf*

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of Zebra Technologies Corp.
Model : ZXP Series 8
To FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 45 of 57

SIEMIC ACREDITATION DETAILS: FCC Test Site Registration No. 783147

FEDERAL COMMUNICATIONS COMMISSION
Laboratory Division
7435 Oakland Mills Road
Columbia, MD 21046

December 20, 2007

Registration Number: 783147

SIEMIC Laboratories
2206 Ringwood Avenue,
San Jose, CA 95131

Attention: Leslie Bai

Re: Measurement facility located at San Jose
3 & 10 meter site
Date of Renewal: December 20, 2007

Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website www.fcc.gov under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,

Phyllis Parrish
Industry Analyst



SIEMIC ACREDITATION DETAILS: Industry of Canada CAB ID : US0160



UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
Gaithersburg, Maryland 20899

March 4, 2009

Mr. Leslie Bai
SIEMIC, Inc.
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by Industry Canada (IC), under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131 USA
Identification No.: US0160
Recognized Scope: CS-03 Part I, II, V, VI, VII and VIII

You may submit test data to IC to verify that the equipment to be imported into Canada satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. Please contact Ms. Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov if you have any questions.

Sincerely,

A handwritten signature in black ink, appearing to read "David F. Alderman".

David F. Alderman
Group Leader, Standards Coordination and Conformity Group
Standards Services Division

Enclosure


cc: CAB Program Manager

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of Zebra Technologies Corp.
Model : ZXP Series 8
To FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 47 of 57

SIEMIC ACREDITATION DETAILS: Industry of Canada Test Site Registration No. 4842-1

May 23rd, 2008

OUR FILE: 46405-4842

Submission No: 126429

Siemic Inc.
2206 Ringwood Ave.
San Jose CA 95131
USA

Attention: Leslie Bai

Dear Sir/Madame:

The Bureau has received your application for the registration / renewal of a 3/10m OATS. Be advised that the information received was satisfactory to Industry Canada. The following number(s) is now associated to the site(s) for which registration / renewal was sought **(4842A-1)**. Please reference the appropriate site number in the body of test reports containing measurements performed on the site. In addition, please be informed that the Bureau is now utilizing a **new site numbering scheme** in order to simplify the electronic filing process. Our goal is to reduce the number of secondary codes associated to one particular company. The following changes have been made to your record.

- Your primary code is: **4842**
- The company number associated to the site(s) located at the above address is: **4842A**
- The table below is a summary of the changes made to the unique site registration number(s):

New Site Number	Obsolete Site Number	Description of Site	Expiry Date (YYYY-MM-DD)
4842A-1	4842-1	3m Chamber	2010-05-23

Furthermore, to obtain or renew a unique site number, the applicant shall demonstrate that the site has been accredited to ANSI C63.4-2003 or later. A scope of accreditation indicating the accreditation by a recognized accreditation body to ANSI C63.4-2003 shall be accepted. Please indicate in a letter the previous assigned site number if applicable and the type of site (example: 3 meter OATS or 3 meter chamber). If the test facility is not accredited to ANSI C63.4-2003 or later, the test facility shall submit test data demonstrating full compliance with the ANSI standard. The Bureau will evaluate the filing to determine if recognition shall be granted.

The frequency for re-validation of the test site and the information that is required to be filed or retained by the testing party shall comply with the requirements established by the accrediting organization. However, in all cases, test site re-validation shall occur on an interval not to exceed two years. There is no fee or form associated with an OATS filing. OATS submissions are encouraged to be submitted electronically to the Bureau using the following URL:
http://strategis.ic.gc.ca/epic/internet/inceb-bhst.nsf/en/h_1t00052e.html.

If you have any questions, you may contact the Bureau by e-mail at certification.bureau@ic.gc.ca. Please reference our file and submission number above for all correspondence.

Yours sincerely,

S. Proulx
Test & Measurement Specialist
Certification and Engineering Bureau
3701 Carling Ave., Building 94
Ottawa, Ontario K2H 8S2



SIEMIC, INC.

Accessing global markets

Title: RF Test Report of Zebra Technologies Corp.
Model : ZXP Series 8
To FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 48 of 57

SIEMIC ACREDITATION DETAILS: FCC DOC CAB Recognition : US1109

FEDERAL COMMUNICATIONS COMMISSION

Laboratory Division

**7435 Oakland Mills Road
Columbia, MD 21046**

August 28, 2008

**Siemic Laboratories
2206 Ringwood Ave.,
San Jose, CA 95131**

Attention: Leslie Bai

Re: Accreditation of Siemic Laboratories
Designation Number: US1109
Test Firm Registration #: 540430


Dear Sir or Madam:

We have been notified by American Association for Laboratory Accreditation that Siemic Laboratories has been accredited as a Conformity Assessment Body (CAB).

At this time Siemic Laboratories is hereby designated to perform compliance testing on equipment subject to Declaration Of Conformity (DOC) and Certification under Parts 15 and 18 of the Commission's Rules.

This designation will expire upon expiration of the accreditation or notification of withdrawal of designation.

Sincerely,


George Tannahill
George Tannahill
Electronics Engineer

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of Zebra Technologies Corp.
Model : ZXP Series 8
To FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 49 of 57

SIEMIC ACREDITATION DETAILS: Australia CAB ID : US0160

UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
Gaithersburg, Maryland 20899

November 20, 2008

Mr. Leslie Bai
SIEMIC, Inc.
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Australian Communications and Media Authority (ACMA) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: Siemic, Inc.
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131
Identification No.: US0160
Recognized Scope: EMC: AS/NZS 4251.1 (until 5/31/2009), AS/NZS 4251.2 (until 5/31/2009), AS/NZS CISPR 11, AS/NZS CISPR 14.1, AS/NZS CISPR 22, AS/NZS 61000.6.3, AS/NZS 61000.6.4
Radiocommunications: AS/NZS 4281, AS/NZS 4268, AS/NZS 4280.1, AS/NZS 4280.2, AS/NZS 4295, AS/NZS 4582, AS/NZS 4583, AS/NZS 4769.1, AS/NZS 4769.2, AS/NZS 4770, AS/NZS 4771
Telecommunications: AS/ACIF S002:05, AS/ACIF S003:06, AS/ACIF S004:06, AS/ACIF S006:01, AS/ACIF S016:01, AS/ACIF S031:01, AS/ACIF S038:01, AS/ACIF S040:01, AS/ACIF S041:05, AS/ACIF S043.2:06, AS/NZS 60950.1

You may submit test data to ACMA to verify that the equipment to be imported into Australia satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. Please contact Ms. Ramona Saar, at (301) 975-5521 or ramona.saar@nist.gov if you have questions.

Sincerely,

David F. Alderman
Group Leader, Standards Coordination and Conformity Group
Standards Services Division

Enclosure

cc: Snell Leong, Siemic, Inc.; Ramona Saar, NIST

SIEMIC, INC.

Accessing global markets

Title: RF Test Report of Zebra Technologies Corp.
Model : ZXP Series 8
To FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 50 of 57

SIEMIC ACREDITATION DETAILS: Korea CAB ID: US0160

UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
Gaithersburg, Maryland 20899

October 1, 2008

Mr. Leslie Bai
SIEMIC, Inc.
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Radio Research Agency (RRA) Korea Communications Commission (KCC) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131
Identification No.: US0160
Recognized Scope: **EMI:** KCC Notice 2008-39, RRL Notice 2008-3: CA Procedures for EMI
KN22: Test Method for EMI
EMS: KCC Notice 2008-38, RRL Notice 2008-4: CA Procedures for EMS
KN24, KN-61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11: Test Method for EMS
Wireless: RRL Notice 2008-26, RRL Notice 2008-2, RRL Notice 2008-10,
RRL Notice 2007-49, RRL Notice 2007-20, RRL Notice 2007-21,
RRL Notice 2007-80, RRL Notice 2004-68
Wired: President Notice 20664, RRL Notice 2007-30,
RRL Notice 2008-7 with attachments 1, 3, 5, 6
President Notice 20664, RRL Notice 2008-7 with attachment 4

You may submit test data to RRA/KCC to verify that the equipment to be imported into Korea satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov.

Sincerely,

David F. Alderman
Group Leader, Standards Coordination and Conformity Group
Standards Services Division

Enclosure

cc: Ramona Saar

SIEMIC ACREDITATION DETAILS: Taiwan BSMI Accreditation No. SL2-IN-E-1130R

UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
Gaithersburg, Maryland 20889

May 3, 2006:

Mr. Leslie Bai
SIEMIC Laboratories
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

I am pleased to inform you that your laboratory has been recognized by the Chinese Taipei's Bureau of Standards, Metrology, and Inspection (BSMI) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. You may submit test data to BSMI to verify that the equipment to be imported into Chinese Taipei satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. The pertinent designation information is as follows:


- BSMI number: **SL2-IN-E-1130R** (Must be applied to the test reports)
- U.S. Identification No: **US0160**
- Scope of Designation: **CNS 13438**
- Authorized signatory: **Mr. Leslie Bai**

The names of all recognized CABs will be posted on the NIST website at <http://ts.nist.gov/mra>. If you have any questions, please contact Mr. Dhillon at 301-975-5521. We appreciate your continued interest in our international conformity assessment activities.

Sincerely,

David F. Alderman
Group Leader, Standards Coordination and Conformity Group

cc: Jagminder Dhillon



SIEMIC ACREDITATION DETAILS: Taiwan NCC CAB ID: US0160



UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
Gaithersburg, Maryland 20899.

November 25, 2008

Mr. LeslieBai
SIEMIC, Inc.
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the National Communications Commission (NCC) for the requested scope expansion under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.
Physical Location: 2206 Ringwood Avenue, San Jose, CA 95131
Identification No.: US0160
Current Scope: LP0002
Additional Scope: PSTN01, ADSL01, ID0002, IS6100 and CNS 14336

You may submit test data to NCC to verify that the equipment to be imported into China satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov.

Sincerely,

David F. Alderman
Group Leader, Standards Coordination and Conformity Group
Standards Services Division

Enclosure

cc: Ramona Saar

NIST

SIEMIC ACREDITATION DETAILS: Mexico NOM Recognition

CAMARA NACIONAL
DE LA INDUSTRIA
ELECTRONICA, DE
TELECOMUNICACIONES
E INFORMATICA

Laboratorio Valentín V. Rivero

Méjico D.F. a 16 de octubre de 2008.

LESLIE BAI
DIRECTOR OF CERTIFICATION
SIEMIC LABORATORIES, INC.
ACCESSING GLOBAL MARKETS
P R E S E N T E

En contestación a su escrito de fecha 5 de septiembre del año en curso, le comentó que estamos muy interesados en su intención de firmar un Acuerdo de Reconocimiento Mutuo, para lo cual adjunto a este escrito encontrara el Acuerdo en idioma inglés y español prefirmado de los cuales le pido sea revisado y en su caso corregido, para que si este de acuerdo poder firmarlo para mandarlo con las autoridades Mexicanas para su visto bueno y así poder ejercer dicho acuerdo.

Aprovecha este escrito para mencionarte que nuestro intermediano gestor será la empresa Isabel de México, S. A. de C. V., empresa que ha colaborado durante mucho tiempo con nosotros en lo relacionado a la evaluación de la conformidad y que cuenta con amplia experiencia en la gestoría de la certificación de cumplimiento con Normas Oficiales Mexicanas de producto en México.

Me despido de usted enviándole un cordial saludo y esperando sus comentarios al Acuerdo que nos ocupa.

Atentamente:

Ing. Faustino Pérez González
Gerente Técnico del Laboratorio de
CANIETI

**SIEMIC, INC.**

Accessing global markets

Title: RF Test Report of Zebra Technologies Corp.
Model : ZXP Series 8
To FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 54 of 57

SIEMIC ACREDITATION DETAILS: Hong Kong OFTA CAB ID : US0160

UNITED STATES DEPARTMENT OF COMMERCE
National Institute of Standards and Technology
Gaithersburg, Maryland 20899

December 8, 2008

Mr. Leslie Bai
SIEMIC, Inc.
2206 Ringwood Avenue
San Jose, CA 95131

Dear Mr. Bai:

NIST is pleased to inform you that your laboratory has been recognized by the Office of the Telecommunications Authority (OFTA) under the Asia Pacific Economic Cooperation for Telecommunications Equipment Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I Procedures**, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: SIEMIC, Inc.
Physical Location: 2206 Ringwood Avenue, San Jose, California 95131 USA
Identification No.: US0160
Recognized Scope: **Radio:** HKTA 1002, 1007, 1008, 1010, 1015, 1016, 1020, 1022, 1026, 1027, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1039, 1041, 1042, 1043, 1044, 1046, 1047, 1048, 1049, 1051
Telecom: HKTA 2011, 2012, 2013, 2014, 2017, 2018, 2022, 2024, 2026, 2027, 2028, 2029, 2030, 2031, 2032, 2033

You may submit test data to OFTA to verify that the equipment to be imported into Hong Kong satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

Recognized CABs are listed on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Ramona Saar at (301) 975-5521 or ramona.saar@nist.gov.

Sincerely,

David F. Alderman
Group Leader, Standards Coordination and Conformity Group
Standards Services Division

Enclosure

cc: Ramona Saar



SIEMIC, INC.

Accessing global markets

Title: RF Test Report of Zebra Technologies Corp.
Model : ZXP Series 8
To FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 55 of 57

SIEMIC ACREDITATION DETAILS: VCCI Radiated Test Site Registration No. R-3083



VCCI Council

CERTIFICATE

Company: SIEMIC Inc.

<Member No. 3081 >

Facility: SIEMIC Inc.

(Radiation 3 meter site)

Location of Facility:

2206 Ringwood Avenue, San Jose, CA 95131 USA

*This is to certify that the following measuring facility
has been registered in accordance with the Rules
for Voluntary Control Measures*

Registration No.: R-3083

Date of Registration: June 12, 2009

This Certificate is valid until September 30, 2010

VCCI Council





SIEMIC, INC.

Accessing global markets

Title: RF Test Report of Zebra Technologies Corp.
Model : ZXP Series 8
To FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 56 of 57

SIEMIC ACREDITATION DETAILS: VCCI Conducted (Main Port) Test Site Registration No. C-3421



VCCI Council

CERTIFICATE

Company: SIEMIC Inc.

<Member No. 3081 >

Facility: SIEMIC Inc.

(Main Ports Conducted Interference Measurement)

Location of Facility:

2206 Ringwood Avenue, San Jose, CA 95181 USA

*This is to certify that the following measuring facility
has been registered in accordance with the Rules
for Voluntary Control Measures*

Registration No.: C-3421

Date of Registration: June 12 , 2009

This Certificate is valid until September 30 , 2010

VCCI Council





SIEMIC, INC.

Accessing global markets

Title: RF Test Report of Zebra Technologies Corp.
Model: ZXP Series 8
To FCC 15.225 2008, RSS210 Issue 7: 2007
www.siemic.com

FCC IC : I28RFID- MAICD-01
IC Number : 3798B-MAICD01
Serial# SL09010703-ZBR-001_ZXP(15.225) (Media Auth)
Issue Date 14 July 2009
Page 57 of 57

SIEMIC ACREDITATION DETAILS: VCCI Conducted (Telecom Port) Test Site Registration No. T-1597



VCCI Council

CERTIFICATE

Company: SIEMIC Inc.

<Member No. 3081 >

Facility: SIEMIC Inc.

(Telecominication Ports Conducted Interference Measurement)

Location of Facility:

2206 Ringwood Avenue, San Jose, CA 95131 USA

*This is to certify that the following measuring facility
has been registered in accordance with the Rules
for Voluntary Control Measures*

Registration No.: T-1597

Date of Registration: June 12 , 2009

This Certificate is valid until September 30 , 2010

VCCI Council

