

A

TEST REPORT FCC Part 22 Type Acceptance

**Spectrian
Power Amplifier
Model: MCPS2350-4-800**

FCC ID: I2OMCPS2000

Report # J98033279

Date of Report: December 1, 1998

Total No. of Pages Contained in this Report: 33

This report shall not be reproduced except in full, without written approval of Intertek Testing Services.

This report must not be used to claim product endorsement by NVLAP or any agency of the U.S. Government.

The results contained in this report were derived from measurements performed on the identified test samples. Any implied performance of other samples on this report is dependent on the representative of the samples tested.

FCC Part 22

Intertek Testing Services NA Inc.

1365 Adams Court, Menlo Park, CA 94025

Tel 650.463.2900 Fax 650.463.2910 www.worldlab.com

Table of Contents

1.0	Introduction	2
1.1	Test Summary	2
1.2	Product Description	3
2.0	RF Power Output	4
2.1	Test Procedure	4
2.2	Test Equipment	4
2.3	Test Results	4
3.0	Effective Radiated Power	8
3.1	Test Procedure	8
3.2	Test Results	8
4.0	Occupied Bandwidth, Emission Limitations	9
4.1	Test Procedure	9
4.2	Test Equipment	9
4.3	Test Results	9
5.0	Out of Band Emissions at Antenna Terminals	13
5.1	Test Procedure	13
5.2	Test Equipment	13
5.3	Test Results	13
6.0	Field Strength of Spurious Radiation	27
6.1	Test Procedure	27
6.2	Test Equipment	27
6.3	Test Configuration Setup - Radiated Emissions	28
6.4	Test Results	29
7.0	Line Conducted Emissions	31
7.1	Test Procedure	31
7.2	Test Configuration Setup - Line Conducted Emissions	31
7.3	Test Results	31
8.0	Frequency Stability vs Temperature	32
8.1	Test Procedure	32
8.2	Test Equipment	32
8.3	Test Results	32
9.0	Frequency Stability vs Voltage	33
9.1	Test Procedure	33
9.2	Test Equipment	33
9.3	Test Results	33

A

Spectrian, Power Amplifier

Date of Test: November 24, 1998

1.0 Introduction

1.1 Test Summary

FCC RULE	DESCRIPTION OF TEST	RESULT	PAGE
2.985	RF Power Output	Pass	4
22.913	Effective Radiated Power	N/A	8
2.989(c), 22.917(b)(d)	Emission Limitation, Occupied Bandwidth.	Pass	9
22.917(e)	Spurious emissions at antenna terminals	Pass	13
2.993, 15.109	Field Strength of Spurious Radiation	Pass	27
15.107	Line Conducted Emissions	N/A	31
2.995(a)	Frequency Stability vs. Temperature	N/A	32
2.995(d)(2)	Frequency Stability vs. Voltage	N/A	33



November 30, 1998

Barry Smith
Test Engineer

Date

A

Spectrian, Power Amplifier

Date of Test: November 24, 1998

1.2 Product Description

The Spectrian Model MCPS2350-4-800 is a power amplifier operating in the frequency range 869 MHz - 894 MHz

For more details, refer to the users manual.

A

Spectrian, Power Amplifier

Date of Test: November 24, 1998

2.0 **RF Power Output**, FCC §2.985(a)

2.1 Test Procedure

The amplifier's output was connected to a power meter and spectrum analyzer through a calibrated coaxial attenuator and directional coupler. The FM test signal was applied to the amplifier's input from a signal generator, and the input level was adjusted to obtain 55.4 dBm average output power.

2.2 Test Equipment

Hewlett Packard 8482A Power Sensor, 438A Power Meter

Hewlett Packard 8594E Spectrum Analyzer, 9 kHz - 2.9 GHz


2.3 Test Results

The average output power is 55.4 dBm (or 350W) measured with a power meter. See also plots attached.

A

Spectrian, Power Amplifier


Date of Test: November 24, 1998



A

Spectrian, Power Amplifier


Date of Test: November 24, 1998



A

Spectrian, Power Amplifier

Date of Test: November 24, 1998



3.0 **Effective Radiated Power, FCC §22.913**

Requirement: The Effective Radiated Power (ERP) must not exceed 500 Watts.

3.1 Test Procedure

Assuming that the EUT has an ideal matching to an antenna the ERP can be calculated as follows:

$$\text{ERP}_{(\text{dBm})} = P_{(\text{dBm})} + 10 \log G = 55.4 + 2.15 = 57.6 \text{ dBm}$$

where: G is the gain of a half-wave dipole

3.2 Test Results

Not Applicable

A

Spectrian, Power Amplifier

Date of Test: November 24, 1998

4.0 **Occupied Bandwidth, Emission Limitations.** FCC §2.989(I), §22.917

4.1 Test Procedure

The RF output of the EUT was connected to the input of the spectrum analyzer through sufficient attenuation. The spectrum with no modulation was plotted.

The EUT was set up to transmit a FM signal and the spectrum with modulation was plotted.

4.2 Test Equipment

Gigatronics 8542C Power Meter

HP 8566B Spectrum Analyzer, 100 Hz - 22 GHz

Tektronix 2784 Spectrum Analyzer, 100 Hz - 40 GHz

HP 7470A Plotter

4.3 Test Results

For test results refer to the attached plots 4.3.a, 4.3.b showing the emissions on the amplifier's output.

The EUT passed the F3E emission mask tests.

A

Spectrian, Power Amplifier

Date of Test: November 24, 1998


Emission Limitations, Occupied Bandwidth Plots:

Plot Number	Description
4.3.a	Output, 869 MHz, FM Modulation, 2.5 kHz Tone, 12 kHz Deviation, span 100 kHz.
4.3.b	Output, 869 MHz, FM Modulation, 2.5 kHz Tone, 12 kHz Deviation, span 200 kHz.

A

Spectrian, Power Amplifier


Date of Test: November 24, 1998



A

Spectrian, Power Amplifier

Date of Test: November 24, 1998



5.0 **Out of Band Emissions at Antenna Terminals** , FCC §2.991, §22.917 (e)

Out of Band Emissions:

The power of emissions must be attenuated below the power of the unmodulated carrier (P) on any frequency twice or more than twice the fundamental frequency by at least $43 + 10 \log P$ dB.

5.1 Test Procedure

The RF output of the EUT was connected to a spectrum analyzer through appropriate attenuation. The FM modulation signal was set up. Sufficient scans were also taken to show the any out-of-band emissions up to 10th harmonic for 3 fundamental frequencies: 869 MHz, 881.5 MHz, and 894 MHz.

5.2 Test Equipment

HP 8566B Spectrum Analyzer, 100 Hz - 22 GHz
Tektronix 2784 Spectrum Analyzer, 100 Hz - 40 GHz

5.3 Test Results

There are no emissions detected above the specified limit.

The EUT passed the test. For test results, refer to the attached plots.

A

Spectrian, Power Amplifier

Date of Test: November 24, 1998


Plots of Out-of-Band Emissions at Antenna Terminal are attached.

PLOT NUMBER	DESCRIPTION
5.3.a	869 MHz, Scan 1 MHz - 100 MHz
5.3.b	869 MHz, Scan 100 MHz - 1 GHz
5.3.c	869 MHz, Scan 1 GHz - 2.5 GHz
5.3.d	869 MHz, Scan 2.5 GHz - 10 GHz
5.3.e	881.5 MHz, Scan 1 MHz - 100MHz
5.3.f	881.5 MHz, Scan 100 MHz - 1 GHz
5.3.g	881.5 MHz, Scan 1 GHz - 2.5 GHz
5.3.h	881.5 MHz, Scan 2.5 GHz - 10 GHz
5.3.i	894 MHz, Scan 1 MHz - 100 MHz
5.3.j	894 MHz, Scan 100 MHz - 1 GHz
5.3.k	894 MHz, Scan 1 GHz - 2.5 GHz
5.3.l	894 MHz, Scan 2.5 GHz - 10 GHz

A

Spectrian, Power Amplifier


Date of Test: November 24, 1998



A

Spectrian, Power Amplifier


Date of Test: November 24, 1998



A

Spectrian, Power Amplifier


Date of Test: November 24, 1998



A

Spectrian, Power Amplifier


Date of Test: November 24, 1998



A

Spectrian, Power Amplifier


Date of Test: November 24, 1998



A

Spectrian, Power Amplifier


Date of Test: November 24, 1998



A

Spectrian, Power Amplifier


Date of Test: November 24, 1998



A

Spectrian, Power Amplifier


Date of Test: November 24, 1998



A

Spectrian, Power Amplifier


Date of Test: November 24, 1998



A

Spectrian, Power Amplifier


Date of Test: November 24, 1998



A

Spectrian, Power Amplifier


Date of Test: November 24, 1998



A

Spectrian, Power Amplifier

Date of Test: November 24, 1998



A

Spectrian, Power Amplifier

Date of Test: November 24, 1998

6.0 **Field Strength of Spurious Radiation, FCC § 2.993, §15.109**

6.1 Test Procedure

A 50 Ohm coaxial load was connected to the amplifier output. The amplifier was placed on a wooden turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

The spurious harmonic attenuation was calculated as the difference between E in dB(uV/m) at the fundamental frequency and at the spurious emission frequency.

The Field Strength at the fundamental frequency (in dBuV/m) was calculated using the formula:

$$E_{dB(uV/m)} = P_{dBm} + 10\log 30 + 10\log G - 20\log D + 90 = 152.8 \text{ dB}(uV/m)$$

where: P = the output power,

G=1.64 for the gain of half-wave dipole,

D= 3 m for the distance

6.2 Test Equipment

EMCO 3115 Horn Antenna

HP 8566B Spectrum Analyzer

Tektronix 2784 Spectrum Analyzer

High Pass Filter


CDI Preamplifier P1000

A

Spectrian, Power Amplifier

Date of Test: November 24, 1998

6.3 Test Configuration Setup - Radiated Emissions



A

Spectrian, Power Amplifier

Date of Test: November 24, 1998

6.4 Test Results

The minimum spurious attenuation was found as 76.6 dB. Please refer to the attached data sheets. Since the limit for spurious attenuation is 68.4 dB, the EUT passed the test by 8.2 dB.

A

Spectrian, Power Amplifier

Date of Test: November 24, 1998

ITS Intertek Testing Services										
1365 Adams Court, Menlo Park CA 94025										
Radiated Emissions Test Data										
Company:	Spectrian			Model #:	4 brick					
EUT:				S/N or FCC#:						
Project #:				Engineer:	Barry					
Test Mode:	Operating at 869MHz			Date of Test:	11/24/98					
Initial:										
Number:	Antenna	Pre-Amp	Cable A	Cable B	OCF	Standard_	FCC PART 22			
Model:	8	8	12	0	0	Limits_	3			
	EMCO 3115 CDI	P1000	Green_M+L	None	None	Test Distance	3	meters		
Frequency	Reading	Det.	Ant. Pol.	Ant. Factor	Pre-Amp	Insert. Loss	D. F.	Fundamental	Atten	
MHz	dB(uV)	P/A/Q	H/V	dB(1/m)	dB	dB	dB	dB(uV/m)	dB	
1738.0	80.4		v	24.9	29.4	0.0	0.0	75.9	152.8	
2607.0	69.1		v	27.9	28.4	2.3	0.0	70.9	152.8	
3476.0	67.6		v	30.2	27.8	2.5	0.0	72.5	152.8	
4345.0	57.2		v	32.5	27.9	2.9	0.0	64.7	152.8	
5214.0	56.6		v	33.1	28.3	3.5	0.0	64.9	152.8	
6083.0	48.6		v	34.4	28.3	3.9	0.0	58.6	152.8	
6952.0	48.8		h	34.0	28.0	4.2	0.0	59.0	152.8	
7821.0	44.7		v	37.5	27.5	4.6	0.0	59.3	152.8	
8690.0	38.4		v	37.3	27.1	4.7	0.0	53.3	152.8	
Goal = 68.4										
Notes: a) P: Peak; A: Average; Q: Quasi Peak; H: Horizontal; V: Vertical; OCF:Other Correction Factor; DF:Distance Factor b) Insert. Loss = Cable A + Cable B + OCF. c) Negative signs (-) in Margin column signify levels below the limits. d) All other emissions not reported are below the equipment noise floor which is at least 20 dB below the limits.										

7.0 **Line Conducted Emissions, FCC § 15.107**

7.1 Test Procedure

Test procedure described in the ANSI C63.4 Standard was employed.

The EUT was connected to an AC line through the LISNs.

Both HOT and NEUTRAL leads were tested.

7.2 Test Configuration Setup - Line Conducted Emissions

Not applicable, the EUT is DC powered only.

7.3 Test Results

Not applicable, the EUT is DC powered only.

A

Spectrian, Power Amplifier

Date of Test: November 24, 1998

8.0 Frequency Stability vs Temperature, FCC § 2.995(a)

8.1 Test Procedure

The RF output of the EUT was connected to a spectrum analyzer via feedthrough attenuators. The EUT was placed inside the temperature chamber. The RF output cable exited the chamber through an opening.

After the temperature stabilized for approximately 20 minutes, the frequency of the output signal was recorded from the spectrum analyzer.

8.2 Test Equipment

Thermotron Ind. Temperature Chamber, Model S-8C

Hewlett Packard 8591E Spectrum Analyzer

8.3 Test Results

Not applicable.

A

Spectrian, Power Amplifier

Date of Test: November 24, 1998

9.0 Frequency Stability vs Voltage, FCC 2.995(d)(2)

9.1 Test Procedure

An external variable AC power source was connected to the EUT. The frequency of the transmitter was measured for 115% of the AC nominal value and for 85% of the nominal value.

9.2 Test Equipment

Hewlett Packard 8591E Spectrum Analyzer

9.3 Test Results.

Not applicable.