



Circuit Description  
For  
DSL5005EN(x) Product

Date: 10. February 2011  
Prepared By: Thiha Kyaw  
Aztech Technologies Pte Ltd  
31, Ubi Road 1, Aztech Building,  
Singapore 408694  
Tel : +65-65942288  
Fax : +65-67491198

## 1. Introduction

The Aztech DSL5005EN(x) is an ADSL2+ router, which has four port 10/100BASE-T Ethernet LAN interface, a single ADSL2+ port, 802.11n wireless interface, and one USB 2.0 host interface. It supports 1T1R with PHY rate at 150Mbps.

### 1.1 ADSL2/2+ Router Processor with Analog Front End

Two-chip ADSL router solution including TC3162U ADSL2/2+ processor and TC3086 integrated analog front end and line driver is used in DSL5005EN(x) product.

The TC3162U ADSL2/2+ processor employs the discrete multi-tone modulation technology compliant to the various standards defined by ANSI and ITU-T. It incorporates a DMT engine, a 32-bit network processor, a USB 2.0 Host or device controller with integrated transceiver, a 10/100 Ethernet MAC with MII interface, an ATM AAL5 hardware SAR, and one PCIe interface for 802.11a/b/g/n WLAN solution. The 10/100 Ethernet MAC with MII interface supports multiple LAN port access. The configurable 480Mbps USB 2.0 host or device controller with transceiver provides storage/print or a plug-and-play service for PC without external device.

TC3086 is a high-performance CMOS analog front end (AFE) with an integrated line driver for Asymmetrical Digital Subscriber Line Customer Premises Equipment (ADSL CPE) applications. It supports all ADSL standards (ADSL1/2/2+), including Annex A, B, I, J & M. It also supports RE-ADSL2 (Annex L).

### 1.2 Four Ports Ethernet Switch

A highly integrated Ethernet switch, TC2205F has a high performance, non-blocking and operates with store-and forward mode. It is a managed switch that meets all IEEE802.3/u/x Fast Ethernet specifications. It has 4-port 10/100 Mbps UTP and one MII/TMII port which supports PHY mode for management and router application.

### 1.3 802.11 b/g/n Wireless

RT5390 is a highly integrated MAC/BBO and 2.4GHz RF/PA/LNA single chip with 150Mbps PHY rate supporting. It fully complies with IEEE 802.11n and IEEE 802.11 b/g feature rich wireless connectivity at high standards. Optimized RF architecture and base band algorithms provide superb performance and low power consumption.

### 1.4 USB Host

The USB port is a dedicated HOST port compliant to USB 2.0 high-speed (480Mbps) which used for storage.

### **1.5 Power Supply**

A 12VDC 1A external switching power supply is used to provide power to the platform. The 12V supply is stepped down to the following voltages using external switching regulators and LDO regulator.

- 7.13V
- 5V
- 3.3V
- 1.8V
- 1.2V