



SAR Exemption Evaluation

Applicant Peavey Electronics Corp.
FCC ID I4S-PV22
Product STEREO MIXER
Model PV 22
Report No. EFTA25050205-IE-05-S1
Issue Date June 6, 2025

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **KDB 447498 D01 General RF Exposure Guidance v06**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Wei Fangying

Approved by: Xu Kai

Eurofins TA Technology (Shanghai) Co., Ltd.

*Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
TEL: +86-021-50791141/2/3
FAX: +86-021-50791141/2/3-8000*

Table of Contents

1	Test Laboratory	3
1.1	Notes of the Test Report.....	3
1.2	Test Facility.....	3
1.3	Testing Location.....	3
1.4	Laboratory Environment	3
2	Description of Equipment Under Test	4
3	Test Specification, Methods and Procedures	6
4	Output Power	7
5	Standalone SAR Test Exclusion Considerations	8
	ANNEX A: The EUT Appearance	9

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <https://www.eurofins.com/electrical-and-electronics>
E-mail: Kain.Xu@cpt.eurofinscn.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25°C
Relative humidity	Min. = 20%, Max. = 80%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2 Description of Equipment Under Test

Client Information

Applicant	Peavey Electronics Corp.
Applicant address	5022 Hartley Peavey Drive, Meridian, MS, USA 39305
Manufacturer	Peavey Electronics Corp.
Manufacturer address	5022 Hartley Peavey Drive, Meridian, MS, USA 39305

General Technologies

Application Purpose	Original Grant
EUT Stage	Identical Prototype
Model	PV 22
Lab Internal SN	EFTA25050205-IE-05/S01
Hardware Version	/
Software Version	/
Antenna Type	Internal Antenna
Date of Testing	May 31, 2025~June 6, 2025
Date of Sample Received	May 29, 2025

Note: The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant.

Wireless Technology and Frequency Range

Wireless Technology	Modulation	Operating Mode	Tx (MHz)
BT	2.4G	Version 5.4 BR/EDR	2402 ~2480

3 Test Specification, Methods and Procedures

Reference Standards

KDB 447498 D01 General RF Exposure Guidance v06

4 Output Power

BT	Conducted Power(dBm)			Tune-up Limit (dBm)	
	Channel/Frequency(MHz)				
	Ch 0/2402 MHz	Ch 39/2441 MHz	Ch 78/2480 MHz		
GFSK	0.84	-0.09	-1.13	4.50	
$\pi/4$ DQPSK	3.00	1.89	0.75	4.50	
8DPSK	3.60	2.39	1.21	4.50	

5 Standalone SAR Test Exclusion Considerations

Per KDB 447498 D01, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

Per KDB 447498 D01, when the minimum test separation distance is $<$ 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Band	Configuration	Frequency (MHz)	Distance (mm)	Tune up (dBm)	Ratio	SAR test exclusion thresholds	Evaluation
Bluetooth	Body-worn	2402	15	4.50	0.29	3.00	No
	Extremity SAR	2402	5	4.50	0.87	7.50	No

Note: Based on SAR test exclusion, all values meet the SAR test exclusion thresholds and are exempt from routine evaluation.

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

*****END OF REPORT*****