


承认书项目表

NO.	内 容 (Contents)	页 数 (Number of Page)	页 码 (Page Code)
1	承认书封面 (Spec Cover)	1	1
2	承认书项目表 (Spec Item)	1	2
3	工程成品图 (Drawing)	1	3
4	电性测试报告 (Test Reports)	1	4
5	S参数测试 (S Parameter)	1	5
6	增益测试 (Gain Test)	1	6
7			
8			
9			
10	-	-	-
11	-	-	-
12	-	-	-

电 性 测 试 报 告

Test Reports

Electrical Properties	
Frequency	2.4GHz 5GHz
Impedance	50 Ohm Nominal
V.S.W.R	2.5 : 1 Max
Return Loss	-12 dB Max
Radiation	Omni-directional
Gain (Peak)	3dBi
Cable Loss	3.2 dB / m Max @ 2450 MHz
Polarization	Linear, Vertical
Admitted Power	1 W
Connector	ipex
Physical Properties	
Antenna Material	FPCB
Cable Type	O.D. 1.13mm // 120 mm
Operating Temp.	-25 ~ +65 °C
Storage Temp.	-30 ~ +75 °C
Cable Color	Black



SIGN	DATE	DESCRIPTION	APPROVER



3	NB030B	FPC	42*12mm	1
2	R-CB-113B	Coaxial Cable	SHOWA-O.D. 1.13mm Black	1
1	CI-113	Connector	Mini Connector	1
No.	Part Number	Name	Material	Q'ty

TITLE: 2.4GHz Antenna				
PART NO.: NB030-13B-IX130			DWG NAME: NB030-13B-IX130.DWG	
APPROVED BY	CHECKED BY	DESIDNED BY		Tolerance
jeff 2014-02-26	leon 2014-02-26	YD 2014-02-26	UNITS: mm	X.X ±0.20
			SCALE: 1/1	X.XX ±0.10
			REVISION: A	X° ±3°

S 参数测试

S Parameter Test

Agilent E5071C



增益测试

Gain Test

*Antenna
Radiation
Pattern
VS
Gain*

