


FCC Co-Location Test Report

FCC ID : I88NBG6817
Equipment : AC2600 MU-MIMO Dual-Band Wireless Gigabit Router
Model No. : NBG6817
Brand Name : ZYXEL
Applicant : ZyXEL Communications Corporation
Address : No.2, Industry East Road IX, Science Park, Hsinchu, Taiwan
Standard : 47 CFR FCC Part 15.247
47 CFR FCC Part 15.407
Received Date : Apr. 13, 2016
Tested Date : May 04 ~ Jul. 19, 2016

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	The Equipment List	6
1.3	Test Standards	7
1.4	Measurement Uncertainty	7
2	TEST CONFIGURATION.....	8
2.1	Testing Condition.....	8
2.2	The Worst Test Modes and Channel Details.....	8
3	TRANSMITTER TEST RESULTS	9
3.1	Unwanted Emissions into Restricted Frequency Bands	9
4	TEST LABORATORY INFORMATION	17

Release Record

Report No.	Version	Description	Issued Date
FR641302CO	Rev. 01	Initial issue	May 30, 2016
FR641302CO	Rev. 02	<ol style="list-style-type: none">1. Location of one antenna cable is changed.2. CPU heat sink changed.3. Capacitor of DC in portion is replaced with a higher capacitance value and specification capacitor.	Jul. 22, 2016
FR641302CO	Rev. 03	Brand name changed.	Jul. 28, 2016

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.247(d)			
15.407(b)	Radiated Emissions	[dBuV/m at 3m]: 220.12MHz 45.54 (Margin -0.46dB) – QP	Pass
15.209			

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

Operating Frequency	802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5745 ~ 5825 MHz
Modulation Type	802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n/ac: OFDM (BPSK / QPSK / 16QAM / 64QAM/256QAM)

1.1.2 Antenna Details

Model	Type	Connector	Operating Frequencies (MHz) / Antenna Gain (dBi)		
			2400~2483.5	5150~5250	5725~5850
RFA-25-Z3-79-140	Dipole	UFL	2.17	1.32	2.09
RFA-25-Z3-79B-200	Dipole	UFL	1.08	2.48	2.81
RFA-25-Z3-79BL-150	Dipole	UFL	2.25	1.3	2.72
RFA-25-Z3-79W-200	Dipole	UFL	1.16	0.98	1.85

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	12Vdc from AC adapter
--------------------------	-----------------------

1.1.4 Accessories

Accessories		
No.	Equipment	Description
1	AC adapter	Brand Name: APD Model Name: WA-36A12FU Power Rating: I/P: 100-240Vac, 50-60Hz, 0.9A Max O/P: 12Vdc, 3A Power Line: 1.5m non-shielded cable with one core
2	RJ45 Cable	0.9m shielded cable without core.

1.2 The Equipment List

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Dec. 13, 2015	Dec. 12, 2016
Receiver	R&S	ESR3	101658	Nov. 04, 2015	Nov. 03, 2016
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Aug. 20, 2015	Aug. 19, 2016
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 16, 2015	Dec. 15, 2016
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 04, 2015	Nov. 03, 2016
Preamplifier	Burgeon	BPA-530	SN:100219	Sep. 10, 2015	Sep. 09, 2016
Preamplifier	Agilent	83017A	MY39501308	Oct. 02, 2015	Oct. 01, 2016
Preamplifier	EMC	EMC184045B	980192	Sep. 01, 2015	Aug. 31, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Dec. 10, 2015	Dec. 09, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Dec. 10, 2015	Dec. 09, 2016
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16139/4	Dec. 10, 2015	Dec. 09, 2016
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Dec. 10, 2015	Dec. 09, 2016
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Dec. 10, 2015	Dec. 09, 2016
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 16, 2015	Nov. 15, 2016
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Feb. 17, 2016	Feb. 16, 2017
Power Meter	Anritsu	ML2495A	1241002	Sep. 21, 2015	Sep. 20, 2016
Power Sensor	Anritsu	MA2411B	1207366	Sep. 21, 2015	Sep. 20, 2016
Signal Generator	R&S	SMB100A	175727	Oct. 05, 2015	Oct. 04, 2016
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA

Note: Calibration Interval of instruments listed above is one year.

1.3 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

47 CFR FCC Part 15.407

ANSI C63.10-2013

FCC KDB 558074 D01 DTS Meas Guidance v03r05

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r02

FCC KDB 644545 D03 Guidance for IEEE 802.11ac New Rules v01

FCC KDB 412172 D01 Determining ERP and EIRP v01r01

1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty	
Parameters	Uncertainty
Radiated emission ≤ 1GHz	±3.66 dB
Radiated emission > 1GHz	±5.63 dB

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
Radiated Emissions	03CH01-WS	22-24°C / 61-66%	Vincent Yeh Anderson Hung
Conducted Emissions	TH01-WS	21°C / 64%	Alex Huang

- FCC site registration No.: 181692
- IC site registration No.: 10807A-1

2.2 The Worst Test Modes and Channel Details

Test item	Modulation Mode	Test Channel	Data Rate	Test Configuration
Radiated Emissions	2.4G 11b + 5G 11a	CH6 + CH165	1Mbps + 6Mbps	---
Conducted Emissions				
NOTE: The selected channel is the maximum power channel of Wi-Fi mode				

3 Transmitter Test Results

3.1 Unwanted Emissions into Restricted Frequency Bands

3.1.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:

Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:

Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.1.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m.
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

3.1.3 Test Setup


Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz




Transmitter Conducted Unwanted Emissions (30MHz~40GHz)




3.1.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	2.4G 11b + 5G 11a	Test Channel	CH6 + CH165																																																																					
Polarization	Horizontal																																																																							
																																																																								
<table border="1"> <thead> <tr> <th>Freq. MHz</th><th>Emission level dBuV/m</th><th>Limit dBuV/m</th><th>Margin dB</th><th>SA reading dBuV</th><th>Factor dB</th><th>Remark</th><th>ANT High cm</th><th>Turn Table deg</th></tr> </thead> <tbody> <tr> <td>1</td><td>200.72</td><td>41.24</td><td>43.50</td><td>-2.26</td><td>60.53</td><td>-19.29</td><td>QP</td><td>100</td><td>162</td></tr> <tr> <td>2</td><td>220.12</td><td>45.54</td><td>46.00</td><td>-0.46</td><td>64.56</td><td>-19.02</td><td>QP</td><td>150</td><td>348</td></tr> <tr> <td>3</td><td>355.92</td><td>37.76</td><td>46.00</td><td>-8.24</td><td>52.40</td><td>-14.64</td><td>Peak</td><td>---</td><td>---</td></tr> <tr> <td>4</td><td>624.61</td><td>38.65</td><td>46.00</td><td>-7.35</td><td>47.76</td><td>-9.11</td><td>Peak</td><td>---</td><td>---</td></tr> <tr> <td>5</td><td>719.67</td><td>33.90</td><td>46.00</td><td>-12.10</td><td>41.53</td><td>-7.63</td><td>Peak</td><td>---</td><td>---</td></tr> <tr> <td>6</td><td>874.87</td><td>35.54</td><td>46.00</td><td>-10.46</td><td>41.10</td><td>-5.56</td><td>Peak</td><td>---</td><td>---</td></tr> </tbody> </table>				Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg	1	200.72	41.24	43.50	-2.26	60.53	-19.29	QP	100	162	2	220.12	45.54	46.00	-0.46	64.56	-19.02	QP	150	348	3	355.92	37.76	46.00	-8.24	52.40	-14.64	Peak	---	---	4	624.61	38.65	46.00	-7.35	47.76	-9.11	Peak	---	---	5	719.67	33.90	46.00	-12.10	41.53	-7.63	Peak	---	---	6	874.87	35.54	46.00	-10.46	41.10	-5.56	Peak	---	---
Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg																																																																
1	200.72	41.24	43.50	-2.26	60.53	-19.29	QP	100	162																																																															
2	220.12	45.54	46.00	-0.46	64.56	-19.02	QP	150	348																																																															
3	355.92	37.76	46.00	-8.24	52.40	-14.64	Peak	---	---																																																															
4	624.61	38.65	46.00	-7.35	47.76	-9.11	Peak	---	---																																																															
5	719.67	33.90	46.00	-12.10	41.53	-7.63	Peak	---	---																																																															
6	874.87	35.54	46.00	-10.46	41.10	-5.56	Peak	---	---																																																															
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m). Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.																																																																								




3.1.5 Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation	2.4G 11b + 5G 11a	Test Channel	CH6 + CH165																																																	
Polarization	Horizontal																																																			
<p>The graph plots Level (dBuV/m) on the y-axis (0 to 90) against Frequency (MHz) on the x-axis (1000 to 40000). Four data points are marked: 2 at ~3388MHz (50.27 dBuV/m), 3 at ~8262MHz (38.72 dBuV/m), 4 at ~3388MHz (51.97 dBuV/m), and a peak at ~8262MHz (74.00 dBuV/m). Two horizontal lines represent limits: FCC CLASS-B at 70 dBuV/m and FCC CLASS-B (AVG) at 54 dBuV/m.</p>																																																				
<table border="1"> <thead> <tr> <th>Freq.</th> <th>Emission level MHz</th> <th>Limit dBuV/m</th> <th>Margin dB</th> <th>SA reading dB</th> <th>Factor dB</th> <th>Remark</th> <th>ANT High cm</th> <th>Turn Table deg</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>3388.00</td> <td>30.27</td> <td>54.00</td> <td>-23.73</td> <td>30.46</td> <td>-0.19</td> <td>Average</td> <td>145</td> <td>204</td> </tr> <tr> <td>2</td> <td>3388.00</td> <td>42.89</td> <td>74.00</td> <td>-31.11</td> <td>43.08</td> <td>-0.19</td> <td>Peak</td> <td>145</td> <td>204</td> </tr> <tr> <td>3</td> <td>8262.00</td> <td>38.72</td> <td>54.00</td> <td>-15.28</td> <td>29.12</td> <td>9.60</td> <td>Average</td> <td>100</td> <td>115</td> </tr> <tr> <td>4</td> <td>8262.00</td> <td>51.97</td> <td>74.00</td> <td>-22.03</td> <td>42.37</td> <td>9.60</td> <td>Peak</td> <td>100</td> <td>115</td> </tr> </tbody> </table>				Freq.	Emission level MHz	Limit dBuV/m	Margin dB	SA reading dB	Factor dB	Remark	ANT High cm	Turn Table deg	1	3388.00	30.27	54.00	-23.73	30.46	-0.19	Average	145	204	2	3388.00	42.89	74.00	-31.11	43.08	-0.19	Peak	145	204	3	8262.00	38.72	54.00	-15.28	29.12	9.60	Average	100	115	4	8262.00	51.97	74.00	-22.03	42.37	9.60	Peak	100	115
Freq.	Emission level MHz	Limit dBuV/m	Margin dB	SA reading dB	Factor dB	Remark	ANT High cm	Turn Table deg																																												
1	3388.00	30.27	54.00	-23.73	30.46	-0.19	Average	145	204																																											
2	3388.00	42.89	74.00	-31.11	43.08	-0.19	Peak	145	204																																											
3	8262.00	38.72	54.00	-15.28	29.12	9.60	Average	100	115																																											
4	8262.00	51.97	74.00	-22.03	42.37	9.60	Peak	100	115																																											
Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB) *Factor includes antenna factor , cable loss and amplifier gain Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).																																																				




3.1.6 Conducted Emissions (30MHz~40GHz)


Conducted Emission Plots of Antenna port 0




Conducted Emission Plots of Antenna port 1



Conducted Emission Plots of Antenna port 2



Conducted Emission Plots of Antenna port 3



4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640
No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666
No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640
No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C..

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666
Fax: 886-3-318-0155
Email: ICC_Service@icertifi.com.tw

==END==