


FCC Test Report

FCC ID : I88NBG6818
Equipment : AC2600 Multi-Gigabit Security WiFi Router
Model No. : NBG6818
Brand Name : ZYXEL
Applicant : Zyxel Communications Corporation
Address : No.2 Industry East RD. IX, Hsinchu Science
Park, Hsinchu 30075, Taiwan, R.O.C
Standard : 47 CFR FCC Part 15.247
Received Date : Sep. 23, 2019
Tested Date : Oct. 19 ~ Nov. 11, 2019


We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:



Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	8
1.3	Test Setup Chart	8
1.4	The Equipment List	9
1.5	Test Standards	11
1.6	Deviation from Test Standard and Measurement Procedure.....	11
1.7	Measurement Uncertainty	11
2	TEST CONFIGURATION.....	12
2.1	Testing Condition	12
2.2	The Worst Test Modes and Channel Details	12
3	TRANSMITTER TEST RESULTS	13
3.1	Conducted Emissions.....	13
3.2	Unwanted Emissions into Restricted Frequency Bands	16
3.3	Unwanted Emissions into Non-Restricted Frequency Bands	33
3.4	Conducted Output Power	38
3.5	Number of Hopping Frequency	41
3.6	20dB and Occupied Bandwidth.....	44
3.7	Channel Separation.....	49
3.8	Number of Dwell Time	54
4	TEST LABORATORY INFORMATION	60

Release Record

Report No.	Version	Description	Issued Date
FR992302AD	Rev. 01	Initial issue	Jan. 07, 2020

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.255MHz 45.91 (Margin -15.69dB) - QP	Pass
15.247(d) 15.209	Radiated Emissions	[dBuV/m at 3m]: 42.61MHz 34.85 (Margin -5.15dB) - PK	Pass
15.247(d)	Band Edge	Meet the requirement of limit	Pass
15.247(b)(1)	Conducted Output Power	Power [dBm]: 4.48	Pass
15.247(a)(1)(iii)	Number of Hopping Channels	Meet the requirement of limit	Pass
15.247(a)(1)	Hopping Channel Separation	Meet the requirement of limit	Pass
15.247(a)(1)(iii)	Dwell Time	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information				
Frequency Range (MHz)	Bluetooth Mode	Ch. Frequency (MHz)	Channel Number	Data Rate
2400-2483.5	BR V4.0	2402-2480	0-78 [79]	1 Mbps
2400-2483.5	EDR V4.0	2402-2480	0-78 [79]	2 Mbps
2400-2483.5	EDR V4.0	2402-2480	0-78 [79]	3 Mbps
Note 1: RF output power specifies that Maximum Peak Conducted Output Power. Note 2: Bluetooth BR uses a GFSK. Note 3: Bluetooth EDR uses a combination of $\pi/4$ -DQPSK and 8DPSK.				

1.1.2 Antenna Details

Ant. No.	Type	Connector	Gain (dBi)	Remarks
1	Printed Monopole Antenna	N/A	4	---

1.1.3 Power Supply Type of Equipment under Test (EUT)

Power Supply Type	12Vdc from adapter
-------------------	--------------------

1.1.4 Accessories


Accessories		
No.	Equipment	Description
1	Adapter	Brand: APD Model: WA-36N12R Power Rating: I/P: 100-240Vac, 50-60Hz 0.9Max O/P: 12Vdc, 3A Power Line: 1.8m non-shielded without core
2	RJ45 cable	Brand: EKSON Model: ZP01-C333 Power Line: 2.15m non-shielded without core

1.1.5 Channel List

Frequency band (MHz)				2400~2483.5			
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461	---	---

1.1.6 Test Tool and Duty Cycle

Test Tool	CBT	
Duty Cycle and Duty Factor	Duty Cycle (%)	Duty Factor (dB)
DH5	48.20%	3.17
3DH5	48.42%	3.15




1.1.7 Power Index of Test Tool

Modulation Mode	Test Frequency (MHz)		
	2402	2441	2480
GFSK/1Mbps	0x0F	0x0F	0x0F
$\pi/4$ -DQPSK /2Mbps	0x0F	0x0F	0x0F
8DPSK/3Mbps	0x0F	0x0F	0x0F

1.2 Local Support Equipment List

Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Remarks
1	USB Flash	Transcend	JetFlash 500 16G	---	---
2	Notebook	DELL	Latitude E6430	DoC	---
3	Notebook	DELL	Latitude E6440	DoC	---
4	RJ45 load	---	---	---	---

1.3 Test Setup Chart



1.4 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Tested Date	Nov. 11, 2019				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101657	Jan. 08, 2019	Jan. 07, 2020
LISN	R&S	ENV216	101579	Mar. 08, 2019	Mar. 07, 2020
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Oct. 22, 2019	Oct. 21, 2020
Measurement Software	AUDIX	e3	6.120210k	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Tested Date	Oct. 19, 2019				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Dec. 27, 2018	Dec. 26, 2019
Receiver	R&S	ESR3	101658	Dec. 11, 2018	Dec. 10, 2019
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 12, 2019	Jul. 11, 2020
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 18, 2018	Dec. 17, 2019
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 15, 2018	Nov. 14, 2019
Loop Antenna	R&S	HFH2-Z2	100315	Jan. 11, 2019	Jan. 10, 2020
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 07, 2019	Oct. 06, 2020
Preamplifier	EMC	EMC02325	980225	Jul. 09, 2019	Jul. 08, 2020
Preamplifier	Agilent	83017A	MY39501308	Oct. 08, 2019	Oct. 07, 2020
Preamplifier	EMC	EMC184045B	980192	Aug. 01, 2019	Jul. 31, 2020
RF Cable	EMC	EMC104-SM-SM-8000	181106	Oct. 07, 2019	Oct. 06, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Oct. 07, 2019	Oct. 06, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Oct. 07, 2019	Oct. 06, 2020
LF cable 1M	EMC	EMCCFD400-NM-NM-1000	160502	Oct. 07, 2019	Oct. 06, 2020
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 07, 2019	Oct. 06, 2020
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Oct. 07, 2019	Oct. 06, 2020
Bluetooth Tester	R&S	CBT	100959	Oct. 18, 2019	Oct. 17, 2020
Measurement Software	AUDIX	e3	6.120210g	NA	NA

Note: Calibration Interval of instruments listed above is one year.

Test Item	Radiated Emission				
Test Site	966 chamber1 / (03CH01-WS)				
Tested Date	Nov. 11, 2019				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Dec. 27, 2018	Dec. 26, 2019
Receiver	R&S	ESR3	101658	Dec. 11, 2018	Dec. 10, 2019
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 12, 2019	Jul. 11, 2020
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 18, 2018	Dec. 17, 2019
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 15, 2018	Nov. 14, 2019
Loop Antenna	R&S	HFH2-Z2	100315	Jan. 11, 2019	Jan. 10, 2020
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 07, 2019	Oct. 06, 2020
Preamplifier	EMC	EMC02325	980225	Jul. 09, 2019	Jul. 08, 2020
Preamplifier	Agilent	83017A	MY39501308	Oct. 08, 2019	Oct. 07, 2020
Preamplifier	EMC	EMC184045B	980192	Aug. 01, 2019	Jul. 31, 2020
RF Cable	EMC	EMC104-SM-SM-80 00	181106	Oct. 07, 2019	Oct. 06, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Oct. 07, 2019	Oct. 06, 2020
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Oct. 07, 2019	Oct. 06, 2020
LF cable 1M	EMC	EMCCFD400-NM-N M-1000	160502	Oct. 07, 2019	Oct. 06, 2020
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 07, 2019	Oct. 06, 2020
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Oct. 07, 2019	Oct. 06, 2020
Bluetooth Tester	R&S	CBT	100959	Oct. 18, 2019	Oct. 17, 2020
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Nov. 01, 2019				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Apr. 17, 2019	Apr. 16, 2020
Power Meter	Anritsu	ML2495A	1241002	Oct. 23, 2019	Oct. 22, 2020
Power Sensor	Anritsu	MA2411B	1207366	Oct. 23, 2019	Oct. 22, 2020
AC POWER SOURCE	APC	AFC-500W	F312060012	Nov. 29, 2018	Nov. 28, 2019
Measurement Software	Sporton	Sporton_1	1.3.30	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

ANSI C63.10-2013

FCC KDB 558074 D01 15.247 Meas Guidance v05r02

1.6 Deviation from Test Standard and Measurement Procedure

None

1.7 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor ($k=2$)).

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	± 34.130 Hz
Conducted power	± 0.808 dB
Power density	± 0.583 dB
Conducted emission	± 2.715 dB
AC conducted emission	± 2.92 dB
Radiated emission ≤ 1 GHz	± 3.41 dB
Radiated emission > 1 GHz	± 4.59 dB
Time	$\pm 0.1\%$

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	23°C / 68%	Akun Chung
Radiated Emissions	03CH01-WS	23-24°C / 63-64%	Roger Lu Aska Huang
RF Conducted	TH01-WS	22°C / 64%	Brad Wu

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- ISED#: 10807A
- CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Data Rate (Mbps)	Test Configuration
Conducted Emissions	8DPSK	2480	3Mbps	---
Radiated Emissions ≤ 1GHz	8DPSK	2480	3Mbps	---
Radiated Emissions > 1GHz	GFSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480	1Mbps 3Mbps	---
Conducted Output Power	GFSK π/4 DQPSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480 2402, 2441, 2480	1Mbps 2Mbps 3Mbps	---
Number of Hopping Channels	GFSK π/4 DQPSK 8DPSK	2402~2480 2402~2480 2402~2480	1Mbps 2Mbps 3Mbps	---
Hopping Channel Separation 20dB and Occupied bandwidth	GFSK π/4 DQPSK 8DPSK	2402, 2441, 2480 2402, 2441, 2480 2402, 2441, 2480	1Mbps 2Mbps 3Mbps	---
Dwell Time	GFSK π/4 DQPSK 8DPSK	2441 2441 2441	1Mbps 2Mbps 3Mbps	---

NOTE:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **X-plane** results were found as the worst case and were shown in this report.

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions

Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz


3.1.3 Test Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions


Modulation Mode	8DPSK	Test Freq. (MHz)	2480
Power Phase	Line		



	Freq MHz	Level dBuV	Limit Line dBuV	Over Limit dB	Read Level dBuV	LISN factor dB	cable loss dB	Remark
1	0.189	35.94	54.06	-18.12	26.16	9.54	0.06	Average
2	0.189	47.74	64.06	-16.32	37.96	9.54	0.06	QP
3	0.255	31.86	51.60	-19.74	22.03	9.55	0.07	Average
4*	0.255	45.91	61.60	-15.69	36.08	9.55	0.07	QP
5	0.291	19.31	50.50	-31.19	9.46	9.56	0.07	Average
6	0.291	37.53	60.50	-22.97	27.68	9.56	0.07	QP
7	0.381	24.36	48.25	-23.89	14.46	9.57	0.08	Average
8	0.381	37.75	58.25	-20.50	27.85	9.57	0.08	QP
9	3.565	21.04	46.00	-24.96	10.79	9.61	0.27	Average
10	3.565	33.83	56.00	-22.17	23.58	9.61	0.27	QP
11	22.063	25.23	50.00	-24.77	14.25	9.65	0.68	Average
12	22.063	32.23	60.00	-27.77	21.25	9.65	0.68	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 Note 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Modulation Mode	8DPSK	Test Freq. (MHz)	2480
Power Phase	Neutral		



	Freq	Level	Limit	Over	Read	LISN	cable	
	MHz	dBuV	Line	Limit	Level	factor	loss	Remark
			dBuV	dB	dBuV	dB	dB	
1	0.198	33.60	53.71	-20.11	23.81	9.58	0.06	Average
2*	0.198	46.10	63.71	-17.61	36.31	9.58	0.06	QP
3	0.264	30.33	51.29	-20.96	20.51	9.59	0.07	Average
4	0.264	42.86	61.29	-18.43	33.04	9.59	0.07	QP
5	0.426	21.46	47.33	-25.87	11.60	9.61	0.08	Average
6	0.426	35.19	57.33	-22.14	25.33	9.61	0.08	QP
7	3.123	23.54	46.00	-22.46	13.37	9.66	0.25	Average
8	3.123	34.45	56.00	-21.55	24.28	9.66	0.25	QP
9	3.346	22.89	46.00	-23.11	12.71	9.66	0.26	Average
10	3.346	34.82	56.00	-21.18	24.64	9.66	0.26	QP
11	19.428	28.00	50.00	-22.00	17.03	9.81	0.65	Average
12	19.428	34.00	60.00	-26.00	23.03	9.81	0.65	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

3.2 Unwanted Emissions into Restricted Frequency Bands

3.2.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9~90 kHz, 110~490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

3.2.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. Radiated emission above 1GHz / Peak value
RBW=1MHz, VBW=3MHz and Peak detector
Radiated emission above 1GHz / Average value for harmonics
The average value is: Average = Peak value + 20log(Duty cycle) Where the duty factor is calculated from following formula for DH5 packet type which has worst duty factor:
3.
$$20\log (\text{Duty cycle}) = 20\log \frac{1\text{s} / 1600 * 5}{100 \text{ ms}} = -30.1\text{dB}$$
4. Radiated emission above 1GHz / Average value for other emissions
RBW=1MHz, VBW=1/T and Peak detector

3.2.3 Test Setup

Radiated Emissions below 1 GHz




Radiated Emissions above 1 GHz



3.2.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal		




The graph displays the radiated unwanted emissions of a transmitter below 1 GHz. The y-axis represents the emission level in dBuV/m, ranging from 0 to 90. The x-axis represents the frequency in MHz, ranging from 30 to 1000. A red line indicates the FCC CLASS-B limit, which is 40 dBuV/m from 30 to 100 MHz, 45 dBuV/m from 100 to 1000 MHz, and 55 dBuV/m at 1000 MHz. A blue line shows the measured emission level, with six specific peaks labeled 1 through 6. The emission level generally increases with frequency, staying below the FCC limit.

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	96.93	28.72	43.50	-14.78	42.05	-13.33	Peak	---	---
2	140.58	28.79	43.50	-14.71	37.65	-8.86	Peak	---	---
3	243.40	27.52	46.00	-18.48	37.55	-10.03	Peak	---	---
4	309.36	24.98	46.00	-21.02	32.74	-7.76	Peak	---	---
5	505.30	29.22	46.00	-16.78	32.15	-2.93	Peak	---	---
6	993.21	37.15	54.00	-16.85	31.95	5.20	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	42.61	34.85	40.00	-5.15	43.11	-8.26	Peak	---	---
2	92.08	34.14	43.50	-9.36	48.21	-14.07	Peak	---	---
3	140.58	28.48	43.50	-15.02	37.34	-8.86	Peak	---	---
4	249.22	25.11	46.00	-20.89	35.07	-9.96	Peak	---	---
5	439.34	28.81	46.00	-17.19	33.15	-4.34	Peak	---	---
6	959.26	37.41	46.00	-8.59	32.58	4.83	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)


*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

3.2.5 Transmitter Radiated Unwanted Emissions (Above 1GHz) for GFSK

Modulation	GFSK		Test Freq. (MHz)		2402	
Polarization	Horizontal					



	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn
	MHz	level			reading			High	Table
		dBuV/m	dBuV/m	dB	dBuV	dB		cm	deg
1	2390.00	38.37	54.00	-15.63	41.19	-2.82	Average	121	40
2	2390.00	51.78	74.00	-22.22	54.60	-2.82	Peak	121	40
3 *	2402.00	69.16			72.00	-2.84	Average	121	40
4 *	2402.00	99.26			102.10	-2.84	Peak	121	40
5	4804.00	15.28	54.00	-38.72	11.76	3.52	Average	122	33
6	4804.00	45.38	74.00	-28.62	41.86	3.52	Peak	122	33
7	12010.00	27.49	54.00	-26.51	13.69	13.80	Average	129	44
8	12010.00	57.59	74.00	-16.41	43.79	13.80	Peak	129	44


Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Note 3: "*" is Peak / Average value of fundamental frequency


Modulation	GFSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.76	54.00	-15.24	41.58	-2.82	Average	100	94
2	2390.00	51.22	74.00	-22.78	54.04	-2.82	Peak	100	94
3 *	2402.00	58.89			61.73	-2.84	Average	100	94
4 *	2402.00	88.99			91.83	-2.84	Peak	100	94
5	4804.00	15.08	54.00	-38.92	11.56	3.52	Average	109	91
6	4804.00	45.18	74.00	-28.82	41.66	3.52	Peak	109	91
7	12010.00	27.07	54.00	-26.93	13.27	13.80	Average	100	88
8	12010.00	57.17	74.00	-16.83	43.37	13.80	Peak	100	88

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).
Note 3: "*" is Peak / Average value of fundamental frequency


Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Horizontal		



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.75	54.00	-15.25	41.57	-2.82	Average	121	40
2	2390.00	51.83	74.00	-22.17	54.65	-2.82	Peak	121	40
3 *	2441.00	70.44			73.31	-2.87	Average	121	40
4 *	2441.00	100.54			103.41	-2.87	Peak	121	40
5	2483.50	38.28	54.00	-15.72	41.24	-2.96	Average	121	40
6	2483.50	51.92	74.00	-22.08	54.88	-2.96	Peak	121	40
7	4882.00	15.43	54.00	-38.57	11.84	3.59	Average	106	54
8	4882.00	45.53	74.00	-28.47	41.94	3.59	Peak	106	54
9	7323.00	21.89	54.00	-32.11	12.74	9.15	Average	109	61
10	7323.00	51.99	74.00	-22.01	42.84	9.15	Peak	109	61

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency

Modulation	GFSK	Test Freq. (MHz)	2441
Polarization	Vertical		



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.61	54.00	-15.39	41.43	-2.82	Average	104	85
2	2390.00	51.12	74.00	-22.88	53.94	-2.82	Peak	104	85
3 *	2441.00	59.46			62.33	-2.87	Average	104	85
4 *	2441.00	89.56			92.43	-2.87	Peak	104	85
5	2483.50	38.11	54.00	-15.89	41.07	-2.96	Average	104	85
6	2483.50	51.71	74.00	-22.29	54.67	-2.96	Peak	104	85
7	4882.00	15.39	54.00	-38.61	11.80	3.59	Average	105	35
8	4882.00	45.49	74.00	-28.51	41.90	3.59	Peak	105	35
9	7323.00	22.16	54.00	-31.84	13.01	9.15	Average	110	29
10	7323.00	52.26	74.00	-21.74	43.11	9.15	Peak	110	29


Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).
Note 3: "*" is Peak / Average value of fundamental frequency

Modulation		GFSK			Test Freq. (MHz)		2480			
Polarization		Horizontal								
Level (dBUV/m)										

Modulation		GFSK			Test Freq. (MHz)		2480			
Polarization		Vertical								
Level (dBuV/m)										

3.2.6 Transmitter Radiated Unwanted Emissions (Above 1GHz) for 8DPSK


Modulation	8DPSK		Test Freq. (MHz)		2402	
Polarization	Horizontal					



	Freq. MHz	Emission level dBUV/m	Limit dBUV/m	Margin dB	SA reading dBUV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.46	54.00	-15.54	41.28	-2.82	Average	125	38
2	2390.00	51.84	74.00	-22.16	54.66	-2.82	Peak	125	38
3 *	2402.00	70.26			73.10	-2.84	Average	125	38
4 *	2402.00	100.36			103.20	-2.84	Peak	125	38
5	4804.00	15.36	54.00	-38.64	11.84	3.52	Average	122	35
6	4804.00	45.46	74.00	-28.54	41.94	3.52	Peak	122	35
7	12010.00	27.55	54.00	-26.45	13.75	13.80	Average	126	43
8	12010.00	57.65	74.00	-16.35	43.85	13.80	Peak	126	43

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).
Note 3: "*" is Peak / Average value of fundamental frequency

Modulation	8DPSK	Test Freq. (MHz)	2402
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.81	54.00	-15.19	41.63	-2.82	Average	100	98
2	2390.00	51.35	74.00	-22.65	54.17	-2.82	Peak	100	98
3 *	2402.00	59.26			62.10	-2.84	Average	100	98
4 *	2402.00	89.36			92.20	-2.84	Peak	100	98
5	4804.00	15.14	54.00	-38.86	11.62	3.52	Average	112	96
6	4804.00	45.24	74.00	-28.76	41.72	3.52	Peak	112	96
7	12010.00	27.12	54.00	-26.88	13.32	13.80	Average	100	91
8	12010.00	57.22	74.00	-16.78	43.42	13.80	Peak	100	91


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency

Modulation	8DPSK	Test Freq. (MHz)	2441
Polarization	Horizontal		

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.79	54.00	-15.21	41.61	-2.82	Average	121	42
2	2390.00	51.92	74.00	-22.08	54.74	-2.82	Peak	121	42
3 *	2441.00	70.84			73.71	-2.87	Average	121	42
4 *	2441.00	100.94			103.81	-2.87	Peak	121	42
5	2483.50	38.44	54.00	-15.56	41.40	-2.96	Average	121	42
6	2483.50	51.96	74.00	-22.04	54.92	-2.96	Peak	121	42
7	4882.00	15.53	54.00	-38.47	11.94	3.59	Average	109	56
8	4882.00	45.63	74.00	-28.37	42.04	3.59	Peak	109	56
9	7323.00	22.14	54.00	-31.86	12.99	9.15	Average	113	59
10	7323.00	52.24	74.00	-21.76	43.09	9.15	Peak	113	59

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
 Note 3: "*" is Peak / Average value of fundamental frequency


Modulation	8DPSK	Test Freq. (MHz)	2441
Polarization	Vertical		



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	2390.00	38.76	54.00	-15.24	41.58	-2.82	Average	104	91
2	2390.00	51.25	74.00	-22.75	54.07	-2.82	Peak	104	91
3 *	2441.00	59.85			62.72	-2.87	Average	104	91
4 *	2441.00	89.95			92.82	-2.87	Peak	104	91
5	2483.50	38.26	54.00	-15.74	41.22	-2.96	Average	104	91
6	2483.50	51.84	74.00	-22.16	54.80	-2.96	Peak	104	91
7	4882.00	15.56	54.00	-38.44	11.97	3.59	Average	108	42
8	4882.00	45.66	74.00	-28.34	42.07	3.59	Peak	108	42
9	7323.00	22.31	54.00	-31.69	13.16	9.15	Average	110	36
10	7323.00	52.41	74.00	-21.59	43.26	9.15	Peak	110	36

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).
Note 3: "*" is Peak / Average value of fundamental frequency

Modulation	8DPSK	Test Freq. (MHz)	2480
Polarization	Horizontal		



	Freq.	Emission	Limit	Margin	SA	Factor	Remark	ANT	Turn
	MHz	level	dBuV/m	dB	reading	dB		High	Table
					dBuV			cm	deg
1	*	2480.00	70.25		73.20	-2.95	Average	131	52
2	*	2480.00	100.35		103.30	-2.95	Peak	131	52
3		2483.50	39.26	54.00	42.22	-2.96	Average	131	52
4		2483.50	52.54	74.00	55.50	-2.96	Peak	131	52
5		4960.00	15.71	54.00	11.90	3.81	Average	132	36
6		4960.00	45.81	74.00	42.00	3.81	Peak	132	36
7		7440.00	22.86	54.00	13.93	8.93	Average	125	51
8		7440.00	52.96	74.00	44.03	8.93	Peak	125	51

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Note 3: "*" is Peak / Average value of fundamental frequency

Modulation	8DPSK			Test Freq. (MHz)	2480				
Polarization	Vertical								

		Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	*	2480.00	60.11			63.06	-2.95	Average	109	84
2	*	2480.00	90.21			93.16	-2.95	Peak	109	84
3		2483.50	38.24	54.00	-15.76	41.20	-2.96	Average	109	84
4		2483.50	52.16	74.00	-21.84	55.12	-2.96	Peak	109	84
5		4960.00	15.37	54.00	-38.63	11.56	3.81	Average	103	102
6		4960.00	45.47	74.00	-28.53	41.66	3.81	Peak	103	102
7		7440.00	22.33	54.00	-31.67	13.40	8.93	Average	100	91
8		7440.00	52.43	74.00	-21.57	43.50	8.93	Peak	100	91

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Note 3: "*" is Peak / Average value of fundamental frequency

3.3 Unwanted Emissions into Non-Restricted Frequency Bands

3.3.1 Limit of Unwanted Emissions into Non-Restricted Frequency Bands

Peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

3.3.2 Test Procedures


Reference level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Use the peak marker function to determine the maximum PSD level


Emission level measurement

1. Set RBW=100kHz, VBW = 300kHz , Detector = Peak, Sweep time = Auto
2. Trace = max hold , Allow Trace to fully stabilize
3. Scan Frequency range is up to 25GHz
4. Use the peak marker function to determine the maximum amplitude level

3.3.3 Test Setup




3.3.4 Unwanted Emissions into Non-Restricted Frequency Bands



BT-EDR(2Mbps)

CSE NdB


2402MHz



BT-EDR(2Mbps)

CSE NdB


2441MHz



BT-EDR(2Mbps)

CSE NdB


2480MHz



BT-EDR(3Mbps)

CSE NdB


2402MHz



BT-EDR(3Mbps)

CSE NdB


2441MHz



BT-EDR(3Mbps)

CSE NdB


2480MHz



BT-BR(1Mbps)

2441MHz


Hopping Ch Bandedge (Non-restricted Band)



BT-EDR(2Mbps)

2441MHz


Hopping Ch Bandedge (Non-restricted Band)



BT-EDR(3Mbps)

2441MHz

Hopping Ch Bandedge (Non-restricted Band)



3.4 Conducted Output Power


3.4.1 Limit of Conducted Output Power

- ☐ 1 Watt
For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band.
- ☒ 0.125 Watt
For all other frequency hopping systems in the 2400–2483.5 MHz band.
- ☐ 0.125 Watt
For Frequency hopping systems operating in the 2400–2483.5 MHz band have hopping channel carrier frequencies that are separated by two-thirds of the 20 dB bandwidth of the hopping channel.

3.4.2 Test Procedures

1. A wideband power meter is used for power measurement. Bandwidth of power sensor and meter is 50MHz
2. If duty cycle of test signal is not 100 %, trigger and gating function of power meter will be enabled to capture transmission burst for measuring output power

3.4.3 Test Setup



3.4.4 Test Result of Conducted Output Power

Summary of Peak Conducted Output Power

Mode	Power (dBm)	Power (W)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	3.26	0.00212
BT-EDR(2Mbps)	4.43	0.00277
BT-EDR(3Mbps)	4.48	0.00281

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	4.00	1.83	21.00
2441MHz	Pass	4.00	1.63	21.00
2480MHz	Pass	4.00	3.26	21.00
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	4.00	2.94	21.00
2441MHz	Pass	4.00	2.81	21.00
2480MHz	Pass	4.00	4.43	21.00
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	4.00	3.03	21.00
2441MHz	Pass	4.00	2.92	21.00
2480MHz	Pass	4.00	4.48	21.00

Summary of Conducted (Average) Output Power

Mode	Power	Power
	(dBm)	(W)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	2.89	0.00195
BT-EDR(2Mbps)	2.64	0.00184
BT-EDR(3Mbps)	2.63	0.00183

Result

Mode	Result	Gain (dBi)	Power (dBm)	Power Limit (dBm)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	4.00	1.44	-
2441MHz	Pass	4.00	1.29	-
2480MHz	Pass	4.00	2.89	-
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	4.00	1.21	-
2441MHz	Pass	4.00	1.02	-
2480MHz	Pass	4.00	2.64	-
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	4.00	1.20	-
2441MHz	Pass	4.00	1.02	-
2480MHz	Pass	4.00	2.63	-

Note: Average power is for reference only.

3.5 Number of Hopping Frequency


3.5.1 Limit of Number of Hopping Frequency

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

3.5.2 Test Procedures

1. Set RBW = 100kHz, VBW = 300kHz, Sweep time = Auto, Detector = Peak Trace max hold.
2. Allow trace to stabilize.

3.5.3 Test Setup



3.5.4 Test Result of Number of Hopping Frequency

Summary


Mode	Max-Hop No
2.4-2.4835GHz	-
BT-BR(1Mbps)	79
BT-EDR(2Mbps)	79
BT-EDR(3Mbps)	79

Result

Mode	Result	Hopping No	Limit
BT-BR(1Mbps)	-	-	-
2441MHz	Pass	79	15
BT-EDR(2Mbps)	-	-	-
2441MHz	Pass	79	15
BT-EDR(3Mbps)	-	-	-
2441MHz	Pass	79	15


BT-BR(1Mbps) 2441MHz

Hopping Ch




BT-EDR(2Mbps) 2441MHz

Hopping Ch



BT-EDR(3Mbps) 2441MHz

Hopping Ch



3.6 20dB and Occupied Bandwidth

3.6.1 Test Procedures


20dB Bandwidth

1. Set RBW=10kHz VBW= 30kHz for BT BR mode, RBW=20kHz, VBW=100kHz for other modes, Sweep time = Auto, Detector=Peak , Trace max hold
2. Allow trace to stabilize
3. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

1. Set RBW=10kHz VBW= 30kHz for BT BR mode, RBW=20kHz, VBW=100kHz for other modes, Sweep time = Auto, Detector=Sample , Trace max hold
2. Allow trace to stabilize
3. Use Occupied bandwidth function of spectrum analyzer to measuring 99% occupied bandwidth

3.6.2 Test Setup



3.6.3 Test result of 20dB and Occupied Bandwidth

Summary

Mode	Max-N dB (Hz)	Max-OBW (Hz)	ITU-Code	Min-N dB (Hz)	Min-OBW (Hz)
2.4-2.4835GHz	-	-	-	-	-
BT-BR(1Mbps)	931.159k	886.397k	886KF1D	931.159k	879.161k
BT-EDR(2Mbps)	1.333M	1.198M	1M20G1D	1.279M	1.179M
BT-EDR(3Mbps)	1.257M	1.212M	1M21G1D	1.257M	1.198M

Max-N dB = Maximum 20dB down bandwidth; **Max-OBW** = Maximum 99% occupied bandwidth;

Min-N dB = Minimum 20dB down bandwidth; **Min-OBW** = Minimum 99% occupied bandwidth;

Result


Mode	Result	Limit (Hz)	Port 1-N dB (Hz)	Port 1-OBW (Hz)
BT-BR(1Mbps)	-	-	-	-
2402MHz	Pass	Inf	931.159k	886.397k
2441MHz	Pass	Inf	931.159k	886.397k
2480MHz	Pass	Inf	931.159k	879.161k
BT-EDR(2Mbps)	-	-	-	-
2402MHz	Pass	Inf	1.312M	1.19M
2441MHz	Pass	Inf	1.333M	1.179M
2480MHz	Pass	Inf	1.279M	1.198M
BT-EDR(3Mbps)	-	-	-	-
2402MHz	Pass	Inf	1.257M	1.212M
2441MHz	Pass	Inf	1.257M	1.198M
2480MHz	Pass	Inf	1.257M	1.201M

Port X-N dB = Port X 20dB down bandwidth; **Port X-OBW** = Port X 99% occupied bandwidth;

BT-BR(1Mbps)

EBW


2402MHz



BT-BR(1Mbps)

EBW


2441MHz



BT-BR(1Mbps)

EBW


2480MHz



BT-EDR(2Mbps)

EBW


2402MHz



BT-EDR(2Mbps)

EBW


2441MHz



BT-EDR(2Mbps)

EBW


2480MHz



BT-EDR(3Mbps)

EBW


2402MHz



BT-EDR(3Mbps)

EBW


2441MHz



BT-EDR(3Mbps)

EBW

2480MHz



3.7 Channel Separation


3.7.1 Limit of Channel Separation

- ☐ Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.
- ☒ Frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

3.7.2 Test Procedures

1. Set RBW=30kHz, VBW=100kHz, Sweep time = Auto, Detector=Peak Trace max hold
2. Allow trace to stabilize
3. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The EUT shall show compliance with the appropriate regulatory limit

3.7.3 Test Setup



3.7.4 Test result of Channel Separation

Summary

Mode	Max-Space (Hz)	Min-Space (Hz)
2.4-2.4835GHz	-	-
BT-BR(1Mbps)	1.004348M	1M
BT-EDR(2Mbps)	1.004348M	1M
BT-EDR(3Mbps)	1.178261M	1M

Result

Mode	Result	Fl (Hz)	Fh (Hz)	Ch.Space (Hz)	Limit (Hz)
BT-BR(1Mbps)	-	-	-	-	-
2402MHz	Pass	2.402161G	2.403161G	1M	620.151894k
2441MHz	Pass	2.441161G	2.442161G	1M	620.151894k
2480MHz	Pass	2.479157G	2.480161G	1.004348M	620.151894k
BT-EDR(2Mbps)	-	-	-	-	-
2402MHz	Pass	2.401983G	2.402987G	1.004348M	873.792k
2441MHz	Pass	2.440983G	2.441987G	1.004348M	887.778k
2480MHz	Pass	2.478983G	2.479983G	1M	851.814k
BT-EDR(3Mbps)	-	-	-	-	-
2402MHz	Pass	2.401983G	2.403161G	1.178261M	837.162k
2441MHz	Pass	2.440983G	2.441983G	1M	837.162k
2480MHz	Pass	2.478983G	2.479983G	1M	837.162k

BT-BR(1Mbps)

Channel Separation

2.402G/2.403GHz



BT-BR(1Mbps)

Channel Separation

2.441G/2.442GHz



BT-BR(1Mbps)

Channel Separation


2.48G/2.479GHz



BT-EDR(2Mbps)

Channel Separation


2.402G/2.403GHz



BT-EDR(2Mbps)

Channel Separation


2.441G/2.442GHz



BT-EDR(2Mbps)

Channel Separation


2.48G/2.479GHz



BT-EDR(3Mbps)

Channel Separation


2.402G/2.403GHz



BT-EDR(3Mbps)

Channel Separation


2.441G/2.442GHz



BT-EDR(3Mbps)

Channel Separation

2.48G/2.479GHz



3.8 Number of Dwell Time


3.8.1 Limit of Dwell time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

3.8.2 Test Procedures

1. Set RBW=300kHz,VBW=1MHz,Sweep time = 10 ms, Detector=Peak, Span=0Hz,Trace max hold
2. Enable gating and trigger function of spectrum analyzer to measure burst on time.
3. The DH1 packet can cover a single time slot. A maximum length packet has duration of 1 time slots.
Non AFH mode
The hopping rate is 1600 hops/second so the maximum dwell time is 1/1600 seconds. DH1 Packet permit maximum $1600 / 79 / 2 = 10.12$ hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $10.12 \times 31.6 = 320$ within 31.6 seconds.
AFH mode
The hopping rate is 800 hops/second so the maximum dwell time is 1/800 seconds. DH1 Packet permit maximum $800 / 20 / 2 = 20$ hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $20 \times 8 = 160$ within 8 seconds.
4. The DH3 packet can cover up to 3 time slots. A maximum length packet has duration of 3 time slots.
Non AFH mode
The hopping rate is 1600 hops/second so the maximum dwell time is 3/1600 seconds. DH3 Packet permit maximum $1600 / 79 / 4 = 5.06$ hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $5.06 \times 31.6 = 160$ within 31.6 seconds.
AFH mode
The hopping rate is 800hops/second so the maximum dwell time is 3/800 seconds. DH3 Packet permit maximum $800 / 20 / 4 = 10$ hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $10 \times 8 = 80$ within 8 seconds.
5. The DH5 packet can cover up to 5 time slots. Operate DH5 at maximum dwell time and maximum duty cycle. A maximum length packet has duration of 5 time slots.
Non AFH mode
The hopping rate is 1600 hops/second so the maximum dwell time is 5/1600 seconds, or 3.125ms. DH5 Packet permit maximum $1600 / 79 / 6 = 3.37$ hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $3.37 \times 31.6 = 106.6$ within 31.6 seconds
AFH mode
The hopping rate is 800 hops/second so the maximum dwell time is 5/800 seconds. DH5 Packet permit maximum $800 / 20 / 6 = 6.667$ hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $6.667 \times 8 = 53.33$ within 8 seconds

3.8.3 Test Setup



3.8.4 Test Result of Dwell Time

Summary

Mode	Max-Dwell (s)
2.4-2.4835GHz	-
BT-BR(1Mbps)	310.530435m_DH5
BT-EDR(2Mbps)	312.075362m_DH5
BT-EDR(3Mbps)	312.075362m_DH5

Result/ Non AFH mode

Mode	Result	Period (s)	Dwell (s)	Limit (s)	Tx On (s)
BT-BR(1Mbps)	-	-	-	-	-
2441MHz	Pass	31.6	310.530435m_DH5	400m	2.913043m
2441MHz	Pass	31.6	266.666667m_DH3	400m	1.666667m
2441MHz	Pass	31.6	129.855072m_DH1	400m	405.797101u
BT-EDR(2Mbps)	-	-	-	-	-
2441MHz	Pass	31.6	312.075362m_DH5	400m	2.927536m
2441MHz	Pass	31.6	268.985507m_DH3	400m	1.681159m
2441MHz	Pass	31.6	134.492754m_DH1	400m	420.289855u
BT-EDR(3Mbps)	-	-	-	-	-
2441MHz	Pass	31.6	312.075362m_DH5	400m	2.927536m
2441MHz	Pass	31.6	266.666667m_DH3	400m	1.666667m
2441MHz	Pass	31.6	134.492754m_DH1	400m	420.289855u


Result/ AFH mode

Mode	Result	Period (s)	Dwell (s)	Limit (s)	Tx On (s)
BT-BR(1Mbps)	-	-	-	-	-
2441MHz	Pass	8	155.3526m_DH5	400m	2.913043m
2441MHz	Pass	8	133.3334m_DH3	400m	1.666667m
2441MHz	Pass	8	64.92754m_DH1	400m	405.797101u
BT-EDR(2Mbps)	-	-	-	-	-
2441MHz	Pass	8	156.1255m_DH5	400m	2.927536m
2441MHz	Pass	8	134.4927m_DH3	400m	1.681159m
2441MHz	Pass	8	67.24638m_DH1	400m	420.289855u
BT-EDR(3Mbps)	-	-	-	-	-
2441MHz	Pass	8	156.1255m_DH5	400m	2.927536m
2441MHz	Pass	8	133.3334m_DH3	400m	1.666667m
2441MHz	Pass	8	67.24638m_DH1	400m	420.289855u

BT-BR(1Mbps)

Dwell

2441MHz




DH5

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	310.530435m	400m	2.913043m

BT-BR(1Mbps)

Dwell

2441MHz




DH3

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	266.666667m	400m	1.666667m

BT-BR(1Mbps)

Dwell

2441MHz




DH1

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	129.855072m	400m	405.797101u

BT-EDR(2Mbps)

Dwell

2441MHz



Port 1 

Ch Freq
2.441GHz

RBW
300kHz

VBW
1MHz

Sweep Time
10ms

TX Time
2.927536ms


DH5

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	312.075362m	400m	2.927536m

BT-EDR(2Mbps)

Dwell

2441MHz



Port 1 

Ch Freq
2.441GHz

RBW
300kHz

VBW
1MHz

Sweep Time
10ms

TX Time
1.681159ms


DH3

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	268.985507m	400m	1.681159m

BT-EDR(2Mbps)

Dwell

2441MHz



Port 1 

Ch Freq
2.441GHz

RBW
300kHz

VBW
1MHz

Sweep Time
10ms

TX Time
420.289855us


DH1

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	134.492754m	400m	420.289855u

BT-EDR(3Mbps)

Dwell

2441MHz



Port 1 

Ch Freq
2.441GHz

RBW
300kHz

VBW
1MHz

Sweep Time
10ms

TX Time
2.927536ms


DH5

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	312.075362m	400m	2.927536m

BT-EDR(3Mbps)

Dwell

2441MHz



Port 1 

Ch Freq
2.441GHz

RBW
300kHz

VBW
1MHz

Sweep Time
10ms

TX Time
1.666667ms


DH3

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	266.666667m	400m	1.666667m

BT-EDR(3Mbps)

Dwell

2441MHz



Port 1 

Ch Freq
2.441GHz

RBW
300kHz

VBW
1MHz

Sweep Time
10ms

TX Time
420.289855us

DH1

Period(s)	Dwell(s)	Limit(s)	Tx On(s)
31.6	134.492754m	400m	420.289855u

4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==