

# FCC Co-Location Test Report

**FCC ID** : I88WAC6502D-E  
**Equipment** : 802.11 ac Unified Pro Access Point  
**Model No.** : WAC6502D-S, WAC6502D-E  
**Brand Name** : ZyXEL  
**Applicant** : ZyXEL Communications Corporation  
**Address** : No. 2, Gongye E. 9th Road, Hsinchu Science  
Park, Hsinchu, Taiwan  
**Standard** : 47 CFR FCC Part 15.247  
47 CFR FCC Part 15.407  
**Received Date** : Dec. 03, 2015  
**Tested Date** : Dec. 25 ~ Dec. 31, 2015

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Approved & Reviewed by:

  
\_\_\_\_\_  
Gary Chang / Manager



---

## Table of Contents

|          |                                                          |           |
|----------|----------------------------------------------------------|-----------|
| <b>1</b> | <b>GENERAL DESCRIPTION .....</b>                         | <b>5</b>  |
| 1.1      | Information.....                                         | 5         |
| 1.2      | The Equipment List .....                                 | 7         |
| 1.3      | Test Standards .....                                     | 7         |
| 1.4      | Measurement Uncertainty .....                            | 8         |
| <b>2</b> | <b>TEST CONFIGURATION .....</b>                          | <b>9</b>  |
| 2.1      | Testing Condition .....                                  | 9         |
| 2.2      | The Worst Test Modes and Channel Details .....           | 9         |
| <b>3</b> | <b>TRANSMITTER TEST RESULTS.....</b>                     | <b>10</b> |
| 3.1      | Unwanted Emissions into Restricted Frequency Bands ..... | 10        |
| <b>4</b> | <b>TEST LABORATORY INFORMATION .....</b>                 | <b>24</b> |

---

## Release Record

| Report No. | Version | Description   | Issued Date   |
|------------|---------|---------------|---------------|
| FR5D0302CO | Rev. 01 | Initial issue | Mar. 31, 2016 |

## Summary of Test Results

| FCC Rules                        | Test Items         | Measured                                                  | Result |
|----------------------------------|--------------------|-----------------------------------------------------------|--------|
| 15.247(d)<br>15.407(b)<br>15.209 | Radiated Emissions | [dBuV/m at 3m]: 2793.00MHz<br>52.68 (Margin -1.32dB) – AV | Pass   |

# 1 General Description

## 1.1 Information

This report is prepared for FCC class II Permissive change.

This report is issued as a supplementary report to the original ICC project no. 491801. The modification is concerned as complying with New U-NII rule requirement.

### 1.1.1 Product Details

The following models are provided to this EUT.

| Brand Name | Model Name | Product Name                       | Description           |
|------------|------------|------------------------------------|-----------------------|
| ZyXEL      | WAC6502D-S | 802.11 ac Unified Pro Access Point | With internal antenna |
|            | WAC6502D-E |                                    | With external antenna |

### 1.1.2 Specification

|                            |                                                                                                                                                  |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Operating Frequency</b> | 802.11b/g/n:<br>2412 MHz ~ 2462 MHz<br>802.11a/n/ac:<br>5180 MHz ~ 5240 MHz<br>5260 MHz ~ 5320 MHz<br>5500 MHz ~ 5700 MHz<br>5745 MHz ~ 5825 MHz |
| <b>Modulation Type</b>     | 802.11b: DSSS (DBPSK / DQPSK / CCK)<br>802.11a/g/n/ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)                                               |

### 1.1.3 Antenna Details

| Ant. No. | Type   | Antenna Connector | Operating Frequencies (MHz) / Antenna Gain (dBi) |           |           |           |           | Remark         |
|----------|--------|-------------------|--------------------------------------------------|-----------|-----------|-----------|-----------|----------------|
|          |        |                   | 2400~2483.5                                      | 5150~5250 | 5250~5350 | 5470~5725 | 5725~5850 |                |
| 1        | Dipole | RSMA              | 5                                                | 7         | 7         | 7         | 7         | For WAC6502D-E |
| 2        | Dipole | IPEX              | 4                                                | 6         | 6         | 6         | 6         | For WAC6502D-S |

**Note:**

- The antenna connector of PCB board of EUT is IPEX.
- WAC6502D-E has a RSMA connector jack to connect antenna and PCB board of EUT.

#### 1.1.4 Power Supply Type of Equipment under Test (EUT)

|                          |                                                                                                                                                                               |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Power Supply Type</b> | 1. AC Adapter (support unit only.)<br>Brand: DVE<br>Model: DSA-24CA-12 120120<br>Rating:<br>I/P: 100-240Vac, 50/60Hz, 0.8A<br>O/P: 12Vdc, 2A                                  |
|                          | 2. POE Injector (support unit for radiated emission test only.)<br>Brand: ZyXEL<br>Model: PoE12-HP<br>Rating:<br>I/P: 100-240V~, 50/60Hz, 1.5A max.<br>O/P: 48Vdc, 42.1W      |
|                          | 3. POE Injector (support unit for conducted emission only.)<br>Brand: PowerDsine 3001GC<br>Model: E018205D G<br>Rating:<br>I/P: 100-240V~, 50/60Hz, 0.5A<br>O/P: 48Vdc, 0.35A |

#### 1.1.5 Accessories

N/A

## 1.2 The Equipment List

| Test Item                                                           | Radiated Emission          |             |                  |                  |                   |
|---------------------------------------------------------------------|----------------------------|-------------|------------------|------------------|-------------------|
| Test Site                                                           | 966 chamber1 / (03CH01-WS) |             |                  |                  |                   |
| Instrument                                                          | Manufacturer               | Model No.   | Serial No.       | Calibration Date | Calibration Until |
| Spectrum Analyzer                                                   | R&S                        | FSV40       | 101498           | Dec. 13, 2015    | Dec. 12, 2016     |
| Receiver                                                            | R&S                        | ESR3        | 101658           | Nov. 04, 2015    | Nov. 03, 2016     |
| Bilog Antenna                                                       | SCHWARZBECK                | VULB9168    | VULB9168-522     | Aug. 20, 2015    | Aug. 19, 2016     |
| Horn Antenna<br>1G-18G                                              | SCHWARZBECK                | BBHA 9120 D | BBHA 9120 D 1096 | Dec. 16, 2015    | Dec. 15, 2016     |
| Horn Antenna<br>18G-40G                                             | SCHWARZBECK                | BBHA 9170   | BBHA 9170517     | Nov. 04, 2015    | Nov. 03, 2016     |
| Loop Antenna                                                        | R&S                        | HFH2-Z2     | 11900            | Nov. 16, 2015    | Nov. 15, 2016     |
| Loop Antenna Cable                                                  | KOAX KABEL                 | 101354-BW   | 101354-BW        | Dec. 10, 2015    | Dec. 09, 2016     |
| Preamplifier                                                        | Burgeon                    | BPA-530     | SN:100219        | Sep. 10, 2015    | Sep. 09, 2016     |
| Preamplifier                                                        | Agilent                    | 83017A      | MY39501308       | Oct. 02, 2015    | Oct. 01, 2016     |
| Preamplifier                                                        | EMC                        | EMC184045B  | 980192           | Sep. 01, 2015    | Aug. 31, 2016     |
| RF Cable                                                            | HUBER+SUHNER               | SUCOFLEX104 | MY16014/4        | Dec. 10, 2015    | Dec. 09, 2016     |
| RF Cable                                                            | HUBER+SUHNER               | SUCOFLEX104 | MY16019/4        | Dec. 10, 2015    | Dec. 09, 2016     |
| RF Cable                                                            | HUBER+SUHNER               | SUCOFLEX104 | MY16139/4        | Dec. 10, 2015    | Dec. 09, 2016     |
| LF cable 3M                                                         | Woken                      | CFD400NL-LW | CFD400NL-001     | Dec. 10, 2015    | Dec. 09, 2016     |
| LF cable 10M                                                        | Woken                      | CFD400NL-LW | CFD400NL-002     | Dec. 10, 2015    | Dec. 09, 2016     |
| Measurement<br>Software                                             | AUDIX                      | e3          | 6.120210g        | NA               | NA                |
| Note: Calibration Interval of instruments listed above is one year. |                            |             |                  |                  |                   |

## 1.3 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.247

47 CFR FCC Part 15.407

ANSI C63.10-2013

FCC KDB 558074 D01 DTS Meas Guidance v03r04

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r01

FCC KDB 644545 D03 Guidance for IEEE 802.11ac New Rules v01

FCC KDB 412172 D01 Determining ERP and EIRP v01r01

## 1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

| Measurement Uncertainty       |               |
|-------------------------------|---------------|
| Parameters                    | Uncertainty   |
| Radiated emission $\leq$ 1GHz | $\pm 3.66$ dB |
| Radiated emission $>$ 1GHz    | $\pm 5.63$ dB |



## 2 Test Configuration

### 2.1 Testing Condition

| Test Item          | Test Site | Ambient Condition | Tested By   |
|--------------------|-----------|-------------------|-------------|
| Radiated Emissions | 03CH01-WS | 22-23°C / 63%     | Vincent Yeh |

➤ FCC site registration No.: 657002

➤ IC site registration No.: 10807A-1

### 2.2 The Worst Test Modes and Channel Details

| Test item                | Modulation Mode          | Test Channel | Data rate (Mbps) / MCS | Test Configuration |
|--------------------------|--------------------------|--------------|------------------------|--------------------|
| Radiated Emissions ≤1GHz | 2.4G 11b + 5G 11ac VHT40 | CH6 + CH46   | 1Mbps + MCS 0          | 1, 2, 3, 4         |
| Radiated Emissions >1GHz | 2.4G 11b + 5G 11ac VHT40 | CH6 + CH46   | 1Mbps + MCS 0          | 2, 4               |

**NOTE:**

1. The following antennas are used on this EUT:
  - 1) Configuration 1: model WAC6502D-S, AC Adapter mode.
  - 2) Configuration 2: model WAC6502D-S, POE mode.
  - 3) Configuration 3: model WAC6502D-E, AC Adapter mode
  - 4) Configuration 4: model WAC6502D-E, POE mode
2. The selected channel is the maximum power channel of each Wi-Fi mode

### 3 Transmitter Test Results

#### 3.1 Unwanted Emissions into Restricted Frequency Bands

##### 3.1.1 Limit of Unwanted Emissions into Restricted Frequency Bands

| Restricted Band Emissions Limit |                       |                         |                      |
|---------------------------------|-----------------------|-------------------------|----------------------|
| Frequency Range (MHz)           | Field Strength (uV/m) | Field Strength (dBuV/m) | Measure Distance (m) |
| 0.009~0.490                     | 2400/F(kHz)           | 48.5 - 13.8             | 300                  |
| 0.490~1.705                     | 24000/F(kHz)          | 33.8 - 23               | 30                   |
| 1.705~30.0                      | 30                    | 29                      | 30                   |
| 30~88                           | 100                   | 40                      | 3                    |
| 88~216                          | 150                   | 43.5                    | 3                    |
| 216~960                         | 200                   | 46                      | 3                    |
| Above 960                       | 500                   | 54                      | 3                    |

**Note 1:**  
Qusai-Peak value is measured for frequency below 1GHz except for 9~90 kHz, 110~490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

**Note 2:**  
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

##### 3.1.2 Test Procedures


1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at test table. For emissions testing at or below 1 GHz, the table height is 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height is 1.5 m
2. Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


1. 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.
2. RBW=1MHz, VBW=3MHz and Peak detector is for peak measured value of radiated emission above 1GHz.
3. RBW=1MHz, VBW=1/T and Peak detector is for average measured value of radiated emission above 1GHz.

### 3.1.3 Test Setup

#### Radiated Emissions below 1 GHz




#### Radiated Emissions above 1 GHz



### Configuration 1: model WAC6502D-S, AC Adapter mode

#### 3.1.4 Transmitter Radiated Unwanted Emissions (Below 1GHz)

|              |                          |                    |            |
|--------------|--------------------------|--------------------|------------|
| Modulation   | 2.4G 11b + 5G 11ac VHT40 | Test Freq. (MHz)   | CH6 + CH46 |
| Polarization | Horizontal               | Test Configuration | 1          |



|   | Freq.<br>MHz | Emission<br>level<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | SA<br>reading<br>dBuV | Factor<br>dB | Remark | ANT<br>High<br>cm | Turn<br>Table<br>deg |
|---|--------------|-----------------------------|-----------------|--------------|-----------------------|--------------|--------|-------------------|----------------------|
| 1 | 65.68        | 27.62                       | 40.00           | -12.38       | 46.17                 | -18.55       | Peak   | ---               | ---                  |
| 2 | 125.25       | 29.74                       | 43.50           | -13.76       | 48.14                 | -18.40       | Peak   | ---               | ---                  |
| 3 | 183.44       | 30.75                       | 43.50           | -12.75       | 49.15                 | -18.40       | Peak   | ---               | ---                  |
| 4 | 375.46       | 31.72                       | 46.00           | -14.28       | 45.82                 | -14.10       | Peak   | ---               | ---                  |
| 5 | 485.82       | 36.25                       | 46.00           | -9.75        | 47.68                 | -11.43       | Peak   | ---               | ---                  |
| 6 | 625.64       | 30.67                       | 46.00           | -15.33       | 39.75                 | -9.08        | Peak   | ---               | ---                  |


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

|                     |                          |                           |            |
|---------------------|--------------------------|---------------------------|------------|
| <b>Modulation</b>   | 2.4G 11b + 5G 11ac VHT40 | <b>Test Freq. (MHz)</b>   | CH6 + CH46 |
| <b>Polarization</b> | Vertical                 | <b>Test Configuration</b> | 1          |



|   | Freq.<br>MHz | Emission<br>level<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | SA<br>reading<br>dBuV | Factor<br>dB | Remark | ANT<br>High<br>cm | Turn<br>Table<br>deg |
|---|--------------|-----------------------------|-----------------|--------------|-----------------------|--------------|--------|-------------------|----------------------|
| 1 | 64.88        | 32.85                       | 40.00           | -7.15        | 51.25                 | -18.40       | QP     | 110               | 139                  |
| 2 | 91.36        | 29.72                       | 43.50           | -13.78       | 52.48                 | -22.76       | Peak   | ---               | ---                  |
| 3 | 125.24       | 29.95                       | 43.50           | -13.55       | 48.35                 | -18.40       | Peak   | ---               | ---                  |
| 4 | 216.65       | 30.84                       | 46.00           | -15.16       | 49.96                 | -19.12       | Peak   | ---               | ---                  |
| 5 | 375.52       | 32.54                       | 46.00           | -13.46       | 46.64                 | -14.10       | Peak   | ---               | ---                  |
| 6 | 529.62       | 36.85                       | 46.00           | -9.15        | 47.58                 | -10.73       | Peak   | ---               | ---                  |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

## Configuration 2: model WAC6502D-S, POE mode

### 3.1.5 Transmitter Radiated Unwanted Emissions (Below 1GHz)

|              |                          |                    |            |
|--------------|--------------------------|--------------------|------------|
| Modulation   | 2.4G 11b + 5G 11ac VHT40 | Test Freq. (MHz)   | CH6 + CH46 |
| Polarization | Horizontal               | Test Configuration | 2          |



|   | Freq.<br>MHz | Emission<br>level<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | SA<br>reading<br>dBuV | Factor<br>dB | Remark | ANT<br>High<br>cm | Turn<br>Table<br>deg |
|---|--------------|-----------------------------|-----------------|--------------|-----------------------|--------------|--------|-------------------|----------------------|
| 1 | 91.24        | 30.26                       | 43.50           | -13.24       | 53.05                 | -22.79       | Peak   | ---               | ---                  |
| 2 | 125.14       | 32.23                       | 43.50           | -11.27       | 50.64                 | -18.41       | Peak   | ---               | ---                  |
| 3 | 155.24       | 30.45                       | 43.50           | -13.05       | 47.17                 | -16.72       | Peak   | ---               | ---                  |
| 4 | 375.34       | 30.26                       | 46.00           | -15.74       | 44.36                 | -14.10       | Peak   | ---               | ---                  |
| 5 | 489.68       | 34.42                       | 46.00           | -11.58       | 45.76                 | -11.34       | Peak   | ---               | ---                  |
| 6 | 625.65       | 30.91                       | 46.00           | -15.09       | 39.99                 | -9.08        | Peak   | ---               | ---                  |


Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

|                     |                          |                           |            |
|---------------------|--------------------------|---------------------------|------------|
| <b>Modulation</b>   | 2.4G 11b + 5G 11ac VHT40 | <b>Test Freq. (MHz)</b>   | CH6 + CH46 |
| <b>Polarization</b> | Vertical                 | <b>Test Configuration</b> | 2          |



|   | Freq.<br>MHz | Emission<br>level<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | SA<br>reading<br>dBuV | Factor<br>dB | Remark | ANT<br>High<br>cm | Turn<br>Table<br>deg |
|---|--------------|-----------------------------|-----------------|--------------|-----------------------|--------------|--------|-------------------|----------------------|
| 1 | 44.85        | 32.45                       | 40.00           | -7.55        | 48.78                 | -16.33       | QP     | 100               | 261                  |
| 2 | 91.28        | 30.92                       | 43.50           | -12.58       | 53.70                 | -22.78       | Peak   | ---               | ---                  |
| 3 | 192.85       | 29.65                       | 43.50           | -13.85       | 48.81                 | -19.16       | Peak   | ---               | ---                  |
| 4 | 489.65       | 37.12                       | 46.00           | -8.88        | 48.46                 | -11.34       | Peak   | ---               | ---                  |
| 5 | 531.53       | 38.43                       | 46.00           | -7.57        | 49.14                 | -10.71       | Peak   | ---               | ---                  |
| 6 | 625.65       | 30.52                       | 46.00           | -15.48       | 39.60                 | -9.08        | Peak   | ---               | ---                  |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

### 3.1.6 Transmitter Radiated Unwanted Emissions (Above 1GHz)

|              |                          |                    |            |
|--------------|--------------------------|--------------------|------------|
| Modulation   | 2.4G 11b + 5G 11ac VHT40 | Test Freq. (MHz)   | CH6 + CH46 |
| Polarization | Horizontal               | Test Configuration | 2          |


  


|   | Freq.<br>MHz | Emission<br>level<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | SA<br>reading<br>dBuV | Factor<br>dB | Remark  | ANT<br>High<br>cm | Turn<br>Table<br>deg |
|---|--------------|-----------------------------|-----------------|--------------|-----------------------|--------------|---------|-------------------|----------------------|
| 1 | 2793.00      | 52.68                       | 54.00           | -1.32        | 54.40                 | -1.72        | Average | ---               | ---                  |
| 2 | 2793.00      | 65.88                       | 74.00           | -8.12        | 67.60                 | -1.72        | Peak    | ---               | ---                  |
| 3 | 7667.00      | 45.69                       | 54.00           | -8.31        | 36.91                 | 8.78         | Average | ---               | ---                  |
| 4 | 7667.00      | 56.48                       | 74.00           | -17.52       | 47.70                 | 8.78         | Peak    | ---               | ---                  |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
\*Factor includes antenna factor , cable loss and amplifier gain  
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).



|                     |                          |                           |            |
|---------------------|--------------------------|---------------------------|------------|
| <b>Modulation</b>   | 2.4G 11b + 5G 11ac VHT40 | <b>Test Freq. (MHz)</b>   | CH6 + CH46 |
| <b>Polarization</b> | Vertical                 | <b>Test Configuration</b> | 2          |



|   | Freq.<br>MHz | Emission<br>level<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | SA<br>reading<br>dBuV | Factor<br>dB | Remark  | ANT<br>High<br>cm | Turn<br>Table<br>deg |
|---|--------------|-----------------------------|-----------------|--------------|-----------------------|--------------|---------|-------------------|----------------------|
| 1 | 2793.00      | 47.25                       | 54.00           | -6.75        | 48.97                 | -1.72        | Average | ---               | ---                  |
| 2 | 2793.00      | 58.96                       | 74.00           | -15.04       | 60.68                 | -1.72        | Peak    | ---               | ---                  |
| 3 | 7667.00      | 42.65                       | 54.00           | -11.35       | 33.87                 | 8.78         | Average | ---               | ---                  |
| 4 | 7667.00      | 52.84                       | 74.00           | -21.16       | 44.06                 | 8.78         | Peak    | ---               | ---                  |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

### Configuration 3: model WAC6502D-E, AC Adapter mode

#### 3.1.7 Transmitter Radiated Unwanted Emissions (Below 1GHz)

|              |                          |                    |            |
|--------------|--------------------------|--------------------|------------|
| Modulation   | 2.4G 11b + 5G 11ac VHT40 | Test Freq. (MHz)   | CH6 + CH46 |
| Polarization | Horizontal               | Test Configuration | 3          |


  


The graph displays the radiated unwanted emissions for the WAC6502D-E model in AC Adapter mode. The y-axis represents the Level in dBuV/m, ranging from 0 to 90. The x-axis represents the Frequency in MHz, ranging from 30 to 1000. A red line indicates the FCC CLASS-B limit, which is 40 dBuV/m from 30 MHz to 100 MHz, 45 dBuV/m from 100 MHz to 1000 MHz, and 70 dBuV/m at 1000 MHz. The blue line shows the measured emission level, with six specific peaks labeled 1 through 6. The table below provides the detailed data for these peaks.

|   | Freq.<br>MHz | Emission<br>level<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | SA<br>reading<br>dBuV | Factor<br>dB | Remark | ANT<br>High<br>cm | Turn<br>Table<br>deg |
|---|--------------|-----------------------------|-----------------|--------------|-----------------------|--------------|--------|-------------------|----------------------|
| 1 | 86.35        | 29.84                       | 40.00           | -10.16       | 52.20                 | -22.36       | Peak   | ---               | ---                  |
| 2 | 194.82       | 33.26                       | 43.50           | -10.24       | 52.45                 | -19.19       | Peak   | ---               | ---                  |
| 3 | 375.44       | 29.86                       | 46.00           | -16.14       | 43.96                 | -14.10       | Peak   | ---               | ---                  |
| 4 | 410.35       | 32.53                       | 46.00           | -13.47       | 45.69                 | -13.16       | Peak   | ---               | ---                  |
| 5 | 500.56       | 31.91                       | 46.00           | -14.09       | 43.02                 | -11.11       | Peak   | ---               | ---                  |
| 6 | 660.44       | 31.29                       | 46.00           | -14.71       | 39.83                 | -8.54        | Peak   | ---               | ---                  |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
\*Factor includes antenna factor , cable loss and amplifier gain  
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).  
Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

|                     |                          |                           |            |
|---------------------|--------------------------|---------------------------|------------|
| <b>Modulation</b>   | 2.4G 11b + 5G 11ac VHT40 | <b>Test Freq. (MHz)</b>   | CH6 + CH46 |
| <b>Polarization</b> | Vertical                 | <b>Test Configuration</b> | 3          |



|   | Freq.<br>MHz | Emission<br>level<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | SA<br>reading<br>dBuV | Factor<br>dB | Remark | ANT<br>High<br>cm | Turn<br>Table<br>deg |
|---|--------------|-----------------------------|-----------------|--------------|-----------------------|--------------|--------|-------------------|----------------------|
| 1 | 44.91        | 31.95                       | 40.00           | -8.05        | 48.27                 | -16.32       | QP     | 100               | 196                  |
| 2 | 91.24        | 29.95                       | 43.50           | -13.55       | 52.74                 | -22.79       | Peak   | ---               | ---                  |
| 3 | 196.88       | 29.63                       | 43.50           | -13.87       | 48.86                 | -19.23       | Peak   | ---               | ---                  |
| 4 | 375.44       | 30.81                       | 46.00           | -15.19       | 44.91                 | -14.10       | Peak   | ---               | ---                  |
| 5 | 470.45       | 33.43                       | 46.00           | -12.57       | 45.17                 | -11.74       | Peak   | ---               | ---                  |
| 6 | 600.46       | 27.82                       | 46.00           | -18.18       | 37.33                 | -9.51        | Peak   | ---               | ---                  |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain


Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

**Configuration 4: model WAC6502D-E, POE mode**

**3.1.8 Transmitter Radiated Unwanted Emissions (Below 1GHz)**

|                     |                          |                           |            |
|---------------------|--------------------------|---------------------------|------------|
| <b>Modulation</b>   | 2.4G 11b + 5G 11ac VHT40 | <b>Test Freq. (MHz)</b>   | CH6 + CH46 |
| <b>Polarization</b> | Horizontal               | <b>Test Configuration</b> | 4          |


  


The graph displays the emission level in dBuV/m across a frequency range from 30 MHz to 1000 MHz. A red line represents the FCC CLASS-B limit, which is 40 dBuV/m from 30 MHz to 100 MHz, 45 dBuV/m from 100 MHz to 1000 MHz, and 55 dBuV/m from 1000 MHz to 1100 MHz. Six peaks are identified and numbered 1 through 6, corresponding to the data in the table below.

|   | Freq.<br>MHz | Emission<br>level<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | SA<br>reading<br>dBuV | Factor<br>dB | Remark | ANT<br>High<br>cm | Turn<br>Table<br>deg |
|---|--------------|-----------------------------|-----------------|--------------|-----------------------|--------------|--------|-------------------|----------------------|
| 1 | 91.25        | 30.92                       | 43.50           | -12.58       | 53.70                 | -22.78       | Peak   | ---               | ---                  |
| 2 | 200.65       | 32.15                       | 43.50           | -11.35       | 51.44                 | -19.29       | Peak   | ---               | ---                  |
| 3 | 250.36       | 37.25                       | 46.00           | -8.75        | 54.96                 | -17.71       | Peak   | ---               | ---                  |
| 4 | 429.53       | 36.13                       | 46.00           | -9.87        | 48.81                 | -12.68       | Peak   | ---               | ---                  |
| 5 | 489.69       | 32.66                       | 46.00           | -13.34       | 44.00                 | -11.34       | Peak   | ---               | ---                  |
| 6 | 625.49       | 30.55                       | 46.00           | -15.45       | 39.63                 | -9.08        | Peak   | ---               | ---                  |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
 \*Factor includes antenna factor , cable loss and amplifier gain  
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).  
 Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

|                     |                          |                           |            |
|---------------------|--------------------------|---------------------------|------------|
| <b>Modulation</b>   | 2.4G 11b + 5G 11ac VHT40 | <b>Test Freq. (MHz)</b>   | CH6 + CH46 |
| <b>Polarization</b> | Vertical                 | <b>Test Configuration</b> | 4          |



|   | Freq.<br>MHz | Emission<br>level<br>dBUV/m | Limit<br>dBUV/m | Margin<br>dB | SA<br>reading<br>dBUV | Factor<br>dB | Remark | ANT<br>High<br>cm | Turn<br>Table<br>deg |
|---|--------------|-----------------------------|-----------------|--------------|-----------------------|--------------|--------|-------------------|----------------------|
| 1 | 44.58        | 34.79                       | 40.00           | -5.21        | 51.14                 | -16.35       | QP     | 106               | 18                   |
| 2 | 91.28        | 31.24                       | 43.50           | -12.26       | 54.02                 | -22.78       | Peak   | ---               | ---                  |
| 3 | 250.34       | 33.66                       | 46.00           | -12.34       | 51.37                 | -17.71       | Peak   | ---               | ---                  |
| 4 | 400.68       | 31.26                       | 46.00           | -14.74       | 44.66                 | -13.40       | Peak   | ---               | ---                  |
| 5 | 500.58       | 28.62                       | 46.00           | -17.38       | 39.73                 | -11.11       | Peak   | ---               | ---                  |
| 6 | 625.62       | 30.85                       | 46.00           | -15.15       | 39.93                 | -9.08        | Peak   | ---               | ---                  |

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor\* (dB)


\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

Note 3: All spurious emissions below 30MHz are more than 20 dB below the limit.

### 3.1.9 Transmitter Radiated Unwanted Emissions (Above 1GHz)


|              |                          |                    |            |
|--------------|--------------------------|--------------------|------------|
| Modulation   | 2.4G 11b + 5G 11ac VHT40 | Test Freq. (MHz)   | CH6 + CH46 |
| Polarization | Horizontal               | Test Configuration | 4          |

|   | Freq.<br>MHz | Emission<br>level<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | SA<br>reading<br>dBuV | Factor<br>dB | Remark  | ANT<br>High<br>cm | Turn<br>Table<br>deg |
|---|--------------|-----------------------------|-----------------|--------------|-----------------------|--------------|---------|-------------------|----------------------|
| 1 | 2793.00      | 28.36                       | 54.00           | -25.64       | 30.08                 | -1.72        | Average | ---               | ---                  |
| 2 | 2793.00      | 40.58                       | 74.00           | -33.42       | 42.30                 | -1.72        | Peak    | ---               | ---                  |
| 3 | 7667.00      | 38.24                       | 54.00           | -15.76       | 29.46                 | 8.78         | Average | ---               | ---                  |
| 4 | 7667.00      | 51.56                       | 74.00           | -22.44       | 42.78                 | 8.78         | Peak    | ---               | ---                  |

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor\* (dB)  
\*Factor includes antenna factor , cable loss and amplifier gain  
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

|                     |                          |                           |            |
|---------------------|--------------------------|---------------------------|------------|
| <b>Modulation</b>   | 2.4G 11b + 5G 11ac VHT40 | <b>Test Freq. (MHz)</b>   | CH6 + CH46 |
| <b>Polarization</b> | Vertical                 | <b>Test Configuration</b> | 4          |



|   | Freq.<br>MHz | Emission<br>level<br>dBUV/m | Limit<br>dBUV/m | Margin<br>dB | SA<br>reading<br>dBUV | Factor<br>dB | Remark  | ANT<br>High<br>cm | Turn<br>Table<br>deg |
|---|--------------|-----------------------------|-----------------|--------------|-----------------------|--------------|---------|-------------------|----------------------|
| 1 | 2793.00      | 33.45                       | 54.00           | -20.55       | 35.17                 | -1.72        | Average | ---               | ---                  |
| 2 | 2793.00      | 46.28                       | 74.00           | -27.72       | 48.00                 | -1.72        | Peak    | ---               | ---                  |
| 3 | 7667.00      | 38.56                       | 54.00           | -15.44       | 29.78                 | 8.78         | Average | ---               | ---                  |
| 4 | 7667.00      | 51.45                       | 74.00           | -22.55       | 42.67                 | 8.78         | Peak    | ---               | ---                  |

Note 1: Emission Level (dBUV/m) = SA Reading (dBUV/m) + Factor\* (dB)

\*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBUV/m) – Limit (dBUV/m).

## 4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp, it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan Hsiang. Location map can be found on our website <http://www.icertifi.com.tw>.

### **Linkou**

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin Kou  
District, New Taipei City, Taiwan,  
R.O.C.

### **Kwei Shan**

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd  
St., Kwei Shan Hsiang, Tao Yuan  
Hsien 333, Taiwan, R.O.C.

### **Kwei Shan Site II**

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd  
St., Kwei Shan Hsiang, Tao Yuan  
Hsien 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: [ICC\\_Service@icertifi.com.tw](mailto:ICC_Service@icertifi.com.tw)

==END==