

VIII. Measurement Results for AIS Extreme Physical Tests Cont'd:

2. Carrier Power at Damp Heat & High Supply Voltage.

High Specification: 40.96 +2/-3 dBm (12.5W +7.3W/-6.25W) Extreme Operation

Low Specification: 33.01 +2/-3 dBm (2W +1.2W/-1W) Extreme Operation



VIII. Measurement Results for AIS Extreme Physical Tests Cont'd:

2. Carrier Power at Vibration Vertical.

High Specification: 40.96 +2/-3 dBm (12.5W +7.3W/-6.25W) Extreme Operation

Low Specification: 33.01 +2/-3 dBm (2W +1.2W/-1W) Extreme Operation



VIII. Measurement Results for AIS Extreme Physical Tests Cont'd:

2. Carrier Power at Vibration Longitudinal.

High Specification: 40.96 +2/-3 dBm (12.5W +7.3W/-6.25W) Extreme Operation

Low Specification: 33.01 +2/-3 dBm (2W +1.2W/-1W) Extreme Operation



VIII. Measurement Results for AIS Extreme Physical Tests Cont'd:

2. Carrier Power at Vibration Lateral.

High Specification: 40.96 +2/-3 dBm (12.5W +7.3W/-6.25W) Extreme Operation

Low Specification: 33.01 +2/-3 dBm (2W +1.2W/-1W) Extreme Operation



VIII. Measurement Results for AIS Extreme Physical Tests Cont'd:

3. Sensitivity at Dry Heat and Low Temperature.

25 kHz Specification: -101 dBm @ 20% PER Normal Operation

Settings: = -94 dBm out -7 dB combiner = -101 dBm at EUT

Measured: -112 dBm @ <20% PER Dry/Low

Measured: -101 dBm @ <0% PER Dry/Low

9/29/04 Section 15.3.1 @ low temp and low power supply @ 156.025 MHz T,155419,288428437

AIS: 75/75 packets (Avg. 53.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 53.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 53.9) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 53.9) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 54.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.2) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.2) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.3) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.4) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.4) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.5) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.5) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.6) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.6) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.7) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.7) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.9) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 54.9) DSC: 0/0 bit-errors (Avg. 0.0000)

9/29/04 Section 15.3.1 @ low temp and normal power supply @ 162.025 MHz T,155801,309796757

AIS: 75/75 packets (Avg. 58.4) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 58.5) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 58.5) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 58.5) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 58.6) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 58.6) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 58.6) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 58.7) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 58.7) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 58.7) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 58.7) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 58.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 58.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 58.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 58.9) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 58.9) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 58.9) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 59.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 59.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 59.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 59.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 59.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 59.1) DSC: 0/0 bit-errors (Avg. 0.0000)

VIII. Measurement Results for AIS Extreme Physical Tests Cont'd:

3. Sensitivity at Dry Heat and Low Temperature.

25 kHz Specification: -101 dBm @ 20% PER Normal Operation

Settings: = -94 dBm out -7 dB combiner = -101 dBm at EUT

Measured: -112 dBm @ <20% PER Dry/Low

Measured: -101 dBm @ <0% PER Dry/Low

9/29/04 Section 15.3.1 @ low temp and normal power supply @ 156.025 MHz T,155536,295814037

AIS: 75/75 packets (Avg. 55.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 55.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 55.8)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 55.8)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 55.8)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 55.9)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 55.9)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 56.0)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 56.0)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 56.1)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 56.1)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 56.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 56.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 56.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 56.3)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 56.3)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 56.4)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 56.4)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 56.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 56.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 56.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 56.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 56.6)	DSC: 0/0 bit-errors (Avg. 0.0000)

9/28/04 Section 15.3.1 @ high temp and high power supply @ 162.025 MHz T,150556,-1742985656

AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)

Measured: -101 dBm @ < 0% PER Dry/Low

[illegible][illegible]

Measured: -101 dBm @ < 0% PER

[illegible]

AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)

VIII. Measurement Results for AIS Extreme Physical Tests Cont'd:

3. Sensitivity at Vibration.

25 kHz Specification: -101 dBm @ 20% PER Normal Operation

Settings: = -94 dBm out -7 dB combiner = -101 dBm at EUT

Measured: -112 dBm @ < 20% PER

Measured: -101 dBm @ < 0% PER

10/14/04Vibration longitudinal axis Endpoint test second test T,181629,197405254

AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.8) DSC: 0/0 bit-errors (Avg. 0.0000)

10/14/04Vibration lateral axis Endpoint test second test T,210813,258381885

AIS: 75/75 packets (Avg. 73.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 73.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 73.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 73.1) DSC: 0/0 bit-errors (Avg. 0.0000)

Measured: -101 dBm @ $< 0\%$ PER

[illegible]

AIS: 75/75 packets (Avg. 74.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 74.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 76/75 packets (Avg. 74.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 74.6)	DSC: 0/0 bit-errors (Avg. 0.0000)

VIII. Measurement Results for AIS Extreme Physical Tests Cont'd:

3. Sensitivity at Dry Heat and Low Temperature.

12.5 kHz Specification: -92 dBm @ 20% PER Normal Operation

Settings: = -85 dBm out -7 dB combiner = -92 dBm at EUT

Measured: -106 dBm @ < 20% PER Low/Dry

Measured: -92 dBm @ < 0% PER

9/29/04 Section 15.3.2 @ low temp and low power @ 160.6375 MHz T,153839,198196117

AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)

9/29/04 Section 15.3.2 @ low temp and low power @ 157.4125 MHz T,154059,211602837

AIS: 75/75 packets (Avg. 64.7) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 64.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 64.9) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 65.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 65.2) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 65.3) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 65.4) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 65.6) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 65.7) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 65.8) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 65.9) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 66.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 66.1) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 66.2) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 66.3) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 66.4) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 75.0) DSC: 0/0 bit-errors (Avg. 0.0000)

VIII. Measurement Results for AIS Extreme Physical Tests Cont'd:

3. Sensitivity (DSC Results) at Dry Heat and Low Temperature.

Specification: -101 dBm @ 0.01 BER Normal

Settings: 94 dBm out -7 dB combiner = -101 dBm at EUT

Measured: -116 dBm @ .01 BER Dry /-114 dBm @ .01 BER Low

Measured: -101 dBm @ < 0% BER

9/29/04 Section 15.4.1 @ low temp and low power supply A= 156.5235 MHz T,152706,131651477

AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0012)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0012)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0012)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0012)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/360 bit-errors (Avg. 0.0012)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0012)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0012)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0012)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0012)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0012)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0012)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0012)

9/28/04 Section 15.4.1 @ high temp and high power supply A= 156.5265 MHz T,161034,-1370656696

AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/360 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)

VIII. Measurement Results for AIS Extreme Physical Tests Cont'd:

4. Adjacent Channel Selectivity at Dry Heat and Low Temperature.

25 kHz Specification: ≥ 60 dB Normal

Measured: 77 dB Dry/60 dB Low

9/28/04 Section 15.3.6 at high temp and high power supply A = 162.025 MHz B = 162.050 MHz T,152730,-1618761656

AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.7)	DSC: 0/0 bit-errors (Avg. 0.0000)

9/29/04 Section 15.3.6 at low temp and low power supply A = 162.025 MHz B = 162.050 MHz T,160333,341663637

AIS: 75/75 packets (Avg. 62.1)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.1)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.1)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 74/75 packets (Avg. 62.1)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.3)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.3)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.3)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.3)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.3)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.4)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.4)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.4)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.4)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.4)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.5)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 62.5)	DSC: 0/0 bit-errors (Avg. 0.0000)

VIII. Measurement Results for AIS Extreme Physical Tests Cont'd:

4. Adjacent Channel Selectivity at Dry Heat and Low Temperature.

12.5 kHz Specification: ≥ 50 dB Normal

Measured: 54 dB Dry/Low

9/29/04 Section 15.3.7 @ low temp and low power supply A = 160.6375 MHz B = 160.650 MHz
T,153220,161782677

AIS: 75/75 packets (Avg. 3.5)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 3.5)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 3.6)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 3.7)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 3.8)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 3.9)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 4.0)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 4.1)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 4.2)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 4.3)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 4.3)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 4.4)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 4.5)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 4.6)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 4.7)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 4.8)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 4.9)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 74/75 packets (Avg. 4.9)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 5.0)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 5.1)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 5.2)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 5.3)	DSC: 0/0 bit-errors (Avg. 0.0013)
AIS: 75/75 packets (Avg. 5.4)	DSC: 0/0 bit-errors (Avg. 0.0013)

9/28/04 Section 15.3.7 @ high temp and high power supply A = 160.6375 MHz B = 160.625 MHz T,160220,-
1418144696

AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 73/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 73/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)
AIS: 75/75 packets (Avg. 74.2)	DSC: 0/0 bit-errors (Avg. 0.0000)

AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/360 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0000)

9/29/04 Section 15.4.4 @ low temp and low power supply A= 156.525 MHz B = 156.550 MHz T,151528,64692117

AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0014)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0014)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0014)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0014)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0014)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0014)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0014)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/360 bit-errors (Avg. 0.0014)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0013)
AIS: 0/75 packets (Avg. 0.0)	DSC: 0/450 bit-errors (Avg. 0.0012)