

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan  
District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053  
Fax: +86 (0) 755 2671 0594  
Email: ee.shenzhen@sgs.com

Report No.: SZEM121100644301  
Page: 1 of 45

## FCC REPORT

**Application No:** SZEM1211006443RF  
**Applicant:** Creative Labs Inc  
**Manufacturer:** Creative Technology Ltd  
**Product Name:** Creative DSxm  
**Model No.(EUT):** MF8150  
**FCC ID:** IBAMF8150  
**Standards:** 47 CFR Part 15, Subpart C (2011)  
**Date of Receipt:** 2012-12-06  
**Date of Test:** 2012-12-11 to 2012-12-21  
**Date of Issue:** 2013-02-07

<b>Test Result:</b>	<b>PASS *</b>
---------------------	---------------

\* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang  
EMC Laboratory Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at [www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm) and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at [www.sgs.com/terms\\_e-document.htm](http://www.sgs.com/terms_e-document.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

## 2 Test Summary

Test Item	Test Requirement	Test method	Result
<b>Antenna Requirement</b>	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2009	PASS
<b>AC Power Line Conducted Emission</b>	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2009	PASS
<b>Conducted Peak Output Power</b>	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	KDB558074 D01	PASS
<b>6dB Occupied Bandwidth</b>	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	KDB558074 D01	PASS
<b>Power Spectral Density</b>	47 CFR Part 15, Subpart C Section 15.247 (e)	KDB558074 D01	PASS
<b>Band-edge for RF Conducted Emissions</b>	47 CFR Part 15, Subpart C Section 15.247(d)	KDB558074 D01	PASS
<b>RF Conducted Spurious Emissions</b>	47 CFR Part 15, Subpart C Section 15.247(d)	KDB558074 D01	PASS
<b>Radiated Spurious Emissions</b>	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS
<b>Band Edge (Radiated Emission)</b>	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2009	PASS

Remark:

Both antenna A and B tested separately, then found the antenna A which is worse case, the test worse case data is recorded in the report.

Only 'one' antenna is selected for use at any one time.



### 3 Contents

	Page
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>2 TEST SUMMARY .....</b>	<b>2</b>
<b>3 CONTENTS .....</b>	<b>3</b>
<b>4 GENERAL INFORMATION.....</b>	<b>4</b>
4.1 CLIENT INFORMATION .....	4
4.2 GENERAL DESCRIPTION OF EUT .....	4
4.3 TEST ENVIRONMENT AND MODE .....	4
4.4 DESCRIPTION OF SUPPORT UNITS.....	5
4.5 TEST LOCATION.....	5
4.6 TEST FACILITY.....	5
4.7 DEVIATION FROM STANDARDS .....	6
4.8 ABNORMALITIES FROM STANDARD CONDITIONS.....	6
4.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	6
4.10 EQUIPMENT LIST .....	7
<b>5 TEST RESULTS AND MEASUREMENT DATA.....</b>	<b>10</b>
5.1 ANTENNA REQUIREMENT .....	10
5.2 CONDUCTED EMISSIONS.....	11
5.3 CONDUCTED PEAK OUTPUT POWER .....	15
5.4 6dB OCCUPY BANDWIDTH.....	19
5.5 POWER SPECTRAL DENSITY.....	22
5.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS.....	25
5.7 RF CONDUCTED SPURIOUS EMISSIONS.....	27
5.8 RADIATED SPURIOUS EMISSIONS.....	30
5.8.1 Radiated emission below 1GHz .....	32
5.8.2 Transmitter emission above 1GHz.....	34
5.9 BAND EDGE (RADIATED EMISSION).....	36-45

## 4 General Information

### 4.1 Client Information

Applicant:	Creative Labs Inc
Address of Applicant:	1901 McCarthy Blvd., Milpitas California 95035 United States
Manufacturer:	Creative Technology Ltd
Address of Manufacturer:	31 International Business Park, Creative Resource, Singapore 609921

### 4.2 General Description of EUT

Product Name:	Creative DSxm
Model No.:	MF8150
Trade Mark:	Creative
Operation Frequency:	5736MHz, 5762MHz, 5814MHz
Channel Numbers:	3
Channel Separation:	N/A
Type of Modulation:	QPSK
Sample Type:	fixed production
Test Power Grade:	N/A
Test Software of EUT:	RFTesting(V0.6)_CreativeDSxm_5.8G_WorldWide.exe
Antenna Type:	PCB Trace antenna
Antenna Gain:	3.0dBi
Power Supply:	AC 120V~ 60Hz
Test Voltage:	AC 120V~ 60Hz
Operating Temperature:	0°C to 45°C

### 4.3 Test Environment and Mode

Operating Environment:	
Temperature:	24.0 °C
Humidity:	50 % RH
Atmospheric Pressure:	1015 mbar
Test mode:	
Transmitter mode:	The EUT transmitted the continuous modulation test signal at the specific channel(s).

## 4.4 Description of Support Units

The EUT has been tested independently.

## 4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,  
No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.  
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

## 4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **VCCI**

The 3m Semi-anechoic chamber, Full-anechoic Chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2197, G-416, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

The 3m Semi-anechoic chamber of SGS-CSTC Standards Technical Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-1.

## **4.7 Deviation from Standards**

None.

## **4.8 Abnormalities from Standard Conditions**

None.

## **4.9 Other Information Requested by the Customer**

None.

## 4.10 Equipment List

Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2013-06-10
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2013-10-24
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2013-05-17
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	SEL0162	2013-11-10
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	SEL0163	2013-11-10
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	SEL0164	2013-11-10
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2013-05-17
8	Coaxial Cable	SGS	N/A	SEL0025	2013-05-29
9	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2013-10-24
10	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2013-10-24
11	Barometer	Chang Chun	DYM3	SEL0088	2013-05-24



RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2013-06-10
2	EMI Test Receiver	Rohde & Schwarz	ESIB26	SEL0023	2013-05-17
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2013-10-24
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2013-10-24
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2013-10-24
7	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2013-05-17
8	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2013-10-24
9	Coaxial cable	SGS	N/A	SEL0027	2013-05-59
10	Coaxial cable	SGS	N/A	SEL0189	2013-05-29
11	Coaxial cable	SGS	N/A	SEL0121	2013-05-29
12	Coaxial cable	SGS	N/A	SEL0178	2013-05-29
13	Band filter	Amindeon	82346	SEL0094	2013-05-17
14	Barometer	Chang Chun	DYM3	SEL0088	2013-05-24
15	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2013-10-24
16	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2013-10-24
17	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2013-05-17
18	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2013-10-24
19	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2013-06-04
20	Signal Conditioning Unit	Rohde & Schwarz	SCU_F1840_G35_BZ3_CSS(F)	10001	2013-03-14
21	EMI test receiver	Rohde & Schwarz	ESU40	100109	2013-06-01
22	Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA91703 73	2013-03-14




<b>RF connected test</b>					
<b>Item</b>	<b>Test Equipment</b>	<b>Manufacturer</b>	<b>Model No.</b>	<b>Inventory No.</b>	<b>Cal.Due date (yyyy-mm-dd)</b>
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2013-10-24
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2013-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2013-10-24
4	Coaxial cable	SGS	N/A	SEL0178	2013-05-29
5	Coaxial cable	SGS	N/A	SEL0179	2013-05-29
6	Barometer	ChangChun	DYM3	SEL0088	2013-05-24
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2013-05-17
8	Band filter	amideon	82346	SEL0094	2013-05-17
9	POWER METER	R & S	NRVS	SEL0144	2013-10-24
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2013-05-17
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2013-10-24
12	Signal Conditioning Unit	Rohde & Schwarz	SCU_F1840_G35_BZ3_CSS(F)	10001	2013-03-14
13	EMI test receiver	Rohde & Schwarz	ESU40	100109	2013-06-01
14	Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA91703 73	2013-03-14

**Note: The calibration interval is one year, all the instruments are valid.**

## 5 Test results and Measurement Data

### 5.1 Antenna Requirement

<b>Standard requirement:</b>	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement:	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.
15.247(b) (4) requirement:	The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6dBi.
<b>EUT Antenna:</b>	The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 3.0dBi.



## 5.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207		
Test Method:	ANSI C63.10: 2009		
Test Frequency Range:	150kHz to 30MHz		
Limit:	Frequency range (MHz)	Limit (dBuV)	
	0.15-0.5	Quasi-peak	Average
	0.5-5	66 to 56*	56 to 46*
	5-30	56	46
* Decreases with the logarithm of the frequency.			
Test Procedure:	<ol style="list-style-type: none"><li>1) The mains terminal disturbance voltage test was conducted in a shielded room.</li><li>2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a <math>50\Omega/50\mu\text{H} + 5\Omega</math> linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.</li><li>3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,</li><li>4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.</li><li>5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2009 on conducted measurement.</li></ol>		

Test Setup:	
Test Mode:	Transmitter mode
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass


### Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.




Live Line:



Site : Shielding Room  
 Condition : 47 CFR PART 15 B QP CE LINE  
 Job No. : 6443RF  
 Test mode : TX

Freq	Cable	LISN	Read	Limit	Over		
	Loss	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB
1	0.28029	0.01	9.70	20.59	30.31	60.81	-30.50 QP
2 0	0.28029	0.01	9.70	13.66	23.37	50.81	-27.43 Average
3	0.36725	0.01	9.77	17.48	27.26	58.56	-31.30 QP
4 0	0.36725	0.01	9.77	10.65	20.43	48.56	-28.13 Average
5	0.49673	0.01	9.80	15.03	24.84	56.05	-31.21 QP
6 0	0.49673	0.01	9.80	10.64	20.45	46.05	-25.60 Average
7	0.90394	0.02	9.80	13.92	23.74	56.00	-32.26 QP
8 0	0.90394	0.02	9.80	9.75	19.57	46.00	-26.43 Average
9	1.772	0.02	9.80	15.24	25.06	56.00	-30.94 QP
10 0	1.772	0.02	9.80	10.98	20.80	46.00	-25.20 Average
11	3.417	0.02	9.86	15.99	25.87	56.00	-30.13 QP
12 0	3.417	0.02	9.86	8.47	18.35	46.00	-27.65 Average

Neutral Line:




Site : Shielding Room  
 Condition : 47 CFR PART 15 B QP CE NEUTRAL  
 Job No. : 6443RF  
 Test mode : TX

Freq	Cable	LISN	Read	Limit	Over	Remark
	MHz	dB	dB	dBuV	dBuV	
1	0.15240	0.02	9.70	17.46	27.18	65.87 -38.68 QP
2	0.15240	0.02	9.70	11.38	21.10	55.87 -34.77 Average
3	0.25751	0.02	9.70	6.68	16.40	51.51 -35.12 Average
4	0.25751	0.02	9.70	12.22	21.93	61.51 -39.58 QP
5	0.32685	0.01	9.73	8.84	18.58	49.53 -30.95 Average
6	0.32685	0.01	9.73	13.96	23.70	59.53 -35.83 QP
7	0.68990	0.02	9.80	7.66	17.48	46.00 -28.52 Average
8	0.68990	0.02	9.80	14.44	24.26	56.00 -31.74 QP
9	2.854	0.02	9.84	14.10	23.96	56.00 -32.04 QP
10	2.854	0.02	9.84	6.13	15.99	46.00 -30.01 Average
11	3.417	0.02	9.86	12.91	22.79	56.00 -33.21 QP
12	3.417	0.02	9.86	4.28	14.16	46.00 -31.84 Average

**Notes:**

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.

### 5.3 Conducted Peak Output Power



Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	KDB558074 D01
Test Setup:	 <p><b>Remark:</b>  <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p>
Test Mode:	Transmitter mode
Limit:	30dBm
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

#### Measurement Data



Transmitter mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
5736MHz	13.45	30.00	Pass
5762MHz	13.33	30.00	Pass
5814MHz	13.48	30.00	Pass

**Test plot as follows:**


Test mode:	Transmitter mode	Test channel:
		5736MHz




Test mode:	Transmitter mode	Test channel:	5762MHz
------------	------------------	---------------	---------



Test mode:	Transmitter mode	Test channel:	5814MHz
------------	------------------	---------------	---------



## 5.4 6dB Occupy Bandwidth


Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	KDB558074 D01
Test Setup:	
Test Mode:	Transmitter mode
Limit:	$\geq 500$ kHz
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

### Measurement Data


Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
5736MHz	12.40	$\geq 500$	Pass
5762MHz	12.48	$\geq 500$	Pass
5814MHz	12.48	$\geq 500$	Pass

**Test plot as follows:**


Test mode:	transmitter	Test channel:	5736MHz
------------	-------------	---------------	---------




Test mode:	transmitter	Test channel:	5762MHz
------------	-------------	---------------	---------



Test mode:	Transmitter	Test channel:	5814MHz
------------	-------------	---------------	---------



## 5.5 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	KDB558074 D01
Test Setup:	 <p><b>Remark:</b> Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</p>
Test Mode:	Transmitter mode
Limit:	≤8dBm
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass


### Measurement Data

Test channel	Power Spectral Density (dBm)	Limit (dBm)	Result
5736MHz	-6.86	≤8.00	Pass
5762MHz	-5.89	≤8.00	Pass
5814MHz	-5.81	≤8.00	Pass




**Test plot as follows:**


Test mode:	Transmitter	Test channel:	5736MHz
------------	-------------	---------------	---------



Test mode:	Transmitter	Test channel:	5762MHz
------------	-------------	---------------	---------



Test mode:	Transmitter	Test channel:	5814MHz
------------	-------------	---------------	---------




## 5.6 Band-edge for RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	KDB558074 D01
Test Setup:	<p style="text-align: center;">   <b>Spectrum Analyzer</b>  <b>E.U.T</b>  <b>Non-Conducted Table</b>  <b>Ground Reference Plane</b> </p> <p><i>Remark:</i>  <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p>
Test Mode:	Transmitter mode
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 Db below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

**Test plot as follows:**


Test mode:	Transmitter	Test channel:	5736MHz
------------	-------------	---------------	---------



Test mode:	Transmitter	Test channel:	5814MHz
------------	-------------	---------------	---------




## 5.7 RF Conducted Spurious Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	KDB558074 D01
Test Setup:	 <p><b>Spectrum Analyzer</b>  <b>E.U.T</b>  <b>Non-Conducted Table</b>  <b>Ground Reference Plane</b></p>
	<p><i>Remark:</i></p> <p><i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p>
Test Mode:	Transmitter mode
Limit:	<p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.</p>
Instruments Used:	Refer to section 4.10 for details
Test Results:	Pass

**Test plot as follows:**


Test mode:	Transmitter	Test channel:	5736MHz
------------	-------------	---------------	---------



Test mode:	Transmitter	Test channel:	5762MHz
------------	-------------	---------------	---------



Test mode:	Transmitter	Test channel:	5814MHz
------------	-------------	---------------	---------



## 5.8 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2009				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30KHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30KHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30KHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30KHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30KHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m )	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					
Test Setup:					




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1 GHz

Test Procedure:	<ol style="list-style-type: none"> <li>The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>
-----------------	---

	g. Test the EUT in the operation channel
Instruments Used:	Refer to section 4.10 for details
Test mode:	Transmitter mode
Test results:	Pass

### 5.8.1 Radiated emission below 1GHz

30MHz~1GHz (QP)			
Test mode:	Transmitter mode	Polarization:	Vertical



Condition : 47 CFR PART 15 B 3m 3142C NEW VERTICAL


Job No : 6443RF

Mode : TX

Freq	Cable			Antenna		Read Level	Limit Level	Line Limit	Over Limit
	Loss	Factor	Factor	dBuV	dBuV/m				
MHz	dB	dB/m	dB	dB	dB	dB	dB	dB	dB
1 0	51.340	0.80	6.82	27.29	48.53	28.86	40.00	-11.14	
2	75.590	0.97	4.58	27.24	47.69	26.00	40.00	-14.00	
3	171.620	1.36	8.73	26.81	42.05	25.32	43.50	-18.18	
4	416.060	2.27	11.54	27.23	39.61	26.19	46.00	-19.81	
5	465.530	2.47	13.27	27.52	40.88	29.10	46.00	-16.90	
6	514.030	2.61	13.90	27.67	41.56	30.40	46.00	-15.60	



Test mode:	Transmitter mode	Polarization:	Horizontal
------------	------------------	---------------	------------



Condition : 47 CFR PART 15 B 3m 3142C NEW HORIZONTAL

Job No : 6443RF

Mode : TX

Freq	Cable	Antenna	Preamp	Read	Limit	Line	Over	
	MHz	Loss	Factor	Level				
1	121.180	1.26	7.75	27.06	40.22	22.17	43.50	-21.33
2	141.550	1.30	8.72	26.95	46.65	29.72	43.50	-13.78
3	171.620	1.36	8.73	26.81	44.49	27.76	43.50	-15.74
4	219.150	1.51	7.14	26.63	47.62	29.64	46.00	-16.36
5	319.060	1.96	9.81	26.54	41.84	27.07	46.00	-18.93
6	489.780	2.56	13.48	27.66	39.40	27.78	46.00	-18.22

### 5.8.2 Transmitter emission above 1GHz

Test mode:		Transmitter		Test channel:		5736MHz		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization		
1762.112	2.69	30.07	39.46	46.74	40.04	74	-33.96	Vertical		
2656.331	3.13	32.91	40.05	47.03	43.02	74	-30.98	Vertical		
3890.255	4.07	33.68	40.95	48.17	44.97	74	-29.03	Vertical		
7076.516	5.62	35.83	39.99	48.75	50.21	74	-23.79	Vertical		
8995.123	6.16	36.59	38.32	46.67	51.10	74	-22.90	Vertical		
10274.240	6.04	38.04	37.56	46.05	52.57	74	-21.43	Vertical		
2259.367	2.94	32.27	39.75	47.23	42.69	74	-31.31	Horizontal		
3196.094	3.49	33.32	40.45	47.37	43.73	74	-30.27	Horizontal		
4482.150	4.48	35.15	41.39	49.09	47.33	74	-26.67	Horizontal		
7305.122	5.90	35.92	39.79	47.38	49.41	74	-24.59	Horizontal		
8943.274	6.16	36.55	38.37	47.42	51.76	74	-22.24	Horizontal		
10514.580	6.10	38.31	37.66	45.92	52.67	74	-21.33	Horizontal		
Test mode:		Transmitter		Test channel:		5762MHz	Remark:		Peak	
Frequency (MHz)	Cable loss (dB)	Antenna factors (dB/m)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Over Limit (dB)	Polarization		
1966.680	2.81	31.55	39.55	48.82	43.63	74	-30.37	Vertical		
3141.145	3.44	33.34	40.41	48.05	44.42	74	-29.58	Vertical		
4482.150	4.48	35.15	41.39	49.00	47.24	74	-26.76	Vertical		
7628.806	6.23	36.00	39.51	48.08	50.80	74	-23.20	Vertical		
9475.497	6.02	37.18	37.91	46.68	51.97	74	-22.03	Vertical		
11012.250	6.22	38.50	37.87	46.11	52.96	74	-21.04	Vertical		
1658.337	2.62	29.33	39.42	46.11	38.64	74	-35.36	Horizontal		
2880.247	3.25	33.24	40.21	47.26	43.54	74	-30.46	Horizontal		
4181.768	4.28	34.31	41.16	47.46	44.89	74	-29.11	Horizontal		
7852.524	6.22	36.00	39.31	48.25	51.16	74	-22.84	Horizontal		
10068.450	5.99	37.78	37.47	45.22	51.52	74	-22.48	Horizontal		
11533.480	6.35	38.43	38.08	46.51	53.21	74	-20.79	Horizontal		



Test mode:		Transmitter		Test channel:		5814MHz		Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization		
1866.977	2.75	30.81	39.51	46.33	40.38	74	-33.62	Vertical		
3299.344	3.56	33.28	40.52	46.37	42.69	74	-31.31	Vertical		
4443.453	4.46	35.06	41.36	47.97	46.13	74	-27.87	Vertical		
6974.982	5.50	35.83	40.08	48.55	49.80	74	-24.20	Vertical		
8866.062	6.16	36.49	38.44	45.60	49.81	74	-24.19	Vertical		
11667.600	6.39	38.57	38.13	45.94	52.77	74	-21.23	Vertical		
2456.913	3.01	32.64	39.91	48.71	44.45	74	-29.55	Horizontal		
3725.195	3.93	33.47	40.83	48.43	45.00	74	-29.00	Horizontal		
4626.946	4.57	35.01	41.50	48.71	46.79	74	-27.21	Horizontal		
7541.114	6.17	36.00	39.59	48.90	51.48	74	-22.52	Horizontal		
10126.820	6.01	37.86	37.50	45.93	52.30	74	-21.70	Horizontal		
11368.000	6.31	38.43	38.02	46.34	53.06	74	-20.94	Horizontal		

**Remark:**

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) The disturbance above 12GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed.
- 3) As shown in this section, the peak field strength of any emission shall not exceed the maximum permitted average limits, So only the peak measurements were shown in the report.

## 5.9 Band Edge (Radiated Emission)

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10 2009		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value

### Test Setup:




Figure 1. 30MHz to 1GHz





Figure 2. Above 1 GHz

Test Procedure:	<ol style="list-style-type: none"><li>a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li><li>b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li><li>c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li><li>d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li><li>e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li><li>f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for operation channel</li><li>g. Test the EUT in the operation channel</li></ol>
Instruments Used:	Refer to section 4.10 for details
Test mode:	Transmitter mode
Test results:	Pass


Test mode:	Transmitter	Test channel:	5736MHz	Remark:	Peak	Horizontal
------------	-------------	---------------	---------	---------	------	------------



Condition : FCC PART15(>1G) PK 3m HORIZONTAL  
 Job No. : 6443RF  
 test mode : 5736bandedge(A)

	Freq	Cable	Antenna	Preamp	Read	Limit	Over	
		Loss	Factor	Factor	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5460.000	4.94	34.85	41.38	48.50	46.90	74.00	-27.10
2 X	5735.200	5.04	35.29	41.15	94.96	94.13	74.00	20.13

Test mode:	Transmitter	Test channel:	5736MHz	Remark:	Peak	Vertical
------------	-------------	---------------	---------	---------	------	----------




Condition : FCC PART15(&gt;1G) PK 3m VERTICAL

Job No. : 6443RF

test mode : 5736bandedge(A)

	Freq	Cable Loss	Antenna Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5460.000	4.94	34.85	41.38	49.66	48.06	74.00	-25.94
2	5735.200	5.04	35.29	41.15	100.44	99.61	74.00	25.61

Test mode:	Transmitter	Test channel:	5736MHz	Remark:	Average	Horizontal
------------	-------------	---------------	---------	---------	---------	------------




Condition : FCC PART15(>1G) AV 3m HORIZONTAL

Job No. : 6443RF

test mode : 5736bandedge(A)

	Freq	Cable Loss	Antenna Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5460.000	4.94	34.85	41.38	35.97	34.37	54.00	-19.63
2	5739.600	5.04	35.29	41.15	88.25	87.42	54.00	33.42

Test mode:	Transmitter	Test channel:	5736MHz	Remark:	Average	Vertical
------------	-------------	---------------	---------	---------	---------	----------




Condition : FCC PART15(>1G) AV 3m VERTICAL

Job No. : 6443RF

test mode : 5736bandedge(A)

	Freq	Cable	Antenna	Preamp	Read	Limit	Over	
		Loss	Factor	Factor	Level	Level	Line	Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	5460.000	4.94	34.85	41.38	35.71	34.11	54.00	-19.89
2	5738.000	5.04	35.29	41.15	91.43	90.60	54.00	36.60

Test mode:	Transmitter	Test channel:	5814MHz	Remark:	Peak	Horizontal
------------	-------------	---------------	---------	---------	------	------------




Condition : FCC PART15(>1G) PK 3m HORIZONTAL  
 Job No. : 6443RF  
 test mode : 5814 bandedge(A)

	Freq	Cable	Antenna	Preamp	Read	Limit	Over	
		Loss	Factor	Factor	Level			
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 X	5811.700	5.06	35.40	41.09	93.87	93.24	74.00	19.24
2	7250.000	5.83	35.90	39.84	46.08	47.98	74.00	-26.02



Test mode:	Transmitter	Test channel:	5814MHz	Remark:	Peak	Vertical
------------	-------------	---------------	---------	---------	------	----------




Condition : FCC PART15(&gt;1G) PK 3m VERTICAL

Job No. : 6443RF

test mode : 5814 bandedge(A)

Freq	Cable	Antenna	Preamp	Read	Limit	Over	
	Loss	Factor	Factor	Level			
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 X	5811.700	5.06	35.40	41.09	96.07	95.44	74.00 21.44
2	7250.000	5.83	35.90	39.84	46.58	48.48	74.00 -25.52

Test mode:	Transmitter	Test channel:	5814MHz	Remark:	Average	Horizontal
------------	-------------	---------------	---------	---------	---------	------------




Condition : FCC PART15(>1G) AV 3m HORIZONTAL

Job No. : 6443RF

test mode : 5814 bandedge(A)

	Freq	Cable Loss	Antenna Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 0	5813.650	5.06	35.40	41.09	87.62	86.99	54.00	32.99
2	7250.000	5.83	35.90	39.84	34.47	36.37	54.00	-17.63

Test mode:	Transmitter	Test channel:	5814MHz	Remark:	Average	Vertical
------------	-------------	---------------	---------	---------	---------	----------



Condition : FCC PART15(&gt;1G) AV 3m VERTICAL

Job No. : 6443RF

test mode : 5814 bandedge(A)

	Freq	Cable Loss	Antenna Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 X	5811.700	5.06	35.40	41.09	86.67	86.04	54.00	32.04
2	7250.000	5.83	35.90	39.84	34.47	36.37	54.00	-17.63

**Note:**

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor