



MOTOROLA

Portable Cellular Phone SAR Test Report

Test Report #: 21072-1F
Date of Report: September 25, 2007
Date of Test: August 31, 2007 – September 19, 2007
FCC ID #: IHDP56HM1
Generic Name: MRQ6-334411C11
Laboratory: Motorola Mobile Devices Business Product Safety & Compliance Laboratory
600 N. US Highway 45
Libertyville, Illinois 60048
Report Author: Katerina Royzen
Engineer

This laboratory is accredited to ISO/IEC 17025-2005 to perform the following tests:

Tests:

Electromagnetic Specific Absorption Rate

Procedures:

IEC 62209-1

RSS-102

IEEE 1528 - 2003

FCC OET Bulletin 65 (*including Supplement C*)

Australian Communications Authority Radio

Communications (Electromagnetic Radiation – Human Exposure) Standard 2003

CENELEC EN 50360 (2001)

CENELEC EN 50361 (2001)

ARIB Std. T-56 (2002)

Accreditation:



TESTING CERT #2518-02

On the following products or types of products:

On the following products or types of products: Wireless Communications Devices (Examples): Two Way Radios; Portable Phones (including Cellular, Licensed Non-Broadcast and PCS); Low Frequency Readers; and Pagers

Statement of Compliance:

Motorola declares under its sole responsibility that the portable cellular telephone model to which this declaration relates, is in conformity with the appropriate General Population/Uncontrolled RF exposure standards, recommendations and guidelines (FCC 47 CFR §2.1093) as well as with CENELEC en50360:2001 and ANSI / IEEE C95.1. It also declares that the product was tested in accordance with IEEE 1528 / CENELEC EN62209-1 (2006), as well as other appropriate measurement standards, guidelines and recommended practices. Any deviations from these standards, guidelines and recommended practices are noted below:

(none)

©Motorola, Inc. 2007

This test report shall not be reproduced except in full, without written approval of the laboratory.

The results and statements contained herein relate only to the items tested. The names of individuals involved may be mentioned only in connection with the statements or results from this report.

Motorola encourages all feedback, both positive and negative, on this test report.

Table of Contents

1. Introduction	2
2. Description of the Device Under Test	2
2.1 Antenna description	2
2.2 Device description	2
3. Test Equipment Used	3
3.1 Dosimetric System	3
3.2 Additional Equipment	3
4. Electrical parameters of the tissue simulating liquid	4
5. System Accuracy Verification	6
6. Test Results	7
6.1 Head Adjacent Test Results	8
6.2 Body Worn Test Results	13
References	17
Appendix 1: SAR distribution comparison for system accuracy verification	18
Appendix 2: SAR distribution plots for Phantom Head Adjacent Use	19
Appendix 3: SAR distribution plots for Body Worn Configuration	20
Appendix 4: Probe Calibration Certificate	21
Appendix 5: Measurement Uncertainty Budget	22
Appendix 6: Photographs of the device under test	24
Appendix 7: Dipole Characterization Certificate	28

1. Introduction

The Motorola Mobile Devices Business Product Safety Laboratory has performed measurements of the maximum potential exposure to the user of the portable cellular phone covered by this test report. The Specific Absorption Rate (SAR) of this product was measured. The portable cellular phone was tested in accordance with [1], [4] and [5]. The SAR values measured for the portable cellular phone are below the maximum recommended levels of 1.6 W/kg in a 1g average set in [3] and 2.0W/kg in a 10g average set in [2].

2. Description of the Device Under Test

2.1 Antenna description

Type	External	
Location	Upper Right	
Dimensions	Length	24 mm
	Width	13 mm
Configuration	stubby	

2.2 Device description

Serial Number	LKW0390036														
Mode(s) of Operation	UMTS 800	UMTS 1900	GSM 850	GSM 900	GSM 1800	GSM 1900	GPRS Class 10 850	GPRS Class 10 900	GPRS Class 10 1800	GPRS Class 10 1900	EDGE Class 10 850	EDGE Class 10 900	EDGE Class 10 1800	EDGE Class 10 1900	Blue tooth
Modulation Mode(s)	QPSK	QPSK	GMSK	GMSK	GMSK	GMSK	GMSK	GMSK	GMSK	GMSK	8PSK	8PSK	8PSK	8PSK	GFSK
Maximum Output Power Setting	24.00 dBm	24.00 dBm	33.0 dBm	33.0 dBm	30.0 dBm	30.0 dBm	33.0 dBm	33.0 dBm	30.0 dBm	30.0 dBm	27.50 dBm	27.50 dBm	26.50 dBm	26.50 dBm	4.0 dBm
Duty Cycle	1:1	1:1	1:8	1:8	1:8	1:8	2:8	2:8	2:8	2:8	2:8	2:8	2:8	2:8	1:1
Transmitting Frequency Range(s)	826.4 - 846.6 MHz	1852.4 - 1907.6 MHz	824.2 - 848.8 MHz	880.2 - 914.8 MHz	1710.2 - 1784.8 MHz	1850.2 - 1909.8 MHz	824.2 - 848.8 MHz	880.2 - 914.8 MHz	1710.2 - 1784.8 MHz	1850.2 - 1909.8 MHz	824.2 - 848.8 MHz	880.2 - 914.8 MHz	1710.2 - 1784.8 MHz	1850.2 - 1909.8 MHz	2400.0 - 2483.5 MHz
Production Unit or Identical Prototype (47 CFR §2.908)	Identical Prototype														
Device Category	Portable														
RF Exposure Limits	General Population / Uncontrolled														

3. Test Equipment Used

3.1 Dosimetric System

The Motorola Mobile Devices Business Product Safety & Compliance Laboratory utilizes a Dosimetric Assessment System (Dasy4™ v4.7) manufactured by Schmid & Partner Engineering AG (SPEAG™), of Zurich Switzerland. All the SAR measurements are taken within a shielded enclosure. The overall 10g RSS uncertainty of the measurement system is $\pm 10.8\%$ (K=1) with an expanded uncertainty of $\pm 21.6\%$ (K=2). The overall 1g RSS uncertainty of the measurement system is $\pm 11.1\%$ (K=1) with an expanded uncertainty of $\pm 22.2\%$ (K=2). The measurement uncertainty budget is given in Appendix 6. Per IEEE 1528, this uncertainty budget is applicable to the SAR range of 0.4W/kg to 10W/kg.

The list of calibrated equipment used for the measurements is shown in the following table.

Description	Serial Number	Cal Due Date
DASY4™ DAE V1	703	5/30/2008
E-Field Probe ETDV6	1397	4/24/2008
Dipole Validation Kit, DV900V2	91	05/1/2007
S.A.M. Phantom used for 800/900MHz	TP-1005	
Dipole Validation Kit, DV1800V2	259tr	05/1/2007
S.A.M. Phantom used for 1800MHz	TP-1139	

3.2 Additional Equipment

Description	Serial Number	Cal Due Date
Signal Generator HP8648C	3847A04982	6/13/2009
Power Meter E4419B	GB39511087	7/19/2008
Power Sensor #1 – E9301	US39210931	7/20/2008
Power Sensor #2 - E9301	US39210932	7/20/2008
Network Analyzer HP8753ES	US39171846	7/19/2008
Dielectric Probe Kit HP85070C	US99360070	

4. Electrical parameters of the tissue simulating liquid

Prior to conducting SAR measurements, the relative permittivity, ϵ_r , and the conductivity, σ , of the tissue simulating liquids were measured with a HP85070 Dielectric Probe Kit. These values, along with the temperature of the simulated tissue are shown in the table below. The recommended limits for permittivity and conductivity are also shown. A mass density of $\rho=1\text{g/cm}^3$ was entered into the system in all the cases. It can be seen that the measured parameters are within tolerance of the recommended limits specified in [1] and [5].

f (MHz)	Tissue type	Limits / Measured	Dielectric Parameters		
			ϵ_r	σ (S/m)	Temp (°C)
835	Head	Measured, 9/2/2007	41.2	0.90	20.5
		Measured, 9/06/2007	40.8	0.90	19.5
		Measured, 9/07/2007	42.3	0.92	19.2
		Measured, 9/10/2007	42.0	0.91	20.5
		Recommended Limits	41.5 $\pm$ 5%	0.90 $\pm$ 5%	18-25
	Body	Measured, 9/06/2007	53.0	0.97	18.6
		Measured, 9/13/2007	53.3	0.97	19.4
		Recommended Limits	55.2 $\pm$ 5%	0.97 $\pm$ 5%	18-25
1880	Head	Measured, 9/04/2007	40.1	1.47	19.3
		Measured, 9/07/2007	39.0	1.39	19.2
		Measured, 9/12/2007	38.0	1.47	18.2
		Measured, 9/19/2007	39.8	1.46	19.2
		Recommended Limits	40.0 $\pm$ 5%	1.40 $\pm$ 5%	18-25
	Body	Measured, 9/07/2007	51.4	1.59	19.1
		Measured, 9/08/2007	51.1	1.57	20.0
		Recommended Limits	53.3 $\pm$ 5%	1.52 $\pm$ 5%	18-25

MOTOROLA, INC. Portable Cellular Phone SAR Test Report Number: 21072-1F

The list of ingredients and the percent composition used for the tissue simulates are indicated in the table below.

Ingredient	835MHz / 900 MHz Head	835MHz / 900 MHz Body	1800MHz / 1900 MHz Head	1800 MHz / 1900 MHz Body	2450MHz Head	2450 MHz Body
Sugar	57	44.9	--	--	--	--
DGBE	--	--	47	30.8	--	30
Diacetin	--	--	--	--	51	
Water	40.45	53.06	52.62	68.8	48.75	70
Salt	1.45	0.94	0.38	0.4	0.15	--
HEC	1	1	--	--	--	--
Bact.	0.1	0.1	--	--	0.1	--

5. System Accuracy Verification

A system accuracy verification of the DASY4™ was performed using the measurement equipment listed in Section 3.1. The daily system accuracy verification occurs within the flat section of the SAM phantom.

A SAR measurement was performed to verify the measured SAR was within $\pm 10\%$ from the target SAR indicated in Appendix 7. These tests were done at 900MHz, 1800MHz. These frequencies are within $\pm 10\%$ of the compliance test mid-band frequency as required in [1] and [5]. The test was conducted on the same days as the measurement of the DUT. Recommended limits for permittivity and conductivity, specified in [5], are shown in the table below. The obtained results from the system accuracy verification are also displayed in the table below. SAR values are normalized to 1W forward power delivered to the dipole. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values. The distributions of SAR compare well with those of the reference measurements (see Appendix 1). The tissue stimulant depth was verified to be 15.0cm ± 0.5 cm. Z-axis scans showing the SAR penetration are also included in Appendix 1.

f (MHz)	Description	SAR (W/kg), 1gram	Dielectric Parameters		Ambient Temp (°C)	Tissue Temp (°C)
			ϵ_r	σ (S/m)		
900	Measured, 9/01/2007	10.93	41.2	0.96	20.1	20.6
	Measured, 9/02/2007	11.10	40.5	0.96	20.1	20.6
	Measured, 9/06/2007	11.05	40.0	0.96	20.4	19.8
	Measured, 9/07/2007	11.53	41.5	0.98	20.3	19.6
	Measured, 9/10/2007	11.00	41.3	0.97	20.5	20.0
	Measured, 9/13/2007	11.18	41.7	0.98	20.5	19.1
	Recommended Limits	11.24	41.5 $\pm 5\%$	0.97 $\pm 5\%$	18-25	18-25
1800	Measured, 8/31/2007	38.23	38.5	1.37	20.1	19.5
	Measured, 9/04/2007	36.55	40.5	1.39	20.6	19.4
	Measured, 9/07/2007	38.40	39.0	1.39	20.3	19.5
	Measured, 9/08/2007	36.33	39.0	1.36	20.4	19.8
	Measured, 9/12/2007	36.60	38.3	1.37	19.7	19.8
	Measured, 9/19/2007	36.90	40.2	1.38	20.5	20.3
	Recommended Limits	37.5	40.0 $\pm 5\%$	1.4 $\pm 5\%$	18-25	18-25

The following probe conversion factors were used on the E-Field probe(s) used for the system accuracy verification measurements:

Description	Serial Number	f (MHz)	Conversion Factor	Cal Cert pg #
E-Field Probe ET3DV6R	SN 1397	900	6.25	8 of 9
		1810	5.17	8 of 9

6. Test Results

The test sample was operated using an actual transmission through a base station simulator. The base station simulator was setup to the proper channel, transmitter power level and transmit mode of operation. The phone was tested in the configurations stipulated in [1], [4] and [5]. The phone was positioned into these configurations using the device holder supplied with the DASY4™ SAR measurement system. The measured dielectric constant of the material used for the device holder is less than 2.9 and the loss tangent is less than 0.02 ($\pm 30\%$) at 850MHz. The default settings for the “coarse” and “cube” scans were chosen and used for measurements. The grid spacing of the course scan was set to 15cm as shown in the SAR plots included in Appendix 2 and 3. Please refer to the DASY4™ manual for additional information on SAR scanning procedures and algorithms used.

The Cellular Phone model covered by this report has the following battery options:

SNN5782B - 1100 mAH Battery

SNN5813A - 910 mAH Battery

The battery with the highest capacity is the SNN5782B. This battery was used to do most of the SAR testing. The phone was placed in the SAR measurement system with a fully charged battery. The configuration that resulted in the highest SAR values were tested using the other batteries listed above.

Per the “SAR Measurement Procedures for 3G Devices” released in June, 2006, 12.2 kbps RMC and 12.2 kbps AMR modes were considered. The conducted power measurements (per 3GPP TS 34.121) for each mode are shown in the table below.

Conducted power (dBm) for WCDMA modes			
	Channel	RMC	AMR
WCDMA 850	4132	23.88	23.97
	4180	23.89	23.93
	4233	23.83	23.89
WCDMA 1900	9262	23.98	23.97
	9400	23.83	23.86
	9538	23.75	23.83

6.1 Head Adjacent Test Results

The SAR results shown in tables 1 through 7 are maximum SAR values averaged over 1 gram of phantom tissue, to demonstrate compliance to [3] and also over 10 grams of phantom tissue, to demonstrate compliance to the [6]. Also shown are the measured conducted output power levels, the temperature of the simulated tissue after the test, the measured drift and the extrapolated SAR. The exact method of extrapolation is $\text{New SAR} = \text{Old SAR} * 10^{(-\text{drift}/10)}$. The SAR reported at the end of the measurement process by the DASY4™ measurement system can be scaled up by the measured drift to determine the SAR at the beginning of the measurement process. This is the most conservative SAR because it corresponds to the average output power at the beginning of the SAR test. This extrapolation has been done because when the DUT is operating properly it may exhibit a slump in radiated power and SAR over time. This is verified by measuring the SAR drift after the test.

The left head and right head SAR contour distributions are similar. Because of this similarity, the cheek/touch and 15° tilt test conditions with the highest SAR values in each band are indicated as bold numbers in the following tables and are included in Appendix 2. All other test conditions measured lower SAR values than those included in Appendix 2.

The SAR measurements were performed using the SAM phantoms listed in section 3.1. Since the same phantoms and simulated tissue were used for the system accuracy verification and the device SAR measurements, the Z-axis scans included in Appendix 1 are applicable for verification of simulated tissue depth to be 15.0cm ±0.5cm.

The following probe conversion factors were used on the E-Field probe(s) used for the head adjacent measurements:

Description	Serial Number	f (MHz)	Conversion Factor	Cal Cert pg #
E-Field Probe ET3DV6R	SN 1397	900	6.25	8 of 9
		1810	5.17	8 of 9

Left Head Cheek Position								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	10g SAR value		1g SAR value	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GSM 850MHz	Channel 128	32.93	20.7	0.00	0.723	0.72	1.09	1.09
	Channel 190	32.84	20.7	-0.02	0.712	0.72	1.09	1.10
	Channel 251	32.80	20.7	-0.03	0.717	0.72	1.10	1.11
GSM 1900MHz	Channel 512	29.89						
	Channel 661	29.86	18.5	-0.05	0.191	0.19	0.353	0.36
	Channel 810	29.83						
WCDMA 850MHz	Channel 4132	23.97	19.5	0.02	0.660	0.66	0.974	0.97
	Channel 4180	23.93	19.5	-0.21	0.841	0.88	1.26	1.32
	Channel 4233	23.89	19.5	-0.01	0.744	0.75	1.11	1.11
WCDMA 1900MHz	Channel 9262	23.97						
	Channel 9400	23.86	19.8	-0.27	0.407	0.43	0.749	0.80
	Channel 9538	23.83						

Table 1: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.

Right Head Cheek Position								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	10g SAR value		1g SAR value	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GSM 850MHz	Channel 128	32.93	20.5	-0.06	0.749	0.76	1.13	1.15
	Channel 190	32.84	20.5	-0.05	0.749	0.76	1.13	1.14
	Channel 251	32.80	20.5	-0.06	0.726	0.74	1.11	1.13
GSM 1900MHz	Channel 512	29.89						
	Channel 661	29.86	19.3	-0.02	0.228	0.23	0.394	0.40
	Channel 810	29.83						
WCDMA 850MHz	Channel 4132	23.97	19.5	-0.01	0.734	0.74	1.09	1.09
	Channel 4180	23.93	19.5	-0.06	0.833	0.84	1.23	1.25
	Channel 4233	23.89	19.5	-0.03	0.810	0.82	1.21	1.22
WCDMA 1900MHz	Channel 9262	23.97						
	Channel 9400	23.86	19.2	-0.10	0.417	0.43	0.727	0.74
	Channel 9538	23.83						

Table 2: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.

Left Head 15° Tilt Position								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	10g SAR value		1g SAR value	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GSM 850MHz	Channel 128	32.93						
	Channel 190	32.84	20.7	0.21	0.188	0.19	0.257	0.26
	Channel 251	32.80						
GSM 1900MHz	Channel 512	29.89						
	Channel 661	29.86	19.3	-0.15	0.058	0.06	0.090	0.09
	Channel 810	29.83						
WCDMA 850MHz	Channel 4132	23.97						
	Channel 4180	23.93	19.5	0.13	0.225	0.23	0.306	0.31
	Channel 4233	23.89						
WCDMA 1900MHz	Channel 9262	23.97						
	Channel 9400	23.86	19.2	-0.08	0.112	0.11	0.175	0.18
	Channel 9538	23.83						

Table 3: SAR measurement results at the highest possible output power, measured in a head 15° Tilt position against the ICNIRP and ANSI SAR Limit.

Right Head 15° Tilt Position								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	10g SAR value		1g SAR value	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GSM 850MHz	Channel 128	32.93						
	Channel 190	32.84	20.5	-0.08	0.216	0.22	0.286	0.29
	Channel 251	32.80						
GSM 1900MHz	Channel 512	29.89						
	Channel 661	29.86	19.3	0.02	0.068	0.07	0.110	0.11
	Channel 810	29.83						
WCDMA 850MHz	Channel 4132	23.97						
	Channel 4180	23.93	19.2	0.00	0.239	0.24	0.314	0.31
	Channel 4233	23.89						
WCDMA 1900MHz	Channel 9262	23.97						
	Channel 9400	23.86	19.2	0.01	0.127	0.13	0.204	0.20
	Channel 9538	23.83						

Table 4: SAR measurement results at the highest possible output power, measured in a head 15° Tilt position against the ICNIRP and ANSI SAR Limit.

Highest Head with SNN5813A battery								
<i>f</i> (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	10g SAR value		1g SAR value	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GSM 850MHz	Channel 128	32.93	20.5	-0.06	0.716	0.73	1.07	1.09
	Channel 190	32.84	20.5	-0.04	0.723	0.73	1.08	1.09
	Channel 251	32.80	20.5	-0.07	0.698	0.71	1.05	1.07
GSM 1900MHz	Channel 512	29.89						
	Channel 661	29.86	19.3	-0.02	0.195	0.20	0.336	0.34
	Channel 810	29.83						
WCDMA 850MHz	Channel 4132	23.97	19.4	0.01	0.697	0.70	1.04	1.04
	Channel 4180	23.93	19.4	-0.38	0.800	0.87	1.20	1.31
	Channel 4233	23.89	19.4	0.01	0.781	0.78	1.17	1.17
WCDMA 1900MHz	Channel 9262	23.97	19.2	-0.59	0.469	0.54	0.811	0.93
	Channel 9400	23.86	19.2	-0.67	0.531	0.62	0.923	1.08
	Channel 9538	23.83	19.2	-0.30	0.514	0.55	0.894	0.96

Table 5: SAR measurement results at the highest possible output power, measured in a head position against the ICNIRP and ANSI SAR Limit.

PTT, 25mm away from flat phantom, GPRS Class 10								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	10g SAR value		1g SAR value	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GPRS 850MHz	Channel 128	32.93						
	Channel 190	32.84	20.5	-0.02	0.171	0.17	0.232	0.23
	Channel 251	32.80						
GPRS 1900MHz	Channel 512	29.89						
	Channel 661	29.86	18.2	0.01	0.151	0.15	0.238	0.24
	Channel 810	29.83						

Table 6: SAR measurement results at the highest possible output power, measured in a PTT position against the ICNIRP and ANSI SAR Limit.

PTT, 25mm away from flat phantom, EDGE Class 10								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	10g SAR value		1g SAR value	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
EDGE 850MHz	Channel 128	27.44						
	Channel 190	27.42	20.5	0.00	0.043	0.04	0.059	0.06
	Channel 251	27.37						
EDGE 1900MHz	Channel 512	26.49						
	Channel 661	26.46	19.7	0.01	0.036	0.04	0.056	0.06
	Channel 810	26.38						

Table 7: SAR measurement results at the highest possible output power, measured in a PTT position against the ICNIRP and ANSI SAR Limit.

6.2 Body Worn Test Results

The SAR results shown in tables 8 through 13 are maximum SAR values averaged over 1 gram of phantom tissue, to demonstrate compliance to [3] and also over 10 grams of phantom tissue, to demonstrate compliance to the [6]. Also shown are the measured conducted output power levels, the temperature of the test facility during the test, the temperature of the tissue simulate after the test, the measured drift and the extrapolated SAR. The exact method of extrapolation is $\text{New SAR} = \text{Old SAR} * 10^{(-\text{drift}/10)}$. The SAR reported at the end of the measurement process by the DASY4™ measurement system can be scaled up by the measured drift to determine the SAR at the beginning of the measurement process. This is the most conservative SAR because it corresponds to the average output power at the beginning of the SAR test. This extrapolation has been done because when the DUT is operating properly it may exhibit a slump in radiated power and SAR over time. This is verified by measuring the SAR drift after the test.

The test conditions that produced the highest SAR values in each band are indicated as bold numbers in the following tables and are included in Appendix 3. All other test conditions measured lower SAR values than those included in Appendix 3.

A “flat” phantom was for the body-worn tests. This “flat” phantom is made out of 1” thick natural High Density Polyethylene with a thickness at the bottom equal to 2.0mm. It measures 52.7cm(long) x 26.7cm(wide) x 21.2cm(tall). The measured dielectric constant of the material used is less than 2.3 and the loss tangent is less than 0.0046 all the way up to 2.184GHz.

The tissue stimulant depth was verified to be 15.0cm ±0.5cm. The same device holder described in section 6 was used for positioning the phone. The functional accessories were divided into two categories, the ones with metal components and the ones with non-metal components. For non-metallic component accessories, testing was performed on the accessory that displayed the closest proximity to the flat phantom. Each metallic component accessory, if any, was checked for uniqueness of metal component so that each is tested with the device. If multiple accessories shared an identical metal component, only the accessory that dictates the closest spacing to the body was tested. In addition to accessory testing, the cellular phone was tested with the front and back of the phone facing the phantom. For voice mode operation, the phone was placed as a distance of 15mm from the phantom. For data mode operation, the phone was placed as a distance of 25mm from the phantom. The cellular phone was tested with a headset connected to the device for all body-worn SAR measurements.

The following probe conversion factors were used on the E-Field probe(s) used for the body worn measurements:

Description	Serial Number	f (MHz)	Conversion Factor	Cal Cert pg #
E-Field Probe ET3DV6R	SN 1397	900	6.04	8 of 9
		1810	4.83	8 of 9

BodyWorn Front of Phone 15mm away from phantom								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	10g SAR value		1g SAR value	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GSM 850MHz	Channel 128	32.93						
	Channel 190	32.84	19.4	-0.07	0.252	0.26	0.349	0.35
	Channel 251	32.80						
GSM 1900MHz	Channel 512	29.89						
	Channel 661	29.86	20.0	-0.00	0.078	0.08	0.122	0.12
	Channel 810	29.83						
WCDMA 850MHz	Channel 4132	23.97						
	Channel 4180	23.93	18.6	-0.12	0.308	0.32	0.422	0.43
	Channel 4233	23.89						
WCDMA 1900MHz	Channel 9262	23.97						
	Channel 9400	23.86	19.1	-0.19	0.168	0.18	0.265	0.28
	Channel 9538	23.83						

Table 8: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

BodyWorn Back of Phone 15mm away from phantom								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	10g SAR value		1g SAR value	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GSM 850MHz	Channel 128	32.93						
	Channel 190	32.84	19.4	-0.07	0.431	0.44	0.614	0.62
	Channel 251	32.80						
GSM 1900MHz	Channel 512	29.89						
	Channel 661	29.86	20.0	-0.04	0.148	0.15	0.234	0.24
	Channel 810	29.83						
WCDMA 850MHz	Channel 4132	23.97						
	Channel 4180	23.93	18.6	-0.09	0.442	0.45	0.622	0.63
	Channel 4233	23.89						
WCDMA 1900MHz	Channel 9262	23.97						
	Channel 9400	23.86	19.1	-0.10	0.348	0.36	0.554	0.57
	Channel 9538	23.83						

Table 9: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

BodyWorn Bluetooth (Highest Body) 15mm away from phantom								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	10g SAR value		1g SAR value	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GSM 850MHz	Channel 128	32.93						
	Channel 190	32.84	19.4	-0.05	0.504	0.51	0.715	0.72
	Channel 251	32.80						
GSM 1900MHz	Channel 512	29.89						
	Channel 661	29.86	20.0	-0.03	0.149	0.15	0.236	0.24
	Channel 810	29.83						
WCDMA 850MHz	Channel 4132	23.97						
	Channel 4180	23.93	18.6	-0.09	0.543	0.55	0.759	0.78
	Channel 4233	23.89						
WCDMA 1900MHz	Channel 9262	23.97						
	Channel 9400	23.86	19.1	-0.16	0.381	0.40	0.609	0.63
	Channel 9538	23.83						

Table 10: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

BodyWorn GPRS Class 10 (Highest Body) 25mm away from phantom								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	10g SAR value		1g SAR value	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GPRS 850MHz	Channel 128	32.93						
	Channel 190	32.84	19.6	-0.02	0.223	0.22	0.307	0.31
	Channel 251	32.80						
GPRS 1900MHz	Channel 512	29.89						
	Channel 661	29.86	18.5	-0.04	0.123	0.12	0.194	0.20
	Channel 810	29.83						

Table 11: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

BodyWorn Edge Class 10 (Highest Body) 25mm away from phantom								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	10g SAR value		1g SAR value	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
EDGE 850MHz	Channel 128	27.44						
	Channel 190	27.42	19.6	-0.02	0.058	0.06	0.079	0.08
	Channel 251	27.37						
EDGE 1900MHz	Channel 512	26.49						
	Channel 661	26.46	19.3	-0.36	0.019	0.02	0.029	0.03
	Channel 810	26.38						

Table 12: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

BodyWorn Highest Body with SNN5813A battery								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	10g SAR value		1g SAR value	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GSM 850MHz	Channel 128	32.93						
	Channel 190	32.84	19.4	-0.04	0.415	0.42	0.597	0.60
	Channel 251	32.80						
GSM 1900MHz	Channel 512	29.89						
	Channel 661	29.86	18.0	-0.00	0.149	0.15	0.241	0.24
	Channel 810	29.83						
WCDMA 850MHz	Channel 4132	23.97						
	Channel 4180	23.93	18.6	-0.10	0.557	0.57	0.780	0.80
	Channel 4233	23.89						
WCDMA 1900MHz	Channel 9262	23.97						
	Channel 9400	23.86	19.1	-0.13	0.367	0.38	0.586	0.60
	Channel 9538	23.83						

Table 13: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

References

- [1] CENELEC, en62209-1:2006 “Human Exposure to Radio Frequency Fields From Hand - Held and Body - Mounted Wireless Communication Devices – Human Models, Instrumentation, and Procedures”
- [2] CENELEC, en50360:2001 “Product standard to demonstrate the compliance of mobile phones with the basic restrictions related to human exposure to electromagnetic fields (300MHz – 3GHz)”.
- [3] ANSI / IEEE, C95.1 1999 Edition “IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300GHz”
- [4] FCC OET Bulletin 65 Supplement C 01-01
- [5] IEEE 1528 2003 Edition “IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”
- [6] ICNIRP Guidelines “Guidelines for Limiting Exposure to Time-Varying Electric, Magnetic, and Electromagnetic Fields (up to 300 GHz)”

Appendix 1

SAR distribution comparison for the system accuracy verification

Date/Time: 9/10/2007 12:28:36 PM

Test Laboratory: Motorola

DUT: Dipole 900 MHz; Type: D900V2; Procedure Notes: 900 MHz System Performance Check /

Dipole Sn# 091; PM1 Power = 200 mW

Sim.Temp@ meas = 20°C; Sim.Temp@ SPC = 20°C; Room Temp@ SPC = 20.5°C;

Communication System: CW - Dipole; Frequency: 900 MHz; Duty Cycle: 1:1

Medium: VALIDATION Only; Medium parameters used: $f = 900 \text{ MHz}$; $\sigma = 0.97 \text{ mho/m}$; $\epsilon_r = 41.3$; $\rho = 1000 \text{ kg/m}^3$

DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(6.25, 6.25, 6.25); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Sugar SAM; Type: SAM; Serial: TP-1005;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Daily SPC Check/Dipole Area Scan (4x9x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 2.23 mW/g

Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 49.4 V/m; Power Drift = -0.015 dB

Peak SAR (extrapolated) = 3.14 W/kg

SAR(1 g) = 2.13 mW/g; SAR(10 g) = 1.38 mW/g

Maximum value of SAR (measured) = 2.31 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 49.4 V/m; Power Drift = -0.015 dB

Peak SAR (extrapolated) = 3.36 W/kg



SAR(1 g) = 2.27 mW/g; SAR(10 g) = 1.46 mW/g

Maximum value of SAR (measured) = 2.46 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):

Measurement grid: dx=20mm, dy=20mm, dz=5mm

Maximum value of SAR (measured) = 2.32 mW/g



Date/Time: 9/7/2007 10:05:49 AM

Test Laboratory: Motorola

DUT: Dipole 900 MHz; Type: D900V2; Procedure Notes: 900 MHz System Performance Check /

Dipole Sn# 091; PM1 Power = 200 mW;

Sim.Temp@ meas = 19.6°C; Sim.Temp@ SPC = 19.6°C; Room Temp@ SPC = 20.3°C

Communication System: CW - Dipole; Frequency: 900 MHz; Duty Cycle: 1:1

Medium: VALIDATION Only; Medium parameters used: $f = 900 \text{ MHz}$; $\sigma = 0.98 \text{ mho/m}$; $\epsilon_r = 41.5$; $\rho = 1000 \text{ kg/m}^3$

DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(6.25, 6.25, 6.25); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Sugar SAM; Type: SAM; Serial: TP-1005;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Daily SPC Check/Dipole Area Scan (4x9x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 2.34 mW/g

Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 50.4 V/m; Power Drift = -0.051 dB

Peak SAR (extrapolated) = 3.30 W/kg

SAR(1 g) = 2.24 mW/g; SAR(10 g) = 1.45 mW/g

Maximum value of SAR (measured) = 2.42 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 50.4 V/m; Power Drift = -0.051 dB

Peak SAR (extrapolated) = 3.50 W/kg



SAR(1 g) = 2.37 mW/g; SAR(10 g) = 1.53 mW/g

Maximum value of SAR (measured) = 2.56 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):

Measurement grid: dx=20mm, dy=20mm, dz=5mm

Maximum value of SAR (measured) = 2.43 mW/g



Date/Time: 9/6/2007 7:24:16 AM

Test Laboratory: Motorola

DUT: Dipole 900 MHz; Type: D900V2; Procedure Notes: 900MHz System Performance Check /
 Dipole Sn# 91; PM1 Power = 200 mW;
 Sim.Temp@ meas = 19.8°C; Sim.Temp@ SPC = 19.8°C; Room Temp@ SPC = 20.4°C

Communication System: CW - Dipole; Frequency: 900 MHz; Duty Cycle: 1:1
 Medium: VALIDATION Only; Medium parameters used: $f = 900 \text{ MHz}$; $\sigma = 0.96 \text{ mho/m}$; $\epsilon_r = 40$; $\rho = 1000 \text{ kg/m}^3$

DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(6.25, 6.25, 6.25); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Sugar SAM; Type: SAM; Serial: TP-1005;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Daily SPC Check/Dipole Area Scan (4x9x1):

Measurement grid: dx=15mm, dy=15mm
 Maximum value of SAR (measured) = 2.31 mW/g

Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm
 Reference Value = 49.0 V/m; Power Drift = -0.038 dB
 Peak SAR (extrapolated) = 3.15 W/kg
SAR(1 g) = 2.14 mW/g; SAR(10 g) = 1.38 mW/g
 Maximum value of SAR (measured) = 2.32 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm
 Reference Value = 49.0 V/m; Power Drift = -0.038 dB
 Peak SAR (extrapolated) = 3.38 W/kg
SAR(1 g) = 2.28 mW/g; SAR(10 g) = 1.47 mW/g
 Maximum value of SAR (measured) = 2.48 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):

Measurement grid: dx=20mm, dy=20mm, dz=5mm
 Maximum value of SAR (measured) = 2.33 mW/g



Date/Time: 9/2/2007 6:15:10 PM

Test Laboratory: Motorola

DUT: Dipole 900 MHz; Type: D900V2; Procedure Notes: 900 MHz System Performance Check /

Dipole Sn# 91; PM1 Power = 200 mW;

Sim.Temp@ meas = 20.7°C; Sim.Temp@ SPC = 20.6°C; Room Temp@ SPC = 20.1°C

Communication System: CW - Dipole; Frequency: 900 MHz; Duty Cycle: 1:1

Medium: VALIDATION Only; Medium parameters used: $f = 900$ MHz; $\sigma = 0.96$ mho/m; $\epsilon_r = 40.5$; $\rho = 1000$ kg/m³

DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(6.25, 6.25, 6.25); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Sugar SAM; Type: SAM; Serial: TP-1005;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Daily SPC Check/Dipole Area Scan (4x9x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 2.16 mW/g

Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 50.8 V/m; Power Drift = -0.045 dB

Peak SAR (extrapolated) = 3.22 W/kg

SAR(1 g) = 2.16 mW/g; SAR(10 g) = 1.39 mW/g

Maximum value of SAR (measured) = 2.35 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 50.8 V/m; Power Drift = -0.045 dB



Peak SAR (extrapolated) = 3.40 W/kg

SAR(1 g) = 2.28 mW/g; SAR(10 g) = 1.47 mW/g

Maximum value of SAR (measured) = 2.48 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):

Measurement grid: dx=20mm, dy=20mm, dz=5mm



Date/Time: 9/1/2007 6:18:59 PM

Test Laboratory: Motorola

DUT: Dipole 900 MHz; Type: D900V2; Procedure Notes: 900 MHz System Performance Check /

Dipole Sn# 91; PM1 Power = 200mW;

Sim.Temp@ meas = 20.7°C; Sim.Temp@ SPC = 20.6°C; Room Temp@ SPC = 20.1°C

Communication System: CW - Dipole; Frequency: 900 MHz; Duty Cycle: 1:1

Medium: VALIDATION Only; Medium parameters used: $f = 900 \text{ MHz}$; $\sigma = 0.96 \text{ mho/m}$; $\epsilon_r = 41.2$; $\rho = 1000 \text{ kg/m}^3$

DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(6.25, 6.25, 6.25); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Sugar SAM; Type: SAM; Serial: TP-1005;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Daily SPC Check/Dipole Area Scan (4x9x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 2.24 mW/g

Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 49.6 V/m; Power Drift = -0.060 dB

Peak SAR (extrapolated) = 3.15 W/kg

SAR(1 g) = 2.13 mW/g; SAR(10 g) = 1.37 mW/g

Maximum value of SAR (measured) = 2.30 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 49.6 V/m; Power Drift = -0.060 dB



Peak SAR (extrapolated) = 3.33 W/kg

SAR(1 g) = 2.24 mW/g; SAR(10 g) = 1.44 mW/g

Maximum value of SAR (measured) = 2.40 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):

Measurement grid: dx=20mm, dy=20mm, dz=5mm



Date/Time: 9/13/2007 7:30:42 AM

Test Laboratory: Motorola

DUT: Dipole 900 MHz; Type: D900V2; Procedure Notes: 900 MHz System Performance Check /

Dipole Sn# 91; PM1 Power = 200mW;

Sim.Temp@ meas = 19.1°C; Sim.Temp@ SPC = 19.1°C; Room Temp @ SPC = 20.5°C

Communication System: CW - Dipole; Frequency: 900 MHz; Duty Cycle: 1:1

Medium: VALIDATION Only; Medium parameters used: $f = 900 \text{ MHz}$; $\sigma = 0.98 \text{ mho/m}$; $\epsilon_r = 41.7$; $\rho = 1000 \text{ kg/m}^3$

DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(6.25, 6.25, 6.25); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Sugar SAM; Type: SAM; Serial: TP-1005;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Daily SPC Check/Dipole Area Scan (4x9x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 2.36 mW/g

Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 47.6 V/m; Power Drift = -0.024 dB

Peak SAR (extrapolated) = 3.21 W/kg

SAR(1 g) = 2.17 mW/g; SAR(10 g) = 1.4 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 47.6 V/m; Power Drift = -0.024 dB



Peak SAR (extrapolated) = 3.40 W/kg

SAR(1 g) = 2.3 mW/g; SAR(10 g) = 1.48 mW/g

Maximum value of SAR (measured) = 2.48 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):

Measurement grid: dx=20mm, dy=20mm, dz=5mm



Date/Time: 9/12/2007 6:49:16 AM

Test Laboratory: Motorola

DUT: Dipole 1800 MHz; Type: D1800V2; Procedure Notes: 1800 MHz System Performance Check /
Dipole Sn# 259tr; PM1 Power = 200 mW
Sim.Temp@ meas = 19.4°C; Sim.Temp@ SPC = 19.8°C; Room Temp@ SPC = 19.7°C

Communication System: CW - Dipole; Frequency: 1800 MHz; Duty Cycle: 1:1
Medium: VALIDATION Only; Medium parameters used: $f = 1800 \text{ MHz}$; $\sigma = 1.37 \text{ mho/m}$; $\epsilon_r = 38.3$; $\rho = 1000 \text{ kg/m}^3$

DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(5.17, 5.17, 5.17); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Glycol SAM; Type: SAM; Serial: TP-1139;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Daily SPC Check/Dipole Area Scan (4x9x1):

Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 7.17 mW/g

Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 59.7 V/m; Power Drift = -0.047 dB
Peak SAR (extrapolated) = 11.8 W/kg
SAR(1 g) = 7.12 mW/g; SAR(10 g) = 3.85 mW/g
Maximum value of SAR (measured) = 8.06 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 59.7 V/m; Power Drift = -0.047 dB
Peak SAR (extrapolated) = 12.5 W/kg
SAR(1 g) = 7.52 mW/g; SAR(10 g) = 4.07 mW/g
Maximum value of SAR (measured) = 8.36 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):

Measurement grid: dx=20mm, dy=20mm, dz=5mm
Maximum value of SAR (measured) = 8.10 mW/g



Date/Time: 9/8/2007 6:57:01 PM

Test Laboratory: Motorola

DUT: Dipole 1800 MHz; Type: D1800V2; Procedure Notes: 1800 MHz System Performance Check /
 Dipole Sn# 259tr; PM1 Power = 200 mW
 Sim.Temp@ meas = 19.8°C; Sim.Temp@ SPC = 19.8°C; Room Temp@ SPC = 20.4°C

Communication System: CW - Dipole; Frequency: 1800 MHz; Duty Cycle: 1:1
 Medium: VALIDATION Only; Medium parameters used: $f = 1800 \text{ MHz}$; $\sigma = 1.36 \text{ mho/m}$; $\epsilon_r = 39$; $\rho = 1000 \text{ kg/m}^3$

DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(5.17, 5.17, 5.17); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Glycol SAM; Type: SAM; Serial: TP-1139;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Daily SPC Check/Dipole Area Scan (4x9x1):

Measurement grid: dx=15mm, dy=15mm
 Maximum value of SAR (measured) = 6.90 mW/g

Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm
 Reference Value = 80.4 V/m; Power Drift = -0.055 dB
 Peak SAR (extrapolated) = 11.6 W/kg
SAR(1 g) = 7.01 mW/g; SAR(10 g) = 3.8 mW/g
 Maximum value of SAR (measured) = 7.87 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm
 Reference Value = 80.4 V/m; Power Drift = -0.055 dB
 Peak SAR (extrapolated) = 12.6 W/kg
SAR(1 g) = 7.52 mW/g; SAR(10 g) = 4.06 mW/g
 Maximum value of SAR (measured) = 8.38 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):

Measurement grid: dx=20mm, dy=20mm, dz=5mm
 Maximum value of SAR (measured) = 7.91 mW/g



Date/Time: 9/7/2007 9:22:34 AM

Test Laboratory: Motorola

DUT: Dipole 1800 MHz; Type: D1800V2; Procedure Notes: 1800 MHz System Performance Check /
Dipole Sn# 259TR; PM1 Power = 200 mW
Sim.Temp@ meas = 19.5°C; Sim.Temp@ SPC = 19.5°C; Room Temp@ SPC = 20.3°C

Communication System: CW - Dipole; Frequency: 1800 MHz; Duty Cycle: 1:1
Medium: VALIDATION Only; Medium parameters used: $f = 1800$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 39$; $\rho = 1000$ kg/m³

DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(5.17, 5.17, 5.17); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Sect.2, Amy Twin; Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Daily SPC Check/Dipole Area Scan (9x4x1):

Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 6.94 mW/g

Daily SPC Check/0-Degree 5x5x7 Cube (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 82.0 V/m; Power Drift = -0.041 dB
Peak SAR (extrapolated) = 12.5 W/kg
SAR(1 g) = 7.46 mW/g; SAR(10 g) = 4.03 mW/g
Maximum value of SAR (measured) = 8.37 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 82.0 V/m; Power Drift = -0.041 dB
Peak SAR (extrapolated) = 13.3 W/kg
SAR(1 g) = 7.9 mW/g; SAR(10 g) = 4.25 mW/g
Maximum value of SAR (measured) = 8.92 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):

Measurement grid: dx=20mm, dy=20mm, dz=5mm
Maximum value of SAR (measured) = 8.40 mW/g



Date/Time: 9/4/2007 7:42:53 AM

Test Laboratory: Motorola

DUT: Dipole 1800 MHz; Type: D1800V2; Procedure Notes: 1800 MHz System Performance Check /
 Dipole Sn# 259tr; PM1 Power = 200 mW
 Sim.Temp@ meas = 19.4°C; Sim.Temp@ SPC = 19.4°C; Room Temp@ SPC = 20.6°C

Communication System: CW - Dipole; Frequency: 1800 MHz; Duty Cycle: 1:1
 Medium: VALIDATION Only; Medium parameters used: $f = 1800 \text{ MHz}$; $\sigma = 1.39 \text{ mho/m}$; $\epsilon_r = 40.5$; $\rho = 1000 \text{ kg/m}^3$

DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(5.17, 5.17, 5.17); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Glycol SAM; Type: SAM; Serial: TP-1139;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Daily SPC Check/Dipole Area Scan (4x9x1):

Measurement grid: dx=15mm, dy=15mm
 Maximum value of SAR (measured) = 6.63 mW/g

Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm
 Reference Value = 77.9 V/m; Power Drift = -0.005 dB
 Peak SAR (extrapolated) = 11.6 W/kg
SAR(1 g) = 7.05 mW/g; SAR(10 g) = 3.83 mW/g
 Maximum value of SAR (measured) = 7.89 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm
 Reference Value = 77.9 V/m; Power Drift = -0.005 dB
 Peak SAR (extrapolated) = 12.5 W/kg
SAR(1 g) = 7.57 mW/g; SAR(10 g) = 4.12 mW/g
 Maximum value of SAR (measured) = 8.49 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):

Measurement grid: dx=20mm, dy=20mm, dz=5mm
 Maximum value of SAR (measured) = 7.94 mW/g



Date/Time: 8/31/2007 7:07:31 AM

Test Laboratory: Motorola

DUT: Dipole 1800 MHz; Type: D1800V2; Procedure Notes: 1800 MHz System Performance Check / Dipole Sn# 259TR; PM1 Power = 200 mW;
Sim.Temp@ meas = 19.1°C; Sim.Temp@ SPC = 19.5°C; Room Temp@ SPC = 20.1°C

Communication System: CW - Dipole; Frequency: 1800 MHz; Duty Cycle: 1:1
Medium: VALIDATION Only; Medium parameters used: $f = 1800 \text{ MHz}$; $\sigma = 1.37 \text{ mho/m}$; $\epsilon_r = 38.5$; $\rho = 1000 \text{ kg/m}^3$

DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(5.17, 5.17, 5.17); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Sect.2, Amy Twin; Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Daily SPC Check/Dipole Area Scan (9x4x1):

Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 7.40 mW/g

Daily SPC Check/0-Degree 5x5x7 Cube (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 78.2 V/m; Power Drift = -0.075 dB
Peak SAR (extrapolated) = 12.5 W/kg
SAR(1 g) = 7.46 mW/g; SAR(10 g) = 4 mW/g
Maximum value of SAR (measured) = 8.43 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 78.2 V/m; Power Drift = -0.075 dB
Peak SAR (extrapolated) = 13.3 W/kg
SAR(1 g) = 7.83 mW/g; SAR(10 g) = 4.2 mW/g
Maximum value of SAR (measured) = 8.68 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):

Measurement grid: dx=20mm, dy=20mm, dz=5mm
Maximum value of SAR (measured) = 8.36 mW/g



Date/Time: 9/19/2007 7:02:23 AM

Test Laboratory: Motorola

DUT: Dipole 1800 MHz; Type: D1800V2; Procedure Notes: 1800 MHz System Performance Check /
 Dipole Sn# 259tr; PM1 Power = 200 mW
 Sim.Temp@ meas = 20.2°C; Sim.Temp@ SPC = 20.3°C; Room Temp@ SPC = 20.5°C

Communication System: CW - Dipole; Frequency: 1800 MHz; Duty Cycle: 1:1
 Medium: VALIDATION Only; Medium parameters used: $f = 1800$ MHz; $\sigma = 1.38$ mho/m; $\epsilon_r = 40.2$; $\rho = 1000$ kg/m³

DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(5.17, 5.17, 5.17); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Glycol SAM; Type: SAM; Serial: TP-1139;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Daily SPC Check/Dipole Area Scan (4x9x1):

Measurement grid: dx=15mm, dy=15mm
 Maximum value of SAR (measured) = 7.75 mW/g

Daily SPC Check/0-Degree, 5x5x7 Cube (5x5x7)/Cube 0:



Measurement grid: dx=8mm, dy=8mm, dz=5mm
 Reference Value = 77.0 V/m; Power Drift = -0.004 dB
 Peak SAR (extrapolated) = 11.8 W/kg
SAR(1 g) = 7.18 mW/g; SAR(10 g) = 3.9 mW/g
 Maximum value of SAR (measured) = 7.94 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm
 Reference Value = 77.0 V/m; Power Drift = -0.004 dB
 Peak SAR (extrapolated) = 12.6 W/kg
SAR(1 g) = 7.58 mW/g; SAR(10 g) = 4.09 mW/g
 Maximum value of SAR (measured) = 8.35 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):

Measurement grid: dx=20mm, dy=20mm, dz=5mm
 Maximum value of SAR (measured) = 8.14 mW/g



Appendix 2

SAR distribution plots for Phantom Head Adjacent Use

Date/Time: 9/4/2007 11:05:55 AM


Test Laboratory: Motorola

Serial: LKW0390036; Procedure Notes: Pwr Step: 0; Accessory Model #: n/a; Battery Model #: SNN5782B; DEVICE POSITION: cheek; Communication System: GSM 1900; Frequency: 1880 MHz; Communication System Channel Number: 661; Duty Cycle: 1:8; Medium: Regular Glycol Head; Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.47 \text{ mho/m}$; $\epsilon_r = 40.1$; $\rho = 1000 \text{ kg/m}^3$; DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(5.17, 5.17, 5.17); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Glycol SAM; Type: SAM; Serial: TP-1139;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Right Head Template/Area Scan - Normal (15mm) (7x17x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$; Maximum value of SAR (measured) = 0.414 mW/g

Right Head Template/5x5x7 Zoom Scan ($\leq 3\text{GHz}$) (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$; Reference Value = 16.7 V/m; Power Drift = -0.025 dB; Peak SAR (extrapolated) = 0.622 W/kg; **SAR(1 g) = 0.394 mW/g; SAR(10 g) = 0.228 mW/g;** Maximum value of SAR (measured) = 0.436 mW/g



Date/Time: 9/2/2007 11:17:55 PM


Test Laboratory: Motorola

Serial: LKW0390036; Procedure Notes: Pwr Step: 5; Accessory Model #: n/a; Battery Model #: SNN5782B; DEVICE POSITION: cheek; Communication System: GSM 850; Frequency: 824.2 MHz; Communication System Channel Number: 128; Duty Cycle: 1:8; Medium: Low Freq Head; Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.9 \text{ mho/m}$; $\epsilon_r = 41.2$; $\rho = 1000 \text{ kg/m}^3$; DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(6.25, 6.25, 6.25); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Sugar SAM; Type: SAM; Serial: TP-1005;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Right Head Template/Area Scan - Normal (10mm) (10x25x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$; Maximum value of SAR (measured) = 1.20 mW/g

Right Head Template/5x5x7 Zoom Scan ($\leq 3\text{GHz}$) (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$; Reference Value = 38.2 V/m; Power Drift = -0.058 dB; Peak SAR (extrapolated) = 1.66 W/kg; **SAR(1 g) = 1.13 mW/g**; **SAR(10 g) = 0.749 mW/g**; Maximum value of SAR (measured) = 1.23 mW/g



Date/Time: 9/19/2007 8:19:10 AM

Test Laboratory: Motorola

Serial: LKW0390036; Procedure Notes: Pwr Step: always up; Accessory Model #: n/a; Battery Model #: SNN5813A; DEVICE POSITION: cheek; Communication System: 3G/WCDMA 1900; Frequency: 1880 MHz; Communication System Channel Number: 9400; Duty Cycle: 1:1; Medium: Regular Glycol Head; Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.46 \text{ mho/m}$; $\epsilon_r = 39.8$; $\rho = 1000 \text{ kg/m}^3$; DASY4 Configuration:


- Probe: ET3DV6R - SN1397; ConvF(5.17, 5.17, 5.17); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R#1 Glycol SAM (extended range), Rev.1 (25-Mar-05); Type: SAM v4.0; Serial: TP-1139;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Left Head Template to Shift Cube/Area Scan - Normal Extended (10mm) (10x28x1):

Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$; Maximum value of SAR (measured) = 0.994 mW/g

Left Head Template to Shift Cube/5x5x7 Zoom Scan ($\leq 3\text{GHz}$) - shifted (5x5x7)/Cube

0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$; Reference Value = 26.9 V/m ; Power Drift = -0.665 dB ; Peak SAR (extrapolated) = 1.48 W/kg ; **SAR(1 g) = 0.923 mW/g ; SAR(10 g) = 0.531 mW/g** ; Maximum value of SAR (measured) = 0.960 mW/g



Date/Time: 9/6/2007 7:14:25 PM


Test Laboratory: Motorola

Serial: LKW0390036; Procedure Notes: Pwr Step: all up; Accessory Model #: n/a; Battery Model #: SNN5782B; DEVICE POSITION: cheek; Communication System: 3G-WCDMA 850; Frequency: 836 MHz; Communication System Channel Number: 4180; Duty Cycle: 1:1; Medium: Low Freq Head; Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.9 \text{ mho/m}$; $\epsilon_r = 40.8$; $\rho = 1000 \text{ kg/m}^3$; DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(6.25, 6.25, 6.25); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Sugar SAM; Type: SAM; Serial: TP-1005;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Left Head Template/Area Scan - Normal (15mm) (7x17x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$; Maximum value of SAR (measured) = 1.35 mW/g

Left Head Template/5x5x7 Zoom Scan ($\leq 3\text{GHz}$) (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$; Reference Value = 37.5 V/m; Power Drift = -0.206 dB; Peak SAR (extrapolated) = 1.82 W/kg; **SAR(1 g) = 1.26 mW/g; SAR(10 g) = 0.841 mW/g;** Maximum value of SAR (measured) = 1.36 mW/g



Date/Time: 9/7/2007 4:18:26 PM


Test Laboratory: Motorola

Serial: LKW0390036; Procedure Notes: Pwr Step: always up; Accessory Model #: n/a; Battery Model #: SNN5782B; DEVICE POSITION: TILT; Communication System: 3G-WCDMA 850; Frequency: 836 MHz; Communication System Channel Number: 4180; Duty Cycle: 1:1; Medium: Low Freq Head; Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.92 \text{ mho/m}$; $\epsilon_r = 42.3$; $\rho = 1000 \text{ kg/m}^3$; DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(6.25, 6.25, 6.25); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R#1 Sugar SAM (extended range), Rev.1 (25-Mar-05); Type: SAM v4.0; Serial: TP-???
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Right Head Template/Area Scan - Normal (15mm) (7x17x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$; Maximum value of SAR (measured) = 0.327 mW/g

Right Head Template/5x5x7 Zoom Scan ($\leq 3\text{GHz}$) (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$; Reference Value = 19.4 V/m; Power Drift = 0.002 dB; Peak SAR (extrapolated) = 0.386 W/kg; **SAR(1 g) = 0.314 mW/g**; **SAR(10 g) = 0.239 mW/g**; Maximum value of SAR (measured) = 0.330 mW/g



Date/Time: 9/4/2007 12:35:27 PM


Test Laboratory: Motorola

Serial: LKW0390036; Procedure Notes: Pwr Step: 0; Accessory Model #: n/a; Battery Model #: SNN5782B; DEVICE POSITION: Tilt; Communication System: GSM 1900; Frequency: 1880 MHz; Communication System Channel Number: 661; Duty Cycle: 1:8; Medium: Regular Glycol Head; Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.47 \text{ mho/m}$; $\epsilon_r = 40.1$; $\rho = 1000 \text{ kg/m}^3$; DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(5.17, 5.17, 5.17); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Glycol SAM; Type: SAM; Serial: TP-1139;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Right Head Template/Area Scan - Normal (15mm) (7x17x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$; Maximum value of SAR (measured) = 0.110 mW/g

Right Head Template/5x5x7 Zoom Scan ($\leq 3\text{GHz}$) (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$; Reference Value = 8.80 V/m; Power Drift = 0.017 dB; Peak SAR (extrapolated) = 0.161 W/kg; **SAR(1 g) = 0.110 mW/g; SAR(10 g) = 0.068 mW/g;** Maximum value of SAR (measured) = 0.120 mW/g



Date/Time: 9/3/2007 12:06:17 AM


Test Laboratory: Motorola

Serial: LKW0390036; Procedure Notes: Pwr Step: 5; Accessory Model #: n/a; Battery Model #: SNN5782B; DEVICE POSITION: Tilt; Communication System: GSM 850; Frequency: 836.6 MHz; Communication System Channel Number: 190; Duty Cycle: 1:8; Medium: Low Freq Head; Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.9 \text{ mho/m}$; $\epsilon_r = 41.2$; $\rho = 1000 \text{ kg/m}^3$; DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(6.25, 6.25, 6.25); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Sugar SAM; Type: SAM; Serial: TP-1005;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Right Head Template/Area Scan - Normal (10mm) (10x25x1): Measurement grid: $dx=10\text{mm}$, $dy=10\text{mm}$; Maximum value of SAR (measured) = 0.305 mW/g

Right Head Template/5x5x7 Zoom Scan ($\leq 3\text{GHz}$) (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$; Reference Value = 19.0 V/m; Power Drift = -0.077 dB; Peak SAR (extrapolated) = 0.357 W/kg; **SAR(1 g) = 0.286 mW/g**; **SAR(10 g) = 0.216 mW/g**; Maximum value of SAR (measured) = 0.299 mW/g



Date/Time: 9/7/2007 9:01:20 PM


Test Laboratory: Motorola

Serial: LKW0390036; Procedure Notes: Pwr Step: always up; Accessory Model #: n/a; Battery Model #: SNN5782B; DEVICE POSITION: Tilt; Communication System: 3G/WCDMA 1900; Frequency: 1880 MHz; Communication System Channel Number: 9400; Duty Cycle: 1:1; Medium: Backup Glycol Head; Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.39 \text{ mho/m}$; $\epsilon_r = 39$; $\rho = 1000 \text{ kg/m}^3$; DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(5.17, 5.17, 5.17); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R#1 Glycol SAM (extended range), Rev.1 (25-Mar-05); Type: SAM v4.0; Serial: TP-1139;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Right Head Template/Area Scan - Normal (15mm) (7x17x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$; Maximum value of SAR (measured) = 0.211 mW/g

Right Head Template/5x5x7 Zoom Scan ($\leq 3\text{GHz}$) (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$; Reference Value = 12.5 V/m; Power Drift = 0.015 dB; Peak SAR (extrapolated) = 0.293 W/kg; **SAR(1 g) = 0.204 mW/g; SAR(10 g) = 0.127 mW/g;** Maximum value of SAR (measured) = 0.224 mW/g



Date/Time: 9/10/2007 5:03:18 PM

Test Laboratory: Motorola

Serial: LKW0390036; Procedure Notes: Pwr Step: 5; Battery Model #: SNN5782B; DEVICE POSITION: Push-to-Talk GPRS CLASS 10, 25MM AWAY FROM PHANTOM, PHONE OPEN; Communication System: GPRS 850 - Class 10; Frequency: 836.6 MHz; Communication System Channel Number: 190; Duty Cycle: 1:4; Medium: Low Freq Head; Medium parameters used: $f = 835$ MHz; $\sigma = 0.91$ mho/m; $\epsilon_r = 42$; $\rho = 1000$ kg/m³; DASY4 Configuration:


- Probe: ET3DV6R - SN1397; ConvF(6.25, 6.25, 6.25); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Sugar SAM; Type: SAM; Serial: TP-1005;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

SAM Phone Against Flat Section/Area Scan - Normal Body (15mm) (13x7x1):

Measurement grid: dx=15mm, dy=15mm; Maximum value of SAR (measured) = 0.247 mW/g

SAM Phone Against Flat Section/5x5x7 Zoom Scan (<=3GHz) (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm; Reference Value = 16.2 V/m; Power Drift = -0.016 dB; Peak SAR (extrapolated) = 0.297 W/kg; **SAR(1 g) = 0.232 mW/g; SAR(10 g) = 0.171 mW/g;** Maximum value of SAR (measured) = 0.246 mW/g



Date/Time: 9/12/2007 7:33:25 PM


Test Laboratory: Motorola

Serial: LKW0390036; Procedure Notes: Pwr Step: 0; Battery Model #: SNN5782B; Accessory Model # = N/A; DEVICE POSITION: Push-to-Talk; Phone Open, 25mm from Flat Phantom; Communication System: GPRS 1900 - Class 10; Frequency: 1880 MHz; Communication System Channel Number: 661; Duty Cycle: 1:4; Medium: Backup Glycol Head; Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.47 \text{ mho/m}$; $\epsilon_r = 38$; $\rho = 1000 \text{ kg/m}^3$; DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(5.17, 5.17, 5.17); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Glycol SAM; Type: SAM; Serial: TP-1139;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

SAM Phone Against Flat Section/Area Scan - Full Body (15mm) (21x15x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$; Maximum value of SAR (measured) = 0.262 mW/g

SAM Phone Against Flat Section/5x5x7 Zoom Scan ($\leq 3\text{GHz}$) (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$; Reference Value = 14.0 V/m ; Power Drift = 0.007 dB ; Peak SAR (extrapolated) = 0.345 W/kg ; **SAR(1 g) = 0.238 mW/g ; SAR(10 g) = 0.151 mW/g ;** Maximum value of SAR (measured) = 0.256 mW/g



Appendix 3

SAR distribution plots for Body Worn Configuration

Date/Time: 9/6/2007 6:27:45 PM


Test Laboratory: Motorola

Serial: LKW0390036; Procedure Notes: Pwr Step: always up; Antenna Position: internal; Battery Model #: SNN5813A; Accessory Model #: n/a; DEVICE POSITION: BLUETOOTH BACK OF PHONE WITH SNN5813A BATTERY; Communication System: 3G-WCDMA 850; Frequency: 836 MHz; Communication System Channel Number: 4180; Duty Cycle: 1:1; Medium: Low Freq Body; Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.97 \text{ mho/m}$; $\epsilon_r = 53$; $\rho = 1000 \text{ kg/m}^3$; DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(6.04, 6.04, 6.04); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Sect.1, Amy Twin; Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Amy Twin Phone Template/Area Scan - Normal Body (15mm) (13x7x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$; Maximum value of SAR (measured) = 0.795 mW/g

Amy Twin Phone Template/5x5x7 Zoom Scan ($\leq 3\text{GHz}$) (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$; Reference Value = 28.8 V/m; Power Drift = -0.101 dB; Peak SAR (extrapolated) = 1.01 W/kg; **SAR(1 g) = 0.780 mW/g; SAR(10 g) = 0.557 mW/g;** Maximum value of SAR (measured) = 0.834 mW/g



Date/Time: 9/8/2007 9:33:37 PM


Test Laboratory: Motorola

Serial: LKW0390036; Procedure Notes: Pwr Step: 0; Battery Model #: SNN5782B; Accessory Model #: n/a; DEVICE POSITION: BODYWORN BACK OF PHONE 15MM AWAY FROM PHANTOM WITH BLUETOOTH ENABLED; Communication System: GSM 1900; Frequency: 1880 MHz; Communication System Channel Number: 661; Duty Cycle: 1:8; Medium: Regular Glycol Body; Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.57 \text{ mho/m}$; $\epsilon_r = 51.1$; $\rho = 1000 \text{ kg/m}^3$; DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(4.83, 4.83, 4.83); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Sect.2, Amy Twin; Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Amy Twin Phone Template/Area Scan - Normal Body (15mm) (13x7x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$; Maximum value of SAR (measured) = 0.243 mW/g

Amy Twin Phone Template/5x5x7 Zoom Scan ($\leq 3\text{GHz}$) (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$; Reference Value = 12.2 V/m; Power Drift = -0.030 dB; Peak SAR (extrapolated) = 0.373 W/kg; **SAR(1 g) = 0.236 mW/g; SAR(10 g) = 0.149 mW/g;** Maximum value of SAR (measured) = 0.251 mW/g



Date/Time: 9/13/2007 10:00:45 AM


Test Laboratory: Motorola

Serial: LKW0390036; Procedure Notes: Pwr Step: 05; Battery Model #: SNN5782B; Accessory Model #: n/a; DEVICE POSITION: BODYWORN (BLUETOOTH) BACK OF PHONE 15MM AWAY FROM PHANTOM; Communication System: GSM 850; Frequency: 836.6 MHz; Communication System Channel Number: 190; Duty Cycle: 1:8; Medium: Low Freq Body; Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.97 \text{ mho/m}$; $\epsilon_r = 53.3$; $\rho = 1000 \text{ kg/m}^3$; DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(6.04, 6.04, 6.04); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Sect.1, Amy Twin; Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Amy Twin Phone Template/Area Scan - Normal Body (15mm) (13x7x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$; Maximum value of SAR (measured) = 0.723 mW/g

Amy Twin Phone Template/5x5x7 Zoom Scan ($\leq 3\text{GHz}$) (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$; Reference Value = 27.5 V/m; Power Drift = -0.051 dB; Peak SAR (extrapolated) = 0.942 W/kg; **SAR(1 g) = 0.715 mW/g**; **SAR(10 g) = 0.504 mW/g**; Maximum value of SAR (measured) = 0.763 mW/g



Date/Time: 9/7/2007 6:29:23 PM


Test Laboratory: Motorola

Serial: LKW0390036; Procedure Notes: Pwr Step: always up; Battery Model #: SNN5782B; Accessory Model #: n/a; DEVICE POSITION: BODYWORN BLUETOOTH BACK 15MM AWAY FROM PHANTOM; Communication System: 3G/WCDMA 1900; Frequency: 1880 MHz; Communication System Channel Number: 9400; Duty Cycle: 1:1
Medium: Regular Glycol Body; Medium parameters used: $f = 1880 \text{ MHz}$; $\sigma = 1.59 \text{ mho/m}$; $\epsilon_r = 51.4$; $\rho = 1000 \text{ kg/m}^3$; DASY4 Configuration:

- Probe: ET3DV6R - SN1397; ConvF(4.83, 4.83, 4.83); Calibrated: 4/24/2007
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn703; Calibrated: 5/30/2007
- Phantom: R1: Sect.2, Amy Twin; Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 53; Postprocessing SW: SEMCAD, V1.8 Build 172

Amy Twin Phone Template/Area Scan - Normal Body (15mm) (13x7x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$; Maximum value of SAR (measured) = 0.632 mW/g

Amy Twin Phone Template/5x5x7 Zoom Scan ($\leq 3\text{GHz}$) (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$; Reference Value = 18.7 V/m ; Power Drift = -0.163 dB ; Peak SAR (extrapolated) = 0.937 W/kg ; **SAR(1 g) = 0.609 mW/g ; SAR(10 g) = 0.381 mW/g** ; Maximum value of SAR (measured) = 0.655 mW/g



Appendix 4

Probe Calibration Certificate



Accredited by the Swiss Federal Office of Metrology and Accreditation
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Motorola Flensburg**

Certificate No: **ET3-1397_Apr07**

CALIBRATION CERTIFICATE

Object **ET3DV6R - SN:1397**

Calibration procedure(s) **QA CAL-01.v5**
Calibration procedure for dosimetric E-field probes

Calibration date: **April 24, 2007**

Condition of the calibrated item **In Tolerance**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
 The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	29-Mar-07 (METAS, No. 217-00670)	Mar-08
Power sensor E4412A	MY41495277	29-Mar-07 (METAS, No. 217-00670)	Mar-08
Power sensor E4412A	MY41498087	29-Mar-07 (METAS, No. 217-00670)	Mar-08
Reference 3 dB Attenuator	SN: S5054 (3c)	10-Aug-06 (METAS, No. 217-00592)	Aug-07
Reference 20 dB Attenuator	SN: S5086 (20b)	29-Mar-07 (METAS, No. 217-00671)	Mar-08
Reference 30 dB Attenuator	SN: S5129 (30b)	10-Aug-06 (METAS, No. 217-00593)	Aug-07
Reference Probe ES3DV2	SN: 3013	4-Jan-07 (SPEAG, No. ES3-3013_Jan07)	Jan-08
DAE4	SN: 654	21-Jun-06 (SPEAG, No. DAE4-654_Jun06)	Jun-07

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (SPEAG, in house check Nov-05)	In house check: Nov-07
Network Analyzer HP 8753E	US37390585	18-Oct-01 (SPEAG, in house check Oct-06)	In house check: Oct-07

	Name	Function	Signature
Calibrated by:	Katja Pokovic	Technical Manager	
Approved by:	Fin Bomholt	R&D Director	

Issued: April 24, 2007

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Federal Office of Metrology and Accreditation
 The Swiss Accreditation Service is one of the signatories to the EA
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not effect the E²-field uncertainty inside TSL (see below *ConvF*).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * *frequency_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * *ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe ET3DV6R

SN:1397

Manufactured:	October 24, 1999
Last calibrated:	May 3, 2006
Recalibrated:	April 24, 2007

Calibrated for DASY Systems

(Note: non-compatible with DASY2 system!)

DASY - Parameters of Probe: ET3DV6R SN:1397

Sensitivity in Free Space^A

Diode Compression^B

NormX	1.79 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$	DCP X	95 mV
NormY	1.70 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$	DCP Y	97 mV
NormZ	1.94 ± 10.1%	$\mu\text{V}/(\text{V}/\text{m})^2$	DCP Z	95 mV

Sensitivity in Tissue Simulating Liquid (Conversion Factors)

Please see Page 8.

Boundary Effect

TSL **900 MHz** **Typical SAR gradient: 5 % per mm**

Sensor Center to Phantom Surface Distance		3.7 mm	4.7 mm
SAR _{be} [%]	Without Correction Algorithm	9.5	4.9
SAR _{be} [%]	With Correction Algorithm	0.1	0.2

TSL **1810 MHz** **Typical SAR gradient: 10 % per mm**

Sensor Center to Phantom Surface Distance		3.7 mm	4.7 mm
SAR _{be} [%]	Without Correction Algorithm	13.5	9.1
SAR _{be} [%]	With Correction Algorithm	0.8	0.1

Sensor Offset

Probe Tip to Sensor Center **2.7 mm**


The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E²-field uncertainty inside TSL (see Page 8).

^B Numerical linearization parameter: uncertainty not required.




Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)


Receiving Pattern (ϕ), $\theta = 0^\circ$



Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)



Dynamic Range $f(\text{SAR}_{\text{head}})$

(Waveguide R22, $f = 1800 \text{ MHz}$)



Uncertainty of Linearity Assessment: $\pm 0.6\%$ ($k=2$)

Conversion Factor Assessment




f [MHz]	Validity [MHz] ^c	TSL	Permittivity	Conductivity	Alpha	Depth	ConvF Uncertainty
900	± 50 / ± 100	Head	41.5 ± 5%	0.97 ± 5%	0.32	2.72	6.25 ± 11.0% (k=2)
1810	± 50 / ± 100	Head	40.0 ± 5%	1.40 ± 5%	0.51	2.65	5.17 ± 11.0% (k=2)
1950	± 50 / ± 100	Head	40.0 ± 5%	1.40 ± 5%	0.57	2.49	4.95 ± 11.0% (k=2)
2450	± 50 / ± 100	Head	39.2 ± 5%	1.80 ± 5%	0.73	1.94	4.56 ± 11.8% (k=2)
900	± 50 / ± 100	Body	55.0 ± 5%	1.05 ± 5%	0.34	2.80	6.04 ± 11.0% (k=2)
1810	± 50 / ± 100	Body	53.3 ± 5%	1.52 ± 5%	0.61	2.48	4.83 ± 11.0% (k=2)
1950	± 50 / ± 100	Body	53.3 ± 5%	1.52 ± 5%	0.73	2.28	4.63 ± 11.0% (k=2)
2450	± 50 / ± 100	Body	52.7 ± 5%	1.95 ± 5%	0.65	2.17	4.18 ± 11.8% (k=2)

^c The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

Deviation from Isotropy in HSL

Error (ϕ , ϑ), $f = 900$ MHz



Uncertainty of Spherical Isotropy Assessment: $\pm 2.6\%$ ($k=2$)

Appendix 5

Measurement Uncertainty Budget

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e = f(d,k)</i>	<i>f</i>	<i>g</i>	<i>h = c x f / e</i>	<i>i = c x g / e</i>	<i>k</i>
Uncertainty Component	IEEE 1528 section	Tol. (± %)	Prob Dist	Div.	<i>c_i</i> (1 g)	<i>c_i</i> (10 g)	1 g <i>u_i</i> (±%)	10 g <i>u_i</i> (±%)	<i>v_i</i>
Measurement System									
Probe Calibration	E.2.1	5.9	N	1.00	1	1	5.9	5.9	∞
Axial Isotropy	E.2.2	4.7	R	1.73	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	E.2.2	9.6	R	1.73	0.707	0.707	3.9	3.9	∞
Boundary Effect	E.2.3	1.0	R	1.73	1	1	0.6	0.6	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	0.3	N	1.00	1	1	0.3	0.3	∞
Response Time	E.2.7	1.1	R	1.73	1	1	0.6	0.6	∞
Integration Time	E.2.8	1.1	R	1.73	1	1	0.6	0.6	∞
RF Ambient Conditions - Noise	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	E.6.1	0.0	R	1.73	1	1	0.0	0.0	∞
Probe Positioner Mech. Tolerance	E.6.2	0.4	R	1.73	1	1	0.2	0.2	∞
Probe Positioning w.r.t Phantom	E.6.3	1.4	R	1.73	1	1	0.8	0.8	∞
Max. SAR Evaluation (ext., int., avg.)	E.5	3.4	R	1.73	1	1	2.0	2.0	∞
Test sample Related									
Test Sample Positioning	E.4.2	3.2	N	1.00	1	1	3.2	3.2	29
Device Holder Uncertainty	E.4.1	4.0	N	1.00	1	1	4.0	4.0	8
SAR drift	6.6.2	5.0	R	1.73	1	1	2.9	2.9	∞
Phantom and Tissue Parameters									
Phantom Uncertainty	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity (target)	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity (measurement)	E.3.3	3.3	N	1.00	0.64	0.43	2.1	1.4	∞
Liquid Permittivity (target)	E.3.2	5.0	R	1.73	0.6	0.49	1.7	1.4	∞
Liquid Permittivity (measurement)	E.3.3	1.9	N	1.00	0.6	0.49	1.1	0.9	∞
Combined Standard Uncertainty			RSS				11.1	10.8	411
Expanded Uncertainty (95% CONFIDENCE LEVEL)			<i>k</i> =2				22.2	21.6	

Appendix 6

Photographs of the device under test

>>> Photographs are moved to Exhibit 7<<<

Appendix 7

Dipole Characterization Certificate

Certification of System Performance Check Targets

Based on WI-0396

-Historical Data-

	900MHz	
IEEE/IEC Target:	10.8	(W/kg)
Measurement Uncertainty (k=1):	9.0%	
Measurement Period:	10-May-06 to 18-April-07	
# of tests performed:	1,562	
Grand Average:	11.24	(W/kg)
% Delta (Average - IEEE1528 Target)	4.1%	
Is % Delta <= Expanded Measurement Uncertainty (k=2)?	Yes	
Accept/Reject Average as new system performance check target?	ACCEPT	
	Applies to Dipole SN's: 55, 69, 77, 78, 79, 80, 91, 92, 93, 94, 95, 96, 97, 1d034, 1d035	

-New System Performance Check Targets- per WI-0396
(based on analysis of historical data)

Frequency	SAR Target (W/kg)	Permittivity	Conductivity (S/m)
900MHz	11.24	41.5 ± 5%	0.97 ± 5%

-Approvals-

Submitted by:

Marge Kaunas

 Date:

24-Apr-07

Signed:

Marge Kaunas

Comments:

Spreadsheet detailing referenced historical measurements is available upon request.

Approved by:

Mark Douglas

 Date:

1-May-07

Signed:

Mark Douglas

Comments:

Certification of System Performance Check Targets

Based on WI-0396

-Historical Data-


	1800MHz	
IEEE1528 Target:	38.1	(W/kg)
Measurement Uncertainty (k=1):	9.0%	
Measurement Period:	10-May-06 to 18-April-07	
# of tests performed:	1314	
Grand Average:	37.5	(W/kg)
% Delta (Average - IEEE1528 Target)	-1.6%	
Is % Delta <= Expanded Measurement Uncertainty (k=2)?	Yes	
Accept/Reject <u>Average</u> as new system performance check target?	ACCEPT	
	Applies to Dipole SN's: 246tr, 250tr, 251tr, 259tr, 263tr, 271tr, 272tr, 276tr, 277tr, 279tr, 280tr, 281tr, 283tr, 284tr, 2d128, 2d129	

-New System Performance Check Targets- per WI-0396
(based on analysis of historical data)

Frequency	SAR Target (W/kg)	Permittivity	Conductivity (S/m)
1800MHz	37.5	40.0 ± 5%	1.40 ± 5%

-Approvals-

Submitted by: Marge Kaunas Date: 24-Apr-07

Signed: 

Comments: Spreadsheet detailing referenced historical measurements is available upon request.

Approved by: Mark Douglas Date: 1-May-07

Signed: 

Comments: