



**MOBILE DEVICES BUSINESS**

**PRODUCT SAFETY AND COMPLIANCE  
EMC LABORATORY**

**EMC TEST REPORT**

**Test Report Number** – 22140-3

**Report Date** – October 8, 2008

The test results contained herein relate only to the model(s) identified. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics.

As the responsible EMC Engineer, I hereby declare that the equipment tested as specified in this report conforms to the requirements indicated.

Signature: 

Name: Albert J. Patapack

Title: EMC Engineer

Date: October 8, 2008

This report must not be reproduced, except in full, without written approval from this laboratory.

**THIS REPORT MUST NOT BE USED TO CLAIM PRODUCT ENDORSEMENT BY A2LA OR ANY AGENCY OF THE U.S. GOVERNMENT.**

A2LA Certificate Number: 2518-02

**Table of Contents**

Test Report Details ..... 3  
Applicable Standards ..... 3  
Summary of Testing..... 4  
General and Special Conditions..... 4  
Equipment and Cable Configurations ..... 5  
Measuring Equipment and Calibration Information ..... 5  
Description of WLAN Transmitter ..... 5  
Measurement Procedures and Data..... 6  
    Spectrum Bandwidth..... 6  
        Measurement Procedure..... 6  
        Measurement Results ..... 6  
    Peak Output Power ..... 13  
        Measurement Procedure..... 13  
        Measurement Results ..... 13  
    Power Spectral Density..... 17  
        Measurement Procedure..... 17  
        Measurement Results ..... 17  
    Spurious RF Conducted Emissions..... 18  
        Measurement Procedure..... 18  
        Measurement Results ..... 18  
    AC Line Conducted Emissions ..... 31  
        Measurement Procedure..... 31  
        Measurement Results ..... 31

**Test Report Details**

Tests Performed By: Motorola Mobile Devices business (MDb)  
Product Safety and Compliance Group  
600 North US Hwy 45  
Libertyville, IL 60048  
PH (847) 523-6167 Fax (847) 523-4538  
Motorola MDb FRN: 0004321311  
FCC Registration Number: 316588  
Industry Canada Number: 1090-1

Tests Requested By: Motorola Inc.  
Mobile Devices Business  
600 North US Hwy 45  
Libertyville, IL 60048

Product Type : Cellular Phone

Signaling Capability: GSM 850, GSM 1900, 800 CDMA, 1900 CDMA,  
Bluetooth, WLAN

FCC ID : IHDP56JL1

Serial Numbers: 8070424A

Testing Complete Date: September 17, 2008

**Applicable Standards**

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

  X   Part 15 Subpart C – Intentional Radiators

Applicable Standards: ANSI 63.4 2003

**Summary of Testing**

Test	Test Name	Pass/Fail
1	Spectrum Bandwidth	Pass
2	Spurious RF Conducted Emissions	Pass
3	Peak Power	Pass
4	Power Spectral Density	Pass
5	Conducted Spurious Emissions	Pass
6	AC Line Conducted Emissions	Pass

Test	Test Name	Results
1	Spectrum Bandwidth	See plots
2	Spurious RF Conducted Emissions	See plots
3	Peak Power	See plots
4	Power Spectral Density	See tables
5	Conducted Spurious Emissions	See plots
6	AC Line Conducted Emissions	See Plots

**General and Special Conditions**

The Cellular Phone hereinafter referred to as the Equipment under Test or EUT was tested using a fully charged battery when applicable. Where a battery could not be used due to the need for a controlled variation of input voltage, an external power supply was utilized.

All testing was done in an indoor controlled environment with an average temperature of 22° C and relative humidity of 50%.

**Equipment and Cable Configurations**

The EUT was tested in a stand-alone configuration that is representative of typical use.

**Measuring Equipment and Calibration Information**

Manufacturer	Equipment Type	Model No.	Serial Number	Calibration Due Date
Rohde Schwarz	Receiver	ESI26	100001	6/03/09
Rohde Schwarz	Receiver	ESI26	838786/010	2/28/09
Hewlett Packard	EMC Analyzer	E7405	US39440191	5/08/09
Rohde & Schwarz	Spectrum Analyzer	1166.1660.26	200432	1/10/09
Attenuator	Weinschel	AS-6	6675	6/13/09
Attenuator	Weinschel	AS-6	6677	6/17/09
ETS	LISN	3810/2NM	2179	1/23/09
ETS	LISN	3810/2NM	00023630	1/23/09

All test equipment was within their calibration date during the time of testing. When equipment went out of calibration during testing it was replaced using a similar piece of calibrated equipment. All these equipments are listed in the equipment list.

**Description of WLAN Transmitter**

The EUT offers WLAN as a feature. The WLAN antenna is mounted inside of the EUT. The antenna installation is permanent. For a more thorough description of the functionality please refer to Exhibit 12 of this package.

As a WLAN transmitter, it is designed operate with other WLAN devices as defined by the industrial standard. In this application, the device is battery operated.

The WLAN Antenna gain is 0.5 dBi.

## **Measurement Procedures and Data**

### **Spectrum Bandwidth**

CFR 47 Part 15.247

### **Measurement Procedure**

The RF output port of the Equipment-Under-Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10dB passive attenuator. A fully charged battery was used for the supply voltage.

The Bluetooth frequency hopping function of the EUT was enabled. The spectrum analyzer used the following settings:


1. RBW  $\geq$  100 kHz
2. VBW  $\geq$  RBW
3. Sweep = auto
4. Detector function = peak
5. Trace = max hold

The trace was allowed to stabilize. The EUT was transmitting at its maximum data rate. The marker-to-peak function was used to set the marker to the peak of the emission. The marker-delta function was used to measure 6 dB down one side of the emission. The marker-delta function and marker was moved to the other side of the emission until it was even with the reference marker. The marker-delta reading at this point was the 6 dB bandwidth of the emission. The same procedure was repeated for 20 dB bandwidth.


### **Measurement Results**

See attached








**6dB Bandwidth Channel 11 @ 11 Mbps**




**20dB Bandwidth Channel 1 @ 11 Mbps**




### 802.11 g @ 9 Mbps




6dB Bandwidth Channel 1 @ 9 Mbps





6dB Bandwidth Channel 6 @ 9 Mbps



6dB Bandwidth Channel 11 @ 9 Mbps



20dB Bandwidth Channel 1 @ 9 Mbps



## **PEAK OUTPUT POWER**

CFR 47 Part 15.247


### **Measurement Procedure**

The RF output port of the Equipment-Under-Test is directly coupled to the input of the Spectrum analyzer through a specialized RF connector and a 10dB passive attenuator. A fully charged battery was used for the supply voltage.


### **Measurement Results**

See Attached

**802.11 b @ 11 Mbps**




**Max. Power Channel 1 @ 11 Mbps**




**Max. Power Channel 6 @ 11 Mbps**





**Max. Power Channel 6 @ 9 Mbps**



**Max. Power Channel 11 @ 9 Mbps**

**Power Spectral Density**

CFR 47 Part 15.247 (d)

**Measurement Procedure**

The RF output port of the Equipment-Under-Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10dB passive attenuator. A fully charged battery was used for the supply voltage.

The WLAN DSSS function of the EUT was enabled. The spectrum analyzer used the following settings:

1. Span = 300kHz
2. VBW =30kHz
3. RBW=3kHz
4. Sweep = 50ms
5. Detector function = peak
6. Trace = max hold

The trace was allowed to stabilize. The EUT was transmitting at its maximum data rate.

**Measurement Results**

<b>2412 MHz</b>	<b>2437MHz</b>	<b>2462MHz</b>
-4.876	-5.497	-5.98

**802.11 b 11Mbps**

<b>2412 MHz</b>	<b>2437MHz</b>	<b>2462MHz</b>
-12.23	-12.84	-13.28

**802.11 g 9Mbps**

## **SPURIOUS RF CONDUCTED EMISSIONS**

CFR 47 Part 15.247


### **Measurement Procedure**

The RF output port of the Equipment-Under-Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 10dB passive attenuator. A fully charged battery was used for the supply voltage.


### **Measurement Results**

See attached:


**802.11 b @ 11Mbps**




**Conducted Spurious Emissions 30-3000MHz (Low Channel)**





**Conducted Spurious Emissions 2-10GHz (Low Channel)**




**Conducted Spurious Emissions 10-20GHz (Low Channel)**




**Conducted Spurious Emissions 20-26.5GHz (Low Channel)**







Conducted Spurious Emissions 10-20GHz (Mid Channel)




Conducted Spurious Emissions 20-26.5GHz (Mid Channel)




**Conducted Spurious Emissions 30-3000MHz (High Channel)**



**Conducted Spurious Emissions 2-10GHz (High Channel)**




**Conducted Spurious Emissions 10-20GHz (High Channel)**




**Conducted Spurious Emissions 20-26.5GHz (High Channel)**


**802.11 g @ 9Mbps**




**Conducted Spurious Emissions 30-3000MHz (Low Channel)**




**Conducted Spurious Emissions 2-10GHz (Low Channel)**




**Conducted Spurious Emissions 10-20GHz (Low Channel)**





**Conducted Spurious Emissions 20-26.5GHz (Low Channel)**




**Conducted Spurious Emissions 30-3000MHz (Mid Channel)**




**Conducted Spurious Emissions 2-10GHz (Mid Channel)**







Conducted Spurious Emissions 30-3000MHz (High Channel)



Conducted Spurious Emissions 2-10GHz (High Channel)



**Conducted Spurious Emissions 10-20GHz (High Channel)**



**Conducted Spurious Emissions 20-26.5GHz (High Channel)**

## **AC LINE CONDUCTED EMISSIONS**

CFR 47 Part 15.207

### **Measurement Procedure**

Measured levels of ac power line conducted emission shall be the radio-noise voltage from the line probe or across the 50  $\Omega$  LISN port, where permitted, terminated into a 50  $\Omega$  noise meter, or where permitted or required, the radio-noise current on the power line sensed by a current probe.


All radio-noise voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord or calibrated extension cord by the use of mating plugs and receptacles on the EUT and LISN. Equipment shall be tested with power cords that are normally supplied using an LISN, the 50  $\Omega$  measuring port is terminated by a 50  $\Omega$  radio-noise meter or a 50  $\Omega$  resistive load. All other ports are terminated in 50  $\Omega$ .

Detectors – Quasi Peak and Average Detector.


### **Measurement Results**

See attached:


**802.11b @ 11Mbps**




**WLAN Channel 1 - Tx Mode - Neutral Coupling**




**WLAN Channel 1 - Tx Mode - Line Coupling**




**WLAN Channel 6 - Tx Mode - Line Coupling**



**WLAN Channel 6 - Tx Mode - Neutral Coupling**




**WLAN Channel 11 - Tx Mode - Line Coupling**




**WLAN Channel 11 - Tx Mode - Neutral Coupling**


**802.11g @ 9Mbps**




**WLAN Channel 1 - Tx Mode - Neutral Coupling**




**WLAN Channel 1 - Tx Mode - Line Coupling**




**WLAN Channel 6 - Tx Mode - Line Coupling**



**WLAN Channel 6 - Tx Mode - Neutral Coupling**



**WLAN Channel 11 - Tx Mode - Line Coupling**



**WLAN Channel 11 - Tx Mode - Neutral Coupling**

**End of Test Report**